

**CARGO STRIPPING FEATURES FOR DUAL-PURPOSE CRYOGENIC TANKS ON
SHIPS OR FLOTAING STORAGE UNITS FOR LNG AND LIQUID NITROGEN**

CROSS REFERENCE TO RELATED APPLICATIONS

5

[0001] This application claims the priority benefit of United States Provisional Patent Application No. 62/904966, filed September 24, 2019, entitled CARGO STRIPPING FEATURES FOR DUAL-PURPOSE CRYOGENIC TANKS ON SHIPS OR FLOTAING STORAGE UNITS FOR LNG AND LIQUID NITROGEN.

10

FIELD OF DISCLOSURE

[0002] The disclosure relates generally to the field of natural gas liquefaction to form liquefied natural gas (LNG). More specifically, the disclosure relates to the transport and storage of LNG and liquid nitrogen (LIN) in dual purpose tanks.

BACKGROUND

15 **Description of Related Art**

[0003] This section is intended to introduce various aspects of the art, which may be associated with the present disclosure. This discussion is intended to provide a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as an admission of prior art.

20

[0004] LNG is a rapidly growing means to supply natural gas from locations with an abundant supply of natural gas to distant locations with a strong demand for natural gas. The conventional LNG cycle includes: a) initial treatments of the natural gas resource to remove contaminants such as water, sulfur compounds and carbon dioxide; b) the separation of some heavier hydrocarbon gases, such as propane, butane, pentane, etc. by a variety of possible methods including self-refrigeration, external refrigeration, lean oil, etc.; c) refrigeration of the natural gas substantially by external refrigeration to form liquefied natural gas at or near atmospheric pressure and about -160 °C; d) transport of the LNG product in ships or tankers designed for this purpose to an import terminal associated with a market location; and e) re-pressurization and regasification of the LNG at a regasification plant to a pressurized natural gas that may distributed to natural gas consumers.

25

30

[0005] One method of natural gas liquefaction employs liquefied nitrogen (LIN) as the refrigerant. Because the nitrogen liquefaction temperature (-196 °C) is lower than the methane liquefaction temperature (-161 °C), LIN can be used advantageously to produce LNG. A challenge in using LIN for LNG production is transporting it to the liquefaction site. It has been
5 proposed to use the otherwise empty LNG carriers to transport the LIN thereto. **Figure 1** shows an example of a method of transporting LNG and LIN in the same carriers, as disclosed in U.S. Patent Application Publication No. 2017/0167787, which is incorporated by reference herein in its entirety. An LNG cargo ship **100a**, also called an LNG carrier, includes one or more dual-use tanks **101** designed to transport LNG and LIN therein at different times. LNG cargo ship **100a**
10 transports LNG from a liquefaction facility to an import terminal **104**, where the LNG may be regasified. The liquefaction facility is shown as a floating LNG production (FLNG) facility **102** where natural gas is liquefied and stored, but alternatively may be an onshore LNG production facility, or even a floating production unit (FPU) that pretreats natural gas for liquefaction on the LNG cargo ship. After the LNG is unloaded, the dual-use tanks **101** are warmed to evaporate
15 any remaining LNG. The tanks are then cooled down, and LIN is loaded into the tanks.

[0006] The LNG cargo ship **100b**, now loaded with LIN, travels to the FLNG facility **102**. The LIN is used to cool and liquefy natural gas to produce LNG. The dual-use tanks **101** are emptied of LIN and optionally warmed to evaporate any remaining LIN therein. Then LNG may be loaded into the dual-use tanks **101**.

[0007] One challenge of using a dual-use tank **101** is that the process of transitioning between LNG to LIN at the import terminal **104** requires virtually all natural gas – liquefied or gaseous – be removed from the tank before LIN can be loaded therein. Inevitably there is a small amount of LNG remaining in the tank that the inlets of the lines for normal loading/unloading pumps cannot access. A smaller line, known as a stripping line, may be used to remove even
25 more LNG, but even a stripping line does not remove all LNG from the tank. What remains must be heated and evaporated so it can be removed in a gaseous state. Because there is so much LNG remaining in the tank, generally the heating process requires heating all or a large portion of the tank to above LNG liquefaction temperature (-161 °C) to vaporize all remaining LNG. However, the more the tank is heated above LNG liquefaction temperature, the longer it will take to cool
30 the tank to below a temperature suitable for LIN transport, i.e., the LIN liquefaction temperature (-196 °C). Known methods of LNG evaporation and tank cooling may take between 20 and 30 hours. Any methods to reduce this time would increase the time the LNG carrier is actually transporting LNG or LIN, thereby increasing profitability of the LNG transportation process.

What is needed is needed is a method to reduce the time needed to transition a dual-use tank from storing LNG to storing LIN.

SUMMARY

[0008] The present disclosure provides a carrier for storing and transporting cryogenic liquids. A tank stores and transports a cryogenic liquid. A first pump fills the tank with the cryogenic liquid, and empties the tank of a first portion of the cryogenic liquid, thereby leaving a second portion of the cryogenic liquid in the tank. A tank structure focuses the second portion of the cryogenic liquid at a location on a bottom of the tank. A second pump is located at the location and empties the tank of the second portion of the cryogenic liquid so that a residual portion of the cryogenic liquid is left therein. A focused heating structure delivers heat to the location. The heat raises the temperature of the residual portion above the liquefaction temperature of the cryogenic liquid, thereby vaporizing all of the residual portion.

[0009] The present disclosure provides a method for transporting liquefied cryogenic liquids in a carrier. A cryogenic liquid is stored and transported in a dual-use cryogenic storage tank. A first pump is used to empty the cryogenic storage tank of a first portion of the cryogenic liquid, thereby leaving a second portion of the cryogenic liquid in the cryogenic storage tank. The second portion of the cryogenic liquid is focused at a location on a bottom of the cryogenic storage tank. A second pump, located at the location, empties the cryogenic storage tank of the second portion of the cryogenic liquid, whereby a residual portion of the cryogenic liquid is left therein. A focused heating structure delivers heat only to the location, and not to other parts of the cryogenic storage tank. The delivered heat raises the temperature of the residual portion above the liquefaction temperature of the cryogenic liquid, thereby vaporizing all of the residual portion.

[0010] The foregoing has broadly outlined the features of the present disclosure so that the detailed description that follows may be better understood. Additional features will also be described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] These and other features, aspects and advantages of the disclosure will become apparent from the following description, appending claims and the accompanying drawings, which are briefly described below.

[0012] Figure 1 is a simplified diagram of a method of LNG liquefaction and regasification according to known principles.

[0013] Figure 2 is a top plan view of a cargo ship capable of carrying LNG and liquid nitrogen (LIN) according to aspects of the disclosure.

[0014] Figure 3A is a cutaway perspective view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

5 [0015] Figure 3B is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

[0016] Figure 3C is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

10 [0017] Figure 3D is a cutaway perspective view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

[0018] Figure 3E is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

[0019] Figure 3F is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

15 [0020] Figure 3G is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

[0021] Figure 3H is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

[0022] Figure 3I is a cutaway view of a loading/discharge line shown in Figure 3H.

20 [0023] Figure 3J is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

[0024] Figure 3K is a cutaway side elevational view of a storage tank on the cargo ship of Figure 2 according to aspects of the disclosure.

25 [0025] Figure 4A is a top plan view of a cargo ship capable of carrying LNG and liquid nitrogen (LIN) according to other aspects of the disclosure.

[0026] Figure 4B is a cutaway side elevational view of storage tanks on the cargo ship of Figure 4A according to aspects of the disclosure.

[0027] Figure 5 is a method for transporting liquefied cryogenic liquids in a carrier according to aspects of the disclosure.

30 [0028] It should be noted that the figures are merely examples and no limitations on the

scope of the present disclosure are intended thereby. Further, the figures are generally not drawn to scale, but are drafted for purposes of convenience and clarity in illustrating various aspects of the disclosure.

DETAILED DESCRIPTION

5 **[0029]** To promote an understanding of the principles of the disclosure, reference will now be made to the features illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is thereby intended. Any alterations and further modifications, and any further applications of the principles of the disclosure as described herein are contemplated as would normally occur to one
10 skilled in the art to which the disclosure relates. For the sake clarity, some features not relevant to the present disclosure may not be shown in the drawings.

[0030] At the outset, for ease of reference, certain terms used in this application and their meanings as used in this context are set forth. To the extent a term used herein is not defined below, it should be given the broadest definition persons in the pertinent art have given that term
15 as reflected in at least one printed publication or issued patent. Further, the present techniques are not limited by the usage of the terms shown below, as all equivalents, synonyms, new developments, and terms or techniques that serve the same or a similar purpose are considered to be within the scope of the present claims.

[0031] As one of ordinary skill would appreciate, different persons may refer to the same
20 feature or component by different names. This document does not intend to distinguish between components or features that differ in name only. The figures are not necessarily to scale. Certain features and components herein may be shown exaggerated in scale or in schematic form and some details of conventional elements may not be shown in the interest of clarity and conciseness. When referring to the figures described herein, the same reference numerals may
25 be referenced in multiple figures for the sake of simplicity. In the following description and in the claims, the terms "including" and "comprising" are used in an open-ended fashion, and thus, should be interpreted to mean "including, but not limited to."

[0032] The articles "the," "a" and "an" are not necessarily limited to mean only one, but rather are inclusive and open ended so as to include, optionally, multiple such elements.

30 **[0033]** As used herein, the terms "approximately," "about," "substantially," and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It

should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numeral ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and are considered to be within the scope of the disclosure.

[0034] **Figure 2** is a top plan view of a cargo ship or carrier **200** having one or more dual-use storage tanks **202** according to disclosed aspects. The storage tanks are designed to carry both LNG and liquid nitrogen (LIN). Cryogenic loading/discharge lines **204** are used to fill and empty the storage tanks **202**. Cryogenic loading/discharge lines are connected to piping (not shown) for loading and unloading LNG and LIN. A stripping line **206**, smaller than the loading/discharge lines, is used to remove from the storage tanks the LNG or LIN that the loading/discharge lines are unable to remove. LNG extracted from storage tank **202** using stripping line **206** may be offloaded from the LNG cargo ship, or may be collected on a separate on-deck tank for use as fuel. LIN extracted from the storage tank using stripping line **206** may be stored and used as inert gas for purging the storage tank.

[0035] **Figures 3A-3K** depict cross-sections of the storage tank **202**, and details thereof, according to aspects of the disclosure. In each of the aspects disclosed in **Figures 3A-3K**, the storage tank and/or the drain systems have been designed to enable complete removal of cryogenic liquids, such as LNG or LIN. In **Figure 3A**, raised corrugated and perforated baffles **310** are disposed at either side of the centerline of the storage tank **202**. The baffles have a mild concave camber. A stripping pump **312** is situated between the baffles **310** and is connected to stripping line **206**. Loading/discharge pumps **314** are disposed outside of baffles **310** and are connected to loading/discharge lines **204**. Alternatively, stripping pump **312** and/or loading/discharge pumps **314** are disposed outside the storage tank **202**. In an evacuation operation, the cargo ship naturally tilts so that liquid in the storage tank flows toward the loading/discharge pumps and the stripping pump. The loading/discharge pumps remove most of the cryogenic liquid from storage tank **202** through loading/discharge lines **204**. Stripping pump **312** then evacuates the remnant cryogenic liquid through stripping line **206**. Baffles **310** force the remnant cryogenic liquid to be concentrated within the baffles, where the stripping pump can readily access the remnant liquid. Using the baffles, more of the remnant liquid can be evacuated by the stripping pump than with known cryogenic tank designs that do not use baffles. Because less of the cryogenic remnant liquid remains in the storage tank, the storage tank may be heated for a shorter period of time, and the vaporization/cooling portion of the tank evacuation process

may be significantly shortened.

[0036] **Figure 3B** shows tank **202** according to another aspect of the disclosure, in which a perforated top **318** is disposed on the baffles **310** to form a box-type structure around the stripping pump **312**. The box-type structure further enhances performance of the stripping pump
5 **312** by further concentrating the remnant cryogenic liquid around the stripping pump.

[0037] Instead of using baffles to concentrate the remnant cryogenic liquid to be adjacent the stripping pump, the shape of the storage tank itself may be modified to produce a similar effect. **Figure 3C** shows a storage tank **320** in which the tank bottom **322** is downwardly slanted toward the stripping pump **312**. The stripping pump is located at the lowest portion **324** of the
10 tank bottom. Remnant cryogenic liquid will naturally collect adjacent the stripping pump, thereby easing the process of removing the remnant cryogenic liquid. The downwardly slanted tank bottom **322** may prevent the loading/discharge pumps **314** from being situated as low in the storage tank as previously disclosed aspects, however. **Figure 3D** shows tank **202** according to another aspect of the disclosure, in which a pump gutter or pump well **330** is made at the bottom
15 of the storage tank. Stripping pump **312** is placed within the pump well **330** to remove as much remnant cryogenic liquid as possible. Loading/discharge pumps **314** are located as close to the bottom of the storage tank as possible to minimize the amount of remnant cryogenic liquid in the storage tank. **Figure 3E** depicts a tank **202** with a variation of **Figure 3D** in which a perforated top **332** is placed on the pump well **330** to create a box-like structure which, like top
20 **318** in **Figure 3B**, further concentrates the remnant cryogenic liquid around stripping pump **312**.

[0038] Aspects of the disclosure as described above concentrate remnant cryogenic liquid at a specific location – adjacent the stripping pump – on the floor of a cryogenic storage tank. Not only does this enable more of the remnant cryogenic liquid to be evacuated from the tank using the stripping pump, but the remnant liquid that cannot be evacuated by the stripping pump or the
25 loading/discharge pumps is still concentrated adjacent the stripping pump. This liquid, termed herein the “residual liquid”, can only be removed through vaporization, but because of its localized concentration only a small portion of the storage tank needs to be heated to vaporize it. **Figures 3F** and **3G** show tanks **202** constructed similar to **Figures 3D** and **3E**, respectively, with the addition of an insulated warm gas injection line **340** having an outlet within the pump
30 well **330** and adjacent the stripping pump **312**. Warm gas, such as nitrogen, may be pumped into the pump well **330** at a temperature higher than the liquefaction temperature of the cryogenic liquid being evacuated from the storage tank, after operation of the stripping pump **312**. Residual liquid, all of which is concentrated in the pump well **330**, is vaporized and can then be removed

from the storage tank **202**. It can be seen that only the pump well **330**, and the portion of the storage tank directly adjacent thereto, is warmed by the warm gas injected therein. Consequently, the temperature of the storage tank has not warmed appreciably, and therefore the time required to cool the storage tank for use with other cryogenic liquids, such as LIN, has been significantly
5 reduced when compared to known storage tank designs. The aspects depicted in **Figures 3F** and **3G** may also be implemented with the baffle structures disclosed in **Figures 3A** and **3B**, or with the slanted floor disclosed in **Figure 3C**.

[0039] Other methods of localized storage tank heating may be implemented. **Figures 3H** and **3I** show a tank **202** according to another aspect of the disclosure in which a warm gas
10 injection line **350** is inserted into one or more of the loading/discharge lines **204** and run to an outlet **352** adjacent stripping pump **312**. Warm gas, such as nitrogen or other gas, is pumped out of the outlet **352** only when liquids are not being evacuated from or discharged into the storage tank **202**, and preferably only after stripping pump **312** has removed as much remnant cryogenic liquid as possible.

[0040] **Figures 3J** and **3K** show tanks **202** according to another aspect of the disclosure in which, instead of inserting a heating medium through the top of the storage tank, a heating system
15 **360** is installed into or under the bottom floor **362** of the storage tank. Specifically, the heating system **360** may be localized and placed directly under the location where the residual liquid has been collected, which in **Figures 3J** and **3K** comprise the pump well **330**. Heating system **360**
20 may comprise electrical heating elements or, alternatively, a series of pipes built into the bottom floor **362** through which a heating fluid may be directed. The heating fluid may comprise a gas, such as ambient air or nitrogen gas, or may comprise a liquid, such as water or glycol. The heating system provides sufficient heat to vaporize the residual liquid. By heating only the pump well **330** and possibly the adjacent portions of the storage tank, the temperature increase in the
25 tank during the vaporization procedure is minimized. The aspects depicted in **Figures 3J** and **3K** may also be implemented with the baffle structures disclosed in **Figures 3A** and **3B**, or with the slanted floor disclosed in **Figure 3C**.

[0041] **Figure 4A** is a top plan view of a cargo ship or carrier **400** having one or more storage tanks **402** according to another aspect of the disclosure. In comparison to storage tanks **202**
30 previously described, storage tanks **402** have a significant longitudinal dimension parallel to the length of the cargo ship **400**. The storage tanks are designed to carry both LNG and liquid nitrogen (LIN). Cryogenic loading/discharge lines **404** are used to fill and empty the storage tanks **402**. Cryogenic loading/discharge lines are connected to piping (not shown) for loading

and unloading LNG and LIN. A stripping line **406**, smaller than the loading/discharge lines, is used to remove from the storage tanks the LNG or LIN that the loading/discharge lines are unable to remove. LNG extracted from storage tank **402** using stripping line **406** may be offloaded from the LNG cargo ship, or may be collected on a separate on-deck tank for use as fuel. LIN extracted from the storage tank using stripping line **406** may be stored and used as inert gas for purging the storage tank. As shown in **Figure 4B**, opposing sides **422** of the bottom **422** of each tank slant toward a central portion **424** of the tank bottom. A stripping pump **412**, connected to stripping line **406**, is located adjacent the central portion **424**. Loading/discharge pumps **414** are connected to the loading discharge lines **404**. During an unloading process, loading/discharge pumps **414** evacuate most of the cryogenic liquid, and the stripping pump **412** evacuates the remnant liquid that the loading/discharge pumps cannot evacuate. In this or other aspects, the time when the loading/discharge pumps and the stripping pump are active may overlap. Disclosed methods may be used to heat and vaporize the residual liquid, i.e., liquid that the loading/discharge pumps cannot evacuate.

[0042] **Figure 5** is a flowchart of a method **500** for transporting liquefied cryogenic liquids in a carrier according to disclosed aspects. At block **502**, a cryogenic liquid is stored and transported in a dual-use cryogenic storage tank. At block **504**, a first pump is used to empty the cryogenic storage tank of a first portion of the cryogenic liquid, thereby leaving a second portion of the cryogenic liquid in the cryogenic storage tank. At block **506**, the second portion of the cryogenic liquid is focused at a location on a bottom of the cryogenic storage tank. At block **508** a second pump, located at the location, empties the cryogenic storage tank of the second portion of the cryogenic liquid, whereby a residual portion of the cryogenic liquid is left therein. At block **510** a focused heating structure delivers heat only to the location, and not to other parts of the cryogenic storage tank. The delivered heat raises the temperature of the residual portion above the liquefaction temperature of the cryogenic liquid, so that at block **512** all of the residual portion is vaporized.

[0043] The steps depicted in **Figure 5** are provided for illustrative purposes only and a particular step may not be required to perform the disclosed methodology. Moreover, **Figure 5** may not illustrate all the steps that may be performed. The claims, and only the claims, define the disclosed system and methodology.

[0044] The aspects described herein have several advantages over known technologies. As previously discussed, directing the remnant cryogenic liquid to the stripper pump using baffles, box-like structures, pump wells, or slanted tank bottoms results in more of the remnant liquid

being evacuated using the stripper pump. Consequently, there is less residual liquid to be heated and vaporized, and the vaporization process takes less time than known technologies. Additionally, because the residual liquid is concentrated or focused in one place (i.e., between the baffles, within the pump wells, etc.), the means to heat and vaporize the residual liquid (warm gas injection lines, heating elements) may be focused at that place, instead of throughout the storage tank as is done with known storage tanks. The focused heating reduces the temperature of the entire storage tank after vaporization is complete, thereby reducing the time needed to cool the storage tank for the next load of cryogenic liquid. Combined, the disclosed methods of concentrating remnant liquid and the methods of focused heating substantially reduce the time required to prepare a storage tank emptied of, for example, LNG, to be filled with, for example, LIN. Such time reduction may be as much as 30%, or 40%, or 50%, or even 50% of the preparation time required by known technologies.

[0045] It should be understood that the numerous changes, modifications, and alternatives to the preceding disclosure can be made without departing from the scope of the disclosure. The preceding description, therefore, is not meant to limit the scope of the disclosure. Rather, the scope of the disclosure is to be determined only by the appended claims and their equivalents. It is also contemplated that structures and features in the present examples can be altered, rearranged, substituted, deleted, duplicated, combined, or added to each other.

CLAIMS

1. A carrier (200, 400) for storing and transporting cryogenic liquids, comprising:
 - a tank (202, 402) configured to store and transport a cryogenic liquid having a liquefaction temperature;
 - a first pump (314, 414) configured to fill the tank with the cryogenic liquid, and empty the tank of a first portion of the cryogenic liquid, thereby leaving a second portion of the cryogenic liquid in the tank;
 - a tank structure (310, 322, 330, 332) that focuses the second portion of the cryogenic liquid at a location on a bottom of the tank; and
 - a second pump (312, 412) located at the location and configured to empty the tank of the second portion of the cryogenic liquid, whereby a residual portion of the cryogenic liquid is left therein, characterized by further comprising a focused heating structure (350, 360) configured to deliver heat to the location, wherein the heat is configured to raise a temperature of the residual portion above the liquefaction temperature, thereby vaporizing all of the residual portion.
2. The carrier of claim 1, wherein the tank structure comprises baffles (310) surrounding the second pump (312), the baffles being attached to the bottom of the tank, optionally further comprising a baffle top (318) that encloses the second pump within the baffles, the baffle top, and the bottom of the tank.
3. The carrier of claim 1, wherein the tank structure comprises a pump well (330) at the bottom of the tank, the pump well comprising an indented portion of the bottom of the tank into which the second pump (312) is situated, optionally further comprising a pump well top (332) that covers the pump well and encloses the second pump in the pump well.
4. The carrier of claim 1, wherein the tank structure comprises a slanted tank bottom (322, 422) that slants downwardly from opposite sides of the tank.

5. The carrier of any one of claims 1-4, wherein the focused heating structure comprises a gas injection line (340, 350) having an outlet adjacent the second pump, the gas injection line configured to introduce a gas at the location at the bottom of the tank, the gas having a temperature above the liquefaction temperature, optionally
5 further comprising a first pump line (204) connected to the first pump (314) and configured to transport the cryogenic liquid in or out of the tank, wherein the gas injection line (350) is disposed within the first pump line.
6. The carrier of any one of claims 1-4, wherein the focused heating structure comprises a heating element (360) disposed underneath the location on the bottom
10 of the tank, wherein the heating element is configured to heat the residual portion of the cryogenic liquid above the liquefaction temperature.
7. The carrier of any one of claims 1-6, wherein the cryogenic liquid is one of liquefied natural gas and liquid nitrogen.
8. A method (500) of transporting liquefied cryogenic liquids in a carrier (200,
15 400), comprising:
- in a dual-use cryogenic storage tank (202, 402), storing and transporting (502) a cryogenic liquid having a liquefaction temperature;
- using (504) a first pump (314, 414) to empty the cryogenic storage tank of a first portion of the cryogenic liquid, thereby leaving a second portion of the cryogenic
20 liquid in the cryogenic storage tank;
- focusing (506) the second portion of the cryogenic liquid at a location on a bottom of the cryogenic storage tank; and
- using (508) a second pump (312, 412) located at the location, emptying the cryogenic storage tank of the second portion of the cryogenic liquid, whereby a
25 residual portion of the cryogenic liquid is left therein;
- characterized by further comprising
- delivering (510) heat only to the location using a focused heating structure;
- using (512) the focused heating structure, raising a temperature of the residual portion above the liquefaction temperature, thereby vaporizing all of the residual portion.
9. The method of claim 8, wherein the second portion of the cryogenic liquid is
30 focused using baffles (310) surrounding the second pump (312), the baffles

being attached to the bottom of the cryogenic storage tank, optionally further comprising a baffle top (318) that encloses the second pump between the baffles, the baffle top, and the bottom of the cryogenic storage tank.

5 10. The method of claim 8, wherein the second portion of the cryogenic liquid is focused using a pump well (330) at the bottom of the cryogenic storage tank, the pump well comprising an indented portion of the bottom of the cryogenic storage tank into which the second pump is situated, optionally further comprising a pump well top (332) that covers the pump well and encloses the second pump in the pump well.

10 11. The method of claim 8, wherein the second portion of the cryogenic liquid is focused using a slanted tank bottom (322, 422) that slants downwardly from opposite sides of the cryogenic storage tank.

 12. The method of any one of claims 8-11, wherein the focused heating structure comprises a gas injection line (340, 350) having an outlet adjacent the second
15 pump (312), the method further comprising:

 using the gas injection line, introducing a gas at the location at the bottom of the cryogenic storage tank, the gas having a temperature above the liquefaction temperature, optionally further comprising:

 transporting the cryogenic liquid in or out of the cryogenic storage tank using a
20 first pump line (204) connected to the first pump (314); and

 disposing the gas injection line (350) within the first pump line.

 13. The method of any one of claims 8-11, wherein the focused heating structure comprises a heating element (360) disposed underneath the location on the bottom of the tank, the method further comprising:

25 using the heating element, heating the residual portion of the cryogenic liquid above the liquefaction temperature.

 14. The method of any one of claims 8-11, wherein the cryogenic liquid is a first cryogenic liquid, and further comprising:

30 after the residual portion is vaporized, cooling the cryogenic storage tank to a temperature that is at or below a liquefaction temperature of a second cryogenic liquid,

wherein a composition of the second cryogenic liquid is different from a composition of the first cryogenic liquid; and

filling the cryogenic storage tank with the second cryogenic liquid.

15. The method of any one of claims 8-14, wherein the cryogenic liquid is one of liquefied natural gas and liquid nitrogen.

5