

**SYSTEM AND METHOD OF APPLYING A MESSAGE AND EMITTING AN
AROMATIC SCENT**

5

BACKGROUND**[0001] 1. Field of the Invention**

[0002] The present invention generally relates to massage apparatuses having scent-emitting modules.

10

[0003] 2. Description of the Related Art

[0004] Massage apparatuses currently available on the market are equipped with a massage member capable of applying diverse types of massage actions on a user's body. According to the needs, a user may select a massage program corresponding to a predetermined combination of movement and pressure actions of the massage member
15 for producing certain desirable relaxing effects. However, the mere application of massage actions may not provide sufficient relaxing results.

[0005] Therefore, there is a need for massage apparatuses that can address at least the foregoing issues.

SUMMARY

20

[0006] The present application describes a massage apparatus that can enhance massage actions using aromatherapy to provide enhanced relaxation effects. In one embodiment, the massage apparatus includes a massage system, a scent-emitting module, and a microcontroller respectively connected with the massage system and the

scent delivery module, the microcontroller being operable to activate the massage system to apply a massage action and to activate the scent-emitting module to emit an aromatic scent.

[0007] In another embodiment, the massage apparatus includes a massage system, a scent-emitting module, and a microcontroller operable to execute a massage program on the massage system for applying a sequence of massage actions on a user's body, the massage program including an instruction to activate the scent-emitting module for emitting an aromatic scent.

[0008] In yet another embodiment, a method of applying a massage through a massage apparatus is described. The method includes performing a first sequence of massage actions, while performing the first sequence of massage actions causing the massage apparatus to emit a first aromatic scent, performing a second sequence of massage actions, and while performing the second sequence of massage actions causing the massage apparatus to emit a second aromatic scent.

[0009] Advantages of the systems and methods described herein include the ability to apply massage actions and emit an aromatic scent so as to effectively relieve stress and provide enhanced relaxation effects. As a result, a user can enjoy enhanced massage experience and obtain effective relaxation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a schematic view illustrating an embodiment of a scent-emitting module suitable for use in a massage apparatus;

[0011] FIG. 2 is a schematic view illustrating the scent-emitting module installed with a scent cartridge

[0012] FIG. 3 is a schematic view illustrating the scent-emitting module with no scent cartridge installed therein;

5 [0013] FIG. 4 is a schematic view illustrating a scent cartridge alone;

[0014] FIG. 5 is a schematic view illustrating the scent cartridge in an opened state for emitting an aromatic scent;

[0015] FIG. 6 is a simplified schematic view illustrating a connection between the housing of the scent-emitting module and a flowing device;

10 [0016] FIG. 7 is a simplified block diagram illustrating one embodiment of a massage apparatus operable to emit an aromatic scent;

[0017] FIG. 8 is a simplified block diagram illustrating a variant embodiment of a massage apparatus operable to selectively emit one or more aromatic scents;

[0018] FIG. 9 is a flowchart illustrating exemplary method steps implemented in
15 a massage apparatus incorporating a scent-emitting module;

[0019] FIG. 10 is a schematic view illustrating an eye massage apparatus including the scent-emitting module;

[0020] FIG. 11 is a schematic view illustrating the connection between the scent-emitting module of the eye massage apparatus with a flowing device; and

[0021] FIG. 12 is a schematic view illustrating a massage chair including the scent-emitting module.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0022] The present application describes massage apparatuses that integrate
5 scent-emitting modules operable to diffuse an aromatic scent while a massage action is applied on a user. The combined application of massage actions and aromatherapy can produce enhanced relaxing effects.

[0023] FIGS. 1-5 are schematic views illustrating a scent-emitting module 100 for use in a massage apparatus. The scent-emitting module 100 can include a scent
10 cartridge 102 and a housing 104. The scent cartridge 102 can be a casing 102A containing a scent medium for diffusing a desirable scent. Examples of the scent medium can include aromatic oil, gel or compressed aromatic air in liquid form, and the aromatic scent can be lemon scent, mint scent, etc. In one embodiment, the scent cartridge 102 may include a heater 103 (shown with phantom lines in Fig. 2) operable to
15 heat the scent medium for producing aromatic vapor, the heater 103 being an exemplary heating resistor. In another embodiment, the scent medium may be diffused through a porous member (not shown) arranged inside the scent cartridge 102. The aromatic scent produced by the scent medium can be emitted out of the scent cartridge 102 through one or more outlet holes 105 provided at a side of the scent cartridge 102.

20 [0024] The housing 104 can exemplary have a generally elongated shape, but any shapes can be applicable in general. The housing 104 can have one or more mount structure 104A for facilitating the assembly and attachment of the scent-emitting module 100 in a massage apparatus. Moreover, the housing 104 can have a cavity 106

in which the scent cartridge 102 can be removably arranged, and can be assembled with a lid 108. The lid 108 is operable to open the housing 104 and allow access to the cavity 106 for installation or removal of the scent cartridge 102, and close the housing 104 to prevent access to the cavity 106 once the scent cartridge 102 is installed therein.

5 In one embodiment, the lid 108 can have a first end portion 108A pivotally connected with the housing 104, and a second end portion forming a resilient tab 108B that can engage with a rim of the cavity 106 to hold the lid 108 in a closed position.

[0025] The housing 104 can have one or more outlet holes 110 connecting to the cavity 106 through which scent exiting the scent cartridge 102 can be emitted out of the
10 scent-emitting module 100 by diffusion. The outlet holes 110 may be arranged at any desirable position on the housing 104 for facilitating diffusion of the scent to a proximate environment outside the scent-emitting module 100. For example, the outlet holes 110 may be arranged at a side of the cavity 106 opposite to that of the first end portion 108A of the lid 108. Outlet holes 110 may be arranged at about a bottom
15 portion of the housing which is at about the second end portion 108A of the lid 108 when in the closed position.

[0026] Referring to FIGS. 1-5, the housing 104 can be further connected with a scent release actuator 114 operable to open or close the outlet holes 110 to allow or disable scent emission out of the housing 104. The scent release actuator 114 can
20 include a frame 116 and an operating portion 118 connected with each other. In one embodiment, the scent release actuator 114 comprised of the frame 116 and the operating portion 118 may be formed integrally as a single body (as shown in Fig. 2). In other embodiments not shown, the frame 116 and the operating portion 118 may be

two distinct components operatively connected with each other. The scent release actuator 114 can be assembled with the housing 104 for sliding movement, the frame 116 being arranged inside the cavity 106, the operating portion 118 being exposed outward for manual operation. In one example of construction, the housing 104 may have a longitudinal axis Y, the scent release actuator 114 can slide relative to the housing 104 along the longitudinal axis Y, and the lid 108 can pivot relative to the housing 104 about a pivot axis extending transversally with respect to the longitudinal axis Y. Longitudinal axis Y may extend from a top portion to a bottom portion of the scent emitting module 100.

[0027] The frame 116 can surround the scent cartridge 102 placed inside the cavity 106, and can have a distal segment 116A affixed with a sealing member 120. The sealing member 120 may be exemplary made of rubber, or other adequate materials, e.g resilient material. The scent release actuator 114 can slide relative to the housing 104 between two positions: a first position where the sealing member 120 closes the holes 105 of the scent cartridge 102 to block scent emission (as better shown in FIG. 2), and a second position where the sealing member 120 is displaced away from the holes 105 to allow scent emission (as better shown in FIG. 5). When the scent release actuator 114 is in the opened position, the spring 122 is compressed, and the scent can exit the scent cartridge 102 through the outlet holes 105, diffuse inside the housing 104, and exit the scent-emitting module 100 via the outlet holes 110.

[0028] Scent release actuator 114 may be biased by a biasing member within the housing 104. For example, a spring 122 can be provided to bias the scent release actuator 114 to the first position sealing the holes 105 of the scent cartridge 102. The

spring 122 can be respectively connected with the housing 104 and the scent release actuator 114, e.g., the distal segment 116A of the frame 116. Moreover, the scent release actuator 114 may be provided with a detent (not shown) that can engage with the housing 104 to hold the scent release actuator 114 in the second position opening the outlet holes 105 of the scent cartridge 102.

[0029] The operating portion 118 may be exposed outside the housing 104 for facilitating manual operation of the scent release actuator 114. In one embodiment, the operating portion 118 may be exemplary disposed near the outlet holes 110 of the housing 104.

10 [0030] While the scent release actuator 114 has been described as being manually operated to open and seal the scent cartridge 102, alternate embodiments may have the scent release actuator 114 electrically or pneumatically controlled to open and seal the scent cartridge 102. For example, in certain embodiment, the scent cartridge 102 may use compressed aromatic gas as scent medium and a valve that holds the
15 pressured aromatic gas in the scent cartridge 102, and the scent release actuator 114 can be electrically controlled to press and open the valve to release the aromatic scent in mist form.

[0031] Referring to FIGS. 3 and 4, in an embodiment where the scent cartridge 102 is activated by heating, the housing 104 can further have an inner sidewall 126
20 provided with a plurality of electric conductors 128, and the scent cartridge 102 can have a plurality of electric terminals 130 (i.e., anode and cathode) that are connected with the heater 103 embedded in the scent cartridge 102. When the scent cartridge 102 is installed in the cavity 106 of the housing 104, the electric terminals 130 of the scent

cartridge 102 can be in electric contact with the electric conductors 128 of the housing 104 so that an electric current can be flowed through the heater 103 to heat the scent medium and produce aromatic vapor.

[0032] While the scent-emitting module 100 has been exemplarily described to receive one scent cartridge 102, it will be understood that the size of the housing 104 may be modified to receive multiple scent cartridges 102. In this case, the scent release actuator 114 can be likewise configured to close or open all the scent cartridges 102 in a concurrent manner.

[0033] The aromatic scent can be typically conveyed by diffusion to a proximate outer environment near the scent-emitting module 100. In some embodiments, a flowing device may be provided for facilitating outward diffusion of the aromatic scent from the housing 104, such as an electric fan, air pump or blower device. For example, the flowing device may be arranged outside the housing 104, and air flow may be transported along a duct from the flowing device to the interior of the housing 104.

FIG. 6 is a simplified schematic view illustrating a connection between the housing 104 of the scent-emitting module 100 and a flowing device 140. A rear surface 104B of the housing 104 opposite to the side of the lid 108 may exemplarily have an opening 142, and a duct 144 can be connected with the opening 142 of the housing 104 and the flowing device 140 disposed remotely from the housing 104. As the scent-emitting module 100 produces a scent, the flowing device 140 can create an air flow through the duct 144 into the housing 104 to promote outward diffusion of the scent through the outlet holes 110 thereof. Exemplary implementation of a massage apparatus having a flowing device is described hereinafter with reference to FIGS. 10 and 11.

[0034] In conjunction with FIGS. 1-6, FIG. 7 is a simplified block diagram illustrating one embodiment of a massage apparatus 200 incorporating the scent-emitting module 100 described previously. The massage apparatus 200 can include a power supply 202, a massage system 204, a microcontroller 206 and the scent-emitting module 100 previously described. The massage system 204 can include components such as actuating arms, electric motors, airbag pumps, solenoids, etc. operable to apply various types of massage actions. Examples of massage actions that may be applied by the massage system 204 can include, without limitation, tapping actions, kneading massage actions, gripping actions and rolling actions.

[0035] The microcontroller 206 can be connected with the massage system 204, and can control and supervise the operation of the massage system 204 to apply various massage actions. Moreover, the microcontroller 206 can be connected with the scent-emitting module 100 via a switch 208, which can be operated to activate or deactivate the scent-emitting module 100 for selective scent emission. In one embodiment, the microcontroller 206 can exemplarily be a 32-bit Reduced Instruction Set Computing (RISC) microcontroller. The microcontroller 206 can select one of a plurality of massage programs stored internally, and execute the selected massage program on the massage system 204. In one embodiment, the microcontroller 206 can exemplarily include a processing unit 210, and a memory 212 for storing massage program codes.

[0036] The memory 212 can store the codes of multiple massage programs 220 available in the massage apparatus 200. Each of the massage programs 220 can be executable by the processing unit 210 so as to actuate the massage system 204 to

perform a sequence of predetermined massage actions on a user's body. One or more of the massage programs 220 may further include an instruction executable by the processing unit 210 to activate the scent-emitting module 100, such that an aromatic scent may be emitted while the massage system 204 applies a massage action on the user's body. Accordingly, the user can inhale the aromatic scent while receiving the massage actions, which can provide enhanced relaxing results.

[0037] In conjunction with FIGS. 1-7, FIG. 8 is a schematic view illustrating a variant embodiment of a massage apparatus 200' operable to emit multiple aromatic scents. In this embodiment, the scent-emitting module 100' can be sized to receive multiple scent cartridges 102 of different scents. The scent-emitting module 100' can be similar to the scent-emitting module 100 described in FIGS. 1-6, except that the housing 104 can be sized to receive multiple scent cartridges 102. The multiple scent cartridges 102 may be respectively connected with distinctive and separate sets of the electric conductors 128 (better shown in FIG. 3), which are respectively connected with the microcontroller 206 via a plurality of switches 208. In the massage apparatus 200', the microcontroller 206 can operate one or more of the switches 208 to activate the scent-emitting module 100 for selectively emitting one or more scents.

[0038] FIG. 9 is a flowchart illustrating exemplary steps of a massage program implemented on the massage apparatus 200'. In initial step 302, the microcontroller 206 can actuate the massage system 204 to perform a first sequence of massage actions on a selected region of a user's body. In step 304, while the first sequence of massage actions are applied on the user, the microcontroller 206 can further activate the scent-emitting module 100' to produce a first scent. The first scent can exemplarily be

lemon scent. Moreover, the scent-emitting module 100' in step 304 may be activated continuously, or repeatedly switched on and off to controllably adjust the amount of scent emitted during the application of the first sequence of massage actions. In step 306, the microcontroller 206 can actuate the massage system 204 to perform a second sequence of massage actions. In step 308, while the second sequence of massage actions are applied, the microcontroller 206 can activate the scent-emitting module 100' to produce a second scent different from the first scent. The second scent can exemplarily be mint scent. Likewise, the scent-emitting module 100' in step 308 may be activated continuously, or repeatedly switched on and off to controllably adjust the amount of scent emitted during the application of the second sequence of massage actions. Accordingly, the massage apparatus 200' can apply massage actions, and selectively emit an aromatic scent associated with the massage actions in a synchronous manner. First scent and second scent may be configured to be activated at the same time to have a combined scent. First scent and second scent may be diffused in varying ratio, e.g. 50%-50%, 40%-60%, 30%-70%, 20%-80% to provide a variety of combination of scents.

[0039] Different types of massage apparatuses incorporating the scent-emitting modules as described previously may be implemented. In conjunction with FIGS. 1-7, FIGS. 10 and 11 are schematic views illustrating an eye massage apparatus 400 including the scent-emitting module 100 or 100'. The eye massage apparatus 400 can include a left-eye portion 402, a right-eye portion 404, and a bridge region 406 that connects the left-eye portion 402 with the right-eye portion 404. Each of the left-eye portion 402 and the right-eye portion 404 can include a massage mechanism operable to apply a massage action to a region around the user's eye. The scent-emitting module

100 or 100' can be arranged in the bridge region 406 above the nasal bridge of a user. In particular, the scent-emitting module 100 or 100' can be placed with the outlet holes 110 of the housing 104 turned downward toward the user's nose. The proximity of the outlet holes 110 to the user's nose can allow efficient delivery of the scent, and reduce
5 waste induced by dispersion.

[0040] Referring to FIG. 11, the eye massage apparatus 400 can be connected with an operator controller 408 via a cable assembly 410. The operator controller 408 is outside the eye massage apparatus 400, and can be used to actuate various functions of the eye massage apparatus 400, such as activating one or more massage programs on
10 a user. The operator controller 408 can have a casing 412 in which is arranged a flowing device 414. In this embodiment, the flowing device 414 can exemplary include an air pump 416 connected with an air valve 418. The cable assembly 410 can enclose a duct 420 having two opposite ends 420A and 420B respectively connected with the air valve 418 of the air pump 416 and the opening 142 on the rear surface 104B
15 of the housing 104. The air pump 416 can be operated to generate an air flow, which is conveyed through the duct 420 into the housing 104 for facilitating diffusion of the scent.

[0041] FIG. 12 is a schematic view illustrating a massage chair 500 including the scent-emitting module 100 or 100'. The massage chair 500 can include a seat 502,
20 a backrest 504 assembled with the seat 502 at a rear thereof, and left and right armrests 506 disposed at the left and right sides of the seat 502. The seat 502 can provide support for a user in a sitting position. The backrest 504 can be pivotally connected with the seat 502, and can be adjustable in inclination. The backrest 504 can be

assembled with a back massaging mechanism operable to apply diverse types of
massage actions along the back of a user. Moreover, the backrest 504 can include a
head resting region 510, and a left and a right wing portion 512 respectively protruding
forward near the head resting region 510. The scent-emitting module 100 or 100' can
5 be arranged near the head resting region 510, e.g., adjacent to one of the left and right
wing portions 512. Moreover, a flowing device (not shown) as described previously
may be coupled with the scent-emitting module 100 or 100' to facilitate outward
diffusion of the aromatic scent. The flowing device may be arranged in the massage
chair, or in an operator controller as described previously with reference to FIG. 11.
10 Scent-emitting module 100 or 100' may be configured to emit scent in close proximity
of the user. In this way, the scent would not be detected by someone beyond a certain
proximity, e.g. 0.5, 1 meter from scent-emitting module 100 or 100'. Scent-emitting
module 100 or 100' may be configured to release a pre-determined amount of scent, e.g.
by programming the time required to open and close holes 105, so as to control the
15 amount of emission of the scent. In this way, scent-emitting module 100 or 100' may be
control to emit scent with a pre-determined range from it.

[0042] Advantages of the massage apparatuses described herein include the
ability to apply massage actions and emit an aromatic scent so as to effectively relieve
stress and pain and provide enhanced healing effects. As a result, a user can enjoy
20 enhanced massage experience and obtain effective relaxation.

[0043] Realizations of the systems and methods have been described only in the
context of particular embodiments. These embodiments are meant to be illustrative
and not limiting. Many variations, modifications, additions, and improvements are

possible. Accordingly, plural instances may be provided for components described herein as a single instance. Structures and functionality presented as discrete components in the exemplary configurations may be implemented as a combined structure or component. These and other variations, modifications, additions, and
5 improvements may fall within the scope of the inventions as defined in the claims that follow.

WHAT IS CLAIMED IS:

1. A message apparatus comprising:
 - a message system;
 - a scent-emitting module; and
 - 5 a microcontroller respectively connected with the message system and the scent delivery module, the microcontroller being operable to activate the message system to apply a message action, and to activate the scent-emitting module to emit an aromatic scent.
2. The message apparatus according to claim 1, wherein the microcontroller is
10 operable to activate the message system and the scent-emitting module to apply the message action and emit the aromatic scent in a synchronous manner.
3. The message apparatus according to claim 1 or 2, wherein the scent-emitting module includes a housing having one or more outlet holes for scent emission outside the scent-emitting module, and a scent release actuator assembled with the housing, the
15 scent release actuator being operable to selectively allow or disable scent emission.
4. The message apparatus according to claim 3, wherein the scent release actuator includes an operating portion exposed outward for manual operation, the operating portion being arranged near the outlet hole.
5. The message apparatus according to claim 3 or 4, wherein the scent-emitting
20 module further includes a scent cartridge containing a scent medium, the scent cartridge being removably installed in the housing.

6. The massage apparatus according to claim 5, wherein the scent cartridge includes one or more second outlet holes through which aromatic scent is emitted outside the scent cartridge, and the scent release actuator is operable to selectively open or seal the second outlet hole of the scent cartridge.

5 7. The massage apparatus according to claim 6, wherein the scent release actuator is spring biased to seal the second outlet hole of the scent cartridge.

8. The massage apparatus according to claim 5, 6 or 7, wherein the housing further includes a plurality of electric conductors, and the scent cartridge includes a heater, the heater being electrically connected with the electric conductors when the scent cartridge
10 is placed in the housing.

9. The massage apparatus according to claim 5, 6, 7 or 8, wherein the housing is assembled with a lid operable to open and close the housing to respectively allow and prevent access to a cavity where is arranged the scent cartridge.

10. The massage apparatus according any preceding claim, wherein the
15 scent-emitting module is connected with a flowing device via a duct, the flowing device being operable to flow air through an interior of the scent-emitting module for facilitating outward diffusion of the aromatic scent.

11. The massage apparatus according to claim 10, wherein the flowing device is arranged in an operator controller of the massage apparatus.

20 12. The massage apparatus according to any preceding claim, being implemented as an eye massage apparatus.

13. The massage apparatus according to claim 12, wherein the eye massage apparatus includes a left-eye portion and a right-eye portion, and a bridge connecting the left-eye portion with the right-eye portion, the scent-emitting module being arranged in the region of the bridge.

5 14. The massage apparatus according to any of claims 1 to 11, being implemented as a massage chair.

15. The massage apparatus according to claim 14, wherein the massage chair includes a head resting region, and a left and a right wing portion respectively protruding forward near the head resting region, the scent-emitting module being
10 arranged in one of the left and right wing portions.

16. A massage apparatus comprising:
a massage system;
a scent-emitting module; and
a microcontroller operable to execute a massage program on the massage system
15 for applying a sequence of massage actions on a user's body, the massage program including an instruction to activate the scent-emitting module for emitting an aromatic scent.

17. The massage apparatus according to claim 16, being implemented as an eye massage apparatus.

20 18. The massage apparatus according to claim 16, being implemented as a massage chair.

19. A method of applying a massage through a massage apparatus, comprising:

performing a first sequence of massage actions;
while performing the first sequence of massage actions, causing the massage
apparatus to emit a first aromatic scent;
performing a second sequence of massage actions; and
5 while performing the second sequence of massage actions, causing the massage
apparatus to emit a second aromatic scent.