

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 October 2009 (29.10.2009)

(10) International Publication Number
WO 2009/131556 A1

(51) International Patent Classification:
C10M 103/06 (2006.01)

(21) International Application Number:
PCT/US2008/005256

(22) International Filing Date:
24 April 2008 (24.04.2008)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **PPT RESEARCH, INC.** [US/US]; 515 Business Park Lane, Allentown, PA 18109 (US).

(74) Agent: **LEZDEY, John**; 2401 West Bay Drive, Suite 118, Largo, FL 33770 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ,

EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: STABLE AQUEOUS SLURRY SUSPENSIONS

(57) Abstract: An aqueous slurry composition for lapping, saw wire cutting, and finishing operations which contains about 0.1 to 70% by weight of abrasive particles, 0.1 to 20% by weight of suspending particles that have a density of less than or similar to the aqueous or semi-aqueous carrier medium, and the method for creating the suspension.



WO 2009/131556 A1