

TOOL MAGAZINE FOR MACHINE TOOL

BACKGROUND OF THE INVENTIONField of the Invention

5 The present invention relates to a tool magazine to be mounted on a machine tool.

Description of the Related Art

10 A known tool magazine proposed in JP-A-6-246572 (laid open on September 6, 1994) has tool pots, a tool pot guide mechanism is constructed by attaching a pair of support rods to the upper surface of each tool pot, fixing a head member and a contact member, which is in contact with adjacent tool pots, to each pair of support rods, and rotatably supporting a guide roller (bearing) and an engagement roller, which engages with a sprocket of a feed mechanism, on each pair of support rods. The tool pot guides are fitted in an endless guide groove having vertical guide surfaces and horizontal guide surfaces with the head members seated on the horizontal guide surfaces, 20 the guide rollers in rolling contact with the vertical guide surfaces, and adjacent tool pots in contact with each other. The tool pots roll as they are moved along the guide groove.

25 Because the tool pots of the above known tool magazine are rollingly guided along the guide groove, the guide rollers must be rotatably supported, which increases the cost. The guide mechanism for guiding each tool pot is constructed by assembling a comparatively large number of parts including the head member, the guide roller, the contact member and the engagement roller and hence the same 30 is costly.

SUMMARY OF THE INVENTION

35 Accordingly, it is an object of the present invention to provide a tool magazine having a construction wherein guide rollers are not used and the number of parts is reduced whereby the cost is reduced.

 According to the present invention, a tool magazine

to be used in combination with a machine tool comprises: a magazine body provided with an endless guide groove; a plurality of vertical tool pots each for holding a tool, fixedly provided with guide members engaging the endless guide groove for sliding movement along the guide groove; and a feed mechanism for moving the tool pots along the endless guide groove; wherein the endless guide groove has horizontal guide surfaces and vertical guide surfaces, each tool pot being fixedly provided at an upper portion thereof with two guide members each having a head portion in sliding contact with the horizontal guide surfaces of the endless guide groove, a guided portion in sliding contact with the vertical guide surfaces of the endless guide groove, and a contact portion, contact portions of adjacent guide members being in contact with each other.

The two guide members may be provided with engagement portions, respectively, which are in engagement with the feed mechanism to be fed thereby.

Further, the guide member may be an integral member having the head portion, the guided portion, the contact portion and the engagement portion. At least either the surface of each guide member or that of the guide groove may be coated with a film that enables each guide member to slide along the guide groove.

The film coating at least either the surface of each guide member or that of the guide groove is preferably a nickel film containing fine particles and formed by electroless plating.

The film coating on either the surface of the guide member or that of the guide groove is preferably a polytetrafluoroethylene film.

According to the present invention, the guide groove has horizontal guide surfaces and vertical guide surfaces, and each tool pot is fixedly provided at an upper portion thereof with two guide members each having a head portion in sliding contact with the horizontal guide surfaces, a guided portion in sliding contact with the

vertical guide surfaces, and a contact portion, contact portions of adjacent guide members being in contact with each other. Therefore, it is not required to provide a rotatably guide roller on each tool pot. Furthermore, the two guide members are provided fixedly. For these reasons, the cost of the tool magazine can be reduced.

The provision of the engagement portions on the guide members makes it possible to feed the tool pots by the feed mechanism. The integral configuration of the head portion, the guided portion, and the contact portion further serves to reduce the cost. Moreover, the provision of the film on at least one of the surfaces of the guide member and the guide groove ensures smooth sliding movement.

The above and other objects, features and advantages of the present invention will become more apparent from the following description taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a plan view of a machining center;

Fig. 2 is a side view of the machining center of Fig. 1;

Fig. 3 is a plan view of a tool magazine according to a preferred embodiment of the present invention;

Fig. 4 is a bottom view of the tool magazine of Fig. 3;

Fig. 5 is a sectional view taken on line V-V in Fig. 3;

Fig. 6 is a sectional view taken on line VI-VI in Fig. 3;

Fig. 7 is a sectional view taken on line VII-VII in Fig. 3;

Fig. 8 is a partly sectional side view of a tool pot and an idler;

Fig. 9 is a view taken in the direction of the arrow IX in Fig. 8; and

Fig. 10 is a sectional view taken on line X-X in

Fig. 8.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A tool magazine in a preferred embodiment of the present invention will be described as applied to a vertical machining center 1. Referring to Figs. 1 and 2, the machining center 1 has a main frame 1a, a column 3 supported for movement in longitudinal and transverse directions in a horizontal plane on the main frame 1a, and a headstock 5 supported for vertical sliding movement, i.e., movement along the axis of a spindle 4, on the column 3. A tool changing device 6 is disposed near the spindle supported in vertical attitude in the headstock 5. A tool magazine 7 is provided beside the column 3. As shown in Fig. 4, the tool magazine 7 suspendingly supports a plurality of tool pots 61 (sixteen tool ports in this embodiment) and a plurality of idlers 62 (sixteen idlers in this embodiment). The tool magazine 7 positions each tool pot 61 holding a desired tool T (Fig. 10) at an indexed position or a standby position P, and the tool changing device 6 replaces a tool T mounted on the spindle with the desired tool T when the headstock 5 is elevated at a position corresponding to a tool change position Q. The tool changing device 6 may be of any suitable type, such as a tool changing device of a double-arm swing type provided with two swing arms each capable of swinging in an angular range of 180°. Refer to JP-A-63-52945 for further details.

Figs. 3 to 7 show the tool magazine 7 that is substantially the same in fundamental construction as a tool magazine proposed in JP-A-6-246572. As shown in Figs. 3 and 5, a magazine body 59 has a base end fastened to a mounting plate 57 fastened to a bracket 58 attached to the side surface of the column 3, and a feed mechanism 55 and a pot extracting mechanism 56 are fixedly mounted on the magazine body 59. As shown in Fig. 4, a noncircular first guide groove 60 is formed along the periphery of the lower surface of the magazine body 59. The first guide groove 60 is continuous but is interrupted only at a cutout portion

97. A slider 9, which is shiftable in the direction of arrow A and formed with a second guide groove 98, is fitted in the cutout portion 97 to form an endless guide groove 60A together with the first guide groove 60. As shown in Fig. 10, each of the first guide groove 60 and the second guide groove 98 has horizontal guide surfaces 108 and vertical guide surfaces 109. The tool pots 61 and the idlers 62 are arranged alternately in the guide groove 60A and supported for movement along the guide groove 60A. Each tool pot 61 and the adjacent idler 62 are contiguous or in contact with each other.

The tool pot 61 and the idler 62 will be described with reference to Figs. 8, 9 and 10. The tool pot 61 has a pot body 61a provided with a tapered hole 65 for receiving the tapered shank of a tool T, balls 67 and springs 68. The springs 68 urge the balls 67 into engagement with the pull stud 66 of the tool T to hold the tool T on the pot body 61a. A pair of guide members 70 are fastened to the upper surface of the pot body 61a in an upright attitude with screws 71. Each guide member 70 has a circular head portion 72, a guided portion 73, a contact portion 74 and an engagement portion 75. The surface of the guide member 70 is coated with a nickel film containing fine particles of oxides, carbides and metals, such as BN, SiC, Al_2O_3 and such, and formed by electroless plating. The nickel film containing such fine particles improves the abrasion resistance and the sliding property of the guide member 70. For example, the surface of the guide member 70 coated with a nickel film containing fine BN particles and formed by electroless plating has a hardness in the range of HV 450 to 500 and a coefficient of dynamic friction of 0.05 or below.

The head portion 72 of the guide member 70 of the tool pot 61 is seated on the horizontal guide surfaces 108 of the guide groove 60A to suspend the tool pot 61 from the magazine body 59. The guided portion 73 of the guide

member 70 is in sliding contact with the vertical guide surfaces 109 of the guide groove 60A so that the tool pot 61 is able to slide along the guide groove 60A. It is important that the idler 62 is identical in construction with the guide member 70. All the tool pots 61 and all the idlers 62 are arranged alternately on the magazine body 59 with the support members 70 of the tool pots 61 and the idlers 62 inserted in the guide groove 60A and the contact portions 74 of the adjacent guide members 70 and the idlers 62 in contact with each other as indicated in Fig. 9. Accordingly, the tool pots 61 are arranged at a pitch S (Fig. 8), which is large enough for each tool pot 61 to hold a large tool LT of a diameter, for example, 75 mm, greater than that of the pot bodies 61a of the tool pots 61. The engagement portions 75 engages with a sprocket 87 (Fig. 3) included in the feed mechanism 55.

Referring to Fig. 6, the feed mechanism 55 has a shaft 86 supported for rotation in bearings 85 on a boss 84 of the magazine body 59, the sprocket 87 fixedly mounted on the lower end of the shaft 86, a reduction gear 88 and a reversible indexing motor 89 having a drive shaft 90. The reduction gear 88 has an output shaft coupled with the shaft 86, and an input shaft coupled with the drive shaft 90 of the indexing motor 89. The indexing motor 89 drives the sprocket 87 for rotation to drive the tool pots 61 and the idlers 62 for movement along the guide groove 60A so that the tool pot 61 holding a desired tool T is positioned at the standby position P.

Referring to Fig. 7, the pot extracting mechanism 56 has a frame 92 fixed to the magazine body 59 and provided with a space 94 opening toward the spindle 4 of the machining center 1. Two guide rods 95 are held so as to extended in a horizontal direction in the space 94 and to project outward from the magazine body 59, and the slider 96 is supported on the guide rods 95 for sliding movement between the standby position P and a tool change position Q. The lower portion of the slider 96 lies in the

cutout portion 97 formed in the lower surface of the magazine body 59 and is provided with the second guide groove 98, which is the same in cross section as the first guide groove 60. When the slider 96 is positioned at the standby position P, the second guide groove 98 is continuous with the first guide groove 60 so that the tool pot 61 can be transferred from the first guide groove 60 to the second guide groove 98. A pot extracting motor 101 is installed on the upper surface of the frame 92, and a swing arm 103 is attached to the output shaft 102 of the pot extracting motor 101. A roller 104 is supported rotatably on the extremity of the swing arm 103 and is fitted in an elongate groove 105 formed in the upper surface of the slider 96. When the swing arm 103 is driven for turning by the pot extracting motor 101, the roller 104 fitted in the elongate groove 105 shifts the slider 96 between the standby position P and the tool change position Q.

The operation of the tool magazine 7 on the machining center 1 will be described below. Tools T necessary for a desired machining operation are put on the tool pots 61, respectively, before starting the machining center 1 for the machining operation. While the tool T chucked on the spindle 4 of the machining center 1 is being used for machining, the tool magazine 7 indexes or positions the tool pot 61 holding the next tool T at the standby position P by rotating the sprocket 87 by the indexing motor 89 to move the tool pots 61 and the idlers 62 along the guide groove 60A with the contact portions 74 of the adjacent tool pots 61 and the idlers 62 in contact with each other. The head portions 72 of the guide members 70 fixed to the tool pot 61, and those of the guide members 70 serving as the idler 62 slide smoothly along the horizontal guide surfaces 108 of the guide groove 60A, and the guide portions 73 of the guide members 70 slide smoothly along the vertical guide surfaces 109 of the guide groove 60A.

Upon the reception of a tool change instruction

from a controller, the tool magazine 7 actuates the pot extracting motor 101 to advance the slider 96 holding the tool pot 61 positioned at the standby position P to position the tool pot 61 at the tool change position Q. At the same time, the headstock 5 is raised relative to the column 3 to a position corresponding to the tool change position Q. Then, the tool changing device 6 removes the tool from the spindle 4 and puts the tool T held by the tool pot 61 positioned at the tool change position Q on the spindle 4. Subsequently, the slider 96 is retracted to return the tool pot 61 from the tool change position Q to the standby position P, and the tool magazine 7 carries out the tool indexing operation to position the tool pot 61 holding the next tool T at the standby position P for preparation for the next tool changing operation.

As described before, the tool pots 61 and the idlers 62 are arranged alternately on the magazine body 59 so as to slide along the guide groove 60A with the contact portions 74 of the guide members 70 fixed to the tool pots 61 and those of the guide members 70 adjacent to the guide members 70 fixed to the tool pots 61 and serving as the idlers 62 in contact with each other. Thus the tool magazine 7 of the present invention is fundamentally the same in construction as the aforesaid prior art tool magazine, but the pitch S between the successive tool pots 61 of the former is greater than that of the successive tool pots of the latter. Therefore, the tool magazine 7 of the present invention is able to handle tools T of diameters greater than the diameter of the pot bodies 61a. Since the surface of each guide member 70 is coated with a nickel film formed by electroless plating and containing fine particles to enable the guide members 70 to slide smoothly along the guide groove 60A, the guide member 70 need not be provided with any guide rollers that roll along the guide groove 60A, which contributes to cost reduction. Since the guide member 70 is an integral member having the head portion 72, the guided portion 73, the contact portion

74 and the engagement portion 75, the tool magazine 7 of the present invention needs less parts than the aforesaid prior art tool magazine, which also contributes to cost reduction.

5 The film for coating the surface of each guide member 70 need not be limited to the nickel film containing fine particles and formed by electroless plating; the surface of each guide member 70 may be coated with any suitable, abrasion-resistant film, provided that the film
10 has a coefficient of dynamic friction of 0.15 or below. For example, the surface of each guide member 70 may be coated with a polytetrafluoroethylene film. The tool magazine 7 may be mounted on a stationary column instead of mounting the same on the movable column 3. The tool
15 magazine 1 may be used in combination with a machine tool other than the vertical machining center 1, such as a horizontal machining center or a boring machine, and may be installed separately from a machine tool.

 Although the invention has been described in its
20 preferred form with a certain degree of particularity, obviously many changes and variations are possible therein. It is therefore to be understood that the present invention may be practiced otherwise than as specifically described herein without departing from the scope and spirit thereof.

25

Claims:

1. A tool magazine to be used in combination with a machine tool, comprising:

5 a magazine body (59) provided with an endless guide groove (60A);

a plurality of vertical tool pots (61) each for holding a tool (T), fixedly provided with guide members (70) engaging the endless guide groove (60A) for sliding movement along the guide groove (60A); and

10 a feed mechanism (55) for moving the tool pots (61) along the endless guide groove (60A);

wherein the endless guide groove (60A) has horizontal guide surfaces (108) and vertical guide surfaces (109), and each tool pot (61) is fixedly provided at an upper portion thereof with two guide members (70) each having a head portion (72) in sliding contact with the horizontal guide surfaces of the endless guide groove, a guided portion (73) in sliding contact with the vertical guide surfaces of the endless guide groove, and a contact portion (74), contact portions (74) of adjacent guide members (70) being in contact with each other.

2. A tool magazine according to claim 1, wherein said guide members (70) are provided with engagement portions (75), respectively, which are in engagement with said feed mechanism (55) to be fed by the feed mechanism.

3. A tool magazine according to claim 2, wherein each of the guide members (70) is an integral member having the head portion (72), the guided portion (73), the contact portion (74) and the engagement portion (75).

4. A tool magazine according to claim 1, wherein at least one of the surface of each guide member (70) and that of the guide groove (60A) is coated with a film for enabling each guide member (70) to slide along the guide groove (60A).



5. A tool magazine according to claim 4, wherein the film on at least one of the surface of each guide member (70) and that of the guide groove (60A) comprises a nickel film containing fine particles and formed by electroless plating.

6. A tool magazine according to claim 4, wherein the film on at least one of the surface of the guide member (70) and that of the guide groove (60A) comprises a polytetrafluoroethylene film.

