

Description

Background of the Invention

The present invention relates to radio paging devices having a display and more particularly to a radio paging device in which successively received message signals are compared against each other for verification before the message is displayed.

Radio paging devices typically include a receiver for receiving repeatedly transmitted signals and a memory for successively storing the received message and address signals. In such radio paging devices the successively received message signals are compared character by character to detect a match between them regardless of the presence of errors. (Such a device is disclosed in document US-A-4 477 807). If a mismatch occurs between them, the successively received message signals are identified as different message signals and stored into respective storage locations of the memory, so that message signals are stored in the memory in chronological order. If the transmitted signals are severely contaminated with random noise, the signals of the same information are likely to be identified as different messages and the memory is overflowed with such error-containing messages. Since the memory is filled with error-containing messages, the reading of a true message from the memory required a complicated program which can be implemented only with the use of a costly microprocessor and a memory having a large capacity.

Summary of the Invention

It is therefore an object of the invention to provide a radio paging device which reduces the likelihood of overflowing a message memory with error-containing messages and reduces the number of errors contained in the message to be displayed.

The radio paging device has a receiver for receiving a paging signal comprising an address signal and a message signal, a decoder for decoding the address signal and a display for displaying the message signal.

According to a broader aspect of the invention, the device comprises means for detecting an error in each of the characters and identifying those characters having no error as error-free characters and identifying those characters in error as error-containing characters. A memory is provided for storing a received message signal into a first storage area and respectively storing into second storage areas a plurality of different message signals received in succession prior to the reception of the message signal in the first storage area. Each of the message signals stored in either the first storage area and second storage areas contains the error-free and error-containing characters, the characters stored in the first storage area respectively corresponding in position to those stored in each of the second storage areas. A control circuit is provided which com-

pares each of the error-free characters in the first storage area with each of positionally corresponding error-free characters in each second storage area to detect a match or a mismatch therebetween. If the mismatch is detected, all the characters of each of the second storage areas are shifted to the next storage area and all the characters of the first storage area written into one of the second storage areas. If there is a match between all the error-free characters of the first storage area and a given one of the second storage areas, characters of the given second storage area are rewritten with positionally corresponding error-free characters of the first storage area. The rewritten message signal is utilized by the user.

The occurrence of message overflow is rendered infrequent due to the exclusion of error-containing message signals from the second storage areas and the rewriting of the message signal stored in a second storage area with the error-free characters reduces the errors.

According to a specific aspect of the invention, the control circuit provides a count indicating the number of the detected matches, shifts all the characters of each of the second storage areas to the next and writes all the characters of the first storage area into the second storage area in which the most recent one of the different messages was stored if the count is smaller than the prescribed value and rewrites characters of the given second storage area with positionally corresponding error-free characters of the first storage area if the count is greater than the prescribed value. If the received paging signal is severely afflicted with errors, the control circuit will interpret successively received signals as different messages even if all of their error-free characters match, and proceed to store the subsequently received message signal into the second storage areas.

Brief Description of the Drawings

The present invention will be described in further detail with reference to the accompanying drawings, in which:

Fig. 1 is a schematic block diagram of a radio paging device embodying the present invention;

Figs. 2A-2C are illustrations of data structures employed in the invention;

Fig. 3 is a flowchart describing the programmed error check routine;

Fig. 4 is a flowchart describing a message display routine;

Fig. 5 is a data structure of an error checked message; and

Fig. 6 is an illustration of temporary and main storage areas.

Detailed Description

In Fig. 1, a radio paging device embodying the invention is schematically illustrated. An antenna 1 intercepts radio paging signals and feeds a receiver 2 where the signals are amplified and fed to a waveshaper 3 by which the signals are

shaped into a waveform having sharply defined edges and levels suitable for digital processing. Each paging signal comprises a preamble P indicating the beginning of a paging signal, frame sync F, calling address signal N and message signals I as shown in Fig. 2A. The calling address signal comprises 31 bits of Bose-Chaudhuri Hocquenghem (32, 21) code format starting with a binary-0 address header, a 20-bit subscriber's address code and a 10-bit error check code. The calling address signal is appended by a parity bit (Fig. 2B). As shown in Fig. 2C, each message signal is also organized in the BCH (32, 21) code format including a binary-1 message header, a 20-bit message code, a 10-bit error check code appended by a parity bit. The message code comprises two seven-bit characters. Because of the binary system limitations the remaining six bits either are all binary zero's if no other information follows or represent the higher six bits of the next character if the amount of information exceeds two characters.

A decoder 4, which is clocked by a crystal-controlled oscillator 5, processes the received paging signals from the waveshaper 3 by detecting and correcting bit errors using the parity and error check codes of the address signal N and comparing the error-corrected address code of each paging signal with the address code of the user which is stored in a programmable read-only memory 6 on a bit-by-bit basis. If they match, the decoder 4 activates a loudspeaker 8 through an amplifier 7 to alert the user of the reception of a call and sends message codes to a microprocessor 9. The alert sound can be stopped by a reset switch 13.

Microprocessor 9 operates in accordance with programmed instructions stored in an instruction memory 14. The instructions include an error check routine by which the contents of repeatedly transmitted messages are checked for the presence or absence of error and the error-checked message signals are stored into a temporary storage area SM (Fig. 6) defined in the RAM 10. The instructions include a display routine by which the message is displayed on the liquid crystal display 12.

More specifically, the instructions of the error check routine are shown in Fig. 3. The error check routine starts with the turn-on of power and calls for the detection of a frame sync (block 20). Exit from decision block 20 is decision block 21 which tests for the presence of a match between the received calling address code and the subscriber's address code stored in PROM 6. Decision blocks 20 and 21 are executed by the decoder 4. The instructions of the microprocessor 9 actually start with decision block 22 which tests for the presence of an end-of-message code in the signal received from the decoder 4. If there is one, the program returns to block 20. If there is none, exit from decision block 22 is to operations block 23 which directs the reading of the received 32-bit message code. The program proceeds to decision block 24 which tests for the presence of an error. If

the answer is affirmative, control proceeds to decision block 25 to check to see if each of the characters contained in the message code comprises 7 bits. If the answer is affirmative, exit from decision block 25 is to operations block 26 which directs the writing of a binary "1" into the error indicating bit position e_i of the error-containing character to "1". Control then proceeds to operations block 27 which directs the writing of the error-checked 8-bit character into temporary storage area SM of the RAM 10. If the answer is negative in decision block 24, exit then is to decision block 28 which tests for the presence of 7-bit characters. If the answer is affirmative, exit from decision block 28 is to operations block 29 which directs the writing of binary "0" into the error bit of the error-free character. The error-checked error-free characters are stored into the temporary storage area SM. As a result, the message stored in temporary storage area SM forms a series of characters identified by a subscript "j" as shown in Fig. 5. If 7-bit character is not detected in blocks 25 and 28, the program jumps to decision block 22. Operations block 27 is followed by the message transfer routine 60.

As shown in Fig. 4, the message transfer routine, starts with a block 30 which initializes a variable "i" to 1. Variable "i" indicates the location of each of main storage areas M_1 to M_n (Fig. 6) which are defined in the random access memory 10. Received messages are stored in main storage areas M_1 through M_n in chronological order with the subscript "1" indicating the most recent one of the stored messages and the subscript "n" indicating the oldest of the messages. Exit from initialization block 30 is to second initialization block 31 which sets a variable "S" to 0 and a variable "j" to 1. Variable "S" indicates the count of matches between each message character stored in an temporary storage area SM (which is also defined in RAM 10) and a corresponding character stored in main storage area M_i . Variable "j" indicates the position of each character in the temporary storage area SM and main storage area M_i . Exit is then to block 32 which reads a character C_j from position "j" of temporary storage area SM and a corresponding character C_j from position "j" of main storage area M_i . Decision block 33 next tests for the presence of an end-of-message code * in either of the characters C_j just read out of the memories SM and M_i . If there is no end-of-message code, control proceeds to decision block 34 to check for the presence of binary 0 in the error bit position in both of the characters C_j . If binary 0 is detected, there is no bit error in these characters $SM(C_j)$ and $M_i(C_j)$ and control exits to decision block 35 which tests for the detection of match between the characters $SM(C_j)$ and $M_i(C_j)$. The detection of a match between these characters causes an exit from decision block 35 to operations block 36 which increments the variable "S" by one. Exit then is to operations block 37 which increments the variable "j" by one and causes control to return to operations block 32. If a binary 1 is

detected in block 34, there is an error in one or both of the two characters to be compared in decision block 35 and control jumps to operations block 37 to increment the variable "j" skipping blocks 35 and 36.

If there is a mismatch between the characters compared in decision block 35, exit from block 35 is to decision block 38 which tests to see if the variable "i" reaches an integer "n" corresponding to main storage area M_n . If variable "i" is smaller than "n", exit from block 38 is to operations block 39 which increments the variable "i" by one. The program now returns to operations block 31.

As a result, if a mismatch is detected in block 35, blocks 31, 32, 33, 34, 35, 38 and 39 are repeatedly executed until variable "i" reaches "n". Control subsequently exits from decision block 38 to operations block 40 which transfers characters from main storage area M_{i-1} to the next main storage area M_i . Exit from block 40 is to block 41 which decrements the variable "i" by one. Variable "i" is successively decremented by executing a loop including block 42 which tests for the presence of $i=1$ and causes an exit from decision block 42 to operations block 40. When the variable "i" is decremented to "1", exit from decision block 42 is to operations block 43 which directs the transfer of characters from temporary storage area SM to main storage area M_1 .

The message transfer operation just described continues as long as there is a mismatch between the character $SM(C_j)$ and character $M_i(C_j)$ of any set. The message transfer operation also occurs if there is a substantial amount of errors in the message signal in either temporary or main storage areas even though there is a match between the characters of the remaining sets. This is achieved by decision block 44 which, after an end-of-message code is detected in block 33, tests to see if the count "S" is greater than a prescribed value B which is typically 50% to 70% of the total number of characters contained in a message. If the count "S" is smaller than the prescribed value, exit from decision block 44 is to block 38.

Main storage areas M_1 to M_n may be filled with error-free message signals of different contents as well as with error-containing message signals of same contents and the oldest message may overflow the storage area M_n . However, the message overflow occurs infrequently due to the fact that the errors detected by block 34 are removed from the comparison step of block 35 which triggers the message transfer operation.

The count "S" becomes greater than the prescribed value B if the received signal is not severely contaminated with errors. In this case, blocks 32 through 37 are repeatedly executed until the count "S" reaches the prescribed value B and control has an exit from block 44 to initialization block 45 which resets a flag "K" to zero and initializes variable "j" to "1". Flag K indicates that one of the messages stored in the temporary storage area SM and the main storage area M_1 is longer than the other. Exit is then to

operations block 46 which directs the reading of characters $SM(C_j)$ and $M_i(C_j)$ and causes an exit from block 46 to decision block 47 which tests for the absence of an end-of-message code in the characters stored in temporary memory SM. If there is no end-of-message code in the temporary storage area, exit from decision block 47 is to decision block 48 which checks to see if the count "K" is zero. If the answer in block 48 is affirmative, exit therefrom is to decision block 49 which tests for the absence of an end-of-message code in the main storage area M_i . The absence of an end-of-message code in main storage area M_i causes an exit from decision block 49 to decision block 50 which tests for the presence of an error-free character in the temporary storage area. If there is one, exit is to operations block 51 which directs the transfer of the error-free character to the main storage area M_i . Exit from block 51 is to operations block 52 which increments the variable "j" by one. If a character in error is detected by block 50, exit therefrom is to operations block 52, so that the main storage area is rewritten by an error-free characters of the same message. Control now returns to operations block 46 to repeat the executions of blocks 46 to 52. As a result, if the previous message stored in a given main storage area M_i has a greater number of errors than those in the message in temporary storage area SM, such error-containing characters in the main storage area M_i are likely to be rewritten by error-free characters in the corresponding positions of temporary storage area SM due to less likelihood of coincidence of errors in the same character positions "j" of temporary and main storage areas.

If the length of the previous message in main storage area M_i is shorter than the length of characters in temporary storage area SM, the end-of-message code of the previous message is detected in block 49 before the end-of-message code of the next message is detected by block 47 and exit from block 49 is to operations block 53 which sets flag "K". Exit from decision block 48 in the following execution cycles is to operations block 51 until the presence of an end-of-message code is detected in the next message by the execution of block 47. The detection of end-of-message code in block 47 causes an exit therefrom to decision block 54 which tests to see if flag "K" has been set. Exit from block 54 is to operations block 55 to rewrite the storage position "j" of main storage area M_i with the end-of-message code now stored in temporary storage area SM, causing control to return to the main routine. Thus, the characters in temporary storage area SM having no corresponding characters in the main storage area M_i are written into the corresponding positions of main storage area M_i without error verification.

Exit from operations block is to operations block 56 which directs the reading of all characters from the main storage area M_i into the liquid crystal display 12.

If the previous message is longer than the next

message, the detection of the end-of-message code by block 47 takes place prior to the setting of flag "K" and exit from block 54 is to the main routine. Thus, the characters in main storage area M₁ having no corresponding characters in the temporary storage area SM remain unchanged.

Due to the rewriting procedure described above, the validity of the message to be displayed is enhanced.

The foregoing description shows only a preferred embodiment of the present invention. Various modifications are apparent to those skilled in the art without departing from the scope of the present invention which is only limited by the appended claims. Therefore, the embodiment shown and described is only illustrative, not restrictive.

Claims

1. A radio paging device having a receiver (2) for receiving a paging signal comprising an address signal and a message signal and means (4, 6) for decoding the address signal in the received paging signal, wherein the message signal comprises a series of characters, comprising:

means (9) for detecting an error in each character of the received message signal and identifying those characters having no error as error-free characters and identifying those characters in error as error-containing characters;

memory means (10) having a first storage area for storing therein a received message signal and second storage areas for respectively storing therein a plurality of different message signals received in succession prior to the reception of the message signal in said first storage area, each of the message signals stored in either of said first storage area and second storage areas containing said error-free and error-containing characters, the characters stored in said first storage area respectively corresponding in position to those stored in each of said second storage areas; and

control means (9) for (a) comparing each of the error-free characters in said first storage area with each of positionally corresponding error-free characters in each of the second storage areas to detect a match or a mismatch therebetween, (b) if said mismatch is detected, shifting all the characters of each of the second storage areas to the next storage area and writing all the characters of said first storage area into one of said second storage areas, and (c) if said match is detected between all the error-free characters of said first storage area and a given one of said second storage areas, rewriting characters of said given second storage area with positionally corresponding error-free characters of said first storage area.

2. A radio paging device as claimed in claim 1, wherein said control means provides a count indicating the number of the detected matches, shifts all the characters of each of the second storage areas to the next and writes all the

characters of said first storage area into the second storage area in which the most recent one of said different messages was stored if the count is smaller than said prescribed value and rewrites characters of said given second storage area with positionally corresponding error-free characters of said first storage area if the count is greater than the prescribed value.

3. A radio paging device as claimed in claim 1 or 2, wherein said message signal contains an end-of-message code, and wherein said control means rewrites said characters by:

detecting each of the error-free characters in said first storage area until said end-of-message code is encountered;

rewriting each of the characters in said given second storage area with the detected error-free character; and

writing each of the characters and the end-of-message code remaining in said first storage area into said given second storage area.

Patentansprüche

1. Funk-Rufvorrichtung mit einem Empfänger (2) zum Empfangen eines Rufsignals, welches ein Adressensignal und ein Mitteilungssignal aufweist, und Einrichtungen (4, 6) zum Decodieren des Adressensignals in dem empfangenen Rufsignal, wobei das Mitteilungssignal eine Folge von Zeichen aufweist, mit:

einer Einrichtung (9) zum Ermitteln eines Fehlers in jedem Zeichen des empfangenen Mitteilungssignals und zum Identifizieren derjenigen Zeichen, die keinen Fehler aufweisen, als fehlerfreie Zeichen, und zum Identifizieren der fehlerhaften Zeichen als Fehler enthaltende Zeichen;

einer Speichereinrichtung (10) mit einem ersten Speicherbereich zum Speichern eines empfangenen Mitteilungssignals und einem zweiten Speicherbereich zum jeweiligen Speichern mehrerer verschiedener Mitteilungssignale, die nacheinander vor dem Empfang des Mitteilungssignals in dem ersten Speicherbereich empfangen wurden, wobei jedes der in dem ersten Speicherbereich oder in dem zweiten Speicherbereich gespeicherten Mitteilungssignale die fehlerfreien und die Fehler enthaltenden Zeichen enthält, wobei die in dem ersten Speicherbereich gespeicherten Zeichen bezüglich ihrer Position jeweils den in jedem der zweiten Speicherbereiche gespeicherten Zeichen entsprechen; und

einer Steuereinrichtung (9) zum (a) Vergleichen jedes der fehlerfreien Zeichen in dem ersten Speicherbereich mit jedem der bezüglich der position entsprechenden fehlerfreien Zeichen in jedem der zweiten Speicherbereiche, um eine Übereinstimmung oder das Fehlen einer Übereinstimmung dazwischen festzustellen, (b) wenn fehlende Übereinstimmung festgestellt wird, Schieben aller Zeichen jeder der zweiten Speicherbereiche in den nächsten Speicherbereich und Schreiben aller Zeichen des ersten Speicherbereichs in einen der zweiten Speicherbereiche, und (c) wenn die Übereinstimmung zwischen allen fehlerfreien

message, the detection of the end-of-message code by block 47 takes place prior to the setting of flag "K" and exit from block 54 is to the main routine. Thus, the characters in main storage area M₁ having no corresponding characters in the temporary storage area SM remain unchanged.

Due to the rewriting procedure described above, the validity of the message to be displayed is enhanced.

The foregoing description shows only a preferred embodiment of the present invention. Various modifications are apparent to those skilled in the art without departing from the scope of the present invention which is only limited by the appended claims. Therefore, the embodiment shown and described is only illustrative, not restrictive.

Claims

1. A radio paging device having a receiver (2) for receiving a paging signal comprising an address signal and a message signal and means (4, 6) for decoding the address signal in the received paging signal, wherein the message signal comprises a series of characters, comprising:

means (9) for detecting an error in each character of the received message signal and identifying those characters having no error as error-free characters and identifying those characters in error as error-containing characters;

memory means (10) having a first storage area for storing therein a received message signal and second storage areas for respectively storing therein a plurality of different message signals received in succession prior to the reception of the message signal in said first storage area, each of the message signals stored in either of said first storage area and second storage areas containing said error-free and error-containing characters, the characters stored in said first storage area respectively corresponding in position to those stored in each of said second storage areas; and

control means (9) for (a) comparing each of the error-free characters in said first storage area with each of positionally corresponding error-free characters in each of the second storage areas to detect a match or a mismatch therebetween, (b) if said mismatch is detected, shifting all the characters of each of the second storage areas to the next storage area and writing all the characters of said first storage area into one of said second storage areas, and (c) if said match is detected between all the error-free characters of said first storage area and a given one of said second storage areas, rewriting characters of said given second storage area with positionally corresponding error-free characters of said first storage area.

2. A radio paging device as claimed in claim 1, wherein said control means provides a count indicating the number of the detected matches, shifts all the characters of each of the second storage areas to the next and writes all the

characters of said first storage area into the second storage area in which the most recent one of said different messages was stored if the count is smaller than said prescribed value and rewrites characters of said given second storage area with positionally corresponding error-free characters of said first storage area if the count is greater than the prescribed value.

3. A radio paging device as claimed in claim 1 or 2, wherein said message signal contains an end-of-message code, and wherein said control means rewrites said characters by:

detecting each of the error-free characters in said first storage area until said end-of-message code is encountered;

rewriting each of the characters in said given second storage area with the detected error-free character; and

writing each of the characters and the end-of-message code remaining in said first storage area into said given second storage area.

Patentansprüche

1. Funk-Rufvorrichtung mit einem Empfänger (2) zum Empfangen eines Rufsignals, welches ein Adressensignal und ein Mitteilungssignal aufweist, und Einrichtungen (4, 6) zum Decodieren des Adressensignals in dem empfangenen Rufsignal, wobei das Mitteilungssignal eine Folge von Zeichen aufweist, mit:

einer Einrichtung (9) zum Ermitteln eines Fehlers in jedem Zeichen des empfangenen Mitteilungssignals und zum Identifizieren derjenigen Zeichen, die keinen Fehler aufweisen, als fehlerfreie Zeichen, und zum Identifizieren der fehlerhaften Zeichen als Fehler enthaltende Zeichen;

einer Speichereinrichtung (10) mit einem ersten Speicherbereich zum Speichern eines empfangenen Mitteilungssignals und einem zweiten Speicherbereich zum jeweiligen Speichern mehrerer verschiedener Mitteilungssignale, die nacheinander vor dem Empfang des Mitteilungssignals in dem ersten Speicherbereich empfangen wurden, wobei jedes der in dem ersten Speicherbereich oder in dem zweiten Speicherbereich gespeicherten Mitteilungssignale die fehlerfreien und die Fehler enthaltenden Zeichen enthält, wobei die in dem ersten Speicherbereich gespeicherten Zeichen bezüglich ihrer Position jeweils den in jedem der zweiten Speicherbereiche gespeicherten Zeichen entsprechen; und

einer Steuereinrichtung (9) zum (a) Vergleichen jedes der fehlerfreien Zeichen in dem ersten Speicherbereich mit jedem der bezüglich der position entsprechenden fehlerfreien Zeichen in jedem der zweiten Speicherbereiche, um eine Übereinstimmung oder das Fehlen einer Übereinstimmung dazwischen festzustellen, (b) wenn fehlende Übereinstimmung festgestellt wird, Schieben aller Zeichen jeder der zweiten Speicherbereiche in den nächsten Speicherbereich und Schreiben aller Zeichen des ersten Speicherbereichs in einen der zweiten Speicherbereiche, und (c) wenn die Übereinstimmung zwischen allen fehlerfreien



Zeichen des ersten Speicherbereichs und eines gegebenen Speicherbereichs der zweiten Speicherbereiche festgestellt wird, Überschreiben von Zeichen des gegebenen zweiten Speicherbereichs mit bezüglich der Position entsprechenden fehlerfreien Zeichen des ersten Speicherbereichs.

2. Funk-Rufvorrichtung nach Anspruch 1, wobei die Steuereinrichtung eine Zählrate liefert, die die Zahl der ermittelten Übereinstimmungen anzeigt, alle Zeichen jeder der zweiten Speicherbereiche in den nächsten Speicherbereich schreibt und alle Zeichen des ersten Speicherbereichs in denjenigen zweiten Speicherbereich schreibt, in dem die jüngste der verschiedenen Mitteilungen gespeichert wurde, wenn die Zählrate kleiner ist als der vorgeschriebene Wert, und Zeichen des gegebenen zweiten Speicherbereichs mit bezüglich der Position entsprechenden fehlerfreien Zeichen des ersten Speicherbereichs überschreibt, wenn die Zählrate größer ist als der vorgeschriebene Wert.

3. Funk-Rufvorrichtung nach Anspruch 1 oder 2, wobei das Mitteilungssignal einen Code enthält, das das Ende der Mitteilung anzeigt, und wobei die Steuereinrichtung die Zeichen überschreibt durch:

Ermitteln jedes der fehlerfreien Zeichen in dem ersten Speicherbereich, bis der Code auftritt, der das Ende der Mitteilung anzeigt;

Überschreiben jedes der Zeichen in dem gegebenen zweiten Speicherbereich mit den ermittelten fehlerfreien Zeichen; und

Schreiben jedes der Zeichen und des das Ende der Mitteilung anzeigenden Codes, die in dem ersten Speicherbereich verbleiben, in den gegebenen zweiten Speicherbereich.

Revendications

1. Dispositif d'appel radio comportant un récepteur (2) pour recevoir un signal d'appel radio comprenant un signal d'adresse et un signal de message, et un moyen (4, 6) pour décoder le signal d'adresse dans le signal d'appel radio reçu, où le signal de message comprend une série de caractères, comportant:

- un moyen (9) pour détecter une erreur dans chaque caractère du signal de message reçu et identifier les caractères n'ayant aucune erreur sous forme de caractères exempts d'erreurs et identifier les caractères erronés sous forme de caractères contenant des erreurs;

- un moyen de mémoire (10) ayant une première zone de stockage pour y stocker un signal de message reçu et des secondes zones de stockage pour respectivement stocker une multiplicité de différents signaux de messages reçus à la suite les uns des autres avant la réception du signal de message dans la première zone de stockage, chacun des signaux de message

stockés dans l'une ou l'autre de la première zone de stockage et des secondes zones de stockage comportant des caractères exempts d'erreurs et contenant des erreurs, les caractères stockés dans la première zone de stockage correspondant respectivement, en matière de position, à ceux stockés dans chacune des secondes zones de stockage; et

- un moyen de commande (9) pour (a) comparer chacun des caractères exempts d'erreurs de la première zone de stockage à chacun des caractères exempts d'erreurs, à la position correspondante, de chacune des secondes zones de stockage afin de détecter une correspondance ou un manque de correspondance entre eux, (b) s'il y a détection d'un manque de correspondance, décaler tous les caractères de chacune des secondes zones de stockage vers la zone de stockage suivante et écrire tous les caractères de la première zone de stockage dans l'une des secondes zones de stockage, et (c) s'il y a détection d'une correspondance entre tous les caractères exempts d'erreurs de la première zone de stockage et une zone donnée parmi les secondes zones de stockage, réécrire les caractères de la seconde zone de stockage donnée avec des caractères exempts d'erreurs, correspondant en matière de position, de la première zone de stockage.

2. Dispositif d'appel radio selon la revendication 1, dans lequel le moyen de commande fournit un comptage indiquant le nombre des correspondances détectées, décale tous les caractères de chacune des secondes zones de stockage vers la suivante et écrit tous les caractères de la première zone de stockage dans la seconde zone de stockage dans laquelle le message le plus récent parmi les messages différents a été stocké si le comptage est inférieur à la valeur prescrite et réécrit les caractères de la seconde zone de stockage donnée avec des caractères exempts d'erreurs, correspondant en matière de position, de la première zone de stockage si le comptage est supérieur à la valeur prescrite.

3. Dispositif d'appel radio selon la revendication 1 ou 2, dans lequel le signal de message contient un code de fin de message, et où le moyen de commande réécrit les caractères en:

- détectant chacun des caractères exempts d'erreurs dans la première zone de stockage jusqu'à rencontrer le code de fin de message,

- réécrivant chacun des caractères dans la seconde zone de stockage donnée avec le caractère exempt d'erreurs détecté, et

- écrivant chacun des caractères et le code de fin de message restant dans la première zone de stockage dans la seconde zone de stockage donnée.



* C L M S *