



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C23F 13/20	A2	(11) International Publication Number: WO 00/26439 (43) International Publication Date: 11 May 2000 (11.05.00)
(21) International Application Number: PCT/GB99/03517 (22) International Filing Date: 28 October 1999 (28.10.99) (30) Priority Data: 9823654.0 29 October 1998 (29.10.98) GB 09/306,419 6 May 1999 (06.05.99) US (71) Applicant (for all designated States except US): FOSROC INTERNATIONAL LIMITED [GB/GB]; Burmah Castrol House, Pipers Way, Swindon, Wiltshire SN3 1RE (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): DAVISON, Nigel [GB/GB]; 3 Chapmans Croft, Cotton-in-the-elms, Swadlincote, Derbyshire DE12 8DG (GB). GORRILL, Christopher [GB/GB]; 3 Wilnecote Grove, Leamington Spa, Warwickshire CV31 1YR (GB). (74) Agent: CLAYTON, Anthony, Nicholas; Group Patents Dept., Burmah Castrol House, Pipers Way, Swindon, Wiltshire SN3 1RE (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: CONNECTOR FOR USE IN CATHODIC PROTECTION AND METHOD OF USE (57) Abstract An assembly for use in the cathodic protection of steel reinforcement in reinforced concrete said assembly comprises: (i) an anode of a metal having a more negative electrode potential than steel and, in electrical contact therewith, (ii) an elongate electrical connector eg a wire made of a ductile metal capable of being wound around the steel reinforcing element to be protected. The anode may be in the form of a block cast around a portion of the length of the elongate connector and preferably the elongate connector comprises a plurality of wires twisted together over a portion of their length with the anode cast around the twisted portion.		