

Description

This invention concerns apparatus for automatically controlling an operating parameter, such as, of an image display device such as a kinescope in a data display video monitor.

Conventional television receivers sometimes employ an automatic kinescope bias (AKB) control system for automatically maintaining a desired black current level for an associated image displaying kinescope. As a result of this operation, displayed picture colors and gray scale tracking of the kinescope are prevented from being adversely affected by unwanted variations of kinescope bias due to aging and temperature effects, among other factors. An AKB system suitable for use in a conventional television receiver is shown, for example, in our U.S. Patents US-A-4,263,622 and US-A-4,387,405.

An AKB system typically operates during image blanking intervals when the kinescope conducts a small black current representative of a black image. This current is sensed by the AKB system to generate a bias control signal representing the difference between the magnitude of the sensed black current and a desired black current reference level. The control signal is applied to the kinescope with a sense for reducing the difference.

The AKB system described in our aforementioned U.S. patents is particularly advantageous with respect to significantly reducing the effects of kinescope leakage currents upon measurement of the black current level. In that system, an induced kinescope cathode output pulse is produced in response to a pulse applied to a grid electrode of the kinescope. The magnitude of the induced pulse is representative of the black current level, and is processed to develop the bias control signal. The "induced pulse" technique can also be employed to maintain a desired white drive, or gain, characteristic of the kinescope in a white balance control system to assure the display of a white image in response to a video signal containing white information.

It is herein recognized that a data display video monitor, such as a computer display terminal, can also benefit from an AKB system, particularly an AKB system of the "induced pulse" type mentioned previously. Specifically, a disclosed embodiment of the invention includes a data display video monitor having a display screen with small visible areas along upper and lower horizontal edges thereof which are normally devoid of displayed data. The development of the induced AKB black current representative pulse over a few horizontal line intervals causes such horizontal lines to illuminate. These illuminated horizontal line intervals are placed in one of the small areas along the

visible upper and lower edges of the display screen, outside the active data display viewing area, to avoid distorting or obscuring the displayed data and to reduce the visible effect of the illuminated lines. To further reduce the visible effect of such illuminated lines, the AKB signal processing circuits are activated for a short sensing interval, illustratively no more than two seconds, between substantially longer holding intervals of illustratively five minutes during which time the AKB signal processing circuits are inactive and the illuminated horizontal lines are absent.

In the drawing:

FIGURE 1 shows a portion of an AKB system for a data display monitor in accordance with the principles of the present invention;

FIGURES 2 and 3 depict circuits suitable for use in the system of FIGURE 1;

FIGURE 4 shows additional details of a data display monitor including an AKB system according to the present invention; and

FIGURE 5 illustrates signal waveforms helpful in understanding the operation of the AKB system shown in FIGURES 1 and 4.

The video monitor system of FIGURE 1 includes an AKB signal processor integrated circuit 15, which is the type CA 3224E integrated circuit commercially available from the Solid State Division of RCA Corporation, Somerville, NJ. Information concerning the structure and operation of the CA 3224E integrated circuit is found in the RCA preliminary data bulletin for the CA 3224E, file No. 1553. Additional information concerning the use of this integrated circuit is found in an article titled "An Automatic Kinescope Biasing System", authored by J.C. Tallant, II, et al., published in the IEEE Transactions on Consumer Electronics, Vol. CE-30, No. 4, November 1984.

Briefly, circuit 15 receives horizontal (H) and vertical (V) synchronizing signals, derived from deflection circuits of the monitor, for providing output signals G, B and P at terminals 11, 13 and 12, respectively. Signal G is a periodic pulse signal which is employed to excite (forward bias) the control grid electrode of an image reproducing kinescope (shown in FIGURE 4) during AKB operating control intervals. This induces a kinescope cathode output pulse, hereinafter referred to as the "AKB pulse," with a magnitude related to the magnitude of black current conducted by the kinescope.

Signal B is a blanking signal which encompasses the AKB operating control interval. Signal B is used to inhibit video signals prior to the kinescope driver stage, as will be seen from FIGURE 4, so that the video signals do not interfere with the operation of the AKB system. Input terminals 2, 4 and 6 of AKB processor circuit 15 are respectively

coupled to the red, green and blue video signal channels for receiving respective sensed black current representative signals during given AKB operating intervals as will be explained.

The kinescope associated with this data display video monitor, e.g., a computer display terminal, is a raster scan device. Each image scanning field interval following the vertical retrace interval includes, in the visible area along the top edge of the kinescope display screen, a small area several horizontal image lines wide where data is normally not displayed. This area is followed by the active data display viewing area which encompasses the remainder of the display screen, except for a further small area along the bottom edge of the display screen at the end of the vertical scanning field (i.e., just prior to the beginning of the vertical retrace interval) where data is normally not displayed. Thus the kinescope of the disclosed system does not include an "overscan" area along and beyond the top and bottom edges of the display screen, out of sight of the viewer.

A sensed black current representative positive pulse signal RS for the red channel, produced as will be discussed in connection with FIGURES 4 and 5, is AC coupled via a signal translating circuit 18a to input terminal 2 of circuit 15. Signal RS is derived from the black current representative AKB pulse produced in response to excitation of the kinescope grid, as will be seen from FIGURE 4. Circuit 18a includes a signal inverting amplifier transistor 20 which receives signal RS, a preset brightness tracking potentiometer 21 in the collector output circuit of transistor 20, an AC coupling capacitor 22, and a Zener diode 23 for limiting large signal amplitudes appearing during image trace intervals, all arranged as shown. Signal translating circuits 18b and 18c respectively receive sensed black current representative signals GS and BS from the green and blue video signal channels for application to input terminals 4 and 6 of circuit 15, and are similar in structure and operation to circuit 18a.

AKB circuit 15 includes signal processing circuits such as clamping, sampling and comparator circuits responsive to translated black current representative input signals RS, GS and BS for producing kinescope bias control output signals RB, GB and BB. These signals are respectively applied to red, green and blue video signal processing channels for maintaining a desired black current DC bias condition of the kinescope as will be discussed in connection with FIGURE 4.

For AKB control purposes circuit 15 produces a so-called auxiliary "program pulse" P of fixed amplitude at output terminal 12 during a prescribed portion of each AKB operating control interval. Brightness control is accomplished by varying the

magnitude of pulse P in accordance with the level of a variable brightness control voltage VB from a brightness control source 10. This produces a pulse P with a magnitude related to the setting of a viewer adjustable brightness control potentiometer 12. Voltage VB is at a maximum positive level for producing maximum image brightness when the wiper of potentiometer is at the uppermost setting. Conversely, minimum brightness is produced at the lowermost setting of the wiper of potentiometer 12.

Pulse P is coupled via a buffer transistor 25 to signal translating circuits 18a, 18b and 18c. Illustratively, in translating circuit 18a, pulse P is coupled to a signal combining point A via a decoupling diode 26 and brightness tracking potentiometer 21. The role of pulse P and other aspects of the AKB system will be better understood by considering the waveforms of FIGURE 5.

In FIGURE 5, signal V includes a positive pulse component occurring during the vertical retrace blanking interval, which encompasses several horizontal line intervals (1H) as illustrated by the waveform of horizontal line signal H. AKB blanking signal B encompasses several horizontal line intervals including a clamp reference interval and a sample interval within the AKB control interval. Negative-going pulse signal G is developed by circuit 15 during the clamp interval, from which a positive pulse component of a grid drive signal G' is developed for driving the grid electrode of the kinescope during the clamp or excitation interval.

Signal RS, as developed at the collector output of amplifier transistor 20 in FIGURE 1, is a negative going amplified version of the black current representative AKB pulse induced when signal G' is applied to the kinescope grid electrode. Amplitude A of pulse RS varies by an amount Δ depending upon the deviation of the black current level from a desired level. Pulse P is a negative going pulse of amplitude A, and occurs during the sample interval following the clamp interval when pulse RS appears. Amplitude A of pulse P is fixed for a given setting of brightness control 10, and does not vary with changes in the kinescope black current level.

Signal RS is conveyed via transistor 20 to signal combining point A, and signal P is conveyed via potentiometer 21 to point A. A signal developed at point A, and AC coupled via capacitor 22 to sense input terminal 2 of AKB circuit 15, exhibits a magnitude related to the magnitude of the AKB pulse. Kinescope red bias control voltage RB for the red kinescope cathode is a function of the magnitude of pulse RS relative to the magnitude of pulse P, as described in detail in US Patent 4,484,228 of R.P. Parker except with respect to varying the magnitude of pulse P with the brightness control setting. Pulses RS and P are processed by AKB bias control circuit 15 such that,

when the kinescope black current bias level is correct, the amplitudes of the pulses are equal, the voltage at point A does not change from the clamp interval to the sample interval, and the level of red cathode bias control voltage RB does not change.

On the other hand, an incorrect black current bias condition will cause sensed pulse RS to exhibit a related amplitude variation of $\pm\Delta$. This amplitude variation relative to the amplitude of pulse P causes the voltage at point A to change by an amount $\pm\Delta$ from the clamp interval to the sample interval, and results in a corresponding change in the level of red bias control voltage RB until by feedback action (as will be seen in connection with FIGURE 4) a correct black current bias condition is achieved and the amplitudes of pulses RS and P are equalized.

The black current conducted by the kinescope cathode is related to the DC bias of the cathode, and the brightness of a displayed image is related to the DC bias of the cathode. A correct cathode black current bias condition is determined by the relationship between the magnitudes of pulses P and RS. The magnitude of pulse P is related to the setting of brightness control 12. Accordingly, adjustment of brightness control 12 causes a change in the brightness of a displayed image.

Signal G, from which grid drive signal G' is ultimately obtained, is coupled via an electronic switch 29 to a grid drive amplifier circuit as will be seen in FIGURE 1. Switch 29 responds to a keying signal K, which is also coupled to toggle inputs of switches 30a, 30b and 30c in a switching network 30 such as the CD 4053 integrated circuit commercially available from the Solid State Division of RCA Corporation, Somerville, NJ. Keying signal K may be derived as will later be explained with respect to FIGURE 2.

The inputs of switches 30a, 30b and 30c are respectively coupled to red, green and blue output terminals 21, 19 and 17 of AKB circuit 15. One output terminal of switches 30a, 30b and 30c is connected directly to storage capacitors 32a, 32b and 32c, respectively, and to a noninverting (+) input terminal of buffer amplifiers 34a, 34b and 34c, respectively. The other output terminal of these switches is coupled to an inverting (-) input of buffer amplifiers 34a, 34b and 34c, respectively. Buffer amplifiers 34a, 34b and 34c each have an output coupled to an inverting input in a voltage follower configuration. In this case these buffers exhibit a very high input impedance at the inverting and noninverting inputs and a low output impedance, and are contained in the MOS-input quad operation amplifier integrated circuit type CA 084 commercially available from the Solid State Division of RCA Corporation, Somerville, NJ.

The output circuitry associated with terminals

17, 19 and 21 of AKB circuit 15 sources and sinks current depending upon the need to correct an improper kinescope bias condition. Such output circuitry produces no output current if kinescope bias is correct. Illustratively, the output current of terminal 21 of AKB circuit 15 charges and discharges capacitor 32a during AKB "sensing" intervals when switch 30 is in the upper position shown and AKB circuit 15 actively modifies the charge on capacitor 32a to produce a correct kinescope bias condition. At other times, hereinafter referred to as "holding" intervals, switch 30a occupies the lower position whereby output terminal 21 of AKB circuit 15 is coupled to the output of buffer 34a, and the charge on capacitor 32a can be held for hours with negligible loss due to the very high input impedance of buffer 34a. During the holding intervals, the bias control voltage on capacitor 32a is coupled via buffer 34a, switch 30a and an internal bipolar buffer circuit of the AKB circuit 15 to output terminal 20 of circuit 15, at which red bias control signal RB appears.

The AKB system is activated for a relatively short "sensing" interval of no more than about 2 seconds in this example, between considerably longer "holding" intervals of approximately 5 minutes duration in this example. This is accomplished in response to keying signal K which controls the position of switches 30a, 30b and 30c, and controls the operation of switch 29 which selectively passes grid signal G to a subsequent grid signal processing network as will be seen in FIGURE 4.

Signal K exhibits a first level during the relatively short sensing interval, and a second, more positive, level during the much longer holding interval. During the sensing interval the AKB system is activated by permitting electronic switch 29 to convey grid signal G to the kinescope grid electrode via the grid drive circuit, and by setting switches 30a, 30b and 30c to the uppermost position, as illustrated, for connecting capacitors 32a, 32b and 32c to red, green and blue output terminals 21, 19 and 17 of AKB circuit 15, respectively. Thus the kinescope cathode black current level is sampled, and the charge on capacitors 32a-32c is monitored and updated as required every vertical field interval for the duration of the sensing interval of signal K.

Signal G energizes the kinescope grid electrode to produce the black current representative AKB pulse during three horizontal lines in each field when the AKB system is activated, as explained previously and as seen from the waveforms of FIGURE 5. As a consequence of the kinescope grid being so energized, three illuminated horizontal lines appear across the visible uppermost edge of the underscanned display screen, beginning shortly after the end of the vertical retrace interval but before the beginning of the active data display

area of the screen, while signal G is present. Circuit 15 includes an internal AKB interval generator which defines the placement of the AKB interval within the display screen raster in response to the horizontal (H) and vertical (V) synchronizing signals.

In the disclosed system the AKB operating interval encompasses clamping and sampling intervals within seven horizontal line intervals immediately after the end of the vertical retrace intervals, as seen from FIGURE 5. In other monitors, the AKB system can be arranged to have the illuminated horizontal lines appear along the bottom of the screen between the end of the active data display area and the beginning of the vertical retrace interval, or along both top and bottom edges of the display screen. In any case, the visible, illuminated horizontal lines are placed outside of the active data display region to prevent destruction or distortion of the data being displayed and to reduce the visible effect of the illuminated lines.

The disclosed preferred sensing interval of up to 2 seconds and the holding interval of about 5 minutes have been observed to produce good bias control results without annoying the viewer. The duration of the sensing intervals depends on factors such as the time constant of the AKB system, the value of the AKB control voltage storage capacitor, and the current conduction capability at the output terminals (e.g., terminal 21) of the AKB circuit.

The maximum duration of the sensing interval is a function of the anticipated viewer tolerance of the potentially disturbing illuminated horizontal lines developed during each AKB interval. A duration of 2 seconds or less has been found to be satisfactory. The minimum length of the sensing interval is primarily a function of the AKB time constant, i.e., the speed at which the AKB system is capable of correcting an improper bias condition within a given time period to assure that proper kinescope bias is maintained. In general the sensing interval should encompass a plurality of vertical field intervals.

The holding interval should be considerably longer than the sensing interval to reduce the potentially disturbing visible effect of the illuminated horizontal lines. The use of high input impedance buffer amplifiers 34a, 34b and 34c advantageously prevents the bias control voltage developed on the storage capacitors from deteriorating during the holding interval, and maintains a substantially constant voltage at output terminals 17, 19 and 21 of AKB circuit 15.

When the AKB system is activated during the sensing intervals, as discussed, storage capacitor 32a is directly connected to output terminal 21 of AKB circuit 15 via switch 30a (up position). Buffer

34a is unused at such times. During holding intervals, the low impedance output of buffer 34a is connected to output terminal 21 of circuit 15 via switch 30a (down position). The bias control voltage developed across capacitor 32a is substantially replicated at the output of buffer 34a and appears at terminal 21. However, during holding intervals, capacitor 32a is essentially isolated from terminal 21 due to the very high input impedance of buffer 34a. Thus the disclosed arrangement of buffer 34a advantageously serves to maintain a substantially constant voltage at terminal 21 and to prevent deterioration of the voltage across capacitor 32a during the long holding intervals. Similar observations apply to the switches, buffers and storage capacitors associated with output terminals 17 and 19 of circuit 15.

The disclosed arrangement of buffers 34a, 34b and 34c also is advantageously used in connection with preset voltages V1, V2 and V3 supplied to storage capacitors 32a, 32b and 32c from a source 40. When a video monitor is initially energized, the kinescope cathodes are cold and consequently conduct very little or no current. The kinescope electron guns warm up to a normal operating temperature several seconds after the system is initially energized. This time delay varies from one kinescope type to another, but typically is on the order of about 10 to 15 seconds, after which the kinescope electron guns come into conduction rapidly.

A typical AKB system usually requires about 2 to 5 seconds to achieve correct kinescope bias after the end of the kinescope warm-up interval. The time delay between energization of the system and achievement of correct kinescope bias is undesirable. During this interval before proper kinescope bias is established, a displayed picture can exhibit distorted colors, with the colors often changing as the kinescope bias is gradually adjusted to the correct value through the action of the AKB system. This undesirable effect is eliminated by means of preset voltage source 40 in association with a switching network 42 and a timer 46 (e.g., a monostable multivibrator), which respond to the operation of a source of AC power 43, a viewer operated power switch 44, and a source of system operating potentials 45.

The system is initially energized in response to plural system operating voltages (B+, (+), . . . (-)) being developed by source 45 when source 45 is energized from AC power source 43 when power switch 44 is placed in the "ON" position. The activation of source 45 causes timer 46 to develop a PRESET pulse of fixed duration, e.g., several seconds corresponding to the time required by the kinescope to warm up sufficiently. The PRESET pulse causes switch elements 42a, 42b and 42c of

network 42 to close, thereby conveying preset voltages V1, V2 and V3 to AKB storage capacitors 32a, 32b and 32c respectively.

These voltages are typically derived from potentiometers in source 40 and exhibit levels such that, when applied to the red, green and blue electron guns of the kinescope via the AKB system, the respective kinescope electron guns are caused to be initially maintained at nominally correct bias values. At the end of the initial interval encompassed by the PRESET pulse, switches 42a, 42b and 42c are caused to open as shown, whereby the preset voltages are decoupled from the storage capacitors. AKB action then continues with respect to warm kinescope electron guns and an associated bias condition which can be expected to approximate the initial bias condition established by the preset network.

Buffers 34a, 34b and 34c advantageously act in the same manner with respect to the preset voltages developed across storage capacitors 32a, 32b and 32c during the initial preset interval as with respect to the holding intervals during normal AKB operation as previously discussed. Only one buffer per channel is required in connection with both the normal holding mode and the initial preset mode.

The generation of the sensing interval pulse component to activate the AKB system can be initiated in several ways, as indicated by FIGURE 2.

In the case of a system having a preset circuit as previously discussed, the AKB system should be activated at the end of the preset interval such as in response to an AKB trigger signal T1 developed by an optional power-up timer 46 at the end of the preset interval, or sooner. The AKB system preferably is automatically activated in response to a periodic trigger signal T2 illustratively produced every five minutes by a programmable timer 50, or manually in response to a trigger signal T3 produced by an optional viewer activated control 52 such as a degaussing switch or a dedicated manual AKB switch.

The detection of certain voltage changes can also be used to activate the AKB system, such as in response to a trigger signal T4 produced by an optional dv/dt detector which senses a rate of change in one or more selected control voltages such as can be associated with the contrast or brightness control functions or with some other auxiliary function. In the disclosed monitor system image brightness can be varied only if the AKB system is enabled, but in any case a contrast or brightness control voltage change may load the power supply of the system, thereby causing a kinescope supply voltage change and a related bias condition change which can be corrected by

the AKB system.

Trigger signals T1-T4 are coupled to inputs of a logic OR gate 56, the output of which is coupled to a timer 58 (e.g., a monostable multivibrator). Signal K is derived from an inverting output of timer 58. Any one of trigger signals T1-T4 will produce the negative going sensing interval pulse component of signal K for activating the AKB system.

FIGURE 3 shows circuit details of a dv/dt detector corresponding to block 54 in FIGURE 2. In FIGURE 3 an operational amplifier 60 is arranged as an active differentiator with a time constant slow enough to produce a large output signal in response to slowly varying input voltages. Brightness, contrast and auxiliary control voltages are coupled via respective resistor-capacitor networks 61a, 61b and 61c to an inverting input of amplifier 60. A feedback capacitor 62 suppresses faster noise components. Both positive and negative output signals from amplifier 60 produce a positive going output signal (T4) from a differential input amplifier 64 for activating the AKB system during sensing intervals. Auxiliary inputs "a" and "b" are provided for coupling optional auxiliary switching signals to a signal inverting input of amplifier 64. These inputs could receive trigger signals T1 and T2 from units 46 and 50 of FIGURE 2, for example, thereby eliminating the need for a 4-input OR gate in the arrangement of FIGURE 2.

Additional details of the AKB control system disclosed in FIGURE 1 are shown in FIGURE 4.

In FIGURE 4, a low level color video signal r from a source 70 is applied to a preamplifier 71 which responds to a gain adjustment (GAIN ADJ.) input signal for varying the amplitude of the red (r) video signal, and to AKB blanking signal B. Blanking signal B inhibits the operation of preamplifier 71 to prevent signal r from interfering with the operation of the AKB system during AKB intervals.

An amplified video signal from preamplifier 71 is applied to a display driver amplifier stage 72 which provides a high level amplified RED color video signal suitable for directly driving a red intensity control cathode electrode 73a of a color kinescope 75. Kinescope 75 has a control grid 76 common to each of cathode electrodes 73a, 73b and 73c. Grid 76 forms an electron gun assembly with each of cathodes 73a, 73b and 73c.

Driver 72 comprises an input common emitter amplifier transistor 84 arranged in a cascode amplifier configuration with a video output common base transistor 86. A transistor 88 comprises an active load circuit for driver 72. The high level RED video signal is developed at the emitter of transistor 88 and is AC coupled via a capacitor 90 and a current limiting resistor 91 to red video signal cathode 73a.

A bias control network 100 comprises the circuit elements of FIGURE 1 with the exception of units 10, 43, 45 and 46 (not shown in FIG 5) which provide the VB and PRESET signals.

Red cathode bias control signal RB from circuit 100 is provided as an input to a DC restoration clamping circuit 105, the output of which is coupled to a video output signal path following AC coupling capacitor 90. Clamp circuit 105 coacts with capacitor 90 to maintain a desired restored DC bias condition for the red kinescope cathode. The magnitude of the restored red cathode bias voltage is a function of the magnitude of bias control voltage RB.

Clamp 105 is normally keyed to operate during the so-called "back porch" portion of each horizontal line blanking interval in response to a clamp keying signal C. The keying signal C may be locally generated in response to horizontal line synchronizing components. Signal C is interrupted during AKB operating intervals by means of a switch 108 in response to AKB blanking signal B, whereby the operation of the clamp is inhibited during AKB operating intervals to prevent the clamp from distorting the induced black level representative AKB pulse.

In like manner, green and blue signal processors 120 and 130 respectively receive low level green (g) and blue (b) video signals from source 70 for producing GREEN and BLUE color video signals for driving kinescope cathodes 73b and 73c. Each of processors 120 and 130 includes a preamplifier, kinescope driver amplifier stage, output AC coupling capacitor and cathode current limiting resistor, and clamp and switch network as discussed above in connection with the red signal path.

A grid blanking signal generator 116 responds to horizontal (H) and vertical (V) deflection signals for producing, during horizontal and vertical blanking intervals, a grid blanking signal GB which is applied via an electronic switch 117 to a grid drive circuit 118 including amplifier circuits. Switch 117 responds to AKB blanking signal B for interrupting the application of grid blanking signal GB to drive circuit 118 during AKB operating intervals. Grid drive circuit 118 also receives signal G which is developed by bias control circuit 100 during AKB intervals as discussed. Grid drive circuit 118 provides grid drive output signal G' to grid electrode 76. Grid drive signal G' includes a positive pulse component during AKB control intervals as shown in FIGURE 5, and a negative grid blanking pulse component (not shown in FIGURE 5) during horizontal and vertical blanking intervals outside of the AKB interval. At other times, i.e., during image trace intervals, signal G' exhibits a given DC level for biasing grid 76.

During AKB operating control intervals when

the positive pulse component of grid drive signal G' is developed, the resulting black current representative AKB pulse is coupled via capacitor 90 to the emitter of transistor 88 of red display driver 72.

A related positive version of the AKB pulse appears across a load resistor 89 in the collector circuit of transistor 88 and is coupled to bias control unit 100 as signal RS. This is processed as discussed previously in connection with FIGURE 1.

Resulting red bias control signal RB is applied to clamp 105 for establishing a desired DC restored bias condition of red cathode 73a. The established DC bias of the red kinescope cathode is a function of the magnitude of the AKB pulse and the setting of the brightness control, as discussed. The green and blue video signal channels operate in a similar manner.

Apparatus in accordance with the principles of the present invention as disclosed can also be used in an automatic white balance control system, sometimes referred to as an automatic kinescope drive (AKD) control system. In an AKD system a white reference level is applied to each video channel, and the signal gain parameter (rather than the bias parameter) of the kinescope is automatically adjusted such as by varying the signal gain of the kinescope driver amplifiers so that the kinescope displays a white image in response to a video signal containing white information.

Claims

1. A data display video monitor system comprising:

an image display device (75) for displaying data on a display screen thereof in response to a video data signal, said display screen including a visible area along a horizontal edge of said display screen which is normally devoid of displayed data;

means connected for exciting (118) said display device during an excitation interval within a sensing interval to produce, at an electrode (73) thereof, a signal having a magnitude representative of the condition of an operating parameter of said display device, said excitation of said display device causing a visible artifact to appear on the display in said visible area along said edge of said display screen; and

control means (100) connected for providing an output control signal (RB) to said display device to maintain a desired condition of said operating parameter in response to the magnitude of said representative signal;

characterized by means for defining each sensing interval preceded by and followed by a holding interval, whereof:



A bias control network 100 comprises the circuit elements of FIGURE 1 with the exception of units 10, 43, 45 and 46 (not shown in FIG 5) which provide the VB and PRESET signals.

Red cathode bias control signal RB from circuit 100 is provided as an input to a DC restoration clamping circuit 105, the output of which is coupled to a video output signal path following AC coupling capacitor 90. Clamp circuit 105 coacts with capacitor 90 to maintain a desired restored DC bias condition for the red kinescope cathode. The magnitude of the restored red cathode bias voltage is a function of the magnitude of bias control voltage RB.

Clamp 105 is normally keyed to operate during the so-called "back porch" portion of each horizontal line blanking interval in response to a clamp keying signal C. The keying signal C may be locally generated in response to horizontal line synchronizing components. Signal C is interrupted during AKB operating intervals by means of a switch 108 in response to AKB blanking signal B, whereby the operation of the clamp is inhibited during AKB operating intervals to prevent the clamp from distorting the induced black level representative AKB pulse.

In like manner, green and blue signal processors 120 and 130 respectively receive low level green (g) and blue (b) video signals from source 70 for producing GREEN and BLUE color video signals for driving kinescope cathodes 73b and 73c. Each of processors 120 and 130 includes a preamplifier, kinescope driver amplifier stage, output AC coupling capacitor and cathode current limiting resistor, and clamp and switch network as discussed above in connection with the red signal path.

A grid blanking signal generator 116 responds to horizontal (H) and vertical (V) deflection signals for producing, during horizontal and vertical blanking intervals, a grid blanking signal GB which is applied via an electronic switch 117 to a grid drive circuit 118 including amplifier circuits. Switch 117 responds to AKB blanking signal B for interrupting the application of grid blanking signal GB to drive circuit 118 during AKB operating intervals. Grid drive circuit 118 also receives signal G which is developed by bias control circuit 100 during AKB intervals as discussed. Grid drive circuit 118 provides grid drive output signal G' to grid electrode 76. Grid drive signal G' includes a positive pulse component during AKB control intervals as shown in FIGURE 5, and a negative grid blanking pulse component (not shown in FIGURE 5) during horizontal and vertical blanking intervals outside of the AKB interval. At other times, i.e., during image trace intervals, signal G' exhibits a given DC level for biasing grid 76.

During AKB operating control intervals when

the positive pulse component of grid drive signal G' is developed, the resulting black current representative AKB pulse is coupled via capacitor 90 to the emitter of transistor 88 of red display driver 72. A related positive version of the AKB pulse appears across a load resistor 89 in the collector circuit of transistor 88 and is coupled to bias control unit 100 as signal RS. This is processed as discussed previously in connection with FIGURE 1.

Resulting red bias control signal RB is applied to clamp 105 for establishing a desired DC restored bias condition of red cathode 73a. The established DC bias of the red kinescope cathode is a function of the magnitude of the AKB pulse and the setting of the brightness control, as discussed. The green and blue video signal channels operate in a similar manner.

Apparatus in accordance with the principles of the present invention as disclosed can also be used in an automatic white balance control system, sometimes referred to as an automatic kinescope drive (AKD) control system. In an AKD system a white reference level is applied to each video channel, and the signal gain parameter (rather than the bias parameter) of the kinescope is automatically adjusted such as by varying the signal gain of the kinescope driver amplifiers so that the kinescope displays a white image in response to a video signal containing white information.

Claims

1. A data display video monitor system comprising:

an image display device (75) for displaying data on a display screen thereof in response to a video data signal, said display screen including a visible area along a horizontal edge of said display screen which is normally devoid of displayed data;

means connected for exciting (118) said display device during an excitation interval within a sensing interval to produce, at an electrode (73) thereof, a signal having a magnitude representative of the condition of an operating parameter of said display device, said excitation of said display device causing a visible artifact to appear on the display in said visible area along said edge of said display screen; and

control means (100) connected for providing an output control signal (RB) to said display device to maintain a desired condition of said operating parameter in response to the magnitude of said representative signal;

characterized by means for defining each sensing interval preceded by and followed by a holding interval, whereof:



each sensing interval encompasses a first plurality of vertical field intervals during which said visible artifacts appear; and

each holding interval encompasses a second plurality of vertical field intervals which is substantially greater than said first plurality of vertical field intervals, and during which said visible artifacts are absent.

2. A system according to Claim 1, characterized in that

said excitation interval encompasses plural horizontal line intervals.

3. A system according to Claim 1 or 2, characterized in that

said display device is a kinescope (75) with a grid electrode (76) excited by said exciting means (118) and a cathode electrode (73) at which said representative signal appears.

4. A system according to Claim 1, 2 or 3, characterized in that

said representative signal exhibits a magnitude representative of the black current bias condition of said display device.

5. A system according to Claim 1, characterized in that said control means (100) includes

a charge storage device (32);

means (15) for developing, at an output terminal of said control means, a signal having a magnitude related to the magnitude of said representative signal;

means for conveying said related signal to said charge storage device, comprising

a) an amplifier (34) having an inverting signal input (-), a noninverting signal input (+), and an output coupled to said inverting input;

b) switch means (30) having an input coupled to said output terminal of said control means, a first output coupled to said charge storage device and to said noninverting input, and a second output coupled to said inverting input and to said output of said amplifier; wherein

c) said switch means (30) occupies a first position during said sensing interval for connecting said output terminal of said control means to said first output of said switch means; and

d) said switch means (30) occupies a second position during said holding interval for connecting said output of said control means to said second output of said switch means.

Patentansprüche

1. Video-Monitorsystem für Datenanzeige, welches aufweist:

ein Bildanzeigegerät (75) zum Anzeigen von Daten auf seinem Bildschirm, abhängig von einem Video-Datensignal, wobei der Bildschirm einen Sehbereich längs seines horizontalen Randes hat, der normalerweise ohne angezeigte Daten ist;

eine Einrichtung zur An- bzw. Erregung des Anzeigegerätes während eines Erregungsintervalles innerhalb eines Erfassungsintervalles, um an einer Elektrode (73) des Anzeigegerätes ein Signal zu erzeugen, welches eine - für den Zustand eines Betriebsparameters des Anzeigegerätes repräsentative - Größe aufweist, wobei die An- bzw. Erregung des Anzeigegerätes einen sichtbaren Artefakt auf dem Bildschirm in dem Sehbereich längs seines Randes entstehen läßt; und

eine Steuereinrichtung (100), um dem Anzeigegerät ein Ausgangs-Steuersignal (RB) zur Aufrechterhaltung eines erwünschten Zustandes des Betriebsparameters - abhängig von der Größe des repräsentativen Signales - zuzuführen,

gekennzeichnet durch

eine Einrichtung zur Festlegung jedes Erfassungsintervalles, denen jeweils ein Halteintervall vorausgeht und folgt, wobei:

jedes Erfassungsintervall eine erste Mehrzahl von Vertikal-Halbbildintervallen (field intervals) aufweist, während denen die sichtbaren Artefakte auftreten; und

jedes Halteintervall eine zweite Mehrzahl von Vertikal-Halbbildintervallen aufweist, die wesentlich größer ist, als die erste Mehrzahl von Vertikal-Halbbildintervallen (field intervals), und während welcher die sichtbaren Artefakte fehlen.

2. System nach Anspruch 1, dadurch gekennzeichnet,

daß das An- bzw. Erregungsintervall mehrere Horizontal-Zeilenintervalle aufweist.

3. System nach Anspruch 1 oder 2, dadurch gekennzeichnet,

daß das Anzeigegerät eine Bildröhre (75) ist, mit einer von der An- bzw. Erregereinrichtung (118) erregten bzw. angeregten Gitterelektrode (76) und mit einer Kathodenelektrode (73), an welcher das Repräsentativsignal erscheint.

4. System nach einem der Ansprüche 1 bis 3, dadurch gekennzeichnet,



daß das Repräsentativsignal eine Größe aufweist, die für den Schwarzstrom-Vorspannungszustand (bias condition) des Anzeigegerätes repräsentativ ist.

5. System nach Anspruch 1, dadurch gekennzeichnet, daß die Steuereinrichtung (100) aufweist:

- eine Ladungsspeichereinrichtung (32);
- eine Schaltung (15) zur Abgabe eines Signals an einem Ausgangsanschluß der Steuereinrichtung mit einer der Größe des Repräsentativsignals verwandten Größe;
- eine weitere Einrichtung zur Weitergabe des verwandten (related) Signales an die Ladungsspeichereinrichtung, welche aufweist:
 - (a) einen Verstärker (34), der einen invertierenden (-) und einen nichtinvertierenden (+) Signaleingang und einen mit dem invertierenden Eingang verbundenen Ausgang hat,
 - (b) eine Schalteinrichtung (30), die einen - mit dem Ausgangsanschluß der Steuereinrichtung (100) gekoppelten - Eingang, einen ersten - mit der Ladungsspeichereinrichtung und dem nichtinvertierenden Eingang gekoppelten - Ausgang und einen zweiten - mit dem invertierenden Eingang und dem Ausgang des Verstärkers gekoppelten - Ausgang aufweist;
 - (c) wobei die Schalteinrichtung (30) während des Erfassungsintervalles eine erste Schaltposition einnimmt zum Verbinden des Ausgangsanschlusses der Steuereinrichtung (100) mit dem ersten Ausgang der Schalteinrichtung; und
 - (d) wobei die Schalteinrichtung (30) während des Halteintervalls eine zweite Schaltposition einnimmt zum Verbinden des Ausgangs der Steuereinrichtung (100) mit dem zweiten Ausgang der Schalteinrichtung.

Revendications

1. Système de moniteur vidéo pour affichage de données comprenant :

- un dispositif d'affichage d'images (75) pour afficher des données sur un écran d'affichage dudit système en réponse à un signal de données vidéo, ledit écran d'affichage comprenant une zone visible le long d'un bord horizontal dudit écran d'affichage qui est normalement dépourvu de données affichées,
- des moyens connectés pour exciter (118)

ledit dispositif d'affichage pendant un intervalle d'excitation dans un intervalle de détection, pour produire, sur une électrode (73) de ce dispositif, un signal possédant une amplitude représentative de l'état d'un paramètre de fonctionnement dudit dispositif d'affichage, ladite excitation du dispositif d'affichage produisant un objet visible devant apparaître sur l'affichage dans ladite zone visible, le long dudit bord de l'écran d'affichage et,

- des moyens de commande (100) connectés de façon à fournir un signal de commande de sortie (RB) dudit dispositif d'affichage pour maintenir ledit état désiré dudit paramètre de fonctionnement en réponse à l'amplitude dudit signal représentatif,

caractérisé par des moyens pour définir chaque intervalle de détection précédé par, ou suivi d'un intervalle de maintien et dans lequel :

chaque intervalle de détection entoure une première pluralité d'intervalles de champ vertical durant lesquels apparaissent lesdits objets visibles et

chaque intervalle de maintien entoure une seconde pluralité d'intervalles de champ vertical qui est sensiblement plus grande que ladite première pluralité d'intervalles de champ vertical, et durant lesquels lesdits objets visibles sont absents.

2. Système selon la revendication 1 caractérisé en ce que ledit intervalle d'excitation entoure plusieurs intervalles de ligne horizontale.

3. Système selon la revendication 1 ou 2 caractérisé en ce que ledit dispositif d'affichage est un cinescope (75) avec une grille (76) excitée par lesdits moyens d'excitation (118) et une cathode (73) sur laquelle apparaît ledit signal représentatif.

4. Système selon la revendication 1, 2 ou 3 caractérisé en ce que ledit signal représentatif présente une amplitude représentative de l'état de polarisation du courant de noir dudit système d'affichage.

5. Système selon la revendication 1, caractérisé en ce que lesdits moyens de commande (100) comprennent :

- un dispositif de stockage de charges (32)



- des moyens (15) pour développer, sur une borne de sortie desdits moyens de commande, un signal connexe présentant une amplitude fonction de l'amplitude dudit signal représentatif ; 5
- des moyens pour transmettre ledit signal connexe au dispositif de stockage de charges, comprenant
 - a) un amplificateur (34), une entrée de signal d'inversion (-), une entrée de signal de non-inversion (+) et une sortie couplée à ladite entrée d'inversion ; 10
 - b) des moyens de commutation (30) ayant une entrée couplée à ladite borne de sortie des moyens de commande, une première sortie couplée audit dispositif de stockage de charges et à ladite entrée de non inversion, et une seconde sortie couplée à ladite entrée d'inversion et à ladite sortie dudit amplificateur, dans lequel : 15
 - c) lesdits moyens de commutation (30) occupent une première position pendant ledit intervalle de détection pour connecter ladite borne de sortie des moyens de commande à ladite première sortie des moyens de commutation, et 25
 - d) lesdits moyens de commutation (30) occupent une seconde position pendant ledit intervalle de maintien pour connecter ladite sortie des moyens de commande à ladite seconde sortie desdits moyens de commutation. 30

35

40

45

50

55

10