



1/21



2/21




FIG. 3




FIG. 4








FIG. 5

3/21








FIG 10

6/21




FIG 11

7/21




FIG 12

8/21




FIG 13

9/21




FIG 14

10/21




FIG 15




FIG 16

11/21




FIG 17




FIG 18

12/21




FIG 19




FIG 20

13/21




FIG 21




FIG 22

14/21




FIG 23

15/21




FIG.24

16/21




FIG.25

17/21




FIG.26

18/21




FIG.27

19/21





FIG.28

	Medium Level Optimization			High Level Optimization		
Color target [nm]	BLUE 460-485nm	GREEN 560-590nm	RED 600-640nm	BLUE 460-485nm	GREEN 560-590nm	RED 600-640nm
P [nm]	280 +/-10	340 +/-10	360 +/-10	340 +/-10	400 +/-10	450 +/-10
d [nm]	100 +/-10	140 +/-10	150 +/-10	220 +/-10	260 +/-10	280 +/-10
Fill factor	0.4 +/-0.05	0.4 +/-0.08	0.4 +/-0.1	0.56 +/-0.05	0.54 +/-0.08	0.56 +/-0.08
L [nm] ZNS Coating	140 +/-10	140 +/-10	180 +/-15	240 +/-10	280 +/-10	300 +/-10
Illumination Angle	-10°	-8°	-10°	-14°	-14°	-14°
Averaged efficiency	>60%	>60%	>60%	>80%	>80%	>80%

FIG.29

**FIG.30**