

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(10) 国际公布号
WO 2020/215286 A1

(43) 国际公布日
2020 年 10 月 29 日 (29.10.2020)

(51) 国际专利分类号:
H04W 24/10 (2009.01)

(21) 国际申请号: PCT/CN2019/084363

(22) 国际申请日: 2019 年 4 月 25 日 (25.04.2019)

(25) 申请语言: 中文

(26) 公布语言: 中文

(71) 申请人: 北京小米移动软件有限公司 (BEIJING XIAOMI MOBILE SOFTWARE CO., LTD.) [CN/CN]; 中国北京市海淀区西二旗中路33号院6号楼8层018号, Beijing 100085 (CN)。

(72) 发明人: 李明菊 (LI, Mingju); 中国北京市海淀区西二旗中路33号院6号楼8层018号, Beijing 100085 (CN)。

(74) 代理人: 北京三高永信知识产权代理有限公司 (BEIJING SAN GAO YONG XIN INTELLECTUAL PROPERTY AGENCY CO., LTD.); 中国北京市海淀区学院路蓟门里和景园A座1单元102室, Beijing 100088 (CN)。

(81) 指定国 (除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG,

BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW。


(84) 指定国 (除另有指明, 要求每一种可提供的地区保护): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), 欧亚 (AM, AZ, BY, KG, KZ, RU, TJ, TM), 欧洲 (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG)。

本国际公布:

— 包括国际检索报告 (条约第21条 (3))。

(54) Title: BEAM FAILURE REPORTING METHOD AND APPARATUS, AND STORAGE MEDIUM

(54) 发明名称: 波束失败的上报方法、装置及存储介质



201 A TERMINAL DETERMINES THAT BEAM FAILURE OCCURS TO A TARGET SECONDARY SERVING CELL IN N ACCESSED SECONDARY SERVING CELLS, N BEING A POSITIVE INTEGER
202 THE TERMINAL SENDS FIRST MAC CE SIGNALING TO A BASE STATION, THE FIRST MAC CE SIGNALING COMPRISING BEAM FAILURE INDICATION INFORMATION

(57) Abstract: The present disclosure relates to the technical field of communications, and relates to a beam failure reporting method and apparatus, and a storage medium. The method comprises: a terminal determines that beam failure occurs to a target secondary serving cell in n accessed secondary serving cells, n being a positive integer; and the terminal sends first MAC CE signaling to a base station, the first MAC CE signaling comprising beam failure indication information. Embodiments of the present disclosure provide a reporting scheme of a terminal when beam failure occurs to a secondary serving cell, thereby implementing reporting of a beam failure situation of the secondary serving cell.

(57) 摘要: 本公开是关于一种波束失败的上报方法、装置及存储介质, 属于通信技术领域。所述方法包括: 终端确定接入的n个辅服务小区中的目标辅服务小区发生波束失败, n为正整数; 终端向基站发送第一MAC CE信令, 第一MAC CE信令中包括波束失败指示信息。本公开实施例提供了一种终端在辅服务小区发生波束失败时的上报方案, 实现了辅服务小区的波束失败情况的上报。

WO 2020/215286 A1