PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : B63B 35/44 — A1

(11) International Publication Number: WO 99/32352

(43) International Publication Date: 1 July 1999 (01.07.99)

(21) International Application Number: PCT/NO98/00373

(22) International Filing Date: 10 December 1998 (10.12.98)

(30) Priority Data:

19975828	11 December 1997 (11.12.97)	NO
19980987	6 March 1998 (06.03.98)	NO

(71) Applicant *(for all designated States except US)*: ORMEN BREDE A/S [NO/NO]; Dæliveien 33B, N–1370 Asker (NO).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: DYBDAHL, Svein [NO/NO]; Dæliveien 33B, N–1370 Asker (NO). REMMEN, Per, Inge [NO/NO]; Nes Terrasse 15A, N–1360 Nesbru (NO).

(74) Agent: BRYNS PATENTKONTOR A/S; P.O. Box 765, Sentrum, N–0106 Oslo (NO).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

In English translation (filed in Norwegian).

(54) Title: FLOATING PRODUCTION INSTALLATION

(57) Abstract

A floating production installation, including a main moonpool (1) and wherein the ship is designed to turn primarily about a centre of rotation (3) so as to be able to adapt to the wave and/or wind direction. On at least one side of the main moonpool there is arranged a substantially slot–shaped moonpool (2, 6) which extends in spaced relation to the centre of rotation (3) of the installation, which slot–shaped moonpool is designed to receive at least a riser (5, 8) which extends from the seabed to the installation. Alternatively, on at least one side of the main moonpool there is arranged a plurality of small moonpools (11, 13), which are positioned in spaced relation to the centre of rotation (3) of the installation. The small moonpools (11, 13) are designed to receive at least a riser (12, 14), which extends from the seabed to the installation.

