

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/055367 A3

(51) International Patent Classification⁷: **F04F 1/00**

(21) International Application Number:
PCT/US2003/039095

(22) International Filing Date:
10 December 2003 (10.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/433,315 13 December 2002 (13.12.2002) US
Not furnished 5 December 2003 (05.12.2003) US

(71) Applicants and


(72) Inventors: **DUKES, Jon, W.** [US/US]; 1200 Marion Street, Columbia, SC 29201 (US). **PENDERGRASS, Rickie, A.** [US/US]; 1735 Mt. Holly Road, Rock Hill, SC 29730 (US). **PLATTS, Drew, L.** [US/US]; 1460 Friendship Road, Barnwell, SC 29812 (US). **SOARES, Jairo, L.** [BR/BR]; Rua Grapecica 142 - Brooklin Novo, CEP 04562-040, Sao Paulo - SP (BR).

(74) Agents: **WEVER, Michael, E.** et al.; Nelson Mullins Riley & Scarborough, P.O. Box 11070, Columbia, SC 29211 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,

[Continued on next page]

(54) Title: GAS PRESSURE DRIVEN FLUID PUMP HAVING COMPRESSION SPRING PIVOT MECHANISM AND DAMPING SYSTEM



(57) Abstract: A gas pressure driven fluid pump (10) having a pump tank (12) with a liquid inlet and a liquid outlet (34). A float assembly (14) is carried within the interior of the pump tank and is movable between a low level position and a high level position. A compression spring (22) is connected between the float assembly and a pivot member (24). Due to the force applied by the compression spring, the pivot member rotates to a first position when the float reaches its high level position and rotates to a second position when the float reaches its low level position. A valve assembly (78) is connected to said pivot member to switch between motive porting and exhaust porting in a snap over fashion due to rotation of said pivot member between said first position and said second position. A damper system (82) may be connected to the valve assembly to slow movement of the valve assembly between motive porting and exhaust porting.



SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
13 January 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.