



(51) International Patent Classification:

F21S 2/00 (2006.01) *F21V 29/00* (2006.01)
F21V 5/00 (2006.01) *F21Y 101/02* (2006.01)
F21V 8/00 (2006.01)

(21) International Application Number:

PCT/IB2011/051867

(22) International Filing Date:

28 April 2011 (28.04.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/328,869 28 April 2010 (28.04.2010) US

(71) Applicant (for all designated States except US): **KLA-TENCOR CORPORATION** [US/US]; 1 Technology Drive, Milpitas, CA 95035 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HILL, Andy** [US/US]; 1382 Hillcrest Court, San Jose, CA 95120 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: RING LIGHT ILLUMINATOR AND BEAM SHAPER FOR RING LIGHT ILLUMINATOR




Fig. 9

(57) Abstract: A ring light illuminator with annularly arranged light sources is disclosed. To each light source there corresponds a beam shaper comprising a light collector, a homogenizing means for light from the light source, and an imaging means for imaging an output of the homogenizing means into an area to be illuminated. The homogenizing means in embodiments is a rod, into which light from the light collector is directed. The end of the rod opposite the light collector is imaged by the imaging means into the area to be illuminated.



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*