CLAIMS

1. Vehicle seat comprising a base portion (2) for attachment in a vehicle (4); a seat bottom part (12), with a top side (18) and an underside (20), which seat bottom part (12) is attached to the base portion (2); a waist belt (26) extending between the seat bottom part´s (12) sides;, ~~characterized in that~~ at least one hinge mechanism (28; 28'), that is adjustable between a first and a second position is arranged at the base portion (2) and that the waist belt (26) is attached to the hinge mechanism (28; 28'), so that the waist belts (26) position in relation to the seat bottom part (12) changes when one on the seat bottom part (12) acting force reaches a predetermined value, which force leads the hinge mechanism (28; 28') from the first to the second position, **characterized in that** the seat bottom part (12) comprises a resilient support surface (14), which is arranged at and supported by an at least partially around the support surface (14) surrounding frame (16), wherein an actuator (34) extends substantially parallel with the seat bottom part´s (12) underside (20) and is attached to the at least one hinge mechanism (28; 28'), so that the actuator (34) leads the hinge mechanism (28; 28') to the second position when the predetermined force acting on the seat bottom part (12) is reached.

~~2. Seat according to claim 1, **characterized in that** an actuator (34) extends substantially parallel with the seat bottom part´s (12) underside (20) and is attached to the at least one hinge mechanism (28; 28'), so that the actuator (34) leads the hinge mechanism (28; 28') to the second position when the predetermined force acting on the seat bottom part (12) is reached.~~

1

~~3~~2. Seat according to claim ~~2~~, **characterized in that** the actuator is a belt (34), extending along the seat bottom part´s (12) underside (20).

~~4. Seat according to any of the previous claims, **characterized in that** the seat bottom part (12) comprises a resilient support surface (14), which is arranged at and supported by an at least partially around the support surface (14) surrounding frame (16).~~

~~5~~3. Seat according to any of the previous claims, **characterized in that** the hinge mechanism (28; 28') comprises a locking lug (38; 38') which interacts with pawls (40; 40', 42; 42')

arranged on the hinge mechanism (28; 28'), such that the locking lug (38; 38') engages with a first pawl (40; 40') when the hinge mechanism (28; 28') is in the first position and that the locking lug (38; 38') engages a second pawl (42; 42') when the hinge mechanism (28; 28') is lead to the second position.

~~6~~4. Seat according to any of the preceding claims, **characterized in that** the hinge mechanism (28) is rotatable between the first and the second position.

~~7~~5. Seat according to claims 3 and 4 ~~5 and 6~~, **characterized in that** the seat bottom part (12) is hingeably attached to the base portion (2), so that the seat bottom part (12) can be raised to a substantially vertical position in which the locking lug (38) engages with a third pawl (44) on the hinge mechanism (28).

~~8~~6. Seat according to claim 5 ~~7~~, **characterized in that** a pull down hook (52) is arranged at the at least one hinge mechanism (28), which pull down hook (52) interacts with the seat bottom part (12), so that the pull down hook (52) rotates the hinge mechanism (28) to the first position when the seat bottom part (12) is lowered from the substantially vertical position to a substantially horizontal position.

~~9~~7. Seat according to any of claims 1-3 ~~1 - 5~~, **characterized in that** the hinge mechanism (28') is substantially linearly displaceable between the first and second position.

~~10~~8. Seat according to any of the previous claims, **characterized in that** a hinge mechanism (28; 28') is arranged on each side of the seat (1) and that the waist belt (26) is extending between the hinge mechanisms (28; 28').

~~11~~9. Seat according to any of the previous claims, **characterized in that** a backrest (22) is arranged at the base portion (2), which backrest (22) is supported by the cords (23) attached to the vehicle (4).

~~12~~10. Seat according to any of the previous claims, **characterized in that** a shoulder belt (30) is at a first end attached to the waist belt (26) and with a second end attached to the vehicle (4).