

Description

The present invention relates to an apparatus and a process for introducing catalyst particles into a moving bed of catalyst.

It is known to introduce catalyst particles into a fluid catalytic cracking reactor by means of a stand pipe interconnecting a regenerator and the bottom part of a reactor of a fluid catalytic cracking unit. A stream of catalyst particles is thus passed by gravity from the regenerator into the bottom part of the reactor (liftpot) through the stand pipe and directed to the upper part of the reactor by means of (lift)gases and the feed to be converted.

A disadvantage of the use of a conventional liftpot, however, is that the catalyst particles only obtain the flow best suited for commercial catalytic cracking (i.e. plug-flow) after they have passed the riser over a substantial length.

It has now been found that catalyst particles can advantageously be brought in plug-flow at a far earlier stage, i.e. when the riser has only been passed over a very short distance, by employing as liftpot an apparatus comprising a housing provided with a particular passage for catalyst particles in the downstream part thereof. As a result thereof improved reaction patterns can be obtained in the reactor, resulting in improved yields of valuable products.

The present invention therefore relates to an apparatus for introducing catalyst particles into a moving bed of catalyst, which apparatus comprises a housing, in the upstream part thereof having inlet means for introducing catalyst particles into the housing and having fluidization means, and in the downstream part thereof having a passage for the catalyst particles defined between directing means and the inner wall of the housing and/or between adjacent directing means facing each other, wherein the passage has a narrowing part and a narrow part in downstream direction and wherein the directing means are not axially displaceable.

Preferably, the housing comprises a single passage defined between a substantially centrally arranged directing means and the inner wall of the housing.

Suitably, the single passage comprises an annular opening.

The annular opening is suitably uninterrupted but an interrupted annular opening comprising a series of openings arranged in an annular pattern can also be applied. Although a single (annular) passage is preferred, it should be understood that a plurality of passages can be arranged in such a way that the housing comprises more than one annular opening, for instance three annular openings to allow the catalyst particles to pass through.

Preferably, the passage of the apparatus according to the present invention comprises a widening part in downstream direction.

Suitably, the housing of the apparatus according to the present invention comprises directing means having a widening part, a wide part and a narrowing part in downstream direction and wherein the directing means are not axially displaceable.

Advantageously, the directing means has a diamond-shape vertical cross-section and is symmetrically arranged in respect to its vertical axis.

Advantageously, the apparatus according to the present invention comprises fluid supply means having at least one fluid outlet opening debouching in the widening part or at or near the narrow part of the passage.

Preferably, the fluid outlet opening is arranged downstream with respect to the narrow part of the passage.

Preferably, the fluid supply means comprises at least one device arranged onto the wall of the housing downstream with respect to the narrow part of the passage.

Advantageously, such a device comprises at least one supply means of which the wall comprises openings. The fluid to be supplied to the housing can thus be introduced into the supply means and mixed with an at least partly surrounding gas which may enter under pressure the supply means through the openings in the wall thereof.

Preferably, the apparatus according to the present invention comprises more than one device as described hereinbefore, for instance four of these devices. For further details on said devices we refer to EP-A-423 876.

Suitably, the housing comprises directing means comprising fluid supply means which extend from the bottom end part of the housing. The fluid outlet opening can suitably be arranged in the narrowing part of the directing means in downstream direction. The fluid outlet opening of the fluid supply means can be an annular opening in the downstream end part of the fluid supply means, or can be a number of openings arranged in an annular pattern in the downstream end part of the fluid supply means.

In another suitable embodiment of the apparatus according to the present invention a directing means is arranged onto the inner wall of the housing whereby the passage is defined between said directing means and the fluid supply means extending from the bottom end part of the housing as described hereinabove.

In yet another suitable embodiment of the apparatus in accordance with the present invention the housing comprises a grid of directing means between which passages are defined having a narrowing part and a narrow part.

The apparatus according to the present invention is suitably provided with both directing means in the form of fluid supply means which extend from the bottom end part of the housing and fluid supply means in the form of devices which are arranged onto the wall of the housing having a fluid outlet opening along the widening part of the passage.

Suitably, the housing comprises a directing means in the form of a single tubular fluid supply means substantially centrally arranged in the bottom end part thereof.

Suitably, the annular passage is of such a size that the catalyst particles pass the opening at a velocity which is at least 0.25 times the velocity of the catalyst particles in the riser reactor. Preferably, the catalyst particles pass the opening at a velocity which is at least 0.5 times the velocity of the catalyst particles in the riser reactor.

In a very attractive embodiment of the present invention the apparatus comprises inlet means for introducing catalyst particles into the housing which inlet means comprises a fluidized bed of catalyst particles.

The inlet means suitably communicates with a fluidized bed of catalyst particles, for instance the bottom part of a stripper vessel or a regeneration vessel. In that way the catalyst particles are advantageously pre-accelerated before they pass the passage by using the static head at the bottom of the stripper vessel or regeneration vessel.

Preferably, the inlet means comprising the fluidized bed of catalyst particles comprises fluidization means (e.g. in the form of a perforated plate or ring-shaped or annular fluidization means) provided with regularly spaced fluidization gas openings through which a fluidization gas can be introduced in the inlet means. Suitable fluidization gases include steam and fluid catalytic cracking off gas.

The inlet means comprising the fluidized bed of catalyst particles is preferably of tubular form and horizontally arranged.

Advantageously, the inlet means of catalyst particles is arranged in such a way that the length thereof is from 2 to 3 times the diameter of the tubular inlet means, and the housing/inlet means diameter ratio is suitably in the range from 1 to 5.

Advantageously, the housing has been provided with substantially horizontally internals upstream the passage for the catalyst particles. In this way advantageously a homogeneous flow of catalyst particles is established upstream the passage of the catalyst particles.

A major advantage of the apparatus according to the present invention is that during operation a stream of catalyst particles obtains an optimal flow mode, i.e. plugflow, at a far shorter distance from the passage for the catalyst particles than conventionally is the case, resulting in improved reaction patterns in the reactor and enabling the use of shorter reactors.

The apparatus according to the present invention is advantageously used in fluid catalytic cracking operations for introducing catalyst particles in a riser reactor.

Hence, the present invention further relates to an apparatus for catalytically cracking of hydrocarbonaceous feedstocks which comprises a riser reactor the bottom end part of which is connected to an apparatus for introducing catalyst particles as described hereinbefore.

When use is made in fluid catalytic cracking of an apparatus according to the present invention wherein the fluid outlet openings for introducing a hydrocarbonaceous feedstock are arranged downstream with respect to the narrow part of the passage a rapid, intimate and uniform mixing of catalyst particles with the hydrocarbonaceous feedstock can be attained.

Suitable embodiments of the present apparatus for introducing catalyst particles in a reactor for the conversion of a hydrocarbonaceous feedstock are described hereinafter, using Figures 1-3 in which reference numerals relating to corresponding parts are the same.

In Figures 1-3 longitudinal sections of bottom parts of fluid catalytic cracking reactors are schematically shown.

The bottom part of the fluid catalytic cracking reactor as depicted in Figure 1 comprises a substantially vertically housing (1) provided with an inlet means (2) for introducing catalyst particles, a directing means (3) arranged in the downstream part of the housing, a passage (4) defined between the directing means (3) and the inner wall of the housing (5) comprising an annular opening (6) and having a narrowing part, a narrow part and a widening part in downstream direction, a moving bed of catalyst (7) and fluid supply

means in the form of devices (8) (of which only two have been shown) for introducing a hydrocarbon oil into the riser reactor. The riser reactor furthermore comprises fluidization means (9), for instance in the form of a ring-shaped or annular fluidization means, provided with regularly spaced fluidization gas openings (e.g. nozzles (10)) through which a fluidization gas, for instance steam, introduced via fluidization gas inlet means (11) emanates into the bottom section (12) of the reactor.

In Figure 2 a preferred embodiment of the apparatus as depicted in Figure 1 is shown wherein the inlet means (2) for introducing catalyst particles comprises a fluidized bed of catalyst particles (14). The inlet means (2) furthermore preferably comprises fluidization means (15) (e.g. in the form of a perforated plate as depicted in Figure 2 or ring-shaped or annular fluidization means) provided with regularly spaced fluidization gas openings (e.g. nozzles (16)) through which a fluidization gas (e.g. steam or a fluid catalytic cracking off gas) introduced via fluidization gas inlet means (17) emanates into the fluidized bed of catalyst (14).

In Figure 3 another suitable embodiment of the apparatus in accordance with the present invention is depicted which comprises directing means in the form of a fluid supply means (13) which extends from the bottom end part of the reactor and comprises fluid outlet openings (18) in its narrowing part (of which only two have been shown).

The invention further relates to a process for introducing catalyst particles into a moving bed, which process comprises introducing a stream of catalyst particles into the upstream part of a housing and allowing the catalyst particles to pass in downstream direction through a passage defined between directing means and the inner wall of the housing and/or between adjacent directing means facing each other, wherein the passage has a narrowing part and a narrow part in downstream direction and wherein the directing means are not axially displaceable.

Preferably, the catalyst particles are allowed to pass through a single passage which is defined between a substantially centrally arranged directing means and the inner wall of the housing.

More preferably, the catalyst particles are allowed to pass through a single passage comprising an annular opening.

In the present process suitably any of the directing means can be applied as described hereinbefore.

The apparatus used in the process according to the present invention preferably comprises a passage having a widening part in downstream direction.

Preferably, the process in accordance with the present invention is carried out in such a way that a stream of fluidized catalyst particles enters the housing. For that purpose the inlet means preferably comprises a fluidized bed of catalyst particles which communicates substantially horizontally with the bottom part of a catalyst stripper vessel or a regeneration vessel. In this way the catalyst particles are advantageously pre-accelerated before passing the passage by use of the static head at the bottom of the stripper vessel or regeneration vessel.

Preferably, a pressure drop is maintained over the passage(s) of at least 0.2 bar.

More preferably, a pressure drop is maintained over the passage(s) of at least 0.3 bar.

Suitably the stream of catalyst particles passes the opening at a velocity of at least 0.25 times the velocity which the catalyst particles have in the riser reactor.

Preferably, the catalyst particles pass the opening at a velocity of at least 0.5 times the velocity of the catalyst particles in the riser reactor.

Suitably, the fluidized stream of catalyst particles is introduced into the upstream part of housing.

Preferably, fluid is introduced downstream with respect to the narrow part, e.g. along the widening part of the passage. Thus a very attractive rapid, intimate and uniform mixing of catalyst particles with fluid is obtained.

Preferably, the fluid is introduced with respect to the narrow part of the passage by means of devices which are arranged onto the wall of the housing. The process according to the present invention can advantageously be used for introducing catalyst particles in the riser reactor of a fluid catalytic cracking unit.

Therefore, the present invention also relates to a process for catalytic cracking of a hydrocarbonaceous feedstock, wherein the feedstock is introduced into a moving bed of catalytic cracking catalyst and catalytically cracked.

Fluids such as those applied in a catalytic cracking process are preferably mixed with the catalyst particles which are passed through the passage at a temperature from 0-800 °C, most preferably from 100-750 °C.

The mixing of fluid and catalyst particles is preferably carried out at elevated pressure, most preferably from 1-100 bar and in particular from 2-50 bar.

A fluid catalytic cracking process is preferably carried out at a temperature from 400-800 °C and a pressure from 1-10 bar.

Such a process is advantageously carried out in a riser reactor for fluid catalytic cracking of a hydrocarbonaceous feedstock as referred to hereinbefore and partly depicted in Figures 1-3 by introducing a stream of catalyst particles originating from a catalyst regenerator by means of the present apparatus.

The catalyst/fluid weight ratio to be applied in the process according to the present invention can vary within a wide range, and may be up to 100. It will be understood that the catalyst/fluid weight ratio of the stream of catalyst particles will have an influence upon the width of the passage for the catalyst particles. The higher the catalyst/fluid weight ratio of the stream of catalyst particles introduced into the housing the larger the width of the passage for the catalyst particles.

The process according to the present invention is normally carried out as follows.

A stream of catalyst particles (e.g. originating from a catalyst regenerator) is introduced through inlet means (2) into the bottom section (12) of the riser reactor. The catalyst particles are transported upwardly by means of for instance steam introduced via line (11) into ring-shaped or annular fluidization means (9) provided with regularly spaced nozzles (10). The upwardly fluidized mass of catalyst particles is subsequently advantageously accelerated over the passage (4) having a narrowing part, a narrow part and a widening part in downstream direction, introduced into the moving bed of catalyst (7) and excellently mixed with the stream of hydrocarbon oil which enters under pressure with a high velocity the reactor via the devices (8) or via fluid supply means (13) through the fluid outlet openings (18).

Although hereinabove a process has been described in which a stream of catalyst particles is passed upwardly through the passage, it should be understood that in accordance with the present invention also a downwardly directed stream of catalyst particles can suitably be introduced in a moving bed of catalyst arranged downstream of the passage.

The use of the apparatus in accordance with the present invention results in a very uniform mixing of the accelerated catalyst particles and the hydrocarbon oil and an optimal flow mode of the stream of catalyst particles at a very early stage in the riser reactor. As a result of this a very attractive increase in gasoline yield can be obtained.

The hydrocarbon oil which can suitably be converted in a fluid catalytic cracking process using the present apparatus comprises heavy hydrocarbon oils, for instance atmospheric or vacuum distillates, cycle oils and slurry oils, deasphalted oils, atmospheric and vacuum residues, thermally cracked residues, asphalts originating from various kinds of deasphalting processes, synthetic residues and hydrocarbon oils originating from hydroconversion processes, tar sands and shale oils of any source, and/or any mixture thereof.

The present invention is illustrated by means of the following Example.

Example

A fluid catalytic cracking experiment is carried out as follows. A stream of fluidized catalyst particles (regenerated zeolite Y catalyst particles) is introduced into a fluid catalytic cracking reactor comprising a liftpot as depicted in Figure 2 at a temperature of 700 °C and a pressure of 3.3 bar, and accelerated over the passage (4). The accelerated stream of catalyst particles is subsequently mixed with a stream of hydrocarbon oil having the properties as shown in Table 1 which oil is introduced via devices (8) at a temperature of 260 °C and a pressure of 6 bar. The catalyst particles enter the riser reactor at a velocity of 15 m/s. The riser reactor is operated at a temperature of 520 °C and a pressure of 3 bar. A comparative experiment is carried out in substantially the same manner as described hereinabove except that a fluid catalytic cracking reactor is used comprising a conventional liftpot. In the experiment which is carried out with the apparatus in accordance with the present invention 1 % wt more gasoline (C₅ -221 °C) is obtained, when compared with the comparative experiment.

TABLE 1

IBP. °C	273
50 % w	463 °C
70 % w	506 °C
density 70/4	0.8831
sulphur	144 ppmw
nitrogen	700 ppmw

Claims

1. Apparatus for introducing catalyst particles into a moving bed of catalyst, which apparatus comprises a housing, in the upstream part thereof having inlet means for introducing catalyst particles into the housing and having fluidization means, and in the downstream part thereof having a passage for the catalyst particles defined between directing means and the inner wall of the housing and/or between adjacent directing means facing each other, wherein the passage has a narrowing part and a narrow part in downstream direction, characterized in that the directing means are not axially displaceable.
2. Apparatus according to claim 1, wherein the housing comprises a single passage defined between a substantially centrally arranged directing means and the inner wall of the housing.
3. Apparatus according to claim 2, wherein the passage comprises an annular opening.
4. Apparatus according to any one of claims 1-3, wherein the passage comprises a widening part in downstream direction.
5. Apparatus according to any one of claims 1-4, wherein the housing comprises directing means comprising a widening part, a wide part and a narrowing part in downstream direction.
6. Apparatus according to any one of claims 1-5, wherein the housing comprises fluid supply means having at least one fluid outlet opening arranged downstream with respect to the narrow part of the passage.
7. Apparatus according to claim 6, wherein the fluid supply means comprises at least one device which is arranged onto the wall of the housing.
8. Apparatus according to any one of claims 1-7, wherein the directing means comprises fluid supply means extending from the bottom end part of the housing.
9. Apparatus according to claim 8, wherein the fluid supply means comprises fluid outlet openings which are circumferentially arranged in the downstream end part of the fluid supply means.
10. Apparatus according to any one of claims 1-9, wherein substantially horizontal internals have been arranged in the housing upstream the passage for the catalyst particles.
11. Apparatus according to any one of claims 1-10, wherein the inlet means for introducing catalyst particles comprises a fluidized bed of catalyst particles.
12. Apparatus according to claim 11, wherein the inlet means for introducing catalyst particles comprises fluidization means.

TABLE 1

IBP. °C	273
50 % w	463 °C
70 % w	506 °C
density 70/4	0.8831
sulphur	144 ppmw
nitrogen	700 ppmw

Claims

1. Apparatus for introducing catalyst particles into a moving bed of catalyst, which apparatus comprises a housing, in the upstream part thereof having inlet means for introducing catalyst particles into the housing and having fluidization means, and in the downstream part thereof having a passage for the catalyst particles defined between directing means and the inner wall of the housing and/or between adjacent directing means facing each other, wherein the passage has a narrowing part and a narrow part in downstream direction, characterized in that the directing means are not axially displaceable.
2. Apparatus according to claim 1, wherein the housing comprises a single passage defined between a substantially centrally arranged directing means and the inner wall of the housing.
3. Apparatus according to claim 2, wherein the passage comprises an annular opening.
4. Apparatus according to any one of claims 1-3, wherein the passage comprises a widening part in downstream direction.
5. Apparatus according to any one of claims 1-4, wherein the housing comprises directing means comprising a widening part, a wide part and a narrowing part in downstream direction.
6. Apparatus according to any one of claims 1-5, wherein the housing comprises fluid supply means having at least one fluid outlet opening arranged downstream with respect to the narrow part of the passage.
7. Apparatus according to claim 6, wherein the fluid supply means comprises at least one device which is arranged onto the wall of the housing.
8. Apparatus according to any one of claims 1-7, wherein the directing means comprises fluid supply means extending from the bottom end part of the housing.
9. Apparatus according to claim 8, wherein the fluid supply means comprises fluid outlet openings which are circumferentially arranged in the downstream end part of the fluid supply means.
10. Apparatus according to any one of claims 1-9, wherein substantially horizontal internals have been arranged in the housing upstream the passage for the catalyst particles.
11. Apparatus according to any one of claims 1-10, wherein the inlet means for introducing catalyst particles comprises a fluidized bed of catalyst particles.
12. Apparatus according to claim 11, wherein the inlet means for introducing catalyst particles comprises fluidization means.



13. Apparatus according to claim 11 or 12, wherein the inlet means for introducing catalyst particles communicates horizontally with a fluidized bed of catalyst particles.
14. Apparatus according to any one of claims 11-13, wherein the length of the inlet means is from 2 to 3 times the diameter of the inlet means.
15. Apparatus for catalytically cracking of hydrocarbonaceous feedstocks which comprises a riser reactor the bottom end part of which is connected to an apparatus for introducing catalyst particles as described in any one of claims 1-14.
16. Process for introducing catalyst particles into a moving bed of catalyst, which process comprises introducing a stream of catalyst particles into the upstream part of a housing and allowing the catalyst particles to pass in downstream direction through a passage defined between directing means and the inner wall of the housing and/or adjacent directing means facing each other, wherein the passage has a narrowing part and a narrow part in downstream direction, and wherein the directing means are not axially displaceable.
17. Process according to claims 16, wherein a pressure drop is maintained over the passage of at least 0.2 bar.
18. Process according to claims 16 or 17, wherein a fluidized stream of catalyst particles is introduced into the upstream part of the housing.
19. Process according to any one of claims 16-18, wherein fluid is introduced into the housing downstream with respect to the narrow part of the passage.
20. Process for catalytically cracking a hydrocarbonaceous feedstock wherein the feedstock is introduced into a moving bed of catalytic cracking catalyst comprising catalyst particles introduced by the process of any one of claims 16-18 and catalytically cracked.

Patentansprüche

1. Vorrichtung zum Einführen von Katalysatorteilchen in ein bewegtes Katalysatorbett, mit einem Gehäuse, in dessen stromaufwärtigem Teil Einlaßmittel zum Einführen der Katalysatorteilchen in das Gehäuse und Fluidisierungsmittel vorgesehen sind, und in dessen stromabwärtigem Teil ein Durchgang für die Katalysatorteilchen vorgesehen ist, der zwischen Leitmitteln und der Innenwand des Gehäuses und/oder zwischen benachbarten, einander zugekehrten Leitmitteln gebildet wird, wobei der Durchgang in stromabwärtiger Richtung einen sich verjüngenden Teil und einen engen Teil aufweist, dadurch gekennzeichnet, daß die Leitmittel nicht axial versetzbar sind.
2. Vorrichtung nach Anspruch 1, bei welcher das Gehäuse einen einzigen Durchgang aufweist, der zwischen im wesentlichen zentral angeordneten Leitmitteln und der Innenwand des Gehäuses angeordnet ist.
3. Vorrichtung nach Anspruch 2, bei welcher der Durchgang eine ringförmige Öffnung aufweist.
4. Vorrichtung nach einem der Ansprüche 1-3, bei welcher der Durchgang einen sich in stromabwärtiger Richtung erweiternden Teil aufweist.
5. Vorrichtung nach einem der Ansprüche 1-4, bei welcher das Gehäuse Leitmittel mit einem sich in stromabwärtiger Richtung erweiternden Teil, einem weiten Teil und einem sich verengenden Teil aufweist.
6. Vorrichtung nach einem der Ansprüche 1-5, bei welcher das Gehäuse Fluidzufuhrmittel aufweist, die zumindest eine Fluidauslaßöffnung haben, welche stromabwärts des engen Teiles des Durchganges angeordnet sind.



7. Vorrichtung nach Anspruch 6, bei welcher die Fluidzufuhrmittel zumindest eine Einrichtung aufweisen, die an der Wand des Gehäuses angeordnet ist.
8. Vorrichtung nach einem der Ansprüche 1-7, bei welcher die Leitmittel Fluidzufuhrmittel aufweisen, die sich vom unteren Endteil des Gehäuses wegerstrecken.
9. Vorrichtung nach Anspruch 8, bei welcher die Fluidzufuhrmittel Fluidauslaßöffnungen aufweisen, die in Umfangsrichtung im stromabwärtigen Endteil der Fluidzufuhrmittel angeordnet sind.
10. Vorrichtung nach einem der Ansprüche 1-9, bei welcher im wesentlichen horizontale Inneneinbauten im Gehäuse stromaufwärts des Durchganges für die Katalysatorteilchen angeordnet sind.
11. Vorrichtung nach einem der Ansprüche 1-10, bei welcher die Einlaßmittel zum Einführen der Katalysatorteilchen ein fluidisiertes Bett von Katalysatorteilchen aufweisen.
12. Vorrichtung nach Anspruch 11, bei welcher die Einlaßmittel zum Einführen der Katalysatorteilchen Fluidisierungsmittel aufweisen.
13. Vorrichtung nach Anspruch 11 oder 12, bei welcher die Einlaßmittel zum Einführen der Katalysatorteilchen horizontal mit einem fluidisierten Bett von Katalysatorteilchen in Verbindung stehen.
14. Vorrichtung nach einem der Ansprüche 11-13, bei welcher die Länge der Einlaßmittel das 2- bis 3-fache des Durchmessers der Einlaßmittel beträgt.
15. Vorrichtung zum katalytischen Cracken von kohlenwasserstoffhaltigen Einsatzmaterialien, mit einem Steigreaktor, dessen unterer Endteil mit einer Vorrichtung zum Einführen von Katalysatorteilchen verbunden ist, wie sie in einem der Ansprüche 1-14 beschrieben ist.
16. Verfahren zum Einführen von Katalysatorteilchen in ein bewegtes Katalysatorbett, bei welchem Verfahren ein Strom von Katalysatorteilchen in den stromaufwärtigen Teil eines Gehäuses eingeführt wird und die Katalysatorteilchen in Richtung stromabwärts durch einen Durchgang strömen gelassen werden, der zwischen Leitmitteln und der Innenwand des Gehäuses und/oder zwischen benachbarten, einander zugekehrten Leitmitteln gebildet ist, wobei der Durchgang in stromabwärtiger Richtung einen sich verengenden Teil und einen engen Teil aufweist und wobei die Leitmittel axial nicht versetzbar sind.
17. Verfahren nach Anspruch 16, bei welchem über dem Durchgang ein Druckabfall von zumindest 0,2 bar aufrechterhalten wird.
18. Verfahren nach Anspruch 16 oder 17, bei welchem ein fluidisierter Strom von Katalysatorteilchen in den stromaufwärtigen Teil des Gehäuses eingeführt wird.
19. Verfahren nach einem der Ansprüche 16-18, bei welchem Fluid in das Gehäuse stromabwärts des engen Teiles des Durchganges eingeführt wird.
20. Verfahren zum katalytischen Cracken von kohlenwasserstoffhaltigem Einsatzmaterial, bei welchem das Einsatzmaterial in ein bewegtes Bett von katalytischem Crackkatalysator eingeführt wird, welches Katalysatorteilchen aufweist, die durch das Verfahren nach einem der Ansprüche 16-18 eingeführt wurden, und katalytisch gecrackt wird.

Revendications

1. Appareillage pour introduire des particules de catalyseur dans un lit mobile de catalyseur, lequel appareillage comprend un logement, ayant dans sa partie amont des moyens d'entrée pour l'introduction des particules de catalyseur dans le logement et des moyens de fluidisation et ayant dans sa partie aval un passage pour les particules de catalyseur défini entre des moyens directionnels et la paroi intérieure du logement et/ou entre des moyens directionnels adjacents qui se font face mutuellement, où le passage a une partie qui se rétrécit et une partie étroite en direction aval, caractérisé en ce que les moyens directionnels ne sont pas déplaçables axialement.



2. Appareillage selon la revendication 1, dans lequel le logement comporte un seul passage défini entre un moyen directionnel situé en position sensiblement centrale et la paroi intérieure du logement.
3. Appareillage selon la revendication 2, dans lequel le passage comprend une ouverture annulaire.
4. Appareillage selon l'une quelconque des revendications 1-3, dans lequel le passage comprend une partie qui s'élargit en direction aval.
5. Appareillage selon l'une quelconque des revendications 1-4, dans lequel le logement comprend des moyens directionnels comprenant une partie qui s'élargit, une partie large et une partie qui se rétrécit en direction aval.
6. Appareillage selon l'une quelconque des revendications 1-5, dans lequel le logement comprend des moyens d'alimentation en fluide ayant au moins une ouverture de sortie pour fluide située en aval par rapport à la partie étroite du passage.
7. Appareillage selon la revendication 6, dans lequel le moyen d'alimentation en fluide comprend au moins un dispositif qui est arrangé sur la paroi du logement.
8. Appareillage selon l'une quelconque des revendications 1-7, dans lequel le moyen directionnel comprend un moyen d'alimentation en fluide s'étendant à partir de la partie terminale inférieure du logement.
9. Appareillage selon la revendication 8, dans lequel le moyen d'alimentation en fluide comporte des ouvertures de sortie pour fluide qui sont arrangées circonférentiellement dans la partie terminale aval du moyen d'alimentation en fluide.
10. Appareillage selon l'une quelconque des revendications 1-9, dans lequel des structures internes substantiellement horizontales ont été prévues dans le logement en amont du passage pour les particules de catalyseur.
11. Appareillage selon l'une quelconque des revendications 1-10, dans lequel le moyen d'entrée pour l'introduction des particules de catalyseur comprend un lit fluidisé de particules de catalyseur.
12. Appareillage selon la revendication 11, dans lequel le moyen d'entrée pour l'introduction des particules de catalyseur comprend un moyen de fluidisation.
13. Appareillage selon la revendication 11 ou 12, dans lequel le moyen d'entrée pour l'introduction des particules de catalyseur communique horizontalement avec un lit fluidisé de particules de catalyseur.
14. Appareillage selon l'une quelconque des revendications 11-13, dans lequel la longueur du moyen d'entrée est comprise entre 2 et 3 fois le diamètre du moyen d'entrée.
15. Appareillage pour le craquage catalytique de charges de départ hydrocarbonées, qui comprend un réacteur à colonne montante dont la partie terminale inférieure est reliée à un appareillage pour introduire des particules de catalyseur tel que décrit dans l'une quelconque des revendications 1-14.
16. Procédé pour introduire des particules de catalyseur dans un lit mobile de catalyseur, selon lequel on introduit un courant de particules de catalyseur dans la partie amont d'un logement et on laisse les particules passer en direction aval par un passage défini entre un moyen directionnel et la paroi intérieure du logement et/ou entre des moyens directionnels adjacents se faisant face, où le passage a une partie qui se rétrécit et une partie étroite en direction aval, et les moyens directionnels ne sont pas déplaçables axialement.
17. Procédé selon la revendication 16, dans lequel une chute de pression d'au moins 0,2 bar est maintenue sur le passage.



18. Procédé selon les revendications 16 ou 17, dans lequel un courant fluidisé de particules de catalyseur est introduit dans la partie amont du logement.
19. Procédé selon l'une quelconque des revendications 16-18, dans lequel le fluide est introduit dans le logement en aval par rapport à la partie étroite du passage.
20. Procédé pour le craquage catalytique d'une charge de départ hydrocarbonée, dans lequel la charge de départ est introduite dans un lit mobile de catalyseur de craquage catalytique comprenant des particules de catalyseur introduites par le procédé de l'une quelconque des revendications 16-18 et craquée catalytiquement.

10

15

20

25

30

35

40

45

50

55

