

ABSTRACT

An exhaust gas cleaning system (1), a method and a use are provided. The exhaust gas cleaning system (1) comprises a particle filter device (9), in turn
5 comprising a casing (15), a plurality of hollow ceramic filter rods (33) arranged at least partly inside an exhaust gas passage (19) of the casing (15), an exhaust gas inlet (25) and an exhaust gas outlet (27). The particle filter device (9) is configured to guide exhaust gas from the exhaust gas inlet (25), through said exhaust gas passage (19) and to the exhaust gas outlet (27). The particle filter device (9) further comprises a
10 perforated plate (29) arranged between the exhaust gas inlet (25) and said exhaust gas passage (19), which perforated plate (29) extends at least partly along said filter rods (33) and partly blocks an exhaust gas flow path (P) from the exhaust gas inlet (25) to said exhaust gas passage (19). The perforated plate (29) defines openings (41) arranged to allow exhaust gas to flow into said exhaust gas passage (19). The filter
15 rods (33) are gas permeable to allow exhaust gas to penetrate, during filtration, a respective wall (53) of said filter rods (33) and flow into said filter rods (33), and a respective open upper end (39) of the filter rods (33) are in communication with said exhaust gas outlet (27) so as to allow exhaust gas to leave the casing (15).