

REPLACED SHEETS	SG
☒ Description : paged ...3... to paged ...3.....	
☒ Claim(s) : paged ...10... to paged ...12.....	1
☒ Drawing(s) : paged ...1/4... to paged ...-.....	
☒ Abstract : paged ...5... to paged ...-.....	
DATE OF RECEIPT	

ADJUSTABLE FLIGHT BARS FOR A PACKAGING MACHINE
AND METHOD OF ADJUSTMENT

5

This invention relates generally to the loading of articles such as cans or bottles into end-loading sleeve type cartons. More particularly, the invention is concerned with an arrangement for varying the distance of an adjacent pair of flight bars so as to render the system adjustable for use with packages of different depths as measured in the direction of movement of the packages.

5

U.S. patent 4,237,673 issued December 9, 1980 discloses an arrangement wherein open ended sleeve type cartons are moved along a predetermined path while containers to be loaded into the cartons are fed at an acute angle to the path of movement of the cartons by transverse flight bars which are provided with wedge shaped end portions to facilitate a container grouping function. The flight bars also act as efficient means for driving the incoming items inwardly toward the path of movement of the open ended cartons so as to load the articles into one or both ends of the carton.

10

15

U.S. patent 5, 176,612 issued January 5, 1993 discloses a machine for feeding open ended sleeve type cartons from a hopper and for manipulating such cartons into set up condition and thereafter for depositing the cartons onto conveyor means having transverse flight bars engageable with the leading and trailing parts of the set up cartons.

20

In order to adapt presently known flight bar systems for use in conjunction with packages of different horizontal dimensions in the direction of package movement it has been necessary to remove existing flight bars from the machine to substitute such bars by other flight bars having different dimensions and tip angles than the original flight bars. Similarly it is known to adjust the spacing between adjacent

25

flight bars by, for example, removing detachable strip portion of the flight bars which renders a packaging system useable with larger packages, such detachable strips being removed individually from all the flight bars. Alternatively, such strips may be added to the flight bars to decrease the spacing there between for use with smaller size packages.

Either of these known methods of adapting a machine for use for different size packages is very time consuming and expensive and requires the services of a knowledgeable operator or mechanic.

One aspect of the present invention provides a method of adjusted the spacing between an adjacent pair of flight bars in a system for advancing packages sequentially along a predetermined path in which a leading component of at least one of said pair of flight bars is shifted relative to a trailing component thereof so as to alter the distance between the said pair of flight bars. Preferably, said leading and trailing components are pivoted towards or away from one another to alter the distance between the flight bars. It is also a preferred feature of this aspect of the invention that the leading and trailing components remain substantially parallel to one another during said relative shifting. A further preferred feature is that a series of such flight bars are adjusted simultaneously.

According to another aspect of the invention there is provided a flight bar assembly for use in advancing packages sequentially along a predetermined path in which at least one of a pair of adjacent flight bars in the assembly includes a leading component and a trailing component and wherein the leading and trailing components are interrelated so that they can be shifted relative to one another to adjust the spacing between said pair of flight bars. Preferably, the leading and trailing components are pivotally connected for movement substantially parallel to one another.

Yet another aspect of the invention provides a flight bar unit for a packaging machine which unit comprises a leading flight bar component and a trailing flight

This Sheet Has Been Replaced



bar component which components are interrelated so that they can be shifted relative to one another, means being provided to form an end face across the space between said components at each end of the unit when the components are moved apart.

5

A still further aspect of the invention provides a flight bar unit for a packaging machine which unit comprises a leading flight bar component and a trailing flight bar component and wherein means are provided for altering the angle of the ends and/or end faces of the ends of the unit when the leading and trailing components are shifted relative to one another.

10

According to this invention in yet another form, open ended sleeve type cartons after being set up into open ended condition are deposited between movable flight bars each having a leading component and a trailing component, a first pair of spaced apart endless driving elements are interconnected with each of said leading components and a second pair of spaced apart endless driving elements are interconnected with each of said trailing components and means for imparting controlled relative movement to said first and second pair of endless driving elements so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately succeeding flight bar thereby to render this system adaptable for use in conjunction with packages of different horizontal dimensions in the direction of movement of the flight bars along a predetermined path.

15

By this invention means for interrelating the leading and trailing components is provided so as to accommodate relative movement therebetween within a predetermined range.

20

By this means a packaging machine is easily converted for use with cartons whose horizontal dimensions in the direction of movement are different and such conversions may be made in a matter of a few minutes.

25

30

This Sheet Has Been Replaced



A flight bar assembly in a packaging machine will now be described, by way of example, with reference to the accompanying drawings, in which:-

5 FIG.1 is a perspective view of the infeed end of a packaging machine similar to that disclosed in the aforementioned U.S. patent 5, 176,612;

FIG.2 is a plan view of a pair of flight bar units of a series according to this invention in which leading and trailing components of each flight bar are hinged apart to decrease the spacing between the units;

10 FIG.3 is a view similar to FIG.2 but shows the leading and trailing components of the flight bars closed in face to face relationship with each other thereby to increase the spacing between the units;

15 FIG.4 is an enlarged view of the end portion of a leading and trailing component together with drive chains;

FIG.5 is a cross-sectional view taken along the line 5-5 as shown in FIG.4;

20 FIG.6 is a cross sectional view taken along the line 6-6 in FIG.4;

FIG.7 is a schematic representation of the system drive components, and;

25 FIG.8 is a schematic representation of a known form of speed reducer.

The structure shown in FIG.1 is similar in some respects to FIG.1 of the aforementioned U.S. patent 5,176,612. Hence, a pair of side frame support panels 1 and 2 are provided and the lower portion of a hopper is disposed atop a crossbar 3 shown in conjunction with a few collapsed cartons which are to be withdrawn from the hopper and set up into open ended condition by suction cups such as 4, 5, 6 and 7. The suction cup assembly is rotatable about main shaft 8 to engage and withdraw the lowermost carton from the hopper and to manipulate the carton

30

panels into set up condition as best shown in the aforementioned U.S. patent 5,176,612 issued January 5, 1993. The cartons 9 and 9a are separated by a flight bar formed according to this invention and which includes a leading component 10 and a trailing component 19. The leading component is driven by a pair of endless driving elements such as a pair of chains one of which is designated by the numeral 13 and the other of which is not shown in FIG.1. Similarly, trailing component 19 is movable by virtue of its connection with endless chain 12 and by a similar chain not shown in FIG.1 but which cooperates with the opposite end of trailing component 19.

10

Means for interconnecting the leading and trailing components is provided so as to limit relative movement therebetween within a predetermined range. Thus, as best shown in FIG.2, leading component 10 is pivotally mounted at pivot 14 to end plate 15 having a slot 16 formed therein which receives a pin 17 secured to an end part 18 of the trailing component 19. The right hand end of leading component 10 of flight bar FB1 is similarly pivotally connected at pivot 20 to end plate 21. A pin 22 is mounted on the right hand end of trailing component 19 and rides in slot 23 formed in end plate 21. Leading component 10 of the leading flight bar unit FB1 of the pair illustrated is secured to endless drive chains 24 and 25, and trailing component 19 of flight bar unit FB1 is secured to endless chains 26 and 27.

In order to adjust the assembly shown in FIG.2 conveying carton P1 for use in conjunction with the larger carton P2 as shown in FIG.3, the chains 24 and 25 are operated to move relative to the chains elements 26 and 27 while the machine is inoperative so as to increase the spacing between the flight bar units. In this embodiment, both the leading and trailing components 10 and 19 are shifted to become disposed adjacent to or in parallel contacting relation with each other, thereby to adapt the structure as shown in FIG.2 for use with a package P2 as shown in FIG.3. This adjustment of the machine can be effected in an efficient and rapid manner.

As shown in FIG.3, the edge 11a of the end part of leading component 10 at each of its ends is angled to facilitate an article grouping function by engagement with rows of incoming articles to be loaded and which are moving at an acute angle into the path of movement of the flight bars. This loading arrangement is shown and described in the U.S. patent 4,237,673. However, when the flight bar unit e.g. FB1 is adjusted so that the leading and trailing components 10, 19, respectively, are moved apart, the angled end part is provided by the end face 21a of plate 21 as shown in FIG.4. It will be appreciated that moving the leading and trailing components of the flight bar units apart decreases the spacing between adjacent units and thus adapts the conveying system for use with smaller sized cartons.

Normal drive and manipulation of the endless drive chains to effect adjustment is provided by the arrangement shown in FIGS. 7 and 8. A drive motor 30 is arranged through its shaft 31 and the sprocket 32 mounted on shaft 31 to drive the driving chain 33 so as to impart rotary motion to driving sprocket 34. The driving sprocket 34 drives sprockets 35, 36 and 37 and chains 24 and 25 through inner shaft 45a. Sprocket 37 drives sprocket 38, shaft 39 and output shaft 41b of gearbox 41.

If input shaft 41a to gearbox 41 is secured against rotation by a clamping bearing 48 then shafts 45 and 45a rotate together with no relative rotation therebetween. Of course, this establishes a static relationship so that chains 24 and 25 do not move relative to chains 26 and 27 and thus the trailing components of each flight bar are held in fixed relation relative to their associated leading components.

When it is desired to condition the system for use in conjunction with the structure shown in FIG.3 from that shown in FIG.2 and vice versa, the clamped condition of input shaft 41a is relieved by loosening clamping bearing 48 which clamps the input shaft 41a against rotation so as to permit rotation. The degree of rotation is effected by means of manually operable crank 49. Schematically represented FIG.8 constitutes a representation of the internal parts of gear box 41. With reference to FIG.8, gearbox 41 includes an internal gear formed on the inside

surface of gearbox 41, a sun gear 50 and planetary gears 51 and 52. Rotation of
 input shaft 41a causes direct rotation of sun gear 50 and hence planetary gears 51
 and 52 rotate respectively about shafts 53 and 54. This causes gearbox 41 to
 rotate about input shaft 41a and at the same time causes planetary gears 51 and 52
 5 themselves to rotate around sun gear 50 in the direction opposite to gearbox 41.
 Rotation of gearbox 41 causes rotation of sprocket 42 and shaft 45. Shaft 45 as
 is apparent from FIG.7 rotates sprockets 43 and 44 which in turn controls the
 movement of chains 26 and 27 thus effecting a shift in position of the trailing
 components 19. While on the other hand, rotation of planetary gears 51 and 52
 10 around sun gear 50 causes shaft 39 to rotate through shafts 53 and 54 together
 with a cross member 55. Rotation of shaft 39 then causes rotation of sprockets 38
 and 37 and shaft 45a. Shaft 45a rotates sprockets 35 and 36 which in turn controls
 the movement of chains 24 and 25 thus effecting a shift in position of the leading
 components 10. Rotations of shafts 45 and 45a resulting from operation of crank
 15 49 are effected in the respective directions opposite to each other, and thus relative
 movement between the leading and trailing components is effected. In order to
 effect a shift in position of the leading and trailing components as from that
 indicated in FIG.2 for example to that indicated in FIG.3, crank 49 is rotated
 clockwise as viewed in FIGS.7 and 8 to rotate shaft 45a clockwise and shaft 45
 20 counterclockwise. Once the desired shift in position of the leading and trailing
 components of the flight bars is effected, clamping bearing 48 is tightly secured
 about input shaft 41a thus precluding further rotation of 41a and causes shafts 45
 and 45a to rotate together in the same direction without any relative rotation
 therebetween. This restores the trailing components in the desired position relative
 25 to their associated leading components.

As shown in FIG.7, driving motor 30 is arranged through its shaft 31 and the
 sprocket 32 mounted on shaft 31 to drive the driving chain 33 so as to impart
 rotary motion to driving sprocket 34. The driving sprocket 34 drives sprockets 35,
 30 36, and 37 and chains 24 and 25 through inner shaft 45a. Thus sprocket 37 drives
 sprocket 38, shaft 39 and output shaft 41b of gearbox 41. Input shaft 41a of
 gearbox 41 is normally restrained as by clamping bearing 48. This causes

sprocket 40 which is attached to gear box 41, to rotate but at slightly different speed from shaft 39 thus driving sprocket 42 which is connected to sprockets 43 and 44 and chains 26 and 27 by virtue of the action of hollow shaft 45.

- 5 The ratio of the gear box 41 that causes shaft 39 and sprocket 40 to rotate at different speeds is compensated for by the difference in the number of teeth on sprocket 38 and sprocket 40 thus causing hollow shaft 45 to rotate at the same speed as the inner shaft.
- 10 In order to impart simultaneous relative movement to all of the leading and trailing components such as 10 and 19. Appropriate rotation of a manually operated control such as crank 49 is effected. Rotation of crank 49 imparts movement to leading and trailing components 10 and 19 through chains 24, 25, 26 and 27 so as to effect rapid and efficient adjustment of the flight bar units for use in conjunction
- 15 with packages having a wide variety of dimensions. Flight bar plates 15 and 21 also move to change the angle of engagement with the incoming products to be loaded thus to ensure a constant speed of the incoming items prior to engagement with the flight bars.
- 20 Although it is normally desirable to adjust all the flight bars simultaneously it is envisaged that a flight bar conveying system according to the invention may be modified by adjusting some, but not all, the flight bars in the series. For example, alternate flight bars only could be adjusted in order to alter the spacing between adjacent flight bars. Moreover, not all the flight bars in the system need be
- 25 adjustable since as in the example referred to where alternate flight bars only are adjusted, the remaining flight bars may be non-adjustable and/or of some other form.
- Other arrangements for controlling the endless chains may alternatively be used in
- 30 the present invention. One of such arrangements may be the one wherein the first pair of endless chains 24 and 25 are operably connected to a motor through a suitable clutch unit and the second pair of endless chains 26 and 27 are operably

connected to the same motor through another suitable clutch unit. Such an arrangement allows the first and second pairs of endless chains to move independently from each other to shift the positions of the leading and trailing components relative to each other.

5

10

15

20

25

30

CLAIMS

5

1. A method of adjusted the spacing between an adjacent pair of flight bars in a system for advancing packages sequentially along a predetermined path in which a leading component of at least one of said pair of flight bars is shifted
10 relative to a trailing component thereof so as to alter the distance between the said pair of flight bars.

2. A method according to claim 2 wherein said leading and trailing components are pivoted towards or away from one another to alter the distance
15 between the flight bars.

3. A method according to claim 1 or claim 2 wherein the leading and trailing components remain substantially parallel to one another during said relative shifting.
20

4. A method according to any of claims 1 to 3 wherein a series of flight bars are adjusted simultaneously.

5. A flight bar assembly for use in advancing packages sequentially along a predetermined path in which at least one of a pair of adjacent flight bars in the
25 assembly includes a leading component and a trailing component and wherein the leading and trailing components are interrelated so that they can be shifted relative to one another to adjust the spacing between said pair of flight bars.

30 6. A flight bar assembly according to claim 5 wherein the leading and trailing components are pivotally connected for movement substantially parallel to one

This Sheet Has Been Replaced





another.

7. A flight bar unit for a packaging machine which unit comprises a leading flight bar component and a trailing flight bar component which components are interrelated so that they can be shifted relative to one another, means being provided to form an end face across the space between said components at each end of the unit when the components are moved apart.
8. A flight bar unit for a packaging machine which unit comprises a leading flight bar component and a trailing flight bar component and wherein means are provided for altering the angle of the ends and/or end faces of the ends of the unit when the leading and trailing components are shifted relative to one another.
9. A system including flight bars for advancing packages in sequence along a predetermined path, each of said flight bars having a leading component and a trailing component, a first endless driving element connected to each of said leading components to move said leading components along said predetermined path, and a second endless driving element connected to each of said trailing components to move said trailing components along said predetermined path, said first and second driving elements being movable in synchronism so as to impart movement to packages along said predetermined path, means for imparting controlled relative movement to said first and second driving elements so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately succeeding flight bar thereby to render the system adaptable for advancing packages of different horizontal dimensions in the direction of movement of the flight bars along said predetermined path, and characterized by means for interconnecting said leading and trailing components with each other to limit relative movement therebetween within a predetermined range.
10. A system according to claim 9 wherein an end plate is pivotally connected

This Sheet Has Been Replaced





with each of said flight bar leading components near each end thereof and a pin is secured to each of said trailing components near each end thereof and wherein each of said end plates includes a slot in which the adjacent pin is slidably disposed.

5

11. A system according to claim 10 wherein each end of each of said leading components is configured in the form of the correct metering angle for product entry into the space between adjacent flight bars.

10

12. A system according to claim 10 wherein said slot is disposed at an angle which results in the disposition of said end plate in such a position that an edge of said end plate forms the correct metering angle for product entry into the space between adjacent flight bars.

15

20

25

30



5

ABSTRACT

10 A system of flight bars each flight bar having a leading component (10) and a trailing component (19), a first pair of endless drive chains (24, 25) interconnected with each leading component and a second pair of endless drive chains (26, 27) interconnected with each trailing component. Controlled relative movement is imparted to the first and second pair of drive chains so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately adjacent flight bar thereby to render the system adaptable for use in
15 conjunction with packages of different dimensions.

This Sheet Has Been Replaced






FIG. 1

This Sheet Has Been Replaced






FIG. 2

3/6




FIG. 3




FIG. 4




FIG. 5

5/6




FIG. 6





FIG. 7

616



THIS SHEET HAS BEEN
REPLACED

13

ADJUSTABLE FLIGHT BARS FOR A PACKAGING MACHINE AND METHOD OF ADJUSTMENT


ABSTRACT

A system of flight bars each flight bar having a leading component (10) and a trailing component (19), a first pair of endless drive chains (24, 25) interconnected with each leading component and a second pair of endless drive chains (26, 27) interconnected with each trailing component. Controlled relative movement is imparted to the first and second pair of drive chains so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately adjacent flight bar thereby to render the system adaptable for use in conjunction with packages of different dimensions.

Fig. 3

REPLACEMENT SHEETS		SG
☐	Description	: paged to paged
☐	Claim(s)	: paged to paged
☒	Drawing(s)	: paged ... <u>4</u> ... to paged ... <u>7</u> ...
☒	Abstract	: paged ... <u>13</u> ... to paged
DATE OF RECEIPT <u>7/11/96</u>		

This Sheet Has Been Replaced



8-34600-22

1/6





FIG. 1



8-2128032

22 DEC 1997

9106512-3

205

2

REPLACEMENT SHEETS SG
☒ Description : paged 2172a to paged
☒ Claim(s) : paged 1... to paged 12..
☐ Drawing(s) : paged to paged
☒ Abstract : paged 14 to paged

DATE OF RECEIPT 22/12/97

flight bars by, for example, removing detachable strip portion of the flight bars which renders a packaging system useable with larger packages, such detachable strips being removed individually from all the flight bars. Alternatively, such strips may be added to the flight bars to decrease the spacing therebetween for use with smaller size packages.

Either of these known methods of adapting a machine for use for different size packages is very time consuming and expensive and requires the services of a knowledgeable operator or mechanic.

According to a first embodiment of this invention there is provided a method of adjusting the spacing between an adjacent pair of transversal flight bars in a system of advancing packages sequentially along a predetermined path in which a leading component of at least one of said pair of flight bars is shifted relative to a trailing component thereof so as to alter the distance between the said pair of flight bars wherein the leading component and the trailing component are adjustably connected together at each of their ends.

According to a second embodiment of this invention there is provided a flight bar assembly for use in advancing packages sequentially along a predetermined path in which at least one of a pair of adjacent flight bars in the assembly includes a leading component and a trailing component and wherein the leading and trailing components are adjustably connected to each other at each of their ends so that they can be shifted relative to one another to adjust the spacing between said pair of flight bars.

According to a third embodiment of this invention there is provided a flight bar unit for a packaging machine which unit comprises a leading flight bar component and a trailing flight bar component which components are interrelated so that they can be shifted relative to one another characterised in that the interrelation comprises linkage means formed to provide an end face across the space between said flight bar components at each end of the unit when the components are spaced apart, said end face being angled to facilitate an article grouping function by engagement with rows of incoming articles to be loaded and which are moved at an acute angle into the path of movement of the flight bar unit.

According to a fourth embodiment of this invention there is provided a system including flight bars for advancing packages in sequence along a predetermined path each of said flight bars having a leading component and a trailing component, a first pair of spaced apart endless driving elements interconnected with each of said leading components and a second pair of spaced apart endless driving elements interconnected with each of said trailing components, said first and said second pairs of endless driving elements being movable in synchronism so as to impart movement to packages along said predetermined path, means for imparting controlled relative movement to said first and

22 DEC 1997


said second pairs of endless driving elements so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately succeeding flight bar thereby to render the system adaptable for advancing packages of different horizontal dimensions in the direction of movement of the flight bars along said predetermined path, and characterized by means for interrelating said leading and trailing components to accommodate relative movement therebetween within a predetermined range, an end plate pivotally connected with each of said flight bar leading components near each end thereof and a pin secured to each of said trailing components near each end thereof and wherein each of said end plates includes a slot in which the adjacent pin is slidably disposed.

According to a fifth embodiment of this invention there is provided a system including flight bars for advancing packages in sequence along a predetermined path each of said flight bars having a leading component and a trailing component, a first pair of spaced apart endless driving elements interconnected with each of said leading components and a second pair of spaced apart endless driving elements interconnected with each of said trailing components, said first and said second pairs of endless driving elements being movable in synchronism so as to impart movement to packages along said predetermined path, and motive means including a driving motor, interconnected with linkage means and with a gear box having rotatable input and output shafts, said output shaft being connected with said linkage means, and means for securing said input shaft against rotation thereby to cause said linkage means to maintain synchronous movement of said pairs of endless driving elements so as to prevent undesired changes in the space relations of said flight bars.

According to a sixth embodiment of this invention there is provided a system including flight bars for advancing packages in sequence along a predetermined path each of said flight bars having a leading component and a trailing component, a first pair of spaced apart endless driving elements interconnected with each of said leading components and a second pair of spaced apart endless driving elements interconnected with each of said trailing components, said first and said second pairs of endless driving elements being movable in synchronism so as to impart movement to packages along said predetermined path, means for imparting controlled relative movement to said first and said second pairs of endless driving elements so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately succeeding flight bar thereby to render the system adaptable for advancing packages of different horizontal dimensions in the direction of movement of the flight bars along said predetermined path, and means for interconnecting said leading and trailing components with each other to limit relative movement therebetween within a predetermined range.

By this invention means for interrelating the leading and trailing components is provided so as to accommodate relative movement therebetween within a predetermined range.

By this means a packaging machine is easily converted for use with cartons whose horizontal dimensions in the direction of movement are different and such conversions may be made in a matter of a few minutes.





CLAIMS

1. A method of adjusting the spacing between an adjacent pair of transversal flight bars in a system of advancing packages sequentially along a predetermined path in which a leading component of at least one of said pair of flight bars is shifted relative to a trailing component thereof so as to alter the distance between the said pair of flight bars wherein the leading component and the trailing component are adjustably connected together at each of their ends.
2. A method according to claim 1 wherein said leading and trailing components are pivotally connected together whereby they are pivoted towards or away from one another to alter the distance between the flight bars.
3. A method according to claim 1 or claim 2 wherein the leading and trailing components remain substantially parallel to one another during said relative shifting.
4. A method according to any of claims 1 to 3 wherein a series of flight bars are adjusted simultaneously.
5. A flight bar assembly for use in advancing packages sequentially along a predetermined path in which at least one of a pair of adjacent flight bars in the assembly includes a leading component and a trailing component and wherein the leading and trailing components are adjustably connected to each other at each of their ends so that they can be shifted relative to one another to adjust the spacing between said pair of flight bars.
6. A flight bar assembly according to claim 5 wherein the leading and trailing components are pivotally connected for movement substantially parallel to one another.
7. A system including flight bar assembly according to claim 5 or claim 6 for advancing packages in sequence along a predetermined path, each of said flight bars having a leading component and a trailing component, a first endless driving element connected to each of said leading components to move said leading components along said predetermined path, and a second endless driving element connected to each of said trailing components to move said trailing components along said predetermined path, said first and second driving elements being movable in synchronism so as to impart movement to packages along said predetermined path, means for imparting controlled relative movement to said first and second driving elements so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately preceding flight bar thereby to render the system adaptable for advancing packages of different horizontal dimensions in the direction of movement of the flight bars along said predetermined path, and characterized by means for interconnecting said leading and trailing components with each other to limit relative movement therebetween within a predetermined range.

REPLACEMENT SHEET

22 DEC 1997



8. A system according to claim 7 wherein a plurality of end plates are pivotally connected with each of said flight bar leading components near each end thereof and a pin is secured to each of said trailing components near each end thereof and wherein each of said end plates includes a slot in which the adjacent pin is slidably disposed.
9. A system according to claim 8 wherein each end of each of said leading components is configured in the form of the correct metering angle for product entry into the space between adjacent flight bars.
10. A system according to claim 8 wherein said slot is disposed at an angle which results in the disposition of said end plate in such a position that an edge of said end plate forms the correct metering angle for product entry into the space between adjacent flight bars.
11. A flight bar unit for a packaging machine which unit comprises a leading flight bar component and a trailing flight bar component which components are interrelated so that they can be shifted relative to one another characterised in that the interrelation comprises linkage means formed to provide an end face across the space between said flight bar components at each end of the unit when the components are spaced apart, said end face being angled to facilitate an article grouping function by engagement with rows of incoming articles to be loaded and which are moved at an acute angle into the path of movement of the flight bar unit.
12. A flight bar unit according to claim 1 wherein when the components are closed, the linkage means is put into an inoperative position and wherein an angled end face of the leading flight bar component being angled to facilitate article grouping function by engagement with rows of incoming articles to be loaded which are moving at an acute angle into the path of movement of the flight bar unit.
13. A flight bar according to claim 1 or claim 2 wherein said linkage means is provided for altering the angle of the ends and/or end faces of the ends of the unit when the leading and trailing components are shifted relative to one another.
14. A flight bar unit according to claim 3 wherein said linkage means is pivoted at one of its ends to said leading flight bar component and includes slot adjacent other end in which a pin provided by the trailing flight bar components is slidably received to facilitate pivoting movement.
15. A system including flight bars for advancing packages in sequence along a predetermined path each of said flight bars having a leading component and a trailing component, a first pair of spaced apart endless driving elements interconnected with each of said leading components and a second pair of spaced apart endless driving elements interconnected with each of said trailing components, said first and said second pairs of endless driving elements being movable in synchronism so as to impart movement to

REPLACEMENT SHEET

22 DEC 1997



packages along said predetermined path, means for imparting controlled relative movement to said first and said second pairs of endless driving elements so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately succeeding flight bar thereby to render the system adaptable for advancing packages of different horizontal dimensions in the direction of movement of the flight bars along said predetermined path, and characterized by means for interrelating said leading and trailing components to accommodate relative movement therebetween within a predetermined range, an end plate pivotally connected with each of said flight bar leading components near each end thereof and a pin secured to each of said trailing components near each end thereof and wherein each of said end plates includes a slot in which the adjacent pin is slidably disposed.

16. A system according to claim 15 wherein means for causing the angle engagement to incoming products to change to insure constant speed of the moving items prior to engagement with the flight bars.

17. A system according to claim 15 or claim 16 wherein each end of each of said leading components is configured in the form of the correct metering angle for product entry into the space between adjacent flight bars.

18. A system according to any one of claims 15 to 17 wherein said slot is disposed at an angle which results in the disposition of said end plate in such a position that an edge of said end plate forms the correct metering angle for product entry into the space between adjacent flight bars.

19. A system including flight bars for advancing packages in sequence along a predetermined path each of said flight bars having a leading component and a trailing component, a first pair of spaced apart endless driving elements interconnected with each of said leading components and a second pair of spaced apart endless driving elements interconnected with each of said trailing components, said first and said second pairs of endless driving elements being movable in synchronism so as to impart movement to packages along said predetermined path, and motive means including a driving motor, interconnected with linkage means and with a gear box having rotatable input and output shafts, said output shaft being connected with said linkage means, and means for securing said input shaft against rotation thereby to cause said linkage means to maintain synchronous movement of said pairs of endless driving elements so as to prevent undesired changes in the space relations of said flight bars.

20. A system according to claim 19 wherein said means for securing said input shaft against rotation is rendered ineffective.

21. A system according to claim 20 wherein control means is effective to impart rotation to said input shaft of said gear box thereby to establish movement to parts of

REPLACEMENT SHEET

22 DEC 1997



said linkage which control the relative positions of said endless driving elements thereby to control the distance of a first flight bar component relative to a second flight bar component.

22. A system according to claim 21 wherein said control means includes crank means.


23. A system according to claim 22 wherein said crank means includes a manually operable crank.

24. A system according to any one of claims 19 to 23 wherein the housing of said gear box is rotatable with its output shaft while said input shaft is secured against movement.

25. A system according to claim 20 wherein rotation of said input shaft imparts movement to parts of said linkage which control the position of one pair of said endless driving elements relative to the other pair of driving elements.

26. A system according to claim 25 wherein the position of said one pair of endless elements relative to the other pair of endless elements may be controlled both during operation of the system or during down time.

27. A system including flight bars for advancing packages in sequence along a predetermined path each of said flight bars having a leading component and a trailing component, a first pair of spaced apart endless driving elements interconnected with each of said leading components and a second pair of spaced apart endless driving elements interconnected with each of said trailing components, said first and said second pairs of endless driving elements being movable in synchronism so as to impart movement to packages along said predetermined path, means for imparting controlled relative movement to said first and said second pairs of endless driving elements so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately succeeding flight bar thereby to render the system adaptable for advancing packages of different horizontal dimensions in the direction of movement of the flight bars along said predetermined path, and means for interconnecting said leading and trailing components with each other to limit relative movement therebetween within a predetermined range.



ADJUSTABLE FLIGHT BARS FOR A PACKAGING MACHINE AND METHOD OF ADJUSTMENT

ABSTRACT

A system of flight bars each flight bar having a leading component (10) and a trailing component (19), a first pair of endless drive chains (24, 25) interconnected with each leading component and a second pair of endless drive chains (26, 27) interconnected with each trailing component. Controlled relative movement is imparted to the first and second pair of drive chains so as to vary the distance between the trailing component of a flight bar and the leading component of an immediately adjacent flight bar thereby to render the system adaptable for use in conjunction with packages of different dimensions.

Fig. 3

