

METHODS OF GENERATING AND UTILIZING UTILITY GAS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 60/987,308, filed 12 November 2007.

FIELD OF THE INVENTION

[0002] This invention relates generally to methods of processing slip streams. More specifically, the invention relates to processes for treating gas dominated process slip streams for use as a utility gas.

BACKGROUND

[0003] This section is intended to introduce the reader to various aspects of art, which may be associated with exemplary embodiments of the present invention, which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with information to facilitate a better understanding of particular techniques of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not necessarily as admissions of prior art.

[0004] Most gas compressor applications or gas processing facilities today utilize some compressed or processed gas to supply seals, fuel systems and other auxiliary equipment within the process as a utility gas fluid. Most of these auxiliary systems or other uses of the gas being compressed often require the gas to be clean and dry including no liquid condensation during pressure regulation or pressure drop through the seals or auxiliary systems (dew point control). They also often require detoxification and corrosion protection by removing specific hazardous or corrosive gases and liquids like hydrogen sulfide (H₂S) or carbon dioxide (CO₂) and water.

[0005] Traditional methods to strip out these unwanted components require capital intensive and large complex equipment such as molecular sieves, distillation towers, glycol contactor and other traditional separation equipment. The volume of gas required for these utilities is often small relative to the overall gas being handled in the process and if these processes are not required for the entire gas stream the costs associated with this separation, dehydration, detoxification, corrosion control or component selection can be prohibitive to a project, especially in remote locations or locations where infrastructure does not yet exist. Alternative systems to pipe in fuel gas, produce inert gas, supply clean dry seal gas at sufficient pressure can also be very complex and costly.

[0006] Compressor shafts are typically sealed using dry gas seals (DGS) which utilize the principle of sealing between a stationary face against a rotating face by using a gas fluid film. This “seal gas” provides the lubrication and cooling properties needed by the seal for long and reliable operation. Seal gas must be free of particulates, free of liquids, and not have physical properties that cause condensation of the seal gas when expanded across the seal faces. A common cause of compressor failure or trip is a result of seals failing and the most predominant cause for seal failure is caused by contaminants in the process gas, both liquid and solid contaminants.

[0007] The source of seal gas for many compressor applications is the process gas being compressed. The pressure needed for seal gas is greater than the compressor suction pressure, but less than the compressor discharge pressure. Therefore many applications utilize discharge gas as the seal gas source when suitable. However, in some applications discharge stream components will condense across the seal faces even after filtering and heating.

[0008] In some situations such as high pressure sour gas service, the seal gas has been obtained from another utility source such as a fuel gas system. Such gas from the other utility gas source is then compressed and used as seal gas. Such gas is used in order to avoid the liquid contamination or liquid drop out encountered by using the process gas. This requires additional process and separation units to generate the fuel gas and a separate seal gas booster compressor (e.g. a reciprocating compressor), which can itself be a source of oil and particulate contamination. Usually a reciprocating compressor is used for this service due to the high compression ratios and low flows. Reciprocating compressors of this type are usually lubricated with cylinder oil that has some miscibility with the gas, especially at high pressures. Thus it can not be filtered out at high pressure but condenses or “drops out” of the gas when the pressure is dropped through the seals or at pressure regulators that control the pressure to the seals. This cylinder oil “carry-over” into the seal gas may damage and cause premature failure of standard DGS’s.

[0009] It is also common with high pressure hydrogen compressors in refineries that process gases can have liquids condense out of the gas with the pressure drop across the dry seal faces. An alternative gas sometimes used is hydrogen from a hydrogen make up line from a reciprocating compressor which may also contaminate the gas with lubrication oil.

[0010] Another example of a use of the gas being processed or compressed is fuel gas for gas turbines and steam boilers. Modern gas combustors, and low emissions combustors

in particular require a substantially constant composition in order to maintain an acceptable operating condition. Additionally, if liquids are entrained or condense (drop) out in these fuel gas systems during pressure drops (e.g. across a fuel control valve) or cooling in piping, problems can result within the turbine or boiler combustion chambers including unstable
5 operation, inefficient operation, reduced reliability, and/or increased emissions of environmentally regulated species, including, for example, nitrogen oxides (NO_x), carbon monoxide (CO) and/or sulfur (e.g. sulfur oxides (SO_x)) emissions. In addition toxic or corrosive components in these gases can be a safety issue as well as detrimental to the equipment and the environment. Detoxification and corrosion control are described in more
10 detail below.

[0011] The removal of H₂S, CO₂, water and other toxic or corrosive components (such as sulfur containing materials) from a gas stream in order to make it less corrosive or toxic are common challenges in trying to utilize well stream gas or saturated gas as a utility fluid. Removal of these types of components can make seal gas systems and fuel gas systems
15 safer, more reliable and more environmentally friendly or make the utility systems simpler and less costly. Gas processing and drying equipment to condition the gas to remove these toxic or corrosive components can be very costly and complex and are often not feasible for the volumes required for fuel gas or for gas seals in a given process or operation.

[0012] Nitrogen or inert gas systems are often used as a utility in gas processing and
20 compression equipment. For example a blanket or inert gas purge is used in seals to ensure toxic or hydrocarbon gasses do not leak to the environment, to prevent an explosive mixture, to sweep out left over hydrocarbons before maintenance, or as a separation barrier between different fluids such as process gas and the lubrication oil in gas seals. Nitrogen systems designed to separate the nitrogen from air are commonly used to provide this inert utility
25 fluid. In some cases the nitrogen is separated out of the process gas if the gas has a high percentage of nitrogen, making it less valuable as a fuel and thus justifying the added high processing cost. However, for small volumes or where the percentage of nitrogen in the gas is small, these types of systems are not justifiable.

[0013] New methods of treating process gas for use as a utility gas are needed.

SUMMARY

[0014] In one embodiment, a method of treating a gaseous feed stream is provided. The method includes the steps of producing a gaseous feed stream; dividing at least a portion of the gaseous feed stream to form a gaseous slip stream; separating the gaseous slip stream

using a selective component removal system having at least one swing adsorption process unit to form a utility stream for use in a utility component; feeding the utility stream into the utility component, wherein the utility stream is compatible with the utility component; and utilizing the utility stream in the utility component. The gaseous feed stream may be a high pressure process stream, a hydrocarbon containing stream, or a compressor discharge stream. The utility component may be a compressor, a dry-seal compressor, a compressor string, a turbo-expander compressor, a turbo-expander generator, a pump, a fired steam boiler, a fired process heater, a gas engine, a hermetically sealed direct-drive electric motor, turbomachinery equipped with magnetic bearings, gas-operated instruments and controls, or a gas turbine. The swing adsorption process unit may be a pressure swing unit, a thermal swing unit, a partial pressure swing or displacement purge adsorption unit, a rapid cycle or compact unit.

[0015] In another embodiment, a method of treating a nitrogen-rich gaseous stream is provided. The method includes producing a nitrogen-rich gaseous stream; separating at least a portion of the nitrogen-rich gaseous stream using a selective component removal system having at least one swing adsorption process unit to form a utility stream for use in a utility component; feeding the utility stream into the utility component, wherein the utility stream is compatible with the utility component; and utilizing the utility stream in the utility component.

[0016] In a third embodiment of the present invention, a system for treating a gaseous feed stream is provided. The system includes a tubular containing a gaseous feed stream operatively connected to a selective component removal system including at least one swing adsorption process unit, wherein the selective component removal system is utilized to separate at least a portion of the gaseous feed stream to form a utility stream; and a utility component configured to receive and utilize the utility stream, wherein the utility stream is compatible with the utility component.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The foregoing and other advantages of the present technique may become apparent upon reading the following detailed description and upon reference to the drawings in which:

[0018] FIG. 1 is an exemplary flow chart of a process of managing a process plant in accordance with certain aspects of the present invention;

[0019] FIGs. 2A-2B are exemplary process layouts utilizing a compressor with the process of FIG. 1;

[0020] FIG. 3 is an exemplary schematic of a process layout of the present invention including a high pressure vessel surrounding the swing adsorption process unit of FIG. 2;

5 [0021] FIG. 4 is an exemplary process layout of the selective component removal system (SCRS) of FIG. 2 utilizing thermal pressure swing adsorption process (thermal PSA) rather than pressure swing adsorption process;

[0022] FIG. 5 is another exemplary process layout of a selective component removal system (SCRS) with a combined pressure-swing/rapid cycle pressure swing and thermal-
10 swing adsorption process unit;

[0023] FIG. 6 is an exemplary illustration of a process layout of a selective component removal system (SCRS) for preparing a utility stream (e.g. seal gas) for a centrifugal dry seal compressor;

[0024] FIG. 7 is an exemplary illustration of a conventional dry gas seal system in a
15 compressor;

[0025] FIG. 8 is a graph depicting the phase envelope associated with an exemplary gaseous slip stream;

[0026] FIG. 9 is a graphic illustration depicting the phase envelope associated with an exemplary gaseous slip stream after treatment to form a treated gaseous slip stream; and

20 [0027] FIG. 10 is an exemplary illustration of a process layout of a selective component removal system (SCRS) for preparing a nitrogen rich utility stream (e.g. seal gas) for a high pressure centrifugal dry seal compressor.

DETAILED DESCRIPTION

[0028] In the following detailed description and example, the invention will be
25 described in connection with its preferred embodiments. However, to the extent that the following description is specific to a particular embodiment or a particular use of the invention, this is intended to be illustrative only. Accordingly, the invention is not limited to the specific embodiments described below, but rather, the invention includes all alternatives, modifications, and equivalents falling within the true scope of the appended claims.

30 [0029] The term “gaseous feed stream” as used herein refers to any gaseous stream or gas dominant stream originating from a man-made process or a terrestrial gaseous source (e.g. a hydrocarbon reservoir, a natural gas production stream, an associated gas stream, or a

syngas feed stream), but does not include atmospheric air or streams of gas primarily derived from the atmosphere.

[0030] The term “slip stream” or “gaseous slip stream” means a volumetric portion of a gaseous feed stream and is generally less than half of the total volume of gas being handled.

5 A “slip stream” is a volumetric fraction of a primary gaseous stream such as a gaseous feed stream and has generally the same composition as the primary gaseous stream.

[0031] The term “utility stream” (e.g. “utilities”) means (unless otherwise specified) anything consumed in a facility or process unit including any fluid (gas or liquid) required in order to operate the overall compressor or gas processing equipment of the facility or process
10 unit. Some common examples of utility streams can include fuel gas, seal gas, instrument and control gas, nitrogen or inert gas, blanket gas, hydraulic fluids, pneumatic systems, water (including non-potable water), diesel or gasoline to run turbines or boilers or any other fluid required to run equipment for a given process (e.g. compression equipment).

[0032] The term “swing adsorption process” includes processes such as pressure
15 swing adsorption (PSA), thermal swing adsorption (TSA), and partial pressure swing or displacement purge adsorption (PPSA), including combinations of these processes. These swing adsorption processes can be conducted with rapid cycles, in which case they are referred to as rapid cycle thermal swing adsorption (RCTSA), rapid cycle pressure swing adsorption (RCPSA), and rapid cycle partial pressure swing or displacement purge adsorption
20 (RCPPSA). The term swing adsorption also includes these rapid cycle processes. Some examples of swing adsorption processes and their application to natural gas separations are provided in U.S. Serial No. 60/930,827, U.S. Serial No. 60/930,826, U.S. Serial No. 60/931,000, and U.S. Serial No. 60/930,993, and U.S. Serial No. 60/930,998, which are hereby incorporated by reference.

25 **[0033]** Pressure swing adsorption (PSA) processes operate on the principle that gases under pressure tend to be adsorbed within the pore structure of microporous adsorbent materials or within the free volume of polymeric materials. The higher the pressure, the more gas is adsorbed. When the pressure is reduced, the gas is released, or desorbed. PSA processes can be used to separate gases in a mixture because different gases tend to fill the
30 micropore or free volume of the adsorbent to different extents. If a gas mixture, such as natural gas, for example, is passed under pressure through a vessel containing polymeric or microporous adsorbent that fills with more nitrogen than it does methane, part or all of the nitrogen will stay in the sorbent bed, and the gas coming out of the vessel will be enriched in

methane. When the bed reaches the end of its capacity to adsorb nitrogen, it can be regenerated by reducing the pressure, thereby releasing the adsorbed nitrogen. It is then ready for another cycle.

[0034] Temperature swing adsorption (TSA) processes operate on the same principle as PSA processes. When the temperature of the adsorbent is increased, the gas is released, or desorbed. By cyclically swinging the temperature of adsorbent beds, TSA processes can be used to separate gases from a mixture when used with an adsorbent that selectively picks up one or more of the components in the gas mixture.

[0035] Rapid cycle pressure swing adsorption (RCPSA) can be constructed with a rotary valving system to conduct the gas flow through a rotary adsorber module that contains a number of separate adsorbent bed compartments or "tubes," each of which is successively cycled through the sorption and desorption steps as the rotary module completes the cycle of operations. The rotary sorber module is normally comprised of multiple tubes held between two seal plates on either end of the rotary sorber module wherein the seal plates are in contact with a stator comprised of separate manifolds wherein the inlet gas is conducted to the RCPSA tubes and the processed purified product gas and the tail retentate gas exiting the RCPSA tubes are conducted away from the rotary sorber module. By suitable arrangement of the seal plates and manifolds, a number of individual compartments or tubes may pass through the characteristic steps of the complete cycle at any given time. In contrast, with conventional PSA, the flow and pressure variations, required for the RCPSA sorption/desorption cycle, changes in a number of separate increments on the order of seconds per cycle, which smoothes out the pressure and flow rate pulsations encountered by the compression and valving machinery. In this form, the RCPSA module includes valving elements angularly spaced around the circular path taken by the rotating sorption module so that each compartment is successively passed to a gas flow path in the appropriate direction and pressure to achieve one of the incremental pressure/flow direction steps in the complete RCPSA cycle.

[0036] To prepare a gaseous feed stream for use in utilities or utility components, classes of separation applications that may be performed include dew point control, sweetening/detoxification, corrosion protection/control, dehydration, heating value control, conditioning, and purification. A few examples of utilities that encompass one or more classes of applications are generation of fuel gas, seal gas, non-potable water, blanket gas, instrument and control gas, refrigerant, inert gas, and hydrocarbon recovery.

[0037] Embodiments of the present invention selectively remove individual or groups of compounds from a gaseous slip stream through selective swing adsorption processes to produce utility streams that each contain one or more of the components present in the gaseous slip stream. The utility streams can be used for any purpose where a specific component or components of a stream are needed or need to be removed.

[0038] Whereas a gas processing facility typically will contain multiple large, traditional bulk separation methods that can supply the various gaseous utility streams required to support the facility, embodiments of the present invention may provide utility gas generation wherever tie-in to an existing gas processing plant unit is not practical or there does not exist the infrastructure to tie into such a plant (i.e., no gas processing plant). Exemplary applications include remote oil and gas production fields in remote geographic locations such as in the desert, in the arctic, subsea, and offshore.

[0039] In some exemplary embodiments of the present invention the gaseous feed stream being processed using the disclosed systems and methods is at a lower pressure (e.g. less than 100 bar), conventional separation processes can also be used to condition the feed gas to ensure that the molecular composition of the gas stream will not condense at the temperatures and pressure conditions found in the seals of a centrifugal dry seal compressor. It is possible to use conventional separation processes such as absorption, phase separation, and distillation to condition the gas stream because the pressure is less than 100 bar. Conventional separation processes (e.g. membrane separation, amines, etc.) are employed at pressures well below 100 bar. At pressures near 100 bar the application of conventional separation processes can be quite challenging (and in some instances impossible). When conventional separation processes are used to tailor the composition of a sour or sweet natural gas stream so that it will not enter a two phase region in the temperature and pressure conditions across the seals of a dry seal compressor, heavy hydrocarbons with carbon numbers greater than 4 are usually removed from the stream. In many applications it can be advantageous to remove more than 50% of the C₄+ hydrocarbons from the stream. More preferably, greater than 90% of the C₄+ hydrocarbons are removed from the stream.

[0040] Turning now to the drawings, and referring initially to FIG. 1, an exemplary flow chart of a process of managing a process plant in accordance with certain aspects of the present invention is provided. The process **100** begins at **102**. A gaseous feed stream is produced at **104**. The gaseous feed stream may be a compressor discharge stream, a process gas stream, or other similar stream, but not an atmospheric gaseous stream such as air.

Preferably, the gaseous feed stream is at a pressure above the critical point of the stream (note that this presents additional challenges with conventional gas separation techniques). As understood in the art, critical point refers to a pressure-temperature point above which liquid cannot exist as a unique separate phase and the system is often referred to as a dense fluid or dense phase to distinguish it from normal vapor or liquid. The gaseous feed stream is divided **106** to form a gaseous slip stream, which is then separated **108** using a selective component removal system (SCRS) having at least one swing adsorption process unit to form a utility stream. The utility stream is then fed into a utility component **110** and utilized therein **112**. The utility stream is compatible with the utility component and may undergo additional treatment or conditioning. The process ends at **114**.

[0041] The utility component **110** is any device that utilizes a dry gas stream to operate and includes at least one of a compressor, a dry seal compressor, a compressor string, a turbo-expander compressor, a turbo-expander generator, a pump, a fired steam boiler, a fired process heater, a gas engine, a hermetically sealed direct-drive electric motor, turbomachinery equipped with magnetic bearings, gas-operated instruments and controls, or a gas turbine. The utility stream is utilized in the utility component **110** in whatever manner is most useful, but may be used, for example, as a gas for a dry gas seal in the utility component.

[0042] In some embodiments of the disclosure, the gaseous feed stream may include at least one hydrocarbon component and may be at a high pressure such as from at least about 50 bar to about 600 bar, or from about 100 bar to about 500 bar, or from about 200 bar to about 320 bar. When the gaseous feed stream contains natural gas or associated gas, a product stream may be produced. Such a product stream is at least a purified gas stream that is transferred to market by pipeline, or a liquefied natural gas, or natural gas liquids, or a gas stream that is reinjected into the subsurface in locations such as the producing field or an underground aquifer, or a combination of these different products.

[0043] The gaseous slip stream may be less than fifty percent of the volume of the gaseous feed stream and will be preferably less than about ten percent of the volume of the gaseous feed stream. As such, the slip stream will have a molar flow rate less than half that of a gaseous hydrocarbon containing feed stream. The slip stream can be generated from the gaseous hydrocarbon containing feed stream with a flow splitter or equivalent device that divides the gas stream being processed into a fraction that will be processed to provide a utility gas stream and a fraction that will be processed or used as a product stream.

[0044] Additionally, in a preferred form of this embodiment the swing adsorption process unit would be operated to produce the utility stream as a seal gas stream for a dry seal compressor. One important application of dry seal compressors is to compress sour gas streams so that they can be reinjected into the producing formation or into another underground formation. For these applications the compressor discharge pressure must exceed the pressure in the underground formation. Pressures in underground formations are usually in excess of 100 bar and often in excess of 250 bar. In these applications it is preferable to operate the swing adsorption process unit operated with an inlet (slip stream) in a range from at least about 100 bar to at least about 500 bar and more preferably in a range from 200 to 320 bar, which is dependent on the compressor suction or sealing pressure. These pressures are in excess of those that have been used in conventional swing adsorption units.

[0045] FIGs. 2A-2B are exemplary process layouts utilizing a compressor with the process of FIG. 1. As such, FIGs. 2A-2B may be best understood with reference to FIG. 1. As shown in FIG. 2A, the process layout **200** includes a compressor **202**, a process stream **204** feeding the compressor **202**, a compressor discharge stream **206** from the compressor **202**, a slip stream **207** divided from the discharge stream **206**, and a rejection stream **222** that may be combined with process stream **204**. The streams **204** and **206** may each be considered a "gaseous feed stream." The process further includes a selective component removal system (SCRS) **201** comprising filters **208A** and **208B**, control valves or flow/pressure control devices **216A** and **216B**, a swing adsorption process unit **210**, and/or an expander **214**. The swing adsorption process unit **210** produces at least a utility stream **212A** and secondary streams **212B-212X**, one of which may partially be a disposal stream **220**. The utility stream **212A** may be at least partially expanded in the expander **214** and filtered in the filter **208B** to form a treated utility stream **218**. The treated utility stream **218** is the result of the SCRS **201** and is fed into the seals of the compressor **202** for utilization as a seal gas or other utility.

[0046] The swing adsorption process unit **210** may be cycled by pressure, temperature or partial pressure purge displacement, and may be a rapid-cycle unit. In one embodiment, the slip stream **207** from the compressor discharge stream **206** may be directed through the filter **208A** and control valve **216A** into the adsorption unit **210**. The filter **208A** may remove any extraneous particles that could contaminate and deactivate (e.g. plug) the adsorbent in the adsorption unit **210**. The control valves **216A-216B** may regulate the flow

of fluids fed into the SCRS **201**. The various streams may be connected by tubulars, which may be constructed from corrosion resistant alloys, carbon steel, or other materials, but preferably the tubulars are capable of handling fluids at high pressure, such as above about 100 bar.

5 [0047] The swing adsorption process unit **210** may produce individual streams **212A**, **212B-212X** containing the separated components from the slip stream **207**, where the reject stream **212X** contains the waste compounds for disposal **220**. In one embodiment, stream **212X** could be recycled back into the compressor **202** suction or into the process stream **204** down stream of a pressure let down for disposal.

10 [0048] The process stream **204** may operate at anywhere from at least about 10 bar to at least about 600 bar. In one exemplary embodiment, the process stream **204** may be a production stream from a subterranean reservoir containing light and heavy hydrocarbons (C_1 to C_{10}), mercaptans, sulfur dioxide, hydrogen sulfide, carbon dioxide, carbonyl sulfide, steam, nitrogen, and other components and any combination thereof. Alternatively, the
15 process stream **204** may be a compressed stream from a utility component such as a compressor **202**, which may be pressurized to 300 bar, 400 bar, 500 bar, 600 bar, or higher and may include components similar to the production stream above, but may additionally include lube oil or similar components picked up in the compression process or other process.

[0049] Referring now to FIG. 2B, the SCRS **201** is shown with reference to an
20 exemplary sour gas process **250**. The compressors **202A**, **202B**, and **202C** may be arranged in a compressor string and generate a single high pressure discharge **256** to an injection well manifold **258**. From the manifold **258**, a stream may be injected through injection wells **260**. A portion of the stream from the manifold **258** may be sent to the SCRS **201** via a filter **264** as a slip stream **207**. From the SCRS **201**, the stream may go to an accumulator **251**, then the
25 treated utility stream **218** may be fed into a seal gas control unit or panel **252**. The accumulator **251** may be a holding vessel to meet certain variational flow requirements and surge capacity issues during operation. The seal gas control panel **252** may then direct the flow of low pressure seal gas (e.g. utility stream) **254A** to a low pressure compressor **202A**, direct medium pressure seal gas **254B** to a medium pressure compressor **202B**, and direct high
30 pressure seal gas **254C** to a high pressure compressor **202C**. Additionally, the SCRS **201** may produce a rejection stream **222** that may be fed back to process stream **204**. In such an arrangement, the compressors **202A**, **202B**, and **202C** may be high pressure sour gas injection compressors, the discharge **256** may be a sour gas injection discharge. A person of

ordinary skill in the art recognizes that the SCRS **201** may be utilized in a variety of applications beyond acid gas/sour gas injection, some of which are disclosed herein.

[0050] FIG. 3 is an exemplary schematic of a process layout of the present invention including a secondary pressure vessel **302** surrounding the swing adsorption process unit **210**.

5 The process may be similar to the process of FIGs. 1 and 2A-2B, but with the addition of the secondary pressure vessel **302**. As such FIG. 3 may be best understood with reference to FIGs. 1 and 2A-2B. The swing adsorption process unit **210** can be placed in a pressure vessel **302** that can be pressurized in order to reduce the overall differential pressure from the adsorption unit **210** to its surrounding environment in order to reduce the differential pressure
10 on the seals in the adsorption unit **210**. Box **304** may include a filter **208A**, expander **214**, valve **216A**, or some combination of such gas handling and treating equipment.

[0051] The swing adsorption process unit **210** utilizes an adsorbent bed **310** contained within a housing **312**. The bed **310** is composed of at least a beaded adsorbent or structured adsorbent. If a heating or cooling fluid is used in the swing adsorption process unit the bed
15 **310** may also contain heating or cooling passages or tubes (not shown), which may be attached to the housing **312** in a manner that prevents contacting the adsorbent with heating or cooling fluids. Specifically, heating may be by electric tracing and cooling may be by a cooling jacket. Valve or valves **316A** may control the periodic flow of feed to the swing adsorption process unit **210** (which is derived from the slip stream **207**) and products (such as
20 the utility stream **212A** and the secondary, reject or other product streams **212B-212X**) into and out of the bed **310**. Other valves (not shown) may also be provided to control the periodic flow of heating and cooling fluids into and out of the bed **310**.

[0052] The choice of valve technologies depends in part on the pressure of the inlet stream, the composition of the inlet stream, the temperature of the inlet stream and the
25 temperature of any required heating or cooling fluids. In all cases the valves **216A**, **316A**, **316B**, **316C** have a sealing surface or packing that prevents leakage of components out of the valve body. The amount of leakage out of the valve body depends on the differential pressure between the atmosphere surrounding the valve and the stream or streams controlled by the valve. When the feed stream is fed at high pressures (e.g. greater than 70 bar) the
30 leakage rate from the valves can be an important safety and operational concern. For example, when the adsorption unit **210** processes H₂S containing sour or acid gas even small amounts of leakage can be a significant safety and operational concern.

[0053] In one exemplary embodiment of the present invention, valve or valve sets **316A** are enclosed in individual housings pressurized to a pressure greater than 10% of the slip stream **207** and in a more preferred embodiment the housings are pressurized to a pressure greater than 90% of the slip stream **207**. An alternative exemplary embodiment of the present invention comprises a secondary pressure vessel **302** around the entire swing adsorption process unit **210** (including valves **316**). In one exemplary embodiment the secondary pressure vessel **302** is pressurized to a pressure greater than 10% of the slip stream **207** and in another exemplary embodiment the secondary pressure vessel **302** is pressurized to a pressure greater than 90% of the slip stream **207**.

[0054] FIG. 4 is an exemplary process layout of FIG. 2A utilizing thermal pressure swing adsorption (thermal PSA) rather than pressure swing adsorption. As such, FIG. 4 may be best understood with reference to FIGs. 1-2A. The process layout **400** utilizing thermal PSA includes a compressor **202**, a process stream **204** feeding the compressor **202**, a compressor discharge stream **206** from the compressor **202**, and a slip stream **207** divided from the discharge stream **206**. The process layout further includes a selective component removal system (SCRS) **401** comprising filters **208A** and **208B**, control valves **216A** and **216B**, a swing adsorption process unit **210**, outlet streams **212A-212X** from the adsorption unit **210**, and at least one heat source **404** and heat sinks (not shown) to provide the heating and cooling necessary to effect the separation. A fluid stream **402** may be heated at heat source **404**, then recycled or sent to waste stream **220** through remainder stream **406**. Instead of relying solely on pressure energy, thermal energy would also be used to effect the separation. The thermal-swing adsorption process unit **210** can be used in combination with a compressor **202** or without a compressor as shown below in FIG. 5. The waste stream **220** may be returned to the compressor suction stream **204** via line **222** or simply discarded.

[0055] FIG. 5 is another exemplary process layout selective component removal system (SCRS) with a combined pressure-swing/rapid cycle pressure swing and thermal-swing adsorption unit. The process **500** includes a process stream **502**, a slip stream **507** off of the process stream **502**, and an SCRS **501**. The SCRS **501** includes a heat exchanger (heater or cooler) **506**, a filter **508**, and a control valve **504A** in combination with an adsorption unit **510**, which may be a combined pressure-swing/rapid cycle pressure swing and thermal-swing adsorption unit. There may also be a heater **514** and lines associated therewith **515**, **517**. After treatment in the adsorption unit **510**, there will be at least a first

utility stream **512A** and optionally additional utility streams **512B-512X**, which may be sent to a waste stream **520**, or recycled through stream **522** to recombine with process stream **502**.

[0056] The processing system **500** may utilize a high pressure process stream **502** with pressure let down to facilitate disposal of waste product **522** back into the process **502**.

5 Some portion of the unused waste or product stream **522** may be returned either to suction of a compressor **202** similar to that shown in FIG. 2A for pressure-swing or after a pressure drop in the process in order to facilitate the waste flowing back into the process as shown in FIG. 5.

[0057] FIG. 6 is an exemplary illustration of a process layout of a selective component removal system (SCRS) for preparing a utility stream (e.g. seal gas) for a centrifugal dry seal compressor. As such, FIG. 6 may be best understood with reference to FIG. 2A. The process layout **600** may include a centrifugal dry seal compressor **602** which boosts the pressure of a process stream **604** yielding a compressed stream **606**. Treated utility streams (e.g. seal gas streams) **618A** and **618B** are generated from stream **608** by a selective component removal system (SCRS) **601**. Stream **608** may be a slip stream taken from process stream **604** or from another process such as fuel gas. A reciprocating compressor **610** may be used to compress stream **608** to a pressure above or slightly above the highest pressure needed for seal gas streams **618A** and **618B**. To remove oil vapor and any other molecular species that might condense in the seal of compressor **602**, stream **612** may be treated in an SCRS **601** having a swing adsorption process unit **627**. To prepare stream **612** for processing by the swing adsorption process unit **627** it is optionally fed to unit **614** that conditions the gas to form conditioned stream **620**. The conditioned stream **620** may be fed to the swing adsorption process unit **627** having a valve or a set of valves **628** which may control (e.g. pulse) the rate of the conditioned feed stream **620** into the adsorption bed **625**. An exit valve or a set of exit valves **636** may periodically open and close to allow a utility stream **640** to leave the swing adsorption unit **627**. The utility stream **640** may then be fed to safety and unit isolation devices **642** such as unit isolation valves, flow checks, or pressure relief valves may optionally be provided to improve operability. An accumulator vessel **644** may also optionally be provided to further reduce flow or pressure fluctuations. Optionally, the accumulator can include a heat exchanger (not shown). Resulting stream **646** is then the treated utility stream (seal gas) produced by the selective component removal system, which may be split into streams **618A** and **618B** for use in the dry gas seals of the compressor **602**. Additionally, a secondary stream **638** may enter the swing adsorption unit

627 via a secondary inlet valve or a set of inlet valves 630, then exit the swing adsorption unit 627 via a secondary exit valve or valves 624 that may periodically open and close to allow the reject (e.g. secondary product) stream or set of streams 626 to leave the swing adsorption unit 627.

5 [0058] In one exemplary embodiment of the process 600, the swing adsorption unit 627 uses a thermal swing adsorption process. In this case, a set of valves 634 and 622 may be provided to pulse the flow of heating or cooling fluids that enter and leave the swing adsorption unit 627 through streams 616 and 632. Electrical heating or jacket cooling (not shown) may also be used to provide the temperature swings. In another exemplary
10 embodiment, the swing adsorption unit 627 may use a partial pressure purge displacement process. In this case a valve or set of valves 630 is provided to pulse the flow of the purge displacement stream 638 into the adsorption bed 625. The adsorption bed 625 is contained within a pressure vessel 629. Optionally, this vessel 629 and the associated valving is contained within a secondary pressure vessel 639. This secondary pressure vessel 639 is
15 designed to mitigate the significance of leaks through seals in the valves 628, 636, 634, 630, 624, and 622. This can be especially important when rotary valves are used. When rotary valves are used, valves 624, 628, and 622 can all be incorporated into a single rotary valve body (e.g. they do not have to be separate valve bodies). Similarly, any optional valves used (636, 630, and 634) can be incorporated with them into a single rotary valve body. To
20 provide a more continuous flow in utility stream 640, several swing adsorption units 627 can be employed. If several swing adsorption units are employed, the several resulting utility streams 640 may be merged.

[0059] In some exemplary embodiments of the process 600, the process stream 604 may be a sour or acid gas stream being compressed for injection into an underground
25 reservoir and may have a pressure in a range from 10-100 bar. The compressed stream 606 may have a pressure in a range from 100-800 bar with the ratio of pressures between stream 606 and 604 being greater than 2:1. In a preferred embodiment the pressure of stream 606 is greater than 250 bar. The centrifugal dry seal compressor 602 may have several compression stages. As such, the pressure in stream 608 is less than 100 bar. In the case where the
30 process stream 604 is sour gas, a slip stream taken from it or the stream used to form it can be treated using conventional absorption, phase separation, and distillation processes to remove water and reduce the amount of H₂S flowing into stream 608. It is also possible to treat the gas flowing in to stream 608 with a molecular sieve bed to remove water. Conventional

separation processes can also be used to condition the gas being fed to stream **608** to ensure that the molecular composition of gas stream **608** will not condense at the temperatures and pressure conditions found in the seals of the centrifugal dry seal compressor **602**. It is possible to use conventional separation processes such as absorption, phase separation, and distillation to condition the gas for stream **608** because the pressure is less than 100 bar. Conventional separation processes are employed at pressures well below 100 bar. At pressures near 100 bar the application of conventional separation processes can be quite challenging (and in some instances impossible). When conventional separation processes are used to tailor the composition of a sour or sweet natural gas stream so that it will not enter a two phase region in the temperature and pressure conditions across the seals of compressor **602**, heavy hydrocarbons with carbon numbers greater than 4 are usually removed from the stream. In many applications it can be advantageous to remove more than 50% of the C₄+ hydrocarbons from the stream that is used to form stream **608**. More preferably, greater than 90% of the C₄+ hydrocarbons are removed from the stream used to form stream **608**.

[0060] The cylinder of the reciprocating compressor **610** may be lubricated with oil that may be carried as a mist or vapor out of the compressor. The lubricating oil can contain additives which enhance its performance and many of these molecules can also be entrained as a vapor or mist in the compressed gas stream **612**. The oil vapor, oil mist, or components of the lubricating oil coming out of the reciprocating compressor **610** can condense in the seals of the dry seal compressor **602**. This becomes a significant problem when the pressure of the compressed stream **612** is greater than 100 bar. As such stream **612** is unsuitable for use as a utility stream (seal gas) for the dry seal compressor **602** when the required seal gas pressures are in excess of 100 bar. Conditioning in optional unit **614** may involve changing the temperature of the stream by heat exchange or can involve filtering particles or oil mist coming from the reciprocating compressor **610**. The SCRS **627** can be designed to adsorb and remove the oil in the dense phase gas where filtration is insufficient.

[0061] FIG. 7 is an exemplary illustration of a conventional dry gas seal system in a compressor **202**. The compressor **202** may be part of the process system **200**, **250**, **300**, **400**, or **600**. Hence, FIG. 7 may be best understood with reference to FIGs. 2A, 2B, 3, 4, and 6. The system **700** includes a process side **702**, a discharge (atmospheric) side **704**, and a high pressure rotating equipment portion **706**. Treated utility gas (e.g. dry seal gas, which may be treated gas **218**, **618A**, or **618B**) enters the system **700** at **708** and exits at **710** and **712**. The gas at **708** is at a sufficiently high pressure to operate the dry gas seal **722**. The exit gas **710**

should be at a sufficiently high pressure to resist pressure from the process side **702** and exit between the labyrinth seal **720** and the rotating equipment **706**. The exit gas **712** is at approximately flare or atmospheric pressure. Gas stream **714** is also flue (e.g. vented to atmosphere) or flare gas and stream **716** is separation gas flow (generally nitrogen or air).

5 **[0062]** In one exemplary embodiment, the invention is used to address the desire to produce a non-condensing seal gas (e.g. utility gas) **708** for a high-pressure centrifugal compressor injecting into a reservoir gas containing any or all of the following: hydrocarbons from C₁ (methane) through C₁₀+ (decanes+), water, sour gas compounds (i.e., H₂S, CO₂, and other sulfur-containing compounds), and inerts (nitrogen, helium). In this
10 service, a form of dew point control, the invention would remove compounds that would otherwise condense as the process gas is expanded across the compressor dry gas seal **722**.

[0063] A slip stream from the discharge would be directed through a particle/liquid removal filter and then through the SCRS to selectively remove the condensable compounds. The treated stream would then be let down in pressure either with valve(s) or expander(s) to
15 the desired seal gas pressure. An expander may also be used in place of any of the aforementioned pressure let down valves or devices to reduce the stream's pressure to the desired pressure while recovering useful work. The reject streams containing waste products and other streams (hydrocarbons, Nitrogen etc.) can then be dealt with on the basis of their utility. Waste streams such as unsaleable CO₂ and H₂S could be recycled back to the
20 compressor suction or other appropriate stream for disposal. Economically-valuable streams (i.e., hydrocarbons) can be recovered and sold or used for other utilities such as fuel gas or separation gas **716** etc.

EXAMPLES

[0064] In one example, compressed gas with the following composition and state
25 downstream of a compressor is being reinjected:

	Mole Fractions
Methane	0.5933
Ethane	0.1084
Propane	0.0579
i-Butane	0.0081
n-Butane	0.0157
i-Pentane	0.0041
n-Pentane	0.0037
n-Hexane	0.0019
n-Heptane	0.0007
Nitrogen	0.0108
H ₂ O	0.0000
H ₂ S	0.1622
CO ₂	0.0324
COS	0.0001
M-Mercaptan	0.0002

[0065] FIG. 8 is a graph depicting the phase envelope associated with the exemplary gaseous slip stream listed above taken directly from the compressor discharge and into the dry gas seals. In the graph **800**, pressure **802** is in bar, enthalpy **804** is in kilocalories per kilogram moles (kcal/kgmol), the bubble point of the process fluid **806** is shown with diamonds, the dew point of the process fluid **808** is shown with squares, and the valve expansion point **810** is shown by a vertical line at about negative 19,900 kcal/kgmol. As shown, the gas will cool as it expands and drops in pressure. At about 77 bar the valve expansion point **810** crosses the dew point **808** resulting in the slip stream gas entering the 2-phase region as liquids condense. Such a result is highly problematic and often causes early failure of dry gas seals.

[0066] FIG. 9 is a graphic illustration depicting the phase envelope associated with the exemplary gaseous slip stream listed above after separation **106** to form a treated utility stream via any one of the processes or systems **100**, **200**, **300**, **400**, and **600**. In the graph **900**, pressure **902** is in bar, enthalpy **904** is in kilocalories per kilogram moles (kcal/kgmol), the bubble point of the process fluid **906** is shown with diamonds, the dew point of the process fluid **908** is shown with squares, and the valve expansion point **910** is shown by a vertical line at about negative 19,350 kcal/kgmol. As shown, the phase envelope **906** and **908** has moved to the left resulting in the utility gas stream remaining in the gaseous state across the seal. Removal of the butanes and heavier hydrocarbons caused the shift. Hence, the utility gas (e.g. seal gas) can be used as the seal gas without danger of liquids condensing. The utility gas stream may be any one of utility gas stream **218**, **512A**, **618A** and **618B**.

[0067] FIG. 10 is an exemplary illustration of a process layout of a selective component removal system (SCRS) for preparing a nitrogen rich utility stream (e.g. seal gas) for a high pressure centrifugal dry seal compressor. As such, FIG. 10 may be best understood with reference to FIG. 2A. The process layout **1000** may include a high pressure centrifugal dry seal compressor **1002** which boosts the pressure of a process stream **1004** yielding a compressed stream **1006**. Utility (e.g. seal gas) streams **1018A** and **1018B** are produced from nitrogen-rich gaseous stream **1008** using an SCRS **1001**. Stream **1008** may originate from a conventional nitrogen production process, such as an air separation plant deploying turbo-expanders or membranes. Stream **1008** may be a slip stream taken from process stream **1004**. A reciprocating compressor **1010** may be used to compress stream **1008** to a pressure above or slightly above the highest pressure needed for seal gas streams **1018A** and **1018B**. However, the cylinder of the reciprocating compressor **1010** is typically lubricated with oil that can be carried as a mist or vapor out of the compressor **1010**, contaminating the compressed gas stream **1012** making the compressed stream **1012** unsuitable for use in dry gas seals. Hence, compressed stream **1012** may be fed into unit **1014** for conditioning. Conditioning may involve changing the temperature of the stream by heat exchange or removing particles or oil mist (e.g. via a filter) coming from the reciprocating compressor **1010**. The conditioned stream **1020** may then be fed to the SCRS **1001** including adsorption unit **1027** having a valve or a set of valves **1028** which may control (e.g. pulse) the rate of the conditioned feed stream **1020** into the adsorption bed **1025**. An exit valve or a set of exit valves **1036** may periodically open and close to allow a utility stream **1040** to leave the adsorption unit **1027**. The utility stream **1040** may then optionally be flowed through safety and unit isolation devices **1042** such as unit isolation valves, flow checks, or pressure relief valves can be provided to improve operability. An accumulator vessel **1044** may also be provided to further reduce flow or pressure fluctuations. Optionally, the accumulator **1044** can include a heat exchanger (not shown). Resulting stream **1046** is then the nitrogen rich treated utility stream (seal gas), which may be split into streams **1018A** and **1018B** for use in the dry gas seals of the compressor **1002**. Additionally, a secondary stream **1038** may enter the swing adsorption unit **1027** via a secondary inlet valve or a set of inlet valves **1030**, then exit the swing adsorption unit **1027** via a secondary exit valve or valves **1024** that may periodically open and close to allow the reject (e.g. secondary product) stream or set of streams **1026** to leave the swing adsorption unit **1027**.

[0068] If the swing adsorption unit employs a pressure swing adsorption process the pressure of stream **1026** is preferably less than 20 percent of stream **1040**. Optionally, the swing adsorption unit uses a thermal swing adsorption process. In this case a set of valves comprising at least **1034** and **1022** is provided to pulse the flow of heating or cooling fluids that enter and leave the vessel **1029** through streams **1016** and **1032**. Electric heating or cooling jacket cooling can also be used to produce the swings. Optionally, the swing adsorption unit **1026** uses a partial pressure purge displacement process. In this case, a valve or set of valves **1030** is provided to pulse the flow of the purge displacement stream **1038** into the adsorption bed **1025**. The adsorption bed **1025** is contained within a pressure vessel **1029**. Optionally, this vessel **1029** and the associated valving is contained within a secondary pressure vessel **1039**. This secondary pressure vessel **1039** is designed to mitigate the significance of leaks through seals in the valves inside the swing adsorption unit **1027**. This can be especially important when rotary valves are used. When rotary valves are used, valves **1024**, **1028**, and **1022** can all be incorporated into a single rotary valve body (e.g. they do not have to be separate valve bodies). Similarly, any optional valves used (**1036**, **1030**, and **1034**) can be incorporated with them into a single rotary valve body. To provide a more continuous flow in purified stream **1040**, several swing adsorption units **1027** may be employed. If several swing adsorption units **1027** are employed, the utility streams **1040** may be merged.

[0069] In some embodiments of the process **1000**, the process stream **1004** can be a sour or acid gas stream that is being compressed for injection into an underground reservoir. Pressure of the process stream **1004** being fed to the centrifugal dry seal compressor **1002** can be in a range from 10-100 bar. Pressure of the compressed stream **1006** can be in a range from 100-800 bar with the ratio of pressures between stream **1006** and **1004** being greater than 2:1. In many instances the centrifugal dry seal compressor **1002** will have several compression stages. In a preferred embodiment, the pressure of stream **1006** is greater than 200 bar, even more preferably greater than 400 bar. In another preferred embodiment the gas flow rate in stream **1006** is greater than 20 million standard cubic feet per day (MMSCFD) and even more preferably greater than 200 MMSCFD. The total flow rate of the utility seal gas streams **1018A** and **1018B** is preferably greater than 0.1 MMSCFD and even more preferably greater than 1.0 MMSCFD. Pressure of the utility seal gas streams **1018A** and **1018B** needed for the high pressure centrifugal dry seal compressor **1002** are preferably greater than 100 bar and even more preferably greater than 200 bar. Because the high

pressure centrifugal dry seal compressor **1002** processes a sour or acid gas stream, the oxygen content in the nitrogen rich seal gas streams **1018A** and **1018B** is preferably less than 5%, more preferably less than 0.1% and most preferably less than 0.001%. Oxygen present in the seal gas can react with H₂S in the process stream causing the formation of COS and in some cases sulfur deposition.

[0070] Conventional nitrogen production processes do not produce a nitrogen stream with sufficient pressure and purity to be used as a seal gas in high pressure centrifugal dry seal compressors such as compressor **1002**. It is possible to produce lower pressure nitrogen streams that meet the purity requirements. However, when a reciprocating compressor is used to pressurize these low pressure nitrogen streams they become unsuitable for use in high pressure seal gas applications because they pick up oil vapor, oil additive vapors as well as oil droplets from the oil used to lubricate the cylinder of the reciprocating compressor. The present invention provides a process **1000** to remove these vapors and oil drops, both of which should be removed to provide seal gas for high pressure centrifugal dry seal compressors. Conventional technologies such as cryogenic distillation, permselective membrane separation, and pressure swing adsorption can produce low to modest pressure nitrogen rich streams from an air feed. Oxygen will be present in all of these nitrogen rich streams with the least amount in streams produced by cryogenic distillation. Several methods can be used to remove oxygen from these streams to the levels requires for seal gas applications. At the flow rates required one of the most attractive methods is to catalytically react oxygen in the stream with a hydrocarbon or hydrogen. Water vapor is a product of both of these reactions and can be removed from low pressure and modest pressure nitrogen rich streams using conventional mole sieve adsorption beds or later on in the process using the swing adsorption bed **1025**. Stream **1008** is a deoxygenated nitrogen rich stream prepared using the processes or variations of the processes that have been discussed. Except for its water vapor content it meets the purity requirements for utility seal gas streams **1018A** and **1018B**.

[0071] In multi-stage systems requiring different seal gas pressures, the gaseous slip stream may come from the discharge of each stage of intermediate compression or from the discharge of any of the compression stages such that adequate pressure is provided to filter and treat the discharge fluid while still meeting the required seal gas pressure.

[0072] Beneficially, it is anticipated that embodiments of the invention could be substantially smaller in size than typical gas treating/conditioning alternatives. Embodiments

of the invention have the potential to be much simpler and smaller than traditional bulk separation methods applied to full process streams or full well streams such as solvent extraction, molecular sieve treating, acid gas conversion, or distillation, for example, where bulk separation occurs. Some of these compounds may be separated for their inherent value
5 as a utility or blended with a product stream, while others may be rejected as waste products. In one form of this invention, these waste products can be returned to the primary process stream from which the gaseous slip stream was originally taken, yielding a process by which no additional waste product streams are produced.

[0073] The SCRS process separation may be carried out in a compact swing
10 adsorption unit that would replace traditional, capially-intense and large equipment such as distillation towers, glycol contactors, and other traditional separation and purification equipment.

[0074] While the present techniques of the invention may be susceptible to various modifications and alternative forms, the exemplary embodiments discussed above have been
15 shown by way of example. However, it should again be understood that the invention is not intended to be limited to the particular embodiments disclosed herein. Indeed, the present techniques of the invention are to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

CLAIMS

What is claimed is:

1. A method of treating a gaseous feed stream, comprising:
producing a gaseous feed stream;
5 dividing at least a portion of the gaseous feed stream to form a gaseous slip stream;
separating the gaseous slip stream using a selective component removal system
having at least one swing adsorption process unit to form a utility stream for use in a utility
component;
feeding the first utility stream into the utility component, wherein the utility stream is
10 compatible with the utility component; and
utilizing the utility stream in the utility component.
2. The method of claim 1, wherein the gaseous slip stream is at least one of a
hydrocarbon containing feed stream, a nitrogen-rich stream, at least a portion of a high
pressure process stream, and at least a portion of a compressor discharge stream.
- 15 3. The method of claim 2, wherein the gaseous slip stream is at a pressure above the
critical point of the gaseous feed stream.
4. The method of claim 3, wherein the gaseous slip stream is at a pressure of from at
least about 100 bar to at least about 500 bar.
5. The method of claim 3, wherein the gaseous slip stream is at a pressure of from at
20 least about 200 bar to at least about 320 bar.
6. The method of any one of claims 1-5, wherein at least one of the at least one utility
component is selected from the group consisting of a compressor, a dry seal compressor, a
compressor string, a turbo-expander compressor, a turbo-expander generator, a pump, a fired
steam boiler, a fired process heater, a gas engine, a hermetically sealed direct-drive electric
25 motor, turbomachinery equipped with magnetic bearings, gas-operated instruments and
controls, and a gas turbine.
7. The method of any one of claims 1-6, wherein the utility component is located
remotely from a gas processing plant.
8. The method of any one of claims 1-7, wherein the utility stream is utilized as a dry
30 seal gas for at least one of a dry gas seal, a labyrinth seal, and a mechanical seal in the at least
one utility component.
9. The method of any one of claims 1-8, wherein the at least one swing adsorption
process unit is selected from the group of units consisting of a pressure swing adsorption

(PSA) unit, a thermal swing adsorption (TSA) unit, a partial pressure swing or displacement
purge adsorption (PPSA) unit, a rapid cycle thermal swing adsorption (RCTSA) unit, a rapid
cycle pressure swing adsorption (RCPSA) unit, a rapid cycle partial pressure swing or
displacement purge adsorption (RCPPSA) unit, a compact PSA, a compact TSA, a compact
5 PPSA, and any combination thereof.

10. The method of any one of claims 1-8, wherein the selective component removal
system (SCRS) further comprises at least one of an absorption unit, a membrane separation
unit, a molecular sieve, a distillation tower, and a glycol contactor.

11. The method of any one of claims 1-10, wherein the utility stream is a non-condensable
10 gas stream at an operating temperature and pressure of the utility component.

12. The method of any one of claims 1-10, wherein the utility stream has a composition,
wherein the composition remains in the gaseous phase throughout its utilization in the utility
component.

13. The method of any one of claims 1-10, wherein the utility stream has a composition,
15 wherein the composition is substantially free of toxic and corrosive components.

14. The method of claim 13, wherein the toxic and corrosive components include at least
one of H_2S , CO_2 , H_2O , and SO_2 .

15. The method of any one of claims 1-10, wherein the utility stream has a composition,
wherein the composition is substantially completely made up of inert components.

20 16. The method of claim 15, wherein the inert components include at least one of nitrogen
and carbon dioxide.

17. The method of any one of claims 1-16, wherein the swing adsorption process is
performed inside a secondary pressure vessel.

18. The method of claim 17, wherein the secondary pressure vessel is maintained at an
25 inside pressure of from at least about 100 bar to at least about 600 bar.

19. The method of claim 18, wherein the secondary pressure vessel is maintained at an
inside pressure of from at least about 200 bar to at least about 500 bar.

20. The method of claim 1, further comprising exchanging heat to or from the swing
adsorption process unit by a heat exchanger selected from the group consisting of internal
30 electric heating, jacket cooling, and any combination thereof.

21. A method of treating a nitrogen-rich gaseous stream, comprising:
producing a nitrogen-rich gaseous stream;

separating at least a portion of the nitrogen-rich gaseous stream using a selective component removal system having at least one swing adsorption process unit to form a utility stream for use in a utility component;

feeding the utility stream into the utility component, wherein the utility stream is
5 compatible with the utility component; and
utilizing the utility stream in the utility component.

22. A system for treating a gaseous feed stream, comprising:

a tubular member containing a gaseous feed stream operatively connected to a selective component removal system including at least one swing adsorption process unit,
10 wherein the selective component removal system is utilized to separate at least a portion of the gaseous feed stream to form a utility stream; and

a utility component configured to receive and utilize the utility stream, wherein the utility stream is compatible with the utility component.

23. The system of claim 22, wherein the gaseous slip stream is at least one of a
15 hydrocarbon containing feed stream, a nitrogen-rich stream, at least a portion of a high pressure process stream, and at least a portion of a compressor discharge stream.

24. The system of any one of claims 22-23, wherein the utility component is at least one of a compressor, a dry seal compressor, a compressor string, a turbo-expander compressor, a turbo-expander generator, a pump, a fired steam boiler, a fired process heater, a gas engine, a
20 hermetically sealed direct-drive electric motor, turbomachinery equipped with magnetic bearings, gas-operated instruments and controls, and a gas turbine.

25. The system of any one of claims 22-24, wherein the at least one swing adsorption process unit is selected from the group of units consisting of a pressure swing adsorption (PSA) unit, a thermal swing adsorption (TSA) unit, a partial pressure swing or displacement
25 purge adsorption (PPSA) unit, a rapid cycle thermal swing adsorption (RCTSA) unit, a rapid cycle pressure swing adsorption (RCPSA) unit, a rapid cycle partial pressure swing or displacement purge adsorption (RCPPSA) unit, a compact PSA, a compact TSA, a compact PPSA, and any combination thereof.

26. The system of any one of claims 22-25, wherein the utility stream is utilized as a dry
30 seal gas for at least one of a dry gas seal, a labyrinth seal, and a mechanical seal in the at least one utility component.