



- (51) **International Patent Classification:** Not classified
- (21) **International Application Number:**
PCT/IB2010/055024
- (22) **International Filing Date:**
5 November 2010 (05.11.2010)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
SG200907418-8 6 November 2009 (06.11.2009) SG
- (71) **Applicant (for all designated States except US):**
MEIBAN INTERNATIONAL PTE. LTD. [SG/SG]; 11 Ubi Rd. 1, Singapore 408723 (SG).
- (72) **Inventor; and**
- (75) **Inventor/Applicant (for US only):** **TODESCO, Pierre, Louis** [SG/SG]; Block 234 Hougang Ave. 1 #10-250, Singapore 530234 (SG).
- (74) **Agents:** **SCHWEIGER, Martin** et al.; Schweiger & Partners (Singapore) LLP, The Octagon, 105 Cecil Street #03-02, Singapore 069534 (SG).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) **Title:** MICRO TEMPERATURE CONTROLLER




Figure 3

(57) **Abstract:** A temperature controller for mounting on an injection tool comprises a comparator for comparing a reference temperature signal with a sensed temperature signal from the injection tool, an opto-coupler coupled to the output of the comparator and a solid-state switching device. A temperature controller for providing a reference temperature signal of a temperature control process in an injection tool has a reference temperature selection circuit arranged for a user to select between first and second reference temperatures.