

Image Recognition Based Workstation for Evaluation on Quality Check of Colonoscopy

TECHNICAL FIELD

[0001] The invention relates to the technical field of intelligent medical treatment, and
5 in particular to an image recognition based workstation for evaluation on colonoscopy
quality.

BACKGROUND

[0002] A colonoscope has been widely used in the diagnosis and treatment of intestinal
diseases. As a safe, accurate and well-tolerated instrument, it plays an important role in
10 both initial screening and subsequent detection of colorectal cancer (CRC). Colonoscopy
is essential for early detection of precancerous lesions and prevention of the CRC, which
can reduce a CRC risk by 77% as shown in studies.

[0003] However, many factors impact on quality of the colonoscopy, including three
types of evaluation indexes impacting on the quality of colonoscopy: basic characteristics
15 of patients, intestinal preparation, etc. (before the colonoscopy), a cecal insertion rate,
colonoscope withdrawal time, an adenoma detection rate, etc. (during the colonoscopy),
and a bleeding rate, a perforation rate, etc. (after the colonoscopy), of which factors
related to a colonoscope operator (that is, during the colonoscopy) are the most impactful.

[0004] Thus, it is crucial to improve quality during the colonoscopy to reduce the CRC
20 risk, especially to reduce an incidence rate of interphase CRC. But colonoscopy doctors
have different professional levels, and an examination standard of the doctors will be
lowered due to exhaustion caused by multiple operations in one day, so it is urgent to
develop an image recognition based workstation for evaluation on colonoscopy quality.

SUMMARY

25 [0005] The object of the present invention is to overcome the above technical defects, so
as to provide an image recognition based workstation for evaluation on colonoscopy
quality.

[0006] In order to achieve the above object, the present invention uses the following

technical solution: the image recognition based workstation for evaluation on colonoscopy quality. The workstation includes: an algorithm module, a timing module, a data transmission module, display equipment, colonoscope equipment and a computer host, where the colonoscope equipment is connected to the data transmission module, the data transmission module is connected to the computer host by means of the algorithm module and the timing module, the display equipment is configured to display a result of the computer host, and

[0007] the algorithm module includes a colonoscopy fuzzy detection algorithm, an examination completeness degree algorithm, a lesion recognition algorithm, a static detection algorithm and a wall collision detection algorithm.

[0008] A fuzzy detection algorithm uses a function in opencv to gray an input image, uses a laplace operator to detect a global variance of the whole image, and conducts marginal detection on the whole image, so that the global variance of the whole image is calculated, and an appropriate threshold value is determined so as to determine whether the image is fuzzy or not; the examination completeness degree algorithm is used to detect an average gray value of part of areas of four corners in the input image and select an appropriate threshold value to determine whether the four corners are bright or dark, and under the condition that brightness of each corner in a certain number of image dead angles continuously input is included, an examination is complete, and otherwise, the examination is incomplete; the lesion recognition algorithm uses a YOLO V3 algorithm, and can detect a position of a lesion in an input video image in real time; the static detection algorithm is used to calculate a gray histogram of two images spaced a certain number of frames apart, and when a matching degree reaches a certain threshold value, it is determined that a colonoscope lens is in a static state within time corresponding to the number of frames; the wall collision detection algorithm trains a collected picture that is too close to an intestinal wall through a deep learning method, so as to obtain a detection model; and the timing module is used to calculate total examination time and colonoscope withdrawal time.

[0009] The present invention has the beneficial effects that the present invention can evaluate different methods of a doctor during colonoscopy every time by means of different image recognition algorithms, and determine whether the doctor operates properly and give a corresponding reference suggestion during the colonoscopy, and can supervise the doctor to conduct the colonoscopy more seriously so as to be responsible to

a patient. Thus, an ability of the doctor during the colonoscopy can be continuously improved, pressure of the doctor can be greatly reduced, the doctor can focus on other more creative tasks, and great economic and social benefits are created.

BRIEF DESCRIPTION OF DRAWINGS

- 5 [0010] Fig. 1 is a structural schematic diagram of the present invention; and
[0011] Fig. 2 is a schematic diagram of a constitution of an algorithm module in the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

10 [0012] The specific embodiments of the present invention will be described in details below in conjunction with the accompanying drawings and the exemplary embodiments. As shown in Fig. 1, an image recognition based workstation for evaluation on colonoscopy quality of the present invention includes parts of an algorithm module, a timing module, a data transmission module, display equipment, colonoscope equipment and a computer host.

15 [0013] As shown in Fig. 2, the algorithm module includes a colonoscopy fuzzy detection algorithm, an examination completeness degree algorithm, a lesion recognition algorithm, a static detection algorithm and a wall collision detection algorithm.

[0014] The examination completeness degree algorithm is used to count the cycle number of rotation of a lens during colonoscope withdrawal through the above method, 20 when a visual field is static, the function is not determined, and when the cycle number of rotation reaches a certain number, it is determined that an intestinal examination by a doctor is complete. The fuzzy detection algorithm is used to calculate the number of fuzzy frames from the colonoscope withdrawal to an end through the above method, and calculate colonoscope withdrawal sharpness of the examination according to a formula:
25 colonoscope withdrawal sharpness = 1 - the number of fuzzy frames / the number of total frames so as to determine operation of the doctor. The lesion recognition algorithm is used to recognize a lesion and mark a position thereof during the examination, and finally record the total number of lesions. The static detection algorithm is used to calculate static time from the colonoscope withdrawal to the end through the above method, and calculate
30 effective colonoscope withdrawal time in cooperation with the timing module. The wall

collision detection algorithm is used to calculate the number of frames of an image that is too close to an intestinal wall during the colonoscopy withdrawal through the above method, and calculate a safety index according to a formula: safety index = 1 - the number of red fuzzy frames/the number of total frames.

5 [0015] The timing module is connected to the colonoscopy equipment, and total examination time, colonoscopy entering time and colonoscopy withdrawal time are calculated according to time nodes, marked by the doctor through stepping on a pedal, of entering an anus, reaching an appendix opening and exiting the anus; and by combining with the above algorithm, the effective colonoscopy withdrawal time is calculated
10 according to a formula: effective colonoscopy withdrawal time (s) = colonoscopy withdrawal time - (the number of static frames + the number of fuzzy frames) / frame rate.

[0016] The meanings of the parameters calculated according to all the algorithms of the present invention are as follows:

15 [0017] Total examination time is to score an index for evaluating proficiency of the doctor; total colonoscopy withdrawal time is to increase a colonoscopy withdrawal speed so as to reflect efficiency of the doctor; the colonoscopy withdrawal sharpness: during the colonoscopy withdrawal, the higher a proportion of clear visual frames, the more effective the examination is, and the fewer omissions are; effective colonoscopy withdrawal time:
20 in unit time of effective colonoscopy withdrawal movement time, a visual field is changed and clearly recognizable, the function is used to evaluate effectiveness of colonoscopy withdrawal operation of the doctor and reduce invalid colonoscopy withdrawal operation, and the effective colonoscopy withdrawal time is monitored to avoid too long meaningless stop of the doctor, and is qualified when longer than or equal to 6 min as
25 required by the doctor; and a safety index is to evaluate a proportion of the doctor touching the intestinal wall during the operation, and under the condition that the proportion is large, the safety index is low, indicating that a risk caused by the operation of the doctor is high.

[0018] The above mentioned description is merely the preferred implementation of the
30 present invention, it should be pointed out that those of ordinary skill in the art may also make some improvements and modifications without departing from the principle of the present invention, and these improvements and modifications should also fall within the scope of protection of the present invention.

What is claimed is:

1. An image recognition based workstation for evaluation on quality check of colonoscopy, comprising: an algorithm module, a timing module, a data transmission module, display equipment, colonoscope equipment and a computer host, wherein the colonoscope equipment is connected to the data transmission module, the data transmission module is connected to the computer host by means of the algorithm module and the timing module, the display equipment is configured to display a result of the computer host, and

the algorithm module comprises a fuzzy detection algorithm, an examination completeness degree algorithm, a lesion recognition algorithm, a static detection algorithm and a wall collision detection algorithm,

wherein the fuzzy detection algorithm uses a function in opencv to gray an input image to obtain a grayed input image, uses a laplace operator to detect a global variance of the grayed input image, and conducts marginal detection on the grayed input image, so that the global variance of the grayed input image is calculated, and a first threshold value is determined so as to determine whether the grayed input image is fuzzy or not; the examination completeness degree algorithm is used to detect an average gray value of part of areas of four corners in the grayed input image and select a second threshold value to determine whether the four corners are bright or dark, and under the condition that brightness of each corner in a certain number of image dead angles continuously input is included, an examination is complete, and otherwise, the examination is incomplete; the lesion recognition algorithm uses a YOLO V3 algorithm, and can detect a position of a lesion in an input video image in real time; the static detection algorithm is used to calculate a gray histogram of two images spaced a certain number of frames apart, and when a matching degree reaches a certain threshold value, it is determined that a colonoscope lens is in a static state within time corresponding to the number of frames; the wall collision detection algorithm trains a collected picture that is too close to an intestinal wall through a deep learning method, so as to obtain a detection model; and the timing module is used to calculate total examination time and colonoscope withdrawal time.