

AS

Assembly and Method for Forming a Frozen Confection

Attorney Docket No. FRKLN-8 PCT



159159

ASSEMBLY AND METHOD FOR FORMING A FROZEN CONFECTIONFOR A FROZEN CONFECTION TYPE FOOD PRODUCTCROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefit of and is a continuation in part of U.S. Provisional Patent Application Serial No. 60/273,145, filed March 3, 2001, in the names of Peter B. Franklin et al.

BACKGROUND OF THE INVENTION

G00002

1. Field of the Invention

This invention relates to ice cream novelties, and the like, and is directed more particularly to an assembly and method for forming a frozen confection portion of a frozen confection food product.

2. Description of the Prior Art

Ice cream novelties are generally well known and may comprise ice cream, supported by a stick, cup, or tubular container, or a combination of ice cream and an edible container, or support, such as a cone, one or more cookies, cake, and the like.

1 In U.S. Patent No. 6,156,357, issued December 5, 2000, to
2 Peter B. Franklin, there is shown and described one such product
3 wherein an ice cream core is cradled in a U-shaped piece of cake.
4 In products of this type it is customary to form the ice cream by
5 freezing the ice cream in a mold, typically of stainless steel,
6 and then removing the ice cream in frozen condition and combining
7 the frozen ice cream with a support, either edible or non-edible.

8 Problems which have manifested themselves in this forming
9 procedure include the fact that it is expensive and time-
10 consuming to initially form solid, metal molds, and to
11 continually sanitize them after each usage. Further, it is
12 expensive to freeze the heavy, solid molds to create a frozen
13 cavity in which to form the product. Further, removal of the
14 frozen product from the mold can be problematic inasmuch as the
15 frozen product is impinging upon the mold wall. The removal
16 process typically requires the use of a stick, which is never
17 removed from the product, making the process unusable for
18 stickless, molded products. Still further, once the product is
19 molded it must be placed into its final packaging configuration
20 immediately, requiring the final assembly processes to be run at
21 the same time the molding process is run. Because the molding
22 and final assembly/packaging are linked, molding equipment is
23 usually at or over capacity during summer months and
24 underutilized during winter months, creating large industry
25 inefficiencies.

1 There is thus a need for an assembly and method for forming
2 frozen confection products which eliminate the aforementioned
3 shortcomings of present systems.
4

5 SUMMARY OF THE INVENTION

6 Accordingly, an object of the present invention is to
7 provide an assembly and method for forming a frozen confection
8 product which do not require continual sanitizing of the molds,
9 and the significant cost of reducing and keeping the molds at an
10 appropriate freezing temperature. Further objects of the
11 invention are to provide for easy handling and transporting of
12 the formed product and to render removal of the frozen product
13 from the mold a quick and easy undertaking without a stick. A
14 still further object of the invention is to separate the molding
15 and final assembly process, thereby extending the life span
16 between formation of the product and safe and enjoyable
17 consumption of the product.

18 With the above and other objects in view, a feature of the
19 invention is the provision of an assembly for forming a frozen
20 confection portion of a frozen confection type food product, the
21 assembly comprising a mold casing of a selected configuration and
22 of an inert material, a pump for moving confection into the mold
23 casing to substantially fill the mold casing, sealing means for
24 sealing the ends of the casing to provide a link of confection, a
25 cutter device for separating links of molded confection, a

1 freezing device for receiving and freezing the link, and
2 apparatus for opening the casing of the link and permitting the
3 frozen confection to exit out of the casing in the selected
4 configuration.

5 In accordance with a further feature of the invention, there
6 is provided a method for forming a frozen confection portion of a
7 frozen confection type food product, the method comprising the
8 steps of providing a mold casing of a selected configuration for
9 a desired frozen confection, pumping the confection into the mold
10 casing to substantially fill the mold casing, sealing ends of the
11 casing to provide a link of confection, separating the link from
12 adjoining links, removing the link from the mold cavity, freezing
13 the link, and removing the link casing from the frozen
14 confection.

15 The above and other features of the invention, including
16 various novel details of combinations of parts and method steps,
17 will now be more particularly described with reference to the
18 accompanying drawings and pointed out in the claims. It will be
19 understood that the particular assembly and method embodying the
20 invention are shown by way of illustration only and not as
21 limitations of the invention. The principles and features of
22 this invention may be employed in various and numerous
23 embodiments without departing from the scope of the invention.
24

25 BRIEF DESCRIPTION OF THE DRAWINGS

1 Reference is made to the accompanying drawings in which are
2 shown illustrative embodiments of the invention, from which its'
3 novel features and advantages will be apparent.

4 In the drawings:

5 FIG. 1 is a diagrammatic illustration of one form of
6 assembly illustrative of an embodiment of the invention; and

7 FIG. 2 is a block diagram showing an illustrative method in
8 accordance with the invention.

9
10 DESCRIPTION OF THE PREFERRED EMBODIMENT

11 Referring to FIG. 1, it will be seen that an illustrative
12 assembly for forming a frozen confection for a frozen confection
13 type food product, such as, for example, that shown and described
14 in the aforementioned U.S. Patent No. 6,156,357, includes an ice
15 cream freezer 20, preferably a continuous batch freezer. It will
16 be understood that use of the term "ice cream" herein is intended
17 to include various frozen confections which might not be
18 considered "ice cream" strictly speaking, such as frozen yogurt,
19 frozen custard, sherbet, sorbet, other dairy and water-based
20 products, and the like. The terms "ice cream" and "frozen
21 confection" are used herein to denote frozen confections
22 generally, just as various devices and products, such as "ice
23 cream freezer" actually are not limited strictly to ice cream,
24 but rather to frozen confections generally.

1 The ice cream freezer 20 may be provided with a pump (not
2 shown) for moving a continuous batch of ice cream through the
3 freezer. Movement of ice cream from the freezer 20 may be
4 accomplished by the freezer pump and/or there may be provided a
5 discrete pump 22. In either instance, the ice cream from the
6 freezer 20 is pumped to a mold assembly 24 having therein a mold
7 cavity 26 of a configuration selected for the particular product
8 desired. Batch ice cream freezers are known in the art and are
9 in use in the ice cream industry. In accordance with the present
10 invention, the ice cream from the batch freezer 20 typically is
11 pumped from the freezer in a partially frozen state.

12 The mold assembly 24 preferably is of the type made and sold
13 by Vemag Corp. and identified as LPG 202 and ROBOT HP 10C (for
14 medium-sized plants) and ROBOT HP 15C (for industrial-scale
15 plants). These machines are intended for the sausage making
16 industry, but have been found by the inventors herein to be
17 suitable for molding frozen confection products. To adapt the
18 sausage-making mold assembly to the forming of ice cream product,
19 it is necessary only to modify solid-handling components to
20 liquid-handling. For example, a "stuffer" portion 23 of the
21 Vemag machine, which conveys sausage ingredients to the mold, is
22 modified to handle a liquid, that is, the partially frozen mix
23 provided by the freezer 20. The "stuffer" 23 typically
24 constitutes a hopper 25 having a paddle-type scraper 27 therein
25 for scraping the inner surface 31 of the hopper 25 and pushing

1 meat into the mold. To handle the liquid ice cream, the paddle
2 27 is modified for closer contact with the hopper walls 31.

3 The freezer 20 provides the partially frozen mix at a
4 temperature such that upon entering the mold 26 the mix is at a
5 temperature of about 22°F.

6 The mold assembly 24 is provided with a casing feed 28 for
7 moving an inert casing 29 into the mold cavity 26. The casing 29
8 preferably is of a natural material, or of a collagen or
9 cellulose material. The casing feed 28 preferably is of the type
10 used on the aforesaid Vemag sausage molding machine, in which the
11 feed apparatus is used to advance casing material.

12 In a preferred embodiment, the mold cavity 26 is formed
13 entirely by the flexible inert casing 29. In this case, the mold
14 assembly 24 does not include the traditional mold with a mold
15 cavity 26, but rather comprises merely support for the casing 29
16 which alone constitutes the mold cavity. In this embodiment, the
17 size and shape of the mold cavity, and therefore the molded
18 product, can easily be changed, even while the assembly is
19 running. Further, multiple flavors can be extruded, including a
20 molded core of one flavor and a surrounding layer of a second
21 flavor.

22 The mold assembly is further provided with sealing means 30
23 for sealing the ends of the casing having therein the confection
24 received from the batch freezer 20. The sealing means 30 thus
25 forms a link of the confection housed in the casing 29. The

1 sealing means 30 preferably comprises a selected one of (i) a
2 twist-link device of the type commonly used in the aforementioned
3 Vemay sausage mold assembly, (ii) a heat-seal device, and (iii) a
4 tie device such as are commonly known in the arts, though
5 believed not heretofore in the frozen confection forming arts.

6 Within the mold assembly 24, or proximate thereto, or remote
7 therefrom, there is provided a cutter device 32 including a blade
8 34 for severing the casing material between formed bodies of
9 confection to separate "links" of encased confection material
10 from each other. The cutter device 32 preferably is of the type
11 used in the aforesaid Vemag assembly.

12 The assembly further includes a nitrogen flash freezing
13 apparatus 40 for lowering the temperature of the ice cream to
14 about 5°F. Such apparatus 40 may be configured to accommodate
15 throughput requirements and available floor space. Preferred
16 devices include a nitrogen immersion freezer and a nitrogen
17 freezing tunnel. An example of the former is a nitrogen
18 immersion freezer of BOC Gases, and an example of the latter is a
19 liquid nitrogen freezing tunnel of Air Products Food Group, both
20 available through market channels.

21 The frozen product is then boxed and stored in a freezer 42
22 capable of further lowering the internal core temperature of the
23 ice cream to at least about -20°F. At this point the product can
24 be stored and/or transported to other locations.

1 Finally, the forming assembly includes an apparatus 50 for
2 slicing open a link with a blade 52, which permits the frozen
3 confection to fall out of, or otherwise exit, the casing 29.
4 Such slicing apparatus is known and used in the preparation of
5 skinless frankfurters. One appropriate apparatus is the Model
6 2600 Skinless Sausage Peeler of Townsend Engineering Company.
7 The apparatus 50 may be disposed physically in the area of the
8 assembly described hereinabove or may be disposed at remote
9 location.

10 The assembly for forming a frozen confection is thus an
11 assembly of essentially known components taken from various
12 diverse industries, including ice cream making and quick
13 freezing, and sausage making.

14 In operation of the above-described assembly, a continuous
15 batch of ice cream is made by the ice cream freezer 20 and pumped
16 into the casing cavity at about 22°F. The casing feed 28 will
17 have disposed the casing 29 to line the mold cavity 26 or to
18 serve as the mold cavity 26 itself. The ice cream is thus pumped
19 into the casing 29 which in due course is filled with ice cream.
20 The ends of the casing 29 adjacent the mold cavity 26 are closed
21 by the sealing means 30, as by twisting, tying, or heat sealing,
22 to produce a "link" of encased ice cream.

23 The encased link is then removed from the mold cavity 26 and
24 directed to the flash freezing apparatus 40 for reducing the ice
25 cream core internal temperature to about 5°F. The link is then

1 boxed and stored in a storage freezer 42 to further reduce the
2 temperature to at least about -20°F. The product may then be
3 stored and/or shipped to another location.

4 After the ends of the casing are sealed to form an encased
5 link of ice cream, the link may be separated from the adjoining
6 links, as by the cutting blades 34. This step may be performed
7 immediately after sealing the casing ends, or at some later
8 point, including any point prior to removing the casing from the
9 link, such as after storing and transporting the links.

10 When desired, either at the point of molding or a remote
11 location, the link casing is cut open, as by the blade 52,
12 permitting the frozen core to fall, or otherwise exit, the
13 casing. Before the casing is cut, the link is allowed to rise to
14 an outside temperature of 10°F, while the internal temperature
15 remains at or below -20°F.

16 The frozen core is exposed to the environment only after it
17 is removed from the casing. Accordingly, if the link is stored
18 and/or shipped well before the casing removal operation, the
19 start of shelf life is delayed for the time of storage and/or
20 transport to market.

21 Inasmuch as the edible product, that is, the ice cream core,
22 does not come in contact with the usual mold cavity, sanitizing a
23 cavity is not required, and removal of the core from the casing
24 cavity is no problem inasmuch as the core readily drops from the
25 casing.

1 The above described assembly and method is much less
2 expensive than the usual assembly and method for forming frozen
3 dairy and water-based products, and is more mobile. The
4 separation of the finished product production from the forming,
5 or molding, process, facilitates enormous manufacturing location
6 and scheduling flexibility. The molded product may be stored
7 and/or shipped long-term and await later final processing.

8 As is shown in FIG. 2, the method is extremely flexible.
9 Once the "further freeze" step has been accomplished, storing,
10 transporting, and even separating the links can be accomplished
11 as and when and where desired. In the "further freeze"
12 condition, the ice cream cores can be stored for up to about two
13 years, or so.

14 It will be understood that many additional changes in the
15 details, materials, method steps and arrangement of components,
16 which have been herein described and illustrated in order to
17 explain the nature of the invention, may be made by those skilled
18 in the art within the principles and scope of the invention as
19 expressed in the appended claims.

What is claimed is:

1. An assembly for forming a frozen confection portion of a frozen confection type food product, the assembly comprising:

a mold assembly provided with a mold casing of a selected configuration, the mold casing being formed by a flexible inert material;

a pump for moving confection into the mold casing to fill the mold casing;

sealing means for sealing the ends of the casing to provide a link of confection;

a cutter device for separating links of molded confection;
and

a freezing device for receiving and freezing the link;

apparatus for opening the casing of the link and permitting the frozen confection to exit out of the casing in the selected configuration.

2. The forming assembly in accordance with claim 1, further comprising a continuous batch confection freezer, said pump being operative to move partially frozen confection from the batch freezer to the mold casing.

3. The forming assembly in accordance with claim 1 wherein said mold assembly includes a casing feed for moving the inert casing into position to receive the confection from the confection freezer.

4. The forming assembly in accordance with claim 1 wherein said sealing means comprises a selected one of (i) twist-link device, (ii) heat seal device, and (iii) tie device.

5. The forming assembly in accordance with claim 1 wherein said freezing device comprises a flash freezing device.

6. The forming assembly in accordance with claim 5 wherein said flash freezing device comprises a nitrogen freezing device.

7. The forming assembly in accordance with claim 6 wherein said nitrogen freezing device comprises a selected one of (i) a nitrogen immersion freezer, and (ii) a liquid nitrogen freezing tunnel.

8. The forming assembly in accordance with claim 1 wherein said apparatus for opening the casing comprises a slicing device for slicing open a link to permit the confection to exit the casing of the link.

9. An assembly for forming a frozen confection portion of a frozen confection type food product, the assembly comprising:

an ice cream freezer for dispensing a batch of partially frozen confection material;

a mold assembly provided with a mold casing of a selected configuration for the desired frozen confection product;

a casing feed associated with said mold assembly for positioning the casing such that the casing receives the confection material from the freezer and expands to substantially fill the mold casing; and

a sealing means for sealing ends of the casing to form a link of encased partially frozen confection.

10. The assembly in accordance with claim 9 and further comprising a freezing device for receiving the link and reducing the temperature thereof to further freeze the link.

11. The assembly in accordance with claim 10 and further comprising a storage freezer for receiving the link and for still further reducing the temperature.

12. The assembly in accordance with claim 9 and further comprising a cutter device for opening the casing of the link to permit the ice cream core to exit the link.

13. A method for forming a frozen confection portion of a frozen confection type food product, the method comprising the steps of:

providing a casing for forming a mold cavity casing of a
selected configuration for a desired frozen
confection;

pumping the confection into the mold casing to substantially
fill the mold cavity;

sealing ends of the casing to provide a link of confection;

separating the link from adjoining links;

removing the link from the mold cavity; and

freezing the link.

14. The method in accordance with claim 13 wherein the step of pumping the confection into the casing comprises flowing the confection from a confection freezer and into the casing at a temperature of about 22°F.

15. The method in accordance with claim 13 wherein the inert casing comprises a material selected from (i) natural, (ii) collagen, and (iii) cellulose.

16. The method in accordance with claim 13 wherein the step of sealing the ends of the casing is accomplished by a selected one of (i) twisting the ends, and (ii) heat sealing the ends, and tying the ends.

17. The method in accordance with claim 13 wherein the step of freezing the link comprises flash freezing to a temperature of about 5°F.

18. The method in accordance with claim 17 wherein the step of flash freezing the link comprises freezing the link by a selected one of (i) nitrogen immersion, and (ii) a liquid nitrogen tunnel.

19. The method in accordance with claim 17 and further comprising the step of placing the link in a freezer-storage device to further reduce the temperature of the link to about - 20°F.

20. The method in accordance with claim 13 and further comprising the step of removing the link casing by slicing open the casing and permitting the frozen confection to exit the casing.

21. A method for forming a frozen confection portion of a frozen confection type food product, the method comprising the steps of:

making the confection in an ice cream freezer;

providing a mold cavity comprised of an inert casing and of a selected configuration for a desired frozen confection;

moving the confection from the ice cream freezer into the mold cavity to substantially fill the mold cavity;

sealing the ends of the casing adjacent ends of the mold
cavity to provide a link of confection;

separating the link from adjoining links; and

removing the link from the mold.

22. A method for forming a frozen confection portion of a frozen
confection type food product, the method comprising the steps of:

providing a casing forming a mold cavity of a selected
configuration for a desired frozen confection;

pumping the confection into the mold cavity to substantially
fill the mold cavity;

sealing ends of the casing adjacent the mold cavity to
provide a link of confection;

removing the link from the mold cavity;

freezing the link;

separating the link from adjoining links; and

stripping the casing off the frozen confection.

23. A method for forming a frozen confection portion of a frozen confection type food product, the method comprising the steps of:

filling a flexible mold with ice cream;

freezing the mold and the ice cream; and

stripping the mold off the ice cream.