

Description

The present invention relates to a method for purifying aqueous dye solutions. More particularly, the present invention provides a water-soluble dye of high purity which is a useful coloring component of a recording agent for an ink-jet recording system or a writing implement (hereinafter such recording liquid is referred to as ink).

Water-soluble dyes such as direct cotton dyes, acid dyes, basic dyes, reactive dyestuffs and the like have conventionally been used widely for dyeing of fibers, woven cloths, etc. Further, these dyes are recently in wide use as coloring components of inks used in ink jet recording wherein an ink is discharged by one of various discharging means to form ink droplets and the ink droplets are allowed to deposit to a recording medium such as a paper or the like in accordance with image signals. Furthermore, the water-soluble dyes are in wide use as coloring components of inks used in writing pens such as fountain pens, felt pen, ball pen and the like.

As coloring component dyes of inks, particularly inks used in ink jet recording, there are generally utilized dyes for dyeing of fibers. These dyes contain large amounts of additives or impurities. Therefore, it is known that when such commercially available dyes are used in inks for ink jet recording, the inks cause various troubles. One of the most serious troubles is clogging of ink-discharging orifice which is the heart of ink jet recording equipment, and another is deposition of impurities on the heat-generating head in the ink jet recording method utilizing a heat energy for ink discharge. In order to prevent such troubles, purification of dyes used in inks have heretofore been proposed and carried out, and some improvements have been achieved and problems caused by inks have been reduced by using dyes of higher purity. However, there still exists a phenomenon that inks free from any problem right after the production, when delivered from ink manufacturers and stored for several months or years, frequently cause troubles not anticipated right after production. These troubles are significant particularly in the ink jet recording method employing heat energy for ink discharge.

The main object of the present invention is to provide a dye capable of giving an ink which remedies the above mentioned shortcomings of prior art, causes even at a high dye concentration no clogging at the orifice, etc. of ink jet recording equipment during use and also during long term storage, forms no deposit on the heat-generating head of ink jet recording equipment utilizing a heat energy, and thus has excellent stability.

According to the present invention, there is provided a method for purifying a dye solution, comprising steps of dissolving a dye in a solvent to prepare a dye solution, treating the dye solution by addition of a flocculant, and removing insoluble matters from the dye solution by filtration or centrifuging.

According to further aspect of the present invention, there is provided a method for producing an ink by utilizing the above method for dye purification.

In order to attain the above object the present inventor made an extensive research. Commercially available dyes contain various impurities (e.g. various inorganic and organic substances such as dispersing agents and leveling agents) and the above mentioned problems are caused mainly by these impurities. Hence, the adverse effects of the impurities were investigated. It was found that the greatest cause for clogging of nozzles and orifices, for formation of precipitates during ink storage and for deposition of impurities on heat-generating heads in the ink jet recording method utilizing heat energy is the presence in ink of Fe, Si, P, polyvalent metal ions, and colloidal substances consisting of these compounds and that these harmful substances can be efficiently removed from dyes used in inks by using a particular method. Thus the present invention has been completed.

The main characteristic of the present invention lies in the use of a flocculant for purification of a water soluble dyes. The dyes to which the present invention is applicable are water-soluble dyes conventionally used mainly for dyeing of various fibers, such as direct cotton dyes, acid dyes, basic dyes, reactive dyestuffs and the like. As dyes which are preferably used in inks for ink jet recording and satisfy such requirements as distinctness, water solubility, stability, light resistance and the like, there are mentioned, for example, C. I. Direct Black 17, 19, 32, 51, 71, 108 and 146; C. I. Direct Blue 6, 22, 25, 71, 86, 90, 106 and 199; C. I. Direct Red 1, 4, 17, 28 and 83; C. I. Direct Yellow 12, 24, 26 and 98; C. I. Direct Orange 34, 39, 44, 46 and 60; C. I. Direct Violet 47 and 48; C. I. Direct Brown 109; C. I. Direct Green 59; C. I. Direct Black 2, 7, 24, 26, 31, 52, 63, 112 and 118; C. I. Acid Blue 9, 22, 40, 59, 93, 102, 104, 113, 117, 120, 31, 52, 63, 112 and 118; C. I. Acid Blue 9, 22, 40, 59, 93, 102, 104, 113, 117, 120, 167, 229 and 234; C. I. Acid Red 1, 6, 32, 35, 37, 51, 52, 80, 85, 87, 92, 94, 115, 180, 256, 317 and 315; C. I. Acid Yellow 11, 17, 23, 25, 29, 42, 61 and 71; C. I. Acid Orange 7 and 19; C. I. Acid Violet 49; C. I. Basic Black 2; C. I. Basic Blue 1, 3, 5, 7, 9, 24, 25, 26, 28 and 29; C. I. Basic Red 1, 2, 9, 12, 13, 14 and 37; C. I. Basic Violet 7, 14 and 27; C. I. Food Black 2; etc. These dyes are very preferably used in the present invention. However, the present invention is not restricted to such dyes.

The water-soluble dyes mentioned above generally are easily available in the market. These commercially available products contain large amounts of sodium chloride, sodium sulfate and other inorganic salts and further contain inorganic substances such as alkaline earth metal salts, various metal compounds and the like as well as many organic substances such as various surfactants, dispersing agents, leveling agents and the like.

Since the above mentioned additives contained in the conventional water-soluble dyes are also water-soluble, purification of these dyes is not so simple. When such dyes are thoroughly purified by employing a

conventionally known purification method such as filtration, salting-out, ion exchange or the like and are used as inks for ink jet recording, such inks show excellent performances as intended at the time right after their preparation. When stored for several months or longer after their preparation, however, these inks cause troubles as mentioned previously. These troubles caused by inks stored over a long period of time after their preparation occur, in many cases, after the inks have been distributed to the market and hence is a serious problem. In order to solve this serious problem, the present inventor made an extensive research. As the result, it was found that (1) the troubles caused by an ink deteriorated by storage over a long period of time cannot be alleviated by treating the ink by ordinary filtration, ion exchange, etc. (2) the main cause of the troubles comes from a colloidal substance which is present in ink with a relatively high stability but lose their stability when the ink encounters environmental changes such as temperature change, concentration change at a discharging nozzle, thermal shock at a heating head and the like, and (3) said troubles can be completely removed by adding a flocculant to a dye solution to be purified, prior to or during ink preparation to flocculate colloidal substances present in the dye solution and separating the resulting flocculates of any size by means of filtration or centrifugation to remove the colloidal substances completely.

According to the invention there is provided a method for purifying a solution of a water soluble dye in water or a mixture of water and a water soluble organic solvent comprising the steps of

- (a) flocculating colloidal substances present in the solution by addition of a flocculant, and
- (b) filtering and/or centrifuging the treated dye solution to remove insolubles from the dye solution.

The flocculant used in the present invention can be any of ions of bi- or higher-valent metals (e.g. iron, manganese, aluminum, magnesium), ions of metal compounds, ions of oxides of metals (semi-metals such as silicon and phosphorous and the like are included), their hydrates and substances which will neutralize electric charges of colloidal substances present in dye solutions, as long as the above ions, hydrates and substances are stable in water. There are preferably used, for example, conventionally known flocculants such as inorganic flocculants (e.g. aluminum hydroxide, aluminum sulfate, ferrous sulfate, ferric chloride, ferric sulfate, ferric hydroxide, calcium sulfate, calcium carbonate, calcium hydroxide, $\text{Fe}_2(\text{SO}_4)_3$, FeCl_3) and organic flocculants (e.g. starch, gelatin, sodium alginate, a polyacrylamide, chitosan). Particularly preferably used in the present invention are flocculants of iron type and aluminum type.

In the present invention method, mainly colloidal substances are changed, by the use of a flocculant, to flocculates which can mostly be removed by filtration. However, in a treatment with a flocculant alone, not all the colloidal substances change to flocculates removable by filtration; fine and insufficiently grown flocculates of colloidal substances pass through a filter membrane or cause clogging of the membrane when an ordinary filtration is conducted; consequently, the filter membrane need be replaced frequently. The present inventors made a research to solve such problems and found that when a centrifugation is conducted subsequently to the treatment with a flocculant, the fine flocculates of colloidal substances which pass through a filter membrane or cause clogging of the membrane are captured by large flocculates and separated together with the larger flocculates, whereby an aqueous dye solution substantially free from colloidal substances can be obtained. Such a purified aqueous dye solution cannot be obtained only by treatment with a flocculant or only by the treatment using a centrifuge alone but can be obtained only when these two treatments are conducted in succession in this order.

In the centrifugation treatment, there can be effectively used any commercially available centrifuges.

In the method for dye purification according to the present invention, a dye to be purified is dissolved in water or in a mixed solvent of water and a water-soluble organic solvent in an amount of 0.1% to 10% by weight, preferably 1 to 5% by weight; to the resulting aqueous dye solution is added 0.01 to 1 part by weight, based on 100 parts by weight of the dye, of a flocculant; and the resulting mixture is thoroughly stirred. Such a treatment will eliminate the electric charges from a majority of stable colloidal substances and the like as mentioned above and accordingly the substances lose the colloidal properties to flocculate. The above aqueous dye solution treated with a flocculant is subjected to a filtration treatment. In case when the previously mentioned troubles arise even after the filtration treatment, there may be successively conducted a centrifugation treatment. In the centrifugation, neither heating nor cooling is required. A centrifugation of 5,000 to 20,000 rpm for about 10 to 60 min can satisfactorily achieve the object of the present invention. Thus an aqueous dye solution from which mainly colloidal substances have been removed can be obtained. The present invention method can be conducted batchwise or continuously.

The purified aqueous dye solution obtained as above, when the dye had been subjected, prior to the above purification method of the present invention, to other purification method to remove other impurities, can be used as it is as an ink for ink jet recording or as an ink for writing pens. When the dye has not been subjected to the other purification method, the purified aqueous dye solution obtained above contains, in many cases, impurities which cannot be removed by a flocculant, such as sodium chloride, sodium sulfate, other metal salts and organic substances; therefore, it is preferable that the purified aqueous dye solution be further purified, as necessary, by a method such as salting-out, fractional precipitation with a water-soluble organic solvent, ultrafiltration, reverse osmosis, ion exchange, exposure to air, lime softening, electrolysis or the like.

The purified aqueous dye solution thus obtained can be made into an ink as it is or after adding thereto necessary additives such as a water-soluble organic solvent and the like, or can be made into a powder by removing the water present in the solution. The amount of impurities remaining in the purified aqueous

dye solution or in the purified powder can easily be determined by the use of atomic absorption spectrometry, inductively coupled plasma emission spectral analysis or the like. It is preferable that the concentration of impurities in the purified dye of the present invention be about 200 ppm or below (each of iron, magnesium and phosphorus), 250 ppm or below (silicon), about 1,000 ppm or below (total colloidal substances including these metal compounds) and about 2% by weight or below (total inorganic substances), all based on powdery dye. A purified dye containing impurities so as not to exceed the above limits can provide an ink useful for use particularly in the ink jet recording method using a heat energy. Use of such an ink can eliminate the previously mentioned troubles even when the ink has been stored for a long period of time after its preparation.

Hereinafter the present invention will be described more specifically by way of Examples. Parts or % in the following refer to parts or % by weight.

Examples 1A to 6A (dye purification)

The commercially available dyes listed in Table 1A which appears later were purified according to an ordinary method such as salting-out, fractional precipitation, ultrafiltration, reverse osmosis, ion exchange or the like. Then, these purified dyes were made respectively into a 2% aqueous solution. To each 500 ml of these solutions was added 10 ml of an aqueous solution containing 10 ppm of a flocculant shown in Table 1A, and they were stirred for 2 hrs. Thereafter, the mixture was subjected to pressure filtration or centrifugation to separate flocculates. The filter for pressure filtration was Fluoropore filter (pore diameter of 0.45 μ m) manufactured by Sumitomo Electric Industries, Ltd. and centrifugation was conducted at 12,000 rpm for 30 min. The content (based on powder dye) of inorganic substances in the purified dye was measured with iron picked up as a representative inorganic substance. The results are shown in Table 1A.

Example 1A (ink evaluation)

Using the purified dye obtained in Example 1A (dye purification), there was prepared an ink for ink jet recording having the following composition.

Dye	2 parts
Diethylene glycol	40 parts
Water	60 parts

This ink was subjected to the following T1 to T5 evaluation tests, using a recording equipment having an on-demand type multi-head (discharging orifice diameter: 35 μ , resistance of heat-generating resistor: 150 Ω , driving voltage: 30 V, frequency: 2 KHz) wherein the ink stored in the recording head was given a heat energy to generate ink droplets for evaluation of recording. The ink gave good results in all the tests.

(T1) Long term storage stability: The ink was sealed in a plastic film bag and stored for 6 months at -30°C and 60°C, separately. No insoluble appeared and further there was no change in ink properties and color.

(T2) Discharging stability: The ink was subjected to continuous discharging of 24 hours in atmospheres of room temperature, 5°C and 40°C, separately. Constantly stable and high quality recording could be conducted in all the conditions.

(T3) Discharging response: Two cases of intermittent discharging of 2 sec and discharging after 2 month standing were examined. In each case, there was no clogging at the orifice tip and there was obtained stable and uniform recording.

(T4) Quality of recorded image: Using the ink, recording was conducted on the recording media listed in Table 2 which appears later. Each recorded image had high optical density and distinctness. When each image was exposed to an indoor light for 6 months, the reduction of its density was 1% or less.

(T5) Fixing on various recording media: Using the ink, printing was conducted on the recording media of Table 2 which appears later. After 15 sec, the printed portion on each recording medium was rubbed with fingers to see image aberration and spreading. In all the cases, there was neither image aberration nor image spreading, and fixing was excellent.

Examples 2A to 6A (ink evaluation)

Using the purified dyes obtained in Examples 2A to 6A (dye purification) according to the present invention method, inks were prepared in the same manner as in Example 1A (ink evaluation). Each ink was subjected to the same T1 to T5 evaluation tests as in Example 1A (ink evaluation). All the inks showed the same excellent results as in Example 1A (ink evaluation).

Example 7A (ink evaluation)

The yellow ink, magenta ink, cyan ink and black ink obtained in Examples 1A, 2A, 3A and 5A (ink evaluation), respectively, were subjected to the same T1 to T5 evaluation tests as in Example 1A (ink evaluation), using a recording equipment having an on-demand type recording head (discharging orifice

diameter: 50 μ , driving voltage for piezoelectric vibrator: 60 V, frequency: 4 KHz) wherein each ink was discharged by the piezoelectric vibrator. All the inks showed excellent results.

Example 8A (ink evaluation)

5 Using the yellow ink, magenta ink, cyan ink and black ink obtained in Examples 1A, 2A, 4A and 6A (ink evaluation), respectively, and the same ink jet recording equipment as in Example 1A (ink evaluation), a photograph of full color was reproduced. In the recorded image, each color was very clear and color reproduction was good.

Example 9A (ink evaluation)

10 Each of the inks of different color prepared in Examples 1A to 6A (ink evaluation) was charged into a felt pen. With the cap removed, each felt pen was left standing for 10 days. Then, recording was made on a paper using these felt pens. There was no ink skipping and the recording was smooth.

Comparative Example A (ink evaluation)

15 Using the dyes of Table 1A before purification with a flocculant and in the same manners as in Examples 1A to 6A (ink evaluation), 6 different inks for comparison were prepared.
These inks were subjected to the same T1 to T5 evaluation tests as in Example 1A (ink evaluation). Each ink formed precipitation of insolubles in one month. In the test (T2), missing of ink discharge was often observed, at which time the driving voltage had to be raised. Upon observation of the surface of the heat-generating head using a microscope, adherence of brown deposits was observed.
20 In the test (T3), clogging occurred at the orifices after standing for 1 month and discharging of ink was unstable.

Examples 1B to 6B (dye purification)

25 The commercially available dyes listed in Table 1B which appears later were purified according to an ordinary method such as salting-out, fractional precipitation, ultrafiltration, reverse osmosis, ion exchange or the like. Then, these purified dyes were respectively made into a 2% aqueous solution. To each 500 ml of these solutions were added 10 ml of an aqueous solution containing 10 ppm of a flocculant shown in Table 1B, and they were stirred for 2 hrs. Thereafter, the mixture was subjected to centrifugation to separate
30 flocculants. The content (based on powdery dye) of inorganic substances in the purified dye was measured for iron as a representative inorganic substance. The results are shown in Table 1B.

Example 1B (ink evaluation)

35 Using the purified dye shown in Example 1B (dye purification), there was prepared an ink for ink jet recording having the following composition.

Dye	2 parts
Diethylene glycol	40 parts
Water	60 parts

40 This ink was subjected to the same T1 to T5 evaluation tests as in Example 1A (ink evaluation). The results were excellent similarly to those of Example 1A (ink evaluation). In the tests T4 and T5, the recording mediums of Table 2 were used.

Examples 2B to 6B (ink evaluation)

50 Using the purified dyes obtained in Examples 2B to 6B (dye purification) according to the present invention method, inks were prepared in the same manner as in Example 1B (ink evaluation). Each ink was subjected to the same T1 to T5 evaluation tests as in Example 1B (ink evaluation). All the inks showed the same excellent results as in Example 1B (ink evaluation).

Example 7B (ink evaluation)

55 The yellow ink, magenta ink, cyan ink and black ink obtained in Examples 1B, 2B, 3B and 5B (ink evaluation), respectively, were subjected to the same T1 to T5 evaluation tests as in Example 1B (ink evaluation), using a recording equipment having an on-demand type recording head (discharging orifice diameter: 50 μ , driving voltage for piezoelectric vibrator: 60 V, frequency: 4 KHz) wherein each ink was discharged by the piezoelectric vibrator. All the inks showed excellent results.

Example 8B (ink evaluation)

60 Using the yellow ink, magenta ink, cyan ink and black ink obtained in Examples 1B, 2B, 4B and 6B (ink evaluation), respectively, and the same ink jet recording equipment as in Example 1B (ink evaluation), a photograph of full color was reproduced. In the recorded image, each color was very clear and color reproduction was good.

EP 0 181 226 B1

Example 9B (ink evaluation)

Each of the inks of different color prepared in Examples 1B to 6B (ink evaluation) was charged into a felt pen. With the cap removed, each felt pen was left standing for 10 days. Then, recording was made on a paper using these felt pens. There was no ink skipping and the recording was smooth.

5

Comparative Example B (ink evaluation)

Using the dyes of Table 1B before purification with a flocculant and in the same manners as in Examples 1B to 6B (ink evaluation), 6 different inks for comparison were prepared.

10 These inks were subjected to the same T1 to T5 evaluation tests as in Example 1B (ink evaluation). When stored, each ink showed precipitation of insolubles in one month. In the test (T2), missing of ink discharge was often observed, at which time the driving voltage had to be raised. Upon observation of the surface of the heating head using a microscope, adherence of brown deposits was seen.

In the test (T3), clogging occurred at the orifice after standing for 1 month and discharging of ink was unstable.

15

20

25

30

35

40

45

50

55

60

65

Table 1A

Example No. (dye purification)	Dye	Flocculant	Post-treatment	Iron content (ppm based on dye)	
				Before purification	After purification
1A	Acid Yellow 23	Ferric chloride	Pressure filtration	525	71
2A	Acid Red 35	Ferrous sulfate	Centrifugation	362	68
3A	Direct Blue 86	Aluminum sulfate	Centrifugation	416	98
4A	Direct Blue 199	Sodium aluminate	Centrifugation	318	110
5A	Food Black 2	Ferric sulfate	Pressure filtration	292	61
6A	Food Black 2	Aluminum hydroxide	Centrifugation	292	50

Table 1B

Example No. (dye purification)	Dye	Flocculant	Centrifugation	Iron analytical value (ppm based on dye)	
				Before purification	After purification
1B	Acid Yellow ₂₃	Ferric chloride	(1)	525	66
2B	Acid Red 35	Ferrous sulfate	(2)	362	68
3B	Direct Blue ₈₆	Aluminum sulfate	(2)	416	98
4B	Direct Blue ₁₉₉	Sodium aluminate	(1)	318	110
5B	Food Black ₂	Ferric sulfate	(1)	292	55
6B	Food Black ₂	Aluminum hydroxide	(2)	292	49

- (1) Continuous centrifuge (A-251, manufactured by Kokusan Enshinki)
16,000 rpm, 30 min, 20 °C
- (2) Centrifuge (18RR-2, manufactured by Hitachi Koki, Co., Ltd.)
15,000 rpm, 45 min, 20 °C

EP 0 181 226 B1

Table 2

	Recording medium (brand name)	Classification	Manufacturer
5	Ginkan	High quality paper	Sanyo-kokusaku Pulp Co., Ltd.
	Seven Star	High quality paper	Hokuetsu Paper Mills Co., Ltd.
10	Hakubotan	Intermediate quality paper	Honshu Paper Co., Ltd.
15	Toyo Roshi No. 4	Non-sized paper	Toyo Roshi K.K.

Claims

- 20 1. A method for purifying a solution of a water soluble dye in water or a mixture of water and a water soluble organic solvent comprising the steps of
 - (a) flocculating colloidal substances present in the solution by addition of a flocculant, and
 - (b) filtering and/or centrifuging the treated dye solution to remove insolubles from the dye solution.
- 25 2. A method according to claim 1, wherein the flocculant is at least one substance selected from the group consisting of aluminum hydroxide, aluminum sulfate, ferrous sulfate, ferric sulfate, ferric chloride and ferric hydroxide, calcium sulfate, calcium carbonate, calcium hydroxide, $\text{Fe}_2(\text{SO}_4)_3 \cdot \text{FeCl}_3$ and sodium aluminate.
- 30 3. A method according to claim 1 or 2, wherein the dye is dissolved in the solvent at a concentration ranging from 0.1 to 10% by weight.
4. A method according to any preceding claim, wherein the flocculant is added in an amount ranging from 0.01 to 1 part by weight based on 100 parts by weight of the dye.
5. A method for producing an ink, comprising preparing a purified dye solution utilizing a method according to any preceding claim and mixing the treated dye solution with water and/or a water-soluble organic solvent, to prepare an ink.

Patentansprüche

- 40 1. Verfahren zum Reinigen einer Lösung eines wasserlöslichen Farbstoffs in Wasser oder in einer Mischung aus Wasser und einem wasserlöslichen organischen Lösungsmittel mit den folgenden Schritten:
 - (a) Koagulieren bzw. Ausflocken kolloidalen Substanzen, die in der Lösung vorhanden sind, durch Zusatz eines Koagulations- bzw. Ausflockungsmittels und
 - (b) Filtrieren und/oder Zentrifugieren der behandelten Farbstofflösung zur Entfernung unlöslicher Substanzen aus der Farbstofflösung.
- 45 2. Verfahren nach Anspruch 1, bei dem das Koagulations- bzw. Ausflockungsmittel wenigstens eine Substanz ist, die aus der Gruppe ausgewählt ist, die aus Aluminiumhydroxid, Aluminiumsulfat, Eisen(II)-sulfat, Eisen(III)-sulfat, Eisen(III)-chlorid und Eisen(III)-hydroxid, Calciumsulfat, Calciumcarbonat, Calciumhydroxid, $\text{Fe}_2(\text{SO}_4)_3 \cdot \text{FeCl}_3$ und Natriumaluminat besteht.
- 50 3. Verfahren nach Anspruch 1 oder 2, bei dem der Farbstoff in dem Lösungsmittel in einer Konzentration von 0,1 bis 10 Masse% gelöst ist.
4. Verfahren nach einem der vorhergehenden Ansprüche, bei dem das Koagulations- bzw. Ausflockungsmittel in einer Menge von 0,01 bis 1 Masseteil je 100 Masseteile des Farbstoffs zugesetzt wird.
5. Verfahren zur Herstellung einer Tinte, bei dem unter Anwendung eines Verfahrens nach einem der vorhergehenden Ansprüche eine gereinigte Farbstofflösung hergestellt und die behandelte Farbstofflösung zur Herstellung einer Tinte mit Wasser und/oder einem wasserlöslichen organischen Lösungsmittel vermischt wird.

Revendications

- 60 1. Procédé pour purifier une solution d'un colorant hydrosoluble dans de l'eau ou un mélange d'eau et d'un solvant organique hydrosoluble, comprenant les étapes consistant
 - (a) à provoquer la floculation des substances colloïdales présentes dans la solution par addition d'un agent de floculation, et
 - (b) à filtrer et/ou centrifuger la solution de colorant traitée pour éliminer les matières insolubles de la solution de colorant.



EP 0 181 226 B1

Table 2

	Recording medium (brand name)	Classification	Manufacturer
5	Ginkan	High quality paper	Sanyo-kokusaku Pulp Co., Ltd.
	Seven Star	High quality paper	Hokuetsu Paper Mills Co., Ltd.
10	Hakubotan	Intermediate quality paper	Honshu Paper Co., Ltd.
15	Toyo Roshi No. 4	Non-sized paper	Toyo Roshi K.K.

Claims

- 20 1. A method for purifying a solution of a water soluble dye in water or a mixture of water and a water soluble organic solvent comprising the steps of
- (a) flocculating colloidal substances present in the solution by addition of a flocculant, and
- 25 (b) filtering and/or centrifuging the treated dye solution to remove insolubles from the dye solution.
2. A method according to claim 1, wherein the flocculant is at least one substance selected from the group consisting of aluminum hydroxide, aluminum sulfate, ferrous sulfate, ferric sulfate, ferric chloride and ferric hydroxide, calcium sulfate, calcium carbonate, calcium hydroxide, $\text{Fe}_2(\text{SO}_4)_3$, FeCl_3 and sodium aluminate.
3. A method according to claim 1 or 2, wherein the dye is dissolved in the solvent at a concentration ranging from 0.1 to 10% by weight.
- 30 4. A method according to any preceding claim, wherein the flocculant is added in an amount ranging from 0.01 to 1 part by weight based on 100 parts by weight of the dye.
5. A method for producing an ink, comprising preparing a purified dye solution utilizing a method according to any preceding claim and mixing the treated dye solution with water and/or a water-soluble organic solvent, to prepare an ink.
- 35

Patentansprüche

1. Verfahren zum Reinigen einer Lösung eines wasserlöslichen Farbstoffs in Wasser oder in einer Mischung aus Wasser und einem wasserlöslichen organischen Lösungsmittel mit den folgenden Schritten
- 40 (a) Koagulieren bzw. Ausflocken kolloidaler Substanzen, die in der Lösung vorhanden sind, durch Zusatz eines Koagulations- bzw. Ausflockungsmittels und
- (b) Filtrieren und/oder Zentrifugieren der behandelten Farbstofflösung zur Entfernung unlöslicher Substanzen aus der Farbstofflösung.
- 45 2. Verfahren nach Anspruch 1, bei dem das Koagulations- bzw. Ausflockungsmittel wenigstens eine Substanz ist, die aus der Gruppe ausgewählt ist, die aus Aluminiumhydroxid, Aluminiumsulfat, Eisen(II)-sulfat, Eisen(III)-sulfat, Eisen(III)-chlorid und Eisen(III)-hydroxid, Calciumsulfat, Calciumcarbonat, Calciumhydroxid, $\text{Fe}_2(\text{SO}_4)_3$, FeCl_3 und Natriumaluminat besteht.
3. Verfahren nach Anspruch 1 oder 2, bei dem der Farbstoff in dem Lösungsmittel in einer Konzentration von 0,1 bis 10 Masse% gelöst ist.
- 50 4. Verfahren nach einem der vorhergehenden Ansprüche, bei dem das Koagulations- bzw. Ausflockungsmittel in einer Menge von 0,01 bis 1 Masseteil je 100 Masseteile des Farbstoffs zugesetzt wird.
5. Verfahren zur Herstellung einer Tinte, bei dem unter Anwendung eines Verfahrens nach einem der vorhergehenden Ansprüche eine gereinigte Farbstofflösung hergestellt und die behandelte Farbstofflösung zur Herstellung einer Tinte mit Wasser und/oder einem wasserlöslichen organischen Lösungsmittel vermischt wird.
- 55

Revendications

- 60 1. Procédé pour purifier une solution d'un colorant hydrosoluble dans de l'eau ou un mélange d'eau et d'un solvant organique hydrosoluble, comprenant les étapes consistant
- (a) à provoquer la floculation des substances colloïdales présentes dans la solution par addition d'un agent de floculation, et
- (b) à filtrer et/ou centrifuger la solution de colorant traitée pour éliminer les matières insolubles de la solution de colorant.
- 65

2. Procédé suivant la revendication 1, dans lequel l'agent de floculation est au moins une substance choisie dans le groupe comprenant l'hydroxyde d'aluminium, le sulfate d'aluminium, le sulfate ferreux, le sulfate ferrique, le chlorure ferrique et l'hydroxyde ferrique, le sulfate de calcium, le carbonate de calcium, l'hydroxyde de calcium, $\text{Fe}_2(\text{SO}_4)_3 \cdot \text{FeCl}_3$ et l'aluminate de sodium.

5 3. Procédé suivant la revendication 1 ou 2, dans lequel le colorant est dissous dans le solvant à une concentration de 0,1 à 10% en poids.

4. Procédé suivant l'une quelconque des revendications précédentes, dans lequel l'agent de floculation est ajouté en une quantité de 0,01 à 1 partie en poids, sur la base de 100 parties en poids du colorant.

10 5. Procédé de production d'une encre, consistant à préparer une solution de colorant purifiée en utilisant un procédé suivant l'une quelconque des revendications précédentes et à mélanger la solution de colorant traitée à de l'eau et/ou un solvant organique hydrosoluble, afin de préparer une encre.

15

20

25

30

35

40

45

50

55

60

65



* C L M S *