

SOFTWARE AIRCRAFT PART INSTALLATION SYSTEM

BACKGROUND

The present disclosure relates generally to aircraft and, in particular, to parts of an aircraft. Still more particularly, the present disclosure relates to a method and apparatus for installing software aircraft parts in an aircraft.

Modern aircraft are extremely complex. For example, an aircraft may have many types of electronic systems on board. A particular electronic system on an aircraft also may be referred to as a line replaceable unit (LRU). A line replaceable unit may take on various forms. A line replaceable unit may be, for example, without limitation, a flight management system, an autopilot, an in-flight entertainment system, a communication system, a navigation system, a flight controller, and a flight recorder.

A line replaceable unit may use software or programming to provide logic or control for various operations and functions. The software and other information used in a line replaceable unit are commonly treated as parts in the airline industry. For example, a software application for use in the line replaceable unit on an aircraft may be tracked separately from the line replaceable unit and referred to as a loadable software aircraft part (LSAP) or as a software aircraft part (SAP).

Software aircraft parts may be loaded into a line replaceable unit as part of the delivery of the aircraft from the manufacturer or as part of a maintenance operation. Software aircraft parts may be loaded by various techniques. For example, computer readable media, such as a floppy disk, a flash memory drive, or a digital versatile disk (DVD) may be taken to the aircraft and loaded into the computing or avionics system for the aircraft.

Other techniques may involve transmitting the software aircraft part to the computing system through a communications

link established between the computing system and the source of the software aircraft part. In yet other examples, a portable data processing system, such as a laptop, may be carried to the aircraft to transfer the software aircraft part.

5 Different aircraft may require different software aircraft parts. For example, different types of aircraft may require different software aircraft parts. As another example, specific aircraft of the same type also may require different software aircraft parts. For example, a particular commercial aircraft
10 may have different versions including various parts from different manufacturers. With this example, one version of this aircraft may use General Electric engines while another version of the aircraft may use Rolls Royce engines. A software aircraft part designed for a line replaceable unit used to
15 control parameters for engines, such as thrust settings, may be different for these different versions of the particular commercial aircraft. As a result, software aircraft parts may be specific for a particular aircraft even within the same type or model.

20 Currently, operators verify that a software aircraft part is appropriate for a particular target aircraft based on an operator checking documents about the software aircraft part to ensure that the target aircraft is an appropriate aircraft for the software aircraft part. Once the appropriate software
25 aircraft part has been identified for a target aircraft, the software aircraft part may be placed on a media for transport to the aircraft. The media may be on a maintenance laptop that is carried by a maintenance operator to the aircraft.

 While in the aircraft, the maintenance operator verifies
30 that the part is the correct part for the aircraft and installs the software aircraft part after verifying that the part is the correct one for the aircraft. This type of process is cumbersome and requires careful checking of software aircraft

parts to ensure that the proper software aircraft part reaches the appropriate target aircraft.

Therefore, it would be desirable to have a method and apparatus that take into account at least some of the issues
5 discussed above, as well as other possible issues.

SUMMARY

In one illustrative embodiment, a method for installing a software aircraft part in an aircraft is presented. A command
10 to install the software aircraft part is received. A determination is made as to whether the software aircraft part is present in the aircraft. A third party verifies that the software aircraft part is to be installed when the software aircraft part is present in the aircraft. The third party is in
15 a location remote to the aircraft. An installation of the software aircraft part in the aircraft is performed when the software aircraft part is present in the aircraft and the software aircraft part is verified for the installation. The aircraft operates with the software aircraft part installed in
20 the aircraft.

In another illustrative embodiment, another method for installing a software aircraft part in an aircraft is presented. The software aircraft part is sent to the aircraft. A command is sent to the aircraft to install the software aircraft part.
25 A request is received from the aircraft to verify an installation of the software aircraft part. A determination is made as to whether the software aircraft part should be installed based on the request. A confirmation that the software aircraft part should be installed when the installation
30 of the software aircraft part is verified is sent. The software aircraft part is installed on the aircraft when the confirmation is received by the aircraft.

In yet another illustrative embodiment, an apparatus comprises a part installer that receives a command to install a

software aircraft part. The part installer determines whether the software aircraft part is present in an aircraft. The part installer also verifies with a third party that the software aircraft part is to be installed when the software aircraft part is present in the aircraft in which the third party is in a location remote to the aircraft. The part installer also installs the software aircraft part in the aircraft when the software aircraft part is present in the aircraft and the software aircraft part is verified for installation. The aircraft operates with the software aircraft part installed in the aircraft.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of a block diagram of a software aircraft part installation environment in accordance with an illustrative embodiment;

Figure 2 is an illustration of message flow between a part installer and a third party for installing a software part in accordance with an illustrative embodiment;

Figure 3 is an illustration of a command in the form of a block diagram in accordance with an illustrative embodiment;

Figure 4 is an illustration of a verification message in the form of a block diagram in accordance with an illustrative embodiment;

Figure 5 is an illustration of a response in the form of a block diagram in accordance with an illustrative embodiment;

Figure 6 is an illustration of a confirmation message sent by a part installer after installing a software aircraft part in the form of a block diagram in accordance with an illustrative embodiment;

Figure 7 is an illustration of metadata generated from an installation of a software aircraft part in the form of a block diagram in accordance with an illustrative embodiment;

Figure 8 is an illustration of a flowchart of a process for installing a software aircraft part in accordance with an illustrative embodiment;

Figure 9 is an illustration of a flowchart of a process for installing a software aircraft part in accordance with an illustrative embodiment;

Figure 10 is an illustration of a flowchart of a verification process in accordance with an illustrative embodiment;

Figure 11 is an illustration of a flowchart of a process for proposing installation of a software aircraft part in accordance with an illustrative embodiment;

Figure 12 is an illustration of a flowchart of a process for installing a software aircraft part in accordance with an illustrative embodiment; and

Figure 13 is an illustration of a data processing system in the form of a block diagram in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

The illustrative embodiments recognize and take into account one or more different considerations. For example, the

illustrative embodiments recognize and take into account that the amount of time needed for maintenance personnel to install software aircraft parts in an aircraft is much more time-consuming and expensive than desired.

5 The illustrative embodiments also recognize and take into account that having personnel from a third party providing software to an operator entering the different aircraft to perform installation of software aircraft parts increases the scheduling complexity for maintaining the aircraft. For
10 example, maintenance personnel may travel to locations to install software aircraft parts. In other illustrative examples, the aircraft may have software aircraft parts installed only in selected locations during operation of the aircraft.

15 Thus, the illustrative embodiments provide a method and apparatus for installing software aircraft parts on an aircraft. In one illustrative example, a process is present for installing a software aircraft part in an aircraft. The process receives a command to install the software aircraft part. The process
20 determines whether the software aircraft part is present in the aircraft. The process verifies with a third party that the software aircraft part is to be installed. The third party is in a location remote to the aircraft for the verification. The process installs the software aircraft part in the aircraft when
25 the software aircraft part is present in the aircraft and the software aircraft part is verified for installation, wherein the aircraft operates with a software aircraft part installed in the aircraft.

 With reference now to the figures and in particular with
30 reference to **Figure 1**, an illustration of a block diagram of a software aircraft part installation environment is depicted in accordance with an illustrative embodiment. In this illustrative example, software aircraft part installation environment 100 includes aircraft 102. Aircraft 102 may take

different forms. For example, aircraft 102 may be a commercial airplane, a rotorcraft, a military aircraft, a helicopter, an unmanned aircraft, or some other type of aircraft.

As depicted, aircraft 102 has computer system 104 on which
5 software aircraft parts 106 may be located. A software aircraft part may be, for example, a program, a configuration file, a database, a manual, a checklist, an application, or some other suitable type of software that may be used in aircraft 102.

In this illustrative example, computer system 104 is one or
10 more computers. When more than one computer is present in computer system 104, the computers may communicate with each other using communications media such as a network. As depicted, the computers may include a flight management system, an electronic flight bag, a navigation system, an in-flight
15 entertainment system, an environmental control system, a general purpose network file server, and other suitable types of systems in aircraft 102 that employed the computers.

The network may include at least one of wired links, optical links, wireless links, or other suitable types of links
20 over which information may be sent. As used herein, the phrase "at least one of," when used with a list of items, means different combinations of one or more of the listed items may be used and only one of each item in the list may be needed. In other words, at least one of means any combination of items and
25 number of items may be used from the list but not all of the items in the list are required. The item may be a particular object, thing, or a category.

For example, without limitation, "at least one of item A, item B, or item C" may include item A, item A and item B, or
30 item B. This example also may include item A, item B, and item C or item B and item C. Of course, any combinations of these items may be present. In some illustrative examples, "at least one of" may be, for example, without limitation, two of item A;

one of item B; and ten of item C; four of item B and seven of item C; or other suitable combinations.

In the illustrative example, software aircraft parts 106 originate from one or more of third parties 110. As depicted, 5 third parties 110 are entities other than operator 112 in aircraft 102. Operator 112 may be, for example, an airline, a delivery company, a government entity, or some other entity.

For example, software aircraft part 114 in software aircraft parts 106 may be supplied by third party 116 in third 10 parties 110. Third party 116 may be selected from one of an aircraft manufacturer, a vendor, a distributor, a manufacturer of aircraft parts, or some other suitable entity. Operator 112 may be an airline in this illustrative example.

As depicted, part installer 118 is a component that may be 15 located in computer system 104. Part installer 118 installs software aircraft parts 106 in aircraft 102. In particular, part installer 118 installs software aircraft parts 106 in computer system 104.

Part installer 118 may be implemented in software, 20 hardware, firmware or a combination thereof. When software is used, the operations performed by part installer 118 may be implemented in program code configured to run on hardware, such as a processor unit. When firmware is used, the operations performed by part installer 118 may be implemented in program 25 code and data and stored in persistent memory to run on a processor unit. When hardware is employed, the hardware may include circuits that operate to perform the operations in part installer 118.

In the illustrative examples, the hardware may take the 30 form of a circuit system, an integrated circuit, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device may be configured to perform the number of operations.

The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. Additionally, the processes may be implemented in organic components integrated with inorganic components and may be comprised entirely of organic components excluding a human being. For example, the processes may be implemented as circuits in organic semiconductors.

As depicted in this illustrative example, software aircraft part 114 is located in storage device 120 in computer system 104 but not installed in computer system 104. In other words, software aircraft part 114 has been uploaded or transferred onto computer system 104 to be installed in computer system 104. Software aircraft part 114 may still be archived, activated, or in some other state where software aircraft part 114 is not usable in computer system 104 until software aircraft part 114 is installed.

In these illustrative examples, the installation of software aircraft part 114 is formed by part installer 118 without needing a human operator in aircraft 102 performing operations to install software aircraft part 114 in computer system 104 in aircraft 102. As depicted, part installer 118 installs software aircraft part 114 in computer system 104 in aircraft 102 in a manner that reduces the amount of time and effort for installation as compared to currently used techniques in which a maintenance operator performs the installation in the aircraft. In this illustrative example, part installer 118 receives command 122 to install software aircraft part 114. In this illustrative example, command 122 is received from third party 116.

When command 122 is received, part installer 118 determines whether command 122 is authentic. In determining whether

command 122 is authentic, part installer 118 determines whether command 122 was actually sent by third party 116. The authentication may be performed using various techniques such as, for example, using a cyclic redundancy check, comparing
5 certificates, and other suitable techniques.

When the command is determined to be authentic, part installer 118 determines whether software aircraft part 114 is present in aircraft 102. If software aircraft part 114 is not present, then the installation is not performed. Part installer
10 118 verifies with third party 116 that software aircraft part 114 is to be installed when software aircraft part 114 is present in aircraft 102. In this illustrative example, third party 116 is in location 124 remote to aircraft 102. In other words, human operators for third party 116 are not present in
15 aircraft 102. The presence of human operators is not necessary for the installation of software aircraft part 114.

Next, part installer 118 installs software aircraft part 114 in aircraft 102 when software aircraft part 114 is present in aircraft 102 and the software aircraft part is verified for
20 installation. In this manner, aircraft 102 may operate with software aircraft part 114 installed in aircraft 102.

With part installer 118, the installation of software aircraft part 114 occurs without the use of human operators located in aircraft 102. In this manner, sending maintenance
25 personnel to each aircraft owned or operated by operator 112 is unnecessary. Through the use of part installer 118, the installation of software aircraft part 114 in some or all of a fleet of aircraft may be performed in a less time-consuming and less expensive manner as compared to current techniques in which
30 maintenance personnel travel to each aircraft in which a software aircraft part is to be installed.

With reference now to **Figure 2**, an illustration of message flow between a part installer and a third party for installing a software part is depicted in accordance with an illustrative

embodiment. The message flow illustrated in this figure occurs between part installer 118 and third party 116. In this example, the messages sent to and sent by third party 116 occur using computer system 200 at third party 116. In this
5 illustrative example, computer system 200 is one or more computers.

In this example, third party 116 sends a command to part installer 118 (message M1). The command is information that tells part installer 118 to install software aircraft part 114
10 in aircraft 102. The command in message M1 may be, for example, command 122 in Figure 1.

In response to receiving the command, part installer 118 sends a verification message to third party 116 (message M3). The verification message is a request to make sure software
15 aircraft part 114 should be installed in aircraft 102.

Third party 116 verifies whether software aircraft part 114 should be installed in aircraft 102 in response to receiving the verification message. After performing the verification, third party 116 sends a response back to part installer 118 (message
20 M5). The response includes an indication as to whether software aircraft part 114 should be installed.

If the response indicates that software aircraft part 114 should be installed, part installer 118 installs software aircraft part 114 in aircraft 102. After the installation of
25 software aircraft part 114, part installer 118 sends a confirmation message to third party 116 indicating that software aircraft part 114 has been installed (message M7). The confirmation message contains metadata about the installation of software aircraft part 114. This metadata may be a flag or code
30 that software aircraft part 114 has been installed or may include other information about the installation of software aircraft part 114 in addition to the flag or code.

On the other hand, if the response in message M5 indicates that the software aircraft part should not be installed, no

installation is performed. Confirmation message **M7** may be sent back with a confirmation that no installation was performed by part installer **118**.

5 All of the messages illustrated in **Figure 2** may be sent between part installer **118** and third party **116** in a secure manner. For example, the message may be sent using any available techniques to reduce at least one of spoofing messages, altering messages without detection, intercepting messages, or other undesired access to the messages that are
10 sent between part installer **118** and third party **116**. For example, at least one of hypertext transfer protocol secure (HTTPS), transport layer security (TLS), secure sockets layer (SSL), a virtual private network, encryption, a digital certificate, a digital signature, a quantum key, or some other
15 suitable mechanism may be used.

Figures 3-7 are illustrative examples of messages that show one manner in which messages may be implemented that are sent between part installer **118** and third party **116** as part of an installation process of software aircraft part **114**. Turning
20 first to **Figure 3**, an illustration of a command is depicted in the form of a block diagram in accordance with an illustrative embodiment. In this example, command **300** is an example of one implementation of a command send in message **m1** in **Figure 2**.

As shown in this example, command **300** includes fields. In
25 this illustrative example, the fields are third party identifier **302**, software part identifier **304**, install command **306**, and digital certificate **308**.

Third party identifier **302** identifies third party **116** in **Figures 1-2** as the party originating the command. In this
30 example, third party identifier **302** may be at least one of name of the third party **116**, a number identifying third party **116**, or some other suitable identifier.

Next, software part identifier **304** indicates the software aircraft part to be installed. In the illustrative example,

software part identifier 304 may be at least one of a name of software part identifier 304, a serial number, a part number, a version identifier, or some other information that identifies software aircraft part 114. As depicted, digital certificate 308 is used to verify that command 300 did come from third party 116.

With reference now to **Figure 4**, an illustration of a verification message is depicted in the form of a block diagram in accordance with an illustrative embodiment. Verification message 400 is an example of one implementation for the verification message in message M3 as shown in this figure.

As depicted, verification message 400 includes a number of different fields. In this illustrative example, verification message 400 includes operator identifier 402, software aircraft part identifier 404, aircraft identifier 406, current version 408, new version 410, and digital certificate 412.

Operator identifier 402 identifies an operator of aircraft 102. Operator identifier 402 may be a name of the operator, a number identifying the operator, or some other information that indicates the identification of the operator.

In the illustrative example, software aircraft part identifier 404 identifies software aircraft part 114 as the software aircraft part to be installed in aircraft 102 seen in **Figure 1**. Aircraft identifier 406 identifies aircraft 102 in which software aircraft part 114 is to be installed. In this illustrative example, aircraft identifier 406 may be, for example, a tail number, a serial number, or some other information that identifies aircraft 102.

Current version 408 is the current version of software aircraft part 114 that is installed in aircraft 102. If the version of software aircraft part 114 is not already present on aircraft 102, current version 408 may be a null value or a flag that indicates that the install adds software aircraft part 114

as a new software aircraft part rather than upgrading or changing the version of an existing software aircraft part.

New version 410 is the version of the software aircraft part 114 that is to be installed in aircraft 102. This new
5 version may be a later version or an earlier version of software aircraft part 114. In some cases, an earlier version of the software aircraft part 114 may be desirable for performance reasons. Digital certificate 412 is used to verify that verification message M3 was sent by part installer 118 in Figure
10 2.

With reference now to Figure 5, an illustration of a response is depicted in the form of a block diagram in accordance with an illustrative embodiment. In this example, response 500 is an example of one implementation of a response
15 sent in message M5 in Figure 2.

As illustrated in the example, response 500 includes a number of fields. As depicted, response 500 includes third party identifier 502, software part identifier 504; installation indicator 506, and digital certificate 508.

20 In the illustrative example, third party identifier 502 identifies third party 116 as the party originating response 500. Software part identifier 504 indicates the software aircraft part for which the verification was requested.

Installation indicator 506 indicates whether software
25 aircraft part 114 should be installed. Installation indicator 506 may be, for example, a flag, a true or false indication, a code, or some other type of indication as to whether software aircraft part 114 should be installed. In this particular example, digital certificate 508 is used to verify whether
30 response 500 was sent by third party 116.

Turning next to Figure 6, an illustration of a confirmation message sent by a part installer after installing a software aircraft part is depicted in the form of a block diagram in accordance with an illustrative embodiment. In this depicted

example, confirmation message 600 includes a number of fields. As illustrated, confirmation message 600 includes operator identifier 602, aircraft identifier 604, metadata 606, and digital certificate 608.

5 Operator identifier 602 identifies the operator of aircraft 102. As depicted, aircraft identifier 604 identifies aircraft 102 on which operations to install software aircraft part 114 was performed by part installer 118 in Figure 1.

10 Metadata 606 is information about at least one of the operations performed by part installer 118, software aircraft part 114, or other suitable information. Digital certificate 608 is used to verify that confirmation message 600 was sent by part installer 118.

15 Turning next to Figure 7, an illustration of metadata generated from an installation of a software aircraft part is depicted in the form of a block diagram in accordance with an illustrative embodiment. An example of information in metadata 606 in Figure 6 is shown in this figure.

20 As depicted, metadata 606 includes a number of different types of information. This information relates to the installation of software aircraft part 114 in the depicted example. As illustrated, metadata 606 includes at least one of indication of success 702, version 704, log 706, use 708, or date of installation 710.

25 Indication of success 702 indicates whether software aircraft part 114 was installed successfully or if an error occurred while installing software aircraft part 114 in Figure 1. Version 704 is the version of software aircraft part 114 that was installed during the installation process. Log 706 is
30 a log of the installation of software aircraft part 114. Log 706 may identify steps such as components for software aircraft part 114 that were installed, removed, or both. Log 706 also may identify the different operations performed.

Use 708 is an indication of the use of software aircraft part 114 by computer system 104 in aircraft 102 in **Figure 1**. Using software aircraft part 114 in aircraft 102 means computer system 104 in aircraft 102 runs software aircraft part 114.

5 For example, after installation of version 704 of software aircraft part 114 in aircraft 102, use 708 may include at least one of a timestamp when version 704 of software aircraft part 114 is run by computer system 104, an amount of time that version 704 of software aircraft part 114 has been running in
10 computer system 104, a number of times version 704 of software aircraft part 114 has been run by computer system 104, a number of lines of code in software aircraft part 114 that have been run in computer system 104, or other suitable indications of use of software aircraft part 114 in the aircraft.

15 Date of installation 710 identifies when software aircraft part 114 was installed. Date of installation 710 may include a month, day, year, and time for the installation for software aircraft part 114.

20 The illustration of the different messages in **Figure 3-7** and the information in those messages have been described for purposes of illustrating one manner in which messages exchanged between part installer 118 and third party 116 may be implemented. These examples are not meant to limit the manner in which messages may be implemented or limit the types or
25 number of messages that may be sent between part installer 118 and third party 116 in these illustrative examples.

30 The illustration of software aircraft part installation environment 100 and the different components in this environment in **Figures 1-7** are not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be unnecessary. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be

combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

For example, one or more aircraft in addition to aircraft 102 may have software aircraft parts loaded into them using part installers located on the these additional aircraft. As another example, the different fields shown for data structures shown in **Figure 3-7** are only intended as examples and not as limitations to the manner in which the data structures may be implemented. For example, the messages may omit a digital certificate.

Instead, a virtual private network or some other mechanism may be used. As another example, aircraft identifier 604 in **Figure 6** may be part of metadata 606 rather than a separate field in confirmation message 600 in **Figure 6**.

With reference next to **Figure 8**, an illustration of a flowchart of a process for installing a software aircraft part is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 8** may be implemented in software aircraft part installation environment 100 in **Figure 1**. In particular, the operations in **Figure 8** may be implemented in part installer 118 in **Figure 1**.

The process begins by receiving a command to install the software aircraft part (operation 800). The process verifies whether the command is authentic (operation 802). The verification may be performed using a number of mechanisms. For example, a digital certificate may be checked, or some other suitable mechanism may be used. Another verification mechanism may be used that results in operation 802 transmitting a confirmation message to a trusted link or endpoint for the third party 116 to independently verify the originator of the command. If the command is not authentic, the process terminates.

Otherwise, the process then determines whether the software aircraft part is present in the aircraft (operation 804). If the software aircraft part is not present in aircraft, the process terminates.

Otherwise, the process verifies with a third party that the software aircraft part is to be installed when the software aircraft part is present in the aircraft (operation 806). In the illustrative example, the third party is in a location remote to the aircraft. In other words, personnel for the third party are not needed in the aircraft to perform the installation process.

The process then determines whether the software aircraft part has been verified as a part to be installed in the aircraft (operation 808). If the software aircraft part has not been verified for installation, the process terminates.

Otherwise, the process performs the installation of the software aircraft part in the aircraft when the software aircraft part is present in the aircraft and the software aircraft part is verified for installation (operation 810). In this illustrative example, the installation may be performed when the verification is received or some other time. For example, the process may set a schedule to install the software aircraft part and install the software aircraft part based on the schedule.

A determination is then made as to whether the software aircraft part is installed during the installation process (operation 812). If the software aircraft part is installed, the process sends a confirmation message to the third party indicating that the software aircraft part has been installed after installing the software aircraft part in the aircraft (operation 814), with the process terminating thereafter.

In this illustrative example, the confirmation message includes metadata generated in the aircraft that describes at least one of a version of a software aircraft part that was installed, a log of an installation of the software aircraft part, a use of software aircraft part installed in the aircraft, or other information relating to the software aircraft part.

As a result of installation, the aircraft operates with a software aircraft part installed in the aircraft. With a new software aircraft part or a new version for existing software aircraft part installed using this process, the aircraft may
5 have a desired level of performance. This performance may be, for example, for at least one of fuel efficiency, passenger comfort, passenger experience, aircraft health monitoring, or other desired types of performance.

With reference again to operation 812, if the software
10 aircraft part was not installed during the installation process, the process sends a confirmation message to the third party indicating that the software aircraft part has not been installed in the aircraft (operation 816), with the process terminating thereafter.

15 In this case, the confirmation message indicates that installation process was performed, but the decision was made not to install the software aircraft part during the process. For example, the software aircraft part may have been corrupted, or otherwise unusable, for installation in the aircraft. In
20 another example, the software aircraft part may be the incorrect version for installation.

Turning next to **Figure 9**, an illustration of a flowchart of a process for installing a software aircraft part is depicted in accordance with an illustrative embodiment. The process
25 illustrated in **Figure 9** is an example of an implementation of operation 810 in **Figure 1**.

The process begins by determining whether the software aircraft part present in the aircraft is valid (operation 900). The determination as to whether the software aircraft present is
30 valid may be based on at least one of a cyclic redundancy check value for the software aircraft part, a certificate of authentication for the software aircraft part, a compatibility of the version of the software aircraft part with other aircraft

parts in the aircraft, an amount of time the software aircraft part has been in the aircraft, or some other suitable factor.

If the software aircraft part is identified as being valid, the process installs the software aircraft part (operation 902).

5 The process then generates metadata with respect to the installation of the software aircraft part (operation 904), with the process terminating thereafter.

With reference again to operation 900, if the software aircraft part has been identified as invalid, an indication is
10 included in the metadata generated in the aircraft indicating that the command received to install the software aircraft part is not performed (operation 906), with the process terminating thereafter. In other words, the operation for installing the software aircraft part may result in not installing the software
15 aircraft part. The termination of this process results in other operations in **Figure 8** being performed.

Turning now to **Figure 10**, an illustration of a flowchart of a verification process is depicted in accordance with an illustrative embodiment. Operations illustrated in **Figure 10**
20 are example of an implementation for operation 808 in **Figure 8**.

The process begins by sending a verification message to the third party to confirm the command to install the software aircraft part (operation 1000). In this illustrative example, the verification message includes an identification of a current
25 version of the software aircraft part installed on the aircraft and an identification of a new version of the software aircraft part to be installed on the aircraft. Of course, other information may be present in the verification message.

The process then receives a response to the verification
30 message from the third party (operation 1002), with the process terminating thereafter. The response indicates whether the command to install the software aircraft part should be followed.

Turning next to **Figure 11**, an illustration of a flowchart of a process for proposing installation of a software aircraft part is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 11** may be implemented in third party 116 in **Figure 1**.

The process begins by proposing an update of the software aircraft part for a group of aircraft to an operator of the aircraft (operation 1100). In the illustrative example, a "group of" as used herein with reference to items means one or more items. For example, a group of aircraft is one or more aircraft. The group of aircraft may be all of the aircraft for the operator. In other illustrative examples, the group of aircraft may be a subset of the aircraft that may be used for quality control or testing purposes.

A determination is made as to whether the proposed update is accepted by the operator (operation 1102). If the proposed update is not accepted, the process terminates. Otherwise, the process sets a schedule to update a group of aircraft including the aircraft when an approval is received from the operator of the aircraft (operation 1104).

The process then sends the software aircraft part to the group of aircraft (operation 1106), with the process terminating thereafter. In these illustrative examples, operation 1106 may be an electronic distribution in which the software aircraft part is sent over a communications link from a third party to each of the aircraft. In other illustrative examples, the software aircraft part may be loaded onto the aircraft through the data processing system carried by a maintenance person. This type of loading of a software aircraft part may be performed when other normal maintenance occurs.

As a result, the software aircraft part is ready for installation based on a desired schedule of when the software aircraft part should be installed. For example, if the software aircraft part is for a new in-flight entertainment system, the

installation of the software aircraft part may not occur until the in-flight entertainment system is installed in the aircraft.

With reference next to **Figure 12**, an illustration of a flowchart of a process for installing a software aircraft part is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 12** may be implemented in third party 116 in **Figure 1**. In particular, the process may be implemented using computer system 200 in **Figure 2** for third party 116. For example, the operations in the process may be performed by a program running in computer system 200 in **Figure 2**.

The process begins by sending the software aircraft part to the aircraft (operation 1200). The process then sends a command to the aircraft to install the software aircraft part (operation 1202).

The process receives a request from the aircraft to verify an installation of the software aircraft part (operation 1204). In this example, the request takes the form of a verification message received from the part installer in the aircraft in which the software aircraft part is to be installed.

The process then verifies whether the software aircraft part should be installed based on the request (operation 1206). This verification may be performed in computer system 200 by a software process, a human operator, or some combination thereof. In other words, the human operator may verify whether the software aircraft part should be installed. This decision, however, may be made at another location other than the aircraft. As a result, the human operator may perform verifications for many aircraft without traveling to the aircraft.

If the verification performed in operation 1206 indicates the software aircraft part is to be installed, a response is sent in the form of a confirmation that the software aircraft part should be installed when the installation of the software

aircraft part is verified (operation 1208), with the process terminating thereafter. As result, the software aircraft part is installed on the aircraft when the confirmation is received by the aircraft. With reference again to operation 1206, if the
5 verification indicates that the software aircraft part should not be installed, the response is sent with an indication that installation should not occur (operation 1210), with the process terminating thereafter.

The flowcharts and block diagrams in the different depicted
10 embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative embodiment. In this regard, each block in the flowcharts or block diagrams may represent at least one of a module, a segment, a function, or a portion of an
15 operation or step. For example, one or more of the blocks may be implemented as program code, in hardware, or a combination of the program code and hardware. When implemented in hardware, the hardware may, for example, take the form of integrated circuits that are manufactured or configured to perform one or
20 more operations in the flowcharts or block diagrams. When implemented as a combination of program code and hardware, the implementation may take the form of firmware.

In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may
25 occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the
30 illustrated blocks in a flowchart or block diagram.

Turning now to **Figure 13**, an illustration of a data processing system in the form of a block diagram is depicted in accordance with an illustrative embodiment. Data processing system 1300 may be used to implement one or more computers or

other data processing devices in computer system 104 in **Figure 1**. Additionally, data processing system 1300 may be used to implement computer system 200 and third party 116 as illustrated in **Figure 2**.

5 As depicted, data processing system 1300 includes communications framework 1302, which provides communications between processor unit 1304, storage devices 1306, communications unit 1308, input/output unit 1310, and display 1312. In some cases, communications framework 1302 may be
10 implemented as a bus system.

Processor unit 1304 is configured to execute instructions for software to perform a number of operations. Processor unit 1304 may comprise a number of processors, a multi-processor core, and/or some other type of processor, depending on the
15 implementation. In some cases, processor unit 1304 may take the form of a hardware unit, such as a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware unit.

Instructions for the operating system, applications, and/or
20 programs run by processor unit 1304 may be located in storage devices 1306. Storage devices 1306 may be in communication with processor unit 1304 through communications framework 1302. As used herein, a storage device, also referred to as a computer readable storage device, is any piece of hardware capable of
25 storing information on a temporary and/or permanent basis. This information may include, but is not limited to, data, program code, and other information.

Memory 1314 and persistent storage 1316 are examples of storage devices 1306. Memory 1314 may take the form of, for
30 example, a random access memory or some type of volatile or non-volatile storage device. Persistent storage 1316 may comprise any number of components or devices. For example, persistent storage 1316 may comprise a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some

combination of the above. The media used by persistent storage 1316 may or may not be removable.

Communications unit 1308 allows data processing system 1300 to communicate with other data processing systems and devices.

5 Communications unit 1308 may provide communications using physical communications links, wireless communications links, or some combination thereof.

10 Input/output unit 1310 allows input to be received from and output to be sent to other devices connected to data processing system 1300. For example, input/output unit 1310 may allow user input to be received through a keyboard, a mouse, and/or some other type of input device. As another example, input/output unit 1310 may allow output to be sent to a printer connected to data processing system 1300.

15 Display 1312 is configured to display information to a user. Display 1312 may comprise, for example, without limitation, a monitor, a touch screen, a laser display, a holographic display, a virtual display device, or some other type of display device.

20 In this illustrative example, the processes of the different illustrative embodiments may be performed by processor unit 1304 using computer-implemented instructions. These instructions may be referred to as program code, computer usable program code, or computer readable program code and may be read and executed by one or more processors in processor unit 1304.

25 In these examples, program code 1318 is located in a functional form on computer readable media 1320, which is selectively removable, and may be loaded onto or transferred to data processing system 1300 for execution by processor unit 1304. Program code 1318 and computer readable media 1320 together form computer program product 1322. In this illustrative example, computer readable media 1320 may be computer readable storage media 1324 or computer readable signal media 1326.

Computer readable storage media 1324 is a physical or tangible storage device used to store program code 1318 rather than a medium that propagates or transmits program code 1318. Computer readable storage media 1324 may be, for example, without limitation, an optical or magnetic disk or a persistent storage device that is connected to data processing system 1300.

Alternatively, program code 1318 may be transferred to data processing system 1300 using computer readable signal media 1326. Computer readable signal media 1326 may be, for example, a propagated data signal containing program code 1318. This data signal may be using at least one of an electromagnetic signal, an optical signal, or some other type of signal that can be transmitted over physical communications links, wireless communications links, or both.

The illustration of data processing system 1300 in **Figure 13** is not meant to provide architectural limitations to the manner in which the illustrative embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system that includes components in addition to or in place of those illustrated for data processing system 1300. Further, components shown in **Figure 13** may be varied from the illustrative examples shown.

Thus, one or more illustrative examples provide a method and apparatus for installing software aircraft parts in an aircraft. The process allows for the installation of software aircraft parts without a human operator traveling to and being present in each aircraft in which the software aircraft part is to be installed.

This solution in the illustrative examples is scalable across an entire fleet of aircraft. Further, with the number of software aircraft parts and periodic updates of the software aircraft parts, the amount of time and effort needed to maintain software aircraft parts for customers such as airlines may be reduced. Further, with the reduction in time needed to install

and maintain software aircraft parts, the availability of aircraft carrying passengers, cargo, or some combination thereof may be increased.

5 In this manner, a third party may more efficiently provide services to a customer operating an aircraft. Further, updates to software aircraft parts and new software aircraft parts that may be desired for an aircraft may be deployed much more quickly as compared to currently used processes in which maintenance personnel carry aircraft parts to the aircraft, or are present
10 in the aircraft to perform installation of the aircraft part.

The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and
15 variations will be apparent to those of ordinary skill in the art. For example, although the different illustrative examples have been described with respect to a third party, these processes also may be implemented by an operator of the aircraft. Further, different illustrative embodiments may
20 provide different features as compared to other desirable embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for
25 various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

1. A method for installing a software aircraft part in an aircraft, the method comprising:

5 receiving a command to install the software aircraft part;
determining whether the software aircraft part is present in the aircraft;

verifying with a third party that the software aircraft part is to be installed when the software aircraft part is present in the aircraft, wherein the third party is in a location remote to the aircraft; and

performing an installation of the software aircraft part in the aircraft when the software aircraft part is present in the aircraft and the software aircraft part is verified for the installation, wherein the aircraft operates with the software aircraft part installed in the aircraft.

2. The method of claim 1 further comprising:

verifying whether the command is authentic.

3. The method of claim 1, wherein the verifying step comprises:

25 sending a verification message to the third party to confirm the command to install the software aircraft part; and
receiving a response to the verification message from the third party, wherein the response indicates whether the command to install the software aircraft part should be followed.

4. The method of claim 3, wherein the verification message includes an identification of a current version of the software aircraft part installed on the aircraft and an identification of a new version of the software aircraft part to be installed on the aircraft.

5. The method of any one of claims 1 to 4 further comprising:
sending a confirmation message to the third party
indicating that the software aircraft part has been installed
after installing the software aircraft part in the aircraft.

5

6. The method of claim 5, wherein the confirmation message
includes metadata generated in the aircraft that describes at
least one of a version of the software aircraft part that was
installed, a log of the installation of the software aircraft
part, and a use of the software aircraft part installed in the
aircraft.

10

7. The method of claim any one of claims 1 to 6, wherein the
installing step comprises:

15

setting a schedule to install the software aircraft part;
and

installing the software aircraft part based on the
schedule.

20

8. The method of any one of claims 1 to 7 further comprising:
proposing an update of the software aircraft part to an
operator of the aircraft; and

setting a schedule to update a group of aircraft including
the aircraft when an approval is received from the operator of
the aircraft.

25

9. The method of any one of claims 1 to 6, wherein the
installing step comprises:

determining whether the software aircraft part present in
the aircraft is valid based on at least one of a cyclic
redundancy check value for the software aircraft part, a
certificate of authentication for the software aircraft part, a
compatibility of a version of the software aircraft part with

30

other aircraft parts in the aircraft, or an amount of time the software aircraft part has been in the aircraft; and

installing the software aircraft part when the software aircraft part is identified as valid.

5

10. The method of claim 9 further comprising:

adding an indication to metadata generated in the aircraft indicating that the command received to install the software aircraft part in the aircraft is not performed when the software aircraft part has been identified as invalid.

10

11. A method for installing a software aircraft part in an aircraft, the method comprising:

sending the software aircraft part to the aircraft;

15

sending a command to the aircraft to install the software aircraft part;

receiving a request from the aircraft to verify an installation of the software aircraft part;

determining whether the software aircraft part should be installed based on the request; and

20

sending a confirmation that the software aircraft part should be installed when the installation of the software aircraft part is verified, wherein the software aircraft part is installed on the aircraft when the confirmation is received by the aircraft.

25

12. The method of claim 11, wherein the determining step is performed by an operator for a third party selected from at least one of a program running on a computer system or a human operator.

30

13. An apparatus comprising:

a part installer that receives a command to install a software aircraft part; determines whether the software aircraft part is present in an aircraft; verifies with a third party that

the software aircraft part is to be installed when the software aircraft part is present in the aircraft in which the third party is in a location remote to the aircraft; and installs the software aircraft part in the aircraft when the software aircraft part is present in the aircraft and the software aircraft part is verified for installation, wherein the aircraft operates with the software aircraft part installed in the aircraft.

10 14. The apparatus of claim 13 further comprising:

a computer system in the aircraft, wherein the part installer is located in the computer system.

15. The apparatus of claim 13 or 14 further comprising:

15 verifying whether the command is authentic.

16. The apparatus of any one of claims 13 to 15, wherein in verifying with the third party that the software aircraft part is to be installed, the part installer sends a message to the third party to confirm the command to install the software aircraft part; and receives a response to the message from the third party, wherein the response indicates whether the command to install the software aircraft part should be followed.

25 17. The apparatus of claim 16, wherein the message includes an identification of a current version of the software aircraft part installed on the aircraft and an identification of a new version of the software aircraft part to be installed on the aircraft.

30 18. The apparatus of claim 17, wherein the message includes metadata generated in the aircraft that describes at least one of a version of the software aircraft part that was installed, a

log of the installation of the software aircraft part, and a use of the software aircraft part installed in the aircraft.

19. The apparatus of any one of claims 13 to 18, wherein the
5 part installer sends a message to the third party indicating that the software aircraft part has been installed after installing the software aircraft part in the aircraft.

20. The apparatus of any one of claims 13 to 18, wherein the
10 part installer installs the software aircraft part in the aircraft when the software aircraft part is present in the aircraft and the software aircraft part is verified for installation, the part installer sets a schedule to install the software aircraft part and installs the software aircraft part
15 based on the schedule.