

METHOD FOR CAPTURING CARBON DIOXIDE IN POWER STATION FLUE GAS AND DEVICE THEREFOR

FIELD OF THE INVENTION

[0001] The invention relates to the field of emission reduction and resource utilization of carbon dioxide from flue gas of a power plant boiler, and more particularly to a method and an apparatus for collecting carbon dioxide from flue gas.

BACKGROUND OF THE INVENTION

[0002] In the 21st century, one of the greatest challenges facing humanity is the greenhouse effect caused by the emissions of greenhouse gas, which causes global warming and climate change and comprehensively affects the ecology, economics, society, and other global environment. Carbon dioxide is the main product from the combustion of the organic substance and fossil fuels, and is also considered as one of the main components contributing to the global warming and the greenhouse effect, accounting for about 2/3 of the total greenhouse gas. At present, the global annual carbon dioxide emissions rose to 30.6 billion tons in 2010. China has become the superpower of carbon dioxide emissions, and the emissions are still increasing.

[0003] In November, 2009, Chinese government solemnly committed himself to the world that the carbon dioxide emissions per unit of GDP in 2020 should be decreased by 40% to 45% compared to the year of 2005. The flue gas from power plants is a longterm, stable, and concentrated emission source of CO₂, which is the top priority for reducing CO₂ emissions. To develop new technologies and devices for reducing CO₂ emissions from power plant flue gas can free the China's economic development from the effects of carbon emission targets, and bring tremendous social and economic benefits.

[0004] Several methods for capturing CO₂ have been developed. A chemical absorption

method is widely applied in industries, and the principle of the chemical absorption method is as follows: CO_2 in the flue gas is prone to react with and be absorbed by a chemical solvent. A rich solution of the chemical solvent is acquired after absorbing CO_2 to an equilibrium state; then the rich solution is introduced into a regeneration tower, heated and decomposed for releasing CO_2 gas and being transformed into a barren solution. After that, the barren solution is recycled to absorb CO_2 from the flue gas. Thus, by circulating an absorbent solution between an absorption tower and the regeneration tower, CO_2 in the flue gas is captured, separated, and purified. Currently, the chemical absorption method using an amino alcohol solution to absorb CO_2 is the most widely applied method, which specifically includes: an MEA (monoethanolamine) method, an MDEA, and a mixed organic amines method. In productive practice, it has been proved that, although the chemical absorption method using the amino alcohol solution which has been applied for about twenty years in chemical field has the characteristics of fast absorption speed, strong absorption ability, it still has the following defects when it is utilized in treating flue gas from power plant: 1) the oxidative degradation of the amino alcohol affects a long term and stable operation of the apparatus, and the solution consumption is large; 2) the apparatus is seriously corroded; and 3) MEA generally has a concentration of less than 20%, and thus the CO_2 absorption rate is low, but the energy consumption in regeneration is high. All these reasons account for the high cost of the method for collecting carbon dioxide by using amino alcohol.

SUMMARY OF THE INVENTION

[0005] In view of the abovedescribed problems, it is one objective of the invention to provide a method and an apparatus for collecting carbon dioxide in power station flue gas. The method is characterized in high collecting efficiency, low energy consumption, and simple process flow.

[0006] To achieve the above objective, in accordance with one embodiment of the invention, there is provided a method for collecting carbon dioxide from flue gas of a power plant, the method comprising the following steps:

[0007] 1) providing an organic amine and an ionic liquid in a molar ratio of (11.1):1, mixing the organic amine, the ionic liquid, and water to obtain an aqueous solution of a composite absorbent having a concentration of between 20 and 40 wt. %;

[0008] using the aqueous solution of the composite absorbent comprising the organic amine and the ionic liquid as a CO₂ absorbent, evenly spraying the aqueous solution of the composite absorbent into the flue gas from a rear part of a power plant boiler after dust removal and desulfurization to allow the flue gas flowing upwardly to fully contact with the downwardly sprayed aqueous solution of the composite absorbent and to allow CO₂ in the flue gas to react with the composite absorbent whereby absorbing CO₂.

Principle of the absorption of CO₂ by the composite absorbent is as follows (A represents the organic amine and B represents the ionic liquid; the following equations do not represent the practical reaction process but include physical absorption and chemical absorption):




[0011] controlling a liquid ratio between 5 and 25 L/m³, a reaction temperature of between 40 and 55°C, and a reaction pressure of between 0.01 and 10 atm, so that the aqueous solution of the composite absorbent is capable of fully reacting with CO₂ in the flue gas at the proper temperature and the pressure, thereby yielding the solution rich in A·CO₂ and B·CO₂;

[0012] 2) allowing the solution rich in A·CO₂ and B·CO₂ to stand and clarify under the action of selfaggregation to form different liquid layers comprising a lower layer being a

mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$ and an upper layer being the aqueous solution of the composite absorbent; separating the lower layer to obtain the mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$;

[0013] conducting heat exchange on the separated mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$ to enable CO_2 gas dissolved or adsorbed by the aqueous solution of the composite absorbent to evaporate whereby yielding a mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$ after heat exchange;

[0014] 3) thermally decomposing the mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$ after heat exchange to release the chemically absorbed CO_2 , whereby obtaining highconcentrated CO_2 gas and the aqueous solution of the composite absorbent, in which, a principal of the chemical reaction is as follows:



[0017] 4) returning the aqueous solution of the composite absorbent obtained in step 3) to step 1) as the CO_2 absorbent for recycling;

[0018] 5) cooling the high CO_2 gas separated from step 3) to condense water vapor therein;

[0019] 6) conducting gasseparation on the high CO_2 gas after the cooling treatment in step 5) to remove a condensed water therein, whereby yielding CO_2 gas having a purity of exceeding 99% (highly purified CO_2 gas); and

[0020] 7) desiccating the highly purified CO_2 gas (at a temperature of 110°C for between 0.1 and 5 min), and compressing and condensing the highly purified CO_2 gas to transform thehighly purified CO_2 gas into a liquid state, whereby obtaining a highconcentrated industrial liquid CO_2 .

[0021] The ionic liquid in step 1) is selected from the group consisting of a conventional ionic liquid, a functionalized ionic liquid, a polymeric ionic liquid, and a mixture thereof in an arbitrary ratio.

[0022] The conventional ionic liquid is selected from the group consisting of an imidazole salt, a pyrrole salt, a pyridine salt, an ammonium salt, a sulfonate, and a mixture thereof in an arbitrary ratio.

[0023] The functionalized ionic liquid is an ionic liquid comprising an amino group.

[0024] The conventional ionic liquid is selected from the group consisting of 1 butyl tetrafluoroborate, 1 hexafluorophosphate, 1 bis(trifluoromethylsulfonyl)imide, 1 hexafluorophosphate, and a mixture thereof in an arbitrary ratio.

[0025] The ionic liquid comprising an amino group is selected from the group consisting of 1(1)bromide, 1(3)tetrafluoroborate, and a mixture thereof in an arbitrary ratio.

[0026] The polymeric ionic liquid is selected from the group consisting of poly(4) tetrafluoroborate, poly(4)hexafluorophosphate, poly(4)imide, poly(4) trifluoromethylsulfonyl imide, poly(4)tetrafluoroborate, and a mixture thereof in an arbitrary ratio.

[0027] The organic amine in step 1) is selected from the group consisting of ethanolamine, Nmethyldiethanolamine, and a mixture thereof in an arbitrary ratio.

[0028] The thermal decomposition in step 3) is conducted at the temperature of between 80 and 110°C, a pressure of between 0.01 and 10 atm, and a time of between 1 and 5 min. $A \cdot CO_2$ is firstly decomposed, in another word, $A \cdot CO_2$ is decomposed into A and CO_2 , while $B \cdot CO_2$ is not prone to release CO_2 at such condition. Because CO_2 in $B \cdot CO_2$ is easily captured by A to form $A \cdot CO_2$ which continues to be decomposed and release CO_2 , so that high CO_2 gas and the aqueous solution of the composite absorbent are obtained.

[0029] The cooling treatment in step 5) comprises cooling the separated high CO_2 gas to

between 20 and 35°C and controlling a cooling time to between 1 and 5 min. Thus, a large amount of water vapor is condensed and returned to a decomposition tower for recycling.

[0030] An apparatus for collecting carbon dioxide from flue gas of a power plant according to the above method, the apparatus comprises: an absorption tower 1, a sedimentation pool 7 comprising slanting boards, a regeneration tower 22, a gasliquid separator 19, a desiccator 18, a compressor 17, and a condenser 16. A rich solution flows from a bottom of the absorption tower 1 into the sedimentation pool 7 comprising the slanting boards for stratification. A gas outlet of the gasseparator 19 is in series connection with the desiccator 18, the compressor 17, the condenser 16, and a liquid carbon dioxide storage tank 15, respectively.

[0031] A bottom flow outlet of the sedimentation pool 7 comprising the slanting boards is connected to a first medium (a mixed condensed liquid) inlet of a second heat exchanger 23 (for conducting a first heating) via a pipe where a rich solution pump 8 is disposed. A supernatant overflow of the sedimentation pool 7 comprising the slanting boards is connected to an inlet of a circulating absorption solution storage tank 10 via a pipe. An outlet of the circulating absorption solution storage tank 10 is connected to a spray pipe of a spray layer 2 in the absorption tower 1 via a pipe where an absorption solution circulating pump 9 is disposed.

[0032] A first medium (the mixed condensed liquid) outlet of the second exchange 23 is connected to a first medium (the mixed condensed liquid) inlet of a first heat exchanger 21 (for conducting a second heating) via a pipe. A first medium outlet of the first heat exchanger 21 is connected to an inlet disposed on an upper part of the regeneration tower 22 via a pipe. A gas outlet disposed on a top of the second heat exchanger 23 is connected to a pipe connecting the first heat exchanger 21 and a cooler 20. A gas outlet disposed on an upper part of the regeneration tower 22 is connected to a second medium (gas, heating

the first medium) inlet of the first heat exchanger 21 via a pipe. A second medium outlet of the first heat exchanger 21 is connected to an inlet of the cooler 20 via a pipe. An outlet of the cooler 20 is connected to an inlet of the gasseparator 19 via a pipe.

[0033] A liquid outlet disposed on a lower part of the regeneration tower 22 is connected to a second medium inlet of the second heat exchanger 23 via a pipe where a lean solution pump 13 is disposed. A second medium outlet of the second heat exchanger 23 is connected to the inlet of the circulating absorption solution storage tank 10 via a pipe where a filter 24 is disposed. A condensate overflow of the gasliquid separator 19 is connected to the inlet of the circulating absorption solution storage tank 10 via a pipe. A solution storage tank 12 for storing the aqueous solution of the composite absorbent is connected to the inlet of the circulating absorption solution storage tank 10 via a pipe where a solution pump is disposed 11.

[0034] The absorption tower 1 is a pneumatic bubbling tower. A sieve plate 5, a pneumatic bubbling layer 4, a filler layer 3, and a demister 26 are respectively arranged bottom up in the absorption tower 1 between a flue gas inlet 6 arranged a lower part of the absorption tower 1 and a flue gas outlet 27 arranged on a top of the absorption tower 1.

[0035] The absorption tower 1 is further provided with a spray layer 2, and the spray layer 2 is provided with between 2 and 4 spray pipes. A plurality of nozzles 25 are disposed on each spray pipe. The sieve plate 5 comprises circular through, and an area ratio of the circular through and the sieve plate 5 is between 30 and 40%. The demister 26 comprises: an upper filter screen, a lower filter screen, and a spray unit disposed therebetween.

[0036] Advantages according to embodiments of the invention are summarized as follows.

[0037] 1. The aqueous solution of the composite absorbent comprises the organic amine

and the ionic liquid, and so the CO₂ removal rate is improved by 10% in contrast to the organic amine method. Both the two components can absorb or adsorb carbon dioxide, and the absorbed or adsorbed carbon dioxide can be released quickly and completely through the transference and decomposition in the regeneration tower. Thus, the method is highly efficient in the collection of carbon dioxide.

[0038] 2. The products from the reaction of the aqueous solution of the composite absorbent and the flue gas are prone to aggregate to form a liquid layer different from water. The liquid layer rich in carbon dioxide is extracted and transported into the regeneration tower, thereby partly preventing the water from entering the regeneration tower, and greatly saving the energy consumption.

[0039] 3. Passing through the second heat exchanger (lean solution heat exchanger), part of carbon dioxide dissolved or adsorbed in the rich solution is released by heating, so the total weight of the rich solution entering the regeneration tower is reduced, thereby saving the energy consumption. Meanwhile, the low temperature rich solution from the absorption tower is heated respectively by the high temperature lean solution from the bottom of the regeneration tower and by the high temperature carbon dioxide from the top of the regeneration tower, thereby increasing the temperature of the rich solution and saving the energy consumption. Furthermore, the high temperature carbon dioxide from the top of the regeneration tower exchanges heat with the low temperature rich solution, thereby reducing the consumption of the cooling water in the cooler and saving the energy consumption.

[0040] 4. The method has a simple process flow, and the involved devices have low costs. The invention solves the longstanding problems resulting from organic amines method, such as serious corrosion of the devices, high energy consumption, and high material consumption.

BRIEF DESCRIPTION OF THE DRAWINGS

[0041] FIG. 1 is a schematic diagram of an apparatus for collecting carbon dioxide from flue gas of a power plant.

[0042] In the drawings, the following reference numbers are used: **1**Absorption tower,**2** Spray layer,**3**Filler layer,**4**-Pneumatic bubbling layer,**5**Sieve plate,**6**Flue gas inlet,**7** Sedimentation pool comprising slanting boards,**8**Rich solution pump,**9**Circulating pump,**10**-Circulating absorption solution storage tank,**11**-Solution pump,**12**-Solution storage tank,**13**-Lean solution pump,**14**-Reboiler,**15**-Liquid carbon dioxide storage tank,**16**-Condenser,**17**-Compressor,**18**- Desiccator,**19**-Gasseparator,**20**-Cooler,**21**-First heat exchanger,**22**-Regeneration tower,**23**-Second heat exchanger (leansolution heat exchanger),**24**-Filter, **25**-Nozzle,**26**-Demister,**27**-Flue gas outlet.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0043] For further illustrating the invention, experiments detailing a method and an apparatus for collecting carbon dioxide from flue gas of a power plant are described below. It should be noted that the following examples are intended to describe and not to limit the invention.

Example 1

[0044] A method for collecting carbon dioxide from flue gas of a power plant, the method comprises the following steps:

[0045] 1) An organic amine and an ionic liquid in a molar ratio of 1.01:1 are collected. The organic amine, the ionic liquid, and water are mixed to obtain an aqueous solution of a composite absorbent having a concentration of 20 wt. %.

[0046] The ionic liquid is 1 tetrafluoroborate of a conventional ionic liquid.

[0047] The organic amine is ethanolamine (MEA).

[0048] The aqueous solution of the composite absorbent comprising the organic amine and the ionic liquid is used as a CO₂ absorbent. The aqueous solution of the composite absorbent is evenly sprayed into the flue gas from a rear part of a power plant boiler after common treatments of dust removal and desulfurization, so that the flue gas flowing upwardly fully contacts with the downwardly sprayed aqueous solution of the composite absorbent to allow CO₂ in the flue gas to react with the composite absorbent and to be absorbed.

[0049] A liquidratio (the liquid herein means the aqueous solution of the composite absorbent, and the gas herein means the flue gas) is controlled at 20 L/m³. A temperature of the reaction between CO₂ in the flue gas and the aqueous solution of the composite absorbent is controlled at 50°C, and a pressure at an inlet of the absorption tower is controlled at 1.2 atm. Thus, the aqueous solution of the composite absorbent is able to fully react with CO₂ in the flue gas at the proper temperature and pressure, and a solution rich in A·CO₂ and B·CO₂ is yielded, in which, A represents the organic amine and B represents the functionalized ionic liquid.

[0050] 2) Matters of A·CO₂ and B·CO₂ after absorbing CO₂ are selfaggregated, and the solution rich in A·CO₂ and B·CO₂ is still and clarified to form different liquid layers. A lower layer is a mixed solution rich in A·CO₂ and B·CO₂ and an upper layer is the aqueous solution of the composite absorbent. Thereafter, the lower layer of the mixed solution rich in A·CO₂ and B·CO₂ is separated.

[0051] 3) Thermal decomposition is conducted on the separated mixed solution rich in A·CO₂ and B·CO₂. A temperature of the thermal decomposition is controlled at 100°C, a pressure of an outlet of a regeneration tower is controlled at 0.3 atm, and a heating time is controlled at 2 min. A·CO₂ is firstly decomposed, in another word, A·CO₂ is decomposed

into A and CO₂, while B·CO₂ is not prone to release CO₂ at such condition. Because CO₂ in B·CO₂ is easily captured by A to form A·CO₂ which continues to be decomposed and release CO₂, so that high CO₂ gas and the aqueous solution of the composite absorbent are obtained.

[0052] 4) The aqueous solution of the composite absorbent obtained in step 3) is returned to step 1) as the CO₂ absorbent for recycling;

[0053] 5) The high CO₂ gas separated from step 3) is cooled to condense hot water vapor therein, during which, the high CO₂ gas is cooled to a temperature of 30°C, and a cooling time is controlled at 1.5 min. Thus, a large amount of water vapor is condensed and returned to a decomposition tower for recycling.

[0054] 6) The high CO₂ gas after the cooling treatment in step 5) is introduced to the gas separator for gas separation. Condensed water therein is removed, and CO₂ gas having a purity of exceeding 99% is obtained.

[0055] 7) The highly purified CO₂ gas obtained in step 6) is desiccated (at a temperature of 110°C for between 2 min), compressed by a compressor, and condensed by a condenser to enable a temperature thereof to be 20°C and a pressure thereof to be 72 atm, and transform the highly purified CO₂ gas into a liquid state, thereby obtaining a high industrial liquid CO₂.

[0056] Experiment results are as follows:

[0057] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v.%, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0058] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

[0059] As shown in FIG. 1, an apparatus for collecting carbon dioxide from flue gas of a power plant according to the above method, the apparatus comprises: an absorption tower **1**, a sedimentation pool **7** comprising slanting boards, a second heat exchanger **23**, a first heat exchanger **21**, a regeneration tower **22**, a gasliquid separator **19**, a desiccator **18**, a compressor **17**, and a condenser **16**.

[0060] The absorption tower **1** is a pneumatic bubbling tower. A filler layer is disposed at an upper part of the absorption tower **1**, a pneumatic bubbling layer is disposed at a middle part of the absorption tower **1**, and a sieve plate is disposed at a lower part of the absorption tower **1**. The regeneration tower **22** is the sieve plate tower.

[0061] The sieve plates **5**, the pneumatic bubbling layer **4**, the filler layer **3**, and the demister **26** are respectively arranged bottom up in the absorption tower **1** between a flue gas inlet **6** arranged at the lower part of the absorption tower **1** and a flue gas outlet **27** arranged at a top of the absorption tower **1**. The absorption tower **1** is further provided with a spray layer **2**, and the spray layer **2** is provided with between 2 and 4 spray pipes. Three spray pipes are shown in FIG. 1, a first spray pipe is disposed above the sieve plate **5**, a second is disposed above the pneumatic bubbling layer **4**, and a third is disposed above the filler layer **3**. A plurality of nozzles **25** are disposed on each spray pipe. The specific number of the nozzles is determined according to the flow rate, and generally each spray pipe is provided with between 2 and 20 nozzles. The sieve plate **5** comprises circular through, and an area ratio of the circular through to the sieve plate **5** is between 30 and 40%. The demister **26** is provided with an upper filter screen, a lower filter screen, and a spray unit disposed therebetween, so that the composite absorbent drops trapped in the flue gas are completely removed.

[0062] A rich solution outlet arranged at a bottom of the absorption tower **1** is connected to an inlet of the sedimentation pool **7** comprising the slanting boards via a pipe, so that the rich solution from the bottom of the absorption tower **1** flows into the sedimentation

pool **7** comprising the slanting boards for stratification. A supernatant in the sedimentation pool **7** comprising the slanting boards is the aqueous solution of the composite absorbent, and a bottom flow therein is primarily a mixed aggregated liquid of a product of the composite absorbent. A bottom flow outlet of the sedimentation pool **7** comprising the slanting boards is connected to a first medium (a mixed aggregated liquid) inlet of a second heat exchanger **23** (for conducting a first heating) via a pipe where a rich solution pump **8** is disposed. A supernatant overflow of the sedimentation pool **7** comprising the slanting boards is connected to an inlet of a circulating absorption solution storage tank **10** via a pipe. An outlet of the circulating absorption solution storage tank **10** is connected to a spray pipe of a spray layer **2** in the absorption tower **1** via a pipe where an absorption solution circulating pump **9** is disposed.

[0063] A first medium (the mixed aggregated liquid) outlet of the second exchange **23** is connected to a first medium (the mixed aggregated liquid) inlet of a first heat exchanger **21** (for conducting a second heating) via a pipe. A first medium (the mixed aggregated liquid) outlet of the first heat exchanger **21** is connected to an inlet disposed on an upper part of the regeneration tower **22** via a pipe. A gas outlet disposed on a top of the second heat exchanger **23** is connected to a pipe connecting the first heat exchanger **21** and a cooler **20**. A gas outlet disposed on an upper part of the regeneration tower **22** is connected to a second medium (gas, heating the first medium) inlet of the first heat exchanger **21** via a pipe. A second medium outlet of the first heat exchanger **21** is connected to an inlet of the cooler **20** via a pipe. An outlet of the cooler **20** is connected to an inlet of the gasseparator **19** via a pipe.

[0064] A reboiler **14** matching with the regeneration tower **22** is disposed outside the bottom of the regeneration tower. An outlet of the reboiler **14** is connected to a liquid storage tank arranged at the bottom of the regeneration tower via a pipe. An inlet of the reboiler **14** is connected to the liquid storage tank at the bottom of the regeneration tower via a pipe. A liquid outlet disposed on a lower part of the regeneration tower **22** is

connected to a second medium inlet of the second heat exchanger **23** via a pipe where a lean solution pump **13** is disposed. A second medium outlet of the second heat exchanger **23** is connected to the inlet of the circulating absorption solution storage tank **10** via a pipe where a filter **24** is disposed.

[0065] A gas outlet of the gasseparator **19** is in series connection with the desiccator **18**, the compressor **17**, the condenser **16**, and a liquid carbon dioxide storage tank **15**, respectively. A condensate overflow of the gasliquid separator **19** is connected to the inlet of the circulating absorption solution storage tank **10** via a pipe.

[0066] A solution storage tank **12** for storing the aqueous solution of the composite absorbent is connected to the inlet of the circulating absorption solution storage tank **10** via a pipe where a solution pump is disposed **11**(supplemental aqueous solution of the composite absorbent and water are added to the solution storage tank **12**).

[0067] The above devices are generally common devices in the field of chemical industry, and specific structures thereof will not be repeatedly illustrated herein.

[0068] The sieve plate are arranged above the flue gas inlet in the lower part of the absorption tower for facilitating even distribution of the flue gas and gascontact. The area ratio of the through holes and the sieve plate is controlled between 20 and 40 %. Thus, in one respect, after the upwardly flowing flue gas passes the sieve plate, the flow distribution thereof becomes more evenly, dead angle of the flue gas flow is effectively eliminated, thereby being beneficial for the full contact between the flue gas and the absorbent solution; and in the other respect, under the action of the interactive jet of a plurality sets of nozzles, a spray coverage on the cross section of the absorption tower reaches exceeding 300%, so that the carbon dioxide in flue gas fully contacts with and reacts with the absorbent solution, thereby being absorbed.

[0069] The leanrich solution heat exchangers are designed. The rich solution outlet arranged at the sedimentation pool **7** comprising the slanting boards is connected to the

inlet arranged on the upper part of the regeneration tower via the rich solution pump, the second (lean solution) heat exchanger, and the first heat exchanger. The lean solution outlet of the regeneration tower is connected to the liquid inlet arranged on the upper part of the circulating absorption solution storage tank via the lean solution pump and the second (lean solution) heat exchanger. Thus, exhaust heat of the lean solution in the regeneration tower and the flue gas at the outlet of the regeneration tower are utilized to preheat the rich solution introduced into the regeneration tower. Meanwhile, temperatures of the lean solution discharged from the lower part of the regeneration tower and the flue gas discharged from the upper part of the regeneration tower are decreased, thereby realizing a virtuous circulation of the heat exchange and saving the heat energy resource.

[0070] Working process of the method and the apparatus for collecting flue gas are as follows:

[0071] The flue gas from the rear part of the power plant boiler after the common treatments of dust removal and desulfurization is introduced into the absorption tower **1** via the flue gas inlet **6** arranged at the lower part the absorption tower **1**. The flue gas flows upwardly and passes the sieve plate **5**, the pneumatic bubbling layer **4**, and the filler layer **3**, respectively. Meanwhile, the aqueous solution of the composite absorbent is sprayed downwardly from the spray layer **2**. The liquid/gas ratio is controlled at between 5 and 25 L/m^3 . A temperature of the reaction between CO_2 in the flue gas and the aqueous solution of the composite absorbent is preferably controlled at between 40 and 55°C , and a reaction pressure is controlled at between 0.01 and 10 atm . Thus, CO_2 in the flue gas fully contacts with the aqueous solution of the composite absorbent in the filler layer **3** and the pneumatic bubbling layer **4**, and CO_2 are chemical composited or absorbed in the solution.

[0072] The flue gas after removal of a large amount of CO_2 continuously flows upwardly, fog droplets of the absorbent therein are removed by the demister **26** arranged on the top

of the absorption tower **1**, and clean flue gas are directly discharged into the atmosphere. The rich solution after CO₂ absorption falls to the bottom of the absorption tower, and flows to the sedimentation pool **7** comprising the slanting boards for aggregation and stratification. A resulting supernatant is a solution containing a small amount of the composite absorbent, and a bottom flow mainly contains aggregated slurry of the product of the composite absorbent. The bottom flow in the sedimentation pool comprising the slanting boards is transported by the rich solution pump to be heated for the first time in the tube side of the second heat exchanger **23** (the leansolution heat exchanger) and be heated for the second time in the first heat exchanger **21**, and then enters the regeneration tower **22** via the inlet arranged on the upper part therein. A partial of dissolved or absorbed CO₂ is released from the rich solution after being heated by the second heat exchanger **23** (the leansolution heat exchanger).

[0073] The rich solution compositing or absorbing CO₂ is sprayed into the regeneration tower **22**, and passes through each sieve plate, respectively. The product of the composite absorbent is heated by the upwardly flowing vapor and decomposed, so that CO₂ is released. Incompletely decomposed slurry of the product of the composite absorbent falls to the bottom of the regeneration tower, heated by the reboiler **14** arranged at the bottom of the regeneration tower to a temperature of between 80 and 110°C, thereby further decomposing highconcentrated CO₂ and completely decomposing the product of the composite absorbent.

[0074] The released CO₂ gas together with a large amount of water vapor flow out of the regeneration tower **22** via the gas outlet arranged on the upper part thereof, and enters the first heat exchanger **21**, and heat the rich solution heated by the second heat exchanger **23** (the leansolution heat exchanger). After the heat exchange, the gas is mixed with the gas released from the heating by the second heat exchanger **23** (the leanrich solution heat exchanger) and the mixed gas is introduced to the cooler **20**, where the CO₂ gas is cooled to a temperature between 25 and 35°C, and a large amount of water vapor therein is

condensed and separated.

[0075] The solution of the composite absorbent decomposed in the regeneration tower **22** is pumped by the lean solution pump **13** and is introduced to the tube side of the second heat exchanger **23** (the lean solution heat exchanger) for releasing the heat energy. The cooled solution of the composite absorbent is introduced to the filter **24**, where the dissolved heavy metal or impurities in the reaction in the flue gas produced are removed. A purified solution of the composite absorbent flows into the circulating absorption solution storage tank **10**. Supplemental composite absorbent and process water are added to the solution storage tank **12** and are transported to the circulating absorption solution storage tank **10** via the solution pump **11**. The circulating absorbing solution is transported by the absorption solution circulating pump to the spray layer **2** in the absorption tower and is sprayed and then absorbed.

[0076] The highly purified CO₂ gas after the treatment of the cooler **20** is introduced to the gas separator **19**. Condensed liquid trapped in the CO₂ gas are completely separated under the centrifugal action, and the CO₂ gas having the purity exceeding 99% is acquired. The separated condensing liquid flows from the condensate outlet of the gas separator **19** into the circulating absorption solution storage tank **10** for recycling. The separated highly purified CO₂ is then desiccated by the desiccator **18**, compressed by the compressor **17**, and condensed by the condenser **16** and is transformed into a liquid state. The high industrial liquid CO₂ is obtained and finally transported to the liquid carbon dioxide storage tank **15** for storage.

Example 2

[0077] A method for collecting carbon dioxide from flue gas of a power plant, the method comprises the following steps:

[0078] 1) An organic amine and a functionalized ionic liquid in a molar ratio of 1.1:1 are collected. The organic amine, the functionalized ionic liquid, and water are mixed to obtain an aqueous solution of a composite absorbent having a concentration of 40 wt. %.

[0079] The functionalized ionic liquid is an ionic liquid comprising an amino group and is 1(1)bromide.

[0080] The organic amine is Nmethyldiethanolamine (MDEA).

[0081] The aqueous solution of the composite absorbent comprising the organic amine and the ionic liquid is used as a CO₂ absorbent. The aqueous solution of the composite absorbent is evenly sprayed into the flue gas from a rear part of a power plant boiler after common treatments of dust removal and desulfurization, so that the flue gas flowing upwardly fully contacts with the downwardly sprayed aqueous solution of the composite absorbent to allow CO₂ in the flue gas to react with the composite absorbent and to be absorbed.

[0082] A liquidgas ratio (the liquid herein means the aqueous solution of the composite absorbent, and the gas herein means the flue gas) is controlled at 20 L/m³. A temperature of the reaction between CO₂ in the flue gas and the aqueous solution of the composite absorbent is controlled at 50°C, and a pressure at an inlet of the absorption tower is controlled at 1.2 atm. Thus, the aqueous solution of the composite absorbent is able to fully react with CO₂ in the flue gas at the proper temperature and pressure, and a solution rich in A·CO₂ and B·CO₂ is yielded, in which, A represents the organic amine and B represents the functionalized ionic liquid.

[0083] 2) Matters of A·CO₂ and B·CO₂ after absorbing CO₂ are selfaggregated, and the solution rich in A·CO₂ and B·CO₂ is stillled and clarified to form different liquid layers. A lower layer is a mixed solution rich in A·CO₂ and B·CO₂ and an upper layer is the aqueous solution of the composite absorbent. Thereafter, the lower layer of the mixed solution rich in A·CO₂ and B·CO₂ is separated.

[0084] 3) Thermal decomposition is conducted on the separated mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$. A temperature of the thermal decomposition is controlled at $100^\circ C$, a pressure of an outlet of a regeneration tower is controlled at 0.3 atm, and a heating time is controlled at 2 min. $A \cdot CO_2$ is firstly decomposed, in another word, $A \cdot CO_2$ is decomposed into A and CO_2 , while $B \cdot CO_2$ is not prone to release CO_2 at such condition. Because CO_2 in $B \cdot CO_2$ is easily captured by A to form $A \cdot CO_2$ which continues to be decomposed and release CO_2 , so that high CO_2 gas and the aqueous solution of the composite absorbent are obtained.

[0085] 4) The aqueous solution of the composite absorbent obtained in step 3) is returned to step 1) as the CO_2 absorbent for recycling;

[0086] 5) The high CO_2 gas separated from step 3) is cooled to condense hot water vapor therein, during which, the high CO_2 gas is cooled to a temperature of $30^\circ C$, and a cooling time is controlled at 1.5 min. Thus, a large amount of water vapor is condensed and returned to a decomposition tower for recycling.

[0087] 6) The high CO_2 gas after the cooling treatment in step 5) is introduced to the gas separator for gas separation. Condensed water therein is removed, and CO_2 gas having a purity of exceeding 99% is obtained.

[0088] 7) The highly purified CO_2 gas obtained in step 6) is desiccated (at a temperature of $110^\circ C$ for between 2 min), compressed by a compressor, and condensed by a condenser to enable a temperature thereof to be $20^\circ C$ and a pressure thereof to be 72 atm, and transform the highly purified CO_2 gas into a liquid state, thereby obtaining a high industrial liquid CO_2 .

[0089] Experiment results are as follows:

[0090] A content of CO_2 in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO_2 in the flue gas at the outlet of the absorption tower is 0.4 v. %, thus, an

absorption efficiency of carbon dioxide reaches 96.7%.

[0091] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.46×10^7 kJ/h, so that the energy consumption is decreased by 30.5%.

Example 3

[0092] A method for collecting carbon dioxide from flue gas of a power plant, the method comprises the following steps:

[0093] 1) An organic amine and an ionic liquid in a molar ratio of 1.05:1 are collected. The organic amine, the ionic liquid, and water are mixed to obtain an aqueous solution of a composite absorbent having a concentration of 40 wt. %.

[0094] The ionic liquid is a polymeric ionic liquid, and the polymeric ionic liquid is poly 1(4)tetrafluoroborate.

[0095] The organic amine comprises ethanolamine (MEA) and N(MDEA); and dosages of MEA and MDEA account for 1/2 of a total weight of the organic amine, respectively.

[0096] The aqueous solution of the composite absorbent comprising the organic amine and the ionic liquid is used as a CO₂ absorbent. The aqueous solution of the composite absorbent is evenly sprayed into the flue gas from a rear part of a power plant boiler after common treatments of dust removal and desulfurization, so that the flue gas flowing upwardly fully contacts with the downwardly sprayed aqueous solution of the composite absorbent to allow CO₂ in the flue gas to react with the composite absorbent and to be absorbed.

[0097] A liquid:gas ratio (the liquid herein means the aqueous solution of the composite absorbent, and the gas herein means the flue gas) is controlled at 20 L/m³. A temperature

of the reaction between CO_2 in the flue gas and the aqueous solution of the composite absorbent is controlled at 50°C , and a pressure at an inlet of the absorption tower is controlled at 1.2 atm. Thus, the aqueous solution of the composite absorbent is able to fully react with CO_2 in the flue gas at the proper temperature and pressure, and a solution rich in $\text{A}\cdot\text{CO}_2$ and $\text{B}\cdot\text{CO}_2$ is yielded, in which, A represents the organic amine and B represents the functionalized ionic liquid.

[0098] 2) Matters of $\text{A}\cdot\text{CO}_2$ and $\text{B}\cdot\text{CO}_2$ after absorbing CO_2 are selfaggregated, and the solution rich in $\text{A}\cdot\text{CO}_2$ and $\text{B}\cdot\text{CO}_2$ is stillled and clarified to form different liquid layers. A lower layer is a mixed solution rich in $\text{A}\cdot\text{CO}_2$ and $\text{B}\cdot\text{CO}_2$ and an upper layer is the aqueous solution of the composite absorbent. Thereafter, the lower layer of the mixed solution rich in $\text{A}\cdot\text{CO}_2$ and $\text{B}\cdot\text{CO}_2$ is separated.

[0099] 3) Thermal decomposition is conducted on the separated mixed solution rich in $\text{A}\cdot\text{CO}_2$ and $\text{B}\cdot\text{CO}_2$. A temperature of the thermal decomposition is controlled at 100°C , a pressure of an outlet of a regeneration tower is controlled at 0.3 atm, and a heating time is controlled at 2 min. $\text{A}\cdot\text{CO}_2$ is firstly decomposed, in another word, $\text{A}\cdot\text{CO}_2$ is decomposed into A and CO_2 , while $\text{B}\cdot\text{CO}_2$ is not prone to release CO_2 at such condition. Because CO_2 in $\text{B}\cdot\text{CO}_2$ is easily captured by A to form $\text{A}\cdot\text{CO}_2$ which continues to be decomposed and release CO_2 , so that high CO_2 gas and the aqueous solution of the composite absorbent are obtained.

[0100] 4) The aqueous solution of the composite absorbent obtained in step 3) is returned to step 1) as the CO_2 absorbent for recycling;

[0101] 5) The high CO_2 gas separated from step 3) is cooled to condense hot water vapor therein, during which, the high CO_2 gas is cooled to a temepature of 30°C , and a cooling time is controlled at 1.5 min. Thus, a large amount of water vapor is condensed and returned to a decomposition tower for recycling.

[0102] 6) The high CO_2 gas after the cooling treatment in step 5) is introduced to the

gasseparator for gasseparation. Condensed water therein is removed, and CO₂ gas having a purity of exceeding 99% is obtained.

[0103] 7) The highly purified CO₂ gas obtained in step 6) is desiccated (at a temperature of 110°C for between 2 min), compressed by a compressor, and condensed by a condenser to enable a temeptrate thereof to be 20°C and a pressure thereof to be 72 atm, and transform the highly purified CO₂ gas into a liquid state, thereby obtaining a highindustrial liquid CO₂.

[0104] Experiment results are as follows:

[0105] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.6 v. %, thus, an absorption efficiency of carbon dioxide reaches95%.

[0106] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.49×10^7 kJ/h, so that the energy consumption is decreased by 29.1%.

Example 4

[0107] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the molar ratio of the organic amine and the ionic liquid is 1:1; the organic amine, the ionic liquid, and water are mixed and a resulting aqueous solution of a composite absorbent has a concentration of 30 wt. %.

[0108] Experiment results are as follows:

[0109] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches94.2%.

[0110] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 5

[0111] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the liquidgas ratio in step 1) is controlled at 5 L/m³, the temperature of the reaction between CO₂ in the flue gas and the aqueous solution of the composite absorbent is controlled at 40°C, and the reaction pressure is controlled at 0.01 atm.

[0112] Experiment results are as follows:

[0113] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0114] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 6

[0115] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the liquidratio in step 1) is controlled at 25 L/m³, the temperature of the reaction between CO₂ in the flue gas and the aqueous solution of the composite absorbent is controlled at 55°C, and the reaction pressure is controlled at 10 atm.

[0116] Experiment results are as follows:

[0117] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0118] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 7

[0119] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that thermal decomposition in step 3) is performed at a temperature of 80°C, a pressure of 0.01 atm, and a heating time of 1 min.

[0120] Experiment results are as follows:

[0121] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0122] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 8

[0123] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that thermal decomposition in step 3) is performed at a temperature of 110°C, a pressure of 10 atm, and a heating time of 5 min.

[0124] Experiment results are as follows:

[0125] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0126] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 9

[0127] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that during the cooling treatment in step 5), the high concentrated CO₂ gas is cooled to a temperature of 20°C, and a cooling time is controlled at 1 min.

[0128] Experiment results are as follows:

[0129] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0130] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 10

[0131] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that during the cooling treatment in step 5), the

high CO_2 gas is cooled to a temperature of 35°C , and a cooling time is controlled at 5 min.

[0132] Experiment results are as follows:

[0133] A content of CO_2 in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO_2 in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0134] Energy consumption for regeneration after absorption of CO_2 for the conventional MEA is $2.1 \times 10^7 \text{ kJ/h}$, and the energy consumption for regeneration tested in this experiment is $1.52 \times 10^7 \text{ kJ/h}$, so that the energy consumption is decreased by 27.6%.

Example 11

[0135] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the desiccation treatment in step 7) is performed at a temperature of 110°C and a time is controlled at 0.1 min

[0136] Experiment results are as follows:

[0137] A content of CO_2 in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO_2 in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0138] Energy consumption for regeneration after absorption of CO_2 for the conventional MEA is $2.1 \times 10^7 \text{ kJ/h}$, and the energy consumption for regeneration tested in this experiment is $1.52 \times 10^7 \text{ kJ/h}$, so that the energy consumption is decreased by 27.6%.

Example 12

[0139] A method for collecting carbon dioxide from flue gas of a power plant is basically

the same as that in Example 1 except that the desiccation treatment in step 7) is performed at a temperature of 110°C and a time is controlled at 5 min.

[0140] Experiment results are as follows:

[0141] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0142] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 13

[0143] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the ionic liquid is 1 tetrafluoroborate of a conventional ion liquid.

[0144] Experiment results are as follows:

[0145] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0146] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 14

[0147] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the ionic liquid is 1 bis(trifluoromethylsulfonyl)imide of a conventional ion liquid.

[0148] Experiment results are as follows:

[0149] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0150] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 15

[0151] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the ionic liquid is 1 hexafluorophosphate of a conventional ion liquid.

[0152] Experiment results are as follows:

[0153] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0154] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 16

[0155] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the ionic liquid includes 1butyl hexafluorophosphate, 1bis(trifluoromethylsulfonyl)imide, and 1hexafluorophosphate of a conventional ion liquid; and dosages thereof account for 1/3 of a total weight of the ionic liquid, respectively.

[0156] Experiment results are as follows:

[0157] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0158] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 17

[0159] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the ionic liquid includes a conventional ionic liquid and a functionalized ionic liquid, and dosages thereof account for 1/2 of a total weight of the ionic liquid, respectively.

[0160] The conventional ionic liquid is 1butyltetrafluoroborate; and the functionalized ionic liquid is 1(1)bromide.

[0161] Experiment results are as follows:

[0162] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0163] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 18

[0164] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 1 except that the ionic liquid includes: a conventional ionic liquid, a functionalized ionic liquid, and a polymeric ionic liquid; and dosages thereof account for 1/3 of a total weight of the ionic liquid, respectively.

[0165] The conventional ionic liquid is 1-yltetrafluoroborate; and the functionalized ionic liquid is 1(1)bromide; and the polymeric ionic liquid is poly(4)tetrafluoroborate

[0166] Experiment results are as follows:

[0167] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.7 v. %, thus, an absorption efficiency of carbon dioxide reaches 94.2%.

[0168] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.52×10^7 kJ/h, so that the energy consumption is decreased by 27.6%.

Example 19

[0169] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 2 except that the functionalized ionic liquid is 1(3) tetrafluoroborate.

[0170] Experiment results are as follows:

[0171] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.4 v. %, thus, an absorption efficiency of carbon dioxide reaches 96.7%.

[0172] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.46×10^7 kJ/h, so that the energy consumption is decreased by 30.5%.

Example 20

[0173] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 2 except that the functionalized ionic liquid includes 1(1) bromide and 1(3)tetrafluoroborate; and dosages thereof account for 1/2 of the total weight of the functionalized ionic liquid, respectively.

[0174] Experiment results are as follows:

[0175] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.4 v. %, thus, an absorption efficiency of carbon dioxide reaches 96.7%.

[0176] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.46×10^7 kJ/h, so that the energy consumption is decreased by 30.5%.

Example 21

[0177] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 3 except that the polymeric ionic liquid is poly(4tyryl) hexafluorophosphate.

[0178] Experiment results are as follows:

[0179] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.6 v. %, thus, an absorption efficiency of carbon dioxide reaches 95%.

[0180] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.49×10^7 kJ/h, so that the energy consumption is decreased by 29.1%.

Example 22

[0181] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 3 except that the polymeric ionic liquid is poly(4)imide.

[0182] Experiment results are as follows:

[0183] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.6 v. %, thus, an absorption efficiency of carbon dioxide reaches 95%.

[0184] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.49×10^7 kJ/h, so that the energy consumption is decreased by 29.1%.

Example 23

[0185] A method for collecting carbon dioxide from flue gas of a power plant is basically the same as that in Example 3 except that the polymeric ionic liquid includes poly(4)trifluoromethylsulfonyl imide and poly(4)tetrafluoroborate; and dosages thereof account for 1/2 of a total weight of the polymeric ionic liquid, respectively.

[0186] Experiment results are as follows:

[0187] A content of CO₂ in the flue gas at the inlet of the absorption tower is 12 v. %, and a content of CO₂ in the flue gas at the outlet of the absorption tower is 0.6 v. %, thus, an absorption efficiency of carbon dioxide reaches 95%.

[0188] Energy consumption for regeneration after absorption of CO₂ for the conventional MEA is 2.1×10^7 kJ/h, and the energy consumption for regeneration tested in this experiment is 1.49×10^7 kJ/h, so that the energy consumption is decreased by 29.1%.

CLAIMS

1. A method for collecting carbon dioxide from flue gas of a power plant, the method comprising the following steps:
 - 1) providing an organic amine and an ionic liquid in a molar ratio of (1.1):1, mixing the organic amine, the ionic liquid, and water to obtain an aqueous solution of a composite absorbent having a concentration of between 20 and 40 wt. %;
using the aqueous solution of the composite absorbent comprising the organic amine and the ionic liquid as a CO₂ absorbent, evenly spraying the aqueous solution of the composite absorbent into the flue gas from a rear part of a power plant boiler after dust removal and desulfurization to allow the flue gas flowing upwardly to fully contact with the downwardly sprayed aqueous solution of the composite absorbent and to allow CO₂ in the flue gas to react with the composite absorbent whereby absorbing CO₂ and yielding a solution rich in A·CO₂ and B·CO₂, in which, A represents the organic amine and B represents the ionic liquid; and
controlling a liquid ratio between 5 and 25 L/m³, a reaction temperature of between 40 and 55°C, and a reaction pressure of between 0.01 and 10 atm;
 - 2) allowing the solution rich in A·CO₂ and B·CO₂ to stand and clarify under the action of self to form different liquid layers comprising a lower layer being a mixed solution rich in A·CO₂ and B·CO₂ and an upper layer being the aqueous solution of the composite absorbent; separating the lower layer to obtain the mixed solution rich in A·CO₂ and B·CO₂;

conducting heat exchange on the separated mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$ to enable CO_2 gas dissolved or absorbed by the aqueous solution of the composite absorbent therein to evaporate whereby yielding a mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$ after heat exchange;

- 3) thermally decomposing the mixed solution rich in $A \cdot CO_2$ and $B \cdot CO_2$ after heat exchange to release the chemically absorbed CO_2 , whereby obtaining high CO_2 gas and the aqueous solution of the composite absorbent;
- 4) returning the aqueous solution of the composite absorbent obtained in step 3) to step 1) as the CO_2 absorbent for recycling;
- 5) cooling the high CO_2 gas separated from step 3) to condense water vapor therein;
- 6) conducting gas separation on the high CO_2 gas after the cooling treatment in step 5) to remove a condensed water therein, whereby yielding CO_2 gas having a purity of exceeding 99%; and
- 7) desiccating, compressing, and condensing the CO_2 gas having the purity of exceeding 99% obtained in step 6) to transform the CO_2 gas into a liquid state, whereby obtaining a highconcentrated industrial liquid CO_2 .

2. The method of claim 1, **characterized in that** the ionic liquid in step 1) is selected from the group consisting of a conventional ionic liquid, a functionalized ionic liquid, a polymeric ionic liquid, and a mixture thereof in an arbitrary ratio.
3. The method of claim 2, **characterized in that** the conventional ionic liquid is selected from the group consisting of an imidazole salt, a pyrrole salt, a pyridine salt, an ammonium salt, a sulfonate, and a mixture thereof in an arbitrary ratio.

4. The method of claim 2, **characterized in that** the functionalized ionic liquid is an ionic liquid comprising an amino group.
5. The method of claim 2 or 3, **characterized in that** the conventional ionic liquid is selected from the group consisting of 1tetrafluoroborate, 1hexafluorophosphate, 1 bis(trifluoromethylsulfonyl)imide, 1hexafluorophosphate, and a mixture thereof in an arbitrary ratio.
6. The method of claim 4, **characterized in that** the ionic liquid comprising an amino group is selected from the group consisting of 1(1)bromide, 1(3)tetrafluoroborate, and a mixture thereof in an arbitrary ratio.
7. The method of claim 2, **characterized in that** the polymeric ionic liquid is selected from the group consisting of poly(4)tetrafluoroborate, poly(4)hexafluorophosphate, poly(4)imide, poly(4)trifluoromethylsulfonyl imide, poly(4)tetrafluoroborate, and a mixture thereof in an arbitrary ratio.
8. The method of claim 1, **characterized in that** the organic amine in step 1) is selected from the group consisting of ethanolamine, Nmethyldiethanolamine, and a mixture thereof in an arbitrary ratio.
9. The method of claim 1, **characterized in that** the thermal decomposition in step 3) is conducted at the temperature of between 80 and 110°C, a pressure of between 0.01 and 10 atm, and a time of between 1 and 5 min.
10. The method of claim 1, **characterized in that** the cooling treatment in step 5) comprises cooling the separated highconcentrated CO₂ gas to between 20 and 35°C and controlling a cooling time to between 1 and 5 min.

11. An apparatus for collecting carbon dioxide from flue gas of a power plant according to the method of claim 1, the apparatus comprising: an absorption tower (1), a sedimentation pool (7) comprising slanting boards, a regeneration tower (22), a gasseparator (19), a desiccator (18), a compressor (17), and a condenser (16); a rich solution flowing from a bottom of the absorption tower (1) into the sedimentation pool (7) comprising the slanting boards for stratification; a gas outlet of the gasseparator (19) being in series connection with the desiccator (18), the compressor (17), the condenser (16), and a liquid carbon dioxide storage tank (15), respectively; **characterized in that**

a bottom flow outlet of the sedimentation pool (7) comprising the slanting boards is connected to a first medium inlet of a second heat exchanger (23) via a pipe where a rich solution pump (8) is disposed; a supernatant overflow of the sedimentation pool (7) comprising the slanting boards is connected to an inlet of a circulating absorption solution storage tank (10) via a pipe; an outlet of the circulating absorption solution storage tank (10) is connected to a spray pipe of a spray layer (2) in the absorption tower (1) via a pipe where an absorption solution circulating pump (9) is disposed;

a first medium outlet of the second exchange (23) is connected to a first medium inlet of a first heat exchanger (21) via a pipe; a first medium outlet of the first heat exchanger (21) is connected to an inlet disposed on an upper part of the regeneration tower (22) via a pipe; a gas outlet disposed on a top of the second heat exchanger (23) is connected to a pipe connecting the first heat exchanger (21) and a cooler (20); a gas outlet disposed on an upper part of the regeneration tower (22) is connected to a second medium inlet of the first heat exchanger (21) via a pipe; a second medium outlet of the first heat exchanger (21) is connected to an inlet of the cooler (20) via a pipe; an outlet of the cooler (20) is connected to an inlet of the gas liquid separator (19) via a pipe;

a liquid outlet disposed on a lower part of the regeneration tower (22) is connected to a second medium inlet of the second heat exchanger (23) via a pipe where a lean solution pump (13) is disposed; a second medium outlet of the second heat exchanger (23) is connected to the inlet of the circulating absorption solution storage tank (10) via a pipe where a filter (24) is disposed; a condensate overflow of the gas separator (19) is connected to the inlet of the circulating absorption solution storage tank (10) via a pipe; a solution storage tank (12) for storing the aqueous solution of the composite absorbent is connected to the inlet of the circulating absorption solution storage tank (10) via a pipe where a solution pump is disposed (11).

12. The apparatus of claim 11, **characterized in that**

the absorption tower (1) is a pneumatic bubbling tower; a sieve plate (5), a pneumatic bubbling layer (4), a filler layer (3), and a demister (26) are respectively arranged bottom up in the absorption tower (1) between a flue gas inlet (6) arranged at a lower part of the absorption tower (1) and a flue gas outlet (27) arranged on a top of the absorption tower (1);

the absorption tower (1) is further provided with a spray layer (2), and the spray layer (2) is provided with between 2 and 4 spray pipes; a plurality of nozzles (25) are disposed on each spray pipe;

the sieve plate (5) comprises circular through, and an area ratio of the circular through and the sieve plate (5) is between 30 and 40%; and

the demister (26) comprises: an upper filter screen, a lower filter screen, and a spray unit disposed therebetween.