



(43) International Publication Date
6 September 2013 (06.09.2013)

(51) International Patent Classification:
E06C 7/42 (2006.01)

(21) International Application Number:
PCT/SG2012/000091

(22) International Filing Date:
23 March 2012 (23.03.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
201201530-1 2 March 2012 (02.03.2012) SG

(72) Inventor; and

(71) Applicant (for all designated States except US): **YONG
FOO, Sia** [SG/SG]; Block 205, #03-1297, Tampines
Street 21, Singapore 520205 (SG).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,

KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— without international search report and to be republished
upon receipt of that report (Rule 48.2(g))

(54) Title: SAFETY LADDER



(57) Abstract: This newly design ladder allow two workers to work safely on top of the ladder which with the fastening of the safety belt. This ladder has four linkages to support and hold the safety of two person on top of it. The linkages are at the side of this ladder, it can support and hold the ladder for falling side way. The ladder can be extendable depend on how high a worker want.