

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
28 January 2010 (28.01.2010)

PCT

(10) International Publication Number
WO 2010/009505 A8(51) International Patent Classification:
A01G 9/02 (2006.01) *E04F 13/08* (2006.01)(21) International Application Number:
PCT/AU2009/000937(22) International Filing Date:
23 July 2009 (23.07.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2008903795 24 July 2008 (24.07.2008) AU

(72) Inventor; and

(71) Applicant : LEE, Alan, Sian, Ghee [SG/SG]; 15 Joan Road, Singapore 298899 (SG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): GREAVES, Henry [AU/AU]; 171 Hopetoun Avenue, Watsons Bay, New South Wales 2030 (AU).

(74) Agent: F B RICE & CO; Level 23, 44 Market Street, Sydney, NWS 2000 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: GREEN WALL SYSTEM



(57) Abstract: A module (10) for use in a green wall system comprises a box having a base (12) sides (16, 18) a front (20), a rear wall (14) and a top (22). At least some of the side, rear and base define a plurality of relatively small apertures (28), typically of the order of 10 to 30 mm in effective diameter. The front (20) defines a plurality of substantially larger apertures typically of the order of 10 to 12 cm in diameter. In some embodiments, the rear wall or side walls may also define larger diameter apertures. In use, the module (10) may be lined with a permeable geo-textile bag (40) and filled with a planting mix (42). The box is closed using its top (22). The bag (40) is slit through the larger apertures in the front panel and plants (200) are inserted into the mix. Once the plants are established, the module is sandwiched between front (100) and rear (102) U-shaped frames to improve its durability and bolted together using threaded bolts and nuts. The nuts define anchor means for attaching an array of the modules to support rails defining keyhole shaped apertures mounted to a wall. In the array, there are small gaps between the modules so that they can be individually removed from the array and replaced.



(48) Date of publication of this corrected version:

20 January 2011

(15) Information about Correction:

see Notice of 20 January 2011