

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 September 2004 (16.09.2004)

PCT

(10) International Publication Number
WO 2004/078638 A2

(51) International Patent Classification⁷: **B81B**

(21) International Application Number:
PCT/US2003/034630

(22) International Filing Date: 28 October 2003 (28.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/248,876 26 February 2003 (26.02.2003) US

(71) Applicant: **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, NJ 10504 (US).

(72) Inventors: **VOLANT, Richard, P.**; 16 Fulton Drive, New Fairfield, CT 06812 (US). **FLORKEY, John E.**; 1997 Route 44, Pleasant Valley, NY 12569 (US). **GROVES, Robert, A.**; 27 Oak Crest Drive, Higland, NY 12528 (US).

(74) Agent: **SCHNURMANN, Daniel, H.**; International Business Machines Corporation, Dept- 18G/Bldg. 300-482, 2070 Route 52, Hopewell Junction, NY 12533 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MICRO-ELECTROMECHANICAL INDUCTIVE SWITCH



(57) Abstract: A micro-electro-mechanical (MEM) switch capable of inductively coupling and decoupling electrical signals is described. The inductive MEM switch consists of a first plurality of coils on a moveable platform and a second plurality of coils on a stationary platform or substrate, the coils on the moveable platform being above or below those in the stationary substrate. Coupling and decoupling occurs by rotating or by laterally displacing the coils

of the moveable platform with respect to the coils on the stationary substrate. Diverse arrangements or coils respectively on the moveable and stationary substrates allow for a multi-pole and multi-position switching configurations. The MEM switches described eliminate problems of stiction, arcing and welding of the switch contacts. The MEMS switches of the invention can be fabricated using standard CMOS techniques.

WO 2004/078638 A2