

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 May 2011 (26.05.2011)

(10) International Publication Number
WO 2011/062669 A2

PCT

(51) International Patent Classification:
E21B 23/06 (2006.01)

(21) International Application Number:
PCT/US2010/046329

(22) International Filing Date:
23 August 2010 (23.08.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/263,120 20 November 2009 (20.11.2009) US

(71) Applicant (*for all designated States except US*):
EXXONMOBIL UPSTREAM RESEARCH COMPANY [US/US]; Corp-Urc-Sw-359, P. O. Box 2189, Houston, TX 77252-2189 (US).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **HAEBERLE, David, C.** [US/US]; 14215 Spyglen Lane, Cypress, TX 77429 (US). **BARRY, Michael, D.** [US/US]; 251 N. Maple Glade Circle, The Woodlands, TX 77382 (US). **HECKER, Michael, T.** [US/US]; 16211 Castlegrove Court, Tomball, TX 77377 (US).

(74) Agents: **KOCH, Stephen, P.** et al.; Exxonmobil Upstream Research Company, Corp-Urc-Sw-359, P.O. Box 2189, Houston, TX 77252-2189 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

(54) Title: OPEN-HOLE PACKER FOR ALTERNATE PATH GRAVEL PACKING, AND METHOD FOR COMPLETING AN OPEN-HOLE WELLBORE

(57) Abstract: Zonal isolation apparatus includes at least one packer assembly and can be used in completing an open-hole portion of a wellbore, which open-hole portion extends through at least two subsurface intervals. The zonal isolation apparatus includes base pipe and filter medium, which together form a sand screen. Each packer assembly comprises at least two mechanically set packer elements. Intermediate the at least two mechanically set packer elements is at least one swellable packer element. The swellable packer element is actuated over time in the presence of a fluid such as water, oil, or a chemical. Swelling may occur should one of the mechanically set packer elements fail. The zonal isolation apparatus also includes alternate flow channel(s) that serve to divert gravel pack slurry from an upper interval to lower intervals during gravel packing operations. A method for completing a wellbore using the zonal isolation apparatus is also provided herein.



WO 2011/062669 A2