

Description

Technical Field of the Invention

The present invention relates to printing apparatus for use with impact sensitive paper.

Background Art

In many industrial, research and similar processes, it has long been desirable to have a data recording apparatus positioned where the operator can readily view the most recent values of important parameters under monitor, such as, for example, temperatures, pressures, flow rates, motor speeds, and many other quantities. The recorded data, moreover, must be presented in a manner which permits the operator to observe changes in the data, and the recorder apparatus itself must have a physical design which can operate reliably in industrial and similar environments. Among the recording apparatus heretofore used for such purposes have been the multi-point or pen recorder which printed a series of marks or a continuous line or a paper scroll, with the left-to-right location of the marks or lines representing the value of the data being recorded. This type of equipment, however, is subject to disadvantages of limited resolution, interpolation errors, and clogged pens, and the requirement for special recording chart paper. The operator, furthermore, is required to interpret the analog meaning of the record and to convert the same to digital value, where required.

It is also often necessary, in addition, that the parameters being recorded or logged for display to the operator be summarized in a form suitable for ultimate presentation in a written report or the like. A tabular form is often desirable. In the past, accordingly, the data has been extracted from the recorder charts and summarized or transcribed manually; or, in more elaborate systems, the data has been transmitted to a computer system in a different part of the plant to be summarized for inclusion in a report.

Other data logging apparatus has involved data acquisition in the form of digital printing on an adding machine-like tape; which not only involves the disadvantage of leafing through long tapes to determine trend comparisons and the like, but is decidedly unsuitable for direct use in reports.

A first important step in obviating some of these problems and disadvantages was provided by the "Digistrip" multipoint recorder of the assignee of the present invention, as described, for example, in Bulletin DR75 (July 6, 1975) of Kaye Instruments of Bedford, Massachusetts; this recorder employing impact paper recording of direct digital print-out. While improving upon direct process recording, this system was still restricted in the operator's visual access to the recording chart and in the quantity of data available at a glance for comparison, and did not provide on-line summaries or similar data compilations, and not in a format directly useable in reports and like documents.

Moreover French Patent 1285817 discloses

printing apparatus for use with impact sensitive paper which is capable of moving recording paper during printing and has a joint head which impacts one side of the paper along transverse directions in a transverse direction with respect to the longitudinal direction of the sheet to produce visible printing thereon.

Also UK Patent GB—A—570780 discloses printing apparatus where the paper being printed is moved thereafter into a receiving tray thereby to render automatic storage of the paper after printing.

Another prior patent germane to the relevant field of the present invention is GB—A—2012463 to which reference may be directed.

The automatic folding system of the printing apparatus of the type disclosed in UK Patent GB—A—570780 if used in the device disclosed in French Patent FR—A—1285817 does not ensure a proper folding of the paper within the limited dimensions of the enclosure and accordingly it is an object of the present invention to obviate this problem in the prior art.

Summary of the Invention

According to the invention there is provided printing apparatus for use with impact-sensitive paper comprising means for mounting the paper as a continuous longitudinally extending substantially flat sheet to be directly viewed from one face thereof, a print head means disposed near the bottom of the other face of the sheet, and means for causing the said print head means to impact said other face along transverse lines to produce visible printing on the said one face, means for moving the paper longitudinally after a transverse line is printed to permit immediate viewing of the data just printed, and means for maintaining in the region of the print head means the sheet vertical in its longitudinal movement characterised in the provision of means for thereafter guiding the sheet downward to a receiving tray inclined toward the direction from which the sheet issues at an acute angle to the horizontal to enable the automatic folding storage of the paper as it drops a predetermined limited vertical distance into the tray, said limited vertical distance being substantially 17.5 cms below the maximum vertical height travelled by said sheet, and said acute angle being substantially within the range 10° to 20°.

An embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings.

Brief Description of the Drawings

Figure 1 of which is an isometric view, partly broken away to illustrate details of the construction, of printing apparatus in accordance with the invention;

Figure 2 is a combined block and schematic circuit diagram of the paper drive for the apparatus of Figure 1;

Figure 3 is a waveform diagram relating to the performance of the circuit diagram of Figure 2;

Figure 4 is a fragmentary isometric view show-

ing the utilization of the printing apparatus of Figure 1 with a temperature-sensing array; and

Figure 5 is an isometric view showing the front door and data acquisition board of the printing apparatus.

Best Mode for Carrying out the Invention

A light source and optical sensor 1', mounted rearwardly with the print head 1, detects, as the head transversely traverses the apparatus, alternate transparent and opaque vertical lines on a fixed transverse strip 8, extending beyond the width of the printed page, and serving as an optical fence, with one end completely opaque, and the other end completely transparent. A special electronic circuit detects each transition from transparent to opaque as a potential print position, and the printer logic will cause the appropriate character to be printed. When the print head 1 reaches either end region and does not detect a transition for a pre-determined period of time, an associated control circuit will continue to print the next line of data or turn off the motor if there is no further data to be printed. By sensing whether the strip is completely transparent or completely opaque, the printer logic is informed whether the print head 1 is at the left or right margin of the page so that, unlike other prior printing apparatus, there is no need to have separate sensors to determine when the print head 1 is at a margin, and to determine which margin.

The control logic is designed such that printing can occur with the print 1 travelling in either transverse direction, so that it is not necessary to bring the print head 1 back to the left margin each time before starting a new line. The construction thus eliminates the typical carriage return operation of most printers. If the next line to be printed is already available, the motor 4 driving the print head 1 does not stop when a margin is detected, but it continues to drive the print head 1, and the slider-pin mechanism 6 automatically reverses the direction of the print head 1. With this type of mechanism, the next complete line to be printed is stored in the hereinafter described micro-processor memory before the printing operation of that line is started.

Exemplary components for this system are, for example, the Model IPM 129 print head of Victor Comptometer Corporation, which includes an optical sensor.

Another important feature resides in the paper feed and take-up mechanism contained within the instrument enclosure.

Paper moves continuously from the paper supply tray 10 through paper guides 9. It then passes between the platen 3 and the print head 1, as before described, vertically upward as a substantially flat sheet through a paper tension mechanism such as side friction clips 11 to the set of feed tractors 12, 12' which pull the paper from the feed tray when a new line has been printed and position it at the proper location for the next line. The print head 1 and the platen 3 must be

oriented so that the motion of the flat sheet of paper by one vertical line space will move the previous printed line into view. This permits an observer immediately to view the current data which has just been printed, unlike other types of printers. In order to maintain even line spacing, the tension clips or other mechanism 11 must maintain proper and uniform tension on the paper at the bottom of the apparatus, the same also preventing the paper from moving in the left-to-right direction and thereby providing a printed page with the desired vertical column alignment. The paper tractors 12, 12' are operated by a single stepping motor 13 through belt 14 and pulley drive mechanism 15.

Details of the printer mechanism carriage controls, sensor and other circuit and constructional details are not presented in order to avoid detracting from the novel features of the invention with well-known mechanisms; but reference to other suitable constructions is made, for example, to the Kaye Instruments "Digistrip Recorder Installation, Operation and Maintenance Manual", dated April 1978.

The electrical circuit to drive the stepping motor 13 has been designed in accordance with the best mode of the invention to minimize the power dissipated, thereby minimizing the temperature rise of the motor and the interior of the semi-sealed enclosure. The stepping-motor drive circuit preferably operates under the principle of pulse-width modulation of the voltage across the stepping motor, as later described in connection with the preferred form of Figure 2. During the time the tractor mechanism is at rest, a very low duty cycle pulse train is used to provide detent action of the mechanism. During the time the tractor mechanism is advancing the paper, a full duty cycle with a voltage which is higher than—more than twice—the rated voltage of the stepping motor is used to provide maximum and higher-than-rated torque. The stepping motor 13 is accordingly operated with lower power consumption when stationary than when moving to attain the above results. Another feature of this circuit allows positioning of the page to be maintained during a power-off/power-on sequence. This facilitates the pagination of the paper even if a power failure occurs.

A typical stepping motor suitable for use in accordance with the invention, such as the Series 87200 of North American Philips Controls Corporation, is divided into two sections, each of which has two sets of windings. In the circuit shown in Figure 2, the first section contains windings 37 and 39, and the second section, windings 41 and 43. Each winding is driven by a drive circuit D the output of which is the collector of a transistor in the common-emitter configuration. When each drive circuit D is activated, current flows from the supply voltage V_D through the corresponding motor winding and through the output transistor to ground. When the driver is deactivated, the current flowing through the winding inductance is shunted back to V_D through

a corresponding shunt diode d. This current will decay to zero in a few milliseconds due to the winding resistance and the diode forward voltage drop.

During normal operation one winding of each section is activated. Stepping is performed by making a transition from one winding to another in one section. The next step would be performed by making a transition in the other section. Flip-flop 31 controls which of windings 37 or 39 is activated, while flip-flop 32 controls which of windings 41 or 43 is activated.

The circuit of Figure 2 is placed in its quiescent or non-stepping state by the reset input to edge-triggered flip-flop 30, or as a natural result of the completion of a step operation. Flip-flop 30 serves as a master control in association with oscillators 34 and 35 and resets further flip-flops 31, 32 and 33. While in the quiescent state, the flip-flop 30 is in the off state, and, in turn, resets flip-flops 31, 32 and 33, and resets oscillator 34 and enables oscillator 35. Oscillator 35 has a time asymmetrical output which is low for 10 microseconds (μsec) and high for 500 μsec . In the quiescent state, only windings 37 and 41 are activated. The drivers place V_D across windings 37 and 39 for 10 μsec out of each 500 μsec period. The current in the windings 37 and 41 does not fall to zero, however, since the winding inductance in combination with the associated shunt diode d keeps current flowing between drive pulses. In this manner, sufficient current is provided to the stepping motor to provide detent action on the paper while the power dissipated is greatly reduced from that required during stepping. Thus, V_D can be two or more times the rated voltage of the stepping motor without causing overheating.

When the present input to master control flip-flop 30 is pulsed, as shown in the top waveform "30" of Figure 3, the stepping operation is initiated. For this mechanism, eight transitions of the winding drive circuits are required to move the paper one line space, Figure 3 indicating the sequence of events for the line space operation, with time periods T_0 through T_8 indicated at the bottom. At time T_0 , the circuit is in the quiescent state with the output of gate circuits 36 and 40 pulsed by the output 35Q, Figure 3, of oscillator 35, Figure 2. When the present pulse is received, flip-flop 30 turns on at 30Q, oscillator 35 is reset and oscillator 34 is enabled at 34Q. Oscillator 34 has a period of approximately 10msec, and the voltage V_D is placed across windings 37 and 41 with full 100% duty cycle. This brings the winding currents up to a high level to maximize stepping torque.

Oscillator 34 clocks respective flip-flops 31 and 32 at 31Q through the necessary sequence of outputs. After four oscillator pulses from 34Q, flip-flop 33 turns on as shown at 33Q. After an additional four oscillator pulses, flip-flop 33 turns off, in turn turning off master control flip-flop 30 and placing the control circuit in the quiescent state once again. The outputs of gates 36 and 40, respectively operating through the drivers D con-

nected with windings 37 and 41, are shown at 36 Out and 40 Out in Figure 3, and the outputs of circuits 34 and 42, respectively connecting the $\bar{Q}$ outputs of flip-flops 31 and 32 to operate the drivers D connected to windings 39 and 43, are illustrated at 38 Out and 42 Out, respectively.

The reset input to the master control flip-flop 30 is used to prevent partial stepping of the circuit when power is turned on by immediately placing the circuit in the quiescent state, thus preventing stepping when power is turned on and, in turn, facilitating the pagination process whereby the paper is held in the same position after a power failure as when power failed.

Unlike conventional line printers, which have available a large vertical descent to facilitate folding the fanfold paper in the proper fashion, the apparatus of the present invention embodies special means to assure a proper folding of the paper within the limited dimensions of the enclosure. These means include an upper electro-static discharge and guide bar 26 and a paper receiver tray 17 which, in accordance with the invention, must be positioned at a rather critical angle inclined to the horizontal of between substantially 10° and 20° , in order to fold the paper properly with a very limited vertical drop of less than, say, 7 inches (≈ 17.50 cms), more or less. With fanfold type paper, and the paper receiving tray thus located at such a height of less than about 7 inches (≈ 17.50 cms) below, the maximum vertical height of the path travelled by the paper, the inclination of the said tray toward the direction from which the paper issues at the said acute angle from the horizontal causes the automatic folding storage.

A feature which is not essential to the operation of the apparatus, but which adds a desirable character of low noise, is a platen 3 constructed of a composite of alternating metallic strips and vibration-damping material.

The electronics to control all printer operations is shown on a single printed circuit board 18 containing a microprocessor and all of the required logic and memory. The printer mechanism can, of course, operate independently of the data acquisition portion of the apparatus, if so desired.

Referring to Figure 5, the data acquisition portion on printed circuit board 50 has an independent microprocessor which controls all operations other than the printing of the data. In accordance with a preferred form of the invention, three types of memory are employed in the data acquisition logic. The read-only memory portion 51 is used to store permanently the programmed instructions to direct the data acquisition functions, and also contains tables which are used for conversion of digital voltage data into the proper engineering data. A second portion of memory 52, called non-volatile random access memory is used to store user-programmed parameters such as the types of input, the frequency of printing, acceptable limits of data and identifying headers to be printed at the top of each page. The third type of memory 53 is

called random access memory and is used to store the real-time data being processed from the analog inputs to the system, as is well-known.

The overall structure of the microprocessor logic on printed circuit board 50 is preferably directed by a "task manager" of the type described in an article entitled "A Task-Scheduling Executive Program for Microcomputer Systems" by David A. Townzen, appearing in *Computer Design*, June, 1977, pp. 194-202. This task manager is an efficient means of controlling task priorities so that a more important task of higher priority will temporarily interrupt a task of lesser priority in order to provide service on a real-time basis.

Suitable microprocessor apparatus is the type 8085 manufactured by Intel Corporation, with memory of the types 2716, 2114 and 5101 of Intel Corporation, or other equally well-known microprocessor apparatus.

As an example of a resulting page of summary data directly useable for reports and the like and stemming from the microprocessor-printer of the invention ($8\frac{1}{2} \times 11$ inch (21.25×27.5 cm) fanfold paper, for example), up to five lines may be made available on the sheet for customized header identification, each line having 128 characters corresponding to a field of 8 characters for each of 16 channel positions. Conventional customer-programmed alpha-numeric messages can be introduced to a conventional keyboard 54, located at the bottom of the front panel of Figure 5, for example, such that the microprocessor enables the automatic printing of the same at the top of every new fanfold page sheet. Suitable keyboard control is provided by a Brady Corporation Lite Touch (TM) panel operating in conjunction with an Intel Corporation type 8279 keyboard interface module. Programming of the header takes only a few minutes using such front panel keyboard entry. The apparatus may provide one to four lined of data, for example, to be printed in normal engineering units as a block, with a blank line inserted after each block to separate the data corresponding to a single scan, if desired. When there are too few lines remaining at the bottom of a page to print a complete block, the program may enable the paper automatically to advance to the top of the next page for header printing. The header printout may also automatically include a day's register printout in the time field locations. Alarms may be indicated by an asterisk printed in the data field of the alarm channel, and the types of printed data may be identified by an alphabetic character representing the appropriate engineering units, and matching that used on the front page panel display, printed as the last character in each channel's data field. Not counting header and margin space, approximately 40 lines per page can be available with the above-described fanfold paper for recording data. With 16 channels printed per line, 96,000 readings can be recorded on a typical stack of paper having about 150 pages.

The use of a microprocessor and its associated

logic permits each user to program the apparatus to satisfy particular requirements most effectively, and also makes possible several few and important features in the data acquisition portion of the apparatus of the invention; in particular, a novel technique for automatically assuring that the analog-to-digital conversion circuit maintains a proper zero level. To illustrate this feature, the example of the before-mentioned most advantageous use of the recorder system of Figures 1, 4 and 5 with temperature sensors, such as thermocouple arrays, will be presented.

An analog-multiplexer 23, shown in figure 4, is provided with one extra switch SW1 with a known zero voltage input. The microprocessor logic is designed, as well known, to read that extra input periodically during the multiplexing sequence, convert same to digital form by means of an analog to digital converter 19, and store the value as an offset which must be subtracted from the other input voltages. In order to obtain greater stability of the zero level, several successive readings of this zero input are maintained in memory and averaged. The average offset is subtracted from all other input signals. Suitable averaging and subtracting is performed by the microprocessor.

In the exemplary showing of application to thermocouple sensing, Figure 4 also illustrates an improvement in the art of uniform temperature references for thermocouple inputs such as that described in U.S. Patent US-A-3,648,523. The sensor system of Figure 4 employs a bar 21 of a highly thermal conductive material, such as aluminum, having opposing flat surfaces provided with a thin insulating coating on the surface 21', such as aluminum oxide, and which is in intimate thermal contact with the printed circuit board mounting screw terminal shafts 25 of all of the input terminals 22. The design permits the insertion of these terminals into a printed circuit board 23 and the insertion of a temperature sensor R1 into the highly conductive bar so that all terminals, as well as sensor R1, are maintained at very nearly the same or equal temperature. The sensor which monitors the terminal temperature is read as a separate input.

In accordance with this improvement, moreover, a single temperature-sensitive resistor R1 made of a material having known resistivity versus temperature characteristics is placed in series with a manually-adjustable resistor R2. A precision voltage V maintains a constant voltage across the series connection of the two resistors. With the temperature sensitive resistor R1 at a known temperature, the other resistor R2 is manually adjusted to provide a predetermined value of voltage across the temperature-sensitive resistor. This single adjustment assures that the proper value of voltage will be produced across the temperature-sensitive resistor at all temperatures within the operating range of the apparatus.

The microprocessor logic before described automatically adds the proper reference voltage for each type of thermocouple corresponding to

the temperature of the input terminals as determined by reading the value of voltage appearing across the temperature-sensitive resistor.

While the incorporation of these improvements with the microprocessor control of the novel recorder of the invention has been illustrated by reference to temperature measurements, moreover, it will be apparent that other types of sensors, controls and data-generating sources may also be readily employed with the novel digital multipoint recording technique and system of the invention; and that further modification will also suggest themselves to those skilled in this art, and are considered to fall within the spirit and scope of the invention as defined in the appended claims.

Claims

1. Printing apparatus for use with impact-sensitive paper comprising means for mounting the paper as a continuous longitudinally extending substantially flat sheet (2) to be directly viewed from one face thereof, a print head means (1) disposed near the bottom of the other face of the sheet, and means for causing the said print head means to impact said other face along transverse lines to produce visible printing on the said one face, means for moving the paper longitudinally after a transverse line is printed to permit immediate viewing of the data just printed, and means for maintaining in the region of the print head means the sheet vertical in its longitudinal movement characterised in the provision of means (16) for thereafter guiding the sheet downward to a receiving tray (17) inclined towards the direction from which the sheet issues at an acute angle to the horizontal to enable the automatic folding storage of the paper as it drops a predetermined limited vertical distance into the tray, said limited vertical distance being substantially 17.5 cms below the maximum vertical height travelled by said sheet, and said acute angle being substantially within the range 10° to 20°.

2. Printing apparatus as claimed in claim 1 characterised in that said guiding means (16) is a guide and electro-static discharge bar disposed transversely of said sheet.

3. Printing apparatus as claimed in claim 1 or 2 characterised by optical sensing means movable with the said print head means (1), and cooperative with transverse optical fence means comprising a central portion having alternating transparent and opaque portions for enabling optical sensing of the location of the print head means relative to the position of the sheet (2) to be printed, and end portions respectively comprising a transparent portion, and an opaque portion for enabling optical sensing determination that the print head means is at an end of the printed portion of a transverse line along said sheet and at which margin of the sheet.

4. Printing apparatus as claimed in any preceding claim, characterised by stepping motor means

for longitudinally advancing the paper sheet one line to the next, and pulse-width modulated drive circuit means for operating the stepping motor means with lower power consumption when the same is stationary than when moving, thereby to permit the same to be operated at higher than rated torque while not exceeding rated time-averaged power.

5. Printing apparatus as claimed in any preceding claim, characterised by sensing means for monitoring electrical signals to be recorded and generating digital voltage data corresponding to the same, and data acquisition means comprising microprocessor means for receiving said digital voltage data and converting the same into desired engineering data for printing.

6. Printing apparatus as claimed in claim 4, characterised in that said microprocessor means further comprises keyboard means for header and other inputs and non-volatile random access memory means for storing user-programmed parameters such as type of input, frequency of printing, acceptable limits of data and identifying headers to be printed at what will become the top of a page formed by a sheet of predetermined length of fanfold or similar paper, thereby to provide a data summary page suitable for direct report user and the like.

7. Printing apparatus as claimed in claim 6, characterised in that the microprocessor means is further provided with further random access memory means to store real-time data being processed from analog inputs from said sensing means to the apparatus.

Patentansprüche

1. Druckvorrichtung für die Verwendung eines selbstschreibenden, durch mechanische Einwirkung bedruckbaren Papiers, mit Mitteln zum Halten des Papiers in Form eines in Längsrichtung kontinuierlichen, im wesentlichen flachen und mit einer Oberflächenseite direkt sichtbaren Streifens (2), mit Druckkopfmitteln (1), die in der Nähe des hinteren Endes der anderen Oberflächenseite des Streifens angeordnet sind, mit Mitteln, die zur Erzeugung eines sichtbaren Eufdruckes auf der einen Oberflächenseite die Druckkopfmittel entlang in Querrichtung verlaufenden Zeilen mit der anderen Oberflächenseite zum Anschlag bringen, mit Mitteln, die das Papier in Längsrichtung bewegen, wenn eine Zeile in Querrichtung ausgedruckt ist, um eine sofortige visuelle Erfassung der gerade ausgedruckten Daten zu ermöglichen, sowie mit Mitteln, die den Streifen im Bereich der Druckkopfmittel senkrecht in seiner Längsbewegung halten, dadurch gekennzeichnet, daß Mittel (16) vorgesehen sind, um anschließend den Streifen nach unten in eine Aufnahme (17) zu führen, und zwar entgegen der Richtung, in der der Streifen ausgegeben wird, gegenüber der Horizontalen um einen spitzen Winkel geneigt, um ein automatisches Falten und Stapeln des Papiers zu erreichen, wenn es um einen vorgegebenen begrenzten vertikalen Abstand in die Aufnahme fällt,

the temperature of the input terminals as determined by reading the value of voltage appearing across the temperature-sensitive resistor.

While the incorporation of these improvements with the microprocessor control of the novel recorder of the invention has been illustrated by reference to temperature measurements, moreover, it will be apparent that other types of sensors, controls and data-generating sources may also be readily employed with the novel digital multipoint recording technique and system of the invention; and that further modification will also suggest themselves to those skilled in this art, and are considered to fall within the spirit and scope of the invention as defined in the appended claims.

Claims

1. Printing apparatus for use with impact-sensitive paper comprising means for mounting the paper as a continuous longitudinally extending substantially flat sheet (2) to be directly viewed from one face thereof, a print head means (1) disposed near the bottom of the other face of the sheet, and means for causing the said print head means to impact said other face along transverse lines to produce visible printing on the said one face, means for moving the paper longitudinally after a transverse line is printed to permit immediate viewing of the data just printed, and means for maintaining in the region of the print head means the sheet vertical in its longitudinal movement characterised in the provision of means (16) for thereafter guiding the sheet downward to a receiving tray (17) inclined towards the direction from which the sheet issues at an acute angle to the horizontal to enable the automatic folding storage of the paper as it drops a predetermined limited vertical distance into the tray, said limited vertical distance being substantially 17.5 cms below the maximum vertical height travelled by said sheet, and said acute angle being substantially within the range 10° to 20°.

2. Printing apparatus as claimed in claim 1 characterised in that said guiding means (16) is a guide and electro-static discharge bar disposed transversely of said sheet.

3. Printing apparatus as claimed in claim 1 or 2 characterised by optical sensing means movable with the said print head means (1), and cooperative with transverse optical fence means comprising a central portion having alternating transparent and opaque portions for enabling optical sensing of the location of the print head means relative to the position of the sheet (2) to be printed, and end portions respectively comprising a transparent portion, and an opaque portion for enabling optical sensing determination that the print head means is at an end of the printed portion of a transverse line along said sheet and at which margin of the sheet.

4. Printing apparatus as claimed in any preceding claim, characterised by stepping motor means

for longitudinally advancing the paper sheet one line to the next, and pulse-width modulated drive circuit means for operating the stepping motor means with lower power consumption when the same is stationary than when moving, thereby to permit the same to be operated at higher than rated torque while not exceeding rated time-averaged power.

5. Printing apparatus as claimed in any preceding claim, characterised by sensing means for monitoring electrical signals to be recorded and generating digital voltage data corresponding to the same, and data acquisition means comprising microprocessor means for receiving said digital voltage data and converting the same into desired engineering data for printing.

6. Printing apparatus as claimed in claim 4, characterised in that said microprocessor means further comprises keyboard means for header and other inputs and non-volatile random access memory means for storing user-programmed parameters such as type of input, frequency of printing, acceptable limits of data and identifying headers to be printed at what will become the top of a page formed by a sheet of predetermined length of fanfold or similar paper, thereby to provide a data summary page suitable for direct report user and the like.

7. Printing apparatus as claimed in claim 6, characterised in that the microprocessor means is further provided with further random access memory means to store real-time data being processed from analog inputs from said sensing means to the apparatus.

Patentansprüche

1. Druckvorrichtung für die Verwendung eines selbstschreibenden, durch mechanische Einwirkung bedruckbaren Papiers, mit Mitteln zum Halten des Papiers in Form eines in Längsrichtung kontinuierlichen, im wesentlichen flachen und mit einer Oberflächenseite direkt sichtbaren Streifens (2), mit Druckkopfmitteln (1), die in der Nähe des hinteren Endes der anderen Oberflächenseite des Streifens angeordnet sind, mit Mitteln, die zur Erzeugung eines sichtbaren Eufdruckes auf der einen Oberflächenseite die Druckkopfmittel entlang in Querrichtung verlaufenden Zeilen mit der anderen Oberflächenseite zum Anschlag bringen, mit Mitteln, die das Papier in Längsrichtung bewegen, wenn eine Zeile in Querrichtung ausgedruckt ist, um eine sofortige visuelle Erfassung der gerade ausgedruckten Daten zu ermöglichen, sowie mit Mitteln, die den Streifen im Bereich der Druckkopfmittel senkrecht in seiner Längsbewegung halten, dadurch gekennzeichnet, daß Mittel (16) vorgesehen sind, um anschließend den Streifen nach unten in eine Aufnahme (17) zu führen, und zwar entgegen der Richtung, in der der Streifen ausgegeben wird, gegenüber der Horizontalen um einen spitzen Winkel geneigt, um ein automatisches Falten und Stapeln des Papiers zu erreichen, wenn es um einen vorgegebenen begrenzten vertikalen Abstand in die Aufnahme fällt,



daß der vorgegebene begrenzte Abstand in etwa 17,5 cm unterhalb der größten vertikalen Höhe der Bewegungsbahn des Streifens liegt, und daß der erwähnte spitze Winkel etwa 10—20° beträgt.

2. Druckvorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Mittel (16) zum anschließenden Führen von einer Führung sowie von einer zur elektrostatischen Entladung dienenden Traverse gebildet sind, welche quer zu dem Streifen angeordnet ist.

3. Druckvorrichtung nach Anspruch 1 oder 2, gekennzeichnet durch optische Abtastmittel, die mit den Druckkopfmitteln (1) bewegbar sind und mit in Querrichtung verlaufenden optischen Gitter- oder Rastermitteln zusammenwirken, welche einen mittleren Bereich mit abwechselnden transparenten und lichtundurchlässigen Abschnitten aufweisen, um optisch die Lage der Druckkopfmittel relativ zu der Lage des zu bedruckenden Streifens (2) festzustellen, sowie Endbereiche mit einem transparenten Abschnitt bzw. einem lichtundurchlässigen Abschnitt besitzen, um optisch festzustellen, daß die Druckkopfmittel sich an einem Ende des zu bedruckenden Teils einer Querzeile des Streifens bzw. an dessen Rand befinden.

4. Druckvorrichtung nach einem der vorausgehenden Ansprüche, gekennzeichnet durch Schrittschaltmotormittel zum Vorwärtsbewegen des Papierstreifens von einer Zeile zur nächsten Zeile, sowie durch impulsbreiten-modulierte Antriebssteuerkreismittel zum Ansteuern der Schrittschaltmotormittel mit niedrigerem Leistungsverbrauch in der Stillstandsphase als in der Bewegungsphase, um so zu erreichen, daß die Schrittschaltmotormittel mit einem Drehmoment höher als das Nenndrehmoment betätigt werden, ohne daß im zeitlichen Mittelwert die Nennleistung überschritten wird.

5. Druckvorrichtung nach einem der vorausgehenden Ansprüche, gekennzeichnet durch Mittel zur Aufnahme elektrischer, aufzuzeichnender Signale sowie zum Erzeugen von Daten, die den elektrischen Signalen entsprechen, in Form einer digitalen Spannung, sowie durch Mittel zur Datengewinnung und/oder Aufbereitung, die Mikroprozessormittel zur Aufnahme der Daten in digitaler Form sowie zur Umformung dieser Daten in die für den Druckvorgang erforderlichen Betriebs- bzw. Maschinendaten aufweisen.

6. Druckvorrichtung nach Anspruch 4, dadurch gekennzeichnet, daß die Mikroprozessormittel weiterhin Eingabetastaturmittel sowie andere Eingänge sowie permanente RAM-Speichermittel zum Speichern von Parametern des Benutzerprogramms aufweisen, wie Art des Eingangs oder Eingangssignals, Druckfrequenz, zulässige Datengrenzen sowie Identifizierungsvermerke oder -Überschriften, die oben auf einer Seite aufgedruckt werden, welche von einem Streifen einer vorgegebenen Länge eines mehrfach gefalteten oder ähnlichen Papiers gebildet ist, um dadurch eine Seite mit einer Datenzusammenstellung bzw. Zusammenfassung zu erhalten, die als direkter Ausdruck usw. geeignet ist.

7. Druckvorrichtung nach Anspruch 5, dadurch gekennzeichnet, daß die Mikroprozessormittel weitere RAM-Speichermittel zum Speichern von Echtzeit-Daten aufweisen, die der Druckvorrichtung von analogen Eingängen der Mittel zum Aufnehmen von Daten zugeführt werden.

Revendications

1. Machine à imprimer à utiliser avec du papier sensible à l'impact comprenant des moyens de montage du papier en forme d'une feuille orientée dans la direction longitudinale, sensiblement plate, (2) pour être directement vue d'un côté, un moyen de tête d'impression (1), placé à proximité du bas de l'autre face de la feuille, et des moyens pour faire frapper ledit moyen de tête d'impression sur ladite autre face, le long de lignes transversales pour produire une impression visible sur ladite première face, des moyens de déplacement du papier dans la direction longitudinale après l'impression d'une ligne pour permettre d'examiner immédiatement les données qui viennent d'être imprimées, et des moyens, situés dans la région du moyen de la tête d'impression pour maintenir la feuille verticale, au cours de son mouvement longitudinal, caractérisée en ce qu'il est prévu des moyens (16) pour guider ensuite la feuille vers le bas en direction d'un plateau récepteur (17), incliné vers la direction d'où vient la feuille sous un angle aigu par rapport à l'horizontale afin de permettre le stockage avec pliage automatique du papier au fur et à mesure qu'il tombe d'une distance verticale prédéterminée dans le plateau, ladite distance verticale prédéterminée étant sensiblement égale à 17,5 cm au-dessous de la hauteur verticale maximale parcourue par ladite feuille, et ledit angle aigu étant sensiblement compris dans la gamme allant de 10° à 20°.

2. Machine à imprimer selon la revendication 1, caractérisée en ce que lesdits moyens de guidage (16) sont constitués par un guide et un barreau à décharge électrostatique disposé en travers de la feuille.

3. Machine à imprimer selon l'une des revendications 1 ou 2, caractérisée par des moyens détecteurs optiques, mobiles avec ledit moyen de la tête d'impression (1) et coopérant avec des moyens de bande optique transversale comprenant une portion centrale ayant des portions transparente et opaque pour permettre la détection optique de l'emplacement du moyen de tête d'impression par rapport à la position de la feuille (2) à imprimer, ainsi que des portions extrêmes constituées respectivement d'une portion transparente et d'une portion opaque pour permettre la détermination par détection optique de la position de la tête d'impression à une extrémité de la portion imprimée d'une ligne transversale le long de ladite feuille et de la marge de la feuille.

4. Machine à imprimer selon l'une quelconque des revendications précédentes, caractérisée par des moyens de moteur pas à pas pour avancer le papier dans la direction longitudinale, d'une ligne



à la suivante, et des moyens à circuits de commande du moyen à moteur pas à pas, à modulation par largeur d'impulsions, pour faire fonctionner ce moteur avec une plus faible consommation d'énergie quand il est à l'arrêt que lorsqu'il tourne, en permettant ainsi à ce moteur de fonctionner avec un couple supérieur au couple nominal sans dépasser la puissance nominale, dont la moyenne est calculée dans le temps.

5. Machine à imprimer selon l'une quelconque des revendications précédentes, caractérisée par des moyens détecteurs pour surveiller des signaux électriques à enregistrer et générer des données de tension numérique correspondant à ces signaux et des moyens de saisie des données comprenant des moyens à microprocesseur pour recevoir lesdites données de tension numérique et les convertir en données techniques pour l'impression.

6. Machine à imprimer selon la revendication 4,

caractérisée en ce que lesdits moyens à microprocesseur comprennent encore de moyens à clavier pour le titre et d'autres entrées ainsi que des moyens de mémoire morte pour le stockage des paramètres programmés par l'utilisateur, tels que le type d'entrée, la fréquence d'impression, les limites acceptables des données et les titres d'identification à imprimer dans ce qui deviendra le haut d'une page formée par une feuille de longueur prédéterminée de papier à pliage en accordéon ou autre semblable, de façon à établir une page résumée des données susceptible d'être utilisée directement dans un rapport ou autre document du même type.

7. Machine à imprimer selon la revendication 6, caractérisée en ce que les moyens à microprocesseur comprennent en plus des moyens de mémoire vive pour stocker les données en temps réel à traiter à partir des entrées analogiques provenant desdits détecteurs de la machine.



* C L M S *

25

30

35

40

45

50

55

60

65

8