
CASTING CUP ASSEMBLY FOR FORMING AN OPHTHALMIC DEVICE

FIELD OF THE INVENTION

[0001] This invention relates, in one embodiment, to a casting cup assembly for forming ophthalmic devices such as contact lenses.

BACKGROUND

[0002] Many ophthalmic devices, including contact lenses, surgical lenses, intraocular lenses, and the like, are often made by performing a polymerization reaction within a casting cup assembly. The casting cup assembly includes a basecurve mold, which forms the portion of the device that rests against the eye, and a frontcurve mold, which forms the portion of the device facing away from the eye. A reaction mixture, which includes one or more polymerizable monomers and other components, is disposed in the frontcurve mold. Thereafter, the basecurve mold is pressed against the frontcurve mold and the reaction mixture is forced to adopt the shape of the volume defined between the two molds. After properly being positioned, the reaction mixture is subjected to polymerization conditions (e.g. photopolymerization or other suitable technique). The resulting polymer is removed from the casting cup assembly and subjected to post-polymerization processing (e.g. rinsing, hydration, etc) to provide a finished ophthalmic device. During this post-polymerization processing, careful inspection of the lenses often

reveals a substantial number of the lenses contain defects.

[0003] Defects include a variety of fabrication errors such as holes in the lenses, tears in the edges, the presence rings of excess polymer around the ophthalmic device, and other similar defects. Therefore, an improved method for providing ophthalmic devices is desired that reduces the occurrence of these defects.

SUMMARY OF THE INVENTION

[0004] Disclosed in this specification is a casting cup assembly comprising precision manufactured frontcurve and basecurve molds which include a ring that circumscribes the respective concave and convex mold surface. When the casting cup is assembled, the rings align with high precision and prevent de-centering and tilting of the concave and convex mold surfaces which, in turn, reduces edge defects.

[0005] An advantage that may be realized in the practice of some disclosed embodiments of the casting cup assembly is the reduction of edge defects by minimizing the de-centering and tilting of the concave and convex mold surface surfaces of a casting cup assembly.

[0006] In one exemplary embodiment, a casting cup assembly is disclosed. The casting cup assembly comprises a frontcurve mold with a concave mold surface circumscribed by a ring. The assembly further comprises a basecurve mold with a convex mold surface and a second ring. When the frontcurve mold is mated with the basecurve mold, edges of the respective rings mate and minimize the de-centering and

tiling of the mold surfaces.

[0007] In another exemplary embodiment, a casting cup assembly is disclosed. The casting cup assembly comprises frontcurve mold with a concave mold surface circumscribed by a ring. The assembly further comprises a basecurve mold with a convex mold surface and a second ring. The basecurve has a textured surface that is continuous with the convex mold surface. The textured surface is between the base of the convex mold surface and the second ring. When the frontcurve mold is mated with the basecurve mold, edges of the respective rings mate.

[0008] In another exemplary embodiment, a method of forming a casting cup assembly is disclosed. The method includes the step of precision lathing a casting cup assembly.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The present invention is disclosed with reference to the accompanying drawings, wherein:

[00010] FIGS. 1A and 1B are profile views of select portions of a prior art casting cup assembly shown in an unassembled and assembled state, respectively;

[00011] FIG. 2A is a top view of a casting cup assembly showing the eccentricity between the frontcurve and basecurve molds and FIG. 2B is a cross-sectional view of a casting cup assembly;

[00012] FIG. 2C is a graph correlating eccentricity to edge defects and FIG. 2D

is a cross-sectional view showing tilting between frontcurve and basecurve molds;

[00013] FIG. 3A and FIG. 3B are profile views of select portions of a casting cup assembly shown in an unassembled and assembled state, respectively;

[00014] FIGS. 4A and 4B are top views of a frontcurve mold and basecurve mold, respectively;

[00015] FIG. 4C is a top view of a casting cup assembly showing the alignment of a basecurve mold and a frontcurve mold;

[00016] FIGS. 5A and 5B are profile views of two mated rings respectively located on a basecurve mold and a frontcurve mold; and

[00017] FIG. 6 is a profile view of a select portion of a frontcurve mold showing first and second continuous rings while FIG. 7 is a profile view of a selection portion of a frontcurve and basecurve mold wherein the basecurve mold includes a textured surface.

[00018] Corresponding reference characters indicate corresponding parts throughout the several views. The examples set out herein illustrate several embodiments of the invention but should not be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION

[00019] Some of the factors that impact the occurrence of edge defects in ophthalmic devices include the relative de-centering and/or tilting of the basecurve mold and the frontcurve mold in which the devices are cured. Referring to FIGS. 1A and 1B, a

prior art casting cup assembly 100 is shown. Casting cup assembly 100 includes frontcurve mold 102 and basecurve mold 104 that mate to define a volume 106. An ophthalmic device is cured within this volume 106. In practice, these mold pieces are often not properly centered and/or become tilted.

[00020] FIG. 2A provides a schematic top-view that depicts de-centering of a convex mold 204 (centered about point 202) disposed within a concave mold 200 (centered about point 206). In FIG. 2A, the center points are offset by eccentricity 208, resulting the distance 210 on one side of the mold being less than the distance 212 on the other side of the mold. After the reaction mixture is cured, the non-hydrated, but fully cured lenses, are immersed in an epoxy mixture and the epoxy cured to lock the lenses in a fixed position. The epoxy and locked lenses are subsequently sliced in half, polished, and analyzed under a microscope for defects. In those situations where the two molds were not centered, edge defects (chips, tears, rings, etc) were more common. FIG. 2B provides a cross-sectional view showing mold pieces are not properly centered. Due to the de-centering in FIG. 2B, the volume 106 is not properly sealed. See distance 212. This improper seal translates into edge defects when the resulting lens is de-molded.

[00021] FIG. 2C graphically depicts the results of certain de-centering experiments. The graph in FIG. 2C correlates eccentricity (in microns) to edge defects. In the first example, lenses with high edge defects were measured with respect to the distance between a first side (214) and a second side (216). In the embodiment of FIG. 2C, approximately a ten micron gap is present showing the eccentricity. In the second

example, lenses with low edge defects were measured in a similar fashion (first side 218, second side 220) and approximately a five micron eccentricity is shown. Without wishing to be bound to any particular theory, applicants believe the low eccentricity between the convex and concave mold surfaces results in reduced edge defects corresponds to those lenses where the volume between the mold surfaces is properly sealed. Applicants suggest sealing defects are caused by de-centering and/or tilting of the mold pieces.

[00022] FIG. 2D provides a schematic top-view that depicts tilting of a convex mold 200 disposed within a concave mold 204. Volume 106 is not properly sealed as show by the formation of distance 212. The edge defects associated with such an improper seal are still problematic.

[00023] FIGS. 3A and 3B are profile views of a portion of casting cup assembly 300 shown before (FIG. 3A) and after (FIG. 3B) basecurve mold 304 is disposed on frontcurve mold 302.

[00024] Frontcurve mold 302 includes a concave mold surface 306 which forms the forward-facing portion of the ophthalmic lens. The perimeter 310 of concave mold surface 306 is sized to receive convex mold surface 316 of basecurve mold 304. Frontcurve mold 302 further includes a planar top surface 312 that is contiguous with perimeter 310. A first ring 314 circumscribes concave mold surface 306 and extends from the top-side of planar top surface 312 and above perimeter 310. In one embodiment, the ring is a continuous ring. The ring is precision manufactured with

respect to the knife edge of the frontcurve mold 302. First ring 314 provides the first half of an interlocking feature described in further detail below. This interlocking feature helps minimize de-centering and tilting of concave mold surface 306 and convex mold surface 316.

[00025] Basecurve mold 304 includes convex mold surface 316 which forms the portion of the ophthalmic lens that contacts an eye. The perimeter 320 of convex mold surface 316 is sized to be disposed just outside perimeter 310 when assembly 300 is formed with the adjacent planar region 330 contiguous with perimeter 320. The curvature of concave mold surface 306 and convex mold surface 316 are different such that, when basecurve mold 304 is disposed on frontcurve mold 302, a stop 326 is created which defines volume 328. The shape of volume 328 determines certain physical parameters of the resulting ophthalmic lens. Basecurve mold 304 includes a second ring 324 which, in one embodiment, is a continuous ring. The second ring is precision manufactured with respect to the axis of the basecurve mold optical surface. The second ring 324 circumscribes the convex mold surface 316 and extends from the bottom surface 322 past the perimeter 320. Second ring 324 provides the second half of the interlocking feature.

[00026] Some machinery used in the manufacturing of ophthalmic devices attempts to position the mold pieces automatically. These machines are rather complex. The interlocking feature moves this complexity away from the machinery and into the mold pieces. The resulting mold pieces are then used to fabricate ophthalmic devices

with a lower frequency of defects and in a more cost effective manner. Due to the self-aligning and self-locking features provided by the interlocking feature, stop 326 is established in a reliable and homogeneous fashion such that there is little variation from one ophthalmic device to the next.

[00027] Referring to FIGS. 4A and 4B, the radius of the two rings is shown. FIG. 4A depicts the top of frontcurve mold 302 showing a first radius 400 of the first ring 314. FIG. 4B depicts basecurve mold 304 showing a second radius 402 of the second ring 324 which, in FIG. 4B, is continuous. In another embodiment, not shown, one or both of the rings is divided into a plurality of segments separated by spaces. In the embodiment depicted in FIG. 1A and FIG. 4B, the first radius 400 of the first ring 314 is smaller than the second radius 402 of the second ring 324 which causes the first ring 314 to be inside the second ring 324 when the casting cup assembly 300 is assembled. See FIG. 4C. As shown in FIG. 4C, planar region 330 and planar top surface 312 are vertically stacked when casting cup assembly 300 is assembled. In another embodiment, not shown, the first radius 400 is larger than the second radius 402 and the second ring 324 is inside of the first ring 314 when the casting cup assembly 300 is assembled. In either embodiment, this difference in radii permits the two rings to contact each other along their edges to establish the interlocking feature. See FIG. 5A and 5B. This interlocking feature minimizes the eccentricity between concave mold surface 306 and convex mold surface 316 thereby reducing edge defects in the resulting ophthalmic device.

[00028] FIG. 5A depicts an exemplary embodiment where first ring 314 is within second ring 324. First ring 314 has a first edge 504 that is configured to mate with a second edge 502 of the second ring 324. In the exemplary embodiment of FIG. 5A, the terminus of each ring (e.g. terminus 512 of second ring 324) does not contact the other ring's supporting structure (e.g. planar top surface 312) and does not function as a stop. In FIG. 5A, the terminus 512 of second ring 324 is spaced from the planar top surface 312 of the frontcurve mold 302 by a gap 506. Likewise, the terminus 514 of first ring 314 is spaced from the planar region 330 of the basecurve mold 304 by a gap 516. The mating of first edge 504 and second edge 502 forms an interference fit 518 between these two edges which prevents de-centering of concave mold surface 306 and convex mold surface 316. In one embodiment, the first ring 314 and the second ring 324 have a cylindrical shape such that first edge 504 and second edge 502 are parallel. This prevents either ring from functioning as a stop and ensuring the stop 326 is properly established at the knife edge.

[00029] When stop 326 is properly established and volume 328 is defined, the interlocking feature minimizes both de-centering and tilting. The parallel first edge 504 and second edge 502 minimize de-centering by forming the interference fit 518. Gap 506 minimizes tilting. Should one of the mold pieces begin to tilt, the gap 506 (on one side of the mold piece or the other) will contact planar top surface 312 and bottom out. The tilt, therefore, cannot exceed the gap 506. By precision manufacturing the mold pieces, the magnitude of the gap 506 can be controlled which, in turn, controls the amount of tilt that

is permitted. In one embodiment, gap 506 is less than 6.5 microns.

[00030] Likewise, when stop 326 is properly established and volume 328 is defined, the interlocking feature also permits one to minimize the use of excess reaction mixture that is squeezed out of volume 328. Since the volume 328 is well defined, a more controlled volume of reaction mixture may be used. Any excess reaction mixture forms a thin film of excess monomer which is subsequently removed during post-polymerization processing. In contrast, many prior art techniques have significantly more excess monomer which requires extensive post-polymerization processing to remove.

[00031] FIG. 5B depicts a second exemplary embodiment, where first edge 504 and second edge 502 have been modified to provide matching first and second grooves. In the embodiment of FIG. 5B, first ring 314 has first grooves 508 and second ring 324 has second grooves 520. The protrusions on the first grooves 508 moves against the protrusions on the second grooves 520 and provides a locking mechanism similar to a ratchet. Such an interlocking feature provides a finite number of locking positions. In FIG. 5B, first grooves 508 and second grooves 520 both include a plurality of tracks. In other embodiments, first grooves 508 or second grooves 520 have a single protrusion that mate with the corresponding grooves on the opposing ring. The grooves may be formed by, for example, increasing the feed-rate on the lathe that forms the respective mold. This permits a small pitch to be formed.

[00032] By providing an interlocking feature that circumscribes the concave

mold surface 306 and the convex mold surface 316 the eccentricity between these surfaces can be minimized. The edge defects that are associated with such eccentricity is therefore reduced. In one embodiment, the eccentricity is less than about thirty microns. In another embodiment, the eccentricity is less than about fifteen microns. In yet another embodiment, the eccentricity is less than about five microns. Additionally, the interlocking feature also prevents tilting by maintaining the frontcurve mold 302 and the basecurve mold 304 in a parallel orientation which further reduces defects. In one embodiment, the two molds are parallel within about ten degrees. In another embodiment, the two molds are parallel within about five degrees. In another embodiment, the two molds are parallel within about three degrees. In yet another embodiment, the two molds are parallel within about one degree.

[00033] FIG. 6 is a profile view of a section of frontcurve mold 602 that includes concave mold surface 606 with perimeter 610. A top planar surface 612 is also shown that has a first ring 614 circumscribing concave mold surface 606 that extends from planar top surface 612 and above perimeter 610. Frontcurve mold 602 further comprises a second continuous ring 600 that functions as a barrier to contain the reaction mixture disposed within concave mold surface 606. When the basecurve mold is mated to frontcurve mold 302, the volume of the reaction mixture is restricted and excess fluid is pressed against second continuous ring 600. The presence of second continuous ring 600 helps control the formation of ring defects in the resulting ophthalmic lens by restriction the flow of the reaction mixture. In one embodiment, second continuous ring 600 abuts a

surface of the corresponding basecurve mold that has been modified to permit second continuous ring 600 to adhere to the basecurve mold. This surface may be modified (e.g. rings, surface roughening, surface energy modification, etc) to cause the second continuous ring 600 to stick to the basecurve mold at demold.

[00034] FIG. 7 is a profile view of another exemplary assembly. Basecurve mold 704 of FIG. 7 includes a textured surface 700 disposed between the perimeter 720 of convex mold surface 716 and the bottom surface 722, from which second ring 724 extends. Textured surface 700 is joined to bottom surface 722 by vertical spacer 703 which provides a space 705 for first ring 714 to reside. Textured surface 700 provides a large surface area which promotes the adhesion of polymerized material. Textured surface 700 is vertically stacked above top planar surface 712, which provides a smooth surface that promotes the release of polymerized material. When the reaction mixture is cured and the frontcurve and basecurve molds are separated, the excess polymeric ring tends to adhere to the textured surface 700 and be separated from the cured ophthalmic lens. The removal of the ring of excess polymer by its adhesion to textured surface 700 helps further minimize the occurrence of edge defects.

[00035] The molds may be formed by, for example, precision lathing techniques such as diamond-point turning. In one embodiment, the rings of the interlocking feature are formed by diamond-point-turning in the same tooling step (i.e. the molds are not removed from the lathe during the process) as the formation of the optical surface of the convex and concave mold surfaces. This ensures accurate concentricity of the locking

feature with respect to the axis and orthogonal plane of the respective mold surface. In one embodiment, the optical surface of the mold piece, as well as the associate ring that forms the interlocking feature, are both precision manufactured in a single pass. For example, a single pass with a lath may form both the optical surface and the interlocking feature.

[00036] While the invention has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof to adapt to particular situations without departing from the scope of the disclosure. Therefore, it is intended that the claims not be limited to the particular embodiments disclosed, but that the claims will include all embodiments falling within the scope and spirit of the appended claims.

What is claimed is:

1. A casting cup assembly for forming an ophthalmic device, the assembly comprising:
 - a frontcurve mold comprising:
 - a concave mold surface on a top-side of the frontcurve mold, the concave mold surface having a perimeter that is surrounded by, and contiguous with, a planar top surface;
 - a first ring circumscribing the concave mold surface and extending from the planar top surface and above the perimeter, the planar top surface being within the first ring;
 - a basecurve mold comprising:
 - a convex mold surface on a bottom-side of the basecurve mold, the convex mold surface having a perimeter that is surrounded by a bottom surface;
 - a second ring circumscribing the convex mold surface and extending from the bottom surface and past the perimeter;wherein the first ring has a first radius and the second ring has a second radius, the first and second radii being different and configured to mate such that a first edge of the first ring contacts a second edge of the second ring when the basecurve mold is disposed on the frontcurve mold.
2. The assembly as recited in claim 1, wherein the concave mold surface and convex mold surface have different curvatures such that, when the basecurve mold is disposed on the frontcurve mold, a stop is defined by a point-of-contact between the concave mold surface and convex mold surface thereby establishing a volume between the concave mold surface and convex mold surface.
3. The assembly as recited in claim 2, wherein the second ring has a terminus that is spaced from the top planar surface by a first gap when the basecurve mold is

disposed on the frontcurve mold and the stop have established the volume between the concave mold surface and convex mold surface.

4. The assembly as recited in claim 2, wherein the bottom surface that surrounds the perimeter of the convex mold surface includes a planar region, the planar region being between the perimeter and the second ring.
5. The assembly as recited in claim 4, wherein the first ring has a terminus that is spaced from the planar region by a second gap when the basecurve mold is disposed on the frontcurve mold and the stop have established the volume between the concave mold surface and convex mold surface.
6. The assembly as recited in claim 3, wherein the first gap is less than 6.5 microns.
7. The assembly as recited in claim 5, wherein the second gap is less than 6.5 microns.
8. The assembly as recited in claim 1, wherein the first edge of the first ring includes a plurality of ridges and the second edge of the second ring includes at least one protrusion that mates with at least one of the ridges when the basecurve mold is disposed on the frontcurve mold.
9. The assembly as recited in claim 1, wherein the second edge of the second ring includes a plurality of ridges and the first edge of the first ring includes at least one protrusion that mates with at least one of the ridges when the basecurve mold is disposed on the frontcurve mold.
10. The assembly as recited in claim 1, wherein the first edge and second edge are parallel.

11. The assembly as recited in claim 1, wherein the first edge of the first ring and the second edge of the second ring form an interference fit when the basecurve mold is disposed on the frontcurve mold.
12. The assembly as recited in claim 1, wherein the frontcurve mold further comprises a second continuous ring circumscribing the concave mold surface and extending from the planar top surface and above the perimeter, the second continuous ring being within the first ring.
13. The assembly as recited in claim 2, wherein the first radius of the first ring and the second radius of the second ring have an eccentricity of thirty microns or less when the basecurve mold is disposed on the frontcurve mold and the stop has established the volume between the concave mold surface and convex mold surface.
14. The assembly as recited in claim 2, wherein the first radius of the first ring and the second radius of the second ring have a eccentricity of fifteen microns or less when the basecurve mold is disposed on the frontcurve mold and the stop has established the volume between the concave mold surface and convex mold surface.
15. The assembly as recited in claim 2, wherein the first radius of the first ring and the second radius of the second ring have a eccentricity of five microns or less when the basecurve mold is disposed on the frontcurve mold and the stop has established the volume between the concave mold surface and convex mold surface.
16. The assembly as recited in claim 2, wherein the frontcurve mold and basecurve mold are parallel within five degrees or less when the basecurve mold is disposed

on the frontcurve mold and the stop has established the volume between the concave mold surface and convex mold surface.

17. The assembly as recited in claim 2, wherein the frontcurve mold and basecurve mold are parallel within one degree or less when the basecurve mold is disposed on the frontcurve mold and the stop has established the volume between the concave mold surface and convex mold surface.
18. A casting cup assembly for forming an ophthalmic device, the assembly comprising:
 - a frontcurve mold comprising:
 - a concave mold surface on a top-side of the frontcurve mold, the concave mold surface having a perimeter that is surrounded by, and contiguous with, a planar top surface;
 - a first ring circumscribing the concave mold surface and extending from the planar top surface and above the perimeter, the planar top surface being within the first ring;
 - a basecurve mold comprising:
 - a convex mold surface on a bottom-side of the basecurve mold, the convex mold surface having a perimeter that is surrounded by a bottom surface, the bottom surface including a textured surface contiguous with convex mold surface and between the base and the second ring;
 - a second ring circumscribing the convex mold surface and extending from the bottom surface and past the perimeter;wherein the first ring has a first radius and the second ring has a second radius, the first and second radii being different and configured to mate such that a first edge of the first ring contacts a second edge of the second ring when the basecurve mold is disposed on the frontcurve mold.

19. A method for forming a casting cup assembly comprising the steps of:
- precision lathing a frontcurve mold with a lathe, the frontcurve mold comprising a concave mold surface on a top-side of the frontcurve mold, the concave mold surface having a curved surface that is surrounded by, and contiguous with, a planar top surface;
- precision lathing a first ring in the frontcurve mold during the step of precision lathing the frontcurve mold such that the first ring circumscribes the concave mold surface and extends from the planar top surface and above the curved surface, the planar top surface being within the first ring, wherein the step of lathing the frontcurve mold and the step of lathing the first ring are performed without removing the frontcurve from the lathe;
- precision lathing a basecurve mold comprising a convex mold surface on a bottom-side of the basecurve mold, the convex mold surface having a base that is surrounded by a bottom surface; and
- precision lathing a second ring in the basecurve mold during the step of precision lathing the basecurve mold such that the second ring circumscribes the convex mold surface and extends from the bottom surface and past the base, the textured surface being within the second ring, wherein the step of lathing the basecurve mold and the step of lathing the second ring are performed without removing the basecurve from the lathe.
20. The method as recited in claim 19, wherein the steps of precision lathing the frontcurve mold and precision lathing the first ring are performed by diamond-point turning.