

SPECIFICATION

FUSE

FIELD OF THE INVENTION

5 The present invention relates to a fuse. More particularly, the present invention relates to a blade-type fuse in which a fuse element, having a fusible portion provided between a pair of parallel flat-plate terminal portions, is mounted within an insulating housing.

10

BACKGROUND ART

 A related fuse 50, shown in Fig. 7, is a blade-type fuse in which a fuse element 56 is formed by providing a fusible portion 52 between a pair of parallel flat-plate metal
15 terminals (hereinafter referred to as "flat-plate terminals") 51 and 51, and a proximal end portion of this fuse element 56 (at which the fusible portion 52 is provided) is received in an insulating housing 53.

 Each of the flat-plate terminals 51 includes a terminal
20 body portion 54, received in the insulating housing 53, and a tab terminal portion 55 considerably projecting outwardly (downwardly in Fig. 7) from the insulating housing 53.

 The fusible portion 52, having a predetermined cross-sectional area, extends between opposed inner side edges
25 54a and 54a of the flat-plate terminals 51 and 51.

As shown in Fig. 8, the fuse 50 is mounted in a fuse mounting portion 60 such as a fuse box, and the tab terminal portions 55 are fixedly gripped by mating terminals 61 of the fuse mounting portion 60, respectively, and therefore are
5 electrically connected to these mating terminals 61, respectively.

As shown in Fig. 9, the mating terminal 61 is, for example, a so-called tuning fork-type connection terminal comprising a terminal piece portion formed at one end of a bus bar, and
10 a distal end portion of this terminal piece portion is bifurcated by a slot 61b of a U-shaped contour extending in a direction of extending of the terminal piece portion, and upper ends of this bifurcated distal end portion are bulged inwardly toward each other to form a pair of gripping portions
15 61a and 61a, respectively.

However, if the tab terminal portions 55 (the lower portions of the flat-plate terminals 51 in Fig. 9) are merely supported by and fixed to the mating terminals 61, respectively, when the fuse 50 is mounted in the fuse mounting portion 60,
20 the balance of supporting of the fuse in the fuse mounting portion 60 is not good.

Therefore, fuse guide walls 62, which support the insulating housing 53, and serve to guide the insertion of the fuse during the mounting operation and also to prevent the
25 deflection and the like of the fuse 50 in its mounted condition,

must be provided at the fuse mounting portion 60 as shown in Fig. 8.

The fuse mounting portion 60 has an insulating wall 63 for preventing a leakage of current between the tab terminal portions 55 and 55 of the mounted fuse 50. This insulating wall 63 need to have a sufficient height in the direction of the length of the tab terminal portions 55 and 55 considerably projecting outwardly from the insulating housing 53. An upper end of the insulating wall 63 is abutted against a lower end edge of the insulating housing 53, thereby positioning the fuse 50 relative to the fuse mounting portion 60.

Therefore, the height of the fuse mounting portion 60 in the fuse-mounting direction is increased because of the provision of the fuse guide walls 62 and the insulating wall 63, and this has invited a problem that the fuse box or the like is increased in size. In addition, the fuse guide walls 62 need to have a high molding precision so as to prevent the deflection of the fuse 50.

And besides, for mounting the fuse 50 in the fuse mounting portion 60, each tab terminal portion 55 must be gripped by the gripping portions 61a and 61a of the mating terminal 61 disposed in a deep bottom portion enclosed by the fuse guide wall 62 and the insulating wall 63, and therefore the efficiency of the inserting operation was not good.

Furthermore, the tab terminal portions 55 of the

flat-plate terminals 51 of the fuse element 56 considerably project outwardly from the insulating housing 53, and therefore there have been encountered problems that upon contact of a plurality of fuses 50 with each other during transport or others, 5 the tab terminal portions 55 of these fuses are damaged, and that the fusible portion 52 is liable to be deformed or broken by an external force applied to the tab terminal portions 55 upon contact with other member.

Therefore, it is an object of the present invention to 10 solve the above problems, and more specifically to provide a good fuse in which a balance of supporting of the fuse in a fuse mounting portion is enhanced while the fuse mounting portion can be formed into a small size, and the efficiency of an inserting operation can be enhanced. Moreover, the 15 deformation and breakage of a fusible portion by an external force can be prevented.

SUMMARY OF THE INVENTION

The above object of the present invention is achieved 20 by a fuse which comprises a fuse element including a pair of parallel flat-plate terminal portions, and a fusible portion formed between inner side edges of the flat-plate terminal portions; and an insulating housing covering the fusible portion and upper end edges and the inner side edges of the 25 flat-plate terminal portions, wherein a middle portion of each

of the flat-plate terminal portions in a mounting direction of the fuse can be fixedly gripped between gripping portions of each mating terminal of a fuse mounting portion in a plate thickness direction of the flat-plate terminal portions, so
5 that the flat-plate terminal portions are electrically connected respectively to the mating terminals.

Further, the above object of the present invention is achieved by a fuse which comprises a fuse element including a pair of parallel flat-plate terminal portions, and a fusible
10 portion formed between inner side edges of the flat-plate terminal portions; and an insulating housing covering the fusible portion and upper end edges and the inner side edges of the flat-plate terminal portions, wherein middle portions of the flat-plate terminal portions, that are respectively
15 located at lateral positions relative to the fusible portion, can be fixedly gripped between gripping portions of mating terminals of a fuse mounting portion in a plate thickness direction of the flat-plate terminal portions.

In the above construction, the fuse element, in which
20 the inner side edges and upper end edges of the flat-plate terminal portions and the fusible portion are covered with the insulating housing, does not have any tab terminal portions considerably projecting outwardly from the insulating housing as in the related fuse.

25 Therefore, even when a plurality of fuses are brought

into contact with each other during transport or others, the fuse elements, each having no tab terminal portion projecting from the insulating housing, are not liable to be brought into contact with each other, and besides are not liable to receive
5 an external force which would be produced upon contact with other member. Therefore, the flat-plate terminal portions are prevented from damage, and also an external force is prevented from being applied to the fusible portion, thus preventing the fusible portion from being deformed or broken.

10 The middle portion of each flat-plate terminal portion of the fuse element in the mounting direction is fixedly gripped by the mating terminal in the direction of the plate thickness of the flat-plate terminal portion. Therefore, as compared with the related fuse in which the tab portions, projecting
15 from the insulating housing, are adapted to be fixedly supported, the balance of supporting of the fuse in the fuse mounting portion is better, and the deflection of the fuse in its mounted condition is suppressed, and besides the overall height of the fuse can be reduced.

20 Therefore, fuse guide walls of the fuse mounting portion do not need to have a high molding precision so as to prevent the deflection and the like of the fuse, and also the height of the fuse guide walls can be reduced. Therefore, the fuse mounting portion can be formed into a small size, and besides
25 the efficiency of the fuse-inserting operation can be enhanced.

In the case where the middle portion of each flat-plate terminal portion, that is located at a lateral position relative to the fusible portion, is adapted to be fixedly gripped by the mating terminal of the fuse mounting portion in the direction of the plate thickness of the flat-plate terminal portion, the substantially central portion of each flat-plate terminal portion in the mounting direction is fixedly gripped by the mating terminal in the direction of the plate thickness of the flat-plate terminal portion, and by doing so, the balance of supporting of the fuse in the fuse mounting portion is made better.

Further, according to a preferred embodiment, the insulating housing includes positioning abutment portions which abut respectively against the mating terminals so as to position the fuse, so that the fuse is directly positioned relative to the mating terminals, and therefore the fuse does not need to be positioned relative to the insulating wall and others of the fuse mounting portion, and the accurate positioning can be effected regardless of the molding precision of the fuse mounting portion.

Further, according to the fourth aspect of the present invention, it is preferable that the insulating housing covers outer side edges of the flat-plate terminal portions. With this construction, the exposure of the fuse element is reduced to the minimum of the required amount, and therefore the damage

prevention and the protection of the fusible portion can be achieved more positively.

Further, according to a preferred embodiment of the present invention, the insulating housing comprises a pair of housing members which are integrally connected together in a manner to hold the fuse element therebetween in the plate thickness direction of the flat-plate terminal portions, and a pair of large and small pins are formed on and project from an inner surface of each of the housing members, and wherein the pins pass respectively through corresponding through holes, formed through the flat-plate terminal portions, and then are fitted respectively in fitting holes formed in the inner surface of the housing member to which the pins are opposed. With this construction, even if the outer side edges and lower end edges of the flat-plate terminal portions receive an external force due to contact with another member, the external force is not directly applied to the fusible portion easily because the flat-plate terminal portions are penetrated and supported by the pins of each of the housing members.

Therefore, a balance of supporting of the fuse in a fuse mounting portion is enhanced while the fuse mounting portion can be formed into a small size, and the efficiency of an inserting operation can be enhanced. Moreover, the deformation and breakage of a fusible portion by an external force can be prevented.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an exploded, perspective view showing a first embodiment of a fuse of the present invention;

Fig. 2 is a front-elevational view of the fuse of Fig. 1;

Fig. 3 is a front-elevational view showing a condition in which the fuse of Fig. 1 is mounted in a fuse mounting portion;

10 Fig. 4 is a side-elevational view showing a condition in which the fuse of Fig. 1 is mounted in the fuse mounting portion;

Fig. 5 is a front-elevational view showing a second embodiment of a fuse of the present invention;

15 Fig. 6 is a front-elevational view showing a third embodiment of a fuse of the present invention;

Fig. 7 is a front-elevational view showing a related fuse;

20 Fig. 8 is a front-elevational view showing a condition in which the fuse of Fig. 7 is mounted in a fuse mounting portion; and

Fig. 9 is a side-elevational view showing a condition in which the fuse of Fig. 7 is mounted in the fuse mounting portion.

DESCRIPTION OF THE PREFERRED EMBODIMENTS OF THE INVENTION

One preferred embodiment of a fuse of the present invention will now be described in detail with reference to the accompanying drawings.

5 Fig. 1 is an exploded, perspective view showing the first embodiment of the fuse of the present invention, Fig. 2 is a front-elevational view of the fuse of Fig. 1, and Figs. 3 and 4 are a front-elevational view and a side-elevational view, respectively, showing a condition in which the fuse of Fig.
10 1 is mounted in a fuse mounting portion.

The fuse 20 of this first embodiment is a blade-type fuse in which a fuse element 25, having a fusible portion 22 provided between a pair of parallel flat-plate terminal portions 21 and 21, is mounted within an insulating housing 23.

15 Each of the flat-plate terminal portions 21 has a substantially rectangular shape, and the fusible portion 22, having a predetermined cross-sectional area, extends between opposed inner side edges 21a and 21a of the flat-plate terminal portions 21 and 21.

20 The insulating housing 23 comprises a pair of housing members 24 and 24 of a substantially T-shape, and these housing members are integrally connected together in a manner to hold the fuse element 25 therebetween in a direction of a plate thickness of this fuse element, and are fixed together by
25 welding. A pair of large and small pins 24a and 24a are formed

on and project from an inner surface of each of the housing members 24, and these pins pass respectively through corresponding through holes 21b, formed through the flat-plate terminal portions 21, and then are fitted respectively in fitting holes 24b formed in the inner surface of the housing member 24 to which these pins 24a are opposed.

Therefore, the insulating housing 23, attached to the fuse element 25, covers the fusible portion 22 and the inner side edges 21a and upper end edges 21c of the flat-plate terminal portions 21. Therefore, as shown in Fig. 2, the fuse element 25 is covered with the insulating housing 23 except obverse and reverse sides of that portion of each flat-plate terminal portion 21 extending from its outer side edge 21d and lower end edge 21e to a region including a middle portion 21f thereof located at the lateral position relative to the fusible portion 22.

Then, the middle portion 21f of each flat-plate terminal portion 21 is fixedly gripped by a mating terminal 11 of the fuse mounting portion 10 (described later), and therefore the flat-plate terminal portion 21 is electrically connected to the mating terminal 11 (see Fig. 3).

Positioning abutment portions 24c as well as jig engagement step portions 24d are formed at those portions of the insulating housing 23 which cover the upper end edges 21c of the flat-plate terminal portions 21.

When the fuse 20 is mounted in the fuse mounting portion 10, the positioning abutment portions 24c abut against upper ends of the mating terminals 11, thereby positioning the fuse 20 in its inserted condition (see Figs. 3 and 4).

5 For removing the fuse 20 mounted in the fuse mounting portion 10, a fuse removal jig (not shown) engages the jig engagement step portions 24d.

Namely, in the fuse 20 of this first embodiment, the inner side edges 21a and upper end edges 21c of the flat-plate terminal portions 22, as well as the fusible portion 22, are covered with the insulating housing 23 as shown in Fig. 2, and therefore the fuse element 25 does not have any tab terminal portions (such as the tab terminal portions 55 of the related fuse 50 shown in Fig. 7) considerably projecting outwardly from the insulating housing 23, and the fuse 20 has a substantially rectangular shape when viewed from the front side thereof.

Therefore, even when a plurality of fuses 20 are brought into contact with each other during transport or others, the fuse elements 25, each having no tab terminal portion projecting from the insulating housing 23, are not liable to be brought into contact with each other, and besides are not liable to receive an external force which would be produced upon contact with other member. Therefore, the flat-plate terminal portions 21 are prevented from damage, and also an external force is prevented from being applied to the fusible

portion 22, thus preventing the fusible portion 22 from being deformed or broken.

Even if the flat-plate terminal portion 21 should receive an external force upon contact of the outer side edge 21d or the lower end edge 21e with other member, the external force hardly acts directly on the fusible portion 22 since the flat-plate terminal portion 21 is supported by the pins 24a of the housing member 24 passing therethrough.

The fuse 20 is mounted in the fuse mounting portion 10 such as a fuse box as shown in Figs. 3 and 4, and the middle portions 21f of the flat-plate terminal portions 21 are fixedly gripped respectively by the mating terminals 11 of the fuse mounting portion 10, and therefore the flat-plate terminal portions 21 are electrically connected to the mating terminals 11, respectively.

As shown in Fig. 4, the mating terminal 11 is, for example, a so-called tuning fork-type connection terminal comprising a terminal piece portion formed at one end of a bus bar, and a distal end portion of this terminal piece portion is bifurcated by a slot 11b of a U-shaped contour extending in a direction of extending of the terminal piece portion, and upper ends of this bifurcated distal end portion are bulged inwardly toward each other to form a pair of gripping portions 11a and 11a, respectively.

Namely, each of the flat-plate terminal portions 21 and

21 of the fuse element 25 of the fuse 20 of this first embodiment is fixedly gripped by the mating terminal 11 at the middle portion 21f thereof which is substantially a central portion thereof in the mounting direction (in the upward-downward direction in the drawings). Therefore, as compared with the related fuse 50 (shown in Figs. 8 and 9) in which the tab terminal portions 55, projecting from the insulating housing 53, are adapted to be fixedly supported, the balance of supporting of the fuse 20 in the fuse mounting portion 10 is better, and the deflection of the fuse in its mounted condition is suppressed, and besides the overall height of the fuse 20 can be reduced.

Therefore, fuse guide walls 13 of the fuse mounting portion 10, shown in Fig. 3, do not need to have a high molding precision so as to prevent the deflection and the like of the fuse 20, and also the height of the fuse guide walls 13 can be reduced.

A leakage of current between the flat-plate terminal portions 21 and 21 of the fuse 20, mounted in the fuse mounting portion 10, is prevented by the insulating housing 23. Therefore, an insulating wall 12 of the fuse mounting portion 10 need only to electrically insulate the pair of mating terminals 11 and 11 from each other, and therefore can have a smaller height as compared with the insulating wall 63 shown in Fig. 8.

Therefore, the fuse mounting portion 10 can be formed into a small size, and besides the efficiency of the operation for inserting the fuse 20 can be enhanced.

5 The insulating housing 23 covers the upper end edges 21c of the flat-plate terminal portions 21, and has the positioning abutment portions 24c for abutment against the upper ends of the mating terminals 11 so as to position the fuse 20 in its inserted condition.

10 Thus, the fuse 20 is directly positioned relative to the mating terminals 11, and therefore the fuse does not need to be positioned relative to the insulating wall 12 and others of the fuse mounting portion 10, so that the accurate positioning can be effected regardless of the molding precision of the fuse mounting portion 10.

15 Therefore, in the fuse 20 of this first embodiment, the flat-plate terminal portions 21 are prevented from damage, and also an external force is prevented from being applied to the fusible portion 22, thus preventing the fusible portion 22 from being deformed or broken, and therefore the reliability is enhanced, and the small-size design can be achieved.

20 And besides, the fuse mounting portion 10, in which the fuse 20 is to be mounted, can be formed into a small size, and is not required to have a high molding precision. Therefore, the efficiency of the operation for inserting the fuse 20, which
25 can be easily inserted, is enhanced, and also the production

cost can be reduced.

The fuse element and the insulating housing of the fuse of the present invention are not limited to the constructions in the above embodiment, but various forms can be adopted.

5 For example, in a second embodiment of a fuse 30 of the present invention shown in Fig. 5, an insulating housing 33, attached to a fuse element 35, covers a fusible portion 32, inner side edges 31a, upper end edges 31c and outer side edges 31d of flat-plate terminal portions 31.

10 Therefore, the fuse element 35 is covered with the insulating housing 33 except obverse and reverse sides of that portion of each flat-plate terminal portion 31 extending from its lower end edge 31e to a region including a middle portion 31f thereof located at the lateral position relative to the
15 fusible portion 32.

 The middle portion 31f of each flat-plate terminal portion 31 is fixedly gripped by the mating terminal 11 of the fuse mounting portion 10, and therefore the flat-plate terminal portion 31 is electrically connected to the mating terminal
20 11.

 Namely, the exposure of the fuse element 35 of the fuse 30 of this second embodiment is reduced to the minimum of the required amount, and therefore the damage prevention and the protection of the fusible portion 32 can be achieved more
25 positively. The other construction and effects are similar

to those of the fuse 20 of the first embodiment.

In a third embodiment of a fuse 40 of the present invention shown in Fig. 6, an insulating housing 43, attached to a fuse element 45, covers a fusible portion 42 and only an
5 inner side edge 41a of each flat-plate terminal portion 41, and obverse and reverse sides of that portion of each flat-plate terminal portion 41, extending from its upper end edge 41c and lower end edge 41e to a region including a middle portion 41f thereof located at the lateral position relative to the fusible
10 portion 42, are exposed from the insulating housing 43.

Namely, the fuse 40 can be mounted in the fuse mounting portion 10 from either of the upper and lower directions, and therefore the efficiency of the fuse mounting operation can be enhanced. The other construction and effects are
15 substantially similar to those of the fuse 20 of the first embodiment.

In each of the above embodiments, although each
flat-plate terminal portion 21 (31, 41) is fixedly gripped at its the middle portion 21f (31f, 41f) located at the lateral
20 position relative to the fusible portion 22 (32, 42), the present invention is not limited to this construction, and in accordance with the construction of the mating terminal, each flat-plate terminal portion can be suitably fixedly gripped at its middle portion in the mounting direction, which middle
25 portion is exposed from the insulating housing.

INDUSTRIAL APPLICABILITY

As described above, the fuse according to the invention is useful as a blade-type fuse which is mounted on a fuse mounting portion of electrical connection box in a vehicle or the like. Specifically, the fuse can be suitably applied in a compact electrical connection box in which the fuse mounting portion is down-sized.

CLAIMS

1. A fuse box having a fuse mounting portion in which a fuse is mounted, said fuse comprising a fuse element having
5 a pair of parallel flat-plate terminal portions and a fusible portion provided between inner side edges of the flat-plate terminal portions, and an insulating housing covering the inner side edges and upper end edges of said flat-plate terminal portions and said fusible portion;
10 characterised in that a mating terminal of said fuse mounting portion fixedly grips the middle portion of each of said flat-plate terminal portions in a mounting direction, in a direction of the plate thickness of said flat-plate terminal portion, so that said mating terminal
15 is electrically connected to said flat-plate terminal portion.
2. A fuse box according to claim 1, wherein the mating terminal of said mounting portion fixedly grips the middle
20 portion of each of said flat-plate terminal portions that is located at a lateral side of said fusible portion.
3. A fuse box according to claim 1 or claim 2, wherein the mating terminals of said fuse mounting portion
25 respectively abut against positioning abutment portions of said insulating housing, thereby positioning said fuse in its inserted condition.
4. A fuse box according to any one of claims 1 to 3,
30 wherein said fuse mounting portion comprises a fuse guide wall supporting the insulating housing of the mounted fuse, and an insulating wall for preventing a leakage of current between said mating terminals, wherein said insulating wall is smaller in height than the mating terminals.