

**APPARATUS FOR REDUCING GREENHOUSE GAS EMISSION IN VESSEL
AND VESSEL INCLUDING THE SAME**

CROSS-REFERENCE TO RELATED PATENT APPLICATION

5

This application claims the benefit of Korean Patent Application No. 10-2020-0077213, filed on June 24, 2020 and No. 10-2020-0132184, filed on October 13, 2020, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

10

BACKGROUND OF THE INVENTION

1. Field of the Invention

15 【0001】 The present invention relates to an apparatus for reducing greenhouse gas emission in a vessel, and a vessel including the same, which are capable of satisfying IMO greenhouse gas emission regulations by separating and discharging NO_x, SO_x, and CO₂ from exhaust gas exhausted from a vessel engine and increasing CO₂ solubility and CO₂ removal efficiency by removing CO₂ after removing SO_x.

20 2. Description of the Related Art

 【0002】 Recently, global warming and related environmental disasters have occurred due to the influence of greenhouse gas emission caused by indiscriminate use of fossil fuels.

 【0003】 In this regard, a series of technologies related to capture and storage of

carbon dioxide, which is the representative greenhouse gas, without carbon dioxide emission are called carbon dioxide capture and storage (CCS) technologies. In recent years, CCS technologies have attracted much attention. Among CCS technologies, chemical absorption is the most commercialized technology in terms of enabling large-scale treatment.

【0004】 In addition, carbon dioxide emission is regulated through the IMO's EEDI. The IMO is targeting a reduction of 50% or more in emissions by 2050 compared to 2008 and a reduction of 40% in emissions by 2030 compared to 2008. Therefore, technologies that do not emit CO₂ or capture emitted CO₂ are attracting attention.

【0005】 For reference, among the carbon dioxide capture and storage (CCS) technologies for directly capturing and storing carbon dioxide, a CO₂ capture technology may be approached in various ways according to CO₂ generation conditions of target processes. Current representative technologies are an absorption method, an adsorption method, and a membrane separation method. Among them, the wet absorption method has high technological maturity in onshore plants and may easily process CO₂ in large quantities. Therefore, the wet absorption method may be said to be the closest capture technology to commercialization of CCS technology. As an absorbent agent, amines and ammonia are mainly used.

【0006】 On the other hand, the above-described technologies for reducing carbon dioxide emission or capturing generated carbon dioxide are not currently commercialized in vessels, and methods of using hydrogen or ammonia as fuel are currently under development and have not reached the level of commercialization.

【0007】 In particular, in vessels equipped with a scrubber so as to use high

sulfur oil, since the solubility of SO_x is high, SO_x is first changed to a compound of NaSO_3 . Therefore, it is difficult to remove CO_2 until SO_x is completely dissolved.

【0008】 In this regard, the need is raised to apply, to vessels using fossil fuels, a technology for converting CO_2 , which is one of exhaust gases discharged from a vessel engine, into materials that do not affect environments, discharging the materials, or
5 converting the materials into useful materials and storing the useful materials.

SUMMARY OF THE INVENTION

【0009】 An object of the present invention is to provide an apparatus for
10 reducing greenhouse gas emission in a vessel and a vessel including the same, which are capable of satisfying IMO greenhouse gas emission regulations by separating and discharging NO_x , SO_x , and CO_2 from exhaust gas, increasing CO_2 solubility and CO_2 removal efficiency by removing CO_2 after removing SO_x , reducing the NH_3 recycling cost by using $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$, reducing the capacity size of the rear end part of the
15 filter, and reducing the removal cost because only NH_3 and $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$ is consumed during CO_2 removal.

【0010】 In order to achieve the above object, an apparatus for reducing greenhouse gas emission in a vessel includes: a seawater supply unit that supplies seawater; an ammonia water producing unit that reacts fresh water with NH_3 to produce
20 and supply ammonia water; an absorption tower including a CO_2 removing unit that cools exhaust gas discharged from a vessel engine by reacting the exhaust gas with the seawater supplied from the seawater supply unit, and removes CO_2 by reacting the cooled exhaust gas with the ammonia water supplied from the ammonia water producing unit to convert

CO₂ into NH₄HCO₃(aq); and an ammonia recycling unit that recycles NH₃ by reacting NH₄HCO₃(aq) discharged from the absorption tower with Ca(OH)₂ or Mg(OH)₂, and returns the recycled NH₃ back to the ammonia water producing unit.

【0011】 In addition, the absorption tower may further include a NO_x absorbing unit that absorbs and removes NO_x of the exhaust gas discharged from the vessel engine, the CO₂ removing unit may cool the exhaust gas, from which the NO_x is removed, by reacting the exhaust gas with the seawater supplied from the seawater supply unit, and remove CO₂ by reacting the cooled exhaust gas with the ammonia water supplied from the ammonia water producing unit to convert CO₂ into NH₄HCO₃(aq), and the ammonia recycling unit may recycle NH₃ and return the recycled NH₃ back to the ammonia water producing unit and the NO_x absorbing unit.

【0012】 In addition, the absorption tower may further include a SO_x absorbing unit that dissolves and removes SO_x while cooling the exhaust gas discharged from the vessel engine by reacting the exhaust gas with the seawater supplied from the seawater supply unit, and the CO₂ removing unit may remove CO₂ by reacting the exhaust gas, from which the SO_x is removed, with the ammonia water supplied from the ammonia water producing unit to convert CO₂ into NH₄HCO₃(aq).

【0013】 In addition, in the absorption tower, a NO_x absorbing unit that absorbs and removes NO_x from the exhaust gas discharged from the vessel engine, a SO_x absorbing unit that dissolves and removes SO_x while cooling the exhaust gas, from which the NO_x has been removed, through reaction with the seawater supplied from the seawater supply unit, and the CO₂ removing unit that removes CO₂ by reacting the exhaust gas, from which the SO_x has been removed, with the ammonia water supplied from the

ammonia water producing unit to convert CO_2 into $\text{NH}_4\text{HCO}_3(\text{aq})$ may be stacked, and the ammonia recycling unit may recycle NH_3 and return the recycled NH_3 back to the ammonia water producing unit and the NO_x absorbing unit.

5 【0014】 In addition, the seawater supply unit may include: a seawater pump that receives seawater from the outside of the vessel through a sea chest and pumps the seawater to the SO_x absorbing unit; and a control valve that controls a flow rate of the seawater supplied from the seawater pump according to an amount of the exhaust gas.

10 【0015】 In addition, the ammonia water producing unit may include: a fresh water tank that stores fresh water; a fresh water pump that pumps and supplies the fresh water from the fresh water tank; an ammonia water production tower including a tower tank, a NH_3 spray nozzle that is formed at a lower end of the tower tank and sprays NH_3 upward, a fresh water spray nozzle that is formed at an upper end of the tower tank and sprays the fresh water from the fresh water pump downward, a first packing material that is formed between the NH_3 spray nozzle and the fresh water spray nozzle and contacts
15 the fresh water with NH_3 to dissolve NH_3 and generate ammonia water, and a cooling jacket that cools heat generated by the tower tank due to a dissolution reaction; and an ammonia water pump that supplies ammonia water from an ammonia water storage tank, which stores ammonia water drained to a lower end of the ammonia water production tower, to an upper end of the CO_2 removing unit.

20 【0016】 In addition, the ammonia water production tower may include a mist removal plate that is formed at the upper end of the tower tank in a curved multi-plate shape and returns mist scattered from the fresh water toward the first packing material.

 【0017】 In addition, the apparatus may further include a NH_3 supply pipe

through which NH_3 exhausted to the upper end of the ammonia water production tower is supplied to an lower end of the CO_2 removing unit.

【0018】 In addition, the first packing material may include multi-stage distilling column packings designed to increase a contact area per unit volume.

5 【0019】 In addition, a solution redistributor may be formed between the multi-stage distilling column packings.

【0020】 In addition, a diameter and a height of the tower tank may be designed so that a flow velocity of the fresh water and a flow velocity of the NH_3 are 1/2 of a flooding velocity.

10 【0021】 In addition, the loss and lack of NH_3 may be compensated for by supplying NH_3 from the ammonia recycling unit through the NH_3 spray nozzle of the ammonia water producing unit or supplying NH_3 from a separate NH_3 storage tank when the loss and lack of NH_3 occur.

15 【0022】 In addition, the NO_x absorbing unit may directly receive NH_3 from the ammonia recycling unit through a blower or a compressor and spray the received NH_3 to a first NH_3 spray nozzle, or when NH_3 is insufficient, the NO_x absorbing unit may receive urea water of a urea water storage tank through a urea water supply pump and spray the received urea water to a second NH_3 spray nozzle so as to compensate for the lack of NH_3 .

20 【0023】 In addition, the SO_x absorbing unit may include a multi-stage seawater spray nozzle that is connected to the control valve and sprays seawater downward.

【0024】 In addition, porous upper plates having a passage through which exhaust gas passes may be respectively formed in multi-stages under the seawater spray nozzle, so that the seawater and the exhaust gas come into contact with each other.

【0025】 In addition, an absorption apparatus filled with a third packing material for allowing seawater and exhaust gas to come into contact with each other may be respectively formed under the seawater spray nozzle, so that the seawater dissolves SO_x.

【0026】 In addition, the SO_x absorbing unit may include an umbrella-shaped partition wall that covers an exhaust gas inlet pipe so as to prevent cleaning water from flowing backward.

【0027】 In addition, the CO₂ removing unit may include: an ammonia water spray nozzle that is connected to the ammonia water pump and sprays ammonia water downward; a second packing material that contacts CO₂ with the ammonia water and converts CO₂ into NH₄HCO₃(aq); a cooling jacket that is formed in multi-stages for each section of an absorption apparatus filled with the second packing material and cools heat generated by a CO₂ removal reaction; a water spray that collects NH₃ discharged to the outside without reacting with CO₂; a mist removal plate that is formed in a curved multi-plate shape and returns the ammonia water toward the second packing material; a partition wall that is formed so that the ammonia water does not flow backward; and an umbrella-shaped blocking plate that covers an exhaust gas inlet hole of the partition wall.

【0028】 In addition, the absorption tower may further include an exhaust gas economizer (EGE) that is formed between the NO_x absorbing unit and the SO_x absorbing unit and performs heat exchange between waste heat of the vessel engine and boiler water.

【0029】 In addition, the apparatus may further include a steam generating unit including: an auxiliary boiler that receives a mixture in the form of saturated water and heat-exchanged steam, separates the steam, and supplies the separated steam to a steam consumer; a boiler water circulating pump that circulates and supplies boiler water from

the auxiliary boiler to the EGE; a cascade tank that recovers condensed water from the steam consumer; and a supply pump and a control valve that supply boiler water from the cascade tank to the auxiliary boiler while controlling an amount of boiler water.

5 **【0030】** In addition, the ammonia recycling unit may include: a $\text{Ca}(\text{OH})_2$ storage tank that stores $\text{Ca}(\text{OH})_2$; a mixing tank in which $\text{NH}_4\text{HCO}_3(\text{aq})$ discharged from the absorption tower is stirred with $\text{Ca}(\text{OH})_2$ by an agitator to generate $\text{CaCO}_3(\text{s})$ and H_2O and $\text{NH}_3(\text{g})$ is recycled; a filter that suctions a solution and precipitate from the mixing tank and separates $\text{CaCO}_3(\text{s})$; a high-pressure pump that transfers the solution and precipitate to the filter at high pressure; and a $\text{CaCO}_3(\text{s})$ storage tank that stores a slurry
10 or $\text{CaCO}_3(\text{s})$ of a solid state.

【0031】 In addition, the ammonia recycling unit may include: a $\text{Mg}(\text{OH})_2$ storage tank that stores $\text{Mg}(\text{OH})_2$; a mixing tank in which $\text{NH}_4\text{HCO}_3(\text{aq})$ discharged from the absorption tower is stirred with $\text{Mg}(\text{OH})_2$ by an agitator to generate $\text{MgCO}_3(\text{s})$ and H_2O and $\text{NH}_3(\text{g})$ is recycled; a filter that suctions a solution and precipitate from the
15 mixing tank and separates $\text{MgCO}_3(\text{s})$; a high-pressure pump that transfers the solution and precipitate to the filter at high pressure; and a $\text{MgCO}_3(\text{s})$ storage tank that stores a slurry or $\text{MgCO}_3(\text{s})$ of a solid state.

【0032】 In addition, ammonia water or fresh water separated by the filter may be supplied to the ammonia water producing unit, or excess ammonia water or excess
20 fresh water additionally generated by the mixing tank compared to a total circulating fresh water may be stored in the fresh water tank.

【0033】 In addition, the fresh water supplied from the fresh water tank may be reacted with CaO to produce $\text{Ca}(\text{OH})_2$ in the $\text{Ca}(\text{OH})_2$ storage tank.

【0034】 In addition, the fresh water supplied from the fresh water tank may be reacted with MgO to produce Mg(OH)₂ in the Mg(OH)₂ storage tank.

【0035】 In addition, the apparatus may further include a discharge unit including: a cleaning water tank that stores cleaning water discharged from the absorption
5 tower; a water treatment device including a filtering unit that controls turbidity to satisfy an outboard discharge condition of the cleaning water transferred to the cleaning water tank by a transfer pump, and a neutralizing agent injecting unit that controls pH; and a sludge storage tank that separates and stores solid emissions.

【0036】 On the other hand, the present invention may provide a vessel including
10 the above-described apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

【0037】 FIG. 1 is a schematic configuration diagram of an apparatus for reducing greenhouse gas emission in a vessel, according to an embodiment of the present
15 invention.

【0038】 FIG. 2 is a circuit diagram of a system implementing the apparatus for reducing greenhouse gas emission in a vessel, illustrated in FIG. 1.

【0039】 FIG. 3 separately illustrates a seawater supply unit of the apparatus for reducing greenhouse gas emission in a vessel, illustrated in FIG. 2.

【0040】 FIG. 4 separately illustrates an ammonia water producing unit of the
20 apparatus for reducing greenhouse gas emission in a vessel, illustrated in FIG. 2.

【0041】 FIG. 5 separately illustrates an absorption tower of the apparatus for reducing greenhouse gas emission in a vessel, illustrated in FIG. 2.

【0042】 FIG. 6 separately illustrates a SO_x absorbing unit of the absorption tower of FIG. 5.

【0043】 FIG. 7 separately illustrates a steam generating unit of the apparatus for reducing greenhouse gas emission in a vessel, illustrated in FIG. 2.

5 【0044】 FIG. 8 separately illustrates an ammonia recycling unit and an ammonia water producing unit of the apparatus for reducing greenhouse gas emission in a vessel, illustrated in FIG. 2.

【0045】 FIG. 9 illustrates various packing materials applied to the apparatus for reducing greenhouse gas emission in a vessel, illustrated in FIG. 2.

10

DETAILED DESCRIPTION OF THE INVENTION

【0046】 Hereinafter, embodiments of the present invention will be described in detail with reference to the accompanying drawings so that the present invention can be easily carried out by those of ordinary skill in the art. The present invention may be
15 embodied in many different forms and is not limited to embodiments of the present invention described herein.

【0047】 An apparatus for reducing greenhouse gas emission in a vessel, according to an embodiment of the present invention, includes: a seawater supply unit that supplies seawater; an ammonia water producing unit that reacts fresh water with NH₃
20 to produce and supply ammonia water; an absorption tower including a CO₂ removing unit that cools exhaust gas discharged from a vessel engine by reacting the exhaust gas with the seawater supplied from the seawater supply unit, and removes CO₂ by reacting the cooled exhaust gas with the ammonia water supplied from the ammonia water

producing unit to convert CO_2 into $\text{NH}_4\text{HCO}_3(\text{aq})$; and an ammonia recycling unit that recycles NH_3 by reacting $\text{NH}_4\text{HCO}_3(\text{aq})$ discharged from the absorption tower with $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$, and returns the recycled NH_3 back to the ammonia water producing unit.

5 **【0048】** At this time, according to the type and specification of the engine (low-pressure engine or high-pressure engine) and the type of fuel supplied to the engine (HFO, MDO, MGO, LNG, ammonia, etc.), the absorption tower may optionally include both the NO_x absorbing unit and the SO_x absorbing.

【0049】 In particular, with respect to the SO_x absorbing unit, as described later,
10 since SO_x may be dissolved by reacting with seawater, cooling of exhaust gas and absorption of SO_x may be performed at once.

【0050】 On the other hand, according to another embodiment of the present invention, a vessel including the apparatus for reducing greenhouse gas emission may be provided.

15 **【0051】** Hereinafter, an embodiment in which the NO_x absorbing unit, the SO_x absorbing unit, and the CO_2 removing unit are stacked on the absorption tower will be described, but the present invention is not limited thereto. As described above, the NO_x absorbing unit and/or the SO_x absorbing unit may or may not be included according to the types of engine and fuel.

20 **【0052】** An apparatus for reducing greenhouse gas emission in a vessel, according to an embodiment of the present invention, includes: a seawater supply unit 110 that supplies seawater; an ammonia water producing unit 120 that reacts fresh water with NH_3 to produce and supply ammonia water; an absorption tower 130 including a

CO₂ removing unit 133 that cools exhaust gas discharged from a vessel engine 10 by reacting the exhaust gas with the seawater supplied from the seawater supply unit 110, and removes CO₂ by reacting the cooled exhaust gas with the ammonia water supplied from the ammonia water producing unit 120 to convert CO₂ into NH₄HCO₃(aq); and an ammonia recycling unit 140 that recycles NH₃ by reacting NH₄HCO₃(aq) discharged from the absorption tower 130 with Ca(OH)₂ or Mg(OH)₂, and returns the recycled NH₃ back to the ammonia water producing unit 120. It is possible to satisfy IMO greenhouse gas emission regulations by separating and discharging NO_x, SO_x, and CO₂ from exhaust gas, increase CO₂ removal efficiency by removing CO₂ after removing SO_x, and removing side reactions caused by SO_x remaining during NH₃ removal, thereby preventing impurities from being included during ammonia recovery.

【0053】 Hereinafter, the apparatus for reducing greenhouse gas emission in the vessel will be described in detail with reference to FIGS. 1 to 9.

【0054】 First, a seawater supply unit 110 supplies seawater to a SO_x absorbing unit 132 of an absorption tower 130. Specifically, as illustrated in FIGS. 2 and 3, the seawater supply unit 110 may include: seawater pumps 111a and 111b that suction seawater from the outside of the vessel through a sea chest (not illustrated) and pump the seawater to the SO_x absorbing unit 132; and a control valve 112 that controls a flow rate of the seawater supplied from the seawater pumps 111a and 111b according to the amount of exhaust gas. Here, the seawater pumps 111a and 111b may include a suction pump 111a that suctions seawater from the outside of the vessel and a seawater transfer pump 111b that pumps and transfers seawater to the SO_x absorbing unit 132.

【0055】 For reference, when the vessel is berthing or sailing, seawater may be

selectively supplied to the seawater pumps 111a and 111b from a high sea chest that
suctions upper seawater or a low sea chest that suction lower seawater according to the
depth of water. That is, when the vessel is berthing, the high sea chest may be used
because the upper seawater is cleaner than the lower seawater, and when the vessel is
5 sailing, the low sea chest may be used because the lower seawater is cleaner than the
upper seawater.

【0056】 Here, the control valve 112 may be a manually operated diaphragm
valve or a solenoid type valve that controls the flow rate of seawater, but the present
invention is not limited thereto. Any type of valve may be applied as long as the amount
10 of seawater injected through a seawater spray nozzle 132a can be controlled according to
the amount of exhaust gas.

【0057】 Next, an ammonia water producing unit 120 reacts fresh water with
 NH_3 recycled or replenished when insufficient to produce and supply ammonia water
($\text{NH}_4\text{OH}(\text{aq})$).

15 【0058】 Specifically, as illustrated in FIGS. 2 and 4, the ammonia water
producing unit 120 may include: a fresh water tank 121 that stores fresh water; a fresh
water pump 122 that pumps and supplies the fresh water from the fresh water tank 121;
an ammonia water production tower 123 including a tower tank 123a, a NH_3 spray nozzle
123b that is formed at a lower end of the tower tank 123a and sprays NH_3 upward, a fresh
20 water spray nozzle 123c that is formed at an upper end of the tower tank 123a and sprays
the fresh water from the fresh water pump 122 downward, a packing material 123d that
is formed between the NH_3 spray nozzle 123b and the fresh water spray nozzle 123c and
contacts the fresh water with NH_3 to dissolve NH_3 and generate ammonia water, and a

cooling jacket 123e that cools heat generated by the tower tank 123a due to the dissolution reaction based on the following [Chemical Formula 1]; and an ammonia water pump 124 that supplies ammonia water from an ammonia water storage tank 124a, which stores the ammonia water drained to a lower end of the ammonia water production tower 123, to an ammonia water spray nozzle 133a, which is formed at an upper end of a CO₂ removing unit 133.

[Chemical Formula 1]



【0059】 Here, the fresh water tank 121 may store distilled water produced on board or fresh water (or ammonia water) separated when CaCO₃ or MgCO₃ is separated by a filter 144 and transferred to the ammonia water production tower 123, that is, surplus fresh water additionally produced through a mixing tank 143 and the filter 144 compared to the total circulating fresh water required for ammonia water production and NH₃ recycling (see FIG. 8).

【0060】 On the other hand, referring to FIG. 4, the ammonia water production tower 123 may further include a mist removal plate 123f that is formed at an upper end of the fresh water spray nozzle 123c disposed at the upper end of the tower tank 123a in a curved multi-plate shape and returns mist scattered from the fresh water toward the packing material 123d. Since the fresh water may be discharged to the outside through the exhaust gas, the mist may collide with the curved portion so that droplets become larger, and the water may be discharged toward the lower packing material 123d.

【0061】 In addition, the ammonia water production tower 123 may further include a NH₃ supply pipe 123g through which NH₃(g) exhausted to the upper end of the

ammonia water production tower 123 is supplied to the lower end of the CO₂ removing unit 133. Excess NH₃(g) that is not dissolved and exhausted is absorbed into the ammonia water flowing down through the CO₂ removing unit 133, thereby minimizing the loss of NH₃.

5 **【0062】** On the other hand, when the lack of NH₃ occurs or the loss of NH₃ itself occurs because the amount of NH₃ recycled by the ammonia recycling unit 140 is insufficient to produce ammonia water by the ammonia water production tower 123 or supply NH₃ to a first NH₃ spray nozzle 131b of a NO_x absorbing unit 131, a separate NH₃ storage tank 123h may be provided to supply NH₃ so as to compensate for the loss and
10 lack of NH₃. That is, NH₃ may be directly supplied from the ammonia recycling unit 140 to the NH₃ spray nozzle 123b of the ammonia water producing unit 120, or NH₃ may be directly supplied to the first NH₃ spray nozzle 131b of the NO_x absorbing unit 131 through a blower 131a or a compressor, or NH₃ may be supplied from the NH₃ storage tank 123h in the event of the loss or lack of NH₃, thereby replacing the loss or lack of
15 NH₃.

【0063】 In addition, the diameter and height of the tower tank 123a are preferably designed so that the flow velocity of fresh water and the flow velocity of NH₃ are 1/2 of the flooding velocity. In this manner, in a state where NH₃ is sprayed at a pressure slightly higher than atmospheric pressure through the NH₃ spray nozzle 123b,
20 the pressure drop may be offset in the wet state of the tower tank 123a.

【0064】 In addition, the packing material 123d may include multi-stage distilling column packings designed to increase a contact area per unit volume. As illustrated in FIG. 9, a distilling column packing suitable for a process may be selected

considering the contact area per unit area, the pressure drop of gas, and the flooding velocity.

5 **【0065】** On the other hand, a solution redistributor (not illustrated) may be formed between the multi-stage distilling column packings so as to prevent channeling of fresh water.

【0066】 In addition, the ammonia water pump 124 may be provided with a centrifugal pump, so that a large amount of ammonia water is pumped and effectively supplied from the ammonia water production tower 123 to the CO₂ removing unit 133.

10 **【0067】** In addition, the cooling jacket 123e may be cooled so that the reaction temperature of the dissolution reaction is maintained at 30°C to 50°C, considering the solubility of NH₃.

【0068】 Next, as illustrated in FIGS. 2 and 5, in the absorption tower 130, a NO_x absorbing unit 131 that absorbs and removes NO_x from exhaust gas discharged from the vessel engine 10 of the main engine or power generation engine, a SO_x absorbing unit
15 132 that dissolves and removes SO_x while cooling exhaust gas, from which NO_x has been removed, through reaction with seawater, and a CO₂ removing unit 133 that removes CO₂ by reacting the exhaust gas, from which SO_x has been removed, with the ammonia water supplied from the ammonia water producing unit 120 to convert CO₂ into NH₄HCO₃(aq) are stacked in the vertical direction to sequentially absorb and remove NO_x, SO_x, and
20 CO₂.

【0069】 Here, the absorption tower 130 may include the NO_x absorbing unit 131, the SO_x absorbing unit 132, the CO₂ removing unit 133, and an exhaust gas economizer (EGE) 134 to be described later, may be modularized and combined with

individual modules, and may be integrated in a single tower form, or the absorption tower 130 itself may include a single tower or a plurality of towers.

【0070】 Specifically, the NO_x absorbing unit 131 is a selective catalyst reactor (SCR). The NO_x absorbing unit 131 may directly receive NH₃ from the ammonia recycling unit 140 through the blower 131a or the compressor and spray the received NH₃ to the first NH₃ spray nozzle 131b, or when NH₃ is insufficient, the NO_x absorbing unit 131 may receive urea water of a urea water storage tank 131c through a urea water supply pump 131d and spray the received urea water to a second NH₃ spray nozzle 131e so as to compensate for the lack of NH₃.

【0071】 Here, since NH₃ and CO₂ are generated when the urea water is decomposed, it may be preferable that NH₃ is directly supplied to reduce the amount of CO₂ generated, and a NO_x sensor 131f (see FIG. 5) that senses NO_x concentration may be formed at the upper end of the NO_x absorbing unit 131.

【0072】 In addition, the SO_x absorbing unit 132 is a section that is in primary contact with seawater and includes a multi-stage seawater spray nozzle 132a that is connected to the control valve 112 and sprays seawater downward. The SO_x absorbing unit 132 may dissolve SO_x, remove dusts such as soot, and cool the temperature of the exhaust gas to 27°C to 33°C, preferably about 30°C, which is required by the CO₂ removing unit 133, through the seawater spray nozzle 132a or a separate cooling jacket (not illustrated).

【0073】 On the other hand, as illustrated in FIG. 6A, porous upper plates 132b having a passage through which exhaust gas passes may be respectively formed in multi-stages under the seawater spray nozzle 132a, so that the seawater and the exhaust gas

come into smooth contact with each other. As illustrated in FIG. 6B, an absorption apparatus 132c filled with a packing material for allowing seawater and exhaust gas to come into contact with each other may be respectively formed under the seawater spray nozzle 132a, so that the seawater dissolves SO_x .

5 **【0074】** On the other hand, a closed loop system may be applied to add a compound forming alkali ions, for example, a basic chemical of NaOH or MgO, in order to further increase the solubility of SO_x .



【0075】 For reference, the closed loop system involves additional consumption of basic chemicals, but has an advantage that the amount of circulating seawater is small,
10 and the open loop system that discharges SO_x dissolved by spraying only seawater to the outside of the vessel has no additional consumption of basic chemicals and is simple. In order to maximize these advantages, a hybrid system in which the open loop system and the closed loop system are combined may be applied.

【0076】 In this regard, by removing SO_x through the SO_x absorbing unit 132
15 and then removing CO_2 through the CO_2 removing unit 133, it is possible to solve the problem that it is difficult to remove CO_2 until SO_x is completely dissolved because the solubility of SO_x is high and thus SO_x is first changed to a compound such as NaSO_3 , thereby improving the solubility of CO_2 and the removal efficiency of CO_2 .

【0077】 Here, cleaning water drained from a discharge unit 160 by the SO_x
20 absorbing unit 132 contains SO_3^- , SO_4^{2-} , soot, NaSO_3 , NaSO_4 , MgCO_3 , MgSO_4 , and other ionic compounds together, and the SO_x absorbing unit 132 may include an umbrella-shaped partition wall 132e that covers an exhaust gas inlet pipe 132d so that the cleaning water does not flow back to the NO_x absorbing unit 131 or the EGE 134.

【0078】 In addition, as illustrated in FIGS. 4 and 5, the CO₂ removing unit 133 may include: an ammonia water spray nozzle 133a that is connected to the ammonia water pump 124 and sprays ammonia water downward; a packing material 133b that contacts CO₂ with the ammonia water and converts CO₂ into NH₄HCO₃(aq) based on the following [Chemical Formula 2]; a cooling jacket (not illustrated) that is formed in multi-stages for each section of the absorption apparatus filled with the packing material 133b and cools heat generated by a CO₂ removal reaction to maintain the heat at 30°C to 50°C; a water spray 133c that collects NH₃ discharged to the outside without reacting with CO₂; a mist removal plate 133d that is formed in a curved multi-plate shape and returns the ammonia water to the packing material 133b; a partition wall 133e that is formed so that the ammonia water does not flow back to the SO_x absorbing unit 132; and an umbrella-shaped blocking plate 133f that covers an exhaust gas inlet hole 133e-1 of the partition wall 133e.

[Chemical Formula 2]



【0079】 Here, since the CO₂ removing unit 133 removes CO₂ by reacting the ammonia water with the exhaust gas from which NO_x and SO_x have been removed, side reactions caused by NO_x and SO_x do not occur during the CO₂ removal process, thereby minimizing the occurrence of impurities and obtaining NH₄HCO with less impurities in a subsequent process.

【0080】 In addition, the packing material 133b may include multi-stage distilling column packings designed to increase a contact area per unit volume. As


illustrated in FIG. 9, a distilling column packing suitable for a process may be selected considering the contact area per unit area, the pressure drop of gas, and the flooding velocity.

5 **【0081】** On the other hand, the absorption tower 130 may further include an EGE 134 that is formed between the NO_x absorbing unit 131 and the SO_x absorbing unit 132 and performs heat exchange between waste heat of the vessel engine 10 and boiler water.


10 **【0082】** Next, the ammonia recycling unit 140 reacts NH₄HCO₃(aq) discharged from the absorption tower 130 with Ca(OH)₂ or Mg(OH)₂ to recycle NH₃, returns NH₃ back to the ammonia water producing unit 120 and the NO_x absorbing unit 131 so as to reuse NH₃, and stores or discharges CO₂ in the form of CaCO₃(s) or MgCO₃(s).

15 **【0083】** Specifically, as illustrated in FIGS. 2 and 8, the ammonia recycling unit 140 may include: a Ca(OH)₂ storage tank 141 or a Mg(OH)₂ storage tank 141 that stores Ca(OH)₂ or Mg(OH)₂; a mixing tank 143 in which NH₄HCO₃(aq) discharged from the CO₂ removing unit 133 of the absorption tower 130 is stirred with Ca(OH)₂ or Mg(OH)₂ by an agitator 142 to generate CaCO₃(s) or MgCO₃(s) and H₂O based on the following [Chemical Formula 3] or [Chemical Formula 4] and NH₃(g) is recycled; a filter 144 that
20 suctions a solution and precipitate from the mixing tank 143 and separates CaCO₃(s) or MgCO₃(s); a high-pressure pump 145 that transfers the solution and precipitate to the filter 144 at high pressure; and a CaCO₃(s) storage tank (not illustrated) or a MgCO₃(s) storage tank (not illustrated) that stores a slurry or CaCO₃(s) or MgCO₃(s) of a solid state transferred to a dryer (not illustrated) and solidified.

 [Chemical Formula 3]



[Chemical Formula 4]



5 **【0084】** Here, $\text{NH}_4\text{HCO}_3(\text{aq})$ and $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$ are continuously reacted by the agitator 142 installed in the mixing tank 143, while maintaining at a constant temperature so that the reaction is smoothly performed.

【0085】 On the other hand, the waste of fresh water may be eliminated by supplying fresh water (or ammonia water) separated by the filter 144 to the fresh water spray nozzle 123c of the ammonia water producing unit 120, or storing, in the fresh water
10 tank 121, excess fresh water (or excess ammonia water) additionally generated by the mixing tank 143 compared to the total circulating fresh water required for ammonia water production and NH_3 recycling.

【0086】 In addition, the $\text{Ca}(\text{OH})_2$ storage tank 141 or the $\text{Mg}(\text{OH})_2$ storage tank 141 may react the fresh water supplied from the fresh water tank 121 with CaO or MgO
15 to generate $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$, store $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$, and supply $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$ to the mixing tank 143. Here, since the solubility of CaO or MgO is low, it is effective to apply a method of preparing $\text{Ca}(\text{OH})_2(\text{aq})$ or $\text{Mg}(\text{OH})_2(\text{aq})$ by adding CaO or MgO to fresh water as necessary. When adding CaO or MgO , heating and stirring have to be accompanied.

20 **【0087】** In this manner, there is no reduction in the concentration of ammonia water, the capacity size of the filter 144 may be reduced, and the NH_3 recycling cost may be reduced. That is, in theory, only MgO is consumed and NH_3 and fresh water are reused, thereby significantly reducing the CO_2 removal cost.

【0088】 In addition, the filter 144 suctions the solution and precipitate from the mixing tank 143, transfers NaHCO_3 and other by-product precipitates at high pressure by the high-pressure pump 145, separates CaCO_3 or MgCO_3 , and stores CaCO_3 or MgCO_3 in a solid state or discharges CaCO_3 or MgCO_3 to the outside of the vessel. Here, as an
5 example of the filter, a membrane filter suitable for precipitate separation by high-pressure fluid transfer may be applied.

【0089】 In addition, the NH_3 recycled by the mixing tank 143 is supplied to the NH_3 spray nozzle 123b of the ammonia water producing unit 120 and the first NH_3 spray nozzle 131b of the NO_x absorbing unit 131 so as to be reused for ammonia water
10 production and NO_x removal, thereby minimizing the consumption of relatively expensive NH_3 and reducing costs.

【0090】 Next, as illustrated in FIG. 7, the steam generating unit 150 may include: an auxiliary boiler 151 that receives a mixture in the form of saturated water and steam heat-exchanged through the EGE 134, separates the steam by a steam drum (not
15 illustrated), and supplies the separated steam to a steam consumer; a boiler water circulating pump 152 that circulates and supplies boiler water from the auxiliary boiler 151 to the EGE 134; a cascade tank 153 that recovers condensed water condensed and phase-changed after being consumed from the steam consumer; and a supply pump 154 and a control valve 155 that supply boiler water from the cascade tank 153 to the auxiliary
20 boiler 151 while controlling the amount of boiler water. The steam generating unit 150 generates and supplies steam required for heating devices in the vessel.

【0091】 Here, when the load of the vessel engine 10 is large, the amount of heat that may be provided from the exhaust gas is large, and thus the amount of steam required

in the vessel may be sufficiently produced through the EGE 134; otherwise, the auxiliary boiler 151 itself may burn fuel to produce necessary steam.

【0092】 Next, as illustrated in FIG. 2, the discharge unit 160 may include: a cleaning water tank 161 that stores cleaning water discharged from the absorption tower 130; a water treatment device 163 including a filtering unit that controls turbidity to satisfy the outboard discharge condition of the cleaning water transferred to the cleaning water tank 161 by the transfer pump 162, and a neutralizing agent injecting unit that controls pH; and a sludge storage tank 164 that separates and stores solid emissions such as soot. The discharge unit 160 may discharge the cleaning water, which passes through the water treatment device 163 and satisfies the outboard discharge condition, to the outside of the vessel, and may separately store the solid emissions, such as soot, which do not satisfy the outboard discharge conditions, in the sludge storage tank 164.

【0093】 On the other hand, NaOH may be used as the neutralizing agent for satisfying the outboard discharge condition. However, assuming that the materials discharged from the absorption tower 130 are acidic and basic, a neutralizing agent capable of neutralizing each of the acidic material and the basic material may be selected and used as necessary.

【0094】 Therefore, as described above, according to the structure of the apparatus for reducing greenhouse gas emission in the vessel, NO_x, SO_x, and CO₂ from the exhaust gas exhausted from the vessel engine may be converted into materials that do not affect environments so as to satisfy IMO greenhouse gas emission regulations. The materials may be separately discharged, or may be converted into useful materials and stored. Since CO₂ is removed after SO_x is removed, the CO₂ dissolution reaction rate,

the CO₂ solubility, and the CO₂ removal efficiency may be increased. The use of Ca(OH)₂ or Mg(OH)₂ may reduce the NH₃ recycling cost. The capacity size of the rear end part of the filter may be reduced. When CO₂ is removed, only relatively inexpensive NH₃ loss and Ca(OH)₂ or Mg(OH)₂ (CaO or MgO) are consumed, reducing removal costs.

5 CO₂ may be stored in the form of CaCO₃(s) or MgCO₃(s) existing in the nature. CaCO₃(s) or MgCO₃(s) may be discharged in sea, and side reactions caused by SO_x remaining during NH₃ recycling may be removed, thereby minimizing the loss of NH₃ and preventing impurities from being included when recovering ammonia. Since only Ca(OH)₂ or Mg(OH)₂ is added, there is no change in the concentration of ammonia water,

10 and the capacity size of the filter may be reduced.

【0095】 According to the present invention, NO_x, SO_x, and CO₂ from exhaust gas exhausted from a vessel engine may be converted into materials that do not affect environments so as to satisfy IMO greenhouse gas emission regulations. The materials may be separately discharged, or may be converted into useful materials and stored.

15 Since CO₂ is removed after SO_x is removed, the CO₂ dissolution reaction rate, the CO₂ solubility, and the CO₂ removal efficiency may be increased. The use of Ca(OH)₂ or Mg(OH)₂ may reduce the NH₃ recycling cost. The capacity size of the rear end part of the filter may be reduced. When CO₂ is removed, only relatively inexpensive NH₃ loss and Ca(OH)₂ or Mg(OH)₂ (CaO or MgO) are consumed, reducing removal costs. Side

20 reactions caused by SO_x remaining during NH₃ recycling may be removed, thereby minimizing the loss of NH₃ and preventing impurities from being included when recovering ammonia. By adding only Ca(OH)₂ or Mg(OH)₂, there is no change in the concentration of ammonia water, and the capacity size of the filter may be reduced.

【0096】 The present invention has been described above with reference to the

embodiments illustrated in the drawings. However, the present invention is not limited thereto, and various modifications or other embodiments falling within the scope equivalent to the present invention can be made by those of ordinary skill in the art. Therefore, the true scope of protection of the present invention should be determined by

5 the appended claims.

What is Claimed is:

1. An apparatus for reducing greenhouse gas emission in a vessel, the apparatus comprising:

a seawater supply unit that supplies seawater;

5 an ammonia water producing unit that reacts fresh water with NH_3 to produce and supply ammonia water;

an absorption tower comprising a CO_2 removing unit that cools exhaust gas discharged from a vessel engine by reacting the exhaust gas with the seawater supplied from the seawater supply unit, and removes CO_2 by reacting the cooled exhaust gas with
10 the ammonia water supplied from the ammonia water producing unit to convert CO_2 into $\text{NH}_4\text{HCO}_3(\text{aq})$; and

an ammonia recycling unit that recycles NH_3 by reacting $\text{NH}_4\text{HCO}_3(\text{aq})$ discharged from the absorption tower with $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$, and returns the recycled NH_3 back to the ammonia water producing unit.

15

2. The apparatus according to claim 1, wherein the absorption tower further comprises a NO_x absorbing unit that absorbs and removes NO_x of the exhaust gas discharged from the vessel engine,

the CO_2 removing unit cools the exhaust gas, from which the NO_x is removed,
20 by reacting the exhaust gas with the seawater supplied from the seawater supply unit, and removes CO_2 by reacting the cooled exhaust gas with the ammonia water supplied from the ammonia water producing unit to convert CO_2 into $\text{NH}_4\text{HCO}_3(\text{aq})$, and

the ammonia recycling unit recycles NH_3 and returns the recycled NH_3 back to the ammonia water producing unit and the NO_x absorbing unit.

3. The apparatus according to claim 1, wherein the absorption tower further comprises a SO_x absorbing unit that dissolves and removes SO_x while cooling the exhaust gas discharged from the vessel engine by reacting the exhaust gas with the seawater supplied from the seawater supply unit, and

the CO₂ removing unit removes CO₂ by reacting the exhaust gas, from which the SO_x is removed, with the ammonia water supplied from the ammonia water producing unit to convert CO₂ into NH₄HCO₃(aq).

4. The apparatus according to claim 1, wherein, in the absorption tower, a NO_x absorbing unit that absorbs and removes NO_x from the exhaust gas discharged from the vessel engine, a SO_x absorbing unit that dissolves and removes SO_x while cooling the exhaust gas, from which the NO_x has been removed, through reaction with the seawater supplied from the seawater supply unit, and the CO₂ removing unit that removes CO₂ by reacting the exhaust gas, from which the SO_x has been removed, with the ammonia water supplied from the ammonia water producing unit to convert CO₂ into NH₄HCO₃(aq) are stacked, and

the ammonia recycling unit recycles NH₃ and returns the recycled NH₃ back to the ammonia water producing unit and the NO_x absorbing unit.

5. The apparatus according to claim 3 or 4, wherein the seawater supply unit comprises:

a seawater pump that receives seawater from the outside of the vessel through a sea chest and pumps the seawater to the SO_x absorbing unit; and

a control valve that controls a flow rate of the seawater supplied from the seawater pump according to an amount of the exhaust gas.

6. The apparatus according to any one of claims 1 to 4, wherein the ammonia
5 water producing unit comprises:

a fresh water tank that stores fresh water;

a fresh water pump that pumps and supplies the fresh water from the fresh water
tank;

an ammonia water production tower comprising a tower tank, a NH_3 spray nozzle
10 that is formed at a lower end of the tower tank and sprays NH_3 upward, a fresh water
spray nozzle that is formed at an upper end of the tower tank and sprays the fresh water
from the fresh water pump downward, a first packing material that is formed between the
 NH_3 spray nozzle and the fresh water spray nozzle and contacts the fresh water with NH_3
to dissolve NH_3 and generate ammonia water, and a cooling jacket that cools heat
15 generated by the tower tank due to a dissolution reaction; and

an ammonia water pump that supplies ammonia water from an ammonia water
storage tank, which stores ammonia water drained to a lower end of the ammonia water
production tower, to an upper end of the CO_2 removing unit.

20 7. The apparatus according to claim 6, wherein the ammonia water production
tower comprises a mist removal plate that is formed at the upper end of the tower tank in
a curved multi-plate shape and returns mist scattered from the fresh water toward the first
packing material.

8. The apparatus according to claim 6, further comprising a NH_3 supply pipe through which NH_3 exhausted to the upper end of the ammonia water production tower is supplied to an lower end of the CO_2 removing unit.

5 9. The apparatus according to claim 6, wherein the first packing material comprises multi-stage distilling column packings designed to increase a contact area per unit volume.

10 10. The apparatus according to claim 9, wherein a solution redistributor is formed between the multi-stage distilling column packings.

15 11. The apparatus according to claim 6, wherein a diameter and a height of the tower tank are designed so that a flow velocity of the fresh water and a flow velocity of the NH_3 are 1/2 of a flooding velocity.

12. The apparatus according to claim 6, wherein the loss and lack of NH_3 are compensated for by supplying NH_3 from the ammonia recycling unit through the NH_3 spray nozzle of the ammonia water producing unit or supplying NH_3 from a separate NH_3 storage tank when the loss and lack of NH_3 occur.

20 13. The apparatus according to claim 2 or 4, wherein the NO_x absorbing unit directly receives NH_3 from the ammonia recycling unit through a blower or a compressor and sprays the received NH_3 to a first NH_3 spray nozzle, or

when NH_3 is insufficient, the NO_x absorbing unit receives urea water of a urea

water storage tank through a urea water supply pump and sprays the received urea water to a second NH_3 spray nozzle so as to compensate for the lack of NH_3 .

14. The apparatus according to claim 5, wherein the SO_x absorbing unit
5 comprises a multi-stage seawater spray nozzle that is connected to the control valve and sprays seawater downward.

15. The apparatus according to claim 14, wherein porous upper plates having a passage through which exhaust gas passes are respectively formed in multi-stages under
10 the seawater spray nozzle, so that the seawater and the exhaust gas come into contact with each other.

16. The apparatus according to claim 14, wherein an absorption apparatus filled with a third packing material for allowing seawater and exhaust gas to come into contact
15 with each other are respectively formed under the seawater spray nozzle, so that the seawater dissolves SO_x .

17. The apparatus according to claim 14, wherein the SO_x absorbing unit comprises an umbrella-shaped partition wall that covers an exhaust gas inlet pipe so as to
20 prevent cleaning water from flowing backward.

18. The apparatus according to claim 6, wherein the CO_2 removing unit comprises:

an ammonia water spray nozzle that is connected to the ammonia water pump

and sprays ammonia water downward;

a second packing material that contacts CO_2 with the ammonia water and converts CO_2 into $\text{NH}_4\text{HCO}_3(\text{aq})$;

a cooling jacket that is formed in multi-stages for each section of an absorption
5 apparatus filled with the second packing material and cools heat generated by a CO_2 removal reaction;

a water spray that collects NH_3 discharged to the outside without reacting with CO_2 ;

a mist removal plate that is formed in a curved multi-plate shape and returns the
10 ammonia water toward the second packing material;

a partition wall that is formed so that the ammonia water does not flow backward;
and

an umbrella-shaped blocking plate that covers an exhaust gas inlet hole of the
partition wall.

15

19. The apparatus according to claim 4, wherein the absorption tower further comprises an exhaust gas economizer (EGE) that is formed between the NO_x absorbing unit and the SO_x absorbing unit and performs heat exchange between waste heat of the vessel engine and boiler water.

20

20. The apparatus according to claim 19, further comprising a steam generating unit comprising:

an auxiliary boiler that receives a mixture in the form of saturated water and heat-exchanged steam, separates the steam, and supplies the separated steam to a steam

consumer;

a boiler water circulating pump that circulates and supplies boiler water from the auxiliary boiler to the EGE;

a cascade tank that recovers condensed water from the steam consumer; and

5 a supply pump and a control valve that supply boiler water from the cascade tank to the auxiliary boiler while controlling an amount of boiler water.

21. The apparatus according to claim 6, wherein the ammonia recycling unit comprises:

10 a $\text{Ca}(\text{OH})_2$ storage tank that stores $\text{Ca}(\text{OH})_2$;

a mixing tank in which $\text{NH}_4\text{HCO}_3(\text{aq})$ discharged from the absorption tower is stirred with $\text{Ca}(\text{OH})_2$ by an agitator to generate $\text{CaCO}_3(\text{s})$ and H_2O and $\text{NH}_3(\text{g})$ is recycled;

a filter that suctions a solution and precipitate from the mixing tank and separates $\text{CaCO}_3(\text{s})$;

15 a high-pressure pump that transfers the solution and precipitate to the filter at high pressure; and

a $\text{CaCO}_3(\text{s})$ storage tank that stores a slurry or $\text{CaCO}_3(\text{s})$ of a solid state.

22. The apparatus according to claim 6, wherein the ammonia recycling unit
20 comprises:

a $\text{Mg}(\text{OH})_2$ storage tank that stores $\text{Mg}(\text{OH})_2$;

a mixing tank in which $\text{NH}_4\text{HCO}_3(\text{aq})$ discharged from the absorption tower is stirred with $\text{Mg}(\text{OH})_2$ by an agitator to generate $\text{MgCO}_3(\text{s})$ and H_2O and $\text{NH}_3(\text{g})$ is recycled;

a filter that suctions a solution and precipitate from the mixing tank and separates $\text{MgCO}_3(\text{s})$;

a high-pressure pump that transfers the solution and precipitate to the filter at high pressure; and

5 a $\text{MgCO}_3(\text{s})$ storage tank that stores a slurry or $\text{MgCO}_3(\text{s})$ of a solid state.

23. The apparatus according to claim 21 or 22, wherein ammonia water or fresh water separated by the filter is supplied to the ammonia water producing unit, or excess ammonia water or excess fresh water additionally generated by the mixing tank compared
10 to a total circulating fresh water is stored in the fresh water tank.

24. The apparatus according to claim 23, wherein the fresh water supplied from the fresh water tank is reacted with CaO to produce $\text{Ca}(\text{OH})_2$ in the $\text{Ca}(\text{OH})_2$ storage tank.

15 25. The apparatus according to claim 23, wherein the fresh water supplied from the fresh water tank is reacted with MgO to produce $\text{Mg}(\text{OH})_2$ in the $\text{Mg}(\text{OH})_2$ storage tank.

26. The apparatus according to any one of claims 1 to 4, further comprising a
20 discharge unit comprising:

a cleaning water tank that stores cleaning water discharged from the absorption tower;

a water treatment device comprising a filtering unit that controls turbidity to satisfy an outboard discharge condition of the cleaning water transferred to the cleaning

water tank by a transfer pump, and a neutralizing agent injecting unit that controls pH;

and

a sludge storage tank that separates and stores solid emissions.

- 5 27. A vessel comprising the apparatus according to any one of claims 1 to 4.