

1P05's copy

9901936-6

5

✓

**HIGH DENSITY HIGH PERFORMANCE
TELECOMMUNICATIONS/DATA LINK AND CONNECTOR WITH
TAP AND CONTACT DISPLACEMENT ASSEMBLY**

10

The invention relates to a high density high performance telecommunications data processing and connector assembly with tap and contact displacement assembly and to a process of forming it.

Commercial space is often provided as open floor areas. These are often
15 divided into work areas (cubicals). The occupant of the commercial space typically determines the most efficient use of the floor space for its own needs and selects how the floor space is to be divided into smaller working areas through the use of portable wall panels and similar structures. So called "systems" furniture is used for dividing

1

9901936-6

23 APR 1999

large floor spaces into smaller work areas (cubicals). Systems furniture arrangements typically utilize interior upright space-dividing panels which connect together serially, through two panel straight or angled connections, or through suitable three- or four-panel connections to define a large plurality of individual work areas. Such panels are typically less than floor-to-ceiling height and cooperate with other furniture components to define an equipped work area.

Each work area must be supplied with adequate electrical power and communication cabling. Various systems and components have been developed including modular electrical systems which cooperate with and which readily mount on the panels. This allows the panels to be reconfigured and allows the supply of power to the work areas.

Systems have been proposed to avoid the use of a large number of conventional four pair communication cables fed through floor conduits or ceiling clearance spaces to the various work areas. Examples of such prior art attempts include the systems and devices disclosed in U.S. Patent Nos. 5,272,277; 5,160,276 and 4,928,303. Numerous systems have been proposed relating to power lines and systems furniture. Many of these systems include features which solve particular problems relating to power transmission and distribution with systems furniture.

U.S. Patent 4,781,609 discloses a multicircuit electrical system which is used with wall panels. The electrical system is a seven conductor system employing three live and three neutral conductors for defining three separate electrical circuits each having a separate neutral. A portable power tap unit (a receptacle unit) can be plugged

into the power block for selective engagement with any one of the three circuits.

Although this system provides great advantages with regard to power and selecting one of the various circuits at the location, after the wall panels are put into place, using the tap feature, the system involves a great many components and is particular to the power
5 distribution problem.

U.S. Patent 5,236,370 discloses another electrical system for use with interior space dividing walls. The system is prefabricated and includes elongate harnesses mounted within channels which extend interiorly of the space-dividing members. Adjacent harnesses are electrically joined by flexible electrical jumpers which create
10 plug like connections with power blocks. This system provides significant advantages as to ease of use. However, the system again includes numerous components which adds significant expense. Additionally, the system again includes features which are directed toward power distribution and problems associated with power distribution.

The invention is therefore based on the technical problem of providing a high
15 density high performance transmission and connector system with high contact density for telecommunication and data applications, the connector having a good physical and electrical connection, so that transmission parts can be connected with a consistently high signal quality, even in the case of radio-frequency applications, and the system allowing a simple tapping of signals at the connector, as well as of providing a
20 production process for the assembly.

The solution to the technical problem is provided by the features of Patent Claims 1 and 17. Further advantageous developments emerge from the subclaims.

THIS SHEET HAS BEEN
REPLACED



It is an object of the invention to provide a high density high performance transmission and connector system for telecommunications and data applications, wherein the connector provides a good physical and electrical connection such that transmission portions can be linked while maintaining high signal quality, even for high frequency applications and which system allows for a simple tapping of signals at the connector.

According to the invention, a telecommunications/data link and connector assembly is provided including a transmission cable comprising a plurality of transmission lines, a first interface end assembly and a second interface end assembly.

10 The first interface end assembly comprises a first contact alignment body including a line connection end and an interface end. A first end plurality of contact elements is provided with each of the contact elements positioned and aligned by the first contact alignment body and extending from adjacent to the line connection end toward the interface end. Each of the first side contact elements is movable between a contact

15 position and a non-contact position. Each of the first side contact elements includes a contact area and a line connection area for an electrical connection with a line. A first end shield housing is provided wherein the first contact alignment body is disposed in the first end shield housing in a locked position. The second interface end assembly has a second contact alignment body including a line connection end and an interface end.

20 A second end plurality of contact elements is provided with each of the contact elements being positioned and aligned by the second contact alignment body and extending from adjacent to the line connection end toward the interface end. Each of



the second side contact elements is movable between a contact position and a non-contact position, each of the second side contact elements including a contact area and a line connection area for an electrical connection with a line. A second end shield housing is provided wherein the second contact alignment body is disposed in the second end shield housing in a locked position. Each of the first end shield and the second end shield is substantially identical and matable. These end shields are also matable with a first end shield and a second end shield of a substantially identical telecommunications/data link and connector assembly. Contact elements carried by each the contact alignment body are in a contact position when an associated end shield is in a mated position. A tap is provided which is insertable between contact elements for tapping signals carried by the contact elements.

The tap includes a tap transmission line and connected contact portions. The tap contact portions make electrical contact with one of a first side plurality of contacts and a second side plurality of contacts elements.

A contact displacement means is provided for moving contacts between the contact position and the non-contact position allowing insertion of the tap between the first side plurality of contact elements and the second side plurality of contact elements. The contact displacement means includes a first contact opening device connected to the first side plurality of contact elements. The first contact opening device is engaged by the tap means for moving contacts between the contact position and the non-contact position allowing insertion of the tap between the first side plurality of contacts and the second side plurality of contacts. The contact displacement means preferably also



includes a second contact opening device connected to the second side plurality of contacts and a tip of the tap means. The first contact opening device and the second contact opening device are for moving contacts between the contact position and the non-contact position.

5 The invention also includes a process of forming a telecommunications/data link and connector assembly including providing a contact alignment body with grooves for contacts and spaces for receiving wire side contact ends. The contacts are positioned in the grooves with wire contact ends extending into a wire and wire side contact end receiving spaces. A contact displacement member is provided connected to ends of the
10 contacts at the interface end. A wire guide with a plurality of wire channels is also provided. The wire guide has a cable end with a small width and a contact alignment body end with a larger width. The wire guide channels each have a wire path of substantially identical length, extending from the cable side to the contact alignment body side. A cable with wire terminal ends is employed. These wire terminal ends are
15 positioned in the guide channels of the wire guide and a contact portion of the terminal ends extends out of the guide channels. The contact portions are electrically connected with corresponding contacts at wire side ends of the contacts. The cable, the wire guide and the contact displacement assembly are joined by applying an overlay molded housing. The overlay housing is applied by positioning a portion of the cable, the wire
20 guide and a portion of the contact displacement assembly in a mold and injecting material in the mold to form the overlay molded housing. The connected elements with the overlay molded housing forms a single contact displacement assembly.



The wire contact ends and the contact wire side ends are preferably electrically connected by ultrasonic bonding (or ultrasonic welding). The contact alignment body preferably includes mold housing receiving sockets for receiving material of the overlay molded housing therein. The overlay molded housing preferably defines support rails.

5 A plurality of the single contact displacement assemblies are provided. These are inserted into a shield element forming a plurality of spaces. The shield element also includes a plurality of alignment portions corresponding to each of the spaces. Two substantially identical shield elements may be mated by connecting the alignment portions. The alignment portions (alignment tabs) are preferably male and female in an
10 alternating arrangement, whereby two shields of substantially identical form are mated by engaging the alignment portions while the shields are facing and one is rotated 180° with respect to the other.

The shields are preferably formed of a plastic with embedded metallic elements. The metallic elements may be for example stainless steel. This provides an important
15 shielding function (shielding one mated contact set from adjacent mated contacts). This advantageously affects the performance of the connector interface ends when they are mated with a substantially identical interface end. After inserting a contact alignment body of each single contact displacement assembly into each space of the shield, the contact alignment bodies are locked into place. When the shields are mated, the
20 contacts are engaged for passing electrical signals.

An indicator label element for a first side of the shield is provided and another indicator label element is provided for another side of the shield. Each indicator label

element includes receiving grooves for receiving a plurality of the support rails to cooperate with the single contact displacement assemblies and the shield to form a connector block.

The invention is explained in more detail below with reference to a preferred
5 exemplary embodiment. In the Figures:

Fig. 1 shows a perspective view showing a six circuit contact displacement assembly including two interface ends;

Fig. 2A shows a left top perspective view of a shield element of the contact displacement assembly of Fig. 1;

10 Fig. 2B shows a right top perspective view of the shield element of Fig. 2A;

Fig. 3A shows an enlarged view of the detail A of Fig. 2A;

Fig. 3B shows an enlarged view of the detail B of Fig. 2B;

Fig. 3C shows an enlarged view of the detail C of Fig. 2A;

15 Fig. 4 shows a cross sectional view of two shield elements in a position oriented for mating, with the tongue element shown in phantom in the locked S mating position;

Fig. 5 shows an exploded view of an interface end with the tap shown in a position for engagement;

20 Fig. 6 shows a perspective view of interface ends of a single contact displacement assembly (CDA), a component of the six circuit CDA of Fig. 1;

Fig. 7A shows a cross-sectional view of an interface end of the single CDA assembly of Fig. 4;

Fig. 7B shows a top view of a cable with twisted pair wires passing through a wire guide and connecting to contacts of the contact alignment body of an interface end;

Fig. 8 shows a perspective view of the wire guide;

Fig. 9A shows a perspective view of the contact alignment body with contacts attached to a lead frame and connected contact displacement device being inserted therein, prior to connection with the wires and wire guide;

Fig. 9B shows a perspective view of the contact alignment body with contacts attached to a lead frame inserted therein, prior to connection with the wires and wire guide;

Fig. 9C shows a cross sectional view showing the contact alignment body prior to insertion of the contacts;

Fig. 9D shows a bottom front perspective view showing the contact alignment body before being associated with the contacts and contact displacement device;

Fig. 10A shows a cutaway view showing a portion of the cable and twisted pair terminal ends;

Fig. 10B shows a cross-sectional view of the cable;

Fig. 11 shows a interior side front perspective view of the color indicator

label of the six circuit contact displacement assembly of Fig. 1;

Fig. 12 shows an interior side front perspective view of the circuit indication label support element of the six circuit contact displacement assembly of Fig. 1;

5 Fig. 13A shows a left top perspective view of the tap according to the invention;

Fig. 13B shows a right bottom perspective view of the tap according to the invention;

Fig. 13C shows a front view of the main tap element, prior to the main
10 tap element being connected with lines of a cable being joined with a tap molded portion;

Figure 14 shows a partial side cutaway view illustrating contact between contacts of mated interfaces; and

Figure 15 shows a side sectional view showing a mated interface with an
15 inserted tap wherein a line is tapped and a downstream line is disconnected.

Referring to the drawings in particular, the invention comprises a multi-circuit contact displacement assembly (CDA) generally designated 10. The assembly includes a first interface end assembly 6 and an identical (substantially identical, apart from
20 minor tolerance variations) second interface end assembly 8. Although the interface ends 6 and 8 are identical, they have male and female portions (alignment tabs) whereby they are adapted to be positioned in a mated contact state. Each interface end 6, 8 is

intended to be used for mating connection with another multi-circuit CDA to provide a linking of transmission lines at the contact interfaces and to provide a tapping region for tapping the lines. The multi-circuit contact displacement assembly 10 is particularly useful when disposed in modular office furniture components such as modular walls
5 used to make office cubicals. A plurality of contact circuit assemblies may be provided in parallel (such as three) for eighteen different single contact displacement assemblies in parallel providing a multiplicity of two pair lines.

Fig. 1 shows a six circuit CDA 10 with each interface end 6, 8 having a shield housing 12 supporting a plurality of contact alignment bodies 14. As discussed further
10 below, the contact alignment bodies 14 may be snapped into shield housing 12 where they are retained for providing one connection side at a contact interface. The contact alignment bodies 14 are part of single contact displacement alignment (CDA) assemblies 18. In the position as shown in Fig. 1, with the single CDAs 18 supported by shield 12, color indicator label element 16 may be connected to the single CDA
15 assemblies 18. Additionally, a circuit indicator element 20 may be connected to the single CDA assemblies 18 on a non-tap insertion side of each interface. On a tap side of the interface, the single CDA assemblies 18 are exposed.

Fig. 2A shows a left top perspective view of a housing, particularly a shield housing 12. The shield housing 12 is preferably a unitary molded structure. The shield
20 housing 12 is preferably formed of a plastic with embedded stainless steel fibers or stainless steel elements to provide an electrical shield function. The shield 12 has an upper surface 26, a tap access side 28, a non-access side 30 as well as a bottom 32 (see

Fig. 1). The bottom 32 includes a tongue 34 which provides an engagement function for connection of two interface ends. The tongue 34 includes a tongue bezel 36. To provide for engagement, each shield includes a male enclosure portion 38 and a female enclosure portion 40 (these are also referred to as alignment tabs). These two enclosure portions 38, 40 mate for connection of two interface ends. The tongue bezel 36 provides for ease of insertion of the tongue 34 between an upper surface of male enclosure portion 38 and an interior surface of upper portion 26. On the underside or bottom side 32, the tongue 34 includes an engagement bezel 42 with a locking rear edge. This allows a locking of one interface side by engagement of the engagement bezel 42 with the back edge of upper portion 26 as shown in phantom line in Fig. 4. The ramp 44 assists in locking the assemblies by providing a friction surface. The stop portion 46 provides a stop function upon contact of the front edge of stop portion 46 with a front edge of the shield upper part 26. Interface sides of single CDA assemblies 18 are connected to each other via single CDA assembly cable 22.

Fig. 3A, 3B and 3C provide enlarged views of the shield 12. As seen in Fig. 3A, at the access side 28 tap entry portion 50 delimits an upper edge of one side of a tap slot 56 which will be defined by mated interface ends. At the tap side 28, the male enclosure portion 38 includes a female recess 52 and a male portion 54. Male portion 54 is tapered to allow ease of connection of the two parts for mating contact. As can be seen from Fig. 3B, just behind each enclosure portion (both male enclosure portion 38 and female enclosure portion 40), the shield housing 12 has locking slots 57. These locking slots 57 are used for fixing the single CDA assemblies 18 to the shield housing

12. The shield 12 is shown in a position oriented for mating with another shield housing 12 in Fig. 4.

Fig. 6 shows a single CDA assembly 18 including a single interface element end and portions of the associated cable 22. Each interface end of the CDA assembly 18 includes an overlay molded housing 58. This overlay molded housing 58 has a function of joining the various components of each interface end of CDA assembly 18. The overlay molded housing 58 includes support rails 60. These are discussed further below. Each assembly 18 also includes a contact alignment body 14 with contacts 62 and contact opening device 66. Each interface end of the assembly 18 also includes a wire guide 64 (see Fig. 7A, 7B and Fig. 8).

Fig. 7A shows a cross-sectional view of an interface end of CDA assembly 18, taken just above the contact surface. It can be seen that the overlay molded housing 58 extends into a region of the contact alignment body 14 to connect overlay molded housing 58 and alignment body 14. In joining with the portion 40, overlay molded housing 58 also houses and surrounds wire guide 64. Overlay molded housing 58 also extends into the channels 88 which are provided for twisted pair terminal ends 110. This is discussed further below.

Fig. 7B shows a cable 22 with twisted pair terminal ends 110 extending into wire guide 64. The twisted pair terminal ends 110 also extend into contact alignment bodies 14 where they are connected and make contact with contact 62. The structure shown in Fig. 7B is the single CDA assembly 18 just prior to the application of the overlay molded housing 58.

Fig. 8 shows the wire guide 64 with a variety of channels 63. These channels 63 are significant as they provide twisted pair channels which are of substantially identical length from one end to an opposite end. In this way, twisted pair wires 110, as shown in Fig. 10 can be used which have terminating ends which are of substantially the same length for each twisted pair 110. This provides a significant advantage as to manufacturing. Wire guide 64 includes alignment protuberances 92 which facilitate alignment of the wire guide 64 and the contact alignment body 14 during manufacture. Wire guide 64 also includes overhang portions 65 which help retain the twisted pair within the channels 63 of wire guide 64.

Fig. 9B shows the contact alignment body 14 with associated contact elements 62 still connected to a lead frame 73 (the lead frame 73 is subsequently removed) and contact displacement device (or contact displacement device) 66. As can be seen in Fig. 9A, the contact opening device 66 has a tap cam follower 68 with locking protuberances (or posts) 70 for locking in the contact position. The cam follower 68 includes bezel ramp 72 which allows insertion of the tap 138 and begins movement of the contact opening device 66 for moving contact portion 76 out of engagement as a tap 138 is inserted between contacts of mated interfaces. Each contact element 62 includes a spring portion with bend 74 and barbs 78.

As can be seen in Figures 9A and 9D, each contact alignment body 14 has a front end with a receiving region 79 and a similar tap side receiving region 79'. These have at their very front edge a engagement bezel 80. As can be seen from Figs. 9A and 9D, each bezel 80 is on an upper and lower side of each alignment body 14. At an

upper side of each contact alignment body 14 there is provided a stop edge element 82. At the back side of contact alignment body 14 there are wire channels 88 as well as alignment slots 90 (see Fig. 9A).

Fig. 9D shows the underside of the contact alignment body 14. This includes a
5 molded housing receiving space 96. By viewing Figs. 9D and 9A, it can be appreciated that the overlap molded housing 58 extends up to the rear side of stop edge 82, extends into molded housing receiving sockets 86 and into molded housing receiving space 96, thereby unifying the contact alignment body 14, the wire guide 64 and the electrically connected contacts and twisted pair terminal ends. This assembly technique has the
10 further advantage that the overlay molded housing 58 (see Figs. 6, 7A and 7B), surrounds the cable jacket 112, surrounds the twisted pair terminal ends 110 and extends into the terminal end panels of wire guide 64. Overlay molded housing 58 also surrounds a rear portion of contact alignment body 14 and extends into the molded housing receiving sockets 86, surrounds the wire contact interface engages the contact
15 barbs 78 and also fills the molded housing receiving space 96. This results in, among other things, a joining of the cable jacket 112 and the contact alignment body 14 such that there is no strain of the individual twisted pair terminating ends 110 and there is no strain at the contact interface between twisted pair terminating ends 110 and contact elements 62. An alternative embodiment of the invention may also be provided wherein
20 no wire guide 64 is provided. In this case the pair of terminating ends 110 are welded or otherwise electrically connected and affixed to contact elements 62 and the overlay molded housing 58 is applied. The overlay molded housing 58 provides isolation of the

twisted pairs 110. The alignment slots 90 are not required.

Fig. 9C shows a cross-sectional view of the contact alignment body 14. In this view the receiving region 79' is shown along with the engagement bezel 80. Further, an alignment region 87 is shown which includes walls and a base support for positioning a contact element 62. Underneath and behind the stop edge 82 there is provided a space 89 which communicates with the mold housing receiving socket 86 and also communicates with the wire channels 88. This space 89 receives the wire side end of contact element 62. Although space 89 communicates with opening 86 and wire channels 88, the upper side regions of space 89 are delimited by the plastic (or other suitable material) walls of contact alignment body 14 such that upon insertion of the wire ends of contact elements 62 into space 89, the barbs 78 engage the contact alignment body housing 14. The contact element 62 cannot be effectively or easily removed from the contact alignment body 14, once they are inserted into the space 89, as the barbs 78 will dig into the plastic contact alignment body housing 14 above space 89, upon a pulling of the contact element 62 in a removal direction. Specifically, the barbs 78 are angled such that insertion of the wire end into the space 89 is fairly smooth but any retraction of the contact element 62 is effectively prevented as the barbs 78 engage the material of the alignment body 14 delimiting parts of space 89.

Figs. 10a and 10b show aspects of the cable 22 for single CDA assembly 18. The cable 22 includes the cable jacket 112 and the twisted pair terminating ends 110. Fig. 10b shows the relative position of the various twisted pairs 110 and the jacket 112.

Fig. 11 shows the interior side of a color indicator label element 16. Element 16

includes a rail receiving portion 116 for receiving ends of rails 60 of an interface end of CDA 10. Each rail 60 is from one single CDA assembly 18. The rail receiving portion 116 includes a narrow ridge such that element 16 slides on the various rails 60 of the various assemblies 18. Locking protuberances 122 cooperate with the locking groove 124 formed in overlay molded housing 58 of each interface end of each assembly 18 (see Fig. 7A). Another locking groove 136 is also provided in each rail 60 of each molded housing 58. Locking protuberance 122 allows the color indicator label element 16 to slide on the rails 60 of the assemblies 18 and be locked into position.

Fig. 12 shows a circuit indicator 20, which is connected to a plurality of assemblies 18 at one interface end, on a side opposite to an access side. The rails 60 on the access side are used for fixing the tap element 138 as described below. Circuit indicator 20 includes a rail receiving groove 126 with a base. The groove also defines a small dimension gap which allows the groove to be attached by sliding circuit indicator element 20 on to the rail 60 or snapping it on. A protuberance 128 extends outwardly from the groove base and provides a locking element for extending into locking groove 136 of molded housing 58.

Figs. 13A and 13B show views of a tap assembly 138. Several tap assemblies may be used with each mated interface. Each tap 138 is used to tap lines at an interface of contacts of single CDA assemblies 18 of mated interface ends of two CDA assemblies 10. Each tap 138 includes a body 140 with grasping region. A tap line 142 extends into the body wherein the various wires of tap line 142 are connected to traces provided in or on a tap slot insertion element 150. The traces extend to contacts 148. A

plurality of contacts 148 are provided on a contact side 152 of the tap slot insertion element 150. The tap body 140 is provided with a rail engagement portion 144. This defines a rail receiving groove 146 for rail 60. With this structure, the tap assembly 138 may be engaged with mated interface ends and fixed at exposed rail 60 on the tap side of one interface body such as interface body 8 (see Fig. 1).

As can be seen in Fig. 14, when interface ends are mated, the contacts are in an electrical contacts position with the contact portions 76 in physical contact for providing an electrical connection. As can be seen by comparing Figure 13A to Figure 13B, each tap slot insertion element 150 includes a contact side 152 and an opposite side 154. When the tap slot insertion element 150 is inserted into the insertion slot 56 (see Fig. 1 and Fig. 3A), the tap is positioned for connection of rail engagement portion 144 with the exposed rails 60 of the assemblies 18, the contacts 148 will connect with contacts 62 at the upstream side of the transmission line (see Fig. 5). The down stream side of the transmission line is broken as the contact 62 on the inner side of the interface (in the upstream interface element) is maintained out of contact with the tap due to the camming surfaces of tap cam follower 68 (protuberances 70, and the surface of tap opposite side 154). This state is shown in Fig. 15. A more detailed discussion of a similar contact displacement arrangement is discussed in EP-97 10 8131.0, which is hereby incorporated by reference.

The protuberances or posts 70 in the contact opening device 66 are such that the contacts 62 are maintained in a non-contact position while the insertion element 150 is inserted between the contacts. When the tap 138 is properly positioned, the posts or

protuberances 70 extend into openings 153. It is possible to only have openings 153 on the contact side 152 and to not have these on the opposite side 154. This will maintain one set of contacts 62 in a non-contact position. However, as no contacts 148 are provided on side 154, holes 153 can be provided on side 154 as well. This allows the
5 contacts to move into a contact position although no electrical contact is made and the down stream line is disconnected. The dimension of the tap slot insertion element 150 and the tap slots 56 defined by engaged parts of shields of mated interface element ends if preferably selected such that very few things can get between the mated interface ends to damage the contact displacement arrangement. The shape of the various portions 50,
10 54 and 52 of the shield housing 12 facilitates defining a small slot with no other access space on either the non-access side 30 or the access side 28.

Fig. 13C shows a front view of the main tap element 160 prior to overlaying or molding on the tap body 140. As can be seen, connection points 162 are provided for soldering on, welding or otherwise connecting lines of the tap cable 142. The tap
15 element 160 is preferably made in the form of a printed circuit board. The printed circuit board 160 has traces or other appropriate connection lines extending from contact points 162 to contacts 148.

The device is assembled by providing a cable at 22 as shown in Fig. 10a and placing twisted pair terminal ends 110 in the channels of the wire guide 64. As noted,
20 the length of each terminal end 110 is the same. The wire guide is placed into contact with the contact alignment body 14 carrying contacts 62 and contact displacement device 66. Electrical contact between the terminal ends 110 and the contacts 62 is

preferably provided by ultrasonic welding. Other known connections may be provided such as displacement contacts soldering or other joining for electrical contact. Ultrasonic welding is preferred as providing better characteristics including no significant additional resistance.

5 A structure as shown in Fig. 5B results from the above steps. Subsequently, this structure is overlay molded to provide overlay molded housing 58. When this is provided on both ends of the cable, this results in a single contact displacement assembly 18 as shown in Fig. 4. The single CDA assembly 18 has two interface ends. One end of CDA assembly 18 is inserted in a shield housing 12. The other end is
10 inserted in another shield housing 12. Engagement bezel 113, at the base of each contact alignment body 14, facilitates the insertion of an interface end of CDA assembly 18. Engagement protuberance 114 has a back edge which provides a locking function upon engagement with locking groove 57 of shield 12 (see Figs. 3B and 3C).

On the non-access side, by rails 60, a circuit indicator 20 may be connected via
15 rails 60 and the connection between groove 124 and protuberance 134. In a similar manner, two color indicator labels can slide onto rails 60 on each side whereby locking protuberance 122 of each element 16 engages a respective locking groove 124 provided on rails 60. With these steps taken with regard to each interface element 8 and 6, an assembly 10 as shown in Fig. 1 is provided. The interface ends of the CDA 10 are
20 identical and each interface element of the assembly 10 may mate with an identical interface element of another identical assembly 10. Mating of interface ends takes place with the tongue 34 being inserted between the lower surface of the top 26 of shield 12

and the upper surface of male enclosure portion 38. Each male enclosure portion 38 extends into each female enclosure portion 40 with the various portions 52, 54 and 50 at the tap side engaging. When the engagement bezel 42 is positioned such that the back edge engages the back edge of shield top 26, the interface body of one assembly 10 is
5 connected to the interface body of another assembly 10. In this position, the contacts 62 are in a contact position such that signals are transmitted downstream.

The tap 138 may be inserted on the tap side 28 of the shields of the mated interface ends. The tap 138 may be fixed via rail 60 and engagement part 144. If the tap 138 is inserted properly, engagement part 144 will connect with rail 60 in the
10 inserted position. This will break the electrical contact between contacts 62 of two interfaces of two assemblies 10. This will provide a tapping contact via the tap contacts 148.

While specific embodiments of the invention have been shown and described in detail to illustrate the application of the principles of the invention, it will be understood
15 that the invention may be embodied otherwise without departing from such principles.

List of designations

- 6) Interface end assembly
- 8) Interface end assembly
- 10) Contact displacement assembly/CDA
- 12) Housing
- 14) Contact alignment body
- 16) Color indicator label element
- 18) Contact displacement alignment assembly/CDA assembly
- 20) Circuit indicator element
- 22) CDA assembly cable
- 26) Upper surface
- 28) Tap access side
- 30) Non-access side
- 32) Bottom
- 34) Tongue
- 36) Tongue bezel
- 38) Male enclosure portion
- 40) Female enclosure portion
- 42) Engagement bezel
- 44) Ramp
- 46) Stop portion

- 50) Tap entry portion
- 52) Female recess
- 54) Male portion
- 56) Tap slot
- 57) Locking slots
- 58) Housing
- 60) Support rails
- 62) Contact
- 63) Channel
- 64) Wire guide
- 66) Contact opening device
- 68) Tap cam follower
- 70) Protuberance/post
- 72) Bezel ramp
- 73) Lead frame
- 74) Bend
- 76) Contact portion
- 78) Barbs
- 79) Receiving region
- 80) Bezel
- 82) Stop edge
- 86) Mold housing receiving sockets

- 87) Alignment region
- 88) Wire channels
- 89) Space
- 90) Alignment slot
- 92) Alignment protuberances
- 94) Wire guide
- 96) Mold housing receiving space
- 110) Pair terminal ends
- 112) Cable jacket
- 114) Engaging protuberance
- 116) Rail receiving portion
- 122) Locking protuberances
- 124) Locking groove
- 134) Protuberance
- 136) Locking groove
- 140) Tap body
- 142) Tap channel
- 144) Rail engaging portion
- 146) Rail receiving element
- 148) Contacts
- 150) Contact opening device engaging surface/tap slot insertion element
- 152) Contact side

- 153) Opening
- 154) Side
- 160) Tap element
- 162) Connection points



THIS SHEET HAS BEEN
REPLACED

Patent claims

5

- 1) A telecommunications/data link and connector assembly, comprising a CDA assembly cable (22) comprising a plurality of transmission lines, a first and second interface end assembly (6, 8), which are respectively disposed at one end of the CDA assembly cable (22) and respectively comprise
 - 10 a contact alignment body (14) including a line end and an interface end, contact elements (62), which are respectively located at the end, are respectively disposed on said contact alignment body (14) and extend from a position adjacent to said line terminal end toward said interface end, each contact element (62) being movable between a contact position and a non-contact position, each contact element (62)
 - 15 comprising a contact area and a line connection area for an electrical connection with a line, a housing (12), which is located at the respective ends, said contact alignment body (14) being disposed at the second end in a locked position, and the housings (12) of the first and/or second end of the telecommunications/data link and connector assembly being designed such that they can be mated with first and/or second ends of a further
 - 20 telecommunications/data link and connector assembly, the respective contact elements (62) in the mated state being contacted in the contact area and a tap (138) being able to be inserted between said contact elements (62), allowing electrical signals to be tapped

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

from said contact elements (62).

- 2) The assembly according to claim 1, wherein said tap (138) includes a tap line (142) and comprises contacts (148) which are connected to said tap line (142) and form an electrical connection with the contacts (62) of the mated interface end assembly
5 (6, 8).
- 3) The assembly according to claim 1 or 2, wherein said contact elements (62) are associated with resilient means for supporting said contact area, allowing said contact area to move between said contact position and said non-contact position.
- 4) The assembly according to one of the preceding claims, wherein said
10 contact elements (62) are associated with contact displacement means for moving said contact elements, allowing said contact elements (62) to move between said contact position and said non-contact position and insertion of said tap (138).
- 5) The assembly according to claim 4, wherein said contact displacement means comprises a contact opening device (66).
- 15 6) The assembly according to one of the preceding claims, wherein the housings (12) disposed at the ends are designed with additional contact alignment bodies (14).
- 7) The assembly according to one of the preceding claims, wherein said assembly (10) comprises a wire guide (64), the CDA assembly cable (32) being
20 designed as twisted wire pairs with pair terminal ends (110), said wire guide (64) having a wire entry side and a narrower wire connection side, said wire guide (64) defining wire paths of substantially equal length from said wire entry side to said wire

This Sheet Has Been Replaced





connection side and said wire guide (64) being disposed between said CDA assembly cable (22) and said contact alignment body (14).

8) The assembly according to claim 7, wherein said assembly (10) has an overlay molded housing (58) connected to said transmission cable (22), to said wire
5 guide (64) and to said contact alignment body (14), said contact alignment body (14) being designed with mold housing receiving sockets (96), said twisted pair terminal ends (110) being electrically connected to said contact elements (62).

9) The assembly according to claim 8, wherein a portion of said contact alignment body (14), said wire guide (64) and a portion of said cable (22) are molded
10 together in one mold.

10) The assembly according to one of the preceding claims, wherein said interface end assemblies (6, 8) comprise a support rail (60), said tap (138) comprising a support rail engaging portion (144) for engaging said support rail (60).

11) The assembly according to one of the preceding claims, wherein said
15 assembly comprises at least one circuit indicator (20) and one color indicator label element (16), which can be connected to said support rail (60).

12) The assembly according to one of the preceding claims, wherein said housings (12) respectively comprise a plurality of male enclosure portions (38) and female enclosure portions (40), which define a space for receiving a contact alignment
20 body (14), the male enclosure portions (38) of one housing (12) being designed such that they can be mated with the female enclosure portions of another housing (12), and said housings (12) comprising locking means for locking to each other.

THIS SHEET HAS BEEN
REPLACED





- 13) The assembly according to claim 12, wherein said locking means comprises a tongue (34) and a tongue receiving portion, said tongue (34) being designed with an engagement bezel (42) for locking on a back edge of a receiving portion of an identical housing (12).
- 5 14) The assembly according to one of the preceding claims, wherein said housings (12 are formed of plastic with embedded metallic elements.
- 15) The assembly according to one of claims 5 to 14, wherein said contact opening device (66) comprises a tapping surface (56) including camming/locking posts (70), said tap (138) comprising a contact opening device engaging surface (150) with
- 10 post receiving openings (153), a tap transmission line (142) and contact portions (148), said contact opening device engaging surface (150) cooperating with said camming/locking posts (70) of said tapping surface (56) upon insertion of said tap (138) to move said contact elements (62) into a non-contact position and to move said contact element (62) into a tapping position upon further insertion of said tap (138), said posts
- 15 (70) extending into corresponding post receiving openings (153), whereby said contact elements (62) return to a contact position and said contact elements (62) make electrical contact with said tap contact portions (148).
- 16) The assembly according to claim 15, wherein said contact elements (62) carried by said contact alignment body (14) of said housing (12) of another connector
- 20 interface assembly are associated with another contact opening device (66) including a tap engaging surface (150) including camming/locking posts (79), said tap (138) having a second contact opening device engaging surface without post receiving openings,

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced





whereby at least some of the said contact elements (62) carried by said contact alignment body (14) of said housing (12) of said another connector interface assembly are urged into a non-contact position upon insertion of said tap (138), said tap (138) including tapping contacts on one contact side (152) only, whereby said contact

5 elements carried by said contact alignment body (14) of said housing (12) of said another connector interface assembly are disconnected while said tap (138) is in said tapping position to interrupt at least one said electrical path through the connector interface assembly to transmission lines of a downstream transmission cable.

- 17) A process of forming a telecommunications/data link and connector
- 10 assembly, the process comprising the steps of:
- a) providing a contact alignment body (14) with grooves for contacts and spaces for receiving wire side contact ends,
 - b) positioning contacts (62) in said grooves, said contacts (62) having wire contact ends extending into said wire contact and receiving spaces and having interface ends,
 - 15 c) providing a contact displacement member (10) connected to said interface ends of said contacts (62),
 - d) providing wire guides (64) with a plurality of wire channels (88), said wire guides (64) having a cable end of a small width and a contact alignment body end of a larger width, said wire channels (88) providing a wire path of substantially identical lengths
 - 20 extending from said cable end to said contact alignment body end,
 - e) providing a cable (22) with wire terminal ends,
 - f) disposing said wire terminal ends in said wire channels (88) of said wire guide (64) in

THIS SHEET HAS BEEN
REPLACED





a contact portion of said terminal ends extending out of said wire channels,

g) electrically connecting said contact portions with corresponding contacts at wire side ends of said contacts and

h) joining said cable (22), said wire guide (64) and said contact displacement assembly

- 5 (10) with an overlay molded housing (58) by positioning a portion of said cable (22), said wire guide (64) and a portion of said contact displacement assembly in a mold and injecting material in said mold to form said overlay molded housing (58).

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced

