



(51) International Patent Classification:
C08L 33/04 (2006.01) **C08L 23/08** (2006.01)

Torsten [DE/DE]; Valentin-Senger-Straße 29, 60389 Frankfurt (DE).

(21) International Application Number:
PCT/EP2010/060518

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
21 July 2010 (21.07.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09171400.6 25 September 2009 (25.09.2009) EP

(71) Applicant (for all designated States except US):
EVONIK ROHMAX ADDITIVES GMBH [DE/DE]; Kirschenallee, 64293 Darmstadt (DE).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SONDJAJA, Ronny** [ID/ID]; Jl. Salendro Timur Raya no 2, 40275 Bاندung (ID). **KOSCHABEK, Rene** [DE/DE]; Hebelstraße 6, 69469 Weinheim (DE). **WEBER, Markus** [DE/DE]; Finkenweg 13, 64395 Brensbach (DE). **BENITO, Jane** [PH/PH]; 90 D. Consunji Street, 2113 San Roque, Samal (PH). **LIU, Jian Mike** [SG/SG]; Block 275C, #02-77, Jurong West Street 25, Singapore 643275 (SG). **STÖHR,**

Published:

— with international search report (Art. 21(3))

(54) Title: A COMPOSITION TO IMPROVE COLD FLOW PROPERTIES OF FUEL OILS

(57) Abstract: The present invention describes a composition comprising at least one polyalkyl(meth)acrylate polymer having a number average molecular weight Mn of from 1000 to 10000 g/mol and a polydispersity Mw/Mn of from 1 to 8 and at least one ethylene vinyl acetate copolymer comprising units being derived from at least one alkyl (meth)acrylate having 1 to 30 carbon atoms in the alkyl residue. The composition is useful as cold flow improver in fossil fuel oil and or biodiesel fuel oil.

