

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F17C 5/06	A1	(11) International Publication Number: WO 97/48944 (43) International Publication Date: 24 December 1997 (24.12.97)
(21) International Application Number: PCT/BR97/00031 (22) International Filing Date: 20 June 1997 (20.06.97) (30) Priority Data: PI 9601861-5 20 June 1996 (20.06.96) BR (71) Applicant (for all designated States except US): EMPRESA BRASILEIRA DE COMPRESSORES S/A. - EMBRACO [BR/BR]; Rua Rui Barbosa, 1020, CEP-89219-901 Joinville, SC (BR). (72) Inventor; and (75) Inventor/Applicant (for US only): RAUBER, Diego, Luiz [BR/BR]; Rua Coelho Neto, 590, CEP-89219-901 Joinville, SC (BR). (74) Agents: ARNAUD, Antonio, M., P. et al.; 7th floor, Rua José Bonifácio, 93, CEP-01003-901 São Paulo, SP (BR).	(81) Designated States: CN, JP, KR, SG, US , European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	



(54) Title: A PRESSURIZING AND SEALING DEVICE AND PROCESS FOR HERMETIC SYSTEMS

(57) Abstract

Patent of invention for pressurizing and sealing device and process for hermetic systems, provided with a gas feeding conduit (1), comprising: a tubular body (10) defining an internal chamber (13) between a first end (11) which can be tightly seated against an open external end (2) of the gas feeding conduit (1) and a second open end (12), and a pressurized gas inlet nozzle (14) opened into the internal chamber (13); an elastomeric plug (30) which can be positioned inside the tubular body (10) in such a way that it can be selectively displaced from a pressurizing condition, sealing the second end (12) of the tubular body (10) when the internal chamber (13) and the hermetic system are pressurized through the pressurized gas inlet nozzle (14), to a plugging condition, in which it is sealingly fitted and maintained in the external end (2) of the gas feeding conduit (1) after said pressurization has ended; and an impelling means (40), which is coupled to the tubular body (10) and which can be selectively activated through the second end (12) of said body so as to conduct the elastomeric plug (30) from the pressurizing condition to the plugging condition.

