PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : C10M 171/00 — A1

(11) International Publication Number: **WO 00/44860**

(43) International Publication Date: 3 August 2000 (03.08.00)

(21) International Application Number: PCT/GB00/00220

(22) International Filing Date: 26 January 2000 (26.01.00)

(30) Priority Data:
9901667.7 26 January 1999 (26.01.99) GB

(71) Applicant *(for all designated States except US)*: IMPERIAL CHEMICAL INDUSTRIES PLC [GB/GB]; Imperial Chemical House, Millbank, London SW1P 3JF (GB).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: CORR, Stuart [GB/GB]; P.O. Box 8, The Heath, Runcorn, Cheshire WA7 4QD (GB). GIBB, Peter, Timothy [GB/GB]; Uniqema Lubricants, P.O. Box 90, Wilton Centre, Middlesborough, Cleveland TS90 8JE (GB). RANDLES, Steven, James [GB/GB]; Uniqema Lubricants, P.O. Box 90, Wilton Centre, Middlesborough, Cleveland TS90 8JE (GB).

(74) Agent: GEARY, Stephen; W.H. Beck, Greener & Co., 7 Stone Buildings, Lincoln's Inn, London WC2A 3SZ (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: REFRIGERATION LUBRICANT COMPOSITION

(57) Abstract

A lubricant composition containing an anti–deposition component having an anti–deposition effect which is especially useful for the lubrication of refrigeration compressors and in reducing or removal of unwanted deposits in constricted areas in a refrigeration system.