

INTEGRATED CIRCUIT DEVICE AND METHOD OF MANUFACTURING THEREOF

BACKGROUND

5 [0001] This invention relates generally to an integrated circuit (IC) device and a method of manufacturing the IC device. More particularly, this invention relates to an IC device including one die or two or more dies arranged in a matrix array package configuration so as to achieve very high pin counts and multiple functionality within the defined device geometry, and to a method of manufacturing such an IC device.

10 [0002] With the miniaturization of electronic products, there is a need to also reduce the size of IC packaged devices and to add more functionality so that more of these IC devices can be packed into a given area of a substrate. Two approaches have been taken to meet such a need. A first approach is to reduce the size of packaging of existing IC device packages. The second approach is focused on increasing the functionalities provided by each IC device, for example to form a system-in-package (SIP) devices.

Figures 1A- 1F show prior art IC devices fabricated in a wafer level configuration. Each individual device is packaged while they are still available in wafer form, prior to the wafer dicing process to obtain chip sized package. Many packaging process steps are added directly on a wafer to realize these chip sized packages, which are of small form factor and reduced weight. However, the IC device obtained in this method are limited to the IO density as the chip size determines the package IO density.

20 [0003] U.S. Patent Nos. 6,777,267; 6,768,331; 6,667,543; 6,635,509; 6,596,560; 6,593,220; 6,465,281; 6,452,238; 6,441,488; 6,429,511; 6,341,070; 5,448,014 discloses an IC device having a footprint approximately the size of a die of the IC device. The steps for manufacturing the IC device includes: (1) providing a wafer that includes multiple dies wherein each die includes multiple connection pads, Different packaging process steps are added to arrive at the final IC device before the same are separated.

30 SUMMARY

[0004] According to an aspect of the present invention, there is provided a method of manufacturing an integrated circuit (IC) device. According to the method, a wafer including multiple dies separated by separation zones is first provided. Each

die includes connection terminals on a first active side of the wafer is separated by wafer dicing process well known in the art of semiconductor manufacturing. A conductive substrate of pre determined thickness and size are patterned for routing traces and partially etched on a first side, by photolithographic method well known in the art of semiconductor process. The patterning and etching are done such that each circuit routing trace pattern corresponds to the plurality of connection terminals that are present in the individual IC chip. Multiple Chip level patterns are arranged in array form on a conductive substrate by clearly defining separation zones to package multiple IC devices simultaneously. Each IC chip's connection terminals are aligned and attached with their plurality of corresponding connection pads on the first side of a substrate. The first side of a substrate along with the attached IC chips are fully encapsulated. The excess conductive material on the second side of the conductive substrate is then removed to expose the patterned and partially etched routing traces of the first side of a substrate. Interconnect contacts are formed on the second side of the substrate. These contacts are electrically connected to the routing terminals in the interior of the partially etched patterns thereby electrically connect with the connection terminals on the first side of the IC chip. The IC chips are separated along the separation zones of the substrate to produce individualized packages, each of which serves as an IC device.

[0005] Preferably, the method may further include forming a plurality of connection pads on the first side of conductive substrate by additive and or subtractive methods that are well known in the art of semiconductor fabrication processes.

[0006] Preferably, the method may further include forming the circuit patterns by additive and or subtractive methods that are well known in the art of semiconductor fabrication processes.

[0007] Preferably removing substrate material includes removing conductive material from a second side of the substrate, opposite the first side, to expose the patterned circuit layer on the first side of the substrate.

[0008] Preferably, the method may further include substrate etching depth be determined by functional requirements.

[0009] The method may further include forming terminals electrically connected to the contacts. Preferably, forming terminals includes forming a solder mask over the routers and contacts on the second side of the substrate, removing portions of

the solder mask over the contacts to expose the contacts and forming solder bumps over the exposed contacts.

[0010] The method may further include, providing a build – up layer directly on the second side of the substrate in order to eliminate the organic build up of BGA package.

[0011] The method may further include routers that route connection pads on a first side of the substrate to corresponding contacts on the second side of the substrate, after the build-up layers.

[0012] Preferably, the method further includes providing at least two functional IC chips interconnected on the first side of the substrate adjacent to each other to form a system in package (SIP) configuration.

[0013] According to another aspect of the present invention, there is provided an integrated circuit (IC) device manufactured according to the method described above. This IC device includes a first die having multiple connection pads on a first active side routed to the corresponding contacts on a second side of the first conductive substrate. The second IC device having multiple connection pads on its first side are routed to the second side of a second conductive substrate. The contacts on the second side of the first conductive substrate of the first die and the contacts on the second side of the second conductive substrate of the second die are further connected using an interposer with conductive contacts forming a stack configuration.

[0014] Preferably, the interposer for connections is made of a flexible circuit board for interconnections between IC devices to the printed circuit board.

[0015] According to another aspect of the present invention, there is provided an integrated circuit (IC) device manufactured according to the method described above. This IC device includes a first die having multiple connection pads on a first active side routed to the corresponding contacts on a second side of the first conductive substrate. Some or all of the ground plane contacts on the second side of the substrate are electrically connected to the heat sink attached to the second side of the molded IC chip.

BRIEF DESCRIPTION OF DRAWINGS

[0016] The invention will be better understood with reference to the drawings, in which:

Figure 1A to 1F are sectioned drawings of a prior art IC devices having a wafer level package configuration and connected to a substrate using solder bumps ;

Figure 2 is a sectioned drawing of the present invention method, showing a first side one (2) and second side (6) of the conductive substrate (8) ;

5 Figure 3 is a sectioned drawing of the present invention, showing patterned routing trace circuitry (13) that is partially etched on the first side (2) of the conductive substrate (8) ;

10 Figure 4 is a sectioned drawing of the present invention method, showing a flip chip (15) attached to the routing trace circuitry (13) on the first side (2) of the conductive substrate (8) ;

Figure 5 is a sectioned drawing of the present invention method, after fully encapsulating (17) the first side (2) of the substrate (8) with flip chip (15) attached to the patterned and etched routing trace circuitry (13) ;

15 Figure 6 is a sectioned drawing of the present invention method, showing exposed routing trace circuitry (19) on the second side (6) of the conductive substrate (8) ;

Figure 7 is a flipped drawing of Fig. 6 shown for easy understanding of further steps of this method of invention ;

20 Figures 8 is a sectioned drawing of the current invention method showing a completed IC device (10) with build up interconnect / insulation layers (21, 23), a solder masking layer (25), solder under bump metallurgy (27) and solder bumps (29);

Figure 9 is a sectioned drawing of a different embodiment shown with three different IC devices (A, B & C) packaged to arrive at a system in package (SIP) configuration (12) ;

25 Figure 10 is a sectioned drawing of yet another embodiment showing two different IC devices (X & Y) packaged to arrive at a stack package configuration ;

30 Figure 11 is a sectioned drawing of yet another embodiment (16) showing a through hole filled conductor (35) bridging the ground planes of the build-up levels (23) with the heat sink (37) attached on the top side of the IC chip for grounding and electrical shielding purposes ;

DETAILED DESCRIPTION

[0017] Figures 2 through 8 are drawings showing steps for manufacturing an integrated circuit (IC) device (10) according to an embodiment of the present

invention. The sequence starts in a PROVIDE AN ELECTRICALLY CONDUCTIVE SUBSTRATE (8) (Figure 2). The substrate (8) may be a four, six, eight or twelve-inch square or round in size. Multiple bond pads or connection pads that corresponds to the plurality of connection terminals of IC devices, along with routing trace circuit patterns (13) are patterned on the first side (2) of the conductive substrate (8) and partially etched (13) (Figure 3). The connection pads on the conductive substrate, having plurality of corresponding connection terminals of IC devices may preferably be processed on the conductive substrate by techniques and skills that are well known in the art of semiconductor manufacturing and not discussed in this invention method. Preferably the entire first side (2) of the conductive substrate may be fully populated with the plurality of multiple IC device connection pads and routing trace circuitry to obtain a matrix array substrate. Pre-solder bumped IC devices (15) (Figure 4) are flip chip bonded with respective bond pads on the first side (2) of the conductive substrate. The bonding of IC device to the substrate are very well known to the people skilled in the art of semiconductor assembly and not discussed here. The first side (2) of the conductive substrate (8) is fully encapsulated (17) (Figure 6) after the IC devices (15) have been attached to the substrate routing trace circuitry (13). Preferably the encapsulation method may involve a transfer molding and or an Injection molding methods using vacuum that are well known to the people skilled in the art of encapsulation techniques. The un - disturbed conductive material on the second side of the conductive substrate (6) (Figure 2) is subsequently removed by chemical and or mechanical processes that are well known to the people skilled in the art of semiconductor processes. Preferably the un-disturbed material on the second side (6) of the substrate (8) is removed in-order to expose the circuitry (13) that is partially etched on the first side (2) of the substrate (8);

[0018] The next step proceeds to a FORM BUILD-UP LAYERS (21 and 23) (Figure 8) on the exposed circuitry at the second side (6) of the substrate (8) to rout the interconnects and obtain a fully encapsulated chip scale package configuration (10) and function. Preferably copper may be used as a conductive trace (21) (Figure 8) material and solder mask be used for dielectric layer (23) purposes. The final passivation mask layer (25) (Figure 8) has been deposited, portions of the passivation layer (25) over the connection pads (21) are removed using conventional techniques, such as photolithography and etching, in a REMOVE PASSIVATION LAYER PORTIONS to expose the connection pads (27) (Figure 8).

[0019] The next step proceeds to a FORM TERMINALS , wherein the substrate (8) is further processed to include electrical terminals such as solder bumps (2)9 (Figure 8). Preferably, this step includes a FORM SOLDER MASK wherein the surface on the second side (6) of the substrate is coated with a layer of solder mask (25) or a third passivation layer, preferably 1 to 25 micron thick as shown in Figure 5 (8). Portions of the solder mask (25) or the third passivation layer covering the contacts (27) are next removed using any conventional technique in a REMOVE SOLDER MASK PORTIONS step to expose the contacts (27). The solder bumps (29) are then formed in a FORM SOLDER BUMPS step over the contacts (27) on the 10 second side 6 of the substrate (8) to function as terminals for the dies (15), as shown in Figure 8. The sequence finally ends in a SEPARATE DIES step not shown in the method of invention.

[0020] It should be noted that the IC device (10) produced according to the above sequence is only one possible embodiment of the present invention. IC 15 devices, such as IC device (12) shown in Figure 9, according to other embodiments can also be manufactured with some steps in the sequence . The structure of the IC device (12) produced according to a above sequence is next described. The IC device (12) includes three different functional devices (A, B & C) attached to the conductive substrate. All the three chips are interconnected by the upper routing 20 trace circuitry and connection pads on the side one of the substrate. Subsequently, side one of the substrate is fully encapsulated by molding compound or a suitable polymer / composite after the IC chips (A, B & C) are attached. The un-disturbed conductive material on the second side of the substrate is now removed and the first side circuitry exposed. Forming appropriate build-up layers on the second side of the 25 substrate to route the new interconnect bump locations and singulation of the multi-chip module (otherwise now known as System in Package - SIP) thus completes the process for this embodiment.

[0021] Another embodiment of the IC chip (14) fabrication is shown in Figure 10 where two IC devices (X & Y) fabricated using this method of invention are vertically 30 stacked using a flex substrate to further increase the functional capability of the IC chip (14). The IC chips (X & Y) of a stacked-die IC device (14) may be of the same function or of different functions. An example of a stacked-die IC device having dies of different functions includes a processor die, a memory die and a MEMS die in a stacked configuration to produce a system-in-chip (SIC) device. These stacked-die

IC devices may also be used for non-optical type of devices, such as MEMS and surface acoustic wave (SAW) devices.

[0022] Another embodiment of the IC chip (16) fabrication is shown in Figure 11 where a through conductor trace (35) is formed between the ground planes and
5 connected with the heat sink (37) on top side of the IC device 16 to provide a good electromagnetic shielding and very effective thermal management that is required for RF wireless and or high power applications.

CLAIMS

I claim:

- 5 1. A method of manufacturing an integrated circuit (IC) device comprising:
- providing a first wafer including a plurality of dies separated by separation zones, each of the plurality of dies including connection terminals on a first active side of the wafer ;
- 10 separating the IC devices along the separation zones to realize individual IC device isolated from each other ;
- providing a first conductive substrate including a plurality of package modules separated by separation lines ;
- forming a plurality of connection pads on the package modules , the plurality of connection pads corresponding to the connection terminals of the
- 15 IC device of the first wafer provided ;
- forming partially etched routers on the first conductive substrate that electrically connect the connection terminals of the IC device of the first wafer to route the connection terminals to an interior of the corresponding connection pads on the first side of the first conductive substrate ;
- 20 forming partially etched routers that electrically connect the connection pads on the first side of the first conductive substrate to the external circuitry on the second side of the first conductive substrate ;
- attaching the connection terminals on the first side of individualized IC devices to the corresponding connection pads on the first side of package
- 25 modules and conductive substrate ;
- encapsulating the first side of the first conductive substrate to embed the IC devices inside the encapsulant together with the partially etched routers ;
- removing un-etched conductive material from a second side, opposite
- 30 the first side, of the first conductive substrate to expose the routers and router terminals;
- forming contacts on the second side of the wafer, the contacts being electrically connected to the routers in the interior of the router terminals to thereby electrically connect with the connection pads on the first side of the

first substrate and connection terminals on the first side of the first IC devices;
and

separating the dies along the separation lines of the first conductive
substrate to produce individualized dies, each of which serves as an IC
5 device:

2. A method according to Claim 1, further comprising forming conductive bumps on
the connection terminals of the IC devices prior to the separation of the IC devices
from the wafer:

3. A method according to Claim 1, further comprising forming conductive pads on
10 the conductive substrate includes ;

depositing conductive material at the plurality of connection pad
locations on the conductive substrate by electro-less plating, electrolytic
plating, evaporation methods, sputter process, CVD deposition methods,
solder printing and reflow methods, wire bonding studs, methods associated
15 with conductive polymers, anisotropic conductive films and conductive pastes
and NANO conductive materials and films.

forming a resist film on the conductive substrate to define the
connection pad locations prior to the deposition of conductive material ;
removing portions of the resist film layers from the first side of the
20 substrate to expose the conductive substrate for making the connection pads
on the substrate ;

4. A method according to Claim 1, further comprising forming routing traces and
terminals that are electrically connected to the connection pads on the first side of the
substrate:

25 5. A method according to Claim 4, wherein forming routing traces and terminals
includes:

depositing resist material on the first side of the substrate followed by
UV exposure and resist development to define the routing traces that are routed from
the connection pads to the routing terminals;

30 partially removing portions of the exposed conductive substrate
material from the first side of the substrate to form routing traces;

removing the resist material from the conductive routing traces and
conduction pads;

6. A method according to Claim 4, wherein forming routing traces and terminals includes:

depositing resist material on the first side of the substrate followed by UV exposure and resist development to define the routing traces that are routed from the connection pads to the routing terminals ;
depositing conductive materials in the defined resist routing traces ;
removing resist material that is present on the first side of the first conductive substrate;

7. A method according to Claim 4, wherein forming routing traces and terminals includes:

depositing conductive material on the first side of the substrate ;
depositing resist material followed by UV exposure and resist development to define the routing traces that are routed from the connection pads to the routing terminals ;
partially removing unwanted conductive materials adjacent to the defined resist routing traces ;
removing resist material on the first side of the first conductive substrate;

8. A method according to Claim 1, further comprising attaching an IC device, the plurality of bumped connection terminals to the connection pads on the first side of the first conductive substrate:

9. A method according to Claim 8, wherein attaching an IC device to the plurality of connection pads on the first side of the first conductive substrate includes

applying solder flux on the conductive substrate and or conductive bumps of the IC device ;

aligning the plurality of connection terminals of the IC device with the corresponding connection pads of the conductive substrate ;

reflowing the conductive substrate along with the IC devices to complete the attachment process;

10. A method according to Claim 8, wherein attaching an IC device to the plurality of connection pads on the first side of the first conductive substrate also includes:

applying anisotropic conductive films and or paste on the first side of the first conductive substrate connection pads ;

aligning the plurality of connection terminals of the IC device with the corresponding connection pads of the conductive substrate ;

applying heat and force in order to attach the IC device to the conductive substrate connection pads ;

- 5 11. A method according to Claim 8, wherein attaching an IC device to the plurality of connection pads on the first side of the first conductive substrate also includes:

applying polymer conductive adhesive on the first side of the first conductive substrate connection pads;

- 10 aligning the plurality of connection terminals of the IC device with the corresponding connection pads of the conductive substrate;

curing the attached device / substrate in order to electrically attach the IC device to the conductive substrate connection pads;

12. A method according to Claim 1, further comprising providing encapsulation
15 on the first side of the first substrate along with the attached IC device in order to fully enclose the IC device;

13. A method according to Claim 12, wherein providing encapsulation on the first side of the first conductive substrate includes :

- 20 transfer molding of the first side of the first conductive substrate with thermo set compound that is attached with the IC device; and or

injection molding of the first side of the first conductive substrate that is attached with the IC device ; and or

mold compound printing and curing on the first side of the first conductive substrate that is attached with the IC device ;

- 25 14. A method according to Claim 1, further comprising removing the conductive material from the second side of the first conductive substrate to expose the routing traces, routing terminals and molded surface on the first side of the first conductive substrate.

15. A method according to Claim 14, wherein removing material from the
30 second side of the first conductive substrate includes wet chemical etching, mechanical aberration, dry chemical etching, sand blasting, water blasting, laser etching etc.

16. A method according to Claim 1, further comprising re-routing of the connection pads that are routed to the routing terminals on the first side of the first conductive substrate to the new interconnect pads on the second side of the conductive substrate in order to interconnect with the external printed circuit board ;
- 5 17. A method according to Claim 16, wherein re-routing of the connection pads that are routed to the routing terminals on the first side of the conductive substrate includes :
- 10 depositing organic photo sensitive passivation coating and or film on the exposed routing traces on the second side of the first conductive substrate ;
 - opening the routing terminals by photolithographic process on the organic passivation ;
 - 15 depositing a layer of conductive metal coating and or film over the organic passivation ;
 - defining the routing traces and interconnection pads on the second side of the first conductive substrate, over the organic passivation and patterning the same using photolithographic process ;
 - 20 depositing another layer of photo sensitive organic passivation layer over the re-routed conductive traces ;
 - opening the interconnection pad via in the organic passivation ;
18. A method according to claim 17, wherein the photo sensitive organic film may include solder mask dry film and or spin-on non conductive polymer materials ;
- 25 19. A method according to claim 17, wherein the conductive metal coating may include aluminium, copper, nickel, palladium, tin, gold, and or any other good electrical conductors ;
20. A method according to claim 17, wherein the deposition methods of passivation films may include spin coating ; lamination ; vapour deposition ;
- 30 electrolytic deposition ;
21. A method according to claim 17, wherein the deposition methods of conductive films may include electro-less plating ; electrolytic plating ; sputtering ; e-beam evaporation ; screen printing ; lamination ;

22. A method according to Claim 1, further comprising providing under bump metallurgy at the exposed interconnection pad via in the organic passivation layer on the second side of the first conductive substrate in order to wet and join to the solder materials ;
- 5 23. A method according to claim 22, wherein providing under bump metallurgy at the exposed interconnection pads may include electro less plating of nickel and gold ; electro less plating of copper and gold ; silver conductive bumps ; gold conductive bumps ; conductive polymer bumps ;
24. A method according to claim 1, further comprising providing solder bumping
10 at the under bump metallurgy of the second side of the first conductive substrate ;
25. A method according to claim 24, wherein providing solder bumping may include stencil screen printing of solder alloys and reflow ;
26. A method according to claim 24, wherein providing solder bumping may include electroplating of solder alloys and reflow ;
- 15 27. A method according to claim 24, wherein providing solder bumping may include stencil screen printing of solder alloy balls and reflow ;
28. A method according to claims 25, 26 & 27 wherein solder alloys used for solder bumping may include eutectic solders (eg. SnPb / AuSn / SnSb etc.) and or high lead solders (eg. (90Pb10Sn / 95Pb5Sn etc.), and or lead free solders
20 (eg. SnAgCu / SnSb / SnAgBiCu etc.).
29. A method according to claim 1, wherein the solder bumps may include bump sizes ranging from as small as 30 micrometers to 875 micrometers in bump diameter.
30. A method according to claim 1, wherein the solder bumps may include bump
25 sizes ranging from as small as 20 micrometer to 875 micrometers in bump height;
31. A method according to claim 1, where in separating the dies along the separation lines of the substrate my include standard wafer dicing process ;
32. A method according to claim 1, where in separating the dies along the separation lines of the substrate my include laser dicing / cutting process ;
- 30 33. A method according to claim 1, where in separating the dies along the separation lines of the substrate my include die shearing process ;
34. A method of manufacturing an integrated circuit (IC) device comprising:

providing a first wafer including a plurality of dies separated by separation zones, each of the plurality of dies including connection terminals on a first active side of the wafer ;

5 separating the IC devices along the separation zones to realize individual IC device isolated from each other ;

providing a conductive substrate including a plurality of package modules separated by separation lines ;

10 forming a plurality of connection pads on the package modules , the plurality of connection pads corresponding to the connection terminals of the IC device of the wafer provided ;

forming partially etched routers on the conductive substrate that electrically connect the connection terminals of the IC device of the first wafer to route the connection terminals to an interior of the corresponding connection pads on the first side of the conductive substrate ;

15 forming partially etched routers that electrically connect the connection pads on the first side of the conductive substrate to the external circuitry on the second side of the conductive substrate ;

20 attaching the connection terminals on the first side of individualized IC devices to the corresponding connection pads on the first side of package modules and conductive substrate ;

encapsulating the first side of the conductive substrate to embed the IC devices inside the encapsulant together with the partially etched routers ;

25 removing un-etched conductive material from a second side, opposite the first side, of the conductive substrate to expose the routers and router terminals ;

30 forming contacts on the second side of the wafer, the contacts being electrically connected to the routers in the interior of the router terminals to thereby electrically connect with the connection pads on the first side of the first substrate and connection terminals on the first side of the IC devices ; and

separating the dies along the separation lines of the conductive substrate to produce individualized dies, each of which serves as an IC device ;

35. A method according to claim 34, wherein the IC device package may include two and or more IC devices to be interconnected and processed on a single substrate module simultaneously;
36. A method according to claim 34, wherein the conductive substrate may be processed with plurality of terminal connection pads for two and or more IC devices in a single module referred to as MCM tile ;
37. A method according to claim 34, wherein the said two and or more IC devices may be interconnected using the routers on the first side of the conductive substrate prior to the IC chip attachment process ;
38. A method according to claim 34, where in the said IC devices may be from the same and or different functional wafers ;
39. A method according to claim 1, wherein the partially etched conductive routers may vary in dimensions depending on power, ground and signal input / output connections ;
40. A method according to claim 1, wherein the IC device / s may be as thin as 30 micrometers in thickness ;
41. A method of manufacturing an integrated circuit (IC) device comprising:
providing a first wafer including a plurality of dies separated by separation zones, each of the plurality of dies including connection terminals on a first active side of the wafer ;
separating the IC devices along the separation zones to realize individual IC device isolated from each other ;
providing a conductive substrate including a plurality of package modules separated by separation lines ;
forming a plurality of connection pads on the package modules , the plurality of connection pads corresponding to the connection terminals of the IC device of the wafer provided ;
forming partially etched routers on the conductive substrate that electrically connect the connection terminals of the IC device of the first wafer to route the connection terminals to an interior of the corresponding connection pads on the first side of the conductive substrate ;
forming partially etched routers that electrically connect the connection pads on the first side of the conductive substrate to the external circuitry on the second side of the conductive substrate ;

attaching the connection terminals on the first side of individualized IC devices to the corresponding connection pads on the first side of package modules and conductive substrate ;

5 encapsulating the first side of the conductive substrate to embed the IC devices inside the encapsulant together with the partially etched routers ; removing un-etched conductive material from a second side, opposite the first side, of the conductive substrate to expose the routers and router terminals ;

10 forming contacts on the second side of the wafer, the contacts being electrically connected to the routers in the interior of the router terminals to thereby electrically connect with the connection pads on the first side of the first substrate and connection terminals on the first side of the IC devices ; and

15 separating the dies along the separation lines of the conductive substrate to produce individualized dies, each of which serves as an IC device ;

42. A method according to claim 41, wherein the encapsulation tool may be provided with a through hole on at least one side of the IC device ;

20 43. A method according to claim 42, wherein the through holes on the encapsulated IC device may be partially and or fully filled with electrically and thermally conductive material ;

44. A method according to claim 43, wherein the conductive material that is in the mold through hole may be interconnected with the ground plane of the IC device that is routed on the second side of the conductive substrate ;

25 45. A method according to claim 41, wherein the exposed top side of the molded IC device to include a conductive material ;

46. A method according to claim 45, wherein the conductive material on the exposed top side of the molded IC device may be deposited using electroplating method ;

30 47. A method according to claim 45, wherein the conductive material on the exposed top side of the molded IC device may be deposited using electro-less plating method ;

48. A method according to claim 45, wherein the conductive material on the exposed top side of the molded IC device may be deposited using sputter process method ;
49. A method according to claim 45, wherein the conductive material on the exposed top side of the molded IC device may be deposited using conductive paste printing method ;
50. A method according to claim 45, wherein the conductive material on the exposed top side of the molded IC device may be deposited using lamination method ;
51. A method according to claim 45, wherein the conductive material on the exposed top side of the molded IC device may be deposited using a thermal plate and thermal adhesive attachment method ;
52. A method according to claims 46 thru 51, wherein the conductive material on the top side of the molded IC device may be joined to the through hole conductive material of the molded IC device ;
53. A method according to claim 52, wherein the conductive material the top side of the molded IC device to act as a good thermal conductor for the IC device;
54. A method according to claim 52, wherein the conductive material the top side of the molded IC device to act as a good electromagnetic shielding of the IC device ;
55. A method of manufacturing an integrated circuit (IC) device comprising :
providing a first wafer including a plurality of dies separated by separation zones, each of the plurality of dies including connection terminals on a first active side of the wafer ;
separating the IC devices along the separation zones to realize individual IC device isolated from each other ;
providing a conductive substrate including a plurality of package modules separated by separation lines ;
forming a plurality of connection pads on the package modules , the plurality of connection pads corresponding to the connection terminals of the IC device of the wafer provided ;
forming partially etched routers on the conductive substrate that electrically connect the connection terminals of the IC device of the first wafer

to route the connection terminals to an interior of the corresponding connection pads on the first side of the conductive substrate ;

forming partially etched routers that electrically connect the connection pads on the first side of the conductive substrate to the external circuitry on the second side of the conductive substrate;

attaching the connection terminals on the first side of individualized IC devices to the corresponding connection pads on the first side of package modules and conductive substrate ;

encapsulating the first side of the conductive substrate to embed the IC devices inside the encapsulant together with the partially etched routers ;

removing un-etched conductive material from a second side, opposite the first side, of the conductive substrate to expose the routers and router terminals ;

forming contacts on the second side of the wafer, the contacts being electrically connected to the routers in the interior of the router terminals to thereby electrically connect with the connection pads on the first side of the first substrate and connection terminals on the first side of the IC devices ;

and
separating the dies along the separation lines of the conductive substrate to produce individualized dies, each of which serves as an IC device ;

forming electrical connection terminals on 1st and 2nd side of the an intermediate flexible printed circuit board to accept two or more IC devices for stack configuration ;

assembling the individualized IC devices on either side of the intermediate flexible printed circuit board to form a stack package ;

56. A method according to claim 55, wherein the IC device may include an intermediate circuit board to form a stack package to increase the functional capability of the IC device :

57. A method according to claim 56, wherein the intermediate circuit board may be of flexible and or a rigid type ;

58. A method according to claim 56, wherein the intermediate circuit board may accept the IC devices on both sides to form a stack device ;
59. A method according to claim 56, wherein the intermediate circuit board may be made from plastic and or ceramic and or glass and or silicon substrate ;
- 5 60. A method according to claim 56, where in the intermediate circuit board may include connection routers and terminals by plating and etching method ;
61. A method according to claim 56, where in the intermediate circuit board may include connection routers and terminals by conductive paste printing method ;