

ACCESS CONTROL METHOD AND RELATED PRODUCT

5

TECHNICAL FIELD

The disclosure relates to the technical field of communications, and in particular to an access control method and a related product.

10

BACKGROUND

In a wireless communication system, a terminal needs to establish a connection with a network, which is commonly referred to as a random access process. In a Long Term Evolution (LTE) system, the following situations usually require the random access process: a wireless link is established in an initial access of a terminal (switched from a Radio Resource Control (RRC) idle state RRC_IDLE to a connected state RRC_CONNECTED); a link is re-established after the wireless link is interrupted; the terminal needs to establish uplink synchronization with a target cell during switching; when the terminal is in the connected state and the terminal is not uplink-synchronized, uplink synchronization is established when uplink or downlink data arrives; user location is performed based on uplink measurement; and when a dedicated scheduling request resource is not allocated to a Physical Uplink Control Channel (PUCCH), a scheduling request is performed.

In LTE, the random access process is divided into a contention-based random access process and a non-contention-based random access process. The contention-based random access process usually consists of the following operations: a terminal randomly selects a random access preamble sequence in a random access preamble sequence set, and transmits the selected random access preamble sequence on a random access resource (Physical Random Access Channel (PRACH)) pre-specified by a base station eNB; the terminal receives a Random Access Response (RAR) message issued by the base station on a Physical Downlink Shared Channel (PDSCH); the terminal needs to transmit, according to a Cell-Radio Network Temporary Identity (C-RNTI) included in the RAR message, a random access process message including

an identity of the terminal in the present cell to the eNB on a Physical Uplink Shared Channel (PUSCH) specified in the RAR message, for contention resolution; and moreover, the terminal needs to receive a contention resolution message transmitted by the eNB, thereby completing the random access process. For the non-contention-

5 based random access process, the terminal uses a random access resource pre-specified by the base station to transmit a random access preamble sequence pre-specified by the base station; and the terminal determines, according to whether a RAR message corresponding to the preamble sequence sent by the terminal is received, whether random access is successful.

10 A 5th-Generation (5G) mobile communication technology NR is a newly proposed topic in a 3rd Generation Partnership Project (3GPP) organization. With the gradual deepening of the discussion of the new generation of 5G technology, on the one hand, because a communication system is backward compatible, a new technology developed later tends to be compatible with the previously standardized

15 technology; on the other hand, because the 4th Generation (4G) mobile communication technology LTE has a large number of existing designs, it is inevitable to sacrifice a lot of flexibility of 5G in order to achieve compatibility, thereby reducing the performance. Therefore, there are currently two parallel studies in the 3GPP organization, where the discussion group without considering backward-

20 compatible technology is called 5G NR.

A 5G/NR system introduces the concept of on-demand SI, that is, a User Equipment (UE) needs to acquire some system messages (such as secondary information block SIB1) by sending uplink requests. These uplink requests may be implemented by a Random Access Channel (RACH) preamble or an MSG3 message

25 (such as a RRC connection request). The uplink request may be sent by a user in the idle state. However, different from an uplink access request in a traditional idle state, the uplink access request is initiated by an Access Stratum (AS) itself rather than a Non-Access Stratum (NAS). If an uplink request of a system message is implemented by an MSG3 message, this means that MSG1 (such as a RACH preamble) may be

30 mixed with other RACH preambles used for other purposes in the same PRACH resource, this means that it is necessary to perform access control on a RACH process used as a system message request.

SUMMARY

Embodiments of the disclosure provide an access control method and a related
5 product, which are intended to reduce reservation overheads of access category
information of a NAS, reduce signaling overheads between the NAS and AS, and
improve the access control efficiency of a UE in an NR system.

According to a first aspect, an embodiment of the disclosure provides an
access control method, which may include:

10 a UE acquires access category information for uplink access, the access
category information at least including first access category information
independently defined by an AS entity; and

the UE initiates uplink access according to the access category information.

According to a second aspect, an embodiment of the disclosure provides an
15 access control method, which may include:

a base station receives access category information transmitted by a UE, the
access category information being transmitted after the UE performs an access barring
operation to perform uplink access according to the access category information, and
the access category information at least including first access category information
20 independently defined by an AS entity; and

the base station performs access control for the UE according to the access
category information.

According to a third aspect, an embodiment of the disclosure provides a UE,
which may include an acquiring unit and an initiating unit, where

25 the acquiring unit is configured to acquire access category information for
uplink access, the access category information at least including first access category
information independently defined by an AS entity; and

the initiating unit is configured to initiate uplink access according to the access
category information.

30 According to a fourth aspect, an embodiment of the disclosure provides a base
station, which may include a receiving unit and an access unit, where

the receiving unit is configured to receive access category information
transmitted by a UE, the access category information being transmitted after the UE

performs an access barring operation to perform uplink access according to the access category information, and the access category information at least including first access category information independently defined by an AS entity; and

the access unit is configured to perform access control for the UE according to
5 the access category information.

According to a fifth aspect, an embodiment of the disclosure provides a UE, which may include a processor, a memory, a radio frequency chip, and programs, where the programs are stored in the memory and configured to be executed by the processor, and the programs include instructions for performing operations in any
10 method according to the first aspect of the embodiment of the disclosure.

According to a sixth aspect, an embodiment of the disclosure provides a base station, which may include a processor, a memory, a communication interface, and programs, where the programs are stored in the memory and configured to be executed by the processor, and the programs include instructions for performing
15 operations in any method according to the second aspect of the embodiment of the disclosure.

According to a seventh aspect, an embodiment of the disclosure provides a computer storage medium, which may store computer programs, where the computer programs enable a computer to perform operations in any method according to the
20 first aspect or the second aspect of the embodiment of the disclosure, and the computer includes a base station and a UE.

According to an eighth aspect, an embodiment of the disclosure provides a computer program product, which may include computer programs. The computer programs may be operated to enable a computer to perform operations in any method
25 according to the first aspect or the second aspect of the embodiment of the disclosure. The computer may include a base station and a UE.

It can be seen that in the embodiments of the disclosure, a UE firstly acquires access category information for uplink access, and the UE secondly initiates uplink access according to the access category information. The acquired access category
30 information at least includes first access category information independently defined by an AS entity, that is, the access category information required by the UE is not all acquired from a NAS entity, or is not acquired from a NAS. For an uplink access request initiated by an AS itself, the mode may reduce inter-layer signaling overheads

between the NAS and the AS, and may help to improve the access control efficiency of a UE in an NR system.

5

BRIEF DESCRIPTION OF DRAWINGS

The drawings required to be used in the description of the embodiments or the prior art will be briefly described below.

10 FIG. 1 is a possible network architecture of an exemplary communication system according to an embodiment of the disclosure.

FIG. 2A is a schematic communication diagram of an access control method according to an embodiment of the disclosure.

FIG. 2B is a schematic communication diagram of another access control method according to an embodiment of the disclosure.

15 FIG. 3 is a schematic diagram of implementing data mapping transmission by a 5G NR system according to an embodiment of the disclosure.

FIG. 4 is a schematic structure diagram of a UE according to an embodiment of the disclosure.

20 FIG. 5 is a schematic structure diagram of a base station according to an embodiment of the disclosure.

FIG. 6 is a composition block diagram of a UE according to an embodiment of the disclosure.

FIG. 7 is a composition block diagram of a base station according to an embodiment of the disclosure.

25

DETAILED DESCRIPTION

30 Please refer to FIG. 1. FIG. 1 is a possible network architecture of an exemplary communication system according to an embodiment of the disclosure. The exemplary communication system may be, for example, a 5G/NR system and other such communication systems. The exemplary communication system specifically includes a UE and a base station. When the UE accesses a mobile communication network provided by the base station, a terminal may be communicatively connected

to the base station through a wireless link. The wireless link may be a single-connection mode or a dual-connection mode or a multi-connection mode. When the communication connection mode is the single-connection mode, the base station is also called a gNB base station. When the communication mode is the dual-connection mode (specifically, it may be implemented by a Carrier Aggregation CA technology or a plurality of base stations), and when the UE is connected to a plurality of base stations, the plurality of base stations may be a Master Cell Group (MCG) and a Secondary Cell Group (SCG). Between the base stations, data is hauled back through a backhaul link. The MCG and the SCG may be gNR base stations.

In the embodiments of the disclosure, terms “network” and “system” are often used alternately, but those skilled in the art may understand the meaning thereof. A terminal involved in the embodiments of the disclosure may include various handheld devices, in-vehicle devices, wearable devices and computing devices having a wireless communication function, or other processing devices connected to a wireless modem, and various forms of UEs, Mobile Stations (MS), terminal devices, and the like. For convenience of description, the devices mentioned above are collectively referred to as terminals.

The technical solutions in the embodiments of the disclosure will be described in detail below with reference to the accompanying drawings.

Please refer to FIG. 2A. FIG. 2A is a schematic flow chart of an access control method according to an embodiment of the disclosure. The method, applied to a 5G/NR communication system including a UE and a base station, includes the following operations.

At 2A01, the UE acquires access category information for uplink access. The access category information at least includes first access category information independently defined by an AS entity.

At 2A02, the UE initiates uplink access according to the access category information.

It can be seen that in the embodiments of the disclosure, a UE firstly acquires access category information for uplink access, and the UE secondly initiates uplink access according to the access category information. The acquired access category information at least includes first access category information independently defined by an AS entity. That is, the access category information needed by the UE is not all

acquired from a NAS entity, or is not acquired from a NAS. For an uplink access request initiated by an AS itself, the mode may reduce inter-layer signaling overheads between the NAS and the AS, and may help to improve the access control efficiency of a UE in an NR system.

5 In a possible example, the operation that the UE initiates uplink access according to the access category information includes: the UE performs an access barring operation according to the access category information to perform uplink access.

10 In a process of acquiring, by the UE, whether to access a current system according to an access category and its own access class, it is also necessary to combine some parameters for access control broadcast by the system.

 It is apparent that in the present example, for the case where the UE applies for system information, since the UE only appeals to obtain the system information, it is not necessary to establish an RRC connection with a network side device, and the UE
15 only needs to perform access control. It is beneficial to improve the processing efficiency of a UE to acquire system information.

 In a possible example, the UE initiates uplink access according to the access category information includes the following operations. The UE performs an access barring operation according to the access category information to initiate uplink
20 access. The UE transmits the access category information. The access category information is used for the base station to perform uplink access control for the UE.

 The UE may transmit the access category to the network side device in MSG3, that is, an RRC connection establishment request.

 It is apparent that in the present example, for the case where the UE applies for
25 establishing an RRC connection, the network side device needs to further control an uplink access request (that is, the transmitted access category) of the UE. Therefore, the user needs to further transmit the access category to a network, thereby achieving a rapid establishment of the RRC connection.

 In the above possible example, the access barring operation includes at least
30 one of the following operations: Access Category Prohibited (ACB), Extended Access Prohibited (EAB), Reverse Service Specific Access Control (SSAC), or Application Specific Congestion Control for Data Communication (ACDC).

 In a possible example, the UE acquires access category information for uplink

access includes the following operations. The UE acquires the first access category information independently defined by the AS entity, and determines the first access category information as access category information for uplink access.

5 When the uplink request process is triggered by the AS, the above access category may be self-determined by the AS.

It is apparent that in the present example, for the case where the UE applies for system information, since the UE only appeals to obtain the system information, it is not necessary to establish an RRC connection with a network side device, and the UE only needs to perform access control. It is beneficial to improve the processing efficiency of a UE to acquire system information.

10

In a possible example, the UE acquires access category information for uplink access includes the following operations. The UE acquires first access category information independently defined by the AS entity, and acquires second access category information defined by a NAS; and the UE determines access category information for uplink access according to the first access category information and the second access category information.

15

When the uplink request process is triggered by the AS, the access category may be self-determined by the AS. However, the uplink request process triggered by the NAS may be triggered at the same time. In this case, both need to be considered at the same time.

20

It is apparent that in the present example, for the case where the UE applies for system information, since the UE only appeals to obtain the system information, it is not necessary to establish an RRC connection with a network side device, and the UE only needs to perform access control. It is beneficial to improve the processing efficiency of a UE to acquire system information. For the case where the UE applies for establishing an RRC connection, the network side device needs to further control an uplink access request (that is, the transmitted access category) of the UE. Therefore, the user needs to further send the access category to a network, thereby achieving a rapid establishment of the RRC connection.

25

30 In a possible example, the access category information includes: a call type, or the call type and an RRC establishment cause.

Consistent with FIG. 2A, FIG. 2B is a schematic flow chart of an access control method according to an embodiment of the disclosure. The method, applied to

a 5G/NR communication system including a UE and a base station, includes the following operations.

At S2B01, the UE acquires access category information for uplink access. The access category information at least includes first access category information
5 independently defined by an AS entity.

At S2B02, the UE performs an access barring operation according to the access category information to initiate uplink access.

At S2B03, the UE transmits the access category information. The access category information is used for the base station to perform uplink access control for
10 the UE.

At S2B04, the base station receives access category information transmitted by the UE. The access category information being transmitted after the UE performs an access barring operation to perform uplink access according to the access category information, and the access category information at least includes first access category
15 information independently defined by an AS entity.

At S2B05, the base station performs access control for the UE according to the access category information.

It can be seen that in the embodiments of the disclosure, a UE firstly acquires access category information for uplink access, performs an access barring operation
20 according to the access category information to initiate uplink access, and transmits the access category information. A base station receives the access category information transmitted by the UE and performs access control for the UE according to the access category information. The acquired access category information at least includes first access category information independently defined by an AS entity, that
25 is, the access category information required by the UE is not all acquired from a NAS entity, or is not acquired from a NAS. For an uplink access request initiated by an AS itself, the mode may reduce inter-layer signaling overheads between the NAS and the AS, and may help to improve the access control efficiency of a UE in an NR system.

In a possible example, the access barring operation includes at least one of the
30 following operations: Access Category Prohibited (ACB), Extended Access Prohibited (EAB), Reverse Service Specific Access Control (SSAC), and Application Specific Congestion Control for Data Communication (ACDC).

In a possible example, the access category information includes: a call type, or

the call type and an RRC establishment cause.

The embodiments of the disclosure are specifically described below in conjunction with specific application scenarios.

As shown in FIG. 3, it is assumed that a UE is a smart phone, a base station is
5 a gNB in a 5G/NR system, and access category information independently defined by
an AS includes a call type and an RRC establishment cause. The access control
method disclosed in the embodiment of the disclosure includes the following
operations.

At S301, the smart phone acquires a call type and an RRC establishment cause,
10 independently defined by an AS, for uplink access.

At S302, the smart phone performs an access barring operation according to
the call type to perform uplink access.

At S303, the smart phone transmits the RRC establishment cause to the base
station.

15 At S304, the base station receives the RRC establishment cause transmitted by
the smart phone.

At S305, the base station performs access control for the smart phone
according to the RRC establishment cause.

It is apparent that in the present scenario example, since the call type and the
20 RRC establishment cause for uplink access are independently defined by the AS, the
smart phone does not need to perform signaling interaction from the NAS to acquire
the above information. For an uplink access request initiated by an AS itself, the mode
may reduce inter-layer signaling overheads between the NAS and the AS, and may
help to improve the access control efficiency of a UE in an NR system.

25 Consistent with the embodiment shown in FIG. 2A, please refer to FIG. 4. FIG.
4 is a schematic structure diagram of a UE according to an embodiment of the
disclosure. As shown in the figure, the UE includes a processor, a memory, a radio
frequency chip, and programs, where the programs are stored in the memory and
configured to be executed by the processor, and the programs include an instruction
30 for performing the following operations.

Acquiring the access category information for the uplink access, the access
category information at least including first access category information
independently defined by an AS entity; and initiating uplink access according to the

access category information.

It can be seen that in the embodiments of the disclosure, a UE firstly acquires access category information for uplink access, and the UE secondly initiates uplink access according to the access category information. The acquired access category
5 information at least includes first access category information independently defined by an AS entity, that is, the access category information required by the UE is not all acquired from a NAS entity, or is not acquired from a NAS. For an uplink access request initiated by an AS itself, the mode may reduce inter-layer signaling overheads between the NAS and the AS, and may help to improve the access control efficiency
10 of a UE in an NR system.

In a possible example, in terms of initiating uplink access according to the access category information, the instructions in the programs are specifically used for performing the following operation: performing an access barring operation according to the access category information to perform uplink access.

15 In a possible example, in terms of initiating uplink access according to the access category information, the instructions in the programs are specifically used for performing the following operations: performing an access barring operation according to the access category information to initiate uplink access; and transmitting the access category information. The access category information is used
20 for a base station to perform uplink access control for the UE.

In a possible example, the access barring operation includes at least one of the following operations: ACB, EAB, SSAC, and ACDC.

In a possible example, in terms of acquiring access category information for uplink access, the instruction in the program is specifically used for performing the
25 following operations: acquiring first access category information independently defined by the AS entity, and determining the first access category information as access category information for uplink access.

In a possible example, in terms of acquiring access category information for uplink access, the instructions in the programs are specifically used for performing the
30 following operations: acquiring first access category information independently defined by the AS entity, and acquiring second access category information defined by a NAS; and determining access category information for uplink access according to the first access category information and the second access category information.

In a possible example, the access category information includes: a call type, or the call type and an RRC establishment cause.

Consistent with the embodiment shown in FIG. 2B, please refer to FIG. 5. FIG. 5 is a schematic structure diagram of a base station according to an embodiment of the disclosure. As shown in the figure, the base station includes a processor, a memory, a communication interface, and programs, where the programs are stored in the memory and configured to be executed by the processor, and the programs include instructions for performing the following operations.

Receiving access category information transmitted by a UE. The access category information is transmitted after the UE performs an access barring operation to perform uplink access according to the access category information. The access category information at least includes first access category information independently defined by an AS entity. Performing, according to the access category information, access control for the UE.

It can be seen that in the embodiments of the disclosure, a UE firstly acquires access category information for uplink access, and the UE secondly initiates uplink access according to the access category information. The acquired access category information at least includes first access category information independently defined by an AS entity, that is, the access category information required by the UE is not all acquired from a NAS entity, or is not acquired from a NAS. For an uplink access request initiated by an AS itself, the mode may reduce inter-layer signaling overheads between the NAS and the AS, and may help to improve the access control efficiency of a UE in an NR system.

In a possible example, the access barring operation includes at least one of the following operations: ACB, EAB, SSAC, and ACDC.

In a possible example, the access category information includes: a call type, or the call type and an RRC establishment cause.

The solution of the embodiments of the disclosure is introduced above mainly from the perspective of interaction between network elements. It will be appreciated that the UE and the base station include corresponding hardware structures and/or software modules for performing the respective functions in order to implement the above functions. Those skilled in the art may easily realize that the units and algorithm operations of each example described in combination with the embodiments

disclosed in the disclosure may be implemented by hardware or a combination of hardware and computer software in the disclosure. Whether a certain function is executed by the hardware or in a manner of driving the hardware by the computer software depends on specific applications and design constraints of the technical solutions. Professionals may implement the described functions for each specific application by use of different methods, but such implementation shall fall within the scope of the disclosure.

According to the embodiments of the disclosure, functional units of the UE and the base station may be divided according to the above method examples. For example, each functional unit may be divided correspondingly to each function and two or more than two functions may also be integrated into a processing unit. The integrated unit may be implemented in the form of hardware and may also be implemented in the form of a software program module. It is to be noted that division of the units in the embodiments of the disclosure is schematic and only logical function division and another division manner may be adopted during practical implementation.

Under the condition of adopting the integrated unit, FIG. 6 is a composition block diagram of a possible functional unit of a UE according to an embodiment of the disclosure. The UE is applied to the above UE of the above embodiment. The UE 600 includes: an acquiring unit 601 and an initiating unit 602.

The acquiring unit 601 is configured to acquire access category information for uplink access. The access category information at least includes first access category information independently defined by an AS entity.

The initiating unit 602 is configured to initiate uplink access according to the access category information.

In a possible example, in terms of initiating uplink access according to the access category information, the initiating unit 602 is specifically configured to perform an access barring operation according to the access category information to perform uplink access.

In a possible example, in terms of initiating uplink access according to the access category information, the initiating unit 602 is specifically configured to: perform an access barring operation according to the access category information to initiate uplink access; and transmit the access category information. The access

category information is used for a base station to perform uplink access control for the UE.

In a possible example, the access barring operation includes at least one of the following operations: ACB, EAB, SSAC, and ACDC.

5 In a possible example, in terms of acquiring access category information for uplink access, the acquiring unit 601 is specifically configured to: acquire first access category information independently defined by the AS entity, and determine the first access category information as access category information for uplink access.

10 In a possible example, in terms of acquiring access category information for uplink access, the acquiring unit 601 is independently configured to: acquire first access category information separately defined by the AS entity, and acquire second access category information defined by a NAS; and determine access category information for uplink access according to the first access category information and the second access category information.

15 In a possible example, the access category information includes: a call type, or the call type and an RRC establishment cause.

The acquiring unit 601 may be a processor, and the initiating unit 602 may be a radio frequency chip or the like.

20 When the acquiring unit 601 is a processor and the initiating unit 602 is a radio frequency chip, the UE involved in the embodiment of the disclosure may be the UE shown in FIG. 4.

25 Under the condition of adopting the integrated unit, FIG. 7 is a composition block diagram of a possible functional unit of a base station according to an embodiment of the disclosure. The base station is applied to a base station. The base station 700 includes: a receiving unit 701 and an access control unit 702.

30 The receiving unit 701 is configured to receive access category information transmitted by a UE. The access category information is transmitted after the UE performs an access barring operation to perform uplink access according to the access category information. The access category information at least includes first access category information separately defined by an AS entity.

The access control unit 702 is configured to perform access control for the UE according to the access category information.

In a possible example, the access barring operation includes at least one of the

following operations: ACB, EAB, SSAC, and ACDC.

In a possible example, the access category information includes: a call type, or the call type and an RRC establishment cause.

The receiving unit 701 may be a communication interface, and the access
5 control unit 702 may be a processor.

When the receiving unit 701 is a communication interface and the access control unit 702 is a processor, the base station involved in the embodiment of the disclosure may be the base station shown in FIG. 5.

An embodiment of the disclosure also provides a computer storage medium,
10 which stores computer programs, where the computer programs enable a computer to perform any of the above operations in the embodiment of the disclosure, and the computer includes a base station and a UE.

An embodiment of the disclosure also provides a computer program product, which includes computer programs. The computer programs may be operated to
15 enable a computer to perform any of the above operations in the embodiment of the disclosure. The computer includes a base station and a UE.

The operations of the method or algorithm described in the embodiments of the disclosure may be implemented in a hardware manner, or may be implemented by a processor executing a software instruction. The software instruction may be
20 composed of corresponding software modules, which may be stored in a Random Access Memory (RAM), a flash memory, a Read Only Memory (ROM), an Erasable Programmable ROM (EPROM), an Electrically EPROM (EEPROM), a register, a hard disk, a mobile hard disk, a Compact Disk ROM (CD-ROM) or any other forms of storage medium known in the art. An exemplary storage medium is coupled to the
25 processor to enable the processor to read information from, and write information to, the storage medium. Of course, the storage medium may also be a component of the processor. The processor and the storage medium may be located in an ASIC. Additionally, the ASIC may be located in an access network device, a target network device, or a core network device. Of course, the processor and the storage medium
30 may also exist, as discrete components, in the access network device, the target network device or the core network device.

Those skilled in the art should realize that in one or more of the above examples, the functions described in the embodiments of the disclosure may be

implemented entirely or partially in hardware, software, firmware, or any combination thereof. When implemented in software, it may be implemented entirely or partially in the form of a computer program product. The computer program product includes one or more computer instructions. When the computer program instructions are loaded and executed on the computer, the flows or functions according to the embodiments of the disclosure are generated entirely or partially. The computer may be a general purpose computer, a dedicated computer, a computer network or another programmable device. The computer instructions may be stored in a computer storage medium or transmitted from one computer storage medium to another computer storage medium. For example, the computer instructions may be borne and transmitted from one website, computer, server or data center to another website, computer, server or data center in a wired (for example, coaxial cable, optical fiber and Digital Subscriber Line (DSL) or wireless (for example, infrared, wireless and microwave) manner. The computer storage medium may be any available medium accessible for the computer or an integrated data storage device such as a server and a data center, including one or more available media. The available medium may be a magnetic medium (for example, a floppy disk, a hard disk and a magnetic tape), an optical medium (for example, a Digital Video Disc (DVD), a semiconductor medium (for example, a Solid State Disk (SSD)) or the like.

The above specific implementation manner further describes the purposes, technical solutions and beneficial effects of the embodiments of the disclosure. It will be appreciated that the above is only the specific implementation manner of the embodiments of the disclosure, and is not intended to limit the scope of protection of the embodiments of the disclosure. Any modifications, equivalent replacements, improvements and the like made on the basis of the technical solutions of the embodiments of the disclosure should be included in the scope of protection of the embodiments of the disclosure.

CLAIMS

5

1. An access control method, comprising:

acquiring, by a User Equipment (UE), access category information for uplink access, the access category information at least comprising first access category information independently defined by an Access Stratum (AS) entity; and

10

initiating, by the UE, the uplink access according to the access category information,

wherein acquiring, by the UE, the access category information for the uplink access comprises:

acquiring from the AS entity, by the UE, the first access category information independently defined by the AS entity; and

15

determining the first access category information as the access category information for the uplink access.

2. The method of claim 1, wherein initiating, by the UE, uplink access according to the access category information comprises:

20

performing, by the UE according to the access category information, an access barring operation to perform the uplink access.

3. The method of claim 1, wherein initiating, by the UE, the uplink access according to the access category information comprises:

25

performing, by the UE according to the access category information, an access barring operation to initiate the uplink access; and

transmitting, by the UE, the access category information, the access category information being used for a base station to perform uplink access control for the UE.

30

4. The method of claim 2 or 3, wherein the access barring operation comprises at least one of the following operations: Access Category Prohibited (ACB), Extended Access Prohibited (EAB), Reverse Service Specific Access Control (SSAC), or Application Specific Congestion Control for Data Communication (ACDC).

35

5. The method of any one of claims 1 to 4, wherein the access category information comprises: a call type, or both the call type and a Radio Resource Control (RRC) establishment cause.

5 6. An access control method, comprising:

receiving, by a base station, access category information transmitted by a User Equipment (UE), the access category information being transmitted after the UE performs an access barring operation to perform uplink access according to the access category information, and the access category information at least comprising first
10 access category information independently defined by an Access Stratum (AS) entity; and

performing, by the base station according to the access category information, access control for the UE, wherein the first access category information independently defined by the AS entity is acquired from the AS entity by the UE and the first access
15 category information is determined by the UE as the access category information for the uplink access.

7. The method of claim 6, wherein the access barring operation comprises at least one of the following operations: Access Category Prohibited (ACB), Extended Access
20 Prohibited (EAB), Reverse Service Specific Access Control (SSAC), or Application Specific Congestion Control for Data Communication (ACDC).

8. The method of claim 6, wherein the access category information comprises: a call type, or the call type and a Radio Resource Control (RRC) establishment cause.

25

9. A User Equipment (UE), comprising an acquiring unit and an initiating unit, wherein the acquiring unit is configured to acquire access category information for uplink access, the access category information at least comprising first access category information independently defined by an Access Stratum (AS) entity; and

30

the initiating unit is configured to initiate the uplink access according to the access category information,

in terms of acquiring access category information for uplink access, the acquiring unit is configured to: acquire, from the AS entity, first access category

information independently defined by the AS entity, and determine the first access category information as the access category information for the uplink access.

5 10. The UE of claim 9, wherein in terms of initiating the uplink access according to the access category information, the initiating unit is configured to: perform, according to the access category information, an access barring operation to perform the uplink access.

10 11. The UE of claim 9, wherein in terms of initiating uplink access according to the access category information, the initiating unit is configured to: perform, according to the access category information, an access barring operation to initiate the uplink access; and transmit the access category information, the access category information being used by a base station to perform uplink access control for the UE.

15 12. The UE of claim 10 or 11, wherein the access barring operation comprises at least one of the following operations: Access Category Prohibited (ACB), Extended Access Prohibited (EAB), Reverse Service Specific Access Control (SSAC), or Application Specific Congestion Control for Data Communication (ACDC).

20 13. The UE of any one of claims 9 to 12, wherein the access category information comprises: a call type, or both the call type and a Radio Resource Control, RRC, establishment cause.

25 14. A base station, comprising a receiving unit and an access control unit, wherein the receiving unit is configured to receive access category information transmitted by a User Equipment (UE), the access category information being transmitted after the UE performs an access barring operation to perform uplink access according to the access category information, and the access category information at least comprising first access category information independently defined by an Access
30 Stratum (AS) entity; and

the access control unit is configured to perform, according to the access category information, access control for the UE, wherein the first access category information independently defined by the AS entity is acquired from the AS entity by the UE and the first access category information is determined by the UE as the access category
35 information for the uplink access.

15. A User Equipment (UE), comprising a processor, a memory, a radio frequency chip, and programs, wherein the programs are stored in the memory and configured to be executed by the processor, the programs comprising instructions for performing the
5 following operations:

acquiring access category information for uplink access, the access category information at least comprising first access category information independently defined by an Access Stratum (AS) entity; and

10 initiating the uplink access according to the access category information,
wherein acquiring, by the UE, the access category information for the uplink access comprises:

acquiring from the AS entity, by the UE, the first access category information independently defined by the AS entity; and

15 determining the first access category information as the access category information for the uplink access.

16. A base station, comprising a processor, a memory, a communication interface, and programs, wherein the programs are stored in the memory and configured to be executed by the processor, the programs comprising instructions for performing the
20 following operations:

receiving access category information transmitted by a User Equipment (UE), the access category information being transmitted after the UE performs an access barring operation to perform uplink access according to the access category information, and the access category information at least comprising first access category
25 information independently defined by an Access Stratum (AS) entity; and

performing, according to the access category information, access control for the UE, wherein the first access category information independently defined by the AS entity is acquired from the AS entity by the UE and the first access category information is determined by the UE as the access category information for the uplink access.

30

17. A computer storage medium, storing computer programs, wherein the computer programs enable a computer to perform the method of any one of claims 1 to 8, the computer comprising a base station and a User Equipment (UE).