

# **BLOCKCHAIN TRANSACTION RECONCILIATION METHOD AND APPARATUS, AND ELECTRONIC DEVICE**

## **CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] This application claims priority to Chinese Patent Application No.  
5 201810533812.0, filed on May 29, 2018, which is hereby incorporated by reference in its entirety.

## **TECHNICAL FIELD**

[0002] One or more implementations of the present specification relate to the field of  
terminal technologies, and in particular, to a blockchain transaction reconciliation method  
10 and apparatus, and an electronic device.

## **BACKGROUND**

[0003] In related technologies, various solutions for implementing blockchain  
transactions such as asset creation and asset transfer through blockchain networks are  
proposed. When transaction operations are implemented based on the blockchain network,  
15 the transaction operations can be automatically implemented through a smart contract, and  
transaction records can be recorded in the blockchain account book without being tampered  
with, thereby eliminating mistrust between blockchain members and also solving the problem  
of interconnection between off-chain management systems of different blockchain members.

## **SUMMARY**

20 [0004] In view of this, one or more implementations of the present specification  
provide a blockchain transaction reconciliation method and apparatus, and an electronic  
device.

[0005] To achieve the previous objective, one or more implementations of the present  
specification provide the following technical solutions:

25 [0006] According to a first aspect of one or more implementations of the present  
specification, a blockchain transaction reconciliation method is proposed, including:  
obtaining, by a blockchain member, a blockchain transaction record that is selected from a  
blockchain and satisfies a specified condition; comparing, by the blockchain member, the  
blockchain transaction record with an off-chain transaction record maintained by the  
30 blockchain member; and changing, by the blockchain member, the off-chain transaction

record based on the blockchain transaction record when the off-chain transaction record is inconsistent with the blockchain transaction record.

**[0007]** According to a second aspect of one or more implementations of the present specification, a blockchain transaction reconciliation apparatus is proposed, including: a selection unit, configured to enable a blockchain member to obtain a blockchain transaction record that is selected from a blockchain and satisfies a specified condition; a comparison unit, configured to enable the blockchain member to compare the blockchain transaction record with an off-chain transaction record maintained by the blockchain member; and a changing unit, configured to enable the blockchain member to change the off-chain transaction record based on the blockchain transaction record when the off-chain transaction record is inconsistent with the blockchain transaction record.

**[0008]** According to a third aspect of one or more implementations of the present specification, an electronic device is proposed, including: a processor; and a memory, configured to store an instruction that can be executed by the processor; wherein the processor is configured to implement the method according to any one of the previous implementations.

## **BRIEF DESCRIPTION OF DRAWINGS**

**[0009]** FIG. 1 is a flowchart illustrating a blockchain transaction reconciliation method, according to an example implementation;

**[0010]** FIG. 2 is a schematic architectural diagram illustrating a blockchain network, according to an example implementation;

**[0011]** FIG. 3 is a schematic diagram illustrating setting a selection condition, according to an example implementation;

**[0012]** FIG. 4 is a schematic diagram illustrating reconciliation based on a selection result, according to an example implementation;

**[0013]** FIG. 5 is a schematic diagram illustrating entering reconciliation-related data into a blockchain, according to an example implementation;

**[0014]** FIG. 6 is a schematic structural diagram illustrating a device, according to an example implementation;

**[0015]** FIG. 7 is a block diagram illustrating a blockchain transaction reconciliation apparatus, according to an example implementation; and

**[0016]** FIG. 8 is a flowchart illustrating an example of a computer-implemented method for blockchain transaction reconciliation, according to an implementation of the present disclosure.

### **DESCRIPTION OF IMPLEMENTATIONS**

**[0017]** Example implementations are described in detail here, and examples of the example implementations are presented in the accompanying drawings. When the following description relates to the accompanying drawings, unless specified otherwise, the same numbers in different accompanying drawings represent same or similar elements. Implementations described in the following example implementations do not represent all implementations consistent with one or more implementations of the present specification. On the contrary, the implementations are only examples of apparatuses and methods that are described in the appended claims in detail and consistent with some aspects of the one or more implementations of the present specification.

**[0018]** It is worthwhile to note that in other implementations, steps of the corresponding method are not necessarily performed in the order shown and described in the present specification. In some other implementations, the method can include more or fewer steps than those described in the present specification. In addition, a single step described in the present specification can be divided into a plurality of steps for description in another implementation, and a plurality of steps described in the present specification can be combined into a single step for description in another implementation.

**[0019]** FIG. 1 is a flowchart illustrating a blockchain transaction reconciliation method, according to an example implementation. As shown in FIG. 1, the method can include the following steps.

**[0020]** Step 102: A blockchain member obtains a blockchain transaction record that is selected from a blockchain and satisfies a specified condition.

**[0021]** In an implementation, the blockchain can include several blockchain nodes, and these blockchain nodes can include a blockchain member (or referred to as a member for short) and an anchor point. The blockchain member can assume the role of the anchor point, or the anchor point can be independent of the blockchain member. To be specific, the role of the anchor point is unnecessarily assumed by the blockchain member.

**[0022]** In an implementation, the blockchain member can be a financial institution, an organization or a platform in another form that supports an asset transfer service.

Implementations are not limited in the present specification.

**[0023]** In an implementation, the anchor point is used to anchor point blockchain assets on the blockchain to off-chain assets outside the blockchain, so that the off-chain asset can be exchanged for an equivalent blockchain asset through the anchor point, and the blockchain asset can also be exchanged for an equivalent off-chain asset through the anchor point, thereby implementing one-to-one mapping between the blockchain assets and off-chain assets. For example, the blockchain member can deposit the off-chain asset at the anchor point, and obtain and hold a blockchain asset issued by the corresponding anchor point on the blockchain. In addition, blockchain members can transfer held blockchain assets to each other, and holdings of the blockchain members in blockchain assets issued by anchor points and changes of the blockchain assets can be registered in a blockchain account book of the blockchain, to manage the blockchain assets together.

**[0024]** In an implementation, the "assets" in the present specification can be in any type, such as cash, securities, and stocks; or devices, vehicles, estates, and goods.

Implementations are not limited in the present specification.

**[0025]** In an implementation, asset transfer operations occurring on the blockchain form corresponding blockchain transaction records in the blockchain account book. These blockchain transaction records can record information related to asset transfer, such as information about an asset transferor, information about an asset transferee, an asset type, a transaction amount, and a transaction time. Implementations are not limited in the present specification.

**[0026]** In an implementation, the blockchain member can connect the inside and the outside of the blockchain network through a bridge module, enabling the blockchain member to transmit a condition that is configured by a user to the inside of the blockchain network to form the specified condition for selecting a blockchain transaction record included in the blockchain account book.

**[0027]** In an implementation, because all blockchain nodes maintain a unified blockchain account book together, each blockchain member can obtain all contents recorded in the blockchain account book, to actively select a corresponding blockchain transaction record based on the specified condition, to obtain a blockchain transaction record satisfying the specified condition.

**[0028]** In an implementation, the blockchain can include a reconciliation service provider. The reconciliation service provider can include one or more specific blockchain

nodes on the blockchain, and can be used to provide a transaction record query service for the blockchain member. For example, the blockchain member can send the specified condition to the reconciliation service provider by using the bridge module, so that the reconciliation service provider can select a blockchain transaction record based on the specified condition.

5 Then the blockchain member receives the blockchain transaction record returned by the reconciliation service provider. Therefore, the blockchain member does not need to actively perform the selection operation. The reconciliation service provider can provide related services for all the blockchain members on the blockchain, and all the blockchain members can enjoy the services provided by the reconciliation service provider without separately  
10 performing the selection operation on the blockchain transaction record, so that the blockchain members can focus more on blockchain-based asset transactions.

**[0029]** In an implementation, the specified condition can include at least one of the following: a time period including a creation moment of the blockchain transaction record, a blockchain member participating in a blockchain transaction corresponding to the blockchain  
15 transaction record, and a condition that the blockchain transaction record is a normal transaction record or a refund transaction record.

**[0030]** Step 104: The blockchain member compares the blockchain transaction record with an off-chain transaction record maintained by the blockchain member.

**[0031]** In an implementation, the blockchain member can export the blockchain  
20 transaction record by using a bridge module configured between the blockchain member and the blockchain, to compare the blockchain transaction record with the off-chain transaction record off the chain. The bridge module is separately connected to a first data interface provided by the blockchain member and a second data interface provided by the blockchain. In another implementation, the blockchain member can export the blockchain transaction  
25 record in another method. Implementations are not limited in the present specification.

**[0032]** Step 106: The blockchain member changes the off-chain transaction record based on the blockchain transaction record when the off-chain transaction record is inconsistent with the blockchain transaction record.

**[0033]** In an implementation, the blockchain transaction record in the blockchain  
30 account book cannot be tampered with and can be traced, so that the blockchain transaction record registered in the blockchain account book is reliable enough and can be trusted by all the blockchain members. Therefore, the blockchain member can change the off-chain transaction record based on the blockchain transaction record, so that the off-chain

transaction record is consistent with the blockchain transaction record.

**[0034]** In an implementation, the blockchain transaction record and the off-chain transaction record can both record information about several dimensions for the same blockchain transaction record. Although there may be a difference between the blockchain transaction record and the dimensions concerned by the off-chain transaction record, and such difference may result in a difference between the content of them, their contents are still consistent and comparable.

**[0035]** In an implementation, the blockchain member can enter the specified condition and change information for the off-chain transaction record into the blockchain, to record in the blockchain account book that the specified condition and the change information cannot be tampered with and can be traced. Therefore, not only regulatory query requirements of regulatory authorities can be satisfied, but also improper changes made by unauthorized personnel to the off-chain transaction record can be determined accordingly.

**[0036]** For ease of understanding, the technical solutions in one or more implementations of the present specification are described below by using an example that a bank performs reconciliation on blockchain transfer data. FIG. 2 is a schematic architectural diagram illustrating a blockchain network, according to an example implementation. As shown in FIG. 2, bank H is used as an example. Bank H serves as a financial institution outside a blockchain, and can conduct services with individuals, enterprises, and other financial institutions. In addition, bank H can maintain a corresponding blockchain node A inside the blockchain, so that bank H can serve as a blockchain member in the blockchain network based on blockchain node A. Bank H is connected to blockchain node A by using bridge module 1 shown in FIG. 2. Through the bridge node A, both on- and off-chain data exchanges between bank H and blockchain node A can be implemented. Similarly, a reconciliation service provider can maintain a corresponding blockchain node B in the blockchain network. For example, the service provider can exchange data with blockchain node B by using bridge module 2 shown in FIG. 2. Certainly, the blockchain network can further include other nodes such as blockchain node C and blockchain node D shown in FIG. 2. Details are omitted here.

**[0037]** Bank H can obtain a blockchain transaction record that bank H is interested by using a plurality of methods.

**[0038]** For example, in an implementation, a staff of bank H can configure a corresponding selection condition for a concerned transaction, and can obtain a blockchain

account book maintained on blockchain node A by using bridge module 1. The blockchain account book is consistent with blockchain account books maintained on other blockchain nodes such as blockchain nodes B, C, and D, and each of the blockchain account books records full blockchain account book information, including blockchain transaction records corresponding to all transactions that occur in the blockchain network. Therefore, the staff of bank H can select a blockchain transaction record from the obtained blockchain account book based on the selection condition, to obtain a corresponding selection result. The selection result includes the blockchain transaction record that bank H is interested.

**[0039]** In an implementation, bank H can entrust the reconciliation service provider so that the reconciliation service provider provides bank H with a blockchain transaction record that bank H is interested. FIG. 3 is a schematic diagram illustrating setting a selection condition, according to an example implementation. As shown in FIG. 3, bank H and the reconciliation service provider can interact with each other by using bridge module 1 and bridge module 2, so that bank H can transmit the selection condition to the reconciliation service provider by using bridge module 1 and bridge module 2. In addition, the reconciliation service provider can obtain a blockchain account book maintained by blockchain node B by using bridge module 1 and bridge module 2. The blockchain account book records full blockchain account book information, including blockchain transaction records corresponding to all transactions that occur in the blockchain network. Therefore, the reconciliation service provider can select a blockchain transaction record from the obtained blockchain account book based on the selection condition set by bank H, to obtain a corresponding selection result. The selection result includes the blockchain transaction record that bank H is interested. Certainly, bank H can transmit the selection condition to blockchain node A by using bridge module 1, and blockchain node A writes the selection condition into the blockchain account book. The reconciliation service provider can read the blockchain account book from blockchain node B by using bridge module 2, to obtain the selection condition written by bank H.

**[0040]** In an implementation, bank H can establish a partnership with the reconciliation service provider off the chain, so that the reconciliation service provider can obtain the selection condition set by bank H and provide bank H with a blockchain transaction record satisfying the condition. In another implementation, bank H and the reconciliation service provider can establish a partnership in the blockchain network by using blockchain nodes A and B. For example, blockchain nodes A and B both join the same smart

contract. The smart contract can require that when a blockchain member (namely, bank H) corresponding to blockchain node A provides a selection condition for a blockchain member (namely, the reconciliation service provider) corresponding to blockchain node B, the blockchain member corresponding to blockchain node B provides a corresponding selection  
 5 result for the blockchain member corresponding to blockchain node A. The selection result includes a blockchain transaction record that satisfies the selection condition in the blockchain account book.

**[0041]** In an implementation, the selection condition can include conditions in one or more dimensions that bank H is interested, for example, include one or more of the following  
 10 dimensions: a time period including a creation moment of the blockchain transaction record, a blockchain member participating in a blockchain transaction corresponding to the blockchain transaction record, and a condition that the blockchain transaction record is a normal transaction record or a refund transaction record. Implementations are not limited in the present specification.

**[0042]** In an implementation, the operation of setting the selection condition by bank H and the selection operation performed by the reconciliation service provider based on the selection condition can be performed asynchronously. For example, after bank H sets the selection condition for the first time, the selection condition can be subsequently used to perform each selection operation without setting the selection condition each time again.  
 20 Certainly, a requirement of bank H possibly changes, and therefore bank H can update the selection condition. However, the reconciliation service provider only needs to determine a current latest selection condition based on a pre-agreed period (for example, every week, every month, and every quarter), and implement the selection operation based on the current latest selection condition.

**[0043]** In an implementation, bank H can actively initiate a selection request to the reconciliation service provider, and adds a current selection condition to the selection request. The reconciliation service provider can perform the selection operation based on the current selection condition. For example, when based on the smart contract method described above, bank H can trigger the smart contract by setting the selection condition, to initiate the  
 30 selection request to the reconciliation service provider based on the smart contract.

**[0044]** In an implementation, the reconciliation service provider can actively initiate an inquiry to bank H based on a pre-agreed period and receive a selection condition returned by bank H, so that the reconciliation service provider can perform the selection operation

based on the selection condition.

**[0045]** FIG. 4 is a schematic diagram illustrating reconciliation based on a selection result, according to an example implementation. As shown in FIG. 4, the reconciliation service provider selects, from the blockchain account book based on a selection condition provided by bank H, a blockchain transaction record satisfying the selection condition, to form a corresponding selection result. In addition, the reconciliation service provider can exchange data with bank H by using bridge module 2 and bridge module 1, to provide the selection result to bank H. Certainly, the reconciliation service provider can also transmit the selection result to blockchain node B by using bridge module 2, and blockchain node B writes the selection result into the blockchain account book. Bank H can read the blockchain account book from blockchain node A by using bridge module 1, to obtain the selection result written by the reconciliation service provider.

**[0046]** In an implementation, bank H records an off-chain transaction record, that is, a transaction maintained by bank H. Therefore, bank H can compare the off-chain transaction record with a blockchain transaction record, which is selected by bank H or provided by the reconciliation service provider, to implement reconciliation processing.

**[0047]** In an implementation, the blockchain transaction record can usually include information about all dimensions related to a transaction, and the off-chain transaction record usually includes only information about dimensions concerned by bank H. Certainly, in some cases, the blockchain transaction record can also only include information about partial dimensions. In conclusion, when the blockchain transaction record and the off-chain transaction record describe the same transaction, although the description dimensions used by them may be different, theoretically, contents recorded in the two transaction records are consistent with each other, and both records are objective descriptions of the same transaction.

**[0048]** However, various problems usually exist in the off-chain transaction record. For example, bank H possibly miss partial information in the off-chain transaction record due to various reasons, and consequently, transaction details cannot be presented completely. For another example, unauthorized personnel possibly tamper with the off-chain transaction record maintained by bank H to achieve an illegal purpose. For another example, a staff of bank H possibly inadvertently performs an erroneous operation on the off-chain transaction record, causing an error in the recorded content.

**[0049]** Based on a feature of the blockchain, the blockchain transaction record recorded in the blockchain account book cannot be tampered with and can be traced, thereby ensuring trueness and reliability of the content in the blockchain transaction record. Therefore, by comparing the blockchain transaction record with the off-chain transaction record, missing information or an error in the off-chain transaction record can be discovered based on the blockchain transaction record, so that bank H can supplement the missing information in the off-chain transaction record and correct the error based on the blockchain transaction record.

**[0050]** FIG. 5 is a schematic diagram illustrating entering reconciliation-related data into a blockchain, according to an example implementation. As shown in FIG. 5, after completing the reconciliation operation, bank H can transmit the reconciliation-related data to blockchain node A by using bridge module 1, and blockchain node A triggers an operation of writing the reconciliation-related data, so that the reconciliation-related data can be written into the blockchain account book for subsequent query and supervision by regulatory authorities.

**[0051]** In an implementation, the reconciliation-related data can include any data related to the reconciliation operation performed by bank H, for example, the selection condition set by bank H, information about a change made by bank H to the off-chain transaction record. Implementations are not limited in the present specification.

**[0052]** FIG. 6 is a schematic structural diagram illustrating a device, according to an example implementation. Referring to FIG. 6, in terms of hardware, the device includes a processor 602, an internal bus 604, a network interface 606, a memory 608, and a nonvolatile memory 610, and certainly can further include the hardware needed by other services. The processor 602 reads a corresponding computer program from the nonvolatile memory 610 into the memory 608 and then runs the corresponding computer program, so as to logically form a blockchain transaction reconciliation apparatus. Certainly, in addition to software implementation, one or more implementations of the present specification do not exclude another implementation, for example, a logic device or a combination of hardware and software. That is, an executive body of the following processing procedure is not limited to each logic unit, and can also be hardware or a logic device.

**[0053]** Referring to FIG. 7, in a software implementation, the blockchain transaction reconciliation apparatus can include: a selection unit 71, configured to enable a blockchain member to obtain a blockchain transaction record that is selected from a blockchain and

satisfies a specified condition; a comparison unit 72, configured to enable the blockchain member to compare the blockchain transaction record with an off-chain transaction record maintained by the blockchain member; and a changing unit 73, configured to enable the blockchain member to change the off-chain transaction record based on the blockchain transaction record when the off-chain transaction record is inconsistent with the blockchain transaction record.

**[0054]** Optionally, the selection unit 71 is specifically configured to: enable the blockchain member to send the specified condition to a reconciliation service provider of the blockchain, and enable the blockchain member to receive the blockchain transaction record returned by the reconciliation service provider.

**[0055]** Optionally, the specified condition includes at least one of the following: a time period including a creation moment of the blockchain transaction record, a blockchain member participating in a blockchain transaction corresponding to the blockchain transaction record, and a condition that the blockchain transaction record is a normal transaction record or a refund transaction record.

**[0056]** Optionally, the comparison unit 72 is specifically configured to: enable the blockchain member to export the blockchain transaction record by using a bridge module configured between the blockchain member and the blockchain, to compare the blockchain transaction record with the off-chain transaction record of the chain

**[0057]** The bridge module is separately connected to a first data interface provided by the blockchain member and a second data interface provided by the blockchain.

**[0058]** Optionally, the apparatus further includes: an entering unit 74, configured to enable the blockchain member to enter the specified condition and change information for the off-chain transaction record into the blockchain.

**[0059]** The system, apparatus, module, or unit illustrated in the previous implementations can be implemented by using a computer chip or an entity, or can be implemented by using a product having a certain function. A typical implementation device is a computer, and the computer can be a personal computer, a laptop computer, a cellular phone, a camera phone, an intelligent phone, a personal digital assistant, a media player, a navigation device, an email receiving and sending device, a game console, a tablet computer, a wearable device, or any combination of several devices in these devices.

**[0060]** In a typical configuration, the computer includes one or more processors (CPU), an input/output interface, a network interface, and a memory.

**[0061]** The memory can include a non-persistent memory, a random access memory (RAM), a nonvolatile memory, and/or another form that are in a computer readable medium, for example, a read-only memory (ROM) or a flash memory (flash RAM). The memory is an example of the computer readable medium.

5 **[0062]** The computer readable medium includes persistent, non-persistent, movable, and unmovable media that can store information by using any method or technology. The information can be a computer readable instruction, a data structure, a program module, or other data. Examples of a computer storage medium include but are not limited to a parameter random access memory (PRAM), a static random access memory (SRAM), a  
10 dynamic random access memory (DRAM), a random access memory (RAM) of another type, a read-only memory (ROM), an electrically erasable programmable read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital versatile disc (DVD) or another optical storage, a magnetic cassette tape, a magnetic disk storage, a quantum memory, a graphene-based storage medium  
15 or another magnetic storage device, or any other non-transmission medium. The computer storage medium can be used to store information that can be accessed by the computing device. Based on the definition in the present specification, the computer readable medium does not include transitory computer readable media (transitory media) such as a modulated data signal and carrier.

20 **[0063]** It is worthwhile to further note that the terms "include", "comprise", or their any other variants are intended to cover a non-exclusive inclusion, so a process, a method, a product or a device that includes a list of elements not only includes those elements but also includes other elements which are not expressly listed, or further includes elements inherent to such process, method, product or device. Without more constraints, an element preceded  
25 by "includes a ..." does not preclude the existence of additional identical elements in the process, method, product or device that includes the element.

**[0064]** Specific implementations of the present specification are described above. Other implementations fall within the scope of the appended claims. In some cases, the actions or steps described in the claims can be performed in an order different from that in the  
30 implementation and the desired results can still be achieved. In addition, the process described in the accompanying drawings does not necessarily require a particular execution order to achieve the desired results. In some implementations, multi-task processing and parallel processing can be performed or can be advantageous.

**[0065]** The terms used in one or more implementations of the present specification are merely for the purpose of describing specific implementations, and are not intended to limit the one or more implementations of the present specification. The terms "a" and "the" in a singular form used in the one or more implementations of the present specification and the  
5 appended claims are also intended to include a plural form, unless otherwise specified in the context clearly. It should be further understood that the term "and/or" used in the present specification indicates and includes any or all possible combinations of one or more associated listed items.

**[0066]** It should be understood that although terms "first", "second", "third", etc. can  
10 be used in one or more implementations of the present specification to describe various types of information, the information is not limited to the terms. These terms are only used to differentiate information of a same type. For example, without departing from the scope of the one or more implementations of the present specification, first information can also be referred to as second information, and similarly, the second information can be referred to as  
15 the first information. Depending on the context, for example, the word "if" used here can be explained as "while", "when", or "in response to determining".

**[0067]** The previous descriptions are only example implementations of one or more implementations of the present specification, but are not intended to limit the one or more implementations of the present specification. Any modification, equivalent replacement,  
20 improvement, etc. made without departing from the spirit and principle of the one or more implementations of the present specification shall fall within the protection scope of the one or more implementations of the present specification.

**[0068]** FIG. 8 is a flowchart illustrating an example of a computer-implemented method 800 for blockchain transaction reconciliation, according to an implementation of the  
25 present disclosure. For clarity of presentation, the description that follows generally describes method 800 in the context of the other figures in this description. However, it will be understood that method 800 can be performed, for example, by any system, environment, software, and hardware, or a combination of systems, environments, software, and hardware, as appropriate. In some implementations, various steps of method 800 can be run in parallel,  
30 in combination, in loops, or in any order.

**[0069]** At 802, a blockchain transaction record that is selected from a blockchain account book associated with a blockchain and satisfies a specified condition is obtained by a blockchain member. In some implementations, the blockchain account book includes a

plurality of blockchain transaction records that record information associated with asset transfer operations occurring on the blockchain. In some implementations, the blockchain includes a reconciliation service provider that provides a transaction record query service for the blockchain member.

5    **[0070]**       In some implementations, obtaining the blockchain transaction record includes sending the specified condition to the reconciliation service provider of the blockchain to enable the reconciliation service provider to select a blockchain transaction record based on the specific condition; and receiving the blockchain transaction record returned by the reconciliation service provider.

10   **[0071]**       In some implementations, the specified condition includes at least one of a moment at which the blockchain transaction record is created, a blockchain member that participates in a blockchain transaction corresponding to the blockchain transaction record, a condition indicating that the blockchain transaction record is a normal transaction record, or a condition indicating that the blockchain transaction is a refund transaction record. From 802,  
15   method 800 proceeds to 804.

**[0072]**       At 804, the blockchain transaction record is compared with an off-chain transaction record maintained by the blockchain member to obtain a comparison value indicating whether the off-chain transaction record is consistent with the blockchain transaction record.

20   **[0073]**       In some implementations, comparing the blockchain transaction record with the off-chain transaction record includes exporting the blockchain transaction record by using a bridge module that is configured between the blockchain member and the blockchain; and comparing the blockchain transaction record with the off-chain transaction record off the blockchain, where the bridge module is separately connected to a first data interface provided  
25   by the blockchain member and a second data interface provided by the blockchain. From 804, method 800 proceeds to 806.

**[0074]**       At 806, a determination is made as to whether the comparison value indicates that the off-chain transaction record is consistent with the blockchain transaction record. If it is determined that the comparison value indicates that the off-chain transaction record is  
30   inconsistent with the blockchain transaction record, method 800 proceeds to 808.

**[0075]**       At 808, the off-chain transaction record is modified based on the blockchain transaction record to make the off-chain transaction record consistent with the blockchain transaction record. In some implementations, method 800 further includes entering the

specified condition and modified information for the off-chain transaction record into the blockchain. After 808, method 800 can stop.

**[0076]** Implementations of the present application can solve technical problems in data record reconciliation. When transaction operations are implemented based on the blockchain network, the transaction operations can be automatically implemented through a smart contract, and transaction records can be recorded in the blockchain account book without being tampered with, thereby eliminating mistrust between blockchain members and solving the problem of interconnection between off-chain management systems of different blockchain members.

**[0077]** Implementations of the present disclosures provide methods and apparatuses for data record conciliation in the blockchain. For example, the described method can be used for clearing documents that are generated for blockchain members based on all transaction flow records by the end of each day. Because content of the blockchain ledger cannot be tampered with and is traceable, the transaction flow records maintained by the blockchain members can be checked and corrected according to the blockchain transaction records, improving, for example, data storage security, and, for example, reducing data storage space.

**[0078]** According to described implementations, the blockchain can include a reconciliation service provider, which can include one or more specific blockchain nodes on the blockchain and can be used to provide a transaction record query service for the blockchain member. For example, the blockchain member can send a specified condition to the reconciliation service provider by using a bridge module, so that the reconciliation service provider can select a blockchain transaction record based on the specified condition. Then the blockchain member receives the blockchain transaction record returned by the reconciliation service provider. Therefore, the blockchain member does not need to actively perform the selection operation. The reconciliation service provider can provide related services for all the blockchain members on the blockchain, and all the blockchain members can enjoy the services provided by the reconciliation service provider without separately performing the selection operation on the blockchain transaction record, so that the blockchain members can focus more on blockchain-based asset transactions.

**[0079]** Embodiments and the operations described in this specification can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification or in combinations of one or more of them. The operations can be implemented as operations performed by a data processing

apparatus on data stored on one or more computer-readable storage devices or received from other sources. A data processing apparatus, computer, or computing device may encompass apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, a system on a chip, or multiple ones, or combinations, of the foregoing. The apparatus can include special purpose logic circuitry, for example, a central processing unit (CPU), a field programmable gate array (FPGA) or an application-specific integrated circuit (ASIC). The apparatus can also include code that creates an execution environment for the computer program in question, for example, code that constitutes processor firmware, a protocol stack, a database management system, an operating system (for example an operating system or a combination of operating systems), a cross-platform runtime environment, a virtual machine, or a combination of one or more of them. The apparatus and execution environment can realize various different computing model infrastructures, such as web services, distributed computing and grid computing infrastructures.

**[0080]** A computer program (also known, for example, as a program, software, software application, software module, software unit, script, or code) can be written in any form of programming language, including compiled or interpreted languages, declarative or procedural languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, object, or other unit suitable for use in a computing environment. A program can be stored in a portion of a file that holds other programs or data (for example, one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (for example, files that store one or more modules, sub-programs, or portions of code). A computer program can be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

**[0081]** Processors for execution of a computer program include, by way of example, both general- and special-purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read-only memory or a random-access memory or both. The essential elements of a computer are a processor for performing actions in accordance with instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data. A computer can be embedded in another device, for

example, a mobile device, a personal digital assistant (PDA), a game console, a Global Positioning System (GPS) receiver, or a portable storage device. Devices suitable for storing computer program instructions and data include non-volatile memory, media and memory devices, including, by way of example, semiconductor memory devices, magnetic disks, and magneto-optical disks. The processor and the memory can be supplemented by, or incorporated in, special-purpose logic circuitry.

**[0082]** Mobile devices can include handsets, user equipment (UE), mobile telephones (for example, smartphones), tablets, wearable devices (for example, smart watches and smart eyeglasses), implanted devices within the human body (for example, biosensors, cochlear implants), or other types of mobile devices. The mobile devices can communicate wirelessly (for example, using radio frequency (RF) signals) to various communication networks (described below). The mobile devices can include sensors for determining characteristics of the mobile device's current environment. The sensors can include cameras, microphones, proximity sensors, GPS sensors, motion sensors, accelerometers, ambient light sensors, moisture sensors, gyroscopes, compasses, barometers, fingerprint sensors, facial recognition systems, RF sensors (for example, Wi-Fi and cellular radios), thermal sensors, or other types of sensors. For example, the cameras can include a forward- or rear-facing camera with movable or fixed lenses, a flash, an image sensor, and an image processor. The camera can be a megapixel camera capable of capturing details for facial and/or iris recognition. The camera along with a data processor and authentication information stored in memory or accessed remotely can form a facial recognition system. The facial recognition system or one-or-more sensors, for example, microphones, motion sensors, accelerometers, GPS sensors, or RF sensors, can be used for user authentication.

**[0083]** To provide for interaction with a user, embodiments can be implemented on a computer having a display device and an input device, for example, a liquid crystal display (LCD) or organic light-emitting diode (OLED)/virtual-reality (VR)/augmented-reality (AR) display for displaying information to the user and a touchscreen, keyboard, and a pointing device by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, for example, visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input. In addition, a computer can interact with a user by sending documents to and receiving documents from a device that is used by the user; for example, by sending

web pages to a web browser on a user's client device in response to requests received from the web browser.

**[0084]** Embodiments can be implemented using computing devices interconnected by any form or medium of wireline or wireless digital data communication (or combination thereof), for example, a communication network. Examples of interconnected devices are a client and a server generally remote from each other that typically interact through a communication network. A client, for example, a mobile device, can carry out transactions itself, with a server, or through a server, for example, performing buy, sell, pay, give, send, or loan transactions, or authorizing the same. Such transactions may be in real time such that an action and a response are temporally proximate; for example an individual perceives the action and the response occurring substantially simultaneously, the time difference for a response following the individual's action is less than 1 millisecond (ms) or less than 1 second (s), or the response is without intentional delay taking into account processing limitations of the system.

**[0085]** Examples of communication networks include a local area network (LAN), a radio access network (RAN), a metropolitan area network (MAN), and a wide area network (WAN). The communication network can include all or a portion of the Internet, another communication network, or a combination of communication networks. Information can be transmitted on the communication network according to various protocols and standards, including Long Term Evolution (LTE), 5G, IEEE 802, Internet Protocol (IP), or other protocols or combinations of protocols. The communication network can transmit voice, video, biometric, or authentication data, or other information between the connected computing devices.

**[0086]** Features described as separate implementations may be implemented, in combination, in a single implementation, while features described as a single implementation may be implemented in multiple implementations, separately, or in any suitable sub-combination. Operations described and claimed in a particular order should not be understood as requiring that the particular order, nor that all illustrated operations must be performed (some operations can be optional). As appropriate, multitasking or parallel-processing (or a combination of multitasking and parallel-processing) can be performed.

## CLAIMS

What is claimed is:

1. A computer-implemented method for blockchain transaction reconciliation, the computer-implemented method comprising:

5 obtaining, by a blockchain member, a blockchain transaction record that is selected from a blockchain and satisfies a specified condition;

comparing, by the blockchain member, the blockchain transaction record with an off-chain transaction record maintained by the blockchain member;

10 determining whether the off-chain transaction record is inconsistent with the blockchain transaction record; and

in response to determining that the off-chain transaction record is inconsistent with the blockchain transaction record, updating, by the blockchain member, the off-chain transaction record based on the blockchain transaction record.

2. The computer-implemented method according to claim 1, wherein obtaining, by the blockchain member, the blockchain transaction record that is selected from a blockchain account book associated with the blockchain and satisfies a specified condition comprises:

15 sending, by the blockchain member, the specified condition to a reconciliation service provider of the blockchain; and

20 receiving, by the blockchain member, the blockchain transaction record returned by the reconciliation service provider.

3. The computer-implemented method according to claim 1, wherein the specified condition comprises at least one of the following:

25 a time period comprising a creation moment of the blockchain transaction record, a blockchain member participating in a blockchain transaction corresponding to the blockchain transaction record, and a condition that the blockchain transaction record is a normal transaction record or a refund transaction record.

4. The computer-implemented method according to claim 1, wherein comparing, by the blockchain member, the blockchain transaction record with the off-chain transaction record maintained by the blockchain member comprises:

5 exporting, by the blockchain member, the blockchain transaction record by using a bridge module configured between the blockchain member and the blockchain, to compare the blockchain transaction record with the off-chain transaction record off the blockchain.

5. The computer-implemented method according to claim 4, wherein the bridge module is separately connected to a first data interface provided by the blockchain member and a second data interface provided by the blockchain.

10 6. The computer-implemented method according to claim 1, further comprising: entering, by the blockchain member, the specified condition and change information for the off-chain transaction record into the blockchain.

7. The computer-implemented method according to claim 1, wherein the blockchain comprises a blockchain node and an anchor point.

15 8. The computer-implemented method according to claim 7, wherein the blockchain node is configured to maintain a blockchain account book, wherein the blockchain member obtains contents recorded in the blockchain account book, to actively select a corresponding blockchain transaction record based on the specified condition, to obtain the blockchain transaction record satisfying the specified condition.

20 9. The computer-implemented method according to claim 7, wherein the anchor point is configured to exchange off-chain assets outside the blockchain into blockchain assets associated to the blockchain transaction record.

10. An apparatus for blockchain transaction reconciliation, the apparatus comprising a plurality of modules configured to perform the computer-implemented method of any one of  
25 claims 1 to 9.