



(51) International Patent Classification:
F41A 9/70 (2006.01)

(21) International Application Number:
PCT/US2013/021996

(22) International Filing Date:
17 January 2013 (17.01.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/587,604 17 January 2012 (17.01.2012) US

(71) Applicant (for all designated States except US): **MAGPUL INDUSTRIES CORP** [US/US]; PO Box 17697, Boulder, Colorado 80308-0697 (US).

(72) Inventors; and

(71) Applicants (for US only): **FIRZPATRICK, Richard** [US/US]; 6816 N 95th Street, Longmont, Colorado 80504 (US). **MAYBERRY, Michael** [US/US]; 3219 W 23rd Avenue, Denver, Colorado 80211 (US). **NAKAYAMA, Bri-**

an [US/US]; 12995 W 63rd Place, Unit #E, Arvada, Colorado 80004 (US).


(74) Agent: **DOBBIN, Geoffrey**; Dobbin IP Law, P.C., 4278 S 6220 W, West Valley City, Utah 84128-6501 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,

[Continued on next page]

(54) Title: AMMUNITION MAGAZINE



(57) Abstract: A new interface for a magazine follower (20) and floor plate (10) is used to provide greater stability to the round stack and a more sturdy system overall. The floor plate (10) is designed with two opposite legs, the rear (24) being shorter than the front leg (22) so as to facilitate travel throughout the magazine and clearing of accumulated dirt and debris. The floor plate (10), in one embodiment, utilizes a lock plate (12) that is shaped and sized to become a shoe for the compressed spring (3) and associated follower (20). In an alternate embodiment, the floor plate (30) itself serves the purpose and, with provided teeth (36, 38), directly fastens to the magazine casing (2) at notches (6, 8) manufactured in the magazine casing for that purpose. Other enhancements to the magazine include at least one matrix of divots (5) to provide a paint surface, an over-insertion stop and lower rear geometry to aid in clearing debris and grit.



TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*
- *of inventorship (Rule 4.17(iv))*

Published:

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

- *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*