

## CLAIMS

1. A computer implemented method for real-time determination of a merchant risk level, the method comprising:

calculating a transaction risk score for each transaction that occurs at a merchant during an hour  $h$ , wherein  $h$  is from 1 to 24;

aggregating the transaction risk scores for each transaction the occurred at the merchant during hour  $h$  to obtain a merchant risk score  $m_h$  for the merchant during each hour  $h$ ;

repeating the calculating step and the aggregating step for each hour  $h$ ;

compiling the merchant risk scores  $m_h$  to calculate a daily merchant risk score  $s_i$ ;

and,

providing the daily merchant risk score  $s_i$  to the merchant.

2. The method of claim 1, wherein the step of aggregating the transaction risk score for each transaction that occurred at the merchant during hour  $h$ , further comprises calculating a mean of the transaction risk scores for all the transactions that occurred during hour  $h$ .

3. The method of claim 1, further comprising:

determining a peer group for the merchant, wherein the peer group comprises one or more peer merchants that provide similar goods or services as the merchant;

calculating a transaction risk score for each transaction that occurs at the peer group during an hour  $h$ , wherein  $h$  is from 1 to 24;

aggregating the transaction risk score for each transaction that occurs at the peer group during hour  $h$  to obtain a peer group risk score  $p_h$  for the peer group;

repeating the calculating step and the aggregating step for each hour  $h$ ;

compiling the peer group scores  $p_h$  to calculate a daily peer group risk score  $p_i$ ;

and,

comparing the daily peer group risk score  $p_i$  to the daily merchant risk score  $s_i$ .

4. The method of claim 1 further comprising:

using an anomaly detection algorithm to determine if an anomaly exists in the daily merchant risk score  $s_i$  and,  
if an anomaly is detected, adding the merchant to a list.

5. The method of claim 4, wherein the anomaly detection algorithm comprises:

determining a first merchant risk level at a time  $t_n$ , wherein the first merchant risk level  $y_n$  is a running average of the merchant daily risk scores  $s_i$ , wherein the first merchant risk level  $y_n$  is calculated as,

$$y_n = \sum_{i=1}^n e^{-(t_n-t_i)/T} s_i / \sum_{i=1}^n e^{-(t_n-t_i)/T}$$

wherein  $T$  is a decay parameter and  $i$  is from 1 to  $n$ .

determining a second merchant risk level at a time  $t_{n+1}$ , wherein the second merchant risk level  $y_{n+1}$  is calculated as,

$$y_{n+1} = \sum_{i=1}^{n+1} e^{-(t_{n+1}-t_i)/T} s_i / \sum_{i=1}^{n+1} e^{-(t_{n+1}-t_i)/T}$$

comparing the first merchant risk level  $y_n$  to the second merchant risk level  $y_{n+1}$ ,  
if the difference between the first merchant risk level  $y_n$  and the second merchant risk level  $y_{n+1}$  is above a threshold, then an anomaly is identified.

6. The method of claim 1, further comprising:

creating a first entity profile using a first dataset  
creating a second entity profile using a second dataset, wherein the second entity profile is created  
using the first entity profile and the second entity profile to train a third dataset containing transaction data to determine a probability that a transaction is fraudulent;  
converting the probability that the transaction is fraudulent into a transaction risk score.

7. The method of claims 6, wherein the transaction risk score is any of 1 to 100.
8. The method of claim 7, wherein a high transaction risk score indicates a high-risk transaction and a low transaction risk score indicates a low risk transaction.
9. The method of claim 6, wherein the first entity profile comprises one or more of a historical fraud rate, a transaction decline rate, and an average dollar amount.
10. The method of claim 6, wherein the second entity profile comprises user and merchant embeddings.
11. A computer system comprising an input output circuit, a memory for storing computer executable instructions and a processor physically configured according to computer executable instructions, the computer executable instructions implementing a method for real-time determination of a merchant risk level, the method comprising computer executable blocks for:
  - calculating a transaction risk score for each transaction that occurs at a merchant during an hour  $h$ , wherein  $h$  is from 1 to 24;
  - aggregating the transaction risk scores for each transaction that occurs at the merchant during hour  $h$  to obtain a merchant risk score  $m_h$  for the merchant during each hour  $h$ ;
  - repeating the calculating step and the aggregating step for each hour  $h$ ;
  - compiling the merchant risk scores  $m_h$  to calculate a daily merchant risk score  $s_i$ ;and,
  - providing the daily merchant risk score  $s_i$  to the merchant.
12. The computer system of claim 11, wherein the step of aggregating the transaction risk score for each transaction that occurred at the merchant during hour  $h$ , further comprises calculating a mean of the transaction risk scores for all the transactions that occurred during hour  $h$ .

13. The computer system of claim 11, further comprising computer executable instructions for:

determining a peer group for the merchant, wherein the peer group comprises one or more peer merchants that provide similar goods or services as the merchant;

calculating a transaction risk score for each transaction that occurs at the peer group during an hour  $h$ , wherein  $h$  is from 1 to 24;

aggregating the transaction risk score for each transaction the occurred at the peer group during hour  $h$  to obtain a peer group risk score  $p_h$  for the peer group;

repeating the calculating step and the aggregating step for each hour  $h$ ;

compiling the peer group scores  $p_h$  to calculate a daily peer group risk score  $p_i$ ;

and,

comparing the daily peer group risk score  $p_i$  to the daily merchant risk score  $s_i$ .

14. The computer system of claim 11, further comprising computer executable instructions for:

using an anomaly detection algorithm to determine if an anomaly exists in the daily merchant risk score  $s_i$  and,

if an anomaly is detected, adding the merchant to a list.

15. The computer system of claim 14, wherein the anomaly detection algorithm comprises computer executable steps for:

determining a first merchant risk level at a time  $t_n$ , wherein the first merchant risk level  $y_n$  is a running average of the merchant daily risk scores  $s_i$ , wherein the first merchant risk level  $y_n$  is calculated as,

$$y_n = \sum_{i=1}^n e^{-(t_n-t_i)/T} s_i / \sum_{i=1}^n e^{-(t_n-t_i)/T}$$

wherein  $T$  is a decay parameter and  $i$  is from 1 to  $n$ .

determining a second merchant risk level at a time  $t_{n+1}$ , wherein the second merchant risk level  $y_{n+1}$  is calculated as,

$$y_{n+1} = \sum_{i=1}^{n+1} e^{-(t_{n+1}-t_i)/T} s_i / \sum_{i=1}^{n+1} e^{-(t_{n+1}-t_i)/T}$$

comparing the first merchant risk level  $y_n$  to the second merchant risk level  $y_{n+1}$ ,  
if the difference between the first merchant risk level  $y_n$  and the second merchant risk level  $y_{n+1}$  is above a threshold, then an anomaly is identified.

16. The computer system of claim 11, further comprising computer executable instructions for:

- creating a first entity profile using a first dataset;
- creating a second entity profile using a second dataset, wherein the second entity profile is created;
- using the first entity profile and the second entity profile to train a third dataset containing transaction data to determine a probability that a transaction is fraudulent;
- converting the probability that the transaction is fraudulent into a transaction risk score.

17. The computer system of claim 16, wherein the transaction risk score is any of 1 to 100.

18. The computer system of claim 17, wherein a high transaction risk score indicates a high-risk transaction and a low transaction risk score indicates a low risk transaction.

19. The computer system of claim 16, wherein the first entity profile comprises one or more of a historical fraud rate, a transaction decline rate, and an average dollar amount.

20. The computer system of claim 16, wherein the second entity profile comprises user and merchant embeddings.