

LoomTechnical field

The invention relates to a loom according to the
5 preamble of claim 1.

Prior art

A loom of the type initially mentioned is known from
WO 99/13145. The loom contains a warp thread tensioning
10 device and a shedding device which has warp threads
pretensioned into a first shedding position. A lifting
device capable of being driven in oscillation is
equipped with drivers for the warp threads, there being
control means actuable by means of actuators, in order
15 to bring the warp threads selectively into engagement
with the drivers which move the warp threads into a
second shedding position. There is the disadvantage
that, in this loom, the lifting device equipped with
the drivers has to move along the entire travel of the
20 warp threads from the first shedding position as far as
the second shedding position. The lifting device
therefore has to execute a relatively long travel,
which, on the one hand, is time-consuming and, on the
other hand, requires higher drive forces. In order to
25 avoid this, in WO 99/13145 there is a further exemplary
embodiment, in which the warp threads assume a middle
shedding position and there are two lifting devices
which each have drivers in order to move the warp
threads either into the top shedding position or into
30 the bottom shedding position. This requires double the
number of drivers, with the result that such a design
variant is highly complicated and consequently cost-
intensive.

35 Presentation of the invention

The object of the invention is to improve a loom of the
type initially mentioned.

The set object is achieved by means of the characterizing features of claim 1. Since the loom has a second lifting device which is common to all the warp threads and which moves the warp threads out of the first shedding position into a switching position effective for the first lifting device, this results, for all the warp threads, in a very simple second lifting device which, moreover, appreciably reduces the switching travel for the first lifting device, so that the first lifting device has to move a warp thread only out of the switching position into the second shedding position. Both lifting devices have to execute only a limited travel for which they require less time. Moreover, since the lifting devices can be active simultaneously, an appreciable increase in the performance of the loom is obtained. In addition, owing to this design, the useful life is also improved owing to the lower susceptibility to wear. The loom also results in lower noise emission.

Advantageous refinements of the loom are described in claims 2 to 22.

According to claim 2, the second lifting device may be a lifting beam extending over all the warp threads. The lifting travel of the second lifting device may vary greatly, and it is advantageous if, according to claim 3, the latter executes at least half the lifting travel of the warp threads in the shed.

For the design of the first lifting device, there are various design variants which are already contained in WO 99/13145. An embodiment as claimed in claim 4 is particularly advantageous, according to which the first lifting device has for each warp thread a control drop wire with a driver slot and an assigned driver, preferably of hook-shaped design, for the associated warp thread. The warp thread can be brought selectively

- 3 -

into engagement with the driver by means of a control drop wire switchable by means of the actuator. According to claim 5, the driver slot is assigned to the displacement path of the driver and, in the switching region, is guided, via a control slot running obliquely with respect to the direction of displacement of the driver, out of the displacement path of the driver into a widened guide slot of the control drop wire. To facilitate the introduction of the warp thread into the control slot, according to claim 6, the guide slot is provided with a run-on side.

In principle, the control drop wire may be configured as a sheet steel strip. The design as claimed in claim 7 is advantageous, however, according to which the control drop wire is formed in the shape of a sleeve with two side walls, between which the driver is mounted displaceably. A reliable guidance of the warp thread from and to the driver is thereby achieved. To protect the warp thread, on the one hand, and to facilitate the run of the warp thread through the control drop wire, on the other hand, according to claim 8 at least the guide slot and the control slot are offset relative to one another in the two side walls of the control drop wire in the direction of run of the warp thread, in such a way that a deflection of the running warp thread in the control drop wire is lower than 90° , preferably 10° .

There are various possibilities for driving the drivers, there being preference, according to claim 9, for all the drivers of a row to be movable up and down by means of a common lifting knife. This affords a particularly simple and cost-effective solution.

Since the warp threads are moved in each case out of a first shedding position into the second shedding position, their displacement travel is such that the

elasticity of the warp thread is not sufficient, as a rule, to ensure satisfactory functioning. It is therefore advantageous if, according to claim 10, the warp thread tensioning device has an individual thread
5 tensioner for each warp thread on the run-in side of the warp threads to the shedding device. The tension of the individual warp thread can thereby be adapted more closely to the respective position of the warp thread in the shed. The loom may have the conventional
10 additional catch thread devices. It is more advantageous, however, if, according to claim 11, the thread tensioner is at the same time also designed as a catch thread device.

15 According to claim 12, each warp thread is guided via two guide elements which are arranged at a distance from one another and between which is arranged the thread tensioner which engages on the warp thread and exerts a pretension on the warp thread. According to
20 claim 13, the pretension may be generated by a tensioning weight. The design as claimed in claim 14 is more advantageous, according to which the pretension is generated by a tensioning spring. This also makes it possible, in particular, to arrange the thread
25 tensioner in a position deviating from the vertical.

The thread tensioner may be provided with a closed eye. The design as claimed in claim 15 is more advantageous, however, according to which each thread tensioner has a
30 lateral run-in eye for the warp thread. According to claim 16, each thread tensioner is provided with a guide orifice, by means of which it is mounted on a holder displaceably in the tensioning direction. Expediently, the thread tensioner is provided, in the
35 direction opposite to the pretensioning direction, with a grip part which preferably has a signal part projecting out of the direction of displacement. Such a signal part may be, for example, a projecting head part

- 5 -

of the thread tensioner. As a result, a thread tensioner on which a thread fault has occurred can be detected more easily, since it emerges from the plane of the thread tensioners which are operating satisfactorily.

It is particularly expedient if, according to claim 17, the thread tensioner is arranged on a holder which has a middle contact part which projects on one side and which, insulated, is embedded into lateral contact parts cooperating with the sides of the guide orifice of the thread tensioner. In the event of a faulty warp thread tension, the contact parts come into touch with an end face of the guide orifice, this touch bridging the contacts and thus triggering a fault signal.

The thread tensioner can be used in the most diverse possible looms. It is preferably used, however, in a loom according to claim 18, in which the warp thread tensioning device has a control device which is connected to the drive of a cloth take-up in such a way as to control the warp beam such that the warp threads as a whole are under a predeterminable tension force. The retaining force may be generated by means of a braking device at the warp let-off. An embodiment as claimed in claim 19 is more advantageous, however, according to which, to generate the retaining force, the warp beam is provided with specific drive which contains a selflocking gear. The warp thread tensioning device can be further improved by means of the design as claimed in claim 20, according to which it has a back bearer for the warp threads which is pretensioned by means of a tensioning spring device. The tensioning spring device is connected to the control device, so that the drives of the warp beam and of the cloth take-up can be controlled in such a way that the predeterminable tension force is maintained at the back bearer. Various variants may be envisaged for the

- 6 -

design of the tensioning spring device. The embodiment as claimed in claim 21 is particularly advantageous, according to which the tensioning spring device has a leaf spring with a flexion converter which delivers
5 corresponding control signals to the control device. In addition, according to claim 22, the warp thread tensioning device may be designed with a safety device which is operatively connected to the back bearer and which contains an emergency switch which responds when
10 the force of the warp threads which occurs in the back bearer is greater than the set tension force by a determinable safety amount.

Brief description of the drawings

15 Exemplary embodiments of the invention are described in more detail below with reference to the drawings in which:

figure 1 shows a diagram of a loom in a side view;
20 figure 2 shows a detail of the shedding device of the loom of figure 1 on a larger scale;
figure 3 shows the shedding device of figure 2 in the section III-III;
figures 4 - 8 show various work stages of the shedding
25 device of figure 2;
figure 9 shows the diagram of a further loom with individual thread tensioners in a side view;
figure 10 shows the thread tensioner of the loom according to figure 9 on a larger scale, and
30 figure 11 shows a detail of the device according to figure 10.

Way of implementing the invention

Figure 1 shows diagrammatically a loom which, in
35 general, has a warp let-off 2 which is designed, for example, as a warp beam, from which warp threads 4 arrive at the shedding device 12 via a back bearer 6, individual thread tensioners 8 and catch thread devices

10. In the shedding device 12, the warp threads 4 are opened to form a shed 14 into which can then be introduced a weft thread 16 which is beaten up at the beating-up edge 18, so that a cloth web 20 is obtained.

5 The cloth web 20, held by a cloth holder 22, is taken up via a cloth take-up 24. A control device 26 serves for controlling the loom.

The loom is provided with a thread tensioning device
10 which primarily contains the cloth take-up 24, the drive 28 of which is controlled by means of the control device 26 such that a predeterminable tension force common to all the warp threads 4 is given as a function of the retaining force of the warp let-off 2. The
15 retaining force of the warp let-off may be generated by means of a braking device 29 or a specific drive, in which a motor is connected to the warp let-off via a selflocking gear. The warp thread tensioning device additionally contains, for each warp thread 4, an
20 individual warp thread tensioner 8 which is arranged between two guide elements 30 and, in the example shown, individually pretensions, by means of a pretensioning spring 32, the warp thread 4 which runs through an eye 34.

25

In the shedding device 12, the warp threads 4 are pretensioned into a first shedding position F_1 between a deflecting roller 36 and a cloth holder 22 which may also be designed as an expander. A first lifting device
30 38 serves for the individual control of the warp threads 4, said lifting device having drivers 40 which can be moved out of a switching position F_2 into the second shedding position F_3 by means of a lifting beam 42. With the aid of control means 46 controllable by
35 actuators 44, the warp threads 4 can be brought selectively into engagement with the drivers 40 when the warp threads have been moved out of the first shedding position F_1 into the switching position F_2 by

- 8 -

means of a common second lifting device 48, as is evident in detail in figures 1 to 8. The control means 46 contain control drop wires 50 which are pretensioned by means of a pretensioning spring 52 against a lifting beam 54 on which they stand via a stop 56. The actuators 44 contain hook parts 58 which cooperate with hook parts 60 on the control drop wires 50 and, in the activated state, hold the control drop wire 50 in the lifted position. A nonactivated actuator 44 enables the displacement travel of the control drop wire 50. In figure 1, each control drop wire 50 is symbolized by its switching travel, as illustrated in detail by means of figures 2 to 8. Thus, the control drop wires contain a driver slot 62 which lies in the displacement travel of the warp thread 2. The driver slot has adjoining it upwardly a control slot 64 which guides the warp thread out of the displacement travel of the driver into a widened guide slot 66, so that it can no longer be grasped by the driver 40.

As may be gathered from figures 2 and 3, the control drop wire is designed in the form of a sleeve and has side walls 68, 70 which are connected by means of end walls 72, 74 and which thus provide a cavity in which the driver 40 is mounted displaceably. In particular, the driver slots 62a and 62b are arranged in the side walls 68, 70 so as to be offset in the direction of run of the thread in such a way that the warp thread, when it passes through the control drop wire, is inclined at an angle α from the vertical with respect to the control drop wire which is smaller than 90° , preferably 40° , in order to keep as low as possible the passage resistance of the warp thread through the control drop wire and consequently the wear of the warp thread, on the one hand, and of the control drop wire, on the other hand.

The functioning of the shedding device is illustrated

in more detail with reference to figure 1 in conjunction with figures 2 to 8. When the control drop wire is in the lifted position, in which it is retained on the actuator, as may be gathered from figure 1 for the actuator on the right and from figure 2, 4 and 5, the warp thread is guided by means of the second lifting device 40 out of the guide slot 66 via an oblique run-on side 76 into the control slot 64 and by means of the latter into the driver slot 62 in which the warp thread lies in the displacement travel of the driver 40. During the downward movement of the driver 40, the warp thread 4 is driven by the hook 40a of the driver 40 out of the switching position F_2 into the second shedding position F_3 which is the bottom shedding position. As long as the control drop wire 50 remains in the lifted state, the warp thread 4 is moved to and fro by the amount of the height H_1 only between the switching position F_2 and the bottom shedding position F_3 , as is evident from figures 2 and 4 to 6.

As soon as the actuator 44 releases the control drop wire 50 and the latter is lowered by the amount of the switching quantity S , during the upward movement of the driver 40 the warp thread passes via the control slot 64 into the widened guide slot 66 and consequently outside the displacement travel of the driver 40. Then, as may be gathered from figures 7 and 8, the warp thread passes again into the displacement travel of the second lifting device 48 and is moved over the height H_2 out of the switching position into the first shedding position F_1 which is the top shedding position.

Figure 9 shows a loom with a special design of the warp thread tensioning device and of the thread tensioners, which loom may have, for example, a shedding device according to the loom of figure 1. The loom contains a warp beam 2a, from which warp threads 4 are guided via

a back bearer 6a to individual thread tensioners 8a which are arranged upstream of a shedding device 12a. The shedding device 12a may be designed similarly to the shedding device 12 of the loom of figure 1, but may also have other designs. The cloth web 20 produced is taken up via a cloth take-up 24a and wound up on a cloth beam 80. The loom contains a control device 26a which is designed, in particular, for controlling the warp thread tensioning device. The warp beam 2a is actuated by a drive 82 which has a selflocking gear 84. The drive is controlled by the control device 26a, specifically as a function of the drive 28a of the cloth take-up 24a and of a tensioning spring device 86 with which the back bearer 6a stands against the warp threads 4. The control is such that the cloth take-up 24a is set as a function of the retaining force of the drive 82 of the warp beam 2a such that a predetermined tension force can be maintained at the back bearer 6a.

The warp beam 6a is fastened to a rocker 88 which is supported via a supporting device 90 on a leaf spring 92 provided with a flexion converter 94 which transfers its data to the control device 26a. The supporting device 90 comprises a safety device 96 containing a screw bolt 98, the head 100 of which is arranged displaceably in a holding bell 102. The holding bell 102 is connected to the rocker 88. The head 100 is supported on a stop 104 of the holding bell. A pretensioning spring 106 arranged outside the holding bell 102 is supported, on the one hand, on the screw bolt 98 via a setscrew 108 and on the holding bell 102 via a washer 110 on the other hand so that the head 100 bears with a corresponding pretensioning force against the stop 104 of the holding bell 102. The screw bolt 98 is connected, further, to the leaf spring 92. If, then, a tension force higher than the tension force set as permissible on the leaf spring 92 occurs at the back bearer 6a, the pretensioning spring 106 is compressed

- 11 -

and the holding bell 102 is displaced on the screw bolt 98, with the result that a switch 112 connected to the holding bell 102 is closed and transmits a fault signal to the control device 26a.

5

Figures 10 and 11 show in detail the design of the thread tensioners 8a which are at the same time also configured as catch thread devices. The thread tensioners 8a are designed as drop wires and each have
10 a guide orifice 114, by means of which they are mounted on a holder 116 displaceably in the tensioning direction. The holders have a middle contact part 118 which projects on one side and which, insulated, is embedded into lateral contact parts 120. The latter are
15 connected to the sides of the guide orifice. In the event of a faulty warp tension, the thread tensioners 8a are displaced by means of the pretensioning spring 32a until the contact parts 118, 120 of the holder 116 stand against an end face 124 of the guide orifice 114
20 and trigger a fault warning. The thread tensioners lie in each case between two guide elements 30a for the warp thread 4 which is pieced up to the thread tensioners 8a via run-in eyes 34a. On the side facing away from the pretensioning spring 32a, the thread
25 tensioners each contain a grip part 126 with a signal part 128 which projects out of the displacement plane of the thread tensioners, so that it is possible to detect those thread tensioners which indicate a broken warp thread and for this reason are no longer in
30 alignment with the remaining signal parts 128. The signal part 128 is formed by a head part projecting out of the displacement plane.

List of reference symbols

F ₁	First shedding position	54	Lifting beam
F ₂	Switching position	56	Stop
F ₃	Second shedding position	58	Hook part of 44
		60	Hook part of 50
H ₁	Lift height of the 1st lifting device	62	Driver slot
		62a	Driver slot
H ₂	Lift height of the 2nd lifting device	62b	Driver slot
		64	Control slot
S	Switching quantity	66	Guide slot
α	Deflection	68	Side wall
		70	Side wall
2, 2a	Warp let-off (warp beam)	72	End wall
		74	End wall
4	Warp thread	76	Run-on side
6, 6a	Back bearer	80	Cloth beam
8, 8a	Thread tensioner	82	Drive
10	Catch thread device	84	Selflocking gear
12, 12a	Shedding device	86	Tensioning spring device
14	Shed		
16	Weft thread	88	Rocker
18	Beating-up edge	90	Supporting device
20	Cloth web	92	Leaf spring
22	Cloth holder	94	Flexion converter
24, 24a	Cloth take-up	96	Safety device
26, 26a	Control device	98	Screw bolt
28, 28a	Drive	100	Head
29	Braking device	102	Holding bell
30, 30a	Guide element	104	Stop
32, 32a	Pretensioning spring	106	Pretensioning spring
34, 34a	Eye	108	Setscrew
36	Deflecting roller	110	Washer
38	First lifting device	112	Switch
40	Driver	114	Guide orifice
40a	Hook	116	Holder
42	Lifting beam	118	Contact part
44	Actuator	120	Lateral contact

- 13 -

46	Control means		parts
48	Second lifting device	124	End face
50	Control drop wire	126	Grip part
52	Pretensioning spring	128	Signal part

Patent Claims

1. A loom with a warp thread tensioning device and with a shedding device (12, 12a) which has warp threads (4) pretensioned into a first shedding position (F_1), furthermore with a lifting device (38) capable of being driven in oscillation and having drivers (40) for the warp threads (4), and also with control means (46) actuable by means of actuators (44), in order to bring the warp threads (4) selectively into engagement with the drivers (40) which move the warp threads (4) into a second shedding position (F_3), characterized in that said loom has a second lifting device (48) common to all the warp threads (4), in order to move the warp threads (4) out of the first shedding position (F_1) into a switching position (F_2) active for the first lifting device (38) and in order to move nonselected warp threads jointly into the first shedding position (F_1) as a result of the pretensioning of the warp threads (4).
2. The loom as claimed in claim 1, characterized in that the second lifting device (48) is designed as a lifting beam extending over all the warp threads (4).
3. The loom as claimed in claim 1 or 2, characterized in that the second lifting device (48) executes at least half (H_2) of the lifting travel of the warp threads in the shed.
4. The loom as claimed in one of claims 1 to 3, characterized in that the first lifting device (38) has, for each warp thread, a control drop wire (50) with a driver slot (62, 62a, 62b) and an assigned driver (40, 40a), preferably of hook-shaped design, for the associated warp thread (4), the warp thread being capable of being brought selectively into engagement with the driver (40, 40a) by means of the control drop wire (50) switchable by means of the actuator (44).

5. The loom as claimed in claim 4, characterized in that the driver slot (62, 62a, 62b) is assigned to the displacement path of the driver (40, 40a) and, in the switching region, leads, via a control slot (64) running obliquely with respect to the direction of displacement of the driver, out of the displacement path of the driver (40, 40a) into a widened guide slot (66) of the control drop wire.

6. The loom as claimed in claim 5, characterized in that the guide slot (66) has a run-on side (76) running toward the control slot (64).

7. The loom as claimed in one of claims 4 to 6, characterized in that the control drop wire (50) is designed in the form of a sleeve with two side walls (68, 70), the driver (40, 40a) being mounted displaceably between the side walls (68, 70).

8. The loom as claimed in claim 7, characterized in that at least the driver slot (62a, 62b) and the control slot (64) are formed in the two side walls (68, 70), the driver slots (62a, 62b) and the control slots (64) of the side walls (68, 70) being offset relative to one another in the direction of run of the warp thread (4) in such a way that a deflection α of the running warp thread in the control drop wire (50) is lower than 90° , preferably 10° .

9. The loom as claimed in one of claims 4 to 8, characterized in that all the drivers (40) of a row can be moved up and down by means of a common lifting beam (42).

10. The loom as claimed in one of claims 1 to 9, characterized in that the warp thread tensioning device has an individual thread tensioner (8, 8a) for each

warp thread (4) on the run-in side of the warp threads (4) to the shedding device (12, 12a).

11. The loom as claimed in claim 10, characterized in
5 that the thread tensioner (8a) is designed as a catch thread device.

12. The loom as claimed in claim 10 or 11,
10 characterized in that each warp thread (4) is guided via two guide elements (30, 30a) which are arranged at a distance from one another and between which is arranged the thread tensioner (8, 8a) which engages on the warp thread and exerts a pretension on the warp thread.

15

13. The loom as claimed in claim 12, characterized in that the pretension is generated by a tensioning weight.

20 14. The loom as claimed in claim 12, characterized in that the pretension is generated by a tensioning spring (32, 32a).

15. The loom as claimed in one of claims 10 to 14,
25 characterized in that each thread tensioner (8a) has a lateral run-in eye (34a) for the warp thread (4).

16. The loom as claimed in one of claims 10 to 15,
30 characterized in that each thread tensioner (8a) has a guide orifice (114), by means of which it is mounted on a holder (116) displaceably in the tensioning direction, the thread tensioner having, in the direction opposite to the pretensioning direction, a grip part (126) which is preferably provided with a
35 signal part (128) projecting out of the displacement direction.

17. The loom as claimed in claim 16, characterized in

that the holder (116) has a middle contact part (118) which projects from one side and which, insulated, is embedded into lateral contact parts (120) cooperating with the sides of the guide orifice (114) of the thread
5 tensioner, and, in the event of a faulty warp thread tension, the contact parts (118, 120) can be bridged by means of an end face (124) of the guide orifice (114) for fault warning.

10 18. The loom as claimed in one of claims 1 to 17, characterized in that the warp thread tensioning device has a control device (26, 26a) which is connected to the drive (28, 28a) of a cloth take-up (24, 24a), in order to control the drive (28, 28a) of the cloth
15 take-up (24, 24a) as a function of the retaining force of a warp beam (2, 2a), in such a way that the warp threads as a whole are under a predeterminable tension force.

20 19. The loom as claimed in claim 18, characterized in that, to generate the retaining force, the warp beam (2a) has a specific drive (82) provided with a selflocking gear (84).

25 20. The loom as claimed in claim 18 or 19, characterized in that the warp thread tensioning device has a back bearer (6a) for the warp threads (4) which is pretensioned by means of a tensioning spring device (86), the tensioning spring device (86) being connected
30 to the control device (26a) in such a way that the drives (82, 28a) of the warp beam (2a) and of the cloth take-up (24a) can be controlled in such a way that the predeterminable tension force can be maintained at the back bearer (6a).

35

21. The loom as claimed in claim 20, characterized in that the tensioning spring device (86) has a leaf spring (92) with a flexion converter (94) which is

- 18 -

connected to the control device (26a).

22. The loom as claimed in claim 20 or 21,
characterized in that the tensioning spring device (86)
5 is connected to the back bearer (6a) via a safety
device (96) having an emergency switch (112) which
responds when the force of the warp threads (4) which
occurs at the back bearer (6a) is higher than the set
tension force by a determinable safety amount.