

Identification and Authentication using Liquid Crystal
Material Markings

Field of the Invention

5 The present invention relates to a machine readable marking for the recognition, identification and authentication of individual items. The marking is made of liquid crystal material, which is applied to a substrate by known variable information printing techniques. The marking is detectable
10 and/or identifiable by passive detecting means, e.g. optical filters under unpolarized (ambient) light, as well as by illumination with polarized light. The marking is applied in the form of indicia, such as a one- or two-dimensional bar code, a matrix code, or the like.

15

Background of the Invention

"Track and Trace" systems are currently used in different fields of industry. Many industries suffer from counterfeit or diverted products, in particular in the field of mass-produced
20 items such as beverages, perfumes, pharmaceutical drugs, cigarettes, CDs/DVDs, as well as other kind of consumables.

Counterfeiting and market diversion are facilitated if the mass products are handled on a lot base, rather than on an
25 individual item base. Counterfeit or diverted products are in such case easily introduced into the supply chain. Producers and retailers would like to be in a position to distinguish their original products from such counterfeit or diverted (parallel imported) products at the level of the individual
30 unit which can be sold.

The underlying technical problem has been addressed in the art

through an individual marking of each sellable item introduced into the supply chain. The markings of the prior art were chosen in such a way that they were not susceptible to photocopying, i.e. preferably covert markings were used, which
5 are not visible to the unaided eye or the photocopying machine.

A "Covert" marking, in the context of the present invention, is any marking or security element, which cannot be
10 authenticated by the unaided eye, but which, for authentication, depends on a detecting or reading device of any kind, such as an optical filter or an electronic authentication equipment.

15 An "Overt" marking, in the context of the present invention, is any marking or security element, which, for authentication, does not depend on a detecting or reading device; i.e. which can be authenticated by the unaided eye.

20 "Color" in the context of the present invention is used to designate any spectrally selective return of light (electromagnetic radiation) from an illuminated object, be it in the visible, the infrared or in the UV range of the electromagnetic spectrum (i.e. in the whole wavelength range
25 from 200nm to 2500nm).

The term "visible" is used to indicate that a property can be revealed by the unaided eye; "detectable" is used for a property that can be revealed by an optical instrument, though
30 not necessarily by the unaided eye, and "invisible" is used for a property that cannot be detected by the unaided eye. In

particular, the term "visible color" means a spectrally selective return of light in the wavelength range from 400nm to 700nm, which is detectable by the unaided eye.

5 A first type of individual markings, useful to prevent counterfeit and diversion, is disclosed in US 5,569,317, US 5,502,304, US 5,542,971 and US 5,525,798. According to these documents, a bar code is applied onto the item, using an ink which is not detectable under light of the visible spectrum
10 (400-700nm wavelength) but which becomes visible when illuminated with light of the UV spectrum (200-380nm wavelength).

A second type of individual markings is disclosed in US
15 5,611,958 and US 5,766,324. According to these documents, a marking is applied onto a commercial good, using an ink which is not detectable in the visible spectrum, but which can be detected through illumination with light of the infrared spectrum (800-1600nm wavelength).

20

Yet another type of individual markings, applied through an ink, is disclosed in US 5,360,628 and US 6,612,494. This marking needs to be illuminated jointly with UV- and IR-light to be revealed.

25

Still another type of individual marking relies on inks comprising up-converting phosphors such as described in US 5,698,397.

30 All of the markings mentioned in the cited prior art are covert markings, which are completely invisible to the unaided

human eye. The reading of such covert markings depends on a corresponding detecting or reading device, able to detect or read the marking. This can be a disadvantage at the retail center or at the point-of-sale, where an appropriate reading
5 device may not always be available.

Overt markings comprising "optically variable" features, e.g. exhibiting viewing-angle dependent color, have been proposed in the art as authentication means for the "person in the
10 street". Among these are the holograms (cf. Rudolf L. van Renesse, "Optical Document Security" 2nd ed., 1998, chapter 10), the optical thin film security devices (idem, chapter 13) and the liquid crystal security devices (idem, chapter 14).

15 Particularly useful as security devices are the cholesteric liquid crystals. When illuminated with white light, the cholesteric liquid crystal structure reflects light of a determined color, which depends on the material in question and generally varies with the angle of observation and the
20 device temperature. The cholesteric material itself is colorless and the observed color is only due to a physical reflection effect at the cholesteric helical structure adopted at a given temperature by the liquid crystal material. (cf. J.L Fergason, *Molecular Crystals*, Vol. 1, pp. 293-307 (1966)).
25 In particular liquid crystal materials, the cholesteric liquid crystal polymers (CLCPs), the cholesteric helical structure is "frozen" in a determined state through polymerization, and thus rendered temperature-independent.

30 If the cholesteric liquid crystal material is applied on a dark or black background, its reflection color is highly

apparent to the unaided eye, because the light transmitted by the cholesteric material is largely absorbed by the background, so that the residual backscattering from the background does not disturb the perception of the cholesteric material's own reflection. A careful choice of the background color can thus contribute to the visibility of such an overt marking.

On a clear or white background the reflection color of the cholesteric liquid crystal material is virtually invisible due to the superposition of the cholesteric material's own reflection with the strong backscattering from the background. The cholesteric liquid crystal material can, however, always be identified with the help of a circular polarization filter because it selectively reflects only one of the two possible circular polarized light components, in accordance with its chiral helical structure.

EP-B1-1 381 520 and EP-A1-1 681 586 refer to a birefringent marking and a method of applying the same in the form of a liquid crystal layer having a non-uniform pattern of regions of different thickness. The applied liquid crystal coating or layer may provide for a hidden image on a reflective substrate, which is invisible when viewed under unpolarized light but rendered visible under polarized light or with the help of a polarization filter.

US 5,678,863 refers to means for the identification of documents of value which include a paper or polymer region, said region having a transparent and translucent characteristic. A liquid crystal material is applied to the

region to produce an optical effect, which differs when viewed in transmitted and reflected light. The liquid crystal material is in liquid form at room temperature and must be enclosed in a containing means such as microcapsules, in order to be used in a printing process such as gravure, roller, spray or ink-jet printing. The printed liquid crystal region can be in the form of a pattern, for example a bar code. The pattern can be verified by visual or machine inspection of the polarization states of the areas having left-handed and right-handed liquid crystal forms.

US 5,798,147 refers to coating compositions of polymerizable liquid crystal monomers which can be applied by conventional printing processes, such as letterpress, rotogravure, flexographic, offset, screen, and ink-jet printing. The printing inks can be used to produce markings and security inscriptions which are invisible to the human eye. The markings can be detected by their circular polarization or their angle dependent reflection color.

20

US 6,899,824 refers to a process for printing or coating a substrate with a multilayer of a liquid-crystalline composition and at least one non-liquid-crystalline coating. The process and the printed substrate are useful for producing a counterfeit-proof marking of articles. Preferred methods for applying such printing or coating are screen printing, planographic printing, flexographic, and letterpress printing.

None of the markings disclosed in the prior art does, however, provide a solution to the technical problem underlying "track & trace" applications, wherein, in addition to a machine-

30

readable individual coding of items with a counterfeit-resistant security marking, an easy authentication of the marking by the unaided eye is required.

5 "Track & Trace" applications are known in the art for e.g., postal services, wherein each mail piece is individually marked and followed throughout its delivery chain. Barcodes, such as 1D-barcodes, stacked 1D-barcodes, 2D-barcodes or matrix-codes, are most often used as the marking and
10 identification means.

No particular effort is devoted to authentication aspects in the case of the said postal markings, given that the mail piece is handled service-internally by the mailing company
15 throughout the entire delivery chain, so that no authentication is needed. Postal "Track & Trace" applications are merely focused on the identification of the mail piece.

Authentication aspects are, however, of crucial importance in
20 retail applications, where there is a potential risk of substitution of the original goods by counterfeit or diverted ones. For this reason, "Track & Trace" applications in this field must be combined with at least one security element, able to certify the authenticity of the marked good as an
25 original one.

In the following, "Secure Track & Trace" means the combination of a "Track & Trace" application, which allows for the identification of an individual item, with at least one
30 security element, which additionally allows for the authentication of the said item as being genuine.

Technical problem

For "Secure Track & Trace" applications, where a good in open circulation must be marked individually as to its authenticity and identity, and followed throughout its life cycle or for a specific period of time, e.g. for liability reasons, there is a need for a marking which is i) uniquely coded, so as to be identifiable ii) machine-readable, iii) copy (counterfeit) resistant, iv) authenticate-able by eye by a human user, and v) authenticate-able by a machine. For particular applications it is furthermore desirable that part of the marking is invisible to the unaided human eye.

Summary of the Invention

The marking of the present invention, for the secure tracking or tracing of an item or article, comprises a polymeric liquid crystal material having determined optical characteristics, which allow for its authentication and reading by a machine, as well as its authentication by the human eye. The marking is produced on a substrate by a variable information printing process in the form of indicia representing a unique code, which allows for its identification. The marking is further preferably laid out such that part of it is invisible to the unaided human eye.

25

The marking of the present invention is applied on items or articles such as value documents, banknotes, passports, identity documents, driving licenses, official permissions, access documents, stamps, tax stamps and banderoles, transportation tickets, event tickets, labels, foils, packaging, spare parts, and consumer goods, which thus carry

the marking, either directly - applied to their surface - or indirectly - applied to a label applied to their surface.

The polymeric liquid crystal material is preferably of the
5 cholesteric (i.e. twisted nematic) type; for certain applications, nematic (birefringent) liquid crystal material may also be used.

The polymeric liquid crystal material of the marking can
10 either be present as a liquid crystal material polymerized on the surface of a substrate, or alternatively consist of pigment flakes of a liquid crystal polymer, comprised in a coating composition applied on a substrate.

15 Said substrate can be any type of substrate, woven or non-woven, in particular it can be paper, cardboard, wood, glass, ceramic, metal, plastic, textile, leather, etc.; the substrate may be coated or uncoated, or comprise a sealed or a non-sealed surface.

20

The polymeric liquid crystal material of the marking preferably comprises further security materials, which are present to increase its resistance towards counterfeiting. These security materials are selected from the group
25 consisting of the inorganic luminescent compounds, the organic luminescent compounds, the IR-absorbers, the magnetic materials, the forensic markers, and combinations thereof.

Said security material can be present as a mere admixture, or,
30 according to the nature of the security material, also as a co-polymerized component of the liquid crystal pigment, of the

liquid crystal precursor composition, or of the ink binder. In particular, organic security materials comprising an acrylic or vinylic functionality are easily co-polymerized into a corresponding main polymer. Alternatively, the security
5 material may be grafted, i.e. chemically linked, onto a pre-existing polymer chain.

The substrate, representing the background on which the liquid crystal material is applied, can be of any color; a white
10 background being a preferred option for realizing a marking which is invisible to the unaided eye in the sense that no visible color is observed. A metallic reflecting background is a further preferred option, in particular in the case of a nematic (birefringent) liquid crystal material. The substrate
15 may in general be selected from the group consisting of reflecting substrates, colored substrates, and transparent substrates.

For enabling an easy authentication by a human user, it is
20 preferred that at least part of the background on which the liquid crystal material is applied has a contrasting color, such as red, green, blue or black, which, in combination with the liquid crystal marking, allows to perceive a visible color and an angle-dependent color change by the unaided eye.

25 Said substrate is thus preferably a patterned substrate, comprising at least two differently colored surface areas, each selected from the group of white surface areas, black surface areas, visibly colored surface areas, reflecting
30 surface areas, transparent surface areas and combinations thereof. It is thus evident to the skilled in the art that the

substrate surface carrying the liquid crystal material can have two or more colored areas underneath the liquid crystal material.

5 The substrate surface, on which the liquid crystal material is applied, can furthermore carry indicia, which may be of any form or color, such as a pattern, an image, a logo, a text, a 1D- or 2D-barcode or a matrix code, etc. The said indicia can be applied by any method of printing or coating.

10

The substrate can furthermore carry at least one security element selected from the group of inorganic luminescent compounds, organic luminescent compounds, IR-absorbers, magnetic materials, and forensic markers or combinations
15 thereof. The security element can be present in the form of indicia on the substrate surface or be incorporated (embedded) in the substrate itself.

The polymeric liquid crystal material is preferably present in
20 the form of indicia, such as a text or a code. Preferred indicia are chosen from the group comprising 1-dimensional, stacked 1-dimensional, and 2-dimensional barcodes. Current barcode symbologies have been disclosed by Bob Williams in "*Understanding Barcoding*", Pira International Ltd., 2004 (ISBN
25 1 85802 917 1)

The liquid crystal marking of the present invention is preferably produced by applying a liquid crystal precursor composition to a substrate and hardening the composition in
30 the ordered liquid crystal state. The said precursor composition comprises reactive monomers or oligomers of at

least one nematic liquid crystal compound. The reactive monomers or oligomers are preferably UV-cure-able; in this case the applied composition is UV-cured and also comprises a photoinitiator system, as known to the skilled person.

5

The ordered liquid crystal state depends upon the presence of a chiral dopant. Nematic liquid crystals without chiral dopant arrange in a molecular texture which is characterized by its birefringence. Nematic precursors are known from EP-A-0 216 712, EP-B-0 847 432, and US-B-6,589,445.

10

For producing a cholesteric (i.e. twisted nematic) liquid crystal polymer, the said precursor composition must also comprise a chiral dopant. Said dopant may be chosen from the derivatives of isosorbides and isomannides and mixtures thereof; as known from EP-B-0 847 432, GB-A-2 330 139, and US-B 6,589,445. Isosorbides are known to induce a right helical twist, whereas isomannides are known to induce a left helical twist.

20

Said dopant induces a helical structure in the nematic liquid crystal compound, characterized by a helical pitch of the order of the wavelength of visible light, leading to light reflection at determined wavelengths, and hence to the appearance of interference color, as well as of angle-dependent color shift. The reflected light from cholesteric liquid crystal phases is circularly polarized (either left-handed or right-handed), according to the rotation sense of the cholesteric helical twist.

30

The marking of the present invention is produced by applying

the liquid crystal precursor composition to a substrate and subsequently hardening the said composition on the substrate. The hardening is preferably performed by subjecting the applied composition to irradiation with UV-light, which
5 induces a polymerization of the reactive monomers or oligomers to form a liquid crystal polymer. The molecular ordering of the liquid crystal is thereby retained, i.e. the nematic or cholesteric texture is fixed in the state which was present during the irradiation. In the case of cholesteric liquid
10 crystal material, the helical pitch, and herewith the optical properties, such as the reflection color and the angle-dependent color shift remain thus fixed.

A method for marking an item or article comprises thus the
15 steps of providing a suitable item or article to be marked, and applying at least one polymeric liquid crystal material in the form of indicia representing a unique code by a variable information printing process onto the said item or article. In particular, the unique code represented by the said indicia
20 may be an encrypted information, and the method may comprise the step of encrypting the said information.

The said liquid crystal precursor composition can be applied to a substrate by any coating or printing technique.
25 Preferably the composition is applied by a variable information printing process, such as laser printing or ink-jet printing of the continuous or of the drop-on-demand type. Said variable information printing method allows for the unique coding of the marking for each printed item.

30

For application by laser printing the liquid crystal polymer

pigment flakes can be incorporated into a toner composition. To this aim, the liquid crystal polymer pigment particles are added in a ratio ranging from 1 wt% to 50 wt% to a toner composition comprising a binder resin and optionally,
5 additives such as, charge control agents or waxes.

Said binder resin present in a ratio ranging from 45 wt% to 95 wt%, is composed of thermoplastic polymers such as polyamides, polyolefines, polyurethanes, vinyl resins, epoxides, styrene
10 butadiene, styrene acrylate copolymers or polyester resins, and has a glass transitions temperature T_g in the range of 40°C to 120°C, preferably 60°C to 70°C, and an average polymer particle size lying in the range of 2-30µm depending on the desired resolution of the printed image. The liquid crystal
15 polymer pigment flakes may be encapsulated in said binder resin.

Optionally, the liquid crystal polymer pigment flakes, incorporated in a toner composition as described above, can be
20 added to a liquid carrier in a ratio ranging from 5 wt% to 60 wt%, thus forming a liquid developer, which can then be used as a liquid toner, as known to the skilled person. Preferred liquid carriers are aliphatic hydrocarbons, alicyclic hydrocarbons or polysiloxanes. Amongst them, paraffin solvents
25 and isoparaffin solvents are preferred.

For application by ink-jet printing, the composition also comprises an organic solvent, in order to adjust the viscosity value of the composition to be compatible with the chosen
30 printing process, as known to the skilled person.

For application by continuous ink-jet printing, the composition also comprises a conducting agent (salt), which must be soluble in the composition used. Such conducting agent is needed as technical requirement of this printing process,
5 as known to the skilled person.

In an alternative embodiment, the liquid crystal marking of the present invention is produced by applying to a substrate a coating composition comprising liquid crystal polymer pigment
10 flakes in a suitable binder.

The said liquid crystal pigment polymer flakes are preferably of cholesteric liquid crystal polymer, exhibiting light reflection at determined wavelengths (interference color), as
15 well as angle-dependent color shift. Such pigments are known to the skilled person from WO 2008/000755 A1 (and related documents), EP 1 213 338 B1; EP 0 685 749 B1; DE 199 22 158 A1; EP 0 601 483 A1; DE 44 18 490 A1; EP 0 887 398 B1, WO2006/063926, US 5,211,877, US 5,362,315, and US 6,423,246.

20 Suitable binders can be chosen from the vinylic resins, acrylic resins, styrene-maleic anhydride copolymer resins, polyacetal resins, polyester resins, fatty acid modified polyester resins and the mixtures thereof. The binder may
25 further be chosen from the UV curing monomers and oligomers, such as acrylates, vinyl ethers, epoxides and combinations thereof.

The marking is preferably applied by ink-jet printing. For a
30 reliable printing and acceptable print quality, the ink-jet equipment used must have a sufficiently large orifice (nozzle)

diameter. The nozzle diameter should be at least 10 times the mean diameter of the liquid crystal pigment polymer flakes. For example, for a mean flake diameter of 25 μm the nozzle diameter should be at least 250 μm . Systems providing said
5 characteristics are valve-jet printers, a particular form of drop-on-demand ink-jet printers.

In general, the method for authenticating an item or article carrying a marking according to the present invention
10 comprises the steps of a) providing an item or article carrying a marking according to the present invention, b) illuminating the marking on said item or article with at least one quality of light from at least one light source, c) detecting the said marking's optical characteristics through
15 the sensing of light reflected by the marking, d) determining the item's or article's authenticity from the detected optical characteristics of the marking.

The marking of the present invention can be authenticated
20 according to a first method by simple visual inspection under ambient light. To this aim, the background, on which the liquid crystal material is applied, must provide sufficient optical contrast, so as to allow the human observer to perceive the reflected color and the color shift of the liquid
25 crystal material. Depending on the background, part of the marking may remain virtually invisible to the unaided eye.

In a second method, the marking is authenticated under ambient light with the help of a passive detecting means such as an
30 optical filter. A preferred such passive detecting means is a left-handed or a right-handed circular polarizing filter, or a

juxtaposition of both. This allows determining the rotation sense of the helical pitch of the cholesteric liquid crystal material by determining the polarization state of the light reflected by the said material. Optionally, the polarization
5 filter can be combined with color filters, in order to reduce the spectral bandwidth to the spectral reflection band of the liquid crystal material, and hence to reduce background contributions. More than one optical filter may be used in conjunction.

10

In a third method, the marking is authenticated with the help of circular polarized light from at least one polarized light source. The liquid crystal material reflects differently light of different circular polarization; hence materials of left
15 and of right helical pitch can be distinguished by their respective response to circularly polarized light. The illumination of the marking by the polarized light source, as well as the observation of the reflected light from the marking, may optionally be performed through a color filter.
20 More than one polarized light sources may be used in conjunction.

In a fourth method, the marking is authenticated with the help of an electro-optical authentication device. In a first
25 embodiment, said device comprises at least one photocell, in combination with a circular polarization filter and/or with a circular polarized light source. In another embodiment said device comprises an electro-optic camera, such as a linear CCD sensor array, a 2-dimensional CCD image sensor array, a linear
30 CMOS image sensor array, or a 2-dimensional CMOS image sensor array, in combination with a circular polarization filter

and/or with a circular polarized light source.

Optionally, the circular polarization filter or the circular polarized light source in the above embodiments can be combined with color filters, to select a particular spectral domain and to enhance the contrast ratio of the light reflected from the liquid crystal material to the light reflected from the background.

10 The circular polarization filters can generally also be replaced by an electro-optic polarization switch. Such device is known in the art, e.g. from DE 102 11 310 B4, and allows to select one or the other circular polarization state by an applied corresponding voltage.

15

In all cases of cholesteric liquid crystal materials, the marking of the present invention is authenticated by verifying one or more of its characteristic properties, namely the circular polarization state and/or the viewing-angle dependent color of the reflected light from the marking. The polarized light source or the polarized light detection equipment or both may be chosen to operate in the visible, the infrared, or the UV region of the electromagnetic spectrum, or in a combination of these, according to the optical characteristics of the marking.

The marking of the present invention can be identified by reading the indicia it represents and by subsequently correlating the information so retrieved from the marking with information stored in a data base. In a particular embodiment, the information represented by the indicia of the marking is

encrypted, and said identification comprises the step of decrypting said information. Preferably, the indicia are read by an electro-optic camera, such as a CCD- or a CMOS-image sensor array.

5

In general, the method for identifying an item or article carrying a marking according to the present invention comprises the steps of a) providing an item or article carrying a marking according to the present invention, b) 10 illuminating the marking on said item or article with at least one quality of light from at least one light source, c) reading the indicia represented by the marking, deriving corresponding information, d) correlating the information retrieved from the indicia of the marking with information 15 stored in a data base, e) obtaining confirmation or denial concerning the item's or articles identity.

The identification of an item or article carrying a marking according to the present invention can be performed with the 20 same reading equipment configuration or assembly which is used for the authentication.

In a first embodiment the said indicia are represented by a 1-dimensional or a 2-dimensional barcode, and the image 25 retrieved by the electro-optic camera in digital form is analyzed using a corresponding algorithm. The information contained in the barcode is retrieved, if necessary, decrypted, and compared with information stored in a data base, hereby identifying the item, and optionally updating the 30 data base with supplementary information, e.g. about the item's history. The camera may be part of a reading device

equipped with own communication capabilities, or part of a communication device, such as a mobile phone, the retrieval of the information taking place using the mobile phone's internal resources. The data base may be either located in the communication device (built-in or exchangeable memory), or on
5 an external server reached via a communication network.

In a second embodiment the said indicia are represented by an alphanumeric code, and the image retrieved by the electro-optic camera (reading device) in digital form is analyzed
10 using a corresponding optical character recognition (OCR) algorithm. The information contained in the code is retrieved and compared with information stored in a data base, hereby identifying the item, and optionally updating the data base.
15 As in the first embodiment, the data base may be either located in the reading device (built-in or exchangeable memory), or on an external server reached via a communication network. The alphanumeric code can be printed using a standard font or a special machine identifiable font. Alternatively,
20 the alphanumeric code can be visually read and either sent via a communication system (e.g. Internet or SMS) to a data center for validation or checked against data provided with the item in form of a label, reference mark or another alphanumeric code.

25

The marking of the present invention, made of polymeric liquid crystal material having determined optical characteristics, can be used for the secure tracking and tracing of items, articles or goods with an individualized, counterfeit-resistant code for the secure tracking and tracing of said
30 items, articles or goods.

The application of an individualized code onto a good or item requires a variable information printing process. A preferred variable information printing process in the context of the present invention is chosen from the group of continuous ink-jet printing and drop-on-demand ink-jet printing; these printing processes allow for a rapid, non-contact application of said individualized code onto any kind of surfaces. Said individualized code allows the identification of each single item at a later stage of its life cycle.

In order to prevent the substitution of the original item by a counterfeit carrying a copy of said individualized code, said individualized code must be counterfeit-resistant. Counterfeit resistance can be provided through a particular security material having particular physical, preferably optical, properties; the said material can be either constitutive or incorporated in the marking. The particular security material can be a polymeric liquid crystal material having determined optical characteristics, or an additive selected from the group of the inorganic luminescent compounds, the organic luminescent compounds, the IR-absorbers, the magnetic materials, the forensic markers, and combinations thereof.

The marking of the present invention can be used on items or articles, such as value documents, banknotes, passports, identity documents, driving licenses, official permissions, access documents, stamps, tax stamps and banderoles (in particular for tobacco products and alcoholic beverages), transportation tickets, event tickets, labels, foils, packaging (in particular for pharmaceutical products), and in

general for marking spare parts and consumer goods (in particular to address liability issues).

The marking of the present invention, applied to items, goods, or articles is suitable for use in the secure tracking and tracing of such marked items, goods or articles. Such secure tracking and tracing of an item or article comprises noteworthy the first commutable steps of a) applying a marking according to the invention to the item or article to be traced; and b) storing information related to the marked item or article in a data base; as well as the second commutable steps of c) authenticating the item or article according to the authentication method disclosed herein; and d) identifying the item or article, according to the identification method disclosed herein, using the information previously stored in the data base. Optionally the data base may hereby be updated with new information elements related to the item or article.

The code applied to the item or good represents digital information, which is stored in a data base, in order to identify the item or good at a later stage. Said code may be encrypted, so as to protect the information it contains upon transmission from and to the data base. Said data base can be part of a data base management system. All kind of encryption algorithms are suitable, e.g. a public-private key of the RSA type.

Said data base may be a local data base, integrated into the authentication device. Alternatively, it may be a remote data base, linked to the authentication device through a wired or wireless connection. A local data base may also be updated

regularly from a remote server.

In a further aspect, the present invention provides for the application of the individual marking by a variable-
5 information printing process. Preferred is ink-jet printing, either using the continuous ink-jet, or the drop-on-demand (DOD) ink-jet or valve-jet printing process. Industrial ink-jet printers, commonly used for numbering and coding applications on conditioning lines and printing presses, are
10 particularly suitable. Preferred ink-jet printers are single nozzle continuous ink-jet printers (also called raster or multi level deflected printers) and drop-on-demand ink-jet, in particular valve-jet, printers.

15 To provide for an entirely covert and machine readable marking, nematic liquid crystal materials are used. To provide for an overt or semi-covert and machine readable marking, cholesteric or chiral-nematic liquid crystal materials are used.

20

Description of the Drawings

For a more complete understanding of the present invention reference is made to the detailed description of the invention and the attached drawings.

25

Fig.1 schematically depicts a cardboard packaging, e.g. a pharmaceutical packaging, carrying representative markings a), b), c) according to the invention, which are printed with liquid crystal material at different locations on said
30 cardboard packaging:

a) shows a Data Matrix code on a particularly dark colored

background, e.g. a black background;

b) shows a Data Matrix code on a background of mixed color, e.g. having dark and light colored parts;

c) shows a Data Matrix code on a white background.

5

Fig.2 shows images captured from an ECC200 data matrix code printed with UV-cured liquid crystal (LC) material on coated cardboard:

10 a) LC Data Matrix code retrieved from a black background, under right-circular polarized white light illumination, having a right-circular polarizing filter in front of the CMOS camera.

15 b) LC Data Matrix code retrieved from a black/white background, under right-circular polarized white light illumination, having a right-circular polarizing filter in front of the CMOS camera.

20 c) LC Data Matrix code retrieved from a black/white background, under right-circular polarized white light illumination, having no filter in front of the CMOS camera.

d) LC Data Matrix code retrieved from a black/white background, under unpolarized white light illumination, having no filter in front of the CMOS camera.

25 Detailed Description of the Invention

In a first embodiment, the marking of the present invention is made of a liquid crystal precursor material, which is applied in a liquid state to the surface of a substrate, and thereupon polymerized (cured) in the ordered liquid crystal state by 30 irradiation with UV light or with electron beam radiation, as known by the skilled in the art.

The liquid crystal material applied in this embodiment is thus a monomeric or oligomeric precursor of a liquid crystal polymer. Said precursor comprises at least one nematic liquid crystal monomer or oligomer, said monomer or oligomer having polymerizable groups. Suitable nematic liquid crystal monomers or oligomers are from the group of bisacrylates such as

benzoic acid 4-[4-[(1-oxo-2-propenyl)oxy] butoxy]-1,4-phenylene ester,

10 benzoic acid 4-[4-[(1-oxo-2-propenyl)oxy] butoxy]-, 2-methyl-1,4-phenylene ester,

benzoic acid 4-[4-[(1-oxo-2-propenyl)oxy] hexoxy]-, 2-methyl-1,4-phenylene ester,

15 benzoic acid 4-[4-[(1-oxo-2-propenyl)oxy] butoxycarboxy]-1,4-phenylene ester,

benzoic acid 4-[4-[(1-oxo-2-propenyl)oxy] butoxycarboxy]-, 2-methyl-1,4-phenylene ester, and the combinations thereof.

20 The nematic liquid crystal monomer or oligomer may be present in the precursor material in a range of 10% to 100% by weight.

In case the curing is performed by UV radiation, the precursor material comprises at least one photoinitiator system comprising at least one photoinitiator and optionally a stabilizer. Suitable photoinitiators can be chosen from the group of Irgacure (e.g. Irgacure 369, 651, 907 or 1300), Genomer (e.g. BP/EPD) or other free radical inducers.

30 Suitable stabilizers are Florstab UV-1 supplied by Kromachem, and Genorad 16 supplied by Rahn.

The photoinitiator may be present in the precursor material in a range of 0.5% to 5% by weight.

For obtaining cholesteric (i.e. twisted nematic) phases, said precursor further comprises at least one chiral dopant (chiral inducer). Suitable chiral dopants comprise the derivatives of isomannide and of isosorbide, such as

- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(acryloyloxyethoxy)benzoate),
- 10 (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(acryloyloxybutoxy)benzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(acryloyloxybutoxy)-2-methylbenzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
- 15 (acryloyloxybutoxy)-3-methoxybenzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(4'-(acryloyloxybutoxy)benzoyloxy)-3-methoxybenzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(acryloyloxy)-2-methylbenzoate),
- 20 (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(acryloyloxy)-3-methylbenzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(4-(acryloyloxy)butoxy)benzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
- 25 (acryloyloxy)-3,5-dimethylbenzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(4-(acryloyloxy)benzoyloxy)benzoate),
- (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(4-(4-(acryloyloxy)butoxy)benzoyloxy)benzoate),
- 30 (3R,3aR,6R,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(4-(4-(acryloyloxy)butoxy)benzoyloxy)-3-methoxybenzoate,
- (3R,3aR,6S,6aR) -hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-

(acryloyloxyethoxy)benzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (acryloyloxybutoxy)benzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 5 (acryloyloxybutoxy)-2-methylbenzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (acryloyloxybutoxy)-3-methoxybenzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (4'-(acryloyloxybutoxy)benzoyloxy)-3-methoxybenzoate),
 10 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (acryloyloxy)-2-methylbenzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (acryloyloxy)-3-methylbenzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 15 (4-(acryloyloxy)butoxy)benzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (acryloyloxy)-3,5-dimethylbenzoate),
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (4-(acryloyloxy)benzoyloxy)benzoate),
 20 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (4-(4-(acryloyloxy)butoxy)benzoyloxy)benzoate) and
 (3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-
 (4-(4-(acryloyloxy)butoxy)benzoyloxy)-3-methoxybenzoate),
 and combinations thereof.

25

The chiral dopant may be present in the precursor material in a range of 0.1% to 25% by weight.

The marking is preferably applied by ink-jet printing, either
 30 of the continuous ink-jet or of the drop-on-demand ink-jet type, preferably by single nozzle/ raster or by valve-jet printing. For application by ink-jet printing, the composition

must further contain a solvent, in order to adjust its viscosity to the low values required by the said printing processes. Typical viscosity values for ink-jet printing inks are in the range of 4 to 30 mPa.s at 25°C. Solvents, which can
5 be used are chosen from the group of the low-viscosity, slightly polar and aprotic organic solvents, such as methyl-ethyl-ketone (MEK), acetone, ethylacetate, ethyl 3-ethoxypropionate or toluene. Chlorinated solvents like dichloromethane, trichloromethane or trichloroethylene are
10 technically suitable, but not desirable in printing inks because of their toxicity.

The solvent is comprised in the ink-jet precursor material in a range of 10% to 95%, typically 55% to 85% by weight.

15

In the case of continuous ink-jet printing, the precursor material also comprises a dissolved conducting agent, typically a salt, such as lithium nitrate, lithium perchlorate, tetrabutylammonium chloride or tetrabutylammonium
20 tetrafluoroborate.

The salt is present in a concentration range of 0.1 to 5% by weight.

25 The precursor material preferably may further comprise security materials, which are present in low to moderate concentration, in order to increase the resistance of the marking towards counterfeiting. These security materials are selected from the group consisting of the inorganic
30 luminescent compounds, the organic luminescent compounds, the IR-absorbers, the magnetic materials, the forensic markers,

and combinations thereof. Concentration ranges are 0.01% to 5% for luminescent compounds, 0.1% to 10% for IR-absorbers or magnetic materials, and 0.001% to 1% for forensic marker materials.

5

The preferred cholesteric liquid crystal precursor material for carrying out the present invention using ink-jet printing equipment comprises a mixture of at least one nematic compound, at least one chiral inducer compound, an organic
10 solvent, and a photoinitiator.

Said nematic compound is preferably of the acrylic- or bis-acrylic type as disclosed in EP-A-0 216 712 and EP-B-0 847 432, US-B-6,589,445, which are herein included by reference.

15 The preferred amount of the nematic compound present in the cholesteric liquid crystal precursor mixture is from about 10 wt% to about 60 wt%, more preferably from about 10 wt% to about 45 wt%.

20 The preferred chiral inducers are selected from the derivatives of isosorbide and isomannide, disclosed in EP-B-0 739 403, GB-A-2 330 139, and US-B-6,589,445, which are herein included by reference. The amount of the chiral inducer present in the cholesteric liquid crystal precursor mixture
25 ranges from about 0.1 wt% to about 25 wt%, preferably from about 0.5 wt% to about 15 wt%.

The liquid crystal precursor material for producing a marking according to the present invention may further comprise dyes,
30 pigments, coloring agents, diluents, conducting salts, surface-active compounds, surface adhesion promoters, wetting

agents, defoamers, and dispersing agents.

The marking of the present invention is preferably applied in the form of indicia representing a unique 1-dimensional, a
5 stacked 1-dimensional, or a 2-dimensional barcode or matrix code. The symbology is preferably chosen among those used in the retail industry for the marking of commercial goods. These symbologies are internationally recognized standards, and the corresponding reading and decoding algorithms are known and
10 implemented in commercially available devices.

Suitable 1-dimensional and stacked 1-dimensional barcode symbologies are known to the skilled person and available under symbology names such as Plessey, U.P.C., Codabar, Code
15 25 - Non-interleaved 2 of 5, Code 25 - Interleaved 2 of 5, Code 39, Code 93, Code 128, Code 128A, Code 128B, Code 128C, Code 11, CPC Binary, DUN 14, EAN 2, EAN 5, EAN 8, EAN 13, GS1-128 (formerly known as UCC/EAN-128), EAN 128, UCC 128, GS1 DataBar formerly Reduced Space Symbology (RSS), ITF-14,
20 Pharmacode, PLANET, POSTNET, OneCode, MSI, PostBar, RM4SCC / KIX, or Telepen.

Suitable 2-dimensional barcode symbologies are known to the skilled person and available under symbology names such as
25 3-DI, ArrayTag, Aztec Code, Small Aztec Code, bCODE, Bullseye, Codablock, Code 1, Code, 16K, Code 49, Color code, CP Code, DataGlyphs, Datamatrix, Datastrip Code, Dot Code A, EZcode, High Capacity Color Barcode, HueCode, INTACTA.CODE, InterCode, MaxiCode, mCode, MiniCode, PDF417, Micro PDF417, PDMark,
30 PaperDisk, Optar, QR Code, Semacode, SmartCode, Snowflake Code, ShotCode, SuperCode, Trillcode, UltraCode, VeriCode, VSCode, WaterCode, and ECC200. This latter has a built-in

error correction code and is defined in international standard ISO/CEI 16022:2006.

Suitable font types for optical character recognition (OCR)
5 are known to the skilled person.

Fig.1 schematically shows a product packaging having a cholesteric liquid crystal marking of the present invention. The marking is present in the form of a ECC200 data matrix
10 code on the surface of said packaging. Data Matrix ECC200 is a public domain symbology. The marking can be applied to any desired position on the packaging. Thus it can be present wholly on a first background color (a), or partially, overlapping with a first background color and a second design
15 color motive present on the packaging (b), or wholly be present on a white or colorless region of the packaging (c).

The reading device for reading the marking of the present invention can be constructed on the basis of commercially
20 available barcode readers, in particular on the basis of hand-held CCD/CMOS-camera reading equipment and reading stations used in the retail industry. In case of an appropriate matching of the marking with the available (narrow-band) illumination, said reading equipment may be directly enabled
25 to read the liquid crystal codes.

In other cases, the reading device can be further adapted (enabled) so as to read the response of the specific security elements implemented in the marking. Correspondingly adapted
30 flat-bed scanners can also be used. CCD-camera based barcode readers are known to the skilled person and are produced by several industrial companies, such as AccuSort, Cognex, DVT,

Microscan, Omron, Sick, RVSI, Keyence, etc.

Said adaptation of the reading device may comprise the implementation of one or several optical filters chosen from the group of linear polarizing filters, right-circular polarizing filters, left-circular polarizing filters, electro-optic polarization filters, wave-plates, and spectrally selective color filters of any type, and combinations thereof. In a particular embodiment at least two different optical filters are used. Said adaptation may further comprise the implementation of one or several particular light sources chosen from the group of spectrally selective (i.e. colored) light sources, linear polarized light sources, left- and right-circular polarized light sources, and combinations thereof.

The light sources, however, can be chosen from ambient light, incandescent light, laser diodes, light emitting diodes, and all type of light sources having color filters. Said light sources may have an emission spectrum in the spectral domain of the visible light (400-700nm wavelength), the near optical infrared (700-1100nm wavelength), the far optical infrared (1100-2500nm wavelength), or the UV (200-400nm wavelength) region of the electromagnetic spectrum.

Said reading device is thus not only enabled to read the marking, but also to authenticate it as being made of the correct security material, i.e. comprising the required security elements. Said reading device delivers a digital information representative of the code which has been read, and pointing towards an entry in a data base corresponding to the item carrying the said marking and code.

Said digital information may be compared with information stored in the reading device or may be exchanged between the reading device and an external data base; the exchange can
5 take place in encrypted form, using e.g. a public/private encoding of the RSA type. Said exchange of information can take place by all kind of transmission means, e.g. wire-bound transmission, wireless radio link, infrared-link, etc... .

10 In the particular case where no chiral inducer is comprised in the precursor material, a nematic liquid crystal polymer is obtained. Such polymer is usually characterized by birefringence, i.e. the molecules in a printed layer are oriented in a predominant direction, and the component of the
15 refractive index along the molecular axes is different from the component of the refractive index orthogonal to the molecular axes.

Such nematic liquid crystal polymer can serve as a security
20 element, by using its birefringent properties, in which case it acts as a wave plate, able to transform linear polarization into circular polarization, or vice versa, at appropriate layer thickness. In case of a reflective substrate, the presence or absence of the applied liquid crystal polymer can
25 then be revealed with the help of a linear polarizing filter placed on top of the marking in appropriate orientation. In case of a transmissive substrate, either a reflector or a second polarizing filter needs to be applied at the back side of the substrate in order to render the marking visible.

30

In a second embodiment, the marking of the present invention

consists of pigment flakes of a liquid crystal polymer; said pigment flakes being comprised in a coating composition, applied to the surface of a substrate.

5 A preferred liquid crystal polymer pigment is of the type described in WO 2008/000755 A1, which is included by reference herein. A marking according to the present invention comprising such a pigment exhibits at least two reflection bands in the 200nm to 2500nm wavelength range.

10

Cholesteric liquid crystal polymer (CLCP) pigments useful to carry out the present invention are disclosed in EP 1 213 338 B1; EP 0 685 749 B1; DE 199 22 158 A1; EP 0 601 483 A1; DE 44 18 490 A1; EP 0 887 398 B1, and WO2006/063926. Reference is
15 also made to US 5,211,877, to US 5,362,315 and to US 6,423,246. Such particles have a thickness of the order of 1 to 10 micrometers and a flake size of the order of 10 to 100 micrometers, and are obtained by comminuting a corresponding liquid crystal polymer film. The preferred flakes for use in
20 the present invention have a thickness in the range of 1 to 10 micrometers, and an average flake diameter in the range of 20 to 50 micrometers.

Said coating composition comprises at least one binder as a
25 mandatory component; optionally, further pigments, dyes, extenders, additives, photoinitiators, etc. may be present, as required by the application process and the substrate to be marked. Preferred binders are chosen from the group of vinylic resins, acrylic resins, styrene-maleic anhydride copolymer
30 resins, polyacetal resins, polyester resins, fatty acid modified polyester resins and UV curing monomers and oligomers, such as acrylates, vinyl ethers, epoxides and

mixtures thereof.

Said coating composition may preferably comprise further security materials, which are present in low to moderate concentration, in order to increase its resistance towards counterfeiting. These security materials are selected from the group consisting of the inorganic luminescent compounds, the organic luminescent compounds, the IR-absorbers, the magnetic materials, the forensic markers, and combinations thereof. Typical concentration ranges are 0.01% to 5% for luminescent compounds, 0.1% to 10% for IR-absorbers or magnetic materials, and 0.001% to 1% for forensic marker materials.

To accommodate particular conditions, the coating composition for producing a marking according to the present invention may further comprise dyes, pigments, coloring agents, diluents, conducting salts, surface-active compounds, surface adhesion promoters, wetting agents, defoamers, and dispersing agents, as known in the art.

20

The authentication and identification of the liquid crystal marking according to the present invention requires a light source and must be done in one of the following ways:

- i) by illuminating the marking with circular or linear polarized light and detecting the marking's reflection;
- ii) by illuminating the marking with unpolarized (e.g. ambient) light and detecting the marking's reflection through a circular or linear polarizing filter,
- iii) by a combination of circular or linear polarized illumination and detection through a circular or linear polarizing filter.

The illumination of a marked item or article is thus performed by a light source chosen from unpolarized light sources, linear polarized light sources, left circular polarized light sources, and right circular polarized light sources.

In all cases, detection may be performed by eye or with the help of electro-optic detection equipment, such as a photocell, or a CCD or CMOS camera. The light sources and the detection may be made or chosen spectrally selective through the use of particular light emitters and/or color filters. The detection is preferably carried out in the visible region (400-700nm wavelength) of the electromagnetic spectrum.

In a particular embodiment the illumination of the marking for authenticating an item or article, is performed using at least two different light sources selected from non-polarized (randomly polarized) light sources, linear polarized light sources, left circular polarized light sources, and right circular polarized light sources.

Fig.2 shows images taken from ECC200 Data matrix codes printed with liquid crystal material on coated cardboard. These images clearly illustrate the advantage of using the polarizing properties of the liquid crystal material marking for the reading of the printed code on a clear or structured background. Most advantageous is a combination of polarized light for illumination and the use of a polarizing filter in front of the camera. All images were taken with the same light source and with the same camera settings, all in black and white mode, and with or without polarizing filters before the

light source and/or the camera. The images were digitally treated for maximum contrast and optimum brightness.

In a preferred option, the liquid crystal marking of the present invention is rendered visible under unpolarized (preferably ambient) light by a passive detecting means such as a linear or a circular polarizing filter. The marking can, however, also be identified and authenticated outside the visible spectrum (400-700nm wavelength), e.g. in the infrared region (700 to 2500nm wavelength), preferably in the near optical infrared (700-1100nm wavelength), in the far optical infrared (1100-2500nm wavelength) or in the UV (200-400nm wavelength) region of the electromagnetic spectrum, given that the marking has a reflection band in these regions.

The cholesteric liquid crystal polymer is, by its nature, a spectrally selective reflector whose reflection band can be tuned across part of the electromagnetic spectrum by an appropriate choice of its helical pitch. Said pitch noteworthy depends on the ratio of nematic precursor material to chiral inducer compound in the liquid crystal precursor, and on the temperature of polymerization. After polymerization, the helical pitch, and hence the reflection color of the material, remains fixed.

As known to the skilled person, low amounts of chiral inducer result in a low helical twisting and hence in a large helical pitch. Therefore, low amounts of the chiral inducer generate a reflection band of the resulting polymer at the long wavelength end of the spectrum, typically in the infrared or red region, whereas higher amounts of inducer generate a

reflection band of the resulting polymer at the short wavelength end of the spectrum, typically in the blue or UV region.

5 Attention must also be paid to the handedness of the chiral inducer, i.e. whether a determined inducer results in a left or in a right helical pitch, resulting in respective opposite circular polarization of the reflected light. Isomannide derivatives are known to induce the reflection of left
10 circular polarized light, whereas isosorbide derivatives are known to induce the reflection of right circular polarized light.

Hereafter is given a typical example of a cholesteric liquid
15 crystal polymer precursor composition, which can be applied by the continuous ink-jet printing process:

	MEK	55.7 wt%
	benzoic acid 4-[4-[(1-oxo-2-propenyl)oxy] butoxycarboxy]-, 2-methyl-1,4-phenylene ester	40.1 wt%
20	(3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(acryloyloxybutoxy)benzoate)	1.70 wt%
	Irgacure 907	1.30 wt%
	LiClO ₄	1.20 wt%

25 The following example is a typical cholesteric liquid crystal polymer pigment composition, which can be applied by the valve-jet (drop-on-demand) ink-jet printing process:

	Pioloform® BL18	5.0 wt%
30	MEK	64.6 wt%
	Diethylene glycol	10.0 wt%

Ethanol	8.0 wt%
LC polymer pigment	10.0 wt%
Byk®-430	1.5 wt%
Byk®-410	0.9 wt%

5

Pioloform® BL18 is a polyvinyl butyral resin with the CAS No. 63148-65-2 supplied by Wacker. Byk®-430 is a solution of modified urea supplied by Byk. Byk®-410 is a solution of high molecular urea modified polar polyamide supplied by Byk.

10

The following is an alternative example of a cholesteric liquid crystal polymer precursor composition, which can be applied by the valve-jet printing process:

MEK	83.0 wt%
benzoic acid 4-[4-[(1-oxo-2-propenyl)oxy] butoxy]-, 2-methyl-1,4-phenylene ester	14.7 wt%
(3R,3aR,6S,6aR)-hexahydrofuro[3,2-b]furan-3,6-diyl bis(4-(acryloyloxybutoxy)benzoate)	1.50 wt%
Irgacure 907	0.8 wt%

20

Based on the indications and exemplary embodiments given hereinbefore, the skilled person is enabled to derive further embodiments of the present invention.

Claims:

1. Marking for an item or article, said marking comprising
polymeric liquid crystal material having determined
5 optical characteristics which allow for its authentication
and reading by a machine, as well as its authentication by
the human eye, the marking being characterized in that it
is produced on a substrate by a variable information
printing process, and has the form of indicia representing
10 a unique code, allowing for its identification.
2. Marking according to claim 1, characterized in that at
least part of the marking is invisible to the unaided
human eye.
15
3. Marking according to one of the claims 1 to 2, wherein
said polymeric liquid crystal material is a cholesteric
liquid crystal material, exhibiting color and an angle-
dependent change of color.
20
4. Marking according to claim 3, wherein the cholesteric
liquid crystal material has a reflection band in the UV
spectrum corresponding to the 200 to 400nm wavelength
range.
25
5. Marking according to claim 3, wherein the cholesteric
liquid crystal material has a reflection band in the
visible spectrum corresponding to the 400 to 700nm
wavelength range.
30
6. Marking according to claim 3, wherein the cholesteric

liquid crystal material has a reflection band in the infrared spectrum corresponding to the 700 to 2500nm wavelength range, preferably in the infrared spectrum corresponding to the 700 to 1100nm wavelength range.

5

7. Marking according to one of the claims 4 to 6, wherein the cholesteric liquid crystal material has a second reflection band in the 200 to 2500nm wavelength range.

10 8. Marking according to one of the claims 1 to 2, wherein said polymeric liquid crystal material is a nematic liquid crystal material, exhibiting optical birefringence.

9. Marking according to one of the claims 1 to 8, wherein
15 said polymeric liquid crystal material comprises further security materials, selected from the group consisting of the inorganic luminescent compounds, the organic luminescent compounds, the IR-absorbers, the magnetic materials, and the forensic markers, and the combinations
20 thereof.

10. Marking according to one of the claims 1 to 9, wherein said substrate is selected from the group of reflecting substrates, colored substrates, and transparent
25 substrates.

11. Marking according to one of the claims 1 to 9, wherein said substrate is a patterned substrate, comprising at least two different surface areas, each selected from the
30 group of white surface areas, black surface areas, colored surface areas, reflecting surface areas, transparent

surface areas and combinations thereof.

12. Marking according to one of the claims 1 to 9, wherein said substrate carries indicia.

5

13. Marking according to one of the claims 1 to 9, wherein said substrate carries at least one security element, selected from the group consisting of the inorganic luminescent compounds, the organic luminescent compounds,
10 the IR-absorbers, the magnetic materials, the forensic markers and combinations thereof.

14. Marking according to claim 13, wherein said security element is present in the form of indicia.

15

15. Marking according to one of the claims 1 to 14, wherein said substrate is selected from the group consisting of the woven substrates, the non-woven substrates, the coated substrates, the papers, the cardboards, the wooden
20 substrates, the glass substrates, the ceramic substrates, the metal substrates, the plastic substrates, the textiles, and the leathers.

16. Marking according to one of the claims 1 to 15, wherein
25 said marking is produced by a process selected from the group of continuous ink-jet printing, drop-on-demand ink-jet printing, and laser printing.

17. Marking according to one of the claims 1 to 16, wherein
30 said indicia representing a unique code are chosen from the group of: 1-dimensional barcodes, stacked 1-

dimensional barcodes, and 2-dimensional barcodes.

18. Marking according to claim 17, wherein said 1-dimensional
5 barcode is selected from the group of Plessey, U.P.C.,
Codabar, Code 25 - Non-interleaved 2 of 5, Code 25 -
Interleaved 2 of 5, Code 39, Code 93, Code 128, Code 128A,
Code 128B, Code 128C, Code 11, CPC Binary, DUN 14, EAN 2,
EAN 5, EAN 8, EAN 13, GS1-128 (formerly known as UCC/EAN-
10 128), EAN 128, UCC 128, GS1 DataBar formerly Reduced Space
Symbology (RSS), ITF-14, Pharmacode, PLANET, POSTNET,
OneCode, MSI, PostBar, RM4SCC / KIX, or Telepen.
19. Marking according to claim 17, wherein said 2-dimensional
15 barcode is selected from the group of 3-DI, ArrayTag,
Aztec Code, Small Aztec Code, bCODE, Bullseye, Codablock,
Code 1, Code, 16K, Code 49, Color code, CP Code,
DataGlyphs, Datamatrix, Datastrip Code, Dot Code A, EZcode,
High Capacity Color Barcode, HueCode, INTACTA.CODE,
20 InterCode, MaxiCode, mCode, MiniCode, PDF417, Micro PDF417,
PDMark, PaperDisk, Optar, QR Code, Semacode, SmartCode,
Snowflake Code, ShotCode, SuperCode, Trillcode, UltraCode,
VeriCode, VSCode, WaterCode, and ECC200.
- 25 20. Marking according to one of the claims 1 to 19, wherein the
polymeric liquid crystal material is present in the form of
pigment flakes comprised in a suitable binder.
21. Marking according to claim 20, wherein the binder is chosen
30 from the group consisting of the vinylic resins, the
acrylic resins, the styrene-maleic anhydride copolymer
resins, the polyacetal resins, the polyester resins, the

fatty acid modified polyester resins and the mixtures thereof.

22. Marking according to claim 20, wherein the binder is chosen
5 from the group consisting of the UV-cure-able monomers and
oligomers of acrylates, vinyl ethers, epoxides and
combinations thereof.
23. Item or article carrying at least one marking according to
10 one of the claims 1 to 22.
24. Item or article according to claim 23, wherein said item
or article is chosen from the group of value documents,
banknotes, passports, identity documents, driving
15 licenses, official permissions, access documents, stamps,
tax stamps and banderoles, transportation tickets, event
tickets, labels, foils, packaging, spare parts, and
consumer goods.
- 20 25. Use of a marking according to one of the claims 1 to 22
for tracking or tracing an item or article.
26. Use according to claim 25, wherein said item or article is
chosen from the group of value documents, banknotes,
25 passports, identity documents, driving licenses, official
permissions, access documents, stamps, tax stamps and
banderoles, transportation tickets, event tickets, labels,
foils, packaging, spare parts, and consumer goods.
- 30 27. Method for producing a marking according to one of claims
1 to 22, said method comprising the steps of

- a) providing a substrate;
b) applying a liquid crystal precursor composition to said substrate, in the form of indicia;
c) hardening the applied composition in the ordered liquid crystal state.
- 5
28. Method according to claim 27, wherein the precursor composition comprises UV-cure-able reactive monomers or oligomers, and the hardening of the applied composition takes place by UV-curing.
- 10
29. Method for marking an item or article, said method comprising the steps of
- a) providing an item or article to be marked;
b) applying at least one marking according to one of the claims 1 to 22 onto the said item or article.
- 15
30. Method according to one of claims 27 to 29, wherein the unique code represented by the indicia is an encrypted information, the method comprising the step of encrypting said information.
- 20
31. Method for authenticating an item or article, said method comprising the steps of
- 25 a) providing an item or article carrying a marking according to one of the claims 1 to 22;
b) illuminating the marking on said article or item with at least one quality of light from at least one light source;
c) detecting the said marking's determined optical characteristics through the sensing of light
- 30

reflected by the marking;

- d) determining the item's or article's authenticity from the detected optical characteristics of the marking.

5

32. Method according to claim 31, wherein the marking comprises a cholesteric liquid crystal material, exhibiting spectrally selective, viewing angle-dependent light reflection, the reflected light having a particular sense of circular polarization.

10

33. Method according to one of claims 31 to 32, wherein said light source is a spectrally selective light source.

15 34. Method according to claim 33, wherein said light source is chosen from the group of ambient light, incandescent light, laser diodes, light emitting diodes, and the light sources having color filters.

20 35. Method according to one of claims 31 to 34, wherein the light source is chosen to emit in a spectral domain of the group consisting of the visible (400-700nm wavelength), the near optical infrared (700-1100nm wavelength), the far optical infrared (1100-2500nm wavelength) and the UV (200-
25 400nm wavelength) region of the electromagnetic spectrum.

36. Method according to one of claims 31 to 35, wherein said illuminating is performed by a light source chosen from the group consisting of the unpolarized, linear polarized, left circular polarized, and right circular polarized
30 light sources.

37. Method according to one of claims 31 to 36, wherein at least two different said light sources are used in conjunction.

5

38. Method according to one of claim 31 to 37, wherein said detecting is performed using at least one optical filter chosen from the group consisting of the linear polarizing, left circular polarizing, right circular polarizing
10 filters and the electro-optic polarization switches.

39. Method according to claim 38, wherein said optical filter is combined with a color filter.

15 40. Method according to one of claims 38 to 39, wherein at least two different said optical filters are used in conjunction.

20 41. Method according to one of claims 31 to 40, wherein said detecting is performed by eye.

42. Method according to one of claims 31 to 40, wherein said detecting is performed by an electro-optic detection equipment.

25

43. Method according to claim 42, wherein said electro-optic detecting equipment is chosen from the group consisting of the photocells, linear CCD image sensor arrays, 2-dimensional CCD image sensor arrays, linear CMOS image
30 sensor arrays, 2-dimensional CMOS image sensor arrays.

44. Method for identifying an item or article, said method comprising the steps of

- a) providing an item or article carrying a marking according to one of the claims 1 to 22;
- 5 b) illuminating the marking on said article or item with at least one quality of light from at least one light source;
- c) reading the indicia represented by the marking, deriving corresponding information;
- 10 d) correlating the information retrieved from the indicia of the marking with information stored in a data base;
- e) obtaining confirmation or denial concerning the item's or article's identity.

15

45. Method according to claim 44, comprising the further step of authenticating said item of article using the method according to one of claims 31 to 43.

20 46. Method according to one of claims 44 to 45, wherein the indicia are read with the help of an electro-optic image sensor array.

47. Method according to claims 46 wherein the electro-optic
25 image sensor array is chosen from the group consisting of the linear CCD image sensor arrays, 2-dimensional CCD image sensor arrays, linear CMOS image sensor arrays, and 2-dimensional CMOS image sensor arrays.

30 48. Method according to one of claims 44 to 47, wherein information about the item or article is stored in the

database.

49. Method according to one of claims 44 to 48, wherein the
information exchange with the database takes place in
5 encrypted form.

50. Method according to one of claims 44 to 49, wherein the
unique code represented by the indicia of the marking is
encrypted information, the method comprising the step of
10 decrypting said information.

51. Method for the secure tracking or tracing of an item or
article, using a marking according to one of the claims 1
to 22, comprising the first commutable steps of
15 a) applying a said marking to the item or article
according to one of the claims 27 to 30;
b) storing information related to the marked item or
article in a data base;
and the second commutable steps of
20 c) authenticating the item or article according to one
of the claims 31 to 43;
d) identifying the item or article, according to one of
the claims 44 to 50, using the information stored in
the data base;
25 and the optional step of
e) updating the data base with new information elements
related to the item or article.

52. Method according to claim 51, wherein said item or article
30 is chosen from the group of value documents, banknotes,
passports, identity documents, driving licenses, official

permissions, access documents, stamps, tax stamps and banderoles, transportation tickets, event tickets, labels, foils, packaging, pharmaceutical products, spare parts, and consumer goods.