

LINE OF SIGHT STABILIZATION SYSTEM

FIELD OF THE INVENTION

This invention relates to line of sight stabilization systems and particularly to systems for providing optical coupling between optical modules and light source and/or light detection modules.

5

BACKGROUND OF THE INVENTION

Line of sight stabilization systems are often used to conjugate and optically couple optical systems such as telescopes with light source modules and/or with light detection modules such as lasers and imagers commonly referred to herein as light
10 modules. Line of sight stabilization systems allow variable orientations of the line of sight of the light modules with respect to the direction of the principal optical axis of the light module.

One known arrangement for such line of sight stabilization is commonly known as the Coudé telescope arrangement illustrated for example in **Figs. 1A and 1B**. The
15 Coudé telescope arrangement includes a telescope mounted on a stabilization assembly to which a light module receiving or transmitting light to the telescope is attached. The telescope includes a fixed internal mirror intersecting its optical axis inclined with respect thereto. The internal mirror operates to reflect light propagation along the optical axis of the telescope towards a light port of the telescope located alongside its
20 optical axis (e.g. an eye piece can be installed in such a light port when the telescope is not mounted on the stabilization assembly). The stabilization assembly according to the Coudé arrangement includes a set of two gimbals connected to the body of the

- 2 -

telescope, allowing its rotation about a pitch and roll direction being respectively a direction perpendicular to the telescope optical axis and a direction perpendicular to the pitch direction. The light module is mounted outside the gimbals and a set of mirrors, located on the roll gimbal, are arranged to provide optical coupling between the light
5 port of the telescope and the light module.

Providing sustainable optical coupling between the telescope and the light module in various orientations of the telescope is obtained by setting the light port of the telescope in optical alignment with the pitch axis of the pitch gimbal such that the direction of light propagating therethrough is not affected by rotation of the telescope
10 about the pitch axis. Additionally, an optical alignment between an optical port of the light module and the roll axis of the roll gimbal is set such that the direction of light propagating from the mirrors on the pitch gimbal towards the optical port is not affected by rotation of the pitch gimbal about the roll axis. Accordingly, optical coupling between the light module and the telescope is maintained while the orientation of the
15 telescope can be changed relative to the light module.

Another example of a line of sight stabilization system is disclosed for example in US patent publication No. 2006/017816. In this publication, a line of sight stabilization system is described using two mirrors pivotally mounted to a fixed platform that can be used with existing imaging systems to provide pitch, roll, and yaw
20 compensation while maintaining image orientation. By deflecting only the photons, the inventive system avoids the need to stabilize the entire imaging sensor and optics system. The only mass to move is that of the two imaging system mirrors. By monitoring attitude changes via an inertial measurement system, platform positions can be estimated for subsequent image acquisitions, and efficient mirror positioning can
25 provide optimal image orientation and stabilization. This approach requires small motors with low torque, providing a less costly, lightweight, and small image orientation and stabilization system.

30 GENERAL DESCRIPTION

There is a need in the art for a novel line of sight stabilization system and method allowing small dimensions of the line of sight stabilization. Also, there is a need in the art for a compact line of sight stabilization system that is adapted for stabilizing

- 3 -

the line of sight of a light module (such as imager) being defined by an optical module (e.g. telescope/optical assembly) optically coupled with the light module. Moreover there is a need in the art for a line of sight stabilization system capable of reorienting the line of sight of the light module while not reorienting the light module.

5 The term *line of sight* (LOS) is used for the purposes of the present application to designate the direction to a region(s) of a scene or of environment that is (or can be) perceived/sensed/projected-on by the light module. When a light module is optically coupled with an optical module (e.g. via the line of sight stabilization system), its LOS is actually associated with the field of view (FOV) of the optical module (the LOS of
10 the light module is generally a direction within the FOV of the optical module) and is thus associated with the orientation of the optical module with respect to the scene/environment. The LOS of the light module is considered herein similar to the LOS of the stabilized optical system. Accordingly, the *orientation of the LOS* is considered herein as the direction/orientation of the line of sight with respect to the
15 environment/scene that is perceived/projected-on by the light module. To discriminate, the term *angular position* of the optical system/optical module is used herein to designate the relative angular position between the principal optical axis of the optical module and the principal optical axis of the light module.

Stabilization systems are widely used today in various applications to enable
20 orienting the LOS of light modules (such as a light source or light detector) while not requiring reorientation of the light module itself with respect to the environment. In many cases light modules are cumbersome or are mounted on a platform/ fixture while it is desirable to allow adjustable/variable orientation of the LOS of the light module that can be varied with respect to the platform/fixture on which the light module can be
25 fixed.

In some cases the LOS of the light module needs to be stabilized against movements/vibrations of the platform to which the light module is mounted and in order to compensate for such movements and to retain stable line of sight of the light module. For example stabilizing the LOS of the light module may be used to maintain a stable
30 image on an imager of the light module; or to stabilize the orientation of a light beam originating from a light source of the light module and emanating from the optical module. Stabilization of the LOS can be achieved by varying the angular position

- 4 -

between the light module and the optical module such as to compensate for movements of the light module and/or of the platform to which it is mounted.

Alternatively or additionally, in some cases the LOS of the light module needs to be varied independently of the orientation of the light module, e.g. the light module
5 may be fixed to a platform which may be moving or not with respect to the environment while the LOS of the light module/optical system can be directed to different orientations to capture different regions of the environment. This permits directing/scanning/projecting light to/from the different regions of the environment by controlling the relative angular position between the optical module and the light
10 module and without necessitating reorientation of the light module itself. Accordingly it allows exposing the optical module to a broader view angle without redirecting it.

One of the deficiencies of known line of sight stabilization systems is that such systems are typically large and/or cumbersome and substantial space/volume is required for their accommodation. For example, line of sight stabilization systems in which the
15 entire optical system (e.g. including the light module/imager and the optical module/telescope) is mounted on gimbals typically include sufficiently large gimbals capable for carrying the entire optical system. Moreover such line of sight stabilization systems and also line of sight stabilization systems in which only the optical module is mounted on the gimbals generally utilize two axis gimbals allowing rotation and
20 orientation of the line of sight about two axes. Accordingly the volume required for accommodation of such line of sight stabilization systems should be large enough to allow rotation of the entire optical system (or of at least the optical module in the latter case) about at least two rotation axes. This restricts use of such stabilization systems for controlling the LOS of optical devices mounted on small platforms such as
25 helmet/head-set and small aerial platforms.

Moreover, another deficiency of many of the known line of sight stabilization systems is that utilizing such stabilization systems for varying the orientation of the LOS of the light module (which is optically coupled to the stabilization system), often effects a twist in the orientation of a light beam with respect to its direction of
30 propagation as it passes through a designated optical path at the stabilization system. Accordingly, in certain cases the light module includes an imager module; variation of the LOS captured by the imager may also cause rotation of the image about an axis perpendicular to the imaging screen/sensor of the imager (on/by which the image is

formed). Additionally when the light module includes a light source generating light beam having a non isotropic cross-sectional structure, variation of the LOS of the light source (toward which the light beam is directed) would also affect in such cases the orientation of the cross-sectional structure of the light beam.

5 Many techniques following the Coudé approach utilize an angular rotation about a combination of the roll axis and additional axis (e.g. pitch or yaw). The roll axis is considered herein as an axis being parallel to nominal direction of the optical axis of the optical module. However, resorting to varying the relative angular position between the optical system and the light module about the roll axis, effects a twist in the orientation
10 of the light beam as described above.

The inventors of the present invention have found that a line of sight stabilization system having substantially smaller dimensions and smaller form factor can be obtained by utilizing a single external axis gimbal (i.e. located outside the optical module) and a rotatable mirror (also referred to as internal mirror). The internal mirror
15 is located within the optical module intersecting its optical path and is mounted for rotation about an axis perpendicular thereto (e.g. mounted on an internal gimbal/rotation-axis located within the optical module); and the single external axis gimbal interconnects the optical system and the light module and allows relative rotation between them about an axis perpendicular to both the optical axis of the optical
20 system and also perpendicular to the rotation axis of the internal mirror.

The configuration of the line of sight stabilization system according to the invention allows a small form factor of the system to be achieved which is advantageous in many applications, such as head mounted imagers and missile technology. The small form factor is, *inter alia*, achieved according to the invention by
25 utilizing only one gimbal that is located externally to the optical system and that permits orientation of the optical module about only one axis. Small form factor is therefore obtained because the single external gimbal (external to the optical system) by itself occupies less space than the conventional configuration in which two external gimbals are used for mounting the optical system. Also since the single external gimbal
30 according to the invention permits reorienting the optical system with respect to only one rotation axis (e.g. the pitch or yaw axes), the effective volume that is required to accommodate the optical system in its various possible orientations is reduced. Reorienting the line of sight about a first axis is provided utilizing the internal mirror

- 6 -

which might be entirely accommodated within the optical system and which thus does not require any additional space for its accommodation. The mirror is rotatable about an axis perpendicular to that of the gimbal's axis such as to provide reorientation of the line of sight about an axis perpendicular to that provided by the external gimbal on which the optical system is mounted. For example if the gimbal allows orienting the optical system about the yaw axis, the internal mirror is rotatable about the pitch axis.

Another advantage of the line of sight stabilization technique of the present invention is that it allows obtaining line of sight stabilization in a manner that does not affect the orientation/rotation of the image about the roll axis. This is based on the understanding that varying the relative angular position between the light module and the optical system about any two rotation axes (Pitch & Yaw; or Pitch & Roll; or Yaw & Roll) allows reorienting the LOS of the optical module to any direction within a visual sphere.

It should be noted that the principles of the present invention are suitable for use in any electromagnetic radiation generating/directing/detecting system, where the spectral range of the radiation is not limited to that typically termed "optical". More specifically, the invention is used with optical systems, and is therefore described below by the commonly used terminology. However, in the scope of the present invention the term light should be construed in its broadest interpretation as relating to electromagnetic (EM) radiations in various wavelength regimes and may include for example electro-magnetic radiation in the visible regime (visible light), the infra-red (IR) regime (e.g. near-, mid- and far- IR regimes) and ultra violet regime as well as EM radiation in the radio frequency (RF) and microwave regimes. Accordingly the terms optics, optical elements and the like should be interpreted as any elements/modules which are capable of manipulating/affecting the propagation of light in its various regimes. Optics and optical elements may for example include diffractive/refractive/reflective elements such as conventional mirrors and/or lenses. Alternatively or additionally the terms optics, optical elements may also include other types of elements (e.g. electronic or electro-optic elements) which are capable of manipulating the direction of EM radiation in the desired wavelengths for example by induction of suitable electromagnetic fields along the optical path of radiation propagation.

Hence, according to a broad aspect of the present invention, there is provided an optical system including a light module, an optical module defining an optical axis and

- 7 -

optically coupled with the light module, and a stabilizer assembly including an *internal* radiation deflector (e.g. mirror) that is located on the optical axis of the optical module in an optical path of light propagating therethrough. The internal mirror is mounted for rotation about a first rotation axis interconnecting the optical module and the *internal* mirror and being substantially orthogonal to the optical axis of the optical module.

The internal mirror is generally located internally to the optical module and is configured and operable to provide optical coupling between at least a section of the optical path of the optical module and an optical path of the light module. The first rotation axis is internal to the optical module and is configured for providing for relative rotation between the internal mirror and the optical module. Such rotation of the internal mirror varies with the section of the optical path of the optical module which is coupled with the optical path of the light module and thereby affects a variation of the direction of the line of sight of the light module while not affecting a change to the orientation and/or to the angular position between the light- and the optical- modules.

It should be understood that the configuration of the stabilized optical system of the invention allows stabilizing the line of sight of the light module in the direction of the first rotation axis. This can be achieved by rotation of the internal mirror about the first rotation axis in a direction opposite to the direction in which the orientation (rotations) of the stabilized optical system is changed with respect to an axis parallel to the first rotation axis, i.e. compensation to a rotation of the optical system about the first rotation axis in the first direction can be compensated by counter (opposite) rotation of the internal mirror. This allows stabilizing at least one of an image or a light beam formed by the light module.

Line of sight stabilization in a second direction is achieved, according to some embodiment of the invention, by configuring the stabilizer assembly to include a gimbal assembly including an external gimbal that is interconnected between the optical module and the light module. The external gimbal is configured to provide rotation of the optical module, with respect to the light module, about a second rotation axis (the second rotation axis being typically orthogonal to both the optical axis of the optical module and to the first rotation axis and is at least non parallel thereto). Compensation for rotation of the stabilized optical system in a direction parallel to the second rotation axis is therefore possible by applying counter (opposite) rotation to the optical module, about the second rotation axis) with respect to the light module. This allows stabilizing

the line of sight of the light module in this direction and to thereby stabilize at least one of an image or a light beam formed by the light module.

It should be understood that alternatively or additionally according to some embodiments of the invention, the internal mirror can be oriented with respect to two rotation axes. For example, the internal mirror can be mounted on a rotation mechanism such as a spherical bearing allowing its orientation of be varied with respect to two axes (i.e. being the first and second axes) that are not parallel to the optical axis of the optical module.

Accordingly, in these embodiments, line of sight stabilization with respect to these two axes can be obtained by only reorienting the internal mirror about these two axes and without utilizing any external gimbal. Accordingly, line of sight compensation is performed, internally to the optical module, in two directions. This allows maintaining a fixed angular position between the optical module and the light module (thus obviating a need for the external gimbal). Also such configuration further reduces the form factor (the size/dimensions) of the stabilized optical system as well as its weight. In this regard, it should also be understood that in these embodiments, compensation for changes of the orientation of the stabilized optical system with respect to both the first and the second rotation axes is performed in a manner that is similar to the manner in which line of sight compensation is performed with respect to the first rotation axis, as described above and also further below with regard to embodiments in which the internal mirror is rotatable only with respect to the first rotation axis.

It should be noted that by utilizing an external gimbal, the angular position (the relative orientation between the optical module and the light module may be changed within an angle of at least 160° with respect to the second rotation axis. Accordingly it allows changing the orientation of the line of sight of the light module by the same angle (160°) or above with respect to the second rotation axis. Changing the orientation of the line of sight (LOS) of the light module by rotating the internal mirror about the first rotation axis (and possibly also about the second rotation axis) allows varying the line of sight (LOS) orientation within an angle of about 90° and more with respect to the first axis (and respectively also with respect to the second axis in embodiments in which the internal mirror is rotatable about this axis).

It should be noted that according to some embodiments of the invention the first rotation axis corresponds (e.g. is parallel) to the pitch rotation axis of the optical

module. The second rotation axis corresponds to a yaw axis of the optical module. It should also be noted that the terms rotation axis (e.g. first and second rotation axes) generally designate virtual axis of rotation, not necessarily the physical rotation mechanism associated therewith (which may be implemented by various elements such as a spherical bearing an actual axis/shaft etc.).

According to some embodiments of the invention, in the stabilized optical system, the optical module includes a telescopic mirror arrangement including at least primary and secondary mirrors arranged such that their respective optical axes substantially coincide with the optical axis of the optical module. The internal mirror is located/mounted for intersecting a section of the optical path of the optical module that is defined by the secondary mirror. The internal mirror is, in this case, arranged to optically couple that section of the optical path with an optical path of the light module. Accordingly, rotation of the internal mirror with respect to the telescopic mirror arrangement varies a location of a region on the secondary mirror that is optically coupled with the optical path of the light module thereby varying the section of the optical path coupled with the optical path of the light module. Allowing the mirror to rotate about two rotation axes (e.g. utilizing spherical bearing) allows utilizing the movement of the internal mirror to stabilize the line of sight in two directions. Alternatively, by mounting the mirror for rotation only about a single axis (the first rotation axis) allows stabilizing the line of sight in one direction by utilizing the mirror (stabilizing the line of sight in another direction can be obtained by an external gimbal, as described above).

It should be understood that in the various embodiments of the invention the light module may include one or more light sensors (e.g. one or more imaging sensors having multiple light sensitive pixels). The one or more light sensors may include light sensors sensitive to light in two or more different spectral ranges (e.g. light sensors sensitive to light the IR and the visible spectral ranges respectively). In such an embodiment, the light module may include one or more wavelength selective splitters (dichotic mirrors) configured for spatially separating light, arriving from the optical module, into at least two light components and directing the two components to the different light sensors. In cases where the light module includes light sensor(s), the internal mirror is configured and operable to collect light portion(s) propagating thereto

- 10 -

from a certain section of the optical path of the optical module and to direct the collected light portion to the light module.

Alternatively or additionally, according to some embodiments of the invention, the light module includes one or more sources of EM radiation (light). The optical module is then optically coupled with the EM radiation source(s) for collecting and directing an EM radiation beam emitted therefrom. The stabilizer is then configured to enable directing the EM radiation beam to various directions with respect to the light module. EM radiation source(s) may include for example a laser source (in which case the optical module includes an arrangement of optical elements adapted for directing electromagnetic radiation in wavelength range of the laser source) and/or it may include a source of radio frequency (RF) radiation in which case the optical module may include an arrangement of elements adapted for directing electromagnetic radiation in the RF regime such as an arrangement of one or more antennas.

It should be noted that generally the light module includes one or more light guiding elements that are configured and operable to define an optical path of the optical module and to provide optical coupling between a light sensor or light source of the light module and the internal mirror. Such light guiding elements may include for example light deflector(s) (mirrors), lenses, waveguides and also other optical elements. The light guiding elements are arranged and are configured and operable for providing optical coupling between the internal mirror and at least one of a light sensor and light source of the light module while the internal mirror and/or the optical module are in various angular positions with respect to the light module.

According to some embodiments of the present invention the stabilized optical system also includes a stabilization control module. The stabilization control module includes at least a first actuation unit connected to the first rotation mechanism associated with the internal mirror (e.g. to the first rotation axis) and configured to actuate a first relative rotation between the optical module and the *internal* mirror. The first relative rotation may be restricted to rotation about the first rotation axis (in cases where the internal mirror's rotation is restricted to one direction) or it may be a rotation with respect to any one or both of the first and second rotation axes (e.g. in cases where the internal mirror is mounted on a spherical bearing). Optionally, in cases where the external gimbal is used for providing rotation of the optical module about the second rotation axis, the stabilization control module includes also a second actuation unit that

- 11 -

is connected to the external gimbal. The second actuation unit is configured to actuate a second relative rotation between the optical module and the light module about the second rotation axis. Additionally, the stabilization control module includes a control unit that is connected to the first and second actuation units and adapted to be responsive to signals, indicative of rotation rates of the stabilized optical system, to operate at least one of the first and actuation units to perform at least one of the first and second relative rotations and to thereby compensate for changes in the orientation of the stabilized optical module (for the rotation rates) and to thereby stabilize the line of sight of the stabilized optical system.

10 According to a further embodiment of the invention, the stabilized optical system also includes a rotation rate measurement system that is connectable to the control unit and is configured and operable for measuring the rotation rates of the stabilized optical system with respect to at least one of the second and the first rotation axes, and generating the signal indicative of the rotation rates.

15 It should be noted that the stabilized optical system may operate as a light source and/or light detector and may be adapted to function for light projection, for imaging and/or as a light transceiver e.g. for operating as a radar. In the former case, the optical module may include, for example, conventional lenses/mirrors while in the latter case it may alternatively or additionally include an array of antennas that are electronically and spatially arranged to define an optical path of light propagation therefrom and/or light reception thereby. Accordingly, the light module may include any one of an electromagnetic radiation source(s) (e.g. a laser source/ RF source) and may also, alternatively or additionally, include one or more light sensitive elements/sensors such as a light intensity/chrominance detector, quadrant detector and imaging
25 sensor(s)/detector(s).

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the invention and to see how it may be carried out in practice, embodiments will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Figs. 1A and 1B illustrate schematically top and perspective views of a Coudé telescope arrangement;

- 12 -

Figs. 2A and 2B illustrate schematically side and perspective views of a stabilized optical system **200** according to the invention allowing line of sight optical stabilization; and

Fig. 3 is a block diagram showing stabilized optical system **200** according to
5 another example of the invention.

DETAILED DESCRIPTION OF EMBODIMENTS

Figs. 1A and 1B illustrate schematically top and perspective views of an example of a known arrangement of a line of sight stabilization system commonly
10 known as the Coudé telescope arrangement **100**. The Coudé telescope arrangement **100** includes a mirror telescope **110**, a light source unit **130** (or an imaging unit) and gimbals set **120** with two gimbals **122** and **124** on which the mirror telescope **110** is mounted. The two gimbals **122** and **124** allow rotation of the mirror telescope **110** with respect to the light source unit **130** about pitch and roll rotation axes in a pitch over roll
15 configuration. The pitch and roll rotation axes are respectively an axis perpendicular to the principal optical axis **OX** of the mirror telescope **110** and an axis which is generally parallel to the nominal direction of the optical axis **OX** of the mirror telescope **110**. A set of mirrors **132** is arranged with fixed positions and orientation with respect to the light source **130** and is configured for collecting light from the light source **130** and
20 directing that light towards a mirror **112** of the mirror telescope **110** which is located intersecting the optical axis **OX** of the mirror telescope **110** with fixed position and orientation with respect to the mirror telescope **110**.

Reference is made to **Figs 2A and 2B** illustrating schematically side and perspective views of a stabilized optical system **200** according to the present invention.
25 The stabilized optical system **200** includes a light module **230**, an optical module **210**, optically coupled with the light module **230** and a stabilizer assembly **220**.

The stabilizer assembly **220** also includes an internal light deflector **222** (e.g. internal mirror) that is mounted within the optical module **210**, therewithin, intersecting an optical axis **OX** of the optical module **210**. The internal mirror **222** is pivotally
30 mounted to the optical module **210** via a first rotation mechanism **FRM** (e.g. a shaft, a bearing or other mechanism) allowing rotation of the internal mirror **222** about a first rotation axis **FRX** which is perpendicular to the second rotation axis **SRX** and to the

optical axis **OX** of the optical module **210**. The stabilizer assembly **220** interconnects the optical module **210** and the light module **230** via a second rotation mechanism **SRM** (generally gimbal, e.g. implemented as a shaft, a bearing or other mechanism) which is configured and operable to change the relative angular position between the light
5 module **230** and the optical module **210** with respect to a single rotation axis referred to herein as a second rotation axis **SRX**. It should be noted that generally the second rotation axis **SRX** is associated with a gimbal (e.g. a rotation mechanism) that is external to the optical module **210**. The first rotation axis **FRX** is located according to the present invention internally to the optical module **210** thus allowing accommodation
10 of the stabilized optical system **200** within smaller spaces/enclosures.

The optical module **210** is associated with a certain field of view (FOV) designating the extent (region/area) of the observable world that is "seen"/"captured" by the optical module **210**. The optical axis **OX** is an axis traversing through the optical module towards the center of its FOV and designates the general direction of light
15 propagation through an optical path **OP** of the optical module **210**. The light module **230** is associated with an optical path **OPL** which is optically coupled with a part/portion/section of the optical path **OP** of the optical module **210** via the internal light deflector **222**. A line of sight (LOS) of the light module **230** is generally associated with the FOV "seen" by the optical module **210** and with the part/portion/section of the
20 optical path **OP** of the optical module **210** which is optically coupled to the optical path **OPL** of the light module **230**.

To this end it should be understood that the light module **230** is associated with a line of sight (LOS) designating the principal direction (the direction within the FOV of the optical module **210**) which is "seen"/"captured" by the light module **230**. For
25 example the **LOS** of the light module **230** designates the direction from the stabilized optical system **200** to the region of the environment captured at the center of an image formed on an image sensor of the light module **230**, or alternatively it designates the direction in the environment towards which a chief beam that emanates from the light module **230** is directed by the optical module **210**.

30 The **LOS** of the light module **230** can be controlled according to the invention by utilizing two mechanisms, **SRM** and **FRM**, respectively allowing to shift/rotate the **LOS** about two perpendicular directions. It should be also noted that the first and second rotation mechanisms **FRM** and **SRM** may include or may be associated with

- 14 -

respectively first and second actuators such as motors (not specifically shown) that are arranged on the stabilizer assembly. The first and second rotation actuators are respectively associated with / connected to the first and second rotation axes **FRX** and **SRX** and are configured and operable for inducing rotations between the optical module
5 **210** and the internal mirror **222** and between light module **230** and the optical module **210**. Such rotations are induced, for example, in response to control signals transmitted/fed to the rotation actuators.

For clarity and without loss of generality, the two perpendicular directions about which rotation is provided by the two rotation mechanisms (**FRM** and **SRM**) are
10 referred to herein respectively as the elevation direction (associated with the elevation angle of the **LOS** with respect to the first rotation axis **FRX**, e.g. pitch rotation axis) and the heading direction (associated with the heading angle of the **LOS** with respect to the second rotation axis **SRX**, e.g. yaw rotation axis). The first rotation mechanism **FRM** implements/allows rotation of the internal mirror **222** about the first rotation axis **FRX**
15 within a predetermined angular range with respect to the optical module **210**. Accordingly, the first mechanism **FRM** permits shifting the elevation angle of the **LOS** of the light module **230** with respect to the **FOV** of the optical module **210** without movement/rotation of the optical module **210** in this direction. The second mechanism **SRM** implements rotation of the optical module **210** (together with the internal mirror
20 **222** mounted thereon) about the second rotation axis **SRX** and thus allows shifting the heading direction of the **FOV** of the optical module **210** in that direction (the **LOS** of the light module **230** inherently rotates in that direction together with the **FOV**).

More specifically, in the present example, the internal light deflector **222** is arranged and configured for optically coupling at least a portion of the optical path **OP**
25 of the optical module **210** with an optical path **OPL** of the light module **230** (or alternatively with an optical pass that is defined by the stabilizer assembly **220** which is not specifically illustrated in the present example). The internal mirror **222** is located at the intersection of the first and second rotation axes **FRX** and **SRX** and the optical axis **OX** of the optical module **210** (about which the optical path **OP** of the optical module
30 **210** is defined). The internal mirror **222** and the optical module **210** are rotatable together about the second rotation axis **SRX** for shifting thereby the orientation of the line of sight of the light module with respect to the second rotation axis **SRX** (the first rotation axis **FRX** is maintained perpendicular to the axes **SRX** and **OX** while the

optical module **210** is in various angular positions with respect to the light module **230**). Rotation of the optical module **210** about the second rotation axis **SRX** allows changing the orientation of the **LOS** of the light module within an angle of about 160° or more with respect to the second rotation axis.

5 Changing the orientation of the line of sight **LOS** of the light module **230** with respect to the first rotation axis **FRX** is achieved by changing the orientation of the internal mirror **222** about the axis **FRX** with respect to the optical module **210**. Rotating the internal mirror **222** about the first rotation axis **FRX** to different angular positions, results in optically coupling, to the optical path **OPL** of the light module **230**, of
10 different directions /regions of the optical path **OP** of the optical module **210**. Consequently, while the internal mirror **222** is in different positions about the first rotation axis, light propagating respectively through different cross-sections of the optical path **OP** of the optical module **210** is coupled to the optical path **OPL** of the light module **230** and/or vice versa, light portions which propagated through the optical
15 path **OPL** of the light module **230** are coupled to the optical path **OP** and are directed to respectively different directions within the field of view **FOV** of the optical module **210**. Hence, the direction of the **LOS** of the light module **230**, which is bounded within the **FOV** of the optical module **210**, is changed when the orientation of the internal mirror **222** about the first rotation axis **FRX** is varied. Such rotation of the internal
20 mirror **222** allows changing the orientation of the **LOS** of the stabilized optical system **200** within an angle of 90° or more with respect to the first rotation axis **FRX**.

As a result of the above described configuration of the stabilizer assembly **220**, while changing the respective angular position between the optical module **210** and the light module **230** by reorienting the optical module **210** with respect to the second
25 rotation axis **SRX**, optical coupling between of the optical path **OP** of the optical module **210** and the optical path **OPL** of the light module **230** is maintained. This is because the internal mirror **222** rotates together with the optical system **210** about the second rotation axis **SRX** and because the internal mirror **222** intersects both the optical axis **OX** of the optical module **210** and the second rotation axis **SRX**. Accordingly,
30 since such optical coupling is maintained, changing the angular position allows changing the orientation of the line of sight **LOS** of the light module **230** with respect to the second rotation axis **SRX** without changing the orientation of the light module **230** itself (i.e. by changing the respective angular position between the light module **230** and

- 16 -

the optical module **210**). Alternatively or additionally, changing the angular position while maintaining the optical coupling also allows to maintain a stable line of sight **LOS** while compensating for changes in the orientation of the light module **230** with respect to the second rotation axis **SRX** (and/or also compensating for movements of the light module **230** in a direction perpendicular to the second rotation axis **SRX**) by affecting counter changes to the angular position.

Also, the internal mirror **222** is configured and operable for optically coupling of light portions from a certain cross-sectional region of the optical path **OP** with the optical path **OPL** of the light module **230**. For example, the internal mirror **222** collects light from propagating there-towards from a cross-sectional region of the optical path **OP** and directs the collected light towards the light module **230** and vice versa when light is propagated in the opposite direction. Rotation of the internal mirror **222** about the first rotation axis **FRX** varies the cross-sectional region of the optical path **OP** which is optically coupled with the optical path **OPL** of the light module **230** and thus varies the direction of the **LOS** of the light module **230** in this direction while not changing the direction of the optical axis **OX** of the optical module **210**. Hence, rotation of the internal mirror **222** about the first rotation axis **FRX** allows selectively coupling different regions of the **FOV** of the optical module **210** to the light module **230** (to the optical path **OPL**) and thus the **LOS** of the light module is changed. This allows changing the orientation of the **LOS** of the light module **230** with respect to the first rotation axis **SRX** neither changing the orientation of the light module **230**, nor the orientation of the optical module **210**.

Line of sight stabilization (for stabilizing an image or a light beam) can be implemented according to the invention by providing compensation to vibrations/rotations of the optical system **200** about axes parallel to the second and first rotation axes **SRX** and **FRX**. Compensating for such rotations of the optical system **200** is performed by inducing respective counter rotation of the optical module **210** and the internal mirror **222** about the second and first rotation axes **SRX** and **FRX**. Rotating the internal mirror **222** about the first rotation axis **FRX** allows compensating for rotations/vibrations of the stabilized optical system **200** about an axis parallel to the first rotation axis **FRX** and counter rotation of the optical module **210** about the second rotation axis **SRX** provides compensation for rotation/vibration of the stabilized optical system **200** about an axis parallel to the second rotation axis **SRX**. This enables

- 17 -

provision of stabilized image on imager unit(s) **IM1** and **IM2** of said light module **230** and also allows stabilizing a light beam emanating through the optical module **210**, from light sources (not shown) of the light module **230**.

As was also noted above, one advantage of the configuration of the stabilizer assembly **220** according to the invention is that it enables accommodating the entire stabilized optical system **200** within a relatively small volume, e.g. within a small enclosure. This is because the stabilizer assembly **220** according to the invention may include gimbals assembly **225** having only a single external axis (being the second rotation axis **SRX**) which allows relative rotation between the optical module **210** and the light module **230** only with respect to that single axis. Orientation of the line of sight of the light module about an axis perpendicular to that single axis (i.e. about the first rotation axis **FRX**) is obtained by rotation of the internal mirror. Accordingly, less space is required for the accommodation of the stabilized optical system **200** since single axis gimbals generally require less space for their accommodation than multi-axes gimbals and because utilizing such a gimbal assembly restricts the angular position of the optical module **210** to rotate about only one axis (**SRX**).

Another advantage of the stabilizer assembly **220** of the invention stems from the fact that the relative orientations of light with respect to its propagation direction is maintained constant in all possible angular positions between the light module **230** and the optical module **210**, i.e. changing the angular position between the light module **230** and the optical module **210** does not effect a rotation (twist) of the light about its propagation direction. Accordingly, when the light module includes an imager that captures an image of the light from the optical module, the orientation of the image (with respect to the axis perpendicular to the image surface) is maintained constant during variation of the respective angular position between the light module **230** and the optical module **210**. This is different and advantageous over other stabilization techniques such as the Coudé technique in which the relative orientation between the optical module and the light module about a roll axis perpendicular to the light module effects a rotation of the image about an axis perpendicular thereto.

Preferably according to the present invention, the stabilizer assembly **220** is configured and operable to change the orientation of the optical module with respect to the light module about two axes orthogonal to the nominal line of sight of the optical module, perpendicular to the roll axis **RRX** of the system. To this end, the roll rotation

- 18 -

axis of the stabilized optical system **200** is an axis designating the nominal direction to which the optical module is directed. The second and first rotation axes, **SRX** and **FRX**, are two axes perpendicular to the roll axis **RRX** and to each other.

Typically when the stabilized optical system is installed on a platform, such as
5 an aerial/aerospace vehicle, the roll axis **RRX** of the stabilized optical system is selected to point to the forward direction being the general direction of the platform's movement (the orientation of the platform with respect to the roll axis is often referred to as the bank angle). The second rotation axis **SRX** is typically selected as the yaw axis of the platform (the orientation of the platform with respect to this axis is often referred
10 to as the heading angle of the platform). Accordingly, the first rotation axis **FRX** is typically selected as the pitch axis (designating the elevation angle of the platform).

Hence, another advantage of the optical system of the present invention is that it allows stabilizing the line of sight **LOS** of the light module against vibration of the platform (i.e. changes in the orientation of the platform/stabilized optical system) with
15 respect to directions perpendicular to the nominal line of sight of the stabilized optical system (e.g. perpendicular to the platform's direction of motion). Such vibrations are compensated directly e.g. compensating for vibration in the platform elevation by rotating the internal mirror **222** about the first (pitch) rotation axis (**FRX**) and compensating for vibration in the heading of the platform by rotation of the optical
20 module (e.g. telescope) about the second (yaw) rotation axis (**SRX**).

For clarity, in the following description the second and first rotation axes (**SRX** and **FRX**) are sometimes referred to as the yaw and pitch axes. It should be however understood that those axes (**SRX** and **FRX**) do not necessarily lie in the respective directions of the yaw and pitch rotation axes of the platform and can be selected to point
25 to another direction (e.g. orthogonal to the roll axis).

In some embodiments of the present invention, as is also illustrated in **Figs. 2A** and **2B** of the present example, the optical module **210** of the stabilized optical system **200** includes a mirror telescope (telescopic mirror arrangement). The telescopic mirror arrangement includes primary and secondary mirrors (**PM** and **SM**) that are arranged
30 with their optical axes substantially coinciding with the optical axis **OP** of the optical module **210**. The primary mirror **PM** collects/reflects light from/to the environment (light to be imaged by the light module is collected and light emanating from the light module is reflected by the primary mirror **PM**. The primary **PM** and secondary **SM**

- 19 -

mirrors are optically coupled such that at least some of the light collected by the primary mirror **PM** is deflected towards the secondary mirror **SM** and vice versa. The internal mirror **222** of the stabilization assembly is therefore posed in such embodiments on the optical axis **OP** of the optical module **210** in between the primary **PM** and
5 secondary **SM** mirrors. The internal mirror **222** is arranged and is configured to couple a light portion reflected from a region of the secondary mirror with the optical path **OPL** of the light module **230** (the coupled light portion may be propagating from or towards the light module **230**). Indeed, rotation of the internal mirror **222** with respect to the telescopic mirror arrangement **MT** (with respect to the optical module **210**) changes the
10 region of the secondary mirror **SM** (the cross-section part of the optical path) from which light portions are coupled with (e.g. collected and directed to) the optical path **OPL** of the light module **230**.

It should be understood that the light module **230** may include any one of an electromagnetic radiation source(s) (e.g. a light source/ FM source) such as a laser
15 emitter and may also, alternatively or additionally, include one or more light sensitive elements/sensors such as a light intensity/chrominance detector, quadrant detector and imaging sensor(s)/detector(s). It should be also noted that the light sensors and/or the light sources of the light module **230** may be sensitive to (or may emit) electro-magnetic radiation in various wavelength regimes for example in the visible light regime, infra-
20 red (IR) regime, ultra violet regime and also FM/microwaves. Accordingly, optical elements of the optical module **210** and of the stabilizer assembly **220** are not necessarily conventional mirrors and/or lenses and may include elements that are adapted to operate adequately with the wavelength regimes sought. In this regard various types of optical elements may included, such as diffractive elements, electro-
25 optical elements and/or electronic elements which manipulate the direction of light by induction of a suitable electromagnetic field (e.g. causing lensing or other electromagnetic effects).

In the present example the light module includes two imagers **IM1** and **IM2**. One of the imagers **IM1** is sensitive to light in the visible regime and includes charge
30 coupled detector (CCD) that includes multiple light sensitive pixels. A second imager **IM2** is sensitive to light in the IR regime e.g. it includes a focal plane array (FPA) detector. The light module also includes light guiding elements defining the optical path **OPL** of the light module **230** and is configured and operable for guiding light

- 20 -

propagating in between the internal mirror **222** of the stabilizer assembly and the light source(s)/light sensor(s) (e.g. imagers **IM1** and **IM2**) of the light module **230**. In the present example the light guide elements include a mirror **MR** and dichroic mirror **DMR**. Mirror **MR** defines the optical path **OPL** which is coupled with the internal mirror **222** and is arranged to couple (e.g. deflect) light from this optical path **OPL** with the dichroic mirror **DMR** (generally a wavelength selective beam splitter/combiner). In turn, the dichroic mirror **DMR** splits light to the imagers **IM1** and **IM2** (or combines light from light sources of the light module **230**) in accordance with the respective wavelengths to which the imagers **IM1** and **IM2** are sensitive (or which the light sources emanate). It should be noted that according to some embodiments of the invention the light guiding elements are obviated altogether and the optical path **OPL** of the light module **230** is defined by the light sources and/or light sensors (imagers) of the light module **230**. Indeed the light module **230** is generally associated with at least one optical path **OPL** which is directly or indirectly (i.e. via an intermediate optical path defined by the stabilizer assembly) optically coupled with the optical path **OP** of the optical module **210**. The optical path **OPL** in the present example is defined by the optical elements **MR** and **DMR** which are attached/fixed to the light module and are considered herein to be a part thereof.

Reference is made to **Fig. 3** showing a block diagram of the stabilized optical system **200** according to an embodiment of the present invention. Reference numerals similar to those of **Figs. 2A and 2B** are used in this figure to designate common elements of the stabilized optical system **200** having similar functionality.

Here, the stabilized optical system **200** includes an optical module **210** and a light module **230** similar to those illustrated in **Figs. 2A and 2B**. The optical module **210** and a light module **230** are interconnected and optically coupled with one another via a stabilizer assembly **220** which is similar to that illustrated in **Figs. 2A and 2B** and which is configured and operable to enable to vary the direction of the line of sight of the light module **230** by rotating the line of sight about two rotation axes (**FRX** and **SRX** in **Fig. 2A**) that are orthogonal to the optical axis of the optical module **210**.

Accordingly and similarly to the stabilizer assembly **220** illustrated in **Figs. 2A and 2B**, also here the stabilizer assembly **220** interconnects the optical module and the light module via second rotation mechanism **SRM** allowing to change their respective angular position about a second rotation axis. The stabilizer assembly **220** includes an

internal mirror **222** and a first rotation mechanism **FRM**. Similarly to the configuration of **Figs. 2A and 2B**, also here the internal mirror is located such that it intersects the optical paths **OP** and **OPL** of the optical module **210** and light module **230** respectively for providing optical coupling between at least parts of these optical paths **OP** and **OPL**. The internal mirror is mounted on the first rotation mechanism **FRM** and is thus capable to rotate about the first rotation axis. This orientation of the internal mirror **222** with respect to the first rotation axis (**FRX** in **Fig. 2A**) controls the parts of the optical paths **OP** and **OPL** which are optically coupled together and thus the relative angle between the line of sight (**LOS** in **Fig. 2A**) of the light module **230** and the optical axis (**OX** in **Fig. 2A**) of the optical module **210**.

It should be noted here that the light module may generally include one or more various types of sources and or sensors which are capable of irradiating/emitting and/or detecting/sensing electro-magnetic radiation in various wavelength regimes. The terms *electromagnetic radiation* and *light* are used herein interchangeably to designate any type of electromagnetic radiation in any suitable wavelength/frequency regime which originate or are detected by the light module **230** of the stabilized optical system **200**. Applicable wavelength regimes, for which the stabilized optical system **200** of the invention can be designed, may include for example, but are not limited to, the visible light regime, ultraviolet light regime, infrared light (Near-, Mid- and Far- IR) and also radio-frequency and microwave regimes. In this respect the stabilized optical system of the invention may be operated as a stabilized imaging- or light-source- system (e.g. operating within the IR to UV wavelength regimes) and/or it may be a radar/radio transmitter/receiver system operating in the microwave and/or the radio frequency regimes.

It should be noted that in embodiments of the invention in which the stabilized optical system **200** is designed in certain wavelength regime(s), both the light module **230** and the optical module **210** are configured and operable to operate in these regimes. In this respect the optical module **210** and the optical elements included therein are generally configured and operable for transmitting/propagating/directing therethrough light in the desired wavelength regime(s) in accordance with those sensed or emitted by the light module. To this end, optical elements of the optical module **210** may include elements such as mirror, lenses and optically diffractive elements and also electro-optical or electronic elements such as antennas or antenna arrays which are referred to

herein also as optical elements. The term optics and optical elements/systems should therefore be construed in the context of the present invention in the broad sense as relating to any elements that are capable of manipulating the propagation on electromagnetic radiation (light).

5 In this embodiment of the invention, the system **200** also includes a stabilization control module **240** including stabilization controller **242** and actuation module **244**. The stabilization controller **242** is configured and operable to receive relative orientation data **RO** indicative of the desired relative orientation of the line of sight of the light module **230** (e.g. relative to the orientation of the light module **230** itself) and
10 to generate and supplement suitable actuation signals **AS** to the actuation module **244** which in turn affect actuation of rotation of the first and second rotation mechanisms to the suitable position in which the desired relative orientation of the line of sight of the light module **230** is obtained. To this end the actuation module includes first and second rotation actuators (actuation units), **FRA** and **SRA**, (e.g. servos/motors) that are
15 operable for receiving the actuation signals **AS** from the stabilization controller **242**. The first and second rotation actuators, **FRA** and **SRA**, are respectively connected to (or are part of) the first and second rotation mechanisms, **FRM** and **SRM**, of the stabilizer assembly **220** and are configured to effect rotations of these mechanisms in response to actuation signal **AS** from the stabilization controller **242**.

20 Generally, the stabilization controller **242** may receive relative orientation data **RO** indicative of the desired relative orientation of the line of sight of the light module **230** from various types of sources. For example, active direction of the line of sight of the light module **230** can be provided by allowing a user/machine to control the relative orientation between the line of sight and the stabilized optical system **200**. In this case
25 for example, relative orientation data **RO** may be generated by a user (person/computer) of the stabilized optical system **200** by utilizing active direction module **250** which may be optionally associated with the stabilized optical system **200**. Active direction module **250** may be for example a user interface module (UI) or an application interface module (API) that provide an interface through which a user or a machine can provide
30 instructions regarding the desired direction of the line of sight of the light module **230**.

Alternatively or additionally, in some cases it is desired to utilize the stabilized optical system **200** of the invention for stabilizing an image or a light beam against changes in the orientation/position of the stabilized optical system **200**. Hence

optionally when image or light beam stabilization is sought, an orientation determination module **260** may be employed to stabilize the image/light beam. The orientation determination module **260** is configured and operable to determine the orientation of the line of sight of the light module **230** (e.g. with respect to the external
5 environment) and/or to determine changes in that orientation and to generate relative orientation data **RO** that is suited for correcting/compensating for such changes and thus stabilizing the image/light beam. Changes in the orientation of the line of sight may be caused, for example, by vibrations or fluctuations in the orientation/position of the stabilized optical system **200**.

10 To this end, the orientation determination module **260** may be connectable to rotation rate sensor module **270**, including one or more rotation rate sensors (e.g. rate gyros) and attached/mounted to the stabilized optical system **200**. Rotation rate sensor module **270** measures the rotation rates of the stabilized optical system **200** at least with respect to the first and second rotation axes (**FRX** and **SRX** in Fig. 2A) and provides
15 data **RRD** (rotation rate data) indicative thereof to the orientation determination module **260**. In turn, orientation determination module **260** applies integration to the received rotation rates from the rotation rate sensor module **270** and determines a change in the orientation of the stabilized optical system **200** and further determines relative rotation data **RO** indicative of the rotation that should be actuated by the first and second
20 rotation mechanisms, **FRM** and **SRM** in order to compensate for the change in orientation of the stabilized optical system **200** and to maintain a stable line of sight of the light module **230**.

It should be understood that, according to the present invention, the orientation determination module **260** is not necessarily associated with rotation rate sensors
25 (module **270**). For example, in cases where the light module **230** includes an imaging system **IM**, changes in the orientation of the stabilized optical system may be determined/calculated based on image data **IMD** that is indicative of images captured by the imaging system **IM**. Determining the changes in the orientation of the optical system based on image data can be performed by comparing two or more images from
30 that image data **IMD** and by utilizing various types of image processing techniques which are known in the art. After changes in the orientation of the stabilized optical system **200** are determined, compensating for such changes by inducing rotation

- 24 -

actuation on the first and second rotation mechanisms (by the first and second rotation actuators, **FRA** and **SRA**) is performed in a manner similar to that described above.

It should also be noted that the system of the present invention may be configured and operable for concurrently performing both active direction of the line of sight of the light module **230** (e.g. based on user or machine inputs) and concurrently applying line of sight stabilization to compensate for changes in the orientation of the stabilized optical system **200**. In such cases the orientation determination module **260** may be configured and operable to receive desired orientation data **DOD** from the rotation rate sensor module **270** (or alternatively image data **IMD** from an imager **IM** of the light module **230**) and to process these data pieces to determine the relative orientation (**RO** data) that should be applied by the first and second rotation mechanisms for both compensating for changes in the orientation of the stabilized optical system **200** and also actively directing the line of sight of the light module to the desired direction.

CLAIMS:

1. An optical system comprising:
a light module;
an optical module defining an optical axis and an optical path of light
5 propagation therethrough; and
a stabilizer configured and operable for providing optical coupling between said optical module and said light module, said stabilizer comprising: a gimbal assembly defining a first rotation axis orthogonal to said optical axis, and an internal deflector located in the optical path of light propagating through said optical module, said internal
10 deflector being mounted for rotation about said first rotation axis and configured and operable to provide optical coupling between at least a section of the optical path of said optical module and an optical path of light passing through said light module.
2. The optical system of claim 1, wherein said gimbal assembly comprises a gimbal interconnected between said optical module and said light module and
15 configured to allow rotation of said optical module about a second rotation axis orthogonal to said optical axis and to said first rotation axis.
3. The stabilized optical system according to claim 1 or 2, wherein said internal deflector is rotatable about said first rotation axis thereby varying the section of the optical path of said optical module which is coupled with the optical path of the light
20 module.
4. The optical system of any one of the preceding claims, wherein rotation of said internal deflector about said first rotation axis in a direction opposite to a direction of rotation of the optical system about an axis parallel to said first rotation axis provides compensation for said rotation of the optical system, thus allowing to stabilize at least
25 one of an image or a light beam formed by said light module.
5. The stabilized optical system of any one of claims 2 to 4, wherein rotation of said optical module about said second rotation axis with respect to said light module provides compensation for rotation of the optical system in a direction opposite to the rotation of said optical module, thus allowing to stabilize at least one of an image or a
30 light beam formed by said light module.
6. The optical system of any one of the preceding claims, wherein said optical module comprises a telescopic mirror arrangement comprising at least primary and

- 26 -

secondary mirrors arranged such that their respective optical axes substantially coincide with said optical axis of the optical module, said internal deflector intersecting a section of the optical path of the optical module defined by said secondary mirror and being arranged to optically couple said section of the optical path with an optical path of the
5 light module.

7. The optical system of claim 6, wherein rotation of said internal deflector with respect to the telescopic mirror arrangement varies a location of a region on the secondary mirror that is optically coupled with the optical path of the light module thereby varying said section of the optical path coupled with the optical path of the light
10 module.

8. The optical system of any one of the preceding claims, wherein said light module comprises at least one light sensor; said internal deflector is configured and operable to collect a light portion propagating thereto from a section of the optical path of the optical module and to direct the collected light portion to said light module.

15 9. The optical system of claim 8, wherein said at least one light sensor comprises an imaging sensor having multiple light sensitive pixels.

10. The optical system of claim 8 or 9, wherein said light module comprises at least two light sensors sensitive to light in at least two different spectral ranges, and at least one wavelength selective splitter configured for spatially separating light from said
20 optical module into at least two light components and directing them to said at least two light sensors.

11. The optical system of claim 10, wherein said at least two light sensors are sensitive to light in at least the IR and the visible spectral ranges, respectively.

12. The optical system of claim 10 or 11, wherein said wavelength selective splitter
25 comprises a dichotic mirror.

13. The optical system of any one of the preceding claims, wherein said light module includes at least one source of electromagnetic radiation and wherein said optical module is optically coupled with said at least one source for collecting and directing an electromagnetic radiation beam emitted therefrom; said stabilizer is
30 configured for directing said radiation beam to various directions with respect to said light module.

14. The optical system of claim 13, wherein said at least one source of electromagnetic radiation comprises a laser source and wherein said optical module

- 27 -

includes an arrangement of optical elements adapted for directing electromagnetic radiation in wavelength range of said laser source.

15. The optical system of claim 13 or 14, wherein said at least one source of electromagnetic radiation comprises a source of radio frequency radiation, said optical
5 module comprising an arrangement of elements adapted for directing electromagnetic radiation in the radio frequency regime.

16. The optical system of claim 15, wherein said arrangement of elements includes one or more antennas.

17. The optical system of any one of the preceding claims, wherein said light
10 module comprises one or more light guiding elements that are configured and operable to define an optical path of said optical module and to provide optical coupling between a light sensor or light source of the light module and the internal deflector.

18. The optical system of claim 17 wherein said one or more light guiding elements comprises at least one light deflector.

15 19. The optical system of claim 17 or 18, wherein said light guiding elements provide optical coupling between the internal deflector and at least one of a light sensor and light source of the light module, while said optical module and said internal deflector are in various angular positions with respect to said light module.

20. The optical system of any one of claims 2 to 19, comprising a stabilization
20 control module comprising:

a first actuation unit connected to said first rotation axis and configured to actuate a first relative rotation between said optical module and said internal deflector about said first rotation axis;

a second actuation unit connected to said gimbal and configured to actuate a
25 second relative rotation between said optical module and said light module about said second rotation axis; and

a control unit connected to said first and second actuation units and adapted to be responsive to signals, indicative of rotation rates of said optical system, to operate at least one of said first and second actuation units to perform at least one of the first and
30 second relative rotations, to thereby compensate for said rotation rates and stabilize a line of sight of said optical system.

21. The optical system of claim 20, comprising a rotation rate measurement system connectable to said control unit and configured and operable for measuring the rotation

- 28 -

rates of said optical system with respect to at least one of the first and the second rotation axes, and generating said signal indicative of said rotation rates.

22. The optical system of any one of claims 2 to 21, wherein said stabilizer and said gimbal are configured and operable to enable a change in orientation of a line of sight of
5 said light module within an angle of at least 160° about said second rotation axis.

23. The optical system of any one of the preceding claims, wherein said stabilizer, said first rotation axis and said optical module are configured and operable to enable a change in orientation of a line of sight (LOS) of said light module within an angle of at least 90° about said first rotation axis.

10 24. The optical system of any one of claims 2 to 23, wherein said second rotation axis corresponds to a yaw axis of said optical module.

25. The optical system of any one of the claims 2 to 24, wherein said gimbal is external to said optical module and is configured for providing relative rotation between said optical module and said light module.

15 26. The optical system of any one of the preceding claims, wherein said first rotation axis corresponds to a pitch axis of said optical module.

27. The optical system of any one of the preceding claims, wherein said first rotation axis is internal to said optical module and is configured for providing relative rotation between the internal deflector and the optical module.

20 28. The optical system of any one of the preceding claims, wherein said internal deflector comprises a mirror.