[0004]

PTL 2 discloses a method for producing a solid milk, in which a gas is dispersed in a liquid milk, the liquid milk is sprayed and dried to form a powdered milk, and the obtained powdered milk is compression-molded to form a solid milk. PTL 2 describes that a load [N] when a solid milk is fractured is obtained by pushing a solid milk having a rectangular parallelepiped shape by a fracture terminal using a commercially available load cell tablet hardness tester and the load is regarded as a hardness [N] of the solid milk.

Citation List

Patent Literature

[0005]

PTL 1: Japanese Patent No. 5,350,799

PTL 2: Japanese Patent No. 5,688,020

Summary

Technical Problem

[0006]

When a solid food and a solid milk are handled in transportation, a store, a home, and the like, it is required to improve transportation suitability to prevent a product from being damaged when the product is

dropped.

[0007]

The present disclosure has been accomplished against the above background, and an object thereof is to provide a solid food and a solid milk that can prevent a product from being damaged when the product is dropped to improve transportation suitability.

Solution to Problem

[0008]

In one aspect of the present disclosure, there is provided a solid food having a solid form obtained by compression-molding a powder, the solid food comprising a body having a first face and a second face facing each other back to back, wherein the body is provided with at least one hole penetrating the body from the first face to reach to the second face, and each of the first face, the second face, and an inner surface of the hole is an outer surface harder than an inner part of the body.

[0009]

In another aspect of the present disclosure, there is provided a solid milk having a solid form obtained by compression-molding a powdered milk, the solid milk comprising a body having a first face and a second face facing each other back to back, wherein the body is provided with at least one

hole penetrating the body from the first face to reach to the second face, and each of the first face, the second face, and an inner surface of the hole is an outer surface harder than an inner part of the body.

Advantageous Effects of the Disclosure

[0010]

According to the present disclosure, at least one hole penetrating the body constituting the solid food is provided and the inner surface of the hole is the outer surface harder than the inner part of the body similarly to the first face and the second face, such that a product can be prevented from being damaged when the product is dropped, thereby improving transportation suitability.

[0011]

According to the present disclosure, at least one hole penetrating the body constituting the solid milk is provided and the inner surface of the hole is the outer surface harder than the inner part of the body similarly to the first face and the second face, such that a product can be prevented from being damaged when the product is dropped, thereby improving transportation suitability.