

CASCADE POWER SYSTEM

RELATED APPLICATIONS

[0001] This application claims priority to United States Patent Application Serial 11/235,654, filed 22 September 2005, which is a Continuation-in-part of United States Patent Application Serial No. 11/099,211, filed 5 April 2005, which is a continuation-in-part of United States Patent Application Serial No. 10/983,970, filed 8 November 2004.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present invention relates to a cascade power system for extracting usable power from heat produced from the combustion of biomass, agricultural waste (such as bagasse,) municipal waste and other fuels. The present invention also relates to a cascade power system where heat is derived from a hot flue gas stream by mixing the stream with a precooled or partially spent flue gas stream so that the mixed flue gas stream has a desired lower temperature for efficient heating of the working fluid without causing undue stress and strain on the heat exchange unit.

[0003] More particularly, the present invention relates to a cascade power system for extracting usable power from heat produced from the combustion of biomass, agricultural waste (such as bagasse,) municipal waste and other fuels, where the system includes an energy extraction subsystem, a separation subsystem, a heat exchange subsystem, a heat transfer subsystem and a condensing subsystem, where the system forms a lean stream and a rich stream from a fully condensed incoming working fluid stream, vaporizes the lean and a rich streams from heat derived directly or indirectly from a heat source stream, converts thermal from the lean and rich streams to a usable form of energy forming a spent outgoing working fluid stream and condensing the outgoing working fluid stream to from the incoming working fluid stream and to methods for converting vaporizing a lean stream and a rich stream and extracting energy therefrom.

2. Description of the Related Art

[0004] Currently, the most efficient biomass fueled power plants have an overall plant efficiency of up to 20%, *i.e.*, the net power output of these plants is up to 20% of the LHV (Lower Heating Value) of the combusted fuel. To achieve this level of efficiency, current biomass power plants require a very complicated combustion system which is comprised of a gasifier and a char

combustor, and a power train that uses both a gas turbine and a steam power system, consequently, such systems are quite expensive.

[0005] Thus, there is a need in the art for a more efficient and simpler system for combusting a fuel such as biomass and converting a higher portion of its Lower Heating Value of the combusted fuel in to usable energy such as electricity.

SUMMARY OF THE INVENTION

[0006] The present invention provides a cascade power system including two interacting cycles. One cycle utilizes a rich working fluid having a higher concentration of a low boiling component, and another cycle utilizes a lean working fluid having a lower concentration of the low boiling component, where the system is designed on a modular principle, and can be embodied in several variants which may or may not include certain modular units or components.

[0007] The present invention provides a cascade power system including an energy extraction subsystem, a separation subsystem, a heat exchange subsystem, a heat transfer subsystem and a condensation subsystem. The system produces a lean stream cycle and a rich stream cycle. In the lean stream cycle, a lean stream is produced from an incoming stream in the separation subsystem, vaporized in the heat exchange subsystem, and a portion of thermal energy is extracted in a lean stream portion of the energy extraction subsystem from the vaporized lean stream. In the rich stream cycle, a rich stream is produced from an incoming stream, vaporized in the heat exchange subsystem and a portion of thermal energy is extracted in a rich stream portion of the energy extraction subsystem from the vaporized rich stream. The spent rich stream from the rich stream portion of the energy extraction system is then condensed in the condensing unit and returned as the incoming stream. The system forms a continuous thermodynamic energy conversion cycle including two interacting subcycles.

[0008] The present invention also provides a cascade power system including an energy extraction subsystem having a rich stream extraction subsystem and a lean stream extraction subsystem, a separation subsystem, a heat exchange subsystem, a heat transfer subsystem and a condensing subsystem. The system forms a lean stream and a rich stream from a fully condensed incoming working fluid stream, vaporizes the lean and a rich streams from heat derived directly or indirectly from an external heat source stream, preferably an external hot flue gas stream, converts a portion of thermal energy in the lean and rich streams to a usable form of energy to form a spent outgoing working fluid stream, and condensing the outgoing working fluid stream to from the incoming working fluid stream, where the system supports a thermodynamic energy extraction cycle including two interacting subcycles.

[0009] The present invention provides a cascade power system including an energy extraction subsystem, a separation subsystem, a heat exchange subsystem, a heat transfer subsystem and a condensing subsystem, where the system supports a thermodynamic energy extraction cycle. The energy extraction subsystem includes a lean stream turbine, at least one rich stream turbine and at least two throttle control valves, where the lean stream turbine is adapted to extract energy from a lean stream, where the rich stream turbine is adapted to extract from a rich stream and where the first throttle control valve adjusts a pressure of a rich stream to that of a pressure of the rich stream turbine, where a second throttle control valve adjusts a pressure of the lean stream to a pressure of the lean stream turbine and optionally a third throttle control valve adjusts a pressure of an optional rich substream to a pressure of a leaner stream. The separation subsystem includes a scrubber, a separator and three pumps, where the separation subsystem is adapted to form a lean stream and a make-up stream having a composition the same or substantially the same as an incoming working fluid stream. The heat exchange subsystem includes at least four heat exchangers adapted to vaporize the rich stream and heat or partially vaporized the lean stream. The heat transfer subsystem includes a heat transfer fluid, a heat transfer fluid pump and two heat exchangers, where the heat transfer subsystem is adapted to transfer heat from a hot flue gas stream to the heat transfer subsystem and then to transfer the absorbed heat of the heat transfer subsystem to the lean stream to vaporize the lean stream. The condensation subsystem is adapted to a fully condensed the spent working fluid stream and can be any condensation subsystem.

[0010] The present invention provides a method including mixing a fully condensed incoming work fluid stream with a pressurized cooled mixed stream, where the incoming stream and the mixed stream have the same or substantially the same composition to form a cooled working fluid stream. The cooled working fluid stream is then brought into a heat exchange relationship with a mixed stream to form the cooled mixed stream and a heated working fluid stream. The heated working fluid stream is then brought into a heat exchange relationship with a first portion of a cooled spent lean stream to form a hotter working fluid stream and a cooler spent lean stream. The hotter working fluid stream is then brought into a heat exchange relationship with a spent lean stream to form a fully vaporized working fluid stream. A first portion of the fully vaporized working fluid stream is then pressure adjusted and forwarded to the rich stream turbine, where the working fluid stream is a rich stream relative to the lean stream. The fully vaporized working fluid stream is then forwarded to the rich stream turbine converting a portion of the thermal energy in the fully vaporized working fluid stream into a first amount of useable form of energy. A second portion of the fully vaporized working fluid stream is then pressure

adjusted and mixed with a partially vaporized leaner stream to form the lean stream. The lean stream is then brought into a heat exchange relationship with a circulated heat transfer fluid to form a fully vaporized lean stream, where the heat transfer fluid is heated by bringing the circulating heat transfer fluid into a heat exchange relationship with a hot flue gas stream. The fully vaporized lean stream is then pressure adjusted to a pressure of the lean stream turbine and forwarded to the lean stream turbine converting a portion of the thermal energy in the fully vaporized lean stream into a second amount of useable form of energy.

[0011] The present invention provides a method for efficient extraction of energy from a hot flue gas stream including the steps of establishing two interacting vaporization and energy extraction cycles, where one cycle utilizes a multi-component fluid stream having a higher concentration of a low boiling component of the multi-component fluid (a rich stream) and the other cycle utilizes a multi-component fluid stream having a higher concentration of a high boiling component of the multi-component fluid (a lean stream), each stream being derived from a fully condensed incoming multi-component working fluid. The lean and rich stream utilized in the two interacting cycles are directly and/or indirectly vaporized by a hot external flue gas stream, where a portion of the indirect heating occurs via a heat transfer cycle utilizing a separately circulating heat transfer fluid to heat and vaporize the lean stream. Once vaporized, a portion of the thermal energy in the lean stream is extracted in a lean turbine and a portion of the thermal energy in the rich stream is extracted in at least one rich turbine. The spent lean stream is used to heat and vaporize the rich stream and is forwarded to a scrubber and separator designed to form the lean stream and to supplement the rich stream. The spent rich stream is forwarded to a condensation unit, where it is fully condensed to form the incoming stream.

[0012] The invention can be better understood with reference to the following detailed description together with the appended illustrative drawings in which like elements are numbered the same:

[0013] **Figure 1** depicts a block diagram of a preferred embodiment, **Variant 1a**, of a cascade power system of this invention;

[0014] **Figure 2** depicts a block diagram of a simple condenser;

[0015] **Figure 3** depicts a block diagram of another preferred embodiment, **Variant 1a1**, of a cascade power system of this invention;

[0016] **Figure 4** depicts a block diagram of another preferred embodiment, **Variant 2a**, of a cascade power system of this invention;

[0017] **Figure 5** depicts a block diagram of another preferred embodiment, **Variant 2a1**, of a

cascade power system of this invention;

[0018] **Figure 6** depicts a block diagram of another preferred embodiment, **Variant 1b**, of a cascade power system of this invention;

[0019] **Figure 7** depicts a block diagram of another preferred embodiment, **Variant 2b**, of a cascade power system of this invention;

[0020] **Figure 8** depicts a block diagram of another preferred embodiment, **Variant 1c**, of a cascade power system of this invention;

[0021] **Figure 9** depicts a block diagram of another preferred embodiment, **Variant 2c**, of a cascade power system of this invention;

[0022] **Figure 10** depicts a block diagram of a preferred embodiment of **CTCSS Variant 1a** of a condensation and thermal compression subsystems;

[0023] **Figure 11** depicts a block diagram of another preferred embodiment of **CTCSS Variant 1b** of a condensation and thermal compression subsystems;

[0024] **Figure 12** depicts a block diagram of a preferred embodiment of **CTCSS Variant 2a** of a condensation and thermal compression subsystems;

[0025] **Figure 13** depicts a block diagram of a preferred embodiment of **CTCSS Variant 2b** of a condensation and thermal compression subsystems;

[0026] **Figure 14** depicts a block diagram of a preferred embodiment of **CTCSS Variant 3a** of a condensation and thermal compression subsystems;

[0027] **Figure 15** depicts a block diagram of a preferred embodiment of **CTCSS Variant 3b** of a condensation and thermal compression subsystems;

[0028] **Figure 16** depicts a block diagram of a preferred embodiment of **CTCSS Variant 4a** of a condensation and thermal compression subsystems;

[0029] **Figure 17** depicts a block diagram of a preferred embodiment of **CTCSS Variant 4b** of a condensation and thermal compression subsystems;

[0030] **Figure 18** depicts a block diagram of a preferred embodiment of **CTCSS Variant 5a** of a condensation and thermal compression subsystems;

[0031] **Figure 19** depicts a block diagram of a preferred embodiment of **CTCSS Variant 5b** of a condensation and thermal compression subsystems;

[0032] **Figure 20** depicts a block diagram of a new preferred embodiment, **Variant 3a**, of a cascade power system of this invention;

[0033] **Figure 21** depicts a block diagram of another preferred embodiment, **Variant 4a**, of a cascade power system of this invention;

[0034] **Figure 22** depicts a block diagram of another preferred embodiment, **Variant 3b**, of a cascade power system of this invention;

[0035] **Figure 23** depicts a block diagram of another preferred embodiment, **Variant 4b**, of a cascade power system of this invention;

[0036] **Figure 24** depicts a block diagram of another preferred embodiment, **Variant 3c**, of a cascade power system of this invention;

[0037] **Figure 25** depicts a block diagram of another preferred embodiment, **Variant 4c**, of a cascade power system of this invention;

[0038] **Figure 26** depicts a block diagram of another preferred embodiment of a cascade power system of this invention;

[0039] **Figure 27** depicts a block diagram of another preferred embodiment of a cascade power system of this invention; and

[0040] **Figure 28** depicts a block diagram of another preferred embodiment of a cascade power system of this invention.

DETAILED DESCRIPTION OF THE INVENTION

[0041] The inventor has found that a new system for extracting usable energy from a source of combustion gases with higher efficiency the known systems. The preferred system of this invention have at least a 30% improvement over a known prior art system. The inventor has also found that the new system is ideally suited for extracting the heat produced in the combustion of a fuels preferably low heat value fuels such as biomass, agricultural waste (such as bagasse,) municipal waste and other low heat value fuels. Preferably, the combustion is carried out in fluidized bed combustors or combustion zone. The term biomass is used herein to refer to all low heat value fuels, but, of course, the systems of this invention can also be used with other fuels including high heat value fuels such as coal, oil or natural gas.

[0042] The present invention broadly relates to a power system including two interacting thermodynamic different working fluid cycles and a heat transfer cycle. One working fluid cycle utilizes a rich working fluid stream, a stream having a higher concentration of a low boiling component of a multi-component fluid, while the other working fluid cycle utilizes a lean working fluid stream, a fluid stream having a lower concentration of the low boiling component. The cycles are adapted to be fully vaporized by absorbing thermal energy directly and/or indirectly from a hot flue gas stream and the convert a portion of their thermal energy into a usable form of energy in separation energy conversion subsystems. The system also includes a heat transfer cycle adapted to indirectly transfer thermal energy from the hot flue gas stream to

vaporize the lean stream prior to energy extraction. The rich stream is vaporized by thermal energy derived from the lean stream and streams derived therefrom.

[0043] The present invention broadly relates to a cascade power system including an energy extraction subsystem, a separation subsystem, a heat exchange subsystem, a heat transfer subsystem and a condensation subsystem. The system produces a lean stream cycle and a rich stream cycle. In the lean stream cycle, a lean stream is produced from an incoming stream in the separation subsystem, vaporized in the heat exchange subsystem, and a portion of thermal energy is extracted in a lean stream portion of the energy extraction subsystem from the vaporized lean stream. In the rich stream cycle, a rich stream is produced from an incoming stream, vaporized in the heat exchange subsystem and a portion of thermal energy is extracted in a rich stream portion of the energy extraction subsystem from the vaporized rich stream. The spent rich stream from the rich stream portion of the energy extraction system is then condensed in the condensing unit and returned as the incoming stream. The system forms a continuous thermodynamic energy conversion cycle including two interacting subcycles.

[0044] The present invention broadly relates to a method including mixing a fully condensed incoming work fluid stream with a pressurized cooled mixed stream, where the incoming stream and the mixed stream have the same or substantially the same composition to form a cooled working fluid stream. The cooled working fluid stream is then brought into a heat exchange relationship with a mixed stream to form the cooled mixed stream and a heated working fluid stream. The heated working fluid stream is then brought into a heat exchange relationship with a first portion of a cooled spent lean stream to form a hotter working fluid stream and a cooler spent lean stream. The hotter working fluid stream is then brought into a heat exchange relationship with a spent lean stream to form a fully vaporized working fluid stream. A first portion of the fully vaporized working fluid stream is then pressure adjusted and forwarded to the rich stream turbine, where the working fluid stream is a rich stream relative to the lean stream. The fully vaporized working fluid stream is then forwarded to the rich stream turbine converting a portion of the thermal energy in the fully vaporized working fluid stream into a first amount of useable form of energy. A second portion of the fully vaporized working fluid stream is then pressure adjusted and mixed with a partially vaporized leaner stream to form the lean stream. The lean stream is then brought into a heat exchange relationship with a circulated heat transfer fluid to form a fully vaporized lean stream, where the heat transfer fluid is heated by bringing the circulating heat transfer fluid into a heat exchange relationship with a hot flue gas stream. The fully vaporized lean stream is then pressure adjusted to a pressure of the lean stream

turbine and forwarded to the lean stream turbine converting a portion of the thermal energy in the fully vaporized lean stream into a second amount of useable form of energy.

[0045] The present invention broadly relates to a method for efficient extraction of energy from a hot flue gas stream including the steps of establishing two interacting vaporization and energy extraction cycles, where one cycle utilizes a multi-component fluid stream having a higher concentration of a low boiling component of the multi-component fluid (a rich stream) and the other cycle utilizes a multi-component fluid stream having a higher concentration of a high boiling component of the multi-component fluid (a lean stream), each stream being derived from a fully condensed incoming multi-component working fluid. The lean and rich stream utilized in the two interacting cycles are directly and/or indirectly vaporized by a hot external flue gas stream, where a portion of the indirect heating occurs via a heat transfer cycle utilizing a separately circulating heat transfer fluid to heat and vaporize the lean stream. Once vaporized, a portion of the thermal energy in the lean stream is extracted in a lean turbine and a portion of the thermal energy in the rich stream is extracted in at least one rich turbine. The spent lean stream is used to heat and vaporize the rich stream and is forwarded to a scrubber and separator designed to form the lean stream and to supplement the rich stream. The spent rich stream is forwarded to a condensation unit, where it is fully condensed to form the incoming stream.

[0046] The preferred embodiments of the system of this invention are high efficiency systems and high efficiency methods that preferably utilize heat produced in a single stage fluidized bed combustor or combustion zone, but can use heat produced by any method that generates a hot flue gas effluent stream.

[0047] The system of this invention uses as its working fluid including a mixture of at least two components, where the components have different normal boiling temperatures. That is the working fluid is a multi-component fluid including at least one higher boiling component and at least one lower boiling component. In a two component working fluid, the higher boiling component is often referred to simply as the high boiling component, while the lower boiling component is often referred to simply as the low boiling component. A composition of the multi-component working fluid is varied throughout the system with energy being extracted from a rich working fluid and a lean working fluid, where rich means that the fluid has a higher concentration of the low boiling component than the in-coming working fluid and lean means that the fluid has a lower concentration of the low boiling component than the in-coming working fluid.

[0048] The working fluid used in the systems of this inventions is a multi-component fluid that

comprises a lower boiling point material – the low boiling component – and a higher boiling point material – the high boiling component. Preferred working fluids include, without limitation, an ammonia-water mixture, a mixture of two or more hydrocarbons, a mixture of two or more freons, a mixture of hydrocarbons and freons, or the like. In general, the fluid can comprise mixtures of any number of compounds with favorable thermodynamic characteristics and solubilities. In a particularly preferred embodiment, the fluid comprises a mixture of water and ammonia.

[0049] Suitable heat transfer fluids include, without limitation, metal fluids such as lithium, sodium, or other metal used as high temperature heat transfer fluids, synthetic or naturally derived high temperature hydrocarbon heat transfer fluids, silicon high temperature heat transfer fluids or any other heat transfer fluid suitable for use with hot flue gas effluent stream from fuel combustion furnaces, where the fuel includes biomass, agricultural waste (such as bagasse,) municipal waste, nuclear, coal, oil, natural gas and other fuels.

[0050] The system of this invention comprises two interacting cycles. One cycle utilizes a rich working fluid having a higher concentration of the low boiling component, and the other cycle utilizes a lean working fluid having a lower concentration of the low boiling component.

[0051] The system of this invention is designed on a modular principle, and can be embodied in several variants which may or may not include certain modular units or components.

Preferred Embodiments

[0052] A preferred embodiment of the power system of the present invention is presented in **Figure 1**. The system shown in **Figure 1** may operate with a simple condenser as shown in **Figure 2** or may operate with a Condensation Thermal Compression Sub Systems (CTCSS) including a CTCSS described in a co-pending application file simultaneously via express mail label number EV 510 916 550 filed concurrently with this application, incorporated by reference and set forth in **Figures 10-19**, herein.

[0053] One preferred embodiment of the system of this invention is the embodiment shown in **Figure 1** is designated **Variant 1a**, and operates as follows. A rich working liquid stream, a stream having a high concentration of the low-boiling component **S100** having parameters as at a point **29** enters the system from either a simple condenser of **Figure 2** or a Condensation Thermal Compression Subsystem (CTCSS) of **Figures 10-19**. The stream **S100** exits the condenser or CTCSS at a high pressure and having a temperature close to ambient. Thereafter, the stream **S100** having the parameters as at the point **29** is mixed with a stream **S102** of working fluid having at parameters as at a point **92**. Usually the pressure of the stream **S102** at point **92**

is equal to the pressure of the stream S100 at point 29, and the composition of the stream S102 at point 92 is the same or similar to the composition of the stream S102 at point 29. As a result of this mixing, a stream S104 having parameters as at a point 91 is formed. Thereafter, the stream S104 having the parameters as at the point 91 passes through a first heat exchanger HE11, where it is heated in counterflow in a first heat exchange process by a condensing stream S106 of rich working fluid having parameters as at a point 95, forming a stream S108 having parameters as at a point 101, where a temperature of the stream S108 is sufficient to bring the fluid close to a state of saturated liquid.

[0054] The stream S106 of rich working fluid having the parameters as at the point 95 passes through the first heat exchanger HE11, where it is cooled and fully condensed, releasing heat for the first heat exchange process, forming a stream S110 having parameters as at a point 98. Thereafter, the fully condensed stream S110 having the parameters as at the point 98 enters into a first circulating pump P10, where it is pumped to a high pressure equal to the pressure of the stream S100 having the parameters as at the point 29, forming the stream S102 having the parameters as at the point 92. The stream S102 having the parameters as at the point 92 is mixed with the stream S100 having the parameters as at the point 29, forming the stream S104 having the parameters as at the point 91 as described above.

[0055] Meanwhile, the stream S108 having the parameters as at the point 101 is divided into two substreams S112 and S114 having parameters as at points 104 and 106, respectively. The stream having S114 having the parameters as at the point 106 passes through a ninth heat exchanger HE20, where it is heated and vaporized in counterflow in a ninth heat exchange process by a stream S116 of flue gas having initial parameters as at a point 602 and final parameters as at a point 603 as described below, forming a stream S118 having parameters as at a point 302, corresponding, or close to, a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor.

[0056] The stream S112 having the parameters as at the point 104 passes through a second heat exchanger HE12, where it is heated and vaporized in counterflow in a second heat exchange process by a stream S120 of condensing working fluid having parameters as at a point 206, forming a stream S122 having parameters as at a point 304, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor.

[0057] Thereafter, the streams S118 and S122 having the parameters as at the points 302 and 304, respectively, are combined to form a vapor stream S124 having parameters as at a point 300.

The vapor stream **S124** having the parameters as at the point **300** is then divided into two substreams **S126** and **S128** having parameters as at points **321** and **322**, respectively. The stream **S126** having the parameters as at the point **321** then passes through a third heat exchanger **HE13**, where it is heated in counterflow in a third heat exchange by a lean working fluid stream **S130** having parameters as at a **316**, forming a stream **S132** having parameters as at point **320**. The stream **S128** having the parameters as at the point **322** passes through an intercooler **HE16**, where it is heated in counterflow in a sixth heat exchange process by a rich working fluid stream **S134** having parameters as at a point **412**, forming a stream **S136** having parameters as at a point **323**. The stream **S134** having the parameters as at the point **323** is then mixed with the stream **S132** having the parameters as at the point **320**, forming a rich working fluid stream **S138** having parameters as at a point **301**.

[0058] The lean working fluid stream **S130** having the parameters as at the point **316** exiting a low concentration turbine **LCT** as described below, passes through the third heat exchanger **HE13**, where it is cooled, releasing heat in the third heat exchange process as describe above, forming the stream **S140** having parameters as at a point **205**, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor. The pressure of the lean working fluid stream **S140** at point **205** is substantially lower than a pressure of the rich working fluid stream **S124** at point **300**, but because the stream **S140** having the parameters as at the point **205** has a substantially lower concentration of the low boiling component, it starts to condense at a temperature of the stream **S140** at point **205**, which is higher than a temperature of the fully vaporized, rich working fluid stream **S124** having the parameters as at the point **300**, which has a substantially higher pressure.

[0059] The returning lean working fluid stream **S140** having the parameters as at the point **205** is then divided into two substreams **S120** and **S142** having parameters as at points **206** and **207**, respectively. The stream **S120** having the parameters as at the point **206** passes through the second heat exchanger **HE12** where it is partially condensed in the second heat exchange process to form a stream **S144** having parameters as at a point **108**, releasing heat to the stream **S114** having the parameters as at the point **104** as described above.

[0060] Thereafter, the lean working fluid stream **S144** having the parameters as at the point **108** is combined with a vapor stream **S146** having parameters as at a point **109**, forming a combined vapor-liquid mixed stream **S148** having parameters as at a point **110**. A composition of the stream **S146** has an even higher concentration of the low boiling component than the rich working fluid stream **S124** having the parameters as at the point **300**. The stream **S148** having

the parameters as at the point 110 then enters into a separator S10, where it is separated into saturated vapor stream S150 having parameters as at a point 111, and saturated liquid stream S152 having parameters as at a point 112. The liquid stream S152 having parameters as at point 112 is then divided into two substreams S154 and S156 having parameters as at points 113 and 114, respectively.

[0061] Thereafter, the stream S156 having the parameters as at the point 114 is combined with the vapor stream S150 having the parameters as at the point 111, forming the stream S106 having the parameters as at the point 95, which has a composition equal or close to the composition of rich working fluid stream S124 having the parameters as at the point 300. The stream S106 having the parameters as at the point 95 is then sent into the first heat exchanger HE11, where it is fully condensed, forming the stream S110 having the parameters as at the point 98, and provides heat for the first heat exchange process as described above.

[0062] The liquid stream S154 having the parameters as at the point 113 enters into a second circulating pump P11, where it is pumped to a pressure sufficient to lift it to a top of a scrubber SC2, which is a direct contact heat / mass exchanger, forming a stream S158 having parameters as at a point 105. Upon reaching to the top of the scrubber SC2, stream S158 having the parameters as at the point 105 obtains parameters as at a point 102, and then enters the top of the scrubber SC2. The lean vapor stream S142 having the parameters as at the point 207 as describe above, enters a lower site of the scrubber SC2. As a result of mass and heat transfer between streams S158 and S142 having the parameters as at the point 102 and 207, respectively, a hot and lean liquid stream S160 having parameters as at a point 103 is collected at a bottom of the scrubber SC2. Meanwhile, the cooled and rich vapor stream S146 having the parameters as at the point 109, is formed at a upper site of the scrubber SC2. The liquid stream S160 having the parameters as at the point 103 is in a state of saturated liquid which is close to equilibrium with the vapor stream S142 having the parameters as at the point 207, whereas the vapor stream S146 having the parameters as at the point 109 is in a state of a saturated vapor close to equilibrium with the liquid stream S158 having the parameters as at the point 102. The vapor stream S146 having the parameters as at the point 109 is combined with the stream S144 having the parameters as at the point 108, forming the stream S148 having the parameters as at the point 110 as described above.

[0063] The liquid stream S160 having the parameters as at the point 103 enters into a second circulating pump P12, where it is pumped to a necessary high pressure, forming a stream S162 having parameters as at a point 203. The composition of the liquid streams S160 and S162 at the

points **103** and **203** are substantially leaner than the lean working fluid streams **S140**, **S120**, **S144** and **S142**.

[0064] The rich working fluid stream **S138** having the parameters as at the point **301** as described above, is then separated into two substreams **S164** and **S166** having parameters as at points **307** and **309**, respectively. The weight flow rate of the stream **S166** at point **309** is equal to the weight flow rate of rich working fluids stream **S100** entering the system at the point **29** from the CTCSS, whereas the flow rate of the stream **S164** at point **307** is equal to the weight flow rate of the stream **S106** at the point **95**. Alternatively, as shown in **Figure 3** illustrating **Variant 1a1**, the stream **S138** having the parameters as at the point **301** is not split into two substreams and instead all of stream **S138** is vaporized and forwarded to the throttle control valve **TV11**. To correct the composition of the stream **S130** having parameters as at the point **316**, the stream **S134** having parameters as at the point **412** is split into two substreams **S192** and **S194** having parameters as at points **337** and **338**, respectively. The stream **S192** is forwarded to the heat exchanger **HE16** emerging as the stream **S180** having the parameters as at the point **413**. The stream **S194** having the parameters as at the point **338** is then mixed with the stream **S130** having the parameters as at the point **316** forming a stream **S196** having parameters as at a point **339** which is then forwarded to the heat exchanger **HE13** emerging as the stream **S126** having the parameters as at the point **321**.

[0065] The stream **S164** having the parameters as at the point **307** passes through a third throttle valve **TV12**, forming a stream **S168** having parameters as at a point **306**. The subcooled liquid stream **S162** having the parameters as at the point **203** as describe above, passes through a seventh heat exchanger **HE17**, where it is heated and fully vaporized in counterflow in a seventh heat exchange process by the stream **S116** of flue gas having initial parameter as at the point **601** and final parameters as at the point **602** as described below, forming a stream **S170** having parameters as at a point **303**, corresponding, or close to, a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor.

[0066] Thereafter, the stream **S170** having the parameters as at the point **303** is combined with the stream **S168** having the parameters as at the point **306**, forming a stream **S172** having parameters as at a point **308**. The composition and mass flow rate of stream **S172** at the point **308** is the same as the composition and mass flow rate of stream **S140** at the point **205** as described above, where the composition comprises the lean working fluid.

[0067] The rich working fluid stream **S166** having the parameters as at the point **309** passes

through a fifth heat exchanger **HE15**, where it is heated in counterflow in a fifth heat exchange step by a stream **S174a** of a high temperature heat transfer agent having initial parameters as at a point **501** and final parameters as at a point **502** as described below, forming a stream **S176** having parameters as at point **409**. Thereafter, the stream **S176** having the parameters as at the point **409** passes through an admission valve **TV11**, forming a rich working fluid stream **S178** having parameters as at a point **410**, and enters into a high pressure turbine **HPT**, where it expands, producing power, and becomes the stream **S134** having the parameters as at the point **412**. Thereafter, the stream **S134** having the parameters as at the point **412** passes through the sixth heat exchanger **HE16**, where it is cooled, releasing heat in the sixth heat exchange process, forming a stream **S180** having parameters as at a point **413**. The rich working fluid stream **S180** having the parameters as at the point **413** enters into the low pressure turbine **LPT**, where it expands, producing power, and becomes a stream **S182** having parameters as at a point **138**. The stream **S182** having parameters as at point **138**, which in the preferred embodiment shall be in, or close to a state of saturated vapor and is then sent into the CTCSS.

[0068] The lean working fluid stream **S172** having the parameters as at the point **308** passes through a fourth heat exchanger **HE14**, where it is heated in counterflow in a fourth heat exchange process by a stream **S174b** of the high temperature heat transfer agent having initial parameters as at a point **503** and final parameters as at a point **504** as described below, forming a stream **S184** having parameters as at a point **408**. The stream **S184** having the parameters as at the point **408** passes through a second admission valve **TV10**, forming a lean working fluid stream **S186** having parameters as at a point **411**, and enters into the low concentration working solution turbine **LCT** as described above, where it is expanded, producing power, and becomes the stream **S130** having the parameters as at the point **316**. The stream **S130** having the parameters as at the point **316** then passes through the third heat exchanger **HE13**, where it is cooled, releasing heat for the third heat exchange process, forming the stream **S140** having the parameters as at the point **205** as describe above.

[0069] If a pressure of the low-concentration working fluid stream **S186** having the parameters as at the point **411** at an inlet to the low concentration working fluid turbine **LCT** as described above, is equal to a pressure of the rich working fluid stream **S178** having the parameters as at the point **410** at an inlet to the high pressure turbine **HPT**, then the pressure of stream **307** does not change when it passes through the third throttle valve **TV12**, and thus the parameters of the stream **S168** at the point **306** are the same as the parameters of the stream **S164** at the point **307**.

[0070] The acquisition of heat by the system of this invention occurs mostly in the superheater

heat exchangers **HE14** and **HE15**, where the working fluid is superheated. In the process of superheating, the film heat transfer coefficient inside the heat exchanger tubes is relatively low, and as a result, if these tubes were to be directly exposed to hot flue gas, then they would be overheated and would suffer severe damage. Therefore, a heat transfer process from the stream **S116** of flue gas to the stream **S174** of the high temperature heat transfer agent is implemented. Thus, the stream **S174** of hot flue gas from the combustion zone or combustion reactor, having initial parameters as at a point **600** passes through a furnace heat exchanger or eighth heat exchanger **F/HE19**, where it is cooled, and obtains final parameters as at the point **601**, transferring heat to the stream **S174** of the high temperature heat transfer agent having initial parameters as at a point **509** and final parameters as at a point **500** as described below. Thereafter, the stream **S174** having the parameters as at the point **500** is divided into the two substreams **S174a** and **S174b** having parameters as at the points **501** and **503**, respectively.

[0071] The high temperature heat transfer agent can be liquid metals, molten salts, or other well known substances. In the tables that follow, the high temperature heat transfer agent is referred to as THERM.

[0072] After the streams **S174b** and **S174a** transfer heat in the fourth and fifth heat exchangers **HE14** and **HE15** to the streams **S166** and **S172**, the streams **S174a** and **S174b** having the parameters as at the points **502** and **504** are combined, reforming the stream **S174** having parameters as at a point **505**. The stream **S174** having the parameters as at the point **505** enters into a therm circulating pump **PT**, where it is pumped to an increased pressure sufficient to provide for a desired circulation rate of the high temperature heat transfer agent, changing the parameters of the stream **S174** to the parameters as at the point **509**.

[0073] The stream **S116** of flue gas having the parameters as at the point **601** exiting from the furnace heat exchanger **F/HE19** as described above, has been cooled to a moderate temperature, and is used further to transfer heat to the stream **S162** and **S114** in the seventh and fourth heat exchange processes in heat exchangers **HE17** and **HE20** as described above. The stream **S116** of flue gas may be further cooled in a CTCSS that is more complex than a simple condenser, providing more complete utilization of available heat from the flue gas stream **S116**.

[0074] A flow diagram of a simple condenser for use in the system of this invention is shown in **Figure 2**, and operates as follows. The rich working fluid stream **S182** having the parameters as at the point **138** passes through a **Condenser**, where it is cooled and fully condensed in counterflow with a stream **S188** of cooling water or air having initial parameters as at a point **51** at an inlet of the Condenser and final parameters as at a point **52** at an outlet of the Condenser,

forming a stream **S190** having parameters as at a point **27**, corresponding to a state of saturated liquid. Thereafter, the fully condensed, rich working fluid stream **S190** having the parameters as at the point **27** is pumped by a feed pump **PF**, to a required high pressure, forming the stream **S100** having the parameters as the point **29**, which is sent back into the system.

[0075] The inventor has performed computations for **Variant 1a**, where hot air was used as the heat source, instead of flue gas. This was done for purposes of generalization because flue gas may have different compositions in different systems. One experienced in the art can easily substitute flue gas for air in the computations. For the purposes of these computations, the specific heat capacity of the high temperature, heat transfer agent, THERM has been set equal to 1. Substituting the actual heat capacity of any specific high temperature, heat transfer agent would change only a weight flow rate of the agent in the high temperature fluid subsystem. One experienced in the art can easily make and calculate such a substitution.

[0076] The parameters of all key points of the **Variant 1a** of the system of this invention, with a simple condenser, are presented in **Table 1**.

TABLE 1
Parameters of the Streams associated with Key Operating Points

Pt.	X	T	P	H	S	G rel	Ph.	Wetness or T
	lb/lb	°F	psia	Btu/lb	Btu/lb-R	G/G=1		lb/lb or °F
Working Fluid								
27	0.8300	65.80	98.823	-17.0503	0.0497	1.00000	Mix	1
28	0.8300	71.82	1,900.000	-6.6035	0.0549	1.00000	Liq	-255.73°F
29	0.8300	71.82	1,900.000	-6.6035	0.0549	1.00000	Liq	-255.73°F
91	0.8300	141.45	1,900.000	73.1694	0.1958	1.82982	Liq	-186.1°F
92	0.8300	220.46	1,900.000	169.3026	0.3460	0.82982	Liq	-107.1°F
95	0.8300	348.73	732.429	734.9088	1.1336	0.82982	Mix	0.0207
98	0.8300	213.54	730.429	161.7429	0.3438	0.82982	Mix	1
101	0.8300	326.73	1,890.000	333.0983	0.5685	1.82982	Mix	1
102	0.3506	348.73	734.429	261.4583	0.5117	0.71068	Liq	-0.34°F
103	0.1658	429.15	735.429	377.8855	0.6235	0.72008	Mix	1
104	0.8300	326.73	1,890.000	333.0983	0.5685	1.58780	Mix	1
105	0.3506	348.92	764.429	261.7082	0.5119	0.71068	Liq	-5°F
106	0.8300	326.73	1,890.000	333.0983	0.5685	0.24202	Mix	1

Pt.	X	T	P	H	S	G rel	Ph.	Wetness or T
108	0.5214	335.73	732.429	381.3522	0.6725	1.02270	Mix	0.714
109	0.7815	369.42	734.429	783.3991	1.1881	0.51780	Mix	0
110	0.6088	348.73	732.429	516.4913	0.8467	1.54050	Mix	0.4725
111	0.8401	348.73	732.429	744.9260	1.1468	0.81263	Mix	0
112	0.3506	348.73	732.429	261.4587	0.5117	0.72788	Mix	1
113	0.3506	348.73	732.429	261.4583	0.5117	0.71068	Mix	1
114	0.3506	348.73	732.429	261.4583	0.5117	0.01719	Mix	1
117	0.8300	0.00	14.693	0.0000	0.0000	0.00000	Mix	0
129	0.8300	71.82	1,900.000	-6.6035	0.0549	1.00000	Liq	-255.73°F
138	0.8300	228.51	100.823	733.8930	1.3382	1.00000	Mix	0
203	0.1658	433.73	1,880.000	383.5250	0.6248	0.72008	Liq	-121.56°F
205	0.5214	431.15	735.429	933.1136	1.3205	1.54990	Mix	0
206	0.5214	431.15	735.429	933.1136	1.3205	1.02270	Mix	0
207	0.5214	431.15	735.429	933.1136	1.3205	0.52720	Mix	0
300	0.8300	413.15	1,885.000	688.4858	0.9996	1.82982	Mix	0
301	0.8300	805.05	1,870.000	1,042.1481	1.3416	1.82982	Vap	392.2°F
302	0.8300	413.15	1,885.000	688.4858	0.9996	0.24202	Mix	0
303	0.1658	595.47	1,870.000	1,065.4074	1.2954	0.72008	Mix	0
304	0.8300	413.15	1,885.000	688.4858	0.9996	1.58780	Mix	0
306	0.8300	805.05	1,870.000	1,042.1481	1.3416	0.82982	Vap	392.2°F
307	0.8300	805.05	1,870.000	1,042.1481	1.3416	0.82982	Vap	392.2°F
308	0.5214	677.54	1,870.000	1,052.9544	1.3522	1.54990	Vap	160.6°F
309	0.8300	805.05	1,870.000	1,042.1481	1.3416	1.00000	Vap	392.2°F
316	0.5214	841.33	742.429	1,216.8921	1.5835	1.54990	Vap	409.3°F
320	0.8300	823.33	1,870.000	1,056.0742	1.3525	1.19652	Vap	410.5°F
321	0.8300	413.15	1,885.000	688.4858	0.9996	1.19652	Mix	0
322	0.8300	413.15	1,885.000	688.4858	0.9996	0.63329	Mix	0
323	0.8300	770.56	1,870.000	1,015.8366	1.3205	0.63329	Vap	357.7°F
408	0.5214	1,051.47	1,850.000	1,333.8795	1.5676	1.54990	Vap	535.4°F
409	0.8300	1,050.96	1,850.000	1,231.5125	1.4796	1.00000	Vap	638.6°F
410	0.8300	1,050.00	1,800.000	1,231.5125	1.4826	1.00000	Vap	638.9°F

Pt.	X	T	P	H	S	G rel	Ph.	Wetness or T
411	0.5214	1,050.00	1,800.000	1,333.8795	1.5706	1.54990	Vap	536.4°F
412	0.8300	788.56	512.867	1,063.5002	1.5021	1.00000	Vap	460.6°F
413	0.8300	476.33	505.867	856.1914	1.3128	1.00000	Vap	149.3°F
Heat Source								
500	THERM	1,075.00	14.693	1,043.0000	1.0990	1.94210	Liq	
501	THERM	1,075.00	14.693	1,043.0000	1.0990	0.77309	Liq	
502	THERM	830.05	14.693	798.0544	0.9251	0.77309	Liq	
503	THERM	1,075.00	14.693	1,043.0000	1.0990	1.16901	Liq	
504	THERM	702.54	14.693	670.5431	0.8210	1.16901	Liq	
505	THERM	753.30	14.693	721.3013	0.8637	1.94210	Liq	
509	THERM	753.30	14.693	721.3013	0.8637	1.94210	Liq	
600	AIR	1,742.00	13.193	466.2399	0.8560	3.27620	Vap	2056.2°F
601	AIR	1,045.33	13.121	275.5404	0.7524	3.27620	Vap	1359.6°F
602	AIR	458.73	13.049	125.6680	0.6270	3.27620	Vap	773.1°F
603	AIR	351.73	12.976	99.4151	0.5970	3.27620	Vap	666.2°F
638	AIR	351.73	12.976	99.4151	0.5970	3.27620	Vap	666.2°F
639	AIR	351.73	12.976	99.4151	0.5970	3.27620	Vap	666.2°F
Coolant								
51	water	51.80	68.773	20.0769	0.0396	14.1078	Liq	-249.93°F
52	water	105.08	58.773	73.3057	0.1387	14.1078	Liq	-186.27°F

[0077] In the system of this invention, as described above, the flue gas which is the heat source used to generate usable energy is cooled to a relatively low temperature. This cooling is possible only in the case where such flue gas is not corrosive, as in the case of biomass combustion or clean coal combustion. But in a case where the flue gas is corrosive, as in the case of municipal waste incineration, *etc.*, it can be cooled only to a relatively high temperature. In the case, where the flue gas can only be cooled to a relatively high temperature, the ninth heat exchanger **HE20** is excluded from the system, and the stream **S116** of flue gas having the parameters as at the point **602** is sent to a stack. The variant of the system of this invention in which the ninth heat exchanger **HE20** is excluded is referred to as **Variant 2a** and is shown in **Figure 4**. It is evident that in this case, the entire stream **S108** having the parameters as at the

point 101 is sent into the second heat exchanger **HE12**, forming directly the stream **S124** having the parameters as at the point 300. Alternatively, as shown in **Figure 5** illustrating **Variant 1a1**, the stream **S138** having the parameters as at the point 301 is not split into two substreams and instead all of stream **S138** is vaporized and forwarded to the throttle control valve **TV11**. To correct the composition of the stream **S130** having parameters as at the point 316, the stream **S134** having parameters as at the point 412 is split into two substreams **S192** and **S194** having parameters as at points 337 and 338, respectively. The stream **S192** is forwarded to the heat exchanger **HE16** emerging as the stream **S180** having the parameters as at the point 413. The stream **S194** having the parameters as at the point 338 is then mixed with the stream **S130** having the parameters as at the point 316 forming a stream **S196** having parameters as at a point 339 which is then forwarded to the heat exchanger **HE13** emerging as the stream **S126** having the parameters as at the point 321.

[0078] Both **Variants 1a** and **Variants 2a** can be simplified by excluding the intercooler or the sixth heat exchanger **HE16**. Such a simplification results in a reduction in an efficiency of the system of this invention to an extent which will be demonstrated below. This simplified variant of the system (with the intercooler **HE16** excluded) when applied to **Variant 1a** shall be referred to as **Variant 1b**, and is shown in **Figure 6**. The analogous simplification of **Variant 2a** is shown in **Figure 7** and is referred to as **Variant 2b**. For the **Variants 1b** and **Variants 2b**, the two stage turbine subsystem for the high concentration or rich working fluid stream **S178** is replaced by a single high concentration working fluid turbine **HCT**, and the stream of rich working fluid stream **S182** having the parameters as at the point 138 exiting the high concentration working fluid turbine **HCT** will be in a state of superheated vapor.

[0079] Both **Variants 1b** and **Variants 2b** may be further simplified by excluding the superheater or fifth heat exchanger **HE15**. In these cases, the rich working fluid stream **S166** having the parameters as at the point 309 is superheated only recuperatively, and is then sent directly into the high pressure turbine **HPT**. This simplification also results in a reduced efficiency in the system of this invention. Such simplified variants of the system excluding the superheater **HE15**, shall be designated as **Variant 1c** when applied to the **Variant 1b**, as shown in **Figure 8**. The analogous simplification of **Variant 2b** is referred to as **Variant 2c** as shown in **Figure 9**. It should be clear that **Variants 2a**, **Variants 2b** and **Variants 2c** can be used not only in cases where the flue gas must not be cooled to too low a temperature, but also as simplifications of **Variants 1a**, **Variants 1b** and **Variants 1c**, respectively.

[0080] Usually, in **Variants 1a**, **Variants 2a**, **Variants 1b** and **Variants 2b**, the temperatures

of admission into high pressure turbine **HPT** or the high concentration working fluid turbine **HCT** and low concentration working stream turbine **LCT** are the same, or very close, where very close means that the temperatures are within about 2.5% of each other. If these temperatures are high enough, then the pressure at the turbine inlet of the low concentration working fluid stream **LCT** for the lean working fluid stream **S186** having the parameters as at the point **411** is the same as the pressure at the turbine inlet to **HPT** or **HCT** for the rich working fluid stream **S178** having the parameters as at the point **410**, and after expansion the lean working fluid stream **S130** having the parameters as at the point **316** is in a state of superheated vapor and can be cooled in the third heat exchanger **HE13**. But if the temperature of admission is relatively low, then the state of the lean working fluid stream **S130** having the parameters as at the point **316** could be a state of saturated or even wet vapor. However, for the operation of the second heat exchanger **HE12** and the scrubber **SC2**, it is necessary that the temperature of the stream **S130** at the point **316** is not lower than a required temperature of the stream **S140** at the point **205**. Therefore, in the case that the temperature of admission is too low, the inlet pressure for the low concentration working fluid turbine **LCT** must be lowered so that the temperature of the stream **S130** at the point **316** would not be lower than a required temperature for the stream **S140** at the point **205**. In such a case, the pressures of the streams **S162**, **S172**, **S140**, and **S184** at points **203**, **308**, **205** and **408** are correspondingly lowered and the stream **S164** having the parameters as at the point **307**, while passing through the third throttle valve **TV12**, has its pressure reduced so that the pressure of the stream **S168** at point **306** is equal to the pressure of the stream **S170** at point **303**. It is evident that in this case, the third heat exchanger **HE13** is not used and does not exist.

[0081] It is clear from the above that the lean working fluid stream **S140** having the parameters as at the point **205**, after partial condensation in the second heat exchanger **HE12** and the heat and mass transfer process in the scrubber **SC2**, has been separated into two streams; a stream **S106** of rich working fluid with a composition as at the point **95** and a streams **S160** and **S162** of lean liquid with a composition as at the points **103** and **203**. Stream **S106** having the parameters as at the point **95** was then combined with a stream **S100** having the parameters as at the point **29** of rich working fluid entering into the system from the CTCSS, and then was fully vaporized together with the rich working fluid stream **S114** in the ninth heat exchanger **HE20** and the rich working fluid stream **S112** in the second heat exchanger **HE12**. As a result, a substantial portion of the initial stream **S140** having the parameters as at the point **205** has been re-vaporized at a high pressure by heat released by the partial condensation of the same stream **S140** having the parameters as at the point **205** at low pressure. This is an important aspect of the

system of this invention.

[0082] The system of this invention, as described above, includes two inlet streams, *i.e.*, the stream **S116** of flue gas having the parameters as at the point **600**, and pressurized subcooled liquid stream **S100** having the parameters as at the point **29**. The system also includes two outlet streams, *i.e.*, the cooled stream **S116** of flue gas having the parameters as at the point **603** in the case of **Variants 1a** and **1b**, and the stream **S116** having the parameters as at the point **602** in the case of **Variant 2a** and **Variant 2b**. The system of this invention also includes a rich working fluid vapor stream **S182** having the parameters as at the point **138**, which has been expanded in the low pressure turbine **LPT** portion of the rich working turbine assembly, *i.e.*, the high pressure turbine and the low pressure turbine in **Variants 1a** and **2a** and the high concentration working fluid turbine **LCT** of **Variants 1b&c** and **2b&c**.

[0083] The stream **S182** having the parameters as at the point **138** must be condensed and then pumped to a pressure equal to that of the stream **S100** at point **29**. The simplest way to do so is to pass the stream **S182** having the parameters **138** through a condenser cooled by outside water or air as described above. The relative performances of six variants of the system of this invention as described above, operating with a simple condenser as shown in **Figure 2**, at ambient ISO conditions (the temperature of air is 59°F; relative humidity of the air is 60% at sea level), are shown in **Table 2**. In **Table 2**, the **Variant 1b** of this invention is shown as having a net output of 10,000 kW. For all other variants, the same heat source is assumed.

[0084] The performance and efficiency of the system of this invention can be significantly increased if it is combined with a CTCSS in place of the simple condenser as described above. The use of an CTCSS allows for the pressure of condensation, and correspondingly the pressure of the stream **S182** having the parameters as at the point **138**, to be substantially lower than is possible using a simple condenser. This will increase the power output of the low pressure turbine **LPT** and the efficiency of the system as a whole. Therefore, in alternate embodiments of the system of this invention, the stream **S182** having the parameters as at the point **138** is sent into a one of several variants of a condensation thermal compression subsystem (CTCSS) where it can be condensed at a pressure significantly lower than the required pressure of condensation of the rich composition working fluid at an ambient temperature, resulting in increased efficiency.

[0085] In a previous application devoted specifically to different variants of the CTCSS, 5 basic variants of CTCSS were described. Each variant of the CTCSS could be embodied in two subvariants, a & b; with (a), and without (b), preheating of the condensed working fluid. For the

proposed system, variants of the CTCSS without preheating of the working fluid are preferred. [0086] For the **Variant 1a-c** of the system this invention, all five variants of the CTCSS can be used. Since **Variant 2a-c** of the system the present invention do not allow for cooling of the flue gas to a low temperature, only **Variants 3-5** of the CTCSS can be used with **Variant 2a-c** of the system this invention.

[0087] The relative performance, at ISO conditions, of **Variant 1a** and **Variant 1b** and **Variant 2a** and **Variant 2b** of the system of this invention, assuming the same heat source and using a simple condenser to condense the stream **S182** to form the stream **S100** are tabulated in **Table 2**. The relative performance, at ISO conditions, of **Variant 1a** and **Variant 1b** and **Variant 2a** and **Variant 2b** with different variants of the CTCSS without preheating as described above are tabulated in **Table 3**.

Table 2
Power Efficiency Data for Variants 1a-c and 2a-c Using a Simple Condenser

System	Net output kW	Thermal efficiency %	Utilization of heat source LHV %	LHV efficiency %	Increment al output %	Pressure at point 138 psia
Variant 1a	10698.28	35.625	83.822	29.861	6.983	100.823
Variant 1b	10000.00	33.305	83.821	27.913	0.0	100.823
Variant 1c	9955.93	33.118	83.912	27.790	-0.441	100.823
Variant 2a	9922.94	35.678	77.633	27.698	-0.771	100.823
Variant 2b	9517.60	34.222	77.631	26.566	-4.824	100.823
Variant 2c	9507.26	34.184	77.631	26.537	-4.927	100.823

Table 3
Power Efficiency Data for Variants 1a-b and 2a-b Using a Different CTCSS Variants

System	Net output kW	Thermal efficiency %	Utilization of heat source LHV %	LHV efficiency %	Incremental output %	Pressure at point 138 psia
Variant 1a CTCSS 5b	11208.88	37.326	83.822	31.287	12.089	73.526
Variant 1a CTCSS 4b	11618.05	38.689	83.822	32.430	16.181	54.382
Variant 1a CTCSS 3b	11721.75	39.035	83.820	32.719	17.218	50.416
Variant 1a CTCSS 2b	11866.93	26.282	91.292	33.123	18.669	44.600
Variant 1a CTCSS 1b	11977.69	38.530	91.522	33.433	19.777	40.842
Variant 1b CTCSS 5b	10871.47	36.203	83.821	30.346	8.751	59.368
Variant 1b CTCSS 4b	11235.70	37.416	83.821	31.362	12.357	45.079
Variant 1b CTCSS 3b	11335.75	37.749	83.821	31.641	12.358	42.067
Variant 1b CTCSS 2b	11430.25	35.020	91.105	31.905	14.303	38.972
Variant 1b CTCSS 1b	11550.80	35.294	91.105	32.242	15.508	35.772
Variant 2a CTCSS 5b	10470.85	37.645	77.633	29.227	4.709	73.526
Variant 2a CTCSS 4b	10899.85	39.188	77.637	30.425	8.999	54.382
Variant 2a CTCSS 3b	11006.77	39.537	77.637	30.723	10.068	50.416
Variant 2b CTCSS 5b	10313.04	37.082	77.631	28.787	3.130	59.368
Variant 2b CTCSS 4b	10647.78	38.283	77.635	29.721	6.478	45.079
Variant 2b CTCSS 3b	10739.09	38.611	77.635	29.976	7.391	42.067

[0088] In sum, the system of this invention consists of 6 variants. In combination with a simple condenser and various variants of the CTCSS, there are 30 possible embodiments and combinations of the power system of this invention. One experienced in the art will be able to select the variant and combination of the system of this invention and a simple condenser or a CTCSS such as will suit any given economic and technical conditions.

[0089] Current state of the art biomass powerplants have an LHV efficiency not exceeding 20%. In contrast, the most simple and least efficient variant of the system of this invention, **Variant 2c** using a simple condenser, has an LHV efficiency of 26.537%; *i.e.*, 1.327 time higher than the state of the art biomass powerplants operated to date. The most efficient variant of the system

of this invention, **Variant 1a** with **Variant 1b** of the CTCSS has an LHV efficiency of 33.433%; *i.e.*, 1.672 times higher than the current state of the art.

CTCSS Variant 1a

[0090] Referring now to **Figure 2**, a preferred embodiment of a CTCSS of this invention, generally **190**, is shown and is referred to herein as **CTCSS Variant 1a**. **CTCSS Variant 1a** represents a very comprehensive variant of the CTCSSs of this invention.

[0091] The operation of **CTCSS Variant 1a** of the CTCSS of this invention is now described.

[0092] A stream **S182** having parameters as at a point **138**, which can be in a state of superheated vapor or in a state of saturated or slightly wet vapor, enters into the CTCSS **200**. The stream **S182** having the parameters as at the point **138** is mixed with a first mixed stream **S202** having parameters as at a point **71**, which is in a state of a liquid-vapor mixture (as describe more fully herein), forming a first combined stream **S204** having parameters as at a point **38**. If the stream **S182** having the parameters as at the point **138** is in a state of saturated vapor, then a temperature of the stream **S202** having the parameters as at the point **71** must be chosen in such a way as to correspond to a state of saturated vapor. As a result, the stream **S204** having the parameters as at the point **38** will be in a state of a slightly wet vapor. Alternatively, if the stream **S182** having the parameters as at the point **138** is in a state of superheated vapor, then stream **S202** having the parameters of at the point **71** must be chosen in such a way that the resulting stream **S204** having the parameters as at a point **38** should be in, or close to, a state of saturated vapor, where close to means the state of the vapor is within 5% of the saturated vapor state for the vapor. In all cases, the parameters of the stream **S202** at the point **71** are chosen in such a way as to maximize a temperature of the stream **S204** at the point **38**.

[0093] Thereafter, the stream **S204** having the parameters as at the point **38** passes through a first heat exchanger **HE1**, where it is cooled and partially condensed and releases heat in a first heat exchange process, producing a second mixed stream **S206** having parameters as at a point **15**. The stream **S206** having the parameters as at the point **15** is then mixed with a stream **S208** having parameters as at a point **8**, forming a stream **S210** having parameters as at a point **16**. In the preferred embodiment of this system, the temperatures of the streams **S208**, **S206** and **S210** having parameters of the points **8**, **15**, and **16**, respectively, are equal or very close, within about 5%. A concentration of the low-boiling component in stream **S208** having the parameters as at the point **8** is substantially lower than a concentration of the low boiling component in the stream **S206** having the parameters as at the point **15**. As a result, a concentration of the low boiling component in the stream **S210** having the parameters as at the point **16** is lower than the

concentration of the low boiling component of the stream **S206** having the parameters as at the point **15**, *i.e.*, stream **S210** having the parameters as at the point **16** is leaner than stream **S206** having the parameters as at the point **15**.

[0094] The stream **S210** having the parameters as at the point **16** then passes through a second heat exchanger **HE2**, where it is further condensed and releasing heat in a second heat exchange process, forming a stream **S212** having parameters as at a point **17**. The stream **S212** having the parameters as at the point **17** then passes through a third heat exchanger **HE3**, where it is further condensed in a third heat exchange process to form a stream **S214** having parameters as at a point **18**. At the point **18**, the stream **S214** is partially condensed, but its composition, while substantially leaner than the compositions of the stream **S182** and **S204** having the parameters as at the points **138** and **38**, is such that it cannot be fully condensed at ambient temperature. The stream **S214** having the parameters as at the point **18** is then mixed with a stream **S216** having parameters as at a point **41**, forming a stream **S218** having parameters as at a point **19**. The composition of the stream **S218** having the parameters as at the point **19** is such that it can be fully condensed at ambient temperature.

[0095] The stream **S218** having the parameters as at the point **19** then passes through a low pressure condenser **HE4**, where it is cooled in a fourth heat exchange process in counterflow with a stream **S220** of cooling water or cooling air having initial parameters as at a point **51** and final parameters as at a point **52**, becoming fully condensed, to form a stream **S222** having parameters as at a point **1**. The composition of the stream **S222** having the parameters as at the point **1**, referred to herein as the "basic solution," is substantially leaner than the composition of the stream **S182** having the parameters at the point **138**, which entered the CTCSS **100**. Therefore, the stream **S222** having the parameters as at the point **1** must be distilled at an elevated pressure in order to produce a stream **S182** having the same composition as at point **138**, but at an elevated pressure that will allow the stream to fully condense.

[0096] The stream **S222** having the parameters as at the point **1** is then divided into two substreams **S224** and **S226** having parameters as at points **2** and **4**, respectively. The stream **S224** having the parameters as at the point **2** enters into a circulating fourth pump **P4**, where it is pumped to an elevated pressure forming a stream **S228** having parameters as at a point **44**, which correspond to a state of subcooled liquid. Thereafter, the stream **S228** having the parameters as at the point **44** passes through a third heat exchanger **HE3** in counterflow with the stream **S212** having the parameters as at the point **17** in a third heat exchange process as described above, is heated forming a stream **S230** having parameters as at a point **14**. The stream

S230 having the parameters as at the point **14** is in, or close to, a state of saturated liquid. Again, the term close to means that the state of the stream **S230** is within 5% of being a saturated liquid. Thereafter, the stream **S230** having parameters as at point **14** is divided into two substreams **S232** and **S234** having parameters as at points **13** and **22**, respectively. The stream **S234** having the parameters as at the point **22** is then divided into two substreams **S236** and **S238** having parameters as at points **12** and **21**, respectively. The stream **S236** having the parameters as at the point **12** then passes through the second heat exchanger **HE2**, where it is heated and partially vaporized in counterflow to the stream **S200** having the parameters as at the point **16** as described above in a second heat exchange process, forming a stream **S240** having parameters as at a point **11**. The stream **S240** having the parameters as at the point **11** then passes through the first heat exchanger **HE1**, where it is further heated and vaporized in counterflow to the stream **S204** having stream **38** as described above in a first heat exchange process, forming a stream **S242** having parameters as at a point **5**.

[0097] The stream **S242** having the parameters as at the point **5**, which is in a state of a vapor-liquid mixture, enters into a first separator **S1**, where it is separated into a saturated vapor stream **S244** having parameters as at a point **6** and saturated liquid stream **S246** having parameters as at a point **7**.

[0098] The liquid stream **S246** having the parameters as at the point **7** is divided into two substreams **S248** and **S250** having parameters as at points **70** and **72**, respectively. The stream **S248** having the parameters as at the point **70**, then passes through an eighth heat exchanger **HE8**, where it is heated and partially vaporized in an eighth heat exchange process, in counterflow to an external heat carrier stream **S252** having initial parameters as a point **638** and final parameters as at a pint **639**, forming a stream **S254** having parameters as at a point **74**. Thereafter, stream **S254** having the parameters as at the point **74** passes through a fifth throttle valve **TV5**, where its pressure is reduced to a pressure equal to a pressure of the stream **S182** having the parameters as at the point **138**, forming the stream **S202** having the parameters as at the point **71**. Thereafter, the stream **S202** having the parameters as at the point **71** is mixed with the stream **S182** having the parameters as at the point **138**, forming the stream **S204** having the parameters as at the point **38** as previously described.

[0099] The stream **S250** having parameters as at point **72**, then passes through a first throttle valve **TV1**, where its pressure is reduced, forming a stream **S256** having parameters as at a point **73**. The pressure of the stream **S256** having the parameters as at the point **73** is equal to a pressure of the streams **S206**, **S208**, and **S210** having the parameters as at the points **15**, **8** and

16. Thereafter the stream **S256** having the parameters as at the point **73** is mixed with a stream **S258** having parameters as at a point **45**, forming the stream **S208** having the parameters as at the point **8**. The stream **S208** having the parameters as at the point **8** is then mixed with the stream **S206** having the parameters as at the point **15**, forming the stream **S210** having the parameters as at the point **16** as described above.

[00100] Meanwhile, the vapor stream **S244** having the parameters as at the point **6** is sent into a bottom part of a first scrubber **SC1**, which is in essence a direct contact heat and mass exchanger. At the same time, the stream **S238** having the parameters as at the point **21** as described above, is sent into a top portion of the first scrubber **SC1**. As a result of heat and mass transfer in the first scrubber **SC1**, a liquid stream **S260** having parameters as at a point **35**, which is in a state close to equilibrium (close means within about 5% of the parameters of the stream **S244**) with the vapor stream **S244** having the parameters as at the point **6**, is produced and removed from a bottom of the first scrubber **SC1**. At the same time, a vapor stream **S262** having parameters as at point **30**, which is in a state close to equilibrium with the liquid stream **S238** having the parameters as at the point **21**, exits from a top of the scrubber **SC1**.

[00101] The vapor stream **S262** having the parameters as at the point **30** is then sent into a fifth heat exchanger **HE5**, where it is cooled and partially condensed, in counterflow with a stream **S264** of working fluid having parameters as at a point **28** in a fifth heat exchange process, forming a stream **S266** having parameters as at a point **25**.

[00102] The liquid stream **S260** having the parameters as at the point **35** is removed from the bottom of the scrubber **SC1** and is sent through a fourth throttle valve **TV4**, where its pressure is reduced to a pressure equal to the pressure of the stream **S256** having the parameters as at the point **73**, forming the stream **S258** having the parameters as at the point **45**. The stream **S258** having the parameters as at the point **45** is then mixed with the stream **S256** having the parameters as at the point **73**, forming the stream **S208** having the parameters as at the point **8** as described above.

[0103] The liquid stream **S232** having the parameters as at the point **13**, which has been preheated in the third heat exchanger **HE3** as described above, passes through a second throttle valve **TV2**, where its pressure is reduced to an intermediate pressure, (*i.e.*, a pressure which is lower than the pressure of the stream **S230** having the parameter as at the point **14**, but higher than the pressure of the stream **S222** having the parameters as at the point **1**), forming a stream **S268** parameters as at a point **43**, corresponding to a state of a vapor-liquid mixture. Thereafter, the stream **S268** having the parameters as at the point **43** is sent into a third separator **S3**, where

it is separated into a vapor stream **S270** having parameters as at a point **34** and a liquid stream **S272** having parameters as at a point **32**.

[0104] A concentration of the low boiling component in the vapor stream **S270** having the parameters as at the point **34** is substantially higher than a concentration of the low boiling component in the stream **S182** having the parameters as at the point **138** as it enters the CTCSS **200** as described above. The liquid stream **S272** having the parameters as at the point **32** has a concentration of low boiling component which is less than a concentration of low boiling component in the stream **S222** having the parameters as at the point **1** as described above.

[0105] The liquid stream **S226** of the basic solution having the parameters as at the point **4** as described above, enters into a first circulating pump **P1**, where it is pumped to a pressure equal to the pressure of the stream **S270** having the parameters as at the point **34**, forming a stream **S274** having parameters as at a point **31** corresponding to a state of subcooled liquid. Thereafter, the subcooled liquid stream **S274** having the parameters as at the point **31** and the saturated vapor stream **S270** having the parameters as at the point **34** are combined, forming a stream **S276** having parameters as at a point **3**. The stream **S276** having the parameters as at the point **3** is then sent into an intermediate pressure condenser or a seventh heat exchanger **HE7**, where it is cooled and fully condensed in a seventh heat exchange process, in counterflow with a stream **S278** of cooling water or air having initial parameters as at a point **55** and having final parameters as at a point **56**, forming a stream **S280** having parameters as at a point **23**. The stream **S280** having parameters as at point **23** then enters into a second circulating pump **P2**, where its pressure is increased to a pressure equal to that of the stream **S266** having the parameters as at the point **25** as described above, forming a stream **S282** parameters as at a point **40**. The stream **S282** having the parameters as at the point **40** is then mixed with the stream **S266** having the parameters as at the point **25** as described above, forming a stream **S284** having parameters as at a point **26**. The composition and flow rate of the stream **S282** having the parameters as at the point **40** are such that the stream **S284** having the parameters as at the point **26** has the same composition and flow rate as the stream **S182** having the parameters as at the point **138**, which entered the CTCSS **100**, but has a substantially higher pressure.

[0106] Thereafter, the stream **S284** having the parameters as at the point **26** enters into a high pressure condenser or sixth heat exchanger **HE6**, where it is cooled and fully condensed in a sixth heat exchange process, in counterflow with a stream **S286** of cooling water or air having initial parameters as at a point **53** and final parameters as at a point **54**, forming a steam **S288** parameters as at a point **27**, corresponding to a state of saturated liquid. The stream **S288** having

the parameters as at the point **27** then enters into a third or feed pump **P3**, where it is pumped to a desired high pressure, forming the stream **S264** having the parameters as at the point **28**. Then the stream **S264** of working fluid having the parameters as at the point **28** is sent through the fifth heat exchanger **HE5**, where it is heated, in counterflow with the stream **S262** having the parameters as at the point **30** in the fifth heat exchange process, forming a stream **S100** having parameters as at a point **29** as described above. The stream **S290** having the parameters as at a point **29** then exits the CTCSS **100**, and returns to the power system. This CTCSS of this invention is closed in that no material is added to any stream in the CTCSS.

[0107] In some cases, preheating of the working fluid which is reproduced in the CTCSS is not necessary. In such cases, the fifth heat exchanger **HE5** is excluded from the **CTCSS Variant 1a** described above. As a result, the stream **S262** having the parameters as at the point **30** and the stream **S266** having the parameters as at the point **25** are the same, and the stream **S264** having the parameters at the point **28** are the stream **S100** having the parameters as at the point **29** are the same as shown in **Figure 3**. The CTCSS system in which **HE5** is excluded is referred to as **CTCSS Variant 1b**.

[0108] The CTCSSs of this invention provide highly effective utilization of heat available from the condensing stream **S182** of the working solution having the parameters as at the point **138** and of heat from external sources such as from the stream **S252**.

[0109] In distinction from an analogous system described in the prior art, the lean liquid stream **S246** having the parameters as at the point **7** coming from the first separator **S1**, is not cooled in a separate heat exchanger, but rather a portion of the stream **S246** is injected into the stream **S200** of working fluid returning from the power system.

[0110] When the stream **S236** of basic solution having the parameters as at the point **12** starts to boil, it initially requires a substantial quantity of heat, while at the same time its rise in temperature is relatively slow. This portion of the reboiling process occurs in the second heat exchanger **HE2**. In the process of further reboiling, the rate of increase in the temperatures becomes much faster. This further portion of the reboiling process occurs in the first heat exchanger **HE1**. At the same time, in the process of condensation of the stream **S204** having the parameters as at the point **38**, initially a relatively large quantity of heat is released, with a relatively slow reduction of temperature. But in further condensation, the rate of reduction of temperature is much higher. As a result of this phenomenon, in the prior art, the temperature differences between the condensing stream of working solution and the reboiling stream of basic solution are minimal at the beginning and end of the process, but are quite large in the middle

of the process.

[0111] In contrast to the prior art, in the CTCSS of this invention, the concentration of the low boiling component in stream **S208** having the parameters as at the point **8** is relatively low and therefore in the second heat exchanger **HE2**, stream **S208** having the parameters as at the point **8** not only condenses itself, but has the ability to absorb additional vapor. As a result, the quantity of heat released in the second heat exchanger **HE2** in the second heat exchange process is substantially larger than it would be if streams **S208** and **S206** having the parameters as at the points **8** and **15**, respectively, were cooled separately and not collectively collect after combining the two stream **S208** and **S206** to form the stream **S210**. As a result, the quantity of heat available for the reboiling process comprising the first and second heat exchange processes is substantially increased, which in turn increases the efficiency of the CTCSS system.

[0112] The leaner the stream **S208** having the parameters at as the point **8** is, the greater its ability to absorb vapor, and the greater the efficiency of the heat exchange processes occurring in the first and second heat exchangers **HE1** and **HE2**. But the composition of the stream **S208** having the parameters at as the point **8** is defined by the temperature of the stream **S242** having the parameters as at the point **5**; the higher the temperature of the stream **S242** having the parameters as at the point **5**, the leaner the composition of stream **S208** having the parameters at as the point **8** can be.

[0113] It is for this reason that external heat derived from stream **S252** is used to heat stream **S248** having the parameters as at the point **70**, thus raising the temperature of the stream **S204** having the parameters as at the point **38**, and as a result also raising the temperature of the stream **S242** having the parameters as at the point **5**. However, increasing of the temperature of the stream **S242** having the parameters as at the point **5**, and correspondingly the temperature of the stream **S244** having the parameters as at a point **6**, leads to a reduction in a concentration of the low boiling component in the vapor stream **S244** having the parameters as at the point **6**.

[0114] Use of the scrubber **SC1**, in place of a heat exchanger, for the utilization of heat from the stream **S244** having the parameters as at the point **6** allows both the utilization of the heat from the stream **S244** having the parameters as at the point **6** and an increase of the concentration of low boiling component in the produced vapor stream **S262** having the parameters as at the point **30**.

[0115] The vapor stream **S262** having the parameters as at the point **30** has a concentration of low-boiling component which is higher than the concentration of the low boiling component in the vapor stream **S244** having the parameters as at the point **6**, and the flow rate of stream **S262**

having the parameters as at the point 30 is higher than the flow rate of the stream S244 having the parameters as at the point 6.

[0116] The concentration of low boiling component in the working fluid is restored in the stream S284 having the parameters at the point 26, by mixing the stream S266, a very rich solution, having the parameters as at the point 25 (or the stream S262 having the parameters as at the point 30, in the case of the **CTCSS Variant 1b**), with the stream S282 having the parameters as at the point 40. The stream S282 having the parameters as at point 40 has a higher concentration of low boiling component than the basic solution, (*i.e.*, is enriched). Such an enrichment has been used in the prior art, but in the prior art, in order to obtain this enrichment, a special intermediate pressure reboiling process is needed requiring several additional heat exchangers.

[0117] In the CTCSSs of this invention, all heat that is available at a temperature below the boiling point of the basic solution (*i.e.*, below the temperature of the stream S230 having the parameters as at the point 14) is utilized in a single heat exchanger, the third heat exchanger HE3. Thereafter, the vapor needed to produce the enriched stream S282 having the parameters as at the point 40 is obtained simply by throttling the stream S232 having the parameters as at the point 13.

[0118] The CTCSSs of this invention can be simplified by eliminating some "modular" components. For instance, it is possible to enrich the stream S282 having the parameters as at the point 40 without using the intermediate pressure condenser, the seventh heat exchanger HE7. Such a system, with preheating of the stream S264 of working fluid having the parameters as at the point 28 is shown in **Figure 3**, and referred to as **CTCSS Variant 2a**. A similar system, but without preheating the stream S264 of working fluid having the parameters as at the point 28, is shown in **Figure 4**, and referred to as **CTCSS Variant 2b**.

[0119] In the **CTCSS Variant 2a** and **CTCSS Variant 2b**, in distinction to the **CTCSS Variant 1a** and **CTCSS Variant 1b**, the pressure of the stream S268 having the parameters as at the point 43 is chosen in such a way that the when mixing the vapor stream S270 having the parameters as at the point 34 and the liquid stream S274 having the parameters as at the point 31, the subcooled liquid stream S274 having the parameters as at the point 31 fully absorbs the vapor stream S270 having the parameters as at the point 34, and the resulting stream S276 having the parameters as at the point 3 is in a state of saturated, or slightly subcooled, liquid. Thereafter, the liquid S276 having the parameters as at the point 3 is sent into the second pump P2, to form the stream S282 having the parameters as at the point 40, and is mixed with stream 25.

[0120] The simplification of the CTCSS of **CTCSS Variant 2a** and **CTCSS Variant 2b** reduces

the overall efficiency of the CTCSSs of this invention, but at the same time, the cost is also reduced.

[0121] Another possible modular simplification of the **CTCSS Variant 1a** and **CTCSS Variant 1b** can be used in a case where external heat is not available, or the choice is made not to utilize external heat. Such a variant of the CTCSS of this invention, with preheating of the stream **S264** of working fluid having the parameters as at the point **28** is shown in **Figure 5**, and is referred to as **CTCSS Variant 3a**. A similar CTCSS of this invention, but without preheating the stream **S264** of the working fluid having the parameters as at the point **28**, is shown in **Figure 6**, and referred to as **CTCSS Variant 3b**.

[0122] In **CTCSS Variant 3a** and **CTCSS Variant 3b**, the stream **S248** having the parameters as at the point **70** is not heated, but rather simply passes through the fifth throttle valve **TV5**, to form the stream **S202** having the parameters as at the point **71**, and is then mixed with the stream **S182** having the parameters as at the point **138**, forming the stream **S204** having the parameters as at the point **38**. This mixing process is used only in a case where the stream **S182** having the parameters as at the point **138** is in a state of superheated vapor. The flow rate of streams **S248** and **S202** having the parameters as at the points **70** and **71** is chosen in such a way that the stream **S204** having the parameters as at the point **38** formed as a result of mixing the stream **S202** having the parameters as at the point **71** and the stream **S182** having the parameters as at the point **138** is in a state of saturated, or slightly wet, vapor.

[0123] It is also possible to simplify **CTCSS Variant 2a** and **CTCSS Variant 2b** in the same manner than **CTCSS Variant 1a** and **CTCSS Variant 1b** are simplified to obtain **CTCSS Variant 3a** and **CTCSS Variant 3b**. This modular simplification of **CTCSS Variant 2a** and **CTCSS Variant 2b**, with preheating of the stream **S264** of the working fluid having the parameters as at the point **28** is shown in **Figure 7**, and is referred to as **CTCSS Variant 4a**; while a similar simplification of **CTCSS Variant 2b**, without preheating the stream **S264** of the working fluid having the parameters as at the point **28**, is shown in **Figure 8**, and referred to as **CTCSS Variant 4b**.

[0124] A final modular simplification is attained by eliminating the scrubber **SC1**, and the use of the stream **S282** having the parameters as at the point **40** without any enrichment, *i.e.*, the composition of stream **S282** having the parameters as at the point **40** is the same as the composition of the basic solution. This modular simplification of **CTCSS Variant 4a**, with preheating of the stream **S264** of the working fluid having the parameters as at the point **28** is shown in **Figure 9**, and is referred to as **CTCSS Variant 5a**. A similar simplification of **CTCSS**

Variant 4b, without preheating the stream **S264** of the working fluid having the parameters as at the point **28**, is shown in **Figure 10**, and referred to as **CTCSS Variant 5b**. It must be noted that the modular simplification of the **CTCSS Variant 5a** and **CTCSS Variant 5b** results in a substantial reduction of the efficiency of the CTCSS. Also in **Variants 5a and 5b**, the stream **S222** having the parameters as at the point **1** is not split into two substreams **S222** and **S224** which are then separately pressurized, but is pressurized in as a single stream in a pump **P5** forming a stream **S292** having parameters as at a point **46**. The stream **S292** is then split to form the stream **S228** having the parameters as at the point **44** and the stream **S282** having the parameters as at the point **40**.

[0125] The CTCSSs of this invention is described in the five basic variants given above; (two of which utilize external heat, and three of which utilize only the heat available from the stream **S200** of the working fluid entering the CTCSSs of this invention). One experienced in the art would be able to generate additional combinations and variants of the proposed systems. For instance, it is possible to simplify **CTCSS Variant 4a** by eliminating the scrubber **SC1**, while retaining the enrichment of the stream **S282** having the parameters as at the points **40**. (Likewise it is possible to retain the scrubber **SC1**, and eliminate only the enrichment process for the stream **S282** having the parameters as at the points **40**.) However all such modular simplifications are still based on the initial **CTCSS Variant 1a** of the CTCSSs of this invention.

[0126] The efficacy of the CTCSS of this invention, *per se*, can be assessed by its compression ratio; *i.e.*, a ratio of the pressure of the stream **S284** having the parameters as at the point **26** (at the entrance to the high pressure condenser, heat exchanger **HE6**) to the pressure of the stream **S182** having the parameters as at the point **138** (at the point of entrance of the stream of working solution into the CTCSS). The impact of the efficacy of the CTCSS on the efficiency of the whole system depends on the structure and parameters of work of the whole system. For assessing the CTCSSs of this invention, several calculations have been performed. A stream comprising a water-ammonia mixture having a composition of 0.83 weight fraction of ammonia (*i.e.*, 83 wt.% ammonia), with an initial temperature of 1050°F and an initial pressure of 1800 psia, has been expanded in a turbine with an isentropic efficiency of 0.875 (87.5%). The parameters of the vapor upon exiting the turbine correspond to the stream **S182** having the parameters at the point **138**. Such computations have been performed for all proposed "b" variants of the CTCSS of this invention described above, and for a simple condenser system as well.

NEW VARIANT OF THE INVENTION

[0127] In the original application, eight different variants of the proposed cascade system were presented. All these systems used, as a heat source, a stream of hot flue gas from a combustor. Due to the fact that the initial temperature of this flue gas can be very high, this flue gas could not be used directly in the heat exchangers, where superheating of the working fluid occurs. In the initial application hot flue gas was initially cooled in a special heat exchanger, where its heat was transferred to a high temperature heat transfer fluid, referred to as "therm." Thereafter, this hot therm was used to transfer heat to the working fluid and to superheat the working fluid. Such an arrangement, while workable, entails additional complication to the system.

[0128] A new system and its variants, methods for implementing them for using heat from a high temperature flue gas are described below. The new systems and methods are described with reference to the six most complete variants described above. The new system and its variants are described in **Figures 20-25** and referred to as **Variants 3a-c** and **Variants 4a-c**. The **Variant 3a** corresponds to the **Variant 1a**; the **Variant 3b** corresponds to the **Variant 1b**; the **Variant 3c** corresponds to the **Variant 1c**; the **Variant 4a** corresponds to the **Variant 2a**; the **Variant 4b** corresponds to the **Variant 4b**; and the **Variant 4c** corresponds to the **Variant 2c**. It should be readily recognized by an ordinary artisan that the **Variants 1a1** and **Variants 2a1** can also be constructed with a heat recovery vapor generator (**HRVG**) as described below.

[0129] Referring now to **Figure 20**, a flow diagram of the **Variant 3a** is shown. The new system operates, in essence, in the same way as the **Variant 1a**, as described above, but its distinctions are explained below.

[0130] A hot flue gas stream **S302** having initial parameters as at a point **600** is mixed with a precooled flue gas stream **S304** having parameters as at a point **510** (as described below) to form a cooled flue gas stream **S306** having parameters as at a point **500**. The flow rate and temperature of the stream **S304** having the parameters as at the point **510** are chosen in such a way as to achieve a desired temperature of the cooled flue gas stream **S306** having the parameters as at the point **500** so that the heat recovery vapor generator (**HRVG**) functions within temperature design specifications.

[0131] Thereafter, the cooled flue gas stream **S306** having the parameters as at the point **500** passes through the **HRVG**, which is an apparatus identical to a heat recovery steam generator of a sort widely used in industry, but used here to moderate the temperature of the heat source stream of hot flue gas.

[0132] The cooled flue gas stream **S306** having the parameters as at the point **500** passing through the **HRVG** is cooled, releasing heat which is transferred to a working fluid of a power

system, which comprises all equipment and streams distinct from the **HRVG**. When, in the process of cooling, the flue gas comprising the stream **S306** reaches a desired operating lower temperature corresponding to a temperature of the stream **S306** at a point **506**, the flue gas stream **S306** is divided into two substreams **S308** and **S310** having parameters as at points **509** and **601**, respectively. The substream **S310** having the parameters as at the point **601** has a flow rate equal to a flow rate of the initial stream **S302** having the parameters as at the point **600**. The substream **S310** having the parameters as at the point **601** is then further cooled in the **HRVG**, until it achieves a final low temperature as at a point **603**, and is then removed from the cascade power system.

[0133] The lower temperature flue gas substream **S308** having the parameters as at the point **509** (as described above) is sent into a recirculating fan **F**, where its pressure is slightly increased to form the precooled flue gas stream **S304** having the parameters as at the point **510**. Thereafter, the precooled flue gas stream **S304** having the parameters as at the point **510** is mixed with the initial hot flue gas stream **S302** having the parameters as at the point **600** to form the cooled flue gas stream **S306** having the parameters as at the point **500** (as described above). Such a change in the process of heat acquisition leads to some changes in the overall process of the cascade power system of this invention.

[0134] The working fluid stream **S114** having the parameters as at the point **106** is sent into a low temperature portion **A** of the **HRVG**, where it is heated to form a heated working fluid stream **S312** having parameters as at a point **202**. (This process is analogous to the heat exchange process **106-302** or **602-603**, which occurs in the heat exchanger **HE20** in the **Variant 1a**.)

[0135] Meanwhile, the stream **S162** having the parameters as at the point **203** is likewise sent into the **HRVG**, where it is initially heated, in counterflow with the flue gas stream **S310** in a heat exchange process **601-602** to form a stream **S314** having parameters as at a point **302**, corresponding to a state of saturated liquid. Thereafter, the stream **S314** having the parameters as at the point **302** is further heated in the **HRVG**, in counterflow with the flue gas stream **S306** in a heat exchange process **505-506** to form a stream **S316** having parameters as at a point **303**. Thereafter, the stream **S316** having the parameters as at the point **303** is mixed with the rich working solution stream **S168** having the parameters as at the point **306** to form a stream **S318** having parameters as at a point **308**.

[0136] The heating of the stream **S162** having the initial parameters as at the point **203** to form the stream **S316** having the final parameters as at the point **303** is analogous, but not identical

to the heat exchange process **203-303** in the heat exchanger **HE17** in the **Variant 1a**. The specific differences in this process between the process of the **Variant 1a** and the process of **Variant 3a** are as follows: (1) in the **Variant 3a**, the process is divided into two parts: (a) the preheating of the stream **S162** in the heat exchange process **203-302** and then the vaporization of the stream **S314** in the heat exchange process **302-303**; and (b) in the heat exchange process **203-302** or **601-602**, the flow rate of the flue gas stream **S310** having the parameters at the point **601** initially and later having parameters as at a point **602** is substantially smaller than the flow rate of the flue gas stream **S306** used in the heat exchange process **302-303** or **505-506**.

[0137] In the **Variant 1a**, the state of the working fluid stream **S170** having the parameters at the point **303** corresponded to a state of saturated vapor, whereas in the **Variant 3a**, the state of the working fluid stream **S316** having the parameters at point **303** is a state of a vapor-liquid mixture. The parameters of the stream **S316** having the parameters as at the point **303** in the **Variant 3a** are chosen in such a way that after being mixed with the stream **S168** having the parameters as at the point **306**, the resulting stream **S318** having parameters as at the point **308** is in a state of saturated vapor, whereas in the **Variant 1a**, the parameters of the stream **S172** having the parameters as at the point **308** corresponds to a state of superheated vapor.

[0138] Thereafter, the stream **S318** having the parameters as at the point **308** continues on through the **HRVG** in counterflow with the flue gas stream **S306** in a heat exchange processes **503-504** and **504-505** or **501-502** and **502-505** to form an intermediate stream **S320** having parameters as at a point **304** and ultimately the superheated stream **S184** having the parameters as at the point **408**.

[0139] In an analogous fashion, **Figures 21-25** describe **HRVG** analogs of the **Variant 2a**, the **Variant 1b**, the **Variant 2b**, the **Variant 1c** and the **Variant 2c**, respectively.

[0140] In the **Variant 3a-c** and the **Variant 4a-c** cascade power systems of this part of the application, replaces the process of heating the working fluid stream **S172** having parameters **308**, respectively by the heat transfer fluid stream **S174** having the parameters of the points **503** through **504** in the heat exchanger **HE14** of the **Variants 1a-c**, **Variants 2a-c**, **Variants 1a1** and **Variants 2a1**.

[0141] Meanwhile, the rich vapor working solution stream **S166** having the parameters as at the point **309** also passes through the **HRVG**, where it is heated in counterflow with the cooled flue gas stream **S306** in the heat exchange process **501-502** to form the stream **S176** having the parameters as at the point **409**. This heating process the **Variant 3a-b** and **Variants 4a-b** replaces the process of heating the working fluid stream **S166** having the parameters as at the

point 309 to form the stream S176 having the parameters as at the point 409 by the heat transfer fluid stream S174 in the heat exchange process 501-502 in heat exchange HE15 in the Variants 1a-b and Variants 2a-b.

[0142] In all other aspects, the Variants 1a-c and Variants 2a-c are identical to the Variants 3a-c and Variants 4a-c.

[0143] The efficiency of the cascade system of the Variants 3a-c and Variants 4a-c is approximately the same as the efficiency of the Variant 1a-c and Variants 2a-c. Additional work required for the use of recirculating fan F in the Variant 3a-c and Variants 4a-c is approximately the same as the work required for the recirculation of the heat transfer fluid in the Variants 1a-c and the Variants 2a-c.

[0144] From the above, it is possible to apply this new method of heating the working fluid to the other variants of the cascade system described in the initial application. The utilization of the heating methods described above for the Variants 3a-c and Variants 4a-c has a substantial advantage in that it allows for the replacement of multiple high pressure heat exchangers with a single HRVG unit, at a substantial savings in cost. In addition, the HRVG/F subsystem removes the need to undertake the expense of maintaining as separate heat transfer fluid and its recirculation subsystem.

[0145] The computation for the Variant 3a has been performed and the summary of performance and parameters of key points are tabulated in Table 4.

TABLE 4
Parameters at key points for Variant 1a-q

Working Fluid									
Pt.	X lb/lb	T °F	P psia	H Btu/lb	S Btu/lb-R	Ex Btu/lb	G rel G/G=1	Ph.	Wetness lb/lb (T °F)
25	0.8300	65.80	98.823	-17.0306	0.0498	38.3062	1.00000	Mix	1
27	0.8300	65.80	98.823	-17.0306	0.0498	38.3062	1.00000	Mix	1
28	0.8300	71.81	1,895.000	-6.6126	0.0549	46.0704	1.00000	Liq	(-255.34°F)
29	0.8300	71.81	1,895.000	-6.6126	0.0549	46.0704	1.00000	Liq	(-255.34°F)
38	0.8300	227.98	99.823	733.7277	1.3391	120.3320	1.00000	Vap	(0°F)
70	0.8300	65.80	98.823	-17.0306	0.0498	38.3062	0.00000	Mix	1
71	0.8300	65.93	99.823	-16.8732	0.0501	38.3125	0.00000	Liq	(-0.44°F)
91	0.8300	141.22	1,895.000	72.9111	0.1955	52.6830	1.82819	Liq	(-185.93°F)
92	0.8300	220.15	1,895.000	168.9321	0.3455	70.8994	0.82819	Liq	(-107°F)
95	0.8300	348.33	730.339	734.0856	1.1329	227.6479	0.82819	Mix	0.0218

98	0.8300	213.26	728.339	161.3946	0.3433	64.4930	0.82819	Mix	1
101	0.8300	326.33	1,885.000	332.3463	0.5676	119.1218	1.82819	Mix	1
102	0.3508	348.33	732.339	260.9545	0.5111	74.8495	0.71156	Liq	(-0.34°F)
103	0.1653	429.04	733.339	377.8327	0.6234	132.6644	0.72102	Mix	1
104	0.8300	326.33	1,885.000	332.3463	0.5676	119.1218	1.58683	Mix	1
105	0.3508	348.52	762.339	261.2044	0.5113	75.0186	0.71156	Liq	(-5.01°F)
106	0.8300	326.33	1,885.000	332.3463	0.5676	119.1218	0.24136	Mix	1
108	0.5206	335.33	730.339	379.9112	0.6707	111.8028	1.02215	Mix	0.7161
109	0.7821	369.02	732.339	783.0812	1.1881	247.7881	0.51760	Mix	0
110	0.6085	348.33	730.339	515.4397	0.8456	157.0334	1.53975	Mix	0.4738
111	0.8407	348.33	730.339	744.6227	1.1467	231.0510	0.81015	Mix	0
112	0.3508	348.33	730.339	260.9546	0.5111	74.8442	0.72960	Mix	1
113	0.3508	348.33	730.339	260.9545	0.5111	74.8441	0.71156	Mix	1
114	0.3508	348.33	730.339	260.9545	0.5111	74.8441	0.01804	Mix	1
117	0.8300	0.00	14.693	0.0000	0.0000	0.0000	0.00000	Mix	0
129	0.8300	71.81	1,895.000	-6.6126	0.0549	46.0704	1.00000	Liq	(-255.34°F)
138	0.8300	227.98	99.823	733.7277	1.3391	120.3320	1.00000	Mix	0
202	0.8300	413.04	1,880.000	689.0005	1.0004	251.2869	0.24136	Mix	0
203	0.1653	433.65	1,885.000	383.5037	0.6247	137.6916	0.72102	Liq	(-122.26°F)
204	0.8300	413.04	1,880.000	689.0005	1.0004	251.2869	1.58683	Mix	0
205	0.5206	431.04	733.339	933.5958	1.3212	328.1121	1.54921	Mix	0
206	0.5206	431.04	733.339	933.5958	1.3212	328.1121	1.02215	Mix	0
207	0.5206	431.04	733.339	933.5958	1.3212	328.1121	0.52706	Mix	0
300	0.8300	413.04	1,880.000	689.0005	1.0004	251.2869	1.82819	Mix	0
301	0.8300	804.87	1,865.000	1,042.1488	1.3419	427.2913	1.82819	Vap	(392.2°F)
302	0.1653	555.09	1,875.000	556.1377	0.8053	216.6478	0.72102	Mix	1
303	0.1653	595.58	1,870.000	1,065.6925	1.2955	471.9083	0.72102	Mix	0
304	0.5206	804.87	1,863.184	1,153.9518	1.4368	488.5043	1.54921	Vap	(288°F)
306	0.8300	805.03	1,870.000	1,042.1488	1.3416	427.4407	0.82819	Vap	(392.2°F)
307	0.8300	804.87	1,865.000	1,042.1488	1.3419	427.2913	0.82819	Vap	(392.2°F)
308	0.5206	677.37	1,870.000	1,053.1063	1.3523	431.4892	1.54921	Vap	(160.2°F)
309	0.8300	804.87	1,865.000	1,042.1488	1.3419	427.2913	1.00000	Vap	(392.2°F)
316	0.5206	840.66	740.339	1,216.8448	1.5838	475.1555	1.54921	Vap	(408.8°F)
320	0.8300	822.66	1,865.000	1,055.6984	1.3526	435.3220	1.19666	Vap	(410°F)

321	0.8300	413.04	1,880.000	689.0005	1.0004	251.2869	1.19666	Mix	0
322	0.8300	413.04	1,880.000	689.0005	1.0004	251.2869	0.63153	Mix	0
323	0.8300	771.19	1,865.000	1,016.4742	1.3213	412.2903	0.63153	Vap	(358.5°F)
408	0.5206	1,051.47	1,850.000	1,334.1621	1.5678	600.7615	1.54921	Vap	(535.2°F)
409	0.8300	1,050.96	1,850.000	1,231.5321	1.4796	545.2641	1.00000	Vap	(638.6°F)
410	0.8300	1,050.00	1,800.000	1,231.5321	1.4827	543.6670	1.00000	Vap	(638.9°F)
411	0.5206	1,050.00	1,800.000	1,334.1621	1.5708	599.2243	1.54921	Vap	(536.2°F)
412	0.8300	789.19	514.563	1,063.9158	1.5021	365.9644	1.00000	Vap	(461°F)
413	0.8300	477.84	507.563	857.1061	1.3134	257.0332	1.00000	Vap	(150.6°F)
Heat Source									
Pt.	X lb/lb	T °F	P psia	H Btu/lb	S Btu/lb-R	Ex Btu/lb	G rel G/G=1	Ph.	T °F
500	AIR	1,200.00	13.193	412.2779	1.9294	133.6975	6.48087	Vap	1514.2°F
501	AIR	1,200.00	13.193	412.2779	1.9294	133.6975	2.61941	Vap	1514.2°F
502	AIR	927.30	13.121	339.9780	1.8822	85.8742	2.61941	Vap	1241.6°F
503	AIR	1,200.00	13.193	412.2779	1.9294	133.6975	3.86146	Vap	1514.2°F
504	AIR	927.30	13.121	339.9780	1.8822	85.8742	3.86146	Vap	1241.6°F
505	AIR	834.41	13.085	315.8715	1.8644	70.9999	6.48087	Vap	1148.7°F
506	AIR	611.68	13.049	259.1817	1.8165	39.1355	6.48087	Vap	926°F
509	AIR	611.68	13.049	259.1817	1.8165	39.1355	3.21159	Vap	926°F
510	AIR	615.62	13.193	260.1702	1.8167	40.0382	3.21159	Vap	929.8°F
511	AIR	927.30	13.121	339.9780	1.8822	85.8742	6.48087	Vap	1241.6°F
600	AIR	1,742.00	13.193	561.7012	2.0072	242.7548	3.26929	Vap	2056.2°F
601	AIR	611.68	13.049	259.1817	1.8165	39.1355	3.26929	Vap	926°F
602	AIR	458.65	12.977	221.1084	1.7785	20.7494	3.26929	Vap	773.1°F
603	AIR	351.33	12.904	194.7776	1.7484	10.0330	3.26929	Vap	665.8°F
638	AIR	351.33	12.904	194.7776	1.7484	10.0330	3.26929	Vap	665.8°F
639	AIR	351.33	12.904	194.7776	1.7484	10.0330	3.26929	Vap	665.8°F
Coolant									
Pt.	X lb/lb	T °F	P psia	H Btu/lb	S Btu/lb-R	Ex Btu/lb	G rel G/G=1	Ph.	T °F
50	water	51.70	58.773	19.9513	0.0394	0.2257	14.2527	Liq	-239.65°F
51	water	51.80	68.773	20.0771	0.0396	0.2540	14.2527	Liq	-249.93°F
52	water	104.53	58.773	72.7518	0.1377	2.0600	14.2527	Liq	-186.82°F

53	water	104.53	58.773	72.7518	0.1377	2.0600	14.2527	Liq	-186.82°F
----	-------	--------	--------	---------	--------	--------	---------	-----	-----------

New Preferred Embodiments

[0146] In the variants set forth in **Figures 20-25** of the invention, the systems include an **HRVG** boiler comprised of two parts, a high temperature part and a low temperature part. Hot flue gas passing through the high temperature part of the **HRVG** is divided into two substreams **S308** and **S310** having the parameters as at the points **509** and **601**, responding. The stream **S308** having the parameters as at the point **509** is removed from the **HRVG** and then recirculated by a fan **F** and combined with the initial flue gas stream **S302** having the parameters as at the point **600** to form the stream **S306** having the parameters as at the point **500**, which then enters the **HRVG**. Simultaneously, the stream **S310** having the parameters as at the point **601** is further cooled in the **HRVG** in the heat exchange process **601-602** or **203-302** providing heat for the process of preheating the lean solution stream **S162** having parameters as at the point **203**.

[0147] As a result, in the **HRVG**, the flow rate of the flue gas is different between the high and low temperature parts of the **HRVG**. This, in turn requires that the cross section of the high temperature part of the **HRVG** is substantially larger than the cross section of the low temperature part of the **HRVG**. This complicates the design of the **HRVG**.

[0148] In the embodiment shown in **Figure 26**, the **HRVG** can be simplified so that the flow rate of the flue gas through the **HRVG** is constant throughout the entire **HRVG**. However, in such a case, due to the fact that the flow rate of the flue gas is controlled by a pinch point temperature difference at the boiling point of the lean solution stream **S314** having the parameters as at the point **302**, the final temperature of the flue gas exiting the **HRVG** is higher than in the previous embodiments. This slightly increases the flow rate of the flue gas which must be recirculated to the entrance of the **HRVG**, and as a result, requires work from the recirculating fan and thus slightly reduces the overall efficiency of the system.

[0149] Referring now to **Figure 26**, a rich working liquid stream **S100** having parameters as at a point **29** and having a high concentration of the low-boiling component enters the system from a Condensation Thermal Compression Subsystem (**CTCSS**) of any of the **CTCSS** embodiments shown in **Figures 10-19** and described in the disclosure associated therewith. The stream **S100** exits the **CTCSS** at a high pressure and having a temperature close to ambient. Thereafter, the stream **S100** having the parameters as at the point **29** is mixed with a stream **S102** of working fluid having at parameters as at a point **92**. Usually the pressure of the stream **S102** having the parameters as at the point **92** is equal to the pressure of the stream **S100** having parameters as at

the point **29**, and the composition of the stream **S102** having the parameters as at the point **92** is the same or similar to the composition of the stream **S102** having the parameters as at the point **29**. As a result of this mixing, a stream **S104** having parameters as at a point **91** is formed. Thereafter, the stream **S104** having the parameters as at the point **91** passes through a first heat exchanger **HE11**, where it is heated in counterflow in a first heat exchange process **91-101** or **95-98** by a condensing stream **S106** of rich working fluid having parameters as at a point **95**, forming a stream **S108** having parameters as at a point **101**, where a temperature of the stream **S108** is sufficient to bring the fluid close to a state of saturated liquid.

[0150] The stream **S106** of rich working fluid having the parameters as at the point **95** passes through the first heat exchanger **HE11**, where it is cooled and fully condensed, releasing heat for the first heat exchange process, forming a stream **S110** having parameters as at a point **98**. Thereafter, the fully condensed stream **S110** having the parameters as at the point **98** enters into a first circulation pump **P10**, where it is pumped to a high pressure equal to the pressure of the stream **S100** having the parameters as at the point **29**, forming the stream **S102** having the parameters as at the point **92**. The stream **S102** having the parameters as at the point **92** is mixed with the stream **S100** having the parameters as at the point **29**, forming the stream **S104** having the parameters as at the point **91** as described above.

[0151] Meanwhile, the stream **S108** having the parameters as at the point **101** passes through a second heat exchanger **HE12**, where it is heated and vaporized in counterflow in a second heat exchange process **101-300** or **206-108** by a stream **S120** of condensing working fluid having parameters as at a point **206**, forming a stream **S124** having parameters as at a point **300**, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor.

[0152] The vapor stream **S124** having the parameters as at the point **300** is then divided into two substreams **S126** and **S128** having parameters as at points **321** and **322**, respectively. The substream **S126** having the parameters as at the point **321** then passes through a third heat exchanger **HE13**, where it is heated in counterflow in a third heat exchange **321-320** or **316-205** process by a lean working fluid stream **S130** having parameters as at a point **316**, forming a stream **S132** having parameters as at a point **320**. The stream **S128** having the parameters as at the point **322** passes through an intercooler **HE16**, where it is heated in counterflow in a fourth heat exchange process **322-323** or **412-413** by a rich working fluid stream **S134** having parameters as at a point **412**, forming a stream **S136** having parameters as at a point **323**. The stream **S136** having the parameters as at the point **323** is then mixed with the stream **S132** having

the parameters as at the point **320**, forming a rich working fluid stream **S138** having parameters as at a point **301**.

[0153] The lean working fluid stream **S130** having the parameters as at the point **316** exiting a low concentration turbine **LCT** as described below, passes through the third heat exchanger **HE13**, where it is cooled, releasing heat in the third heat exchange process **321-320** or **316-205** as describe above, forming the stream **S140** having parameters as at a point **205**, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor. The pressure of the lean working fluid stream **S140** having the parameters as at the point **205** is substantially lower than a pressure of the rich working fluid stream **S124** having the parameters as at the point **300**, but because the stream **S140** having the parameters as at the point **205** has a substantially lower concentration of the low boiling component, it starts to condense at a temperature of the stream **S140** having the parameters as at the point **205**, which is higher than a temperature of the fully vaporized, rich working fluid stream **S124** having the parameters as at the point **300**, which has a substantially higher pressure.

[0154] The returning lean working fluid stream **S140** having the parameters as at the point **205** is then divided into two substreams **S120** and **S142** having parameters as at points **206** and **207**, respectively. The stream **S120** having the parameters as at the point **206** passes through the second heat exchanger **HE12**, where it is partially condensed in the second heat exchange process **206-108** or **101-300** to form a stream **S144** having parameters as at a point **108**, releasing heat to the stream **S108** having the parameters as at the point **101** as described above.

[0155] Thereafter, the lean working fluid stream **S144** having the parameters as at the point **108** is combined with a vapor stream **S146** having parameters as at a point **109**, forming a combined vapor-liquid mixed stream **S148** having parameters as at a point **110**. A composition of the stream **S146** having the parameters as at the point **109** has an even higher concentration of the low boiling component than the rich working fluid stream **S124** having the parameters as at the point **300**. The stream **S148** having the parameters as at the point **110** then enters into a separator **S10**, where it is separated into saturated vapor stream **S150** having parameters as at a point **111**, and saturated liquid stream **S152** having parameters as at a point **112**. The liquid stream **S152** having parameters as at point **112** is then divided into two substreams **S154** and **S156** having parameters as at points **113** and **114**, respectively.

[0156] Thereafter, the stream **S156** having the parameters as at the point **114** is combined with the vapor stream **S150** having the parameters as at the point **111**, forming the stream **S106** having

the parameters as at the point **95**, which has a composition equal or close to the composition of rich working fluid stream **S124** having the parameters as at the point **300**. The stream **S106** having the parameters as at the point **95** is then sent into the first heat exchanger **HE11**, where it is fully condensed, forming the stream **S110** having the parameters as at the point **98**, and provides heat for the first heat exchange process **91-101** and **95-98** as described above.

[0157] The liquid stream **S154** having the parameters as at the point **113** enters into a second circulation pump **P11**, where it is pumped to a pressure sufficient to lift it to a top of a scrubber **SC2**, which is a direct contact heat/mass exchanger, forming a stream **S158** having parameters as at a point **105**. Upon reaching to the top of the scrubber **SC2**, stream **S158** having the parameters as at the point **105** obtains parameters as at a point **102**, and then enters the top of the scrubber **SC2**. The lean vapor stream **S142** having the parameters as at the point **207** as describe above, enters a lower portion of the scrubber **SC2**. As a result of mass and heat transfer between streams **S158** and **S142** having the parameters as at the point **102** and **207**, respectively, a hot and lean liquid stream **S160** having parameters as at a point **103** is collected at a bottom of the scrubber **SC2**. Meanwhile, the cooled and rich vapor stream **S146** having the parameters as at the point **109**, is formed at a upper portion of the scrubber **SC2**. The liquid stream **S160** having the parameters as at the point **103** is in a state of saturated liquid, which is close to equilibrium with the vapor stream **S142** having the parameters as at the point **207**, whereas the vapor stream **S146** having the parameters as at the point **109** is in a state of a saturated vapor close to equilibrium with the liquid stream **S158** having the parameters as at the point **102**. The vapor stream **S146** having the parameters as at the point **109** is combined with the stream **S144** having the parameters as at the point **108**, forming the stream **S148** having the parameters as at the point **110** as described above.

[0158] The liquid stream **S160** having the parameters as at the point **103** enters into a third circulation pump **P12**, where it is pumped to a necessary high pressure, forming a stream **S162** having parameters as at a point **203**. The composition of the liquid streams **S160** and **S162** at the points **103** and **203** are substantially leaner than the lean working fluid streams **S140**, **S120**, **S144** and **S142** having the parameters as at the points **205**, **206**, **108** and **207**, respectively.

[0159] The rich working fluid stream **S138** having the parameters as at the point **301** as described above, is then separated into two substreams **S164** and **S166** having parameters as at points **307** and **309**, respectively. The weight flow rate of the stream **S166** having the parameters as at the point **309** is equal to the weight flow rate of rich working fluids stream **S100** having the parameters as at the point **29** entering the system from the **CTCSS**, whereas the flow rate of the

stream **S164** at point **307** is equal to the weight flow rate of the stream **S106** at the point **95**.

[0160] The stream **S164** having the parameters as at the point **307** passes through a third throttle valve **TV12**, forming a stream **S168** having parameters as at a point **306**. The streams **S162** stream having the parameters as at the point **203** enters into a bottom of the **HRVG**. The **S168** stream having parameters as at the point **306** enters a middle of the **HRVG**. The stream **S166** having parameters as at the point **309** enters into and through an upper portion **HE15** of the **HRVG**.

[0161] The stream **S162** having the parameters as at the point **203** is heated in a first **HRVG** heat exchange process **203-302** or **601-506** with a flue gas stream **S307c** having parameters as at a point **601** to form a stream **S314** having parameters as at a point **302** and a flue gas stream **S307d** having parameters as at a point **506**.

[0162] The heated stream **S314** having the parameters as at the point **302** is further heated in a mid heat exchange portion **HE19** of the **HRVG** in a second **HRVG** heat exchange process **302-303** or **505-601** with a flue gas stream **S307b** having parameters as at a point **505** to form a stream **S316** having parameters as at a point **303** and the flue gas stream **S307c** having the parameters as at the point **601**.

[0163] The stream **S316** is then mixed with the stream **S168** having the parameters as at the point **306** to form a combined stream **S318** having parameters as at the **308** in a middle of the **HRVG**. The combined stream **S318** is then partially vaporized in a third **HRVG** heat exchange process **308-304** or **502/504-505** with a flue gas stream **S307a** having parameters as at the point **502/504** to form a partially vaporized stream **S320** having parameters as at the point **304** and the flue gas stream **S307b** having parameters as at the point **505**.

[0164] Finally in a heat exchange portion **HE14** of the **HRVG**, the stream **S320** having parameters as at the point **304** is fully vaporized and preferably superheated in a fourth heat exchange process **304-408** or **501/503-502/504** with a cooled flue gas stream **S306** having the parameters as at a point **500** or **501/503** to form a fully vaporized and preferably superheated working fluid stream **S184** having parameters as at a point **408** and the flue gas stream **S307a** having the parameters as at the point **502/504**.

[0165] Simultaneously, the rich working fluid stream **S166** having the parameters as at the point **309** passes into and through the upper portion **HE15** of the **HRVG** in a parallel fourth heat exchange process **309-409** or **501/503-502/504** with the flue gas stream **S306** to form a fully vaporized rich working fluid stream **S176** having parameters as at point a **409**. Thereafter, the stream **S176** having the parameters as at the point **409** passes through an admission valve **TV11**,

forming a rich working fluid stream **S178** having parameters as at a point **410**. The rich working fluid stream **S178** having the parameters as at the point **410** then enters into a high pressure turbine **HPT**, where it expands and the turbine **HPT** converts a portion heat in the stream **S178** into a usable form of energy such as electrical power, and becomes the stream **S134** having the parameters as at the point **412**. Thereafter, the stream **S134** having the parameters as at the point **412** passes through the intercooler or fourth heat exchanger **HE16**, where it is cooled, releasing heat in the fourth heat exchange process **412-413** or **322-323**, forming a lower pressure, rich working fluid stream **S180** having parameters as at a point **413**. The lower pressure, rich working fluid stream **S180** having the parameters as at the point **413** then enters into a low pressure turbine **LPT**, where it expands and the turbine **LPT** converts a portion heat in the stream **S180** into a usable form of energy such as electrical power, and becomes a stream **S182** having parameters as at a point **138**. The stream **S182** having parameters as at the point **138**, which in the preferred embodiment shall be in, or close to a state of saturated vapor and is then sent into the **CTCSS**.

[0166] Simultaneously, the lean working fluid stream **S184** having parameters as at a point **408** passes through a second admission valve **TV10**, forming a lean working fluid stream **S186** having parameters as at a point **411**. The lean working fluid stream **S186** having the parameters as at the point **411** then enters into the low concentration working solution turbine **LCT** as described above, where it is expanded and the turbine **LCT** converts a portion heat in the stream **S186** into a usable form of energy such as electrical power, and becomes the stream **S130** having the parameters as at the point **316**. The stream **S130** having the parameters as at the point **316** then passes through the third heat exchanger **HE13**, where it is cooled, releasing heat for the third heat exchange process **316-205** or **321-320**, forming the stream **S140** having the parameters as at the point **205** as describe above.

[0167] If a pressure of the low-concentration working fluid stream **S186** having the parameters as at the point **411** at an inlet to the low concentration working fluid turbine **LCT** as described above, is equal to a pressure of the rich working fluid stream **S178** having the parameters as at the point **410** at an inlet to the high pressure turbine **HPT**, then the pressure of stream **S164** having parameters as at the point **307** does not change when it passes through the third throttle valve **TV12**, and thus the parameters of the stream **S168** having the parameters as at the point **306** are the same as the parameters of the stream **S164** having the parameter as at the point **307**.

[0168] After leaving the **HRVG**, the spent flue gas stream **S307d** having the parameters as at the point **506** is split into two substream **S307e** and **S308** having parameters as at points **602** and

509, respectively. The stream **S308** having the parameters as at the point **509** is then passed a recirculating fan **F**, where its pressure is slightly increased to form a precooled flue gas stream **S304** having the parameters as at a point **510**. Thereafter, the precooled flue gas stream **S304** having the parameters as at the point **510** is mixed with an initial hot flue gas stream **S302** having the parameters as at a point **600** to form the cooled flue gas stream **S306** having the parameters as at the point **500** or **531/503** as described above. Such a change in the process of heat acquisition leads to some changes in the overall process of the cascade power system of this invention.

[0169] In another preferred embodiment and alternate variant of the system of this invention shown in **Figure 27**, the pinch point in the process of heating the lean solution can be eliminated. In this embodiment, a stream of superheated rich solution is divided into two substreams as is the case in the variant of **Figure 26**. However, thereafter, one of the substreams, which comprises all of the rich vapor that must be mixed with the lean stream entering the HRVG, is in turn divided once more into two substreams. One of the substream of rich vapor is then mixed with lean stream prior to entering the HRVG, where the lean stream is in a state of subcooled liquid and the rich vapor stream is in a state of superheated vapor. The mixing of these two streams is performed in such a way that the subcooled lean liquid stream fully absorbs all of rich vapor stream. As a result, a new stream in a state of saturated or slightly subcooled liquid is formed. This stream then enters into the **HRVG** where it immediately starts to boil. As a result, the pinch point at the boiling point of the lean solution is now located at the entrance into the cold end of the **HRVG**, and is outside of the **HRVG**. This allows for better cooling of the flue gas in the **HRVG**.

[0170] Referring now to **Figure 27**, A rich working liquid stream **S100** having parameters as at a point **29** and having a high concentration of the low-boiling component enters the system from a Condensation Thermal Compression Subsystem (CTCSS) of **Figures 10-19**. The stream **S100** exits the CTCSS at a high pressure and having a temperature close to ambient. Thereafter, the stream **S100** having the parameters as at the point **29** is mixed with a stream **S102** of working fluid having at parameters as at a point **92**. Usually the pressure of the stream **S102** having the parameters as at the point **92** is equal to the pressure of the stream **S100** having parameters as at the point **29**, and the composition of the stream **S102** having the parameters as at the point **92** is the same or similar (within 5%) to the composition of the stream **S102** having the parameters as at the point **29**. As a result of this mixing, a stream **S104** having parameters as at a point **91** is formed. Thereafter, the stream **S104** having the parameters as at the point **91** passes through a

first heat exchanger **HE11**, where it is heated in counterflow in a first heat exchange process **91-101** or **95-98** by a condensing stream **S106** of rich working fluid having parameters as at a point **95**, forming a stream **S108** having parameters as at a point **101**, where a temperature of the stream **S108** is sufficient to bring the fluid close to a state of saturated liquid.

[0171] The stream **S106** of rich working fluid having the parameters as at the point **95** passes through the first heat exchanger **HE11**, where it is cooled and fully condensed, releasing heat for the first heat exchange process, forming a stream **S110** having parameters as at a point **98**. Thereafter, the fully condensed stream **S110** having the parameters as at the point **98** enters into a first circulation pump **P10**, where it is pumped to a high pressure equal to the pressure of the stream **S100** having the parameters as at the point **29**, forming the stream **S102** having the parameters as at the point **92**. The stream **S102** having the parameters as at the point **92** is mixed with the stream **S100** having the parameters as at the point **29**, forming the stream **S104** having the parameters as at the point **91** as described above.

[0172] Meanwhile, the stream **S108** having the parameters as at the point **101** passes through a second heat exchanger **HE12**, where it is heated and vaporized in counterflow in a second heat exchange process **101-300** or **206-108** by a stream **S120** of condensing working fluid having parameters as at a point **206**, forming a stream **S124** having parameters as at a point **300**, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor.

[0173] The vapor stream **S124** having the parameters as at the point **300** is then divided into two substreams **S126** and **S128** having parameters as at points **321** and **322**, respectively. The substream **S126** having the parameters as at the point **321** then passes through a third heat exchanger **HE13**, where it is heated in counterflow in a third heat exchange **321-320** or **316-205** process by a lean working fluid stream **S130** having parameters as at a point **316**, forming a stream **S132** having parameters as at a point **320**. The stream **S128** having the parameters as at the point **322** passes through an intercooler **HE16**, where it is heated in counterflow in a fourth heat exchange process **322-323** or **412-413** by a rich working fluid stream **S134** having parameters as at a point **412**, forming a stream **S136** having parameters as at a point **323**. The stream **S136** having the parameters as at the point **323** is then mixed with the stream **S132** having the parameters as at the point **320**, forming a rich working fluid stream **S138** having parameters as at a point **301**.

[0174] The lean working fluid stream **S130** having the parameters as at the point **316** exiting a low concentration turbine **LCT** as described below, passes through the third heat exchanger

HE13, where it is cooled, releasing heat in the third heat exchange process **321-320** or **316-205** as describe above, forming the stream **S140** having parameters as at a point **205**, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor. The pressure of the lean working fluid stream **S140** having the parameters as at the point **205** is substantially lower than a pressure of the rich working fluid stream **S124** having the parameters as at the point **300**, but because the stream **S140** having the parameters as at the point **205** has a substantially lower concentration of the low boiling component, it starts to condense at a temperature of the stream **S140** having the parameters as at the point **205**, which is higher than a temperature of the fully vaporized, rich working fluid stream **S124** having the parameters as at the point **300**, which has a substantially higher pressure.

[0175] The returning lean working fluid stream **S140** having the parameters as at the point **205** is then divided into two substreams **S120** and **S142** having parameters as at points **206** and **207**, respectively. The stream **S120** having the parameters as at the point **206** passes through the second heat exchanger **HE12**, where it is partially condensed in the second heat exchange process **206-108** or **101-300** to form a stream **S144** having parameters as at a point **108**, releasing heat to the stream **S108** having the parameters as at the point **101** as described above.

[0176] Thereafter, the lean working fluid stream **S144** having the parameters as at the point **108** is combined with a vapor stream **S146** having parameters as at a point **109**, forming a combined vapor-liquid mixed stream **S148** having parameters as at a point **110**. A composition of the stream **S146** having the parameters as at the point **109** has an even higher concentration of the low boiling component than the rich working fluid stream **S124** having the parameters as at the point **300**. The stream **S148** having the parameters as at the point **110** then enters into a separator **S10**, where it is separated into saturated vapor stream **S150** having parameters as at a point **111**, and saturated liquid stream **S152** having parameters as at a point **112**. The liquid stream **S152** having parameters as at point **112** is then divided into two substreams **S154** and **S156** having parameters as at points **113** and **114**, respectively.

[0177] Thereafter, the stream **S156** having the parameters as at the point **114** is combined with the vapor stream **S150** having the parameters as at the point **111**, forming the stream **S106** having the parameters as at the point **95**, which has a composition equal or close (within 5%) to the composition of rich working fluid stream **S124** having the parameters as at the point **300**. The stream **S106** having the parameters as at the point **95** is then sent into the first heat exchanger **HE11**, where it is fully condensed, forming the stream **S110** having the parameters as at the point

98, and provides heat for the first heat exchange process 91-101 and 95-98 as described above. [0178] The liquid stream S154 having the parameters as at the point 113 enters into a second circulation pump P11, where it is pumped to a pressure sufficient to lift it to a top of a scrubber SC2, which is a direct contact heat/mass exchanger, forming a stream S158 having parameters as at a point 105. Upon reaching to the top of the scrubber SC2, the stream S158 having the parameters as at the point 105 obtains parameters as at a point 102, and then enters the top of the scrubber SC2. The lean vapor stream S142 having the parameters as at the point 207 as describe above, enters a lower portion of the scrubber SC2. As a result of mass and heat transfer between streams S158 and S142 having the parameters as at the point 102 and 207, respectively, a hot and lean liquid stream S160 having parameters as at a point 103 is collected at a bottom of the scrubber SC2. Meanwhile, the cooled and rich vapor stream S146 having the parameters as at the point 109, is formed at a upper portion of the scrubber SC2. The liquid stream S160 having the parameters as at the point 103 is in a state of saturated liquid, which is close to equilibrium (within 5%) with the vapor stream S142 having the parameters as at the point 207, whereas the vapor stream S146 having the parameters as at the point 109 is in a state of a saturated vapor close to equilibrium (within 5%) with the liquid stream S158 having the parameters as at the point 102. The vapor stream S146 having the parameters as at the point 109 is combined with the stream S144 having the parameters as at the point 108, forming the stream S148 having the parameters as at the point 110 as described above.

[0179] The liquid stream S160 having the parameters as at the point 103 enters into a third circulation pump P12, where it is pumped to a necessary high pressure, forming a stream S162 having parameters as at a point 203. The composition of the liquid streams S160 and S162 at the points 103 and 203, respectively, are substantially leaner than the lean working fluid streams S140, S120, S144 and S142 having the parameters as at the points 205, 206, 108 and 207, respectively.

[0180] The rich working fluid stream S138 having the parameters as at the point 301 as described above, is then separated into two substreams S164 and S166 having parameters as at points 307 and 309, respectively. The weight flow rate of the stream S166 having the parameters as at the point 309 is equal to the weight flow rate of rich working fluids stream S100 having the parameters as at the point 29 entering the system from the CTCSS, whereas the flow rate of the stream S164 at point 307 is equal to the weight flow rate of the stream S106 at the point 95.

[0181] The stream S164 having the parameters as at the point 307 is then divided into two substreams S168a and S168b having parameters as at a point 306 and 305, respectively. The

streams **S162** stream having the parameters as at the point **203** is then combined with the substream **S168b** to form a stream **S314** having parameters as at a point **302**. The stream **S314** having the parameters as at the point **302** then enters into a bottom of the **HRVG**. The **S168a** stream having parameters as at the point **306** enters a middle of the **HRVG**. The stream **S166** having parameters as at the point **309** entered into and passes through an upper portion **HE15** of the **HRVG**.

[0182] The stream **S314** having the parameters as at the point **302** is heated a lower portion **HE19** of the **HRVG** in a second **HRVG** heat exchange process **302-303** or **505-506** with a flue gas stream **S307b** having parameters as at a point **505** to form a heated stream **S316** having parameters as at a point **303** and a flue gas stream **S307d** having parameters as at a point **506**.

[0183] The heated stream **S316** having the parameters as at the point **303** is then mixed with the stream **S168a** having the parameters as at the point **306** to form a combined stream **S318** having parameters as at the **308** in a lower middle point of the **HRVG**. The combined stream **S318** having the parameters as at the **308** is then partially vaporized in a third **HRVG** heat exchange process **308-304** or **502/504-505** with a flue gas stream **S307a** having parameters as at the point **502/504** to form a partially vaporized stream **S320** having parameters as at the point **304** and the flue gas stream **S307b** having parameters as at the point **505**.

[0184] Finally in a heat exchange portion **HE14** of the **HRVG**, the stream **S320** having parameters as at the point **304** is fully vaporized and preferably superheated in a fourth heat exchange process **304-408** or **501/503-502/504** with a cooled flue gas stream **S306** having the parameters as at a point **500** or **501/503** to form a fully vaporized and preferably superheated working fluid stream **S184** having parameters as at a point **408** and the flue gas stream **S307a** having the parameters as at the point **502/504**.

[0185] Simultaneously, the rich working fluid stream **S166** having the parameters as at the point **309** passes into and through an upper portion **HE15** of the **HRVG** in a parallel fourth heat exchange process **309-409** or **501/503-502/504** with the flue gas stream **S306** to form a fully vaporized rich working fluid stream **S176** having parameters as at point a **409**. Thereafter, the stream **S176** having the parameters as at the point **409** passes through an admission valve **TV11**, forming a rich working fluid stream **S178** having parameters as at a point **410**, and enters into a high pressure turbine **HPT**, where it expands and the turbine **HPT** converts a portion heat in the stream **S178** into a usable form of energy such as electrical power, and becomes the stream **S134** having the parameters as at the point **412**. Thereafter, the stream **S134** having the parameters as at the point **412** passes through the fourth heat exchanger **HE16**, where it is cooled,

releasing heat in the fourth heat exchange process **412-413** or **322-323**, forming a lower pressure, rich working fluid stream **S180** having parameters as at a point **413**. The lower pressure, rich working fluid stream **S180** having the parameters as at the point **413** then enters into a low pressure turbine **LPT**, where it expands and the turbine **LPT** converts a portion heat in the stream **S180** into a usable form of energy such as electrical power, and becomes a stream **S182** having parameters as at a point **138**. The stream **S182** having parameters as at the point **138**, which in the preferred embodiment shall be in, or close to a state of saturated vapor and is then sent into the **CTCSS**.

[0186] Simultaneously, the lean working fluid stream **S184** having parameters as at a point **408** passes through a second admission valve **TV10**, forming a lean working fluid stream **S186** having parameters as at a point **411**. The lean working fluid stream **S186** having the parameters as at the point **411** then enters into the low concentration working solution turbine **LCT** as described above, where it is expanded and the turbine **LCT** converts a portion heat in the stream **S186** into a usable form of energy such as electrical power, and becomes the stream **S130** having the parameters as at the point **316**. The stream **S130** having the parameters as at the point **316** then passes through the third heat exchanger **HE13**, where it is cooled, releasing heat for the third heat exchange process **316-205** or **321-320**, forming the stream **S140** having the parameters as at the point **205** as describe above.

[0187] If a pressure of the low-concentration working fluid stream **S186** having the parameters as at the point **411** at an inlet to the low concentration working fluid turbine **LCT** as described above, is equal to a pressure of the rich working fluid stream **S178** having the parameters as at the point **410** at an inlet to the high pressure turbine **HPT**, then the pressure of stream **S164** having parameters as at the point **307** does not change when it passes through the third throttle valve **TV12**, and thus the parameters of the stream **S168** having the parameters as at the point **306** are the same as the parameters of the stream **S164** having the parameter as at the point **307**.

[0188] After leaving the **HRVG**, the spent flue gas stream **S307d** is split into two substream **S307e** and **S308** having parameters as at points **602** and **509**, respectively. The stream **S308** having the parameters as at the point **509** is then passed a recirculating fan **F**, where its pressure is slightly increased to form a precooled flue gas stream **S304** having the parameters as at a point **510**. Thereafter, the precooled flue gas stream **S304** having the parameters as at the point **510** is mixed with an initial hot flue gas stream **S302** having the parameters as at a point **600** to form the cooled flue gas stream **S306** having the parameters as at the point **500** or **531/503** as described above. Such a change in the process of heat acquisition leads to some changes in the

overall process of the cascade power system of this invention.

[0189] In this embodiment, the stream **S138** of superheated rich solution with parameters as at point **301** is divided into two substreams **S166** and **S164** having the parameters as at the points **309** and **307**, respectively, as is the case in the previous variant. However, thereafter, stream **S164** having the parameters as at the point **307**, which is all of the rich vapor which must be mixed with the lean stream **S162** having the parameters as at the point **203**, is in turn divided once more into two substreams **S168a** and **S168b** having the parameters as at points **306** and **305**, respectively. The stream **S168b** of rich vapor having the parameters as at the point **305** is then mixed with a stream **S162** of lean liquid having the parameters as at the point **203**. The stream **S162** having the parameters as at the point **203** is in a state of subcooled liquid, whereas stream **S168b** the parameters as at the point **305** is in a state of superheated vapor. The mixing of these two streams is performed in such a way that the subcooled liquid stream **S162** the parameters as at the point **203** fully absorbs all of stream **S168b** the parameters as at the point **305**. As a result, a new stream **S314** the parameters as at the point **302** is formed, which is in a state of saturated or slightly subcooled liquid.

[0190] The stream **S314** the parameters as at the point **302** enters into the **HRVG** where it immediately starts to boil. As a result, the pinch point at the boiling point of the lean solution is now located at the entrance into the cold end of the **HRVG**, and is outside of the **HRVG**. This allows for better cooling of the flue gas in the **HRVG**.

[0191] The stream **S314** the parameters as at the point **302** partially boils in the **HRVG** to form the stream **S316** having the parameters as at the point **303**, corresponding to a state of vapor liquid mixture. Thereafter, the stream **S316** the parameters as at the point **303** is mixed with the substream **S168a** of superheated rich vapor the parameters as at the point **306** as described above and forms a stream **S318** of lean working solution the parameters as at the point **308**. The parameters of the stream **S316** at the point **303** are chosen in such a way that after mixing with stream **S168a** the parameters as at the point **306**, the resulting stream **S318** the parameters as at the point **308** is in a state of saturated or slightly superheated vapor. Thereafter, the stream **S318** of lean working solution with parameters as at point **308** is superheated in the **HRVG**, as in the previous variants.

[0192] Referring now to **Figure 28**, a rich working liquid stream **S100** having parameters as at a point **29** and having a high concentration of the low-boiling component enters the system from a Condensation Thermal Compression Subsystem (**CTCSS**) of **Figures 10-19**. The stream **S100** exits the **CTCSS** at a high pressure and having a temperature close to ambient. Thereafter, the

stream **S100** having the parameters as at the point **29** is mixed with a stream **S102** of working fluid having at parameters as at a point **92**. Usually the pressure of the stream **S102** having the parameters as at the point **92** is equal to the pressure of the stream **S100** having parameters as at the point **29**, and the composition of the stream **S102** having the parameters as at the point **92** is the same or similar (within 5%) to the composition of the stream **S102** having the parameters as at the point **29**. As a result of this mixing, a stream **S104** having parameters as at a point **91** is formed. Thereafter, the stream **S104** having the parameters as at the point **91** passes through a first heat exchanger **HE11**, where it is heated in counterflow in a first heat exchange process **91-101** or **95-98** by a condensing stream **S106** of rich working fluid having parameters as at a point **95**, forming a stream **S108** having parameters as at a point **101**, where a temperature of the stream **S108** is sufficient to bring the fluid close to a state of saturated liquid.

[0193] The stream **S106** of rich working fluid having the parameters as at the point **95** passes through the first heat exchanger **HE11**, where it is cooled and fully condensed, releasing heat for the first heat exchange process, forming a stream **S110** having parameters as at a point **98**. Thereafter, the fully condensed stream **S110** having the parameters as at the point **98** enters into a first circulation pump **P10**, where it is pumped to a high pressure equal to the pressure of the stream **S100** having the parameters as at the point **29**, forming the stream **S102** having the parameters as at the point **92**. The stream **S102** having the parameters as at the point **92** is mixed with the stream **S100** having the parameters as at the point **29**, forming the stream **S104** having the parameters as at the point **91** as described above.

[0194] Meanwhile, the stream **S108** having the parameters as at the point **101** passes through a second heat exchanger **HE12**, where it is heated and vaporized in counterflow in a second heat exchange process **101-300** or **206-108** by a stream **S120** of condensing working fluid having parameters as at a point **206**, forming a stream **S124** having parameters as at a point **300**, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor.

[0195] The vapor stream **S124** having the parameters as at the point **300** is then divided into two substreams **S126** and **S128** having parameters as at points **321** and **322**, respectively. The substream **S126** having the parameters as at the point **321** then passes through a third heat exchanger **HE13**, where it is heated in counterflow in a third heat exchange **321-320** or **316-205** process by a lean working fluid stream **S130** having parameters as at a point **316**, forming a stream **S132** having parameters as at a point **320**. The stream **S128** having the parameters as at the point **322** passes through an intercooler **HE16**, where it is heated in counterflow in a fourth

heat exchange process **322-323** or **412-413** by a rich working fluid stream **S134** having parameters as at a point **412**, forming a stream **S136** having parameters as at a point **323**. The stream **S136** having the parameters as at the point **323** is then mixed with the stream **S132** having the parameters as at the point **320**, forming a rich working fluid stream **S138** having parameters as at a point **301**.

[0196] The lean working fluid stream **S130** having the parameters as at the point **316** exiting a low concentration turbine **LCT** as described below, passes through the third heat exchanger **HE13**, where it is cooled, releasing heat in the third heat exchange process **321-320** or **316-205** as describe above, forming a stream **S140** having parameters as at a point **205**, corresponding or close to a state of saturated vapor, where close to means that the parameters of the stream are within about 5% of being in a state of saturated vapor. The pressure of the lean working fluid stream **S140** having the parameters as at the point **205** is substantially lower than a pressure of the rich working fluid stream **S124** having the parameters as at the point **300**, but because the stream **S140** having the parameters as at the point **205** has a substantially lower concentration of the low boiling component, it starts to condense at a temperature of the stream **S140** having the parameters as at the point **205**, which is higher than a temperature of the fully vaporized, rich working fluid stream **S124** having the parameters as at the point **300**, which has a substantially higher pressure.

[0197] The returning lean working fluid stream **S140** having the parameters as at the point **205** is then divided into two substreams **S120** and **S142** having parameters as at points **206** and **207**, respectively. The stream **S120** having the parameters as at the point **206** passes through the second heat exchanger **HE12**, where it is partially condensed in the second heat exchange process **206-108** or **101-300** to form a stream **S144** having parameters as at a point **108**, releasing heat to the stream **S108** having the parameters as at the point **101** as described above.

[0198] Thereafter, the lean working fluid stream **S144** having the parameters as at the point **108** is combined with a vapor stream **S146** having parameters as at a point **109**, forming a combined vapor-liquid mixed stream **S148** having parameters as at a point **110**. A composition of the stream **S146** having the parameters as at the point **109** has an even higher concentration of the low boiling component than the rich working fluid stream **S124** having the parameters as at the point **300**. The stream **S148** having the parameters as at the point **110** then enters into a separator **S10**, where it is separated into saturated vapor stream **S150** having parameters as at a point **111**, and saturated liquid stream **S152** having parameters as at a point **112**. The liquid stream **S152** having parameters as at point **112** is then divided into two substreams **S154** and **S156** having

parameters as at points 113 and 114, respectively.

[0199] Thereafter, the stream S156 having the parameters as at the point 114 is combined with the vapor stream S150 having the parameters as at the point 111, forming the stream S106 having the parameters as at the point 95, which has a composition equal or close (within 5%) to the composition of rich working fluid stream S124 having the parameters as at the point 300. The stream S106 having the parameters as at the point 95 is then sent into the first heat exchanger HE11, where it is fully condensed, forming the stream S110 having the parameters as at the point 98, and provides heat for the first heat exchange process 91-101 and 95-98 as described above.

[0200] The liquid stream S154 having the parameters as at the point 113 enters into a second circulation pump P11, where it is pumped to a pressure sufficient to lift it to a top of a scrubber SC2, which is a direct contact heat/mass exchanger, forming a stream S158 having parameters as at a point 105. Upon reaching to the top of the scrubber SC2, the stream S158 having the parameters as at the point 105 obtains parameters as at a point 102, and then enters the top of the scrubber SC2. The lean vapor stream S142 having the parameters as at the point 207 as describe above, enters a lower portion of the scrubber SC2. As a result of mass and heat transfer between streams S158 and S142 having the parameters as at the point 102 and 207, respectively, a hot and lean liquid stream S160 having parameters as at a point 103 is collected at a bottom of the scrubber SC2. Meanwhile, the cooled and rich vapor stream S146 having the parameters as at the point 109, is formed at a upper portion of the scrubber SC2. The liquid stream S160 having the parameters as at the point 103 is in a state of saturated liquid, which is close to equilibrium (within 5%) with the vapor stream S142 having the parameters as at the point 207, whereas the vapor stream S146 having the parameters as at the point 109 is in a state of a saturated vapor close to equilibrium (within 5%) with the liquid stream S158 having the parameters as at the point 102. The vapor stream S146 having the parameters as at the point 109 is combined with the stream S144 having the parameters as at the point 108, forming the stream S148 having the parameters as at the point 110 as described above.

[0201] The liquid stream S160 having the parameters as at the point 103 enters into a third circulation pump P12, where it is pumped to a necessary high pressure, forming a stream S162 having parameters as at a point 203. The composition of the liquid streams S160 and S162 at the points 103 and 203, respectively, are substantially leaner than the lean working fluid streams S140, S120, S144 and S142 having the parameters as at the points 205, 206, 108 and 207, respectively.

[0202] The rich working fluid stream S138 having the parameters as at the point 301 as described

above, is then separated into two substreams **S164** and **S166** having parameters as at points **307** and **309**, respectively. The weight flow rate of the stream **S166** having the parameters as at the point **309** is equal to the weight flow rate of rich working fluids stream **S100** having the parameters as at the point **29** entering the system from the **CTCSS**, whereas the flow rate of the stream **S164** at point **307** is equal to the weight flow rate of the stream **S106** at the point **95**.

[0203] The stream **S164** having the parameters as at the point **307** is then passed through a fourth throttle valve **TV13** to form a stream **S168** having parameters as at a point **305**. The streams **S162** stream having the parameters as at the point **203** is then combined with the stream **S168** having parameters as at the point **305** to form a stream **S314** having parameters as at a point **302**. The stream **S314** having the parameters as at the point **302** then enters into a bottom of the **HRVG**.

[0204] The stream **S314** having the parameters as at the point **302** is heated in a lower portion **HE19** of the **HRVG** in a second **HRVG** heat exchange process **302-303** or **505-506** with a flue gas stream **S307a** having parameters as at a point **502/504** to form a partially vaporized stream **S320** having parameters as at the point **304** and the flue gas stream **S307a** having parameters as at the point **502/504**.

[0205] Finally in a heat exchange portion **HE14** of the **HRVG**, the stream **S320** having parameters as at the point **304** is fully vaporized and preferably superheated in a fourth heat exchange process **304-408** or **501/503-502/504** with a cooled flue gas stream **S306** having the parameters as at a point **500** or **501/503** to form a fully vaporized and preferably superheated working fluid stream **S184** having parameters as at a point **408** and the flue gas stream **S307a** having the parameters as at the point **502/504**.

[0206] Simultaneously, the rich working fluid stream **S166** having the parameters as at the point **309** passes into and through an upper portion **HE15** of the **HRVG** in a parallel fourth heat exchange process **309-409** or **501/503-502/504** with the flue gas stream **S306** to form a fully vaporized rich working fluid stream **S176** having parameters as at point a **409**. Thereafter, the stream **S176** having the parameters as at the point **409** is divided into two substreams **S177a** and **S177b** having parameters as at points **422** and **420**, respectively. The stream **S177a** having the parameters as at the point **422** passes through an admission valve **TV11**, forming a rich working fluid stream **S178** having parameters as at a point **410**. The rich working fluid stream **S178** having the parameters as at the point **410** then enters into a high pressure turbine **HPT**, where it expands and the turbine **HPT** converts a portion heat in the stream **S178** into a usable form of energy such as electrical power, and becomes the stream **S134** having the parameters as at the

point 412. Thereafter, the stream S134 having the parameters as at the point 412 passes through the intercooler or fourth heat exchanger HE16, where it is cooled, releasing heat in the fourth heat exchange process 412-413 or 322-323, forming a lower pressure, rich working fluid stream S180 having parameters as at a point 413. The lower pressure, rich working fluid stream S180 having the parameters as at the point 413 then enters into a low pressure turbine LPT, where it expands and the turbine LPT converts a portion heat in the stream S180 into a usable form of energy such as electrical power, and becomes a stream S182 having parameters as at a point 138. The stream S182 having parameters as at the point 138, which in the preferred embodiment shall be in, or close to a state of saturated vapor and is then sent into the CTCSS.

[0207] Simultaneously, the lean working fluid stream S184 having parameters as at a point 408 passes through a second admission valve TV10, forming a lean working fluid stream S185 having parameters as at a point 423. The stream S185 is then combined or mixed with a stream S177c having parameters as at a point 421 to form a combined stream S186 having parameters as at a point 411. The stream S177c having the parameters as at the point 421 is derived from the stream S177b having the parameters as at the point 420 after it has been passed through a third throttle valve TV12. The lean working fluid stream S186 having the parameters as at the point 411 then enters into the low concentration working solution turbine LCT as described above, where it is expanded and the turbine LCT converts a portion heat in the stream S186 into a usable form of energy such as electrical power, and becomes the stream S130 having the parameters as at the point 316. The stream S130 having the parameters as at the point 316 then passes through the third heat exchanger HE13, where it is cooled, releasing heat for the third heat exchange process 316-205 or 321-320, forming the stream S140 having the parameters as at the point 205 as describe above.

[0208] If a pressure of the low-concentration working fluid stream S186 having the parameters as at the point 411 at an inlet to the low concentration working fluid turbine LCT as described above, is equal to a pressure of the rich working fluid stream S178 having the parameters as at the point 410 at an inlet to the high pressure turbine HPT, then the pressure of stream S164 having parameters as at the point 307 does not change when it passes through the third throttle valve TV12, and thus the parameters of the stream S168 having the parameters as at the point 306 are the same as the parameters of the stream S164 having the parameter as at the point 307.

[0209] After leaving the HRVG, the spent flue gas stream S307d is split into two substream S307e and S308 having parameters as at points 602 and 509, respectively. The stream S308 having the parameters as at the point 509 is then passed a recirculating fan F, where its pressure

is slightly increased to form a precooled flue gas stream **S304** having the parameters as at a point **510**. Thereafter, the precooled flue gas stream **S304** having the parameters as at the point **510** is mixed with an initial hot flue gas stream **S302** having the parameters as at a point **600** to form the cooled flue gas stream **S306** having the parameters as at the point **500** or **531/503** as described above. Such a change in the process of heat acquisition leads to some changes in the overall process of the cascade power system of this invention.

[0210] A further alternate variant is possible in which the arrangement of the **HRVG** is yet further simplified. The lean solution stream **S162** having the parameters as at the point **203** is mixed with the stream **S168** of rich superheated vapor having the parameters as at the point **305**, and forms a stream **S314** having the parameters as at the point **302**, which is in a state of saturated or slightly subcooled liquid. This arrangement is the same arrangement as was described in the previous variant; however, thereafter the stream **S314** of intermediate concentration having the parameters as at the point **302** passes through the **HRVG** where it is fully vaporized and superheated, obtaining the stream **S814** having the parameters as at the point **408**. At the same time, the stream **S166** of rich superheated vapor having the parameters as at the point **309** passes through the high temperature portion of the **HRVG**, where it is superheated, forming the stream **S176** having the parameters as at the point **409**. Then the stream **S176** of superheated vapor having the parameters as at the point **409** is divided into two substreams **S177b** and **S177a** having the parameters as at the points **420** and **422**, respectively. The stream **S177a** having the parameters as at the point **422** is then sent through an admission valve **TV11**, where its pressure is reduced, and enters into the **HPT** turbine as in all prior variants.

[0211] The stream **S184** of intermediate solution having the parameters as at the point **408** passes through a admission valve, **TV10**, where its pressure is reduced, to form the stream **S185** having the parameters as at the point **423**. Meanwhile, the stream **S177b** of rich superheated vapor having the parameters as at the point **420** as described above passes through a throttle valve **TV12**, where its pressure is reduced to a pressure equal to the pressure of the stream **S185** having the parameters as at the point **423**, to form the stream **S177c** having the parameters as at the point **421**. Thereafter the streams **S185** and **S177c** having the parameters as at the points **423** and **421**, respectively, are mixed, forming the stream **S186** of lean working solution having the parameters as at the point **411**. Then, the stream **S186** having the parameters as at the point **411** into the **LCT**.

[0212] All of the variants described above achieve the same result and differ only in their degree of complexity. The efficiency of all of these variants do not differ to any meaningful degree. One

experienced in the art can thus choose from the variants above, or from the original variant, such a configuration as is best suited to the circumstances of a given project or application of the system.

[0213] All references cited herein are incorporated by reference. Although the invention has been disclosed with reference to its preferred embodiments, from reading this description those of skill in the art may appreciate changes and modification that may be made which do not depart from the scope and spirit of the invention as described above and claimed hereafter.

CLAIMS

We claim:

[0214] 1. A cascade power system comprising an energy extraction subsystem, a separation subsystem, a heat exchange subsystem, a heat recovery vapor generator (HRVG) subsystem and a condensation thermal compression (CTCSS) subsystem, where the system is designed to establish two interacting working fluid cycles, one cycle utilizes a rich multi-component working fluid stream having a higher concentration of a low boiling component and the other cycle utilizes a lean working multi-component working fluid stream having a lower concentration of the low boiling component, where each stream is derived from a fully condensed incoming multi-component stream, where the separation subsystem is designed to produce the lean and rich working fluid streams, where the heat exchange subsystem and the heat recovery vapor generator subsystem are designed to vaporize the lean working fluid stream and the rich working fluid stream from heat derived directly and/or indirectly from an external flue gas stream, where the energy extraction subsystem is designed to extract energy from the lean working fluid stream and the rich working fluid stream in separate turbine or turbine stages, and where the CTCSS subsystem is designed to condense a spent rich stream to form the fully condensed incoming multi-component stream and where the flue gas flow rate is the same throughout the entire HRVG and where an initial hot flue gas stream is cooled by a re-circulated portion of a spent flue gas stream exiting the HRVG.

[0215] 2. The system of claim 1, wherein the energy extraction subsystem comprises a lean stream turbine, at least one rich stream turbine and at least two throttle control valves, where the lean stream turbine is adapted to extract energy from a lean stream, where the rich stream turbine is adapted to extract from a rich stream and where the first throttle control valve adjusts a pressure of a rich stream to that of a pressure of the rich stream turbine, where a second throttle control valve adjusts a pressure of the lean stream to a pressure of the lean stream turbine and optionally a third throttle control valve adjusts a pressure of an optional rich substream to a pressure of a leaner stream.

[0216] 3. The system of claim 1, wherein the separation subsystem comprises a scrubber, a separator and three pumps, where the separation subsystem is adapted to form a lean stream and a make-up stream having a composition the same or substantially the same as an incoming

working fluid stream.

[0217] 4. The system of claim 1, wherein the heat exchange subsystem comprises at least four heat exchangers adapted to vaporize the rich stream and heat or partially vaporized the lean stream.

[0218] 5. The system of claim 1, wherein the heat recovery vapor generator subsystem comprises a heat recovery vapor generator and a recirculating fan, where the heat recovery vapor generator subsystem is adapted cool a hot flue gas stream with a portion of a cool flue gas stream to form a cooled flue gas stream and to transfer heat from the cooled flue gas stream to the lean and rich working fluid streams and where the cooled flue gas stream has a higher flow rate than the hot flue gas stream and where the cooled flue gas stream has a desired temperature lower than a temperature of the hot flue gas stream.

[0219] 6. The system of claim 1, wherein the condensation subsystem comprising a condenser.

[0220] 7. The system of claim 1, wherein the condensation subsystem comprising:
a condensation separation subsystem comprising a separator adapted to produce a rich vapor stream and a lean liquid stream;

a condensation heat exchange subsystem comprising three heat exchangers and two throttle control valves adapted to mix a pressure adjusted first portion of the lean liquid stream with an incoming stream to form a pre-basic solution stream, to mix a pressure adjusted second portion of the lean liquid stream with the pre-basic solution stream to form a basic solution stream, to bring a first portion of a pressurized fully condensed basic solution stream into a heat exchange relationship with the pre-basic solution stream to form a partially condensed basic solution stream;

a first condensing and pressurizing subsystem comprising a first condenser and a first pump adapted to fully condense the partially condensed basic solution stream to form a fully condensed basic solution stream and to pressurize the fully condensed basic solution stream to form a pressurized fully condensed working fluid stream; and

a second condensing and pressurizing subsystem comprising a second condenser and a second pump adapted to mix a second portion of the fully condensed basic solution stream and the rich

vapor stream to form an outgoing stream, to fully condense the outgoing stream and to pressurize the outgoing stream to a desired high pressure,

where the first portion of the lean liquid stream is pressure adjusted to have the same or substantially the same pressure as the incoming stream and where the second portion of the lean stream is pressure adjusted to have the same or substantially the same pressure as the pre-basic solution stream and where the streams comprise at least one lower boiling component and at least one higher boiling component and the compositions of the streams are the same or different with the composition of the incoming stream and the outgoing stream being the same.

[0221] 8. The system of claim 1, wherein the composition of the incoming multi-component stream is selected from the group consisting of an ammonia-water mixture, a mixture of two or more hydrocarbons, a mixture of two or more freons, and a mixture of hydrocarbons and freons.

[0222] 9. The system of claim 1, wherein the composition of the incoming multi-component stream comprises a mixture of water and ammonia.

[0223] 10. The system of claim 1, wherein the hot flue gas stream comprises a combustion effluent stream formed from combustion of biomass, agricultural waste (such as bagasse,) municipal waste, coal, oil, natural gas and other fuels.

[0224] 11. A cascade power system comprising:

a separation subsystem adapted to produce a lean working fluid stream and a rich working fluid stream from an incoming multi-component fluid stream comprising a low boiling component and a high boiling component, where the lean working fluid stream comprises a lower concentration of a low boiling component and the rich stream has a higher concentration of the low boiling component,

a heat exchange subsystem is adapted to heat and vaporize the rich working fluid stream and to heat the lean working fluid stream indirectly from heat derived from a hot flue gas stream,

a heat recovery vapor generator (HRVG) subsystem is adapted to vaporize the lean and rich working fluid streams directly from heat derived from a cooled flue gas stream comprising the hot flue gas stream and a re-circulated portion of a spent flue gas stream exiting the HRVG subsystem,

an energy extraction subsystem is adapted to convert a portion of the thermal energy in the rich working fluid stream and the lean working fluid stream to a usable form of energy , and
a condensation thermal compression (CTCSS) subsystem adapted to fully condensing the spent rich stream to form the fully condensed incoming working fluid stream,
where the system establishes two interacting working fluid cycles, a lean stream cycle and a rich stream cycle designed to improve the efficiency of energy conversion of thermal energy from the external flue gas stream.

[0225] 12. The system of claim 11, wherein the energy extraction subsystem comprises a lean stream turbine, at least one rich stream turbine and at least two throttle control valves, where the lean stream turbine is adapted to extract energy from a lean stream, where the rich stream turbine is adapted to extract from a rich stream and where the first throttle control valve adjusts a pressure of a rich stream to that of a pressure of the rich stream turbine, where a second throttle control valve adjusts a pressure of the lean stream to a pressure of the lean stream turbine and optionally a third throttle control valve adjusts a pressure of an optional rich substream to a pressure of a leaner stream.

[0226] 13. The system of claim 11, wherein the separation subsystem comprises a scrubber, a separator and three pumps, where the separation subsystem is adapted to form a lean stream and a make-up stream having a composition the same or substantially the same as an incoming working fluid stream.

[0227] 14. The system of claim 11, wherein the heat exchange subsystem comprises at least four heat exchangers adapted to vaporize the rich stream and heat or partially vaporized the lean stream.

[0228] 15. The system of claim 11, wherein the heat recovery vapor generator subsystem comprises a heat recovery vapor generator and a recirculating fan, where the heat recovery vapor generator subsystem is adapted cool a hot flue gas stream with a portion of a cool flue gas stream to form a cooled flue gas stream and to transfer heat from the cooled flue gas stream to the lean and rich working fluid streams and where the cooled flue gas stream has a higher flow rate than the hot flue gas stream and where the cooled flue gas stream has a desired temperature lower than a temperature of the hot flue gas stream.

[0229] 16. The system of claim 11, wherein the condensation subsystem comprising a condenser.

[0230] 17. The system of claim 11, wherein the condensation subsystem comprising:

- a condensation separation subsystem comprising a separator adapted to produce a rich vapor stream and a lean liquid stream;

- a condensation heat exchange subsystem comprising three heat exchangers and two throttle control valves adapted to mix a pressure adjusted first portion of the lean liquid stream with an incoming stream to form a pre-basic solution stream, to mix a pressure adjusted second portion of the lean liquid stream with the pre-basic solution stream to form a basic solution stream, to bring a first portion of a pressurized fully condensed basic solution stream into a heat exchange relationship with the pre-basic solution stream to form a partially condensed basic solution stream;

- a first condensing and pressurizing subsystem comprising a first condenser and a first pump adapted to fully condense the partially condensed basic solution stream to form a fully condensed basic solution stream and to pressurize the fully condensed basic solution stream to form a pressurized fully condensed working fluid stream; and

- a second condensing and pressurizing subsystem comprising a second condenser and a second pump adapted to mix a second portion of the fully condensed basic solution stream and the rich vapor stream to form an outgoing stream, to fully condense the outgoing stream and to pressurize the outgoing stream to a desired high pressure,

where the first portion of the lean liquid stream is pressure adjusted to have the same or substantially the same pressure as the incoming stream and where the second portion of the lean stream is pressure adjusted to have the same or substantially the same pressure as the pre-basic solution stream and where the streams comprise at least one lower boiling component and at least one higher boiling component and the compositions of the streams are the same or different with the composition of the incoming stream and the outgoing stream being the same.

[0231] 18. The system of claim 11, wherein the external flue gas stream comprises a combustion effluent stream formed from combustion of biomass, agricultural waste (such as bagasse,) municipal waste, coal, oil, natural gas and other fuels.

[0232] 19. The system of claim 11, wherein the composition of the incoming multi-component stream is selected from the group consisting of an ammonia-water mixture, a mixture of two or more hydrocarbons, a mixture of two or more freons, and a mixture of hydrocarbons and freons.

[0233] 20. The system of claim 11, wherein the composition of the incoming multi-component stream comprises a mixture of water and ammonia.

[0234] 21. A method comprising:

mixing a fully condensed incoming work fluid stream comprising a low boiling point component and a high boiling component with a pressurized cooled mixed stream to form a rich working fluid stream, where the incoming stream and the rich working fluid stream have the same or substantially the same composition;

bringing the rich working fluid stream into a heat exchange relationship with a mixed stream to form a cooled mixed stream and a heated rich working fluid stream;

bringing the heated rich working fluid stream into a heat exchange relationship with a first portion of a cooled spent lean working fluid stream to form a hotter rich working fluid stream and a cooled first portion of cooled spent lean working fluid stream;

bringing the hotter rich working fluid stream into a heat exchange relationship with a spent lean working fluid stream to form a fully vaporized rich working fluid stream;

adjusting a pressure of the fully vaporized rich working fluid stream to a pressure of a rich working fluid stream turbine;

converting a portion of thermal energy in the fully vaporized rich working fluid stream into a first amount of a usable form of energy;

bringing the lean working fluid stream into a heat exchange relationship with a cooled external flue gas stream to form a heated lean working fluid stream;

bringing the heated lean working fluid stream into a heat exchange relationship in a heat recovery vapor generator subsystem comprising a heat recovery vapor generator and a recirculating fan with a cooled flue gas stream to form a fully vaporized lean working fluid stream, where the cooled heat transfer fluid comprises a hot flue gas stream and a portion of a cool flue gas stream taken from an intermediate point of the heat recovery vapor generator;

adjusting a pressure of the fully vaporized lean stream to a pressure adjusted to a pressure of the lean working fluid stream turbine;

converting a portion of thermal energy in the fully vaporized lean working fluid stream into a second amount of the useable from of energy;

scrubbing a second portion of the cooled lean working fluid stream and a pressure adjusted first portion of a separator lean liquid stream to form a liquid lean working fluid stream and a rich scrubber stream;

pressurizing the liquid lean working fluid stream to a desired higher pressure to form the lean working fluid stream;

mixing the rich scrubber stream and the cooled second portion of the cooled spent lean working fluid stream to form a pre-separator feed stream;

separating the pre-separator feed stream to form a separator lean liquid stream and a separator rich liquid stream;

mixing a second portion of the separator lean liquid stream with the separator rich liquid stream to form the mixed stream; and

condensing a spent rich working fluid stream to form the fully condensed incoming working fluid stream.

[0235] 22. The method of claim 21, wherein the external flue gas stream comprises a combustion effluent stream formed from combustion of biomass, agricultural waste (such as bagasse,) municipal waste, coal, oil, natural gas and other fuels.

[0236] 23. The method of claim 21, wherein the composition of the incoming multi-component stream is selected from the group consisting of an ammonia-water mixture, a mixture of two or more hydrocarbons, a mixture of two or more freons, and a mixture of hydrocarbons and freons.

[0237] 24. The method of claim 21, wherein the composition of the incoming multi-component stream comprises a mixture of water and ammonia.

[0238] 25. The method of claim 21, further comprising:

splitting the fully vaporized rich working fluid stream into two substream, one being forwarded to the rich working fluid stream turbine and the other being pressure adjusted and mixed with the heated lean working fluid stream prior to fully vaporization.

[0239] 26. A method for efficient extraction of energy from a hot flue gas stream comprising the steps of:

establishing two interacting vaporization and energy extraction cycles, where one cycle utilizes a multi-component fluid stream having a higher concentration of a low boiling component of the multi-component fluid, a rich working fluid stream, and the other cycle utilizes a multi-component fluid stream having a higher concentration of a high boiling component of the multi-component fluid, a lean working fluid stream, each stream being derived from a fully condensed incoming multi-component working fluid stream;

vaporizing the lean and rich working fluid streams utilized in the two interacting cycles from heat derived directly and/or indirectly from a hot flue gas stream, where the direct heat transfer occurs between a cooled flue gas stream comprising a hot flue gas stream and a portion of a cool flue gas stream and the lean and rich working fluid streams;

converting a portion of thermal energy associated with the lean working fluid stream and the rich working fluid stream to a usable form of energy to form a spent rich working fluid stream and a spent lean working fluid stream,

separating a portion of the spent lean working fluid stream to form the lean working fluid stream and a make-up stream, where the make-up stream has a composition the same or substantially the same as the incoming multi-component working fluid stream; and

condensing the spent rich working fluid stream to form the fully condensed incoming multi-component working fluid stream. The spent rich stream is forwarded to a condensation unit, where it is fully condensed to form the incoming stream.

[0240] 27. The method of claim 26, wherein the external flue gas stream comprises a combustion effluent stream formed from combustion of biomass, agricultural waste (such as bagasse,) municipal waste, coal, oil, natural gas and other fuels.

[0241] 28. The method of claim 26, wherein the composition of the incoming multi-component stream is selected from the group consisting of an ammonia-water mixture, a mixture of two or more hydrocarbons, a mixture of two or more freons, and a mixture of hydrocarbons and freons.

[0242] 29. The method of claim 26, wherein the composition of the incoming multi-component stream comprises a mixture of water and ammonia.