CLAIMS

1. A method for time domain resource assignment, performed by a terminal device, comprising:

acquiring a time domain resource assignment (TDRA) table, wherein the TDRA table comprises a first field, and a second field corresponding to the first field; and

performing time domain resource assignment according to the first field and the second field;

wherein the first field comprises: a symbol length occupied by a transmission opportunity;

the second field comprises: a total number of transmission opportunities.

2. The method according to claim 1, wherein performing the time domain resource assignment according to the first field and the second field comprises:

acquiring a time domain resource assignment manner; and

performing the time domain resource assignment according to the first field, the second field, and the time domain resource assignment manner.

3. The method according to claim 2, further comprising:

determining a number of effective rows in the TDRA table based on the time domain resource assignment manner; and

performing the time domain resource assignment according to the first field, the second field, and the number of effective rows in the TDRA table.

4. The method according to claim 2, wherein the time domain resource assignment manner is applied to at least one of the following transmission manners:

a transport block processing over multi-slots (TBoMS) manner;

a repetition manner; or

a TBoMS with repetition manner.

5. The method according to claim 2, wherein acquiring the time domain resource assignment manner comprises:

receiving a first configuration signaling; and

determining the time domain resource assignment manner based on the first configuration signaling.

6. The method according to claim 5, wherein the first configuration signaling is a radio resource control (RRC) signaling, or a downlink control information (DCI) signaling.

7. The method according to claim 2, wherein acquiring the time domain resource assignment manner comprises:

acquiring configuration information of the terminal device; and

determining the time domain resource assignment manner based on the configuration information of the terminal device.

8. The method according to claim 7, wherein determining the corresponding time domain resource assignment manner based on the configuration information of the terminal device comprises:

acquiring a repetition number; and

determining the corresponding time domain resource assignment manner based on the configuration information of the terminal device and the repetition number.

9. The method according to claim 8, wherein acquiring the repetition number comprises:

acquiring whether the TDRA table comprises state information of a repetition number field; and

determining the repetition number based on the state information.

10. A method for time domain resource assignment, performed by a base station, comprising:

configuring a time domain resource assignment (TDRA) table for a terminal device, wherein the TDRA table comprises a first field, and a second field corresponding to the first field; and

performing time domain resource assignment according to the first field and the second

field;

wherein the first field comprises: a symbol length occupied by a transmission opportunity;

the second field comprises: a total number of transmission opportunities.

11. The method according to claim 10, wherein performing the time domain resource assignment according to the first field and the second field comprises:

configuring a time domain resource assignment manner for the terminal device; and

performing the time domain resource assignment according to the first field, the second field, and the time domain resource assignment manner.

12. The method according to claim 11, further comprising:

determining a number of effective rows in the TDRA table based on the time domain resource assignment manner; and

performing the time domain resource assignment according to the first field, the second field, and the number of effective rows in the TDRA table.

13. The method according to claim 11, wherein the time domain resource assignment manner comprises at least one of the following transmission manners:

a transport block processing over multi-slots (TBoMS) manner;

a repetition manner; or

a TBoMS with repetition manner.

14. The method according to claim 11, wherein acquiring the time domain resource assignment manner comprises:

receiving a first configuration signaling; and

determining the time domain resource assignment manner based on the first configuration signaling.

15. The method according to claim 14, wherein the first configuration signaling is aa radio resource control (RRC) signaling, or a downlink control information (DCI) signaling.

16. The method according to claim 11, wherein acquiring the time domain resource assignment manner comprises:

receiving configuration information of the terminal device; and

determining the time domain resource assignment manner based on the configuration information of the terminal device.

17. The method according to claim 16, wherein determining the corresponding time domain resource assignment manner based on the configuration information of the terminal device comprises:

acquiring a repetition number; and

determining the corresponding time domain resource assignment manner based on the configuration information of the terminal device and the repetition number.

18. The method according to claim 17, wherein acquiring the repetition number comprises:

acquiring whether the TDRA table comprises state information of a repetition number field; and

determining the repetition number based on the state information.

19. A communication device, comprising a processor and a memory having a computer program stored thereon, wherein the processor is configured to execute the computer program stored in the memory, causing the device to implement the method according to any one of claims 1 to 18.

20. A computer-readable storage medium having instructions stored thereon, wherein the instructions are configured to be executed, causing the method according to any one of claims 1 to 18 to be implemented.