(12) 特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関
国際事務局

(43) 国際公開日
2017 年 9 月 8 日(08.09.2017)

WIPO | PCT

(10) 国際公開番号
WO 2017/150259 A1

(51) 国際特許分類:
G01N 27/447 (2006.01)

(21) 国際出願番号: PCT/JP2017/006207

(22) 国際出願日: 2017 年 2 月 20 日(20.02.2017)

(25) 国際出願の言語: 日本語

(26) 国際公開の言語: 日本語

(30) 優先権データ:
特願 2016-042841 2016 年 3 月 4 日(04.03.2016) JP

(71) 出願人: シャープライフサイエンス株式会社 (SHARP LIFE SCIENCE CORPORATION) [JP/JP]; 〒6500047 兵庫県神戸市中央区港島南町７丁目１番１６号 Hyogo (JP).

(72) 発明者: 矢部 公彦(YABE, Kimihiko). 大木 博(OHKI, Hiroshi). 松永 貴輝(MATSUNAGA, Takateru). 音無 美恵子(OTONASHI, Mieko). 木下 英樹(KINOSHITA, Hideki). 和辻 徹(WATSUJI, Toru).

(74) 代理人: 特許業務法人ＨＡＲＡＫＥＮＺＯ ＷＯＲＬＤ ＰＡＴＥＮＴ ＆ ＴＲＡＤＥＭＡＲＫ (HARAKENZO WORLD PATENT & TRADEMARK); 〒5300041 大阪府大阪市北区天神橋２丁目北２番６号 大和南森町ビル Osaka (JP).

(81) 指定国 (表示のない限り、全ての種類の国内保護が可能): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) 指定国 (表示のない限り、全ての種類の広域保護が可能): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), ユーラシア (AM, AZ, BY, KG, KZ, RU, TJ, TM), ヨー

[続葉有]

(54) **Title**: SAMPLE SEPARATING IMPLEMENT AND SAMPLE ANALYZING DEVICE

(54) 発明の名称 : サンプル分離器具およびサンプル分析装置

FIG. 4A




FIG. 4B





FIG. 4C



(57) **Abstract**: Provided are a novel sample separating implement and sample analyzing device that can be suitably employed for discharge transfer. A sample separating implement (100) for discharge transfer is provided with a separating medium (10) and an accommodating portion (21), wherein: the accommodating portion (21) has an opening (21b) at an end portion side; the separating medium (10) has an exposed part (10b); and the exposed part (10b) has an extended part (10a) which extends along a peripheral edge portion (21a) of the opening (21b) of the accommodating portion (21).

(57) 要約: 排出転写に好適に用いることができる新規なサンプル分離器具およびサンプル分析装置を提供する。排出転写のためのサンプル分離器具（１００）であって、分離媒体（１０）と、収容部（２１）と、を備え、収容部（２１）は、端部側に開口（２１ｂ）を有し、分離媒体（１０）は、露出部分（１０ｂ）を有し、露出部分（１０ｂ）は、収容部（２１）における開口（２１ｂ）の周縁部（２１ａ）上に延出する延出部分（１０ａ）を有している。

WO 2017/150259 A1

ロッパ (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

添付公開書類:

— 国際調査報告（条約第 21 条(3)）