

5 PROJECTION LENSES HAVING REDUCED LATERAL COLOR FOR
 USE WITH PIXELIZED PANELS

FIELD OF THE INVENTION

 This invention relates to projection lenses and, in particular, to
10 projection lenses which can be used, inter alia, to form an image of an object
 composed of pixels, e.g., an LCD, a reflective LCD, a DMD, or the like.

DEFINITIONS

 As used in this specification and in the claims, the following terms
shall have the following meanings:

15 (1) Telecentric

 Telecentric lenses are lenses which have at least one pupil at
infinity. In terms of principal rays, having a pupil at infinity means that
the principal rays are parallel to the optical axis (a) in object space, if the
entrance pupil is at infinity, or (b) in image space, if the exit pupil is at
20 infinity. Since light can propagate through a lens in either direction, the
pupil at infinity can serve as either an entrance or an exit pupil depending
upon the lens' orientation with respect to the object and the image.
Accordingly, the term "telecentric pupil" will be used herein to describe the
lens' pupil at infinity, whether that pupil is functioning as an entrance or
25 an exit pupil.

 In practical applications, the telecentric pupil need not actually be at
infinity since a lens having an entrance or exit pupil at a sufficiently large
distance from the lens' optical surfaces will in essence operate as a
telecentric system. The principal rays for such a lens will be substantially
30 parallel to the optical axis and thus the lens will in general be functionally
equivalent to a lens for which the theoretical (Gaussian) location of the

pupil is at infinity.

Accordingly, as used herein, the terms "telecentric" and "telecentric lens" are intended to include lenses which have at least one pupil at a long distance from the lens' elements, and the term "telecentric pupil" is used to describe such a pupil at a long distance from the lens' elements. For the projection lenses of the invention, the telecentric pupil distance will in general be at least about 10 times the lens' focal length.

(2) Q-Value

As described in J. Hoogland, "The Design of Apochromatic Lenses," in Recent Development in Optical Design, R.A. Ruhloff editor, Perkin-Elmer Corporation, Norwalk, CT, 1968, pages 6-1 to 6-7, the contents of which are incorporated herein by reference, Q-values can be calculated for optical materials and serve as a convenient measure of the partial dispersion properties of the material.

Hoogland's Q-values are based on a material's indices of refraction at the e-line (546 nanometers), the F' line (480 nanometers), and the C' line (643.8 nanometers). The wavelengths used herein, both in the specification and in the claims, are the d line (587.56 nanometers), the F line (486.13 nanometers), and the C line (656.27 nanometers).

(3) V-Value

In the specification and the claims, V-values are for the d, F, and C lines.

(4) Composite V-Value

In accordance with certain aspects of the invention (see below), projection lenses are provided having a positive second lens unit (U_2) which has a composite V-value ($V_{U2/C}$) defined by the following formula:

$$V_{U2/C} = f_{U2} \{ \sum (V_{U2/i} / f_{U2/i}) \}$$

where f_{U2} is the focal length of the second lens unit, $f_{U2/i}$ and $V_{U2/i}$ are the focal length and V-value of the i^{th} lens element of the second lens unit, and the summation is over all lens elements of the second lens unit.

(5) Pseudo-Aperture Stop

The term "pseudo-aperture stop" is used herein in the same manner as it is used in commonly-assigned U.S. Patent No. 5,313,330 to Ellis Betensky, the contents of which are incorporated herein by reference.

5 (6) Zoom Lenses

In certain embodiments, the projection lens of the invention is a zoom lens. In applying the various aspects of the invention to these embodiments, the properties of the lens, e.g., its focal length, back focal length, field of view, aperture stop or pseudo-aperture stop location, telecentricity, etc., are evaluated at the zoom lens' short focal length position.

10 BACKGROUND OF THE INVENTION

Projection lens systems (also referred to herein as "projection systems") are used to form an image of an object on a viewing screen. Such systems can be of the front projection or rear projection type, depending on whether the viewer and the object are on the same side of the screen (front projection) or on opposite sides of the screen (rear projection).

The basic structure of such a system is shown in Figure 10, where 10 is a light source (e.g., a tungsten-halogen lamp), 12 is illumination optics which forms an image of the light source (hereinafter referred to as the "output" of the illumination system), 14 is the object which is to be projected (e.g., an LCD matrix of on and off pixels), and 13 is a projection lens, composed of multiple lens elements, which forms an enlarged image of object 14 on viewing screen 16. The system can also include a field lens unit, e.g., a Fresnel lens, in the vicinity of the pixelized panel to appropriately locate the exit pupil of the illumination system.

For front projection systems, the viewer will be on the left side of screen 16 in Figure 10, while for rear projection systems, the viewer will be on the right side of the screen. For rear projection systems which are to be housed in a single cabinet, a mirror is often used to fold the optical path and thus reduce the system's overall size.

Projection lens systems in which the object is a pixelized panel are used in a variety of applications. Such systems preferably employ a single projection lens which forms an image of, for example, a single panel having red, green, and blue pixels. In some cases, e.g., large image rear projection systems, multiple panels and multiple projection lenses are used, with each panel/projection lens combination producing a portion of the overall image. In either case, projection lenses used with such systems generally need to have a relatively long back focal length to accommodate the prisms, beam splitters, color wheels, etc. normally used with pixelized panels.

A particularly important application of projection lens systems employing pixelized panels is in the area of microdisplays, e.g., front projection systems which are used to display data and rear projection systems which are used as computer monitors. Recent breakthroughs in manufacturing technology has led to a rise in popularity of microdisplays employing digital light valve devices such as DMDs, reflective LCDs, and the like.

Projection displays based on these devices offer advantages of small size and light weight. As a result, a whole new class of ultra portable lightweight projectors operating in front-projection mode and employing digital light valves has appeared on the market. Lightweight compact rear-projection systems can also be achieved through the use of these devices.

To display images having a high information content, these devices must have a large number of pixels. Since the devices themselves are small, the individual pixels are small, a typical pixel size ranging from 17μ for DMD displays to approximately 8μ or even less for reflective LCDs. This means that the projection lenses used in these systems must have a very high level of correction of aberrations. Of particular importance is the correction of chromatic aberrations and distortion.

A high level of chromatic aberration correction is important because color aberrations can be easily seen in the image of a pixelized panel as a smudging of a pixel or, in extreme cases, the complete dropping of a pixel

from the image. These problems are typically most severe at the edges of the field.

All of the aberrations of the system need to be addressed, with lateral color, chromatic variation of coma, astigmatism, and distortion typically being most challenging. Lateral color, i.e., the variation of magnification with color, is particularly troublesome since it manifests itself as a decrease in contrast, especially at the edges of the field. In extreme cases, a rainbow effect in the region of the full field can be seen.

In projection systems employing cathode ray tubes (CRTs) a small amount of (residual) lateral color can be compensated for electronically by, for example, reducing the size of the image produced on the face of the red CRT relative to that produced on the blue CRT. With a pixelized panel, however, such an accommodation cannot be performed because the image is digitized and thus a smooth adjustment in size across the full field of view is not possible. A higher level of lateral color correction, including correction of secondary lateral color, is thus needed from the projection lens.

The use of a pixelized panel to display data leads to stringent requirements regarding the correction of distortion. This is so because good image quality is required even at the extreme points of the field of view of the lens when viewing data. As will be evident, an undistorted image of a displayed number or letter is just as important at the edge of the field as it is at the center. Moreover, projection lenses are often used with offset panels. In such a case, the distortion at the viewing screen does not vary symmetrically about a horizontal line through the center of the screen but can increase monotonically from, for example, the bottom to the top of the screen. This effect makes even a small amount of distortion readily visible to the viewer.

Low distortion and a high level of color correction are particularly important when an enlarged image of a WINDOWS type computer interface is projected onto a viewing screen. Such interfaces with their parallel lines, bordered command and dialog boxes, and complex coloration, are in essence

test patterns for distortion and color. Users readily perceive and object to even minor levels of distortion or color aberration in the images of such interfaces.

The above-mentioned microdisplays typically require that the light beam from the illumination system has a near-normal angle of incidence upon the display. In terms of the projection lens, this translates into a requirement that the lens has a telecentric entrance pupil, i.e., the projection lens must be telecentric in the direction of its short imaging conjugate where the object (pixelized panel) is located. This makes the lens asymmetric about the stop which makes the correction of lateral color more difficult.

In addition to the foregoing, for rear projection systems, there is an ever increasing demand for smaller cabinet sizes (smaller footprints). In terms of the projection lens, this translates into a requirement that the lens has a wide field of view in the direction of the image (screen). This requirement makes it even more difficult to correct the lateral color of the lens. Similarly, the requirement for a relatively long back focal length also makes it more difficult to correct lateral color.

SUMMARY OF THE INVENTION

In view of the foregoing, there exists a need in the art for projection lenses for use with pixelized panels which have some and preferably all of the following properties:

- (1) a high level of lateral color correction, including correction of secondary lateral color;
- (2) low distortion;
- (3) a large field of view in the direction of the image;
- (4) a telecentric entrance pupil; and
- (5) a relatively long back focal length.

The projection lenses of the invention address this need as follows.

In accordance with a first aspect, the invention provides a projection lens for forming an image of an object which consists in order from its

image end to its object end of:

- (A) a first lens unit U_1 having a negative power and comprising three lens elements E_P , E_N , and $E_{N'}$, arranged in any order and having focal lengths $f_{U1/P}$, $f_{U1/N}$, and $f_{U1/N'}$, V-values $V_{U1/P}$, $V_{U1/N}$, and $V_{U1/N'}$, and Q-values
- 5 $Q_{U1/P}$, $Q_{U1/N}$, and $Q_{U1/N'}$, respectively;
- (B) a second lens unit having a positive power; and
- (C) an optional field lens unit;

wherein:

- $f_{U1/P} > 0$,
- 10 $f_{U1/N} < 0$,
- $f_{U1/N'} < 0$,
- $V_{U1/N} > V_{U1/P}$,
- $V_{U1/N'} > V_{U1/P}$,
- $Q_{U1/N} > 0$,
- 15 $Q_{U1/N} > Q_{U1/P}$,
- $Q_{U1/N} > V_{U1/N}$,
- $Q_{U1/N'} > 0$, and
- $Q_{U1/N'} > Q_{U1/P}$.

Examples 1A, 1B, 1C, 2A, and 3-7 illustrate this first aspect of the

20 invention.

In accordance with a second aspect, the invention provides a projection lens for forming an image of an object which consists in order from its image end to its object end of:

- (A) a first lens unit U_1 having a negative power and comprising
- 25 two lens elements E_P and E_N , arranged in any order and having focal lengths $f_{U1/P}$ and $f_{U1/N}$, V-values $V_{U1/P}$ and $V_{U1/N}$, and Q-values $Q_{U1/P}$ and $Q_{U1/N}$, respectively;
- (B) a second lens unit having a positive power; and
- (C) an optional field lens unit;

30 wherein:

$f_{U1/P} > 0$,
 $f_{U1/N} < 0$,
 $V_{U1/N} > V_{U1/P}$,
 $Q_{U1/N} > 0$, and
5 $Q_{U1/P} < 0$.

Examples 1A, 1B, 1C, 3, 5, and 6 illustrate this second aspect of the invention.

In accordance with a third aspect, the invention provides a projection lens for forming an image of an object which consists in order from its
10 image end to its object end of:

(A) a first lens unit U_1 having a negative power and comprising two lens elements E_P and E_N , arranged in any order and having focal lengths $f_{U1/P}$ and $f_{U1/N}$, V-values $V_{U1/P}$ and $V_{U1/N}$, and Q-values $Q_{U1/P}$ and $Q_{U1/N}$, respectively;

15 (B) a second lens unit having a positive power; and

(C) an optional field lens unit;

wherein:

$f_{U1/P} > 0$,
 $f_{U1/N} < 0$,
20 $V_{U1/N} > V_{U1/P}$,
 $Q_{U1/N} > V_{U1/N}$, and
 $Q_{U1/N} > 125$.

Preferably, $Q_{U1/N}$ is greater than 135, and most preferably greater than 145.

25 Examples 1D, 1G, and 3 illustrate this third aspect of the invention.

In accordance with a fourth aspect, the invention provides a projection lens for forming an image of an object which consists in order from its image end to its object end of:

(A) a first lens unit U_1 having a negative power;

30 (B) a second lens unit U_2 having a positive power and comprising two lens elements E'_P and E'_N , arranged in any order and having focal

lengths f_{U2P} and f_{U2N} , V-values V_{U2P} and V_{U2N} , and Q-values Q_{U2P} and Q_{U2N} , respectively; and

(C) an optional field lens unit;

wherein:

- 5 $f_{U2P} > 0$,
 $f_{U2N} < 0$,
 $V_{U2P} > V_{U2N}$,
 $Q_{U2P} > V_{U2P}$, and
 $Q_{U2P} > 135$ (preferably, $Q_{U2P} > 145$).

10 Examples 1E, 1F, 1G, 2A, 7 and 9 illustrate this fourth aspect of the invention.

In accordance with a fifth aspect, the invention provides a projection lens for forming an image of an object composed of pixels, said projection lens consisting in order from its image end to its object end of:

- 15 (A) a first lens unit U_1 having a negative power;
 (B) an aperture stop or a pseudo-aperture stop;
 (C) a second lens unit U_2 having a positive power and comprising a positive lens elements having a V-value V_{U2P} ; and
 (D) an optional field lens unit;

20 wherein:

$$V_{U2P} > 75, \text{ and}$$

$$V_{U2C} > 0.1/(p' \cdot F\#_{U2}),$$

where V_{U2C} is the composite V-value of the second lens unit defined above, $F\#_{U2}$ is the f-number of the second lens unit as traced from the object
 25 (pixelized panel) towards the image, and p' is the pixel width divided by f_0 , where f_0 is the focal length of the combination of the first and second lens units. Preferably, V_{U2P} is greater than 80.

Examples 1A, 1C, 1E, 2A, 2B, 3, 4, 5, 7, 8 and 9 illustrate this fifth aspect of the invention.

30 As illustrated in the examples, the various aspects of the invention can be used separately or preferably in combination. As also illustrated in

the examples, by means of these various aspects of the invention, retrofocus projection lenses are provided having some and preferably all of the following properties:

- (i) the projection lens has a half field of view in the direction of the image of at least 20° and preferably at least 25°;
- (ii) the lateral color blur of the projection lens at its full field for wavelengths in the range from 460 nanometers to 620 nanometers is less than a pixel and preferably less than three-quarters of a pixel (note that the level of lateral color correction can be determined at the object plane or the image plane, a magnified pixel being used when the determination is performed at the image plane);
- (iii) the distortion of the projection lens is less than 1.5 percent, preferably less than 1.0 percent, and most preferably less than 0.5 percent;
- (iv) the ratio of the lens's back focal length (BFL) to its focal length is greater than 0.7, preferably greater than 1.0, and most preferably greater than 1.5.

The projection lenses of the invention can be designed using the location of the output of the illumination system as a pseudo-aperture stop/entrance pupil of the projection lens (see the above-referenced Betensky patent). In this way, efficient coupling is achieved between the light output of the illumination system and the projection lens.

BRIEF DESCRIPTION OF THE DRAWINGS

Figures 1-9 are schematic side views of projection lenses constructed in accordance with the invention.

Figure 10 is a schematic diagram showing an overall projection lens system in which the projection lenses of the present invention can be used.

The foregoing drawings, which are incorporated in and constitute part of the specification, illustrate the preferred embodiments of the invention, and together with the description, serve to explain the principles of the invention. It is to be understood, of course, that both the drawings

and the description are explanatory only and are not restrictive of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The projection lenses of the present invention are of the retrofocus or
5 the inverted telephoto type and consist of two lens units, i.e., a negative unit (U_1) on the long conjugate side and a positive unit (U_2) on the short conjugate side, which are typically separated by an aperture stop or a pseudo-aperture stop.

The use of this overall lens form to produce an image of a pixelized
10 panel has various advantages. Thus, telecentricity is readily achieved by locating the lens' aperture stop or pseudo-aperture stop in the front focal plane of the second positive unit. Additional advantages are a long back focal length and the ability to handle a wide field of view. Both of these characteristics are particularly useful in rear projection systems, where the
15 lens must have a wide field of view to achieve the smallest possible overall package size, and where there is a need to accommodate beam splitting prisms between the lens and the pixelized panel. These prisms may include polarizing beam splitters, as well as color splitting prisms.

The lenses of the invention achieve a high level of distortion
20 correction by using one or more aspherical surfaces in the first lens unit. Some residual distortion, as well as spherical aberration of the lens' entrance pupil, is corrected through the use of one or more aspherical surfaces in the second lens unit. The spherical aberration of the entrance pupil should be minimized to achieve telecentricity for any arbitrary point
25 in the object plane of the lens. Preferably, the aspherical surfaces are formed on plastic lens elements.

The most critical aberration that must be corrected is the lens' lateral color. In accordance with the first through fourth aspects of the invention set forth above, the design strategy for correcting this aberration
30 is as follows:

(1) For the negative first lens unit:

(a) To correct primary lateral color, high dispersion (low V-value) positive elements in combination with low dispersion (high V-value) negative elements are used.

5 (b) To correct secondary lateral color, the high dispersion (low V-value) positive elements should be as strongly positive as possible and should preferably have a negative Q-value and the low dispersion (high V-value) negative elements should be as strongly negative as possible with positive Q-values (preferably, large positive Q-values).

10 (2) For the positive second lens unit:

(a) To correct primary lateral color, as well as primary axial color, low dispersion (high V-value) positive elements in combination with high dispersion (low V-value) negative elements are used.

(b) To correct secondary lateral color, the low dispersion
15 (high V-value) positive elements should be as strongly positive as possible and should have positive Q-values (preferably, large positive Q-values) and the high dispersion (low V-value) negative elements should be as strongly negative as possible with negative Q-values or positive Q-values which are as small as possible.

20 In general terms, a high dispersion material is a material having a dispersion like flint glass and a low dispersion material is a material having a dispersion like crown glass. More particularly, high dispersion flint materials are those having V-values ranging from 20 to 50 for an index of refraction in the range from 1.85 to 1.5, respectively, and low dispersion
25 crown materials are those having V-values ranging from 35 to 75 for the same range of indices of refraction.

For plastic lens elements, the high and low dispersion materials can be styrene and acrylic, respectively. Other plastics can, of course, be used if desired. For example, in place of styrene, polycarbonates and copolymers of
30 polystyrene and acrylic (e.g., NAS) having flint-like dispersions can be used. In place of acrylic, cyclic olefin copolymers, e.g., Topas 5013 manufactured

by Hoechst, can be used. For a general discussion of optical plastics, see The Handbook of Plastic Optics, U.S. Precision Lens, Inc., Cincinnati, Ohio, 1983, pages 17-29.

In terms of the "crown" and "flint" designations, the design strategy of the first through fourth aspects of the invention can be summarized as:

(1) For the negative first lens unit, use positive flints which preferably have negative Q-values with negative crowns having positive Q-values (preferably, large positive Q-values).

(2) For the positive second lens unit, use positive crowns having positive Q-values (preferably, large positive Q-values) with negative flints having negative Q-values or small positive Q-values.

The fifth aspect of the invention is directed specifically to the V-values of the lens elements used in the second lens unit. In retrofocus lenses, correction of axial color is preferably achieved in the rear (second) unit since the height of the axial marginal ray is largest in that unit. Such correction is achieved through the use of low dispersion glasses in positive power elements and high dispersion glasses in negative power elements.

Lateral color correction, on the other hand, is preferably achieved in the front (first) unit where the chief ray height is significantly larger than that of the axial marginal ray. In this case, the correction is achieved through the use of high dispersion glasses in positive power elements and low dispersion glasses in negative power elements, i.e., the reverse of the rear unit.

In telecentric lenses of the type disclosed herein, the height of the chief ray in the rear unit is not insignificant. As a result, the choice of glasses in that unit can have a substantial effect on the correction the lateral color. In particular, it has been found that lateral color can be significantly improved when the rear unit includes at least one positive lens element having a V-value greater than 75 and where the composite V-value of the rear unit V_{U2C} satisfies the relationship:

$$V_{U2C} > 0.1/(p' \cdot F\#_{U2}),$$

where p' and $F\#_{U2}$ are as defined above.

This aspect of the invention is based on the discovery that the lateral color of the entire lens can be improved by reducing axial color aberrations between the lens' entrance pupil and its aperture stop. That is, the image
5 of the entrance pupil by the rear unit should have small axial color to achieve low lateral color for the entire lens.

This interaction between the axial color of the rear unit and the lateral color of the entire lens can be seen as follows. Consider red, green, and blue chief rays. If the axial color of the rear unit is small, after passing
10 through the rear unit, these rays will strike the optical axis at essentially the same location (the aperture stop) with essentially the same angle. Accordingly, when these rays enter the front unit they will be at essentially the same height. The ability of the front unit to correct lateral color will thus be improved. For a telecentric entrance pupil, the red, green, and blue
15 chief rays will, of course, enter the entrance pupil substantially parallel to the optical axis.

When V_{U2C} satisfies the above relationship, the axial color of the rear unit's image of the entrance pupil is improved and thus the lens' overall lateral color relative to the size of a pixel is improved.

20 Without intending to limit it in any manner, the present invention will be more fully described by the following examples.

Examples

Figures 1-9 illustrate projection lenses constructed in accordance with the invention. Corresponding prescriptions and optical properties
25 appear in Tables 1-9, respectively. Note that Example 1H is a comparative example and does not employ any of the aspects of the invention.

HOYA, OHARA, or SCHOTT designations are used for the various glasses employed in the lens systems. Equivalent glasses made by other manufacturers can be used in the practice of the invention. Industry
30 acceptable materials are used for the plastic elements. The designation

490573 used in Tables 4, 5, and 7 represents acrylic plastics having an index of refraction of 1.490 and a V-value at the d line of 57.3.

The aspheric coefficients set forth in the tables are for use in the following equation:

$$z = \frac{cy^2}{1 + [1 - (1+k)c^2y^2]^{1/2}} + Dy^4 + Ey^6 + Fy^8 + Gy^{10} + Hy^{12} + Iy^{14}$$

where z is the surface sag at a distance y from the optical axis of the system, c is the curvature of the lens at the optical axis, and k is a conic constant, which is zero except where indicated in the prescriptions of Tables 1-9.

The designation "a" associated with various surfaces in the tables represents an aspherical surface, i.e., a surface for which at least one of D, E, F, G, H, or I in the above equation is not zero; and the designation "c" indicates a surface for which k in the above equation is not zero. The various planar structures located on the short conjugate side of U₂ in the figures and tables represent components which are used with or are a part of the pixelized panel. They do not constitute part of the projection lens. All dimensions given in the tables are in millimeters.

The prescription tables are constructed on the assumption that light travels from left to right in the figures. In actual practice, the viewing screen will be on the left and the pixelized panel will be on the right, and light will travel from right to left. In particular, the references in the prescription tables to objects/images and entrance/exit pupils are reversed from that used in the rest of the specification and in the claims. The pixelized panel is shown in the figures by the designation "PP" and the aperture stop or pseudo-aperture stop is shown by the designation "AS".

The projection lenses of the invention can be focused in various ways, e.g., by moving the entire lens relative to the pixelized panel. In addition to focusing, the projection lens can also have zoom capabilities as illustrated in Examples 4-7. Conventional mechanisms known in the art are used to move the lens and/or its component parts during focusing and zooming.

The zoom projection lenses of Examples 4, 5, and 7 were designed using the pseudo-aperture stop/entrance pupil technique of Betensky, U.S. Patent No. 5,313,330. In accordance with this approach, the illumination system is used to define the entrance pupil for the projection lens, with the entrance pupil being located at a constant position relative to the pixelized panel for all lens focal lengths and conjugates. The location of this pupil is determined by the substantially parallel light (substantially telecentric light) which passes through the pixelized panel from the illumination system.

Table 10 summarizes various properties of Examples 1A, 2A, 2B, 3, 8, and 9 which were designed in accordance with the fifth aspect of the invention. As shown in this table, each of these lenses has a $V_{U2/C}$ value which is greater than $0.1/(p' \cdot F\#_{U2})$. As shown by their corresponding prescription tables, each of these examples also includes a positive lens element in its rear unit which has a V-value greater than 75.

Table 11 summarizes various properties of the lenses of Examples 1-9. As can be seen from this table and from the corresponding prescription tables, the lens systems of the invention have the five desired properties discussed above for projection lenses which are to be used with pixelized panels. A comparison of Examples 1A through 1G, which employ various aspects of the invention, with Example 1G, which does not employ any aspect of the invention, further shows that the lenses of the invention achieve improved lateral color correction.

It is important to note that the lenses of the invention achieve all of the above desired properties in a manner which allows the lenses to be manufactured at a cost suitable for a consumer item, e.g., a computer monitor. This is especially so when the high Q lens elements are composed of a COC plastic.

Although specific embodiments of the invention have been described and illustrated, it is to be understood that a variety of modifications which

do not depart from the scope and spirit of the invention will be evident to persons of ordinary skill in the art from the foregoing disclosure.

TABLE 1A

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	59.3714	5.00000	ACRYLIC	36.80
2	ac	10.6086	19.08902		24.45
3		-34.1021	2.00000	S-FPL51	20.41
4		45.8791	4.50000	S-LAH60	20.06
5		-45.8791	12.81672		19.73
6	Aperture stop		15.63439		10.16
7		-403.8211	8.00000	S-FPL51	21.66
8		-16.6819	2.00000	S-TIH4	23.40
9		-40.3246	0.50000		26.59
10		37.7035	10.00000	S-FPL51	30.87
11		-37.7035	0.50000		31.24
12	a	-350.0000	5.00000	ACRYLIC	30.04
13	a	-43.6995	1.92883		29.02
14		∞	30.00000	BK7	28.12
15		∞	2.75000	SIO2	22.19
16		∞	4.55807		21.63

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-8.7623E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	-7.8434E-07	1.7523E-08	-5.8084E-11	4.4903E-14	5.0784E-17	-7.2011E-20
2	3.1184E-05	8.6569E-09	1.7167E-09	-7.3921E-12	5.7015E-15	2.6858E-17
12	2.3951E-06	1.1099E-08	1.6764E-10	1.2859E-13	-1.5123E-15	-1.8927E-18
13	2.0975E-05	4.4000E-08	-6.6749E-11	1.1233E-12	2.1064E-17	-1.2502E-17

First Order Data

f/number	2.75	Overall Length	1118.44
Magnification	-0.0133	Forward Vertex Distance	124.277
Object Height	-762.00	Barrel Length	119.719
Object Distance	-994.165	Entrance Pupil Distance	19.6973
Effective Focal Length	13.4862	Exit Pupil Distance	1317.06
Image Distance	4.55807	Stop Diameter	10.159
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1A (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f
1	1 2	-0.36784E-01	-27.186
2	3 4	-0.25618E-01	-39.036
3	4 5	0.35546E-01	28.133
4	7 8	0.28758E-01	34.773
5	8 9	-0.25576E-01	-39.099
6	10 11	0.25203E-01	39.678
7	12 13	0.99007E-02	101.00

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	0.11763E-01	85.014
4 5	7 9	0.23996E-02	416.74

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-2.02
2	S-FPL51	OHARA	1.496999	81.5	120.0	-2.89
3	S-LAH60	OHARA	1.834000	37.2	-34.0	2.09
4	S-FPL51	OHARA	1.496999	81.5	120.0	2.58
5	S-TIH4	OHARA	1.755199	27.5	46.0	-2.90
6	S-FPL51	OHARA	1.496999	81.5	120.0	2.94
7	ACRYLIC	PLASTICS	1.491738	57.4	120.0	7.49

TABLE 1B

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	103.6090	3.32000	ACRYLIC	35.51
2	ac	11.1107	18.27333		25.26
3		-46.8988	1.66000	S-FPL51	22.34
4		72.0284	5.39500	LAF7	22.13
5		-39.0089	16.24558		21.86
6	Aperture stop	16.96362			10.15
7	"	7.88500		FC5	22.28
8		-17.2589	1.66000	FD6	23.78
9		-46.1508	0.41500		26.85
10		67.5491	8.30000	BACD5	30.01
11		-32.1168	0.41500		30.74
12		-332.0000	4.98000	ACRYLIC	29.89
13	a	-43.6995	5.00249		29.49
14	"	30.00000		BSC7	27.58
15	"	2.75000		SIO2	22.00
16	"	4.36043			21.47

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-8.7623E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	7.6176E-07	1.0942E-08	-7.0780E-11	5.5932E-14	1.0626E-16	-5.0397E-20
2	2.2483E-05	-2.9910E-08	1.5696E-09	-7.5487E-12	-1.3617E-14	1.0615E-16
13	1.5668E-05	2.0198E-08	-1.4769E-10	6.7756E-13	-1.4567E-15	1.7726E-18

First Order Data

f/number	3.00	Overall Length	1118.49
Magnification	-0.0133	Forward Vertex Distance	127.625
Object Height	-762.00	Barrel Length	123.265
Object Distance	-990.865	Entrance Pupil Distance	18.3005
Effective Focal Length	13.4230	Exit Pupil Distance	2167.68
Image Distance	4.36043	Stop Diameter	9.675
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1B (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f
1	1 2	-0.39044E-01	-25.612
2	3 4	-0.17578E-01	-56.888
3	4 5	0.29003E-01	34.480
4	7 8	0.28246E-01	35.404
5	8 9	-0.28458E-01	-35.140
6	10 11	0.26229E-01	38.125
7	12 13	0.98272E-02	101.76

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	0.12806E-01	78.086
4 5	7 9	-0.66544E-03	-1502.8

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-1.91
2	S-FPL51	OHARA	1.496999	81.5	120.0	-4.24
3	LAF7	HOYA	1.749497	35.0	-32.0	2.57
4	FC5	HOYA	1.487490	70.4	13.0	2.64
5	FD6	HOYA	1.805184	25.5	48.0	-2.62
6	BACD5	HOYA	1.589129	61.3	-3.3	2.84
7	ACRYLIC	PLASTICS	1.491738	57.4	120.0	7.58

TABLE 1C

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	130.7027	3.32000	ACRYLIC	34.99
2	ac	10.9287	18.25812		25.01
3		-54.7993	1.66000	S-FPL51	22.25
4		78.0558	5.39500	LAF7	22.04
5		-39.6992	16.00627		21.75
6	Aperture stop		16.66916		10.32
7		-1557.5450	7.88500	S-FPL51	22.07
8		-20.3147	1.66000	FD6	23.96
9		-49.6442	0.41500		26.34
10		55.6114	8.30000	S-FPL51	29.20
11		-34.2137	0.41500		29.90
12		1158.2491	4.98000	ACRYLIC	29.43
13	a	-43.3343	4.88391		29.15
14		∞	30.00000	BSC7	27.33
15		∞	2.75000	SIO2	21.93
16		∞	4.35566		21.41

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-8.7623E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	6.8149E-07	1.1190E-08	-7.1594E-11	5.3469E-14	1.0217E-16	-6.2815E-20
2	1.9588E-05	-3.3366E-08	1.6125E-09	-7.7623E-12	-1.5088E-14	9.8917E-17
13	1.5546E-05	2.0202E-08	-1.6352E-10	6.8030E-13	-1.2036E-15	8.9310E-19

First Order Data

f/number	3.00	Overall Length	1118.39
Magnification	-0.0133	Forward Vertex Distance	126.953
Object Height	-762.00	Barrel Length	122.597
Object Distance	-991.436	Entrance Pupil Distance	17.8249
Effective Focal Length	13.4226	Exit Pupil Distance	-4205.55
Image Distance	4.35566	Stop Diameter	9.808
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1C (continued)**First Order Properties of Elements**

Element Number	Surface Numbers		Power	f'
1	1	2	-0.40856E-01	-24.476
2	3	4	-0.15501E-01	-64.513
3	4	5	0.27922E-01	35.813
4	7	8	0.24187E-01	41.344
5	8	9	-0.22825E-01	-43.811
6	10	11	0.22744E-01	43.969
7	12	13	0.11756E-01	85.063

First-Order Properties of Doublets

Element Numbers	Surface Numbers		Power	f'
2 3	3	5	0.13605E-01	73.502
4 5	7	9	0.96261E-03	1038.8

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-1.82
2	S-FPL51	OHARA	1.496999	81.5	120.0	-4.81
3	LAF7	HOYA	1.749497	35.0	-32.0	2.67
4	S-FPL51	OHARA	1.496999	81.5	120.0	3.08
5	FD6	HOYA	1.805184	25.5	48.0	-3.26
6	S-FPL51	OHARA	1.496999	81.5	120.0	3.28
7	ACRYLIC	PLASTICS	1.491738	57.4	120.0	6.34

TABLE 1D

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	77.4529	3.32000	COC	34.48
2	ac	11.2265	17.52400		24.89
3		-100.0278	1.66000	LAC8	21.81
4		46.2601	5.39500	FD15	21.45
5		-37.3085	15.90334		21.19
6	Aperture stop		16.77422		10.12
7		∞	7.88500	FC5	22.33
8		-17.4982	1.66000	FD6	23.86
9		-46.0327	0.41500		26.89
10		70.7374	8.30000	BACD5	29.97
11		-31.5287	0.41500		30.71
12		-419.6868	4.98000	ACRYLIC	29.82
13	a	-46.9933	5.57933		29.38
14		∞	30.00000	BSC7	27.45
15		∞	2.75000	SIO2	22.11
16		∞	5.02074		21.61

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number Constant
2 -8.7623E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	-4.1055E-08	7.5201E-09	-7.4178E-11	6.4778E-14	1.4525E-16	-3.8985E-20
2	2.4287E-05	-3.8037E-08	1.4486E-09	-8.1959E-12	-1.4643E-14	1.3569E-16
13	1.4875E-05	2.2348E-08	-1.4883E-10	6.6828E-13	-1.4400E-15	1.9154E-18

First Order Data

f/number	3.00	Overall Length	1118.24
Magnification	-0.0133	Forward Vertex Distance	127.582
Object Height	-762.00	Barrel Length	122.561
Object Distance	-990.661	Entrance Pupil Distance	17.9096
Effective Focal Length	13.4139	Exit Pupil Distance	-24282.3
Image Distance	5.02074	Stop Diameter	9.766
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1D (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f'
1	1 2	-0.39910E-01	-25.056
2	3 4	-0.22647E-01	-44.156
3	4 5	0.32944E-01	30.354
4	7 8	0.27859E-01	35.895
5	8 9	-0.27783E-01	-35.993
6	10 11	0.26201E-01	38.166
7	12 13	0.93332E-02	107.14

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f'
2 3	3 5	0.11872E-01	84.233
4 5	7 9	-0.37209E-03	-2687.5

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	COC	PLASTICS	1.533300	56.2	150.0	-1.87
2	LAC8	HOYA	1.712997	53.9	-40.0	-3.29
3	FD15	HOYA	1.698941	30.0	30.0	2.26
4	FC5	HOYA	1.487488	70.4	13.0	2.68
5	FD6	HOYA	1.805178	25.5	48.0	-2.68
6	BACD5	HOYA	1.589127	61.3	-3.3	2.85
7	ACRYLIC	PLASTICS	1.491736	57.4	120.0	7.99

TABLE 1E

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	76.8525	3.32000	ACRYLIC	33.16
2	ac	11.5697	19.57361		23.72
3		-50.1666	1.66000	TAF1	17.91
4		25.1662	5.39500	FD8	17.70
5		-32.4216	16.81906		17.65
6	Aperture stop		17.81341		11.14
7		2898.2890	7.88500	S-FPL53	22.83
8		-17.8509	1.66000	NBFD15	24.32
9		-44.3692	0.41500		27.44
10		67.9928	8.30000	S-FPL53	30.92
11		-28.1136	0.41500		31.53
12		4802.4648	4.98000	ACRYLIC	31.25
13	a	-39.5799	13.18499		31.15
14		∞	30.00000	BSC7	27.12
15		∞	2.75000	SIO2	22.03
16		∞	5.02004		21.54

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface Number**

Constant
2 -8.7623E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	2.4193E-06	1.6999E-08	-6.6477E-11	2.8634E-14	-6.2845E-18	2.3440E-19
2	2.5202E-05	-1.8176E-08	1.6793E-09	-5.9882E-12	-8.5168E-15	5.7833E-17
13	1.2319E-05	1.7274E-08	-1.3959E-10	6.8649E-13	-1.5802E-15	1.6450E-18

First Order Data

f/number	3.00	Overall Length	1118.68
Magnification	-0.0133	Forward Vertex Distance	139.191
Object Height	-762.00	Barrel Length	134.171
Object Distance	-979.493	Entrance Pupil Distance	18.9477
Effective Focal Length	13.2791	Exit Pupil Distance	-11308.2
Image Distance	5.02004	Stop Diameter	10.628
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1E (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f
1	1 2	-0.35499E-01	-28.170
2	3 4	-0.46537E-01	-21.488
3	4 5	0.46766E-01	21.383
4	7 8	0.24710E-01	40.470
5	8 9	-0.26235E-01	-38.117
6	10 11	0.21478E-01	46.559
7	12 13	0.12522E-01	79.859

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	0.40621E-02	246.18
4 5	7 9	-0.19165E-02	-521.77

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	$1/f_0$
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-2.12
2	TAF1	HOYA	1.772500	49.6	-44.0	-1.62
3	FD8	HOYA	1.688931	31.2	2.7	1.61
4	S-FPL53	OHARA	1.438750	95.0	160.0	3.05
5	NBFD15	HOYA	1.806100	33.3	-11.0	-2.87
6	S-FPL53	OHARA	1.438750	95.0	160.0	3.51
7	ACRYLIC	PLASTICS	1.491738	57.4	120.0	6.01

TABLE 1F

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	93.5739	3.32000	ACRYLIC	35.12
2	ac	10.9890	17.65325		25.03
3		-92.4844	1.66000	LAC8	21.92
4		50.9108	5.39500	FD15	21.58
5		-37.1377	15.97087		21.32
6	Aperture stop		16.67433		10.12
7		∞	7.88500	FC5	22.29
8		-17.5555	1.66000	FD6	23.84
9		-46.0739	0.41500		26.85
10		71.5714	8.30000	BACD5	29.90
11		-31.6450	0.41500		30.67
12		-315.3373	4.98000	COC	29.85
13	a	-47.4483	5.58566		29.48
14		∞	30.00000	BSC7	27.51
15		∞	2.75000	SIO2	22.13
16		∞	5.01569		21.62

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-8.7623E-01

Even Polynomial Aspheres

Surf. No.	D	E	F	G	H	I
1	1.8835E-07	8.6676E-09	-7.2453E-11	6.4925E-14	1.3523E-16	-8.8201E-20
2	2.4575E-05	-3.7278E-08	1.5002E-09	-7.8715E-12	-1.4516E-14	1.2247E-16
13	1.3615E-05	2.0730E-08	-1.4448E-10	6.7018E-13	-1.5230E-15	1.9444E-18

First Order Data

f/number	3.00	Overall Length	1118.44
Magnification	-0.0133	Forward Vertex Distance	127.680
Object Height	-762.00	Barrel Length	122.664
Object Distance	-990.756	Entrance Pupil Distance	18.1203
Effective Focal Length	13.4181	Exit Pupil Distance	55457.5
Image Distance	5.01569	Stop Diameter	9.728
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1F (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f
1	1 2	-0.38970E-01	-25.661
2	3 4	-0.21819E-01	-45.832
3	4 5	0.31728E-01	31.517
4	7 8	0.27768E-01	36.012
5	8 9	-0.27652E-01	-36.164
6	10 11	0.26048E-01	38.391
7	12 13	0.96101E-02	104.06

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	0.11451E-01	87.331
4 5	7 9	-0.32974E-03	-3032.7

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	ACRYLIC	PLASTICS	1.491736	57.4	120.0	-1.91
3	LAC8	HOYA	1.712997	53.9	-40.0	-3.42
4	FD15	HOYA	1.698941	30.0	30.0	2.35
7	FC5	HOYA	1.487488	70.4	13.0	2.68
8	FD6	HOYA	1.805178	25.5	48.0	-2.70
10	BACD5	HOYA	1.589127	61.3	-3.3	2.86
12	COC	PLASTICS	1.533300	56.2	150.0	7.76

TABLE 1G

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	76.6089	3.32000	COC	34.54
2	ac	11.2724	17.48853		24.94
3		-98.8496	1.66000	LAC8	21.82
4		45.3051	5.39500	FD15	21.45
5		-37.2860	15.89351		21.20
6	Aperture stop		16.80939		10.11
7		∞	7.88500	FC5	22.35
8		-17.4743	1.66000	FD6	23.88
9		-46.0510	0.41500		26.92
10		70.2170	8.30000	BACD5	30.03
11		-31.4670	0.41500		30.77
12		-366.8816	4.98000	COC	29.87
13	a	-49.4824	5.54915		29.44
14		∞	30.00000	BSC7	27.51
15		∞	2.75000	SIO2	22.13
16		∞	5.01802		21.62

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-8.7623E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	1.8386E-07	7.8317E-09	-7.4925E-11	6.3331E-14	1.4726E-16	-4.7105E-20
2	2.4794E-05	-3.6540E-08	1.4596E-09	-8.1096E-12	-1.4567E-14	1.3092E-16
13	1.3549E-05	2.1636E-08	-1.4773E-10	6.7442E-13	-1.4352E-15	1.7667E-18

First Order Data

f/number	3.00	Overall Length	1118.08
Magnification	-0.0133	Forward Vertex Distance	127.539
Object Height	-762.00	Barrel Length	122.521
Object Distance	-990.544	Entrance Pupil Distance	17.9667
Effective Focal Length	13.4134	Exit Pupil Distance	10215.2
Image Distance	5.01802	Stop Diameter	9.728
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1G (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f'
1	1 2	-0.39636E-01	-25.230
2	3 4	-0.23061E-01	-43.364
3	4 5	0.33255E-01	30.071
4	7 8	0.27898E-01	35.845
5	8 9	-0.27853E-01	-35.903
6	10 11	0.26292E-01	38.035
7	12 13	0.93749E-02	106.67

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f'
2 3	3 5	0.11799E-01	84.752
4 5	7 9	-0.40378E-03	-2476.6

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	COC	PLASTICS	1.533302	56.2	150.0	-1.88
2	LAC8	HOYA	1.713000	53.9	-40.0	-3.23
3	FD15	HOYA	1.698945	30.1	30.0	2.24
4	FC5	HOYA	1.487490	70.4	13.0	2.67
5	FD6	HOYA	1.805184	25.5	48.0	-2.68
6	BACD5	HOYA	1.589129	61.3	-3.3	2.84
7	COC	PLASTICS	1.533302	56.2	150.0	7.95

TABLE 1H

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	88.3121	3.32000	ACRYLIC	35.20
2	ac	10.9340	17.71330		25.10
3		-90.1977	1.66000	LAC8	22.02
4		55.5315	5.39500	FD15	21.69
5		-36.9749	16.02150		21.44
6	Aperture stop	16.75151			10.06
7		∞	7.88500	FC5	22.33
8		-17.4485	1.66000	FD6	23.86
9		-45.6537	0.41500		26.89
10		73.8137	8.30000	BACD5	29.94
11		-31.7233	0.41500		30.73
12		-332.0000	4.98000	ACRYLIC	29.95
13	a	-43.6995	5.55400		29.59
14		∞	30.00000	BSC7	27.57
15		∞	2.75000	SIO2	22.14
16		∞	5.01303		21.62

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number Constant
2 -8.7623E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	-3.5930E-07	8.2239E-09	-7.0588E-11	7.1058E-14	1.3597E-16	-1.5686E-19
2	2.4857E-05	-4.0707E-08	1.4840E-09	-7.8653E-12	-1.4656E-14	1.2211E-16
13	1.4517E-05	2.2248E-08	-1.3968E-10	6.5242E-13	-1.6562E-15	2.2768E-18

First Order Data

f/number	3.00	Overall Length	1117.70
Magnification	-0.0133	Forward Vertex Distance	127.833
Object Height	-762.00	Barrel Length	122.820
Object Distance	-989.871	Entrance Pupil Distance	18.1793
Effective Focal Length	13.4075	Exit Pupil Distance	6234.75
Image Distance	5.01303	Stop Diameter	9.726
Stop Surface Number	6	Distance to Stop	0.00

TABLE 1H (continued)**First Order Properties of Elements**

Element Number	Surface Numbers		Power	f'
1	1	2	-0.38848E-01	-25.742
2	3	4	-0.20843E-01	-47.978
3	4	5	0.30734E-01	32.537
4	7	8	0.27939E-01	35.793
5	8	9	-0.27761E-01	-36.022
6	10	11	0.25778E-01	38.793
7	12	13	0.98272E-02	101.76

First-Order Properties of Doublets

Element Numbers	Surface Numbers		Power	f'
2 3	3	5	0.11378E-01	87.889
4 5	7	9	-0.27550E-03	-3629.8

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-1.92
2	LAC8	HOYA	1.713000	53.9	-40.0	-3.58
3	FD15	HOYA	1.698945	30.1	30.0	2.43
4	FC5	HOYA	1.487490	70.4	13.0	2.67
5	FD6	HOYA	1.805184	25.5	48.0	-2.69
6	BACD5	HOYA	1.589129	61.3	-3.3	2.89
7	ACRYLIC	PLASTICS	1.491738	57.4	120.0	7.59

TABLE 2A

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	-186.0847	3.00000	ACRYLIC	25.57
2	ac	11.2883	15.69341		17.57
3		-271.4427	1.50000	FCD1	11.89
4		9.5378	4.00000	FF5	10.79
5		-456.3765	8.34007		9.87
6	Aperture stop		10.75956		5.14
7		-91.6778	9.00000	S-FPL53	12.60
8		-10.0114	1.80000	NBFD15	15.69
9		-23.3591	0.50000		18.88
10		61.9879	8.00000	FC5	21.98
11		-19.0062	0.50000		23.27
12		-131.7084	4.00000	ACRYLIC	22.91
13	a	-36.0270	1.44958		22.90
14		∞	25.40000	SF1	22.50
15		∞	25.40000	BK7	20.41
16		∞	1.35000	BK7	18.04
17		∞	-0.01237		17.92

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-1.6440E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	1.8743E-04	-1.0081E-06	1.1545E-09	1.1360E-11	-4.0909E-14	4.4384E-17
2	1.7734E-04	1.3800E-06	-9.4574E-09	-1.9479E-10	-8.2983E-13	3.1606E-14
13	2.2974E-05	-9.6651E-09	4.4534E-10	-9.3065E-13	-8.7352E-15	6.8537E-17

First Order Data

f/number	5.00	Overall Length	618.125
Magnification	-0.0235	Forward Vertex Distance	120.680
Object Height	-381.00	Barrel Length	120.693
Object Distance	-497.445	Entrance Pupil Distance	14.2058
Effective Focal Length	12.0272	Exit Pupil Distance	-22731.4
Image Distance	-.123740E-01	Stop Diameter	5.074
Stop Surface Number	6	Distance to Stop	0.00

TABLE 2A (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f
1	1 2	-0.46436E-01	-21.535
2	3 4	-0.54035E-01	-18.507
3	4 5	0.63239E-01	15.813
4	7 8	0.40351E-01	24.782
5	8 9	-0.43240E-01	-23.127
6	10 11	0.32428E-01	30.837
7	12 13	0.10052E-01	99.480

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	0.94962E-02	105.31
4 5	7 9	-0.55710E-02	-179.50

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	t/f_0
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-1.79
2	FCD1	HOYA	1.496997	81.6	120.0	-1.54
3	FF5	HOYA	1.592703	35.4	28.0	1.31
4	S-FPL53	OHARA	1.438750	95.0	160.0	2.06
5	NBFD15	HOYA	1.806100	33.3	-11.0	-1.92
6	FC5	HOYA	1.487490	70.4	13.0	2.56
7	ACRYLIC	PLASTICS	1.491738	57.4	120.0	8.27

TABLE 2B

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	-373.3806	3.00000	ACRYLIC	26.71
2	ac	13.4329	13.61509		18.79
3		-197.8296	1.50000	LAC8	13.19
4		13.0362	4.00000	FD6	12.10
5		147.1213	10.49557		11.09
6	Aperture stop		11.11013		5.03
7		330.3008	9.00000	FCD1	13.59
8		-9.6915	1.80000	NBFD15	15.99
9		-24.8691	0.50000		19.34
10		307.3694	8.00000	CF6	21.50
11		-17.8236	0.50000		23.20
12		-91.4836	4.00000	ACRYLIC	22.78
13	a	-36.8932	2.52287		22.82
14		∞	25.40000	SF1	22.29
15		∞	25.40000	BK7	20.30
16		∞	1.35000	BK7	18.04
17		∞	-0.00123		17.92

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-1.6440E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	1.7194E-04	-7.5475E-07	2.1301E-10	1.0133E-11	-2.7500E-14	2.1094E-17
2	1.6679E-04	1.6614E-06	-1.7644E-08	-6.5292E-11	4.4482E-13	7.6509E-15
13	2.0353E-05	-6.3420E-09	4.0020E-10	-1.3029E-12	-4.9655E-15	5.6123E-17

First Order Data

f/number	5.00	Overall Length	618.000
Magnification	-0.0235	Forward Vertex Distance	122.192
Object Height	-381.00	Barrel Length	122.194
Object Distance	-495.807	Entrance Pupil Distance	15.2741
Effective Focal Length	12.0137	Exit Pupil Distance	-11317.2
Image Distance	-.122983E-02	Stop Diameter	4.962
Stop Surface Number	6	Distance to Stop	0.00

TABLE 2B (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f'
1	1 2	-0.38179E-01	-26.193
2	3 4	-0.58729E-01	-17.027
3	4 5	0.57573E-01	17.369
4	7 8	0.52475E-01	19.057
5	8 9	-0.48407E-01	-20.658
6	10 11	0.30594E-01	32.686
7	12 13	0.81800E-02	122.25

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f'
2 3	3 5	-0.16896E-02	-591.86
4 5	7 9	0.28047E-02	356.54

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	t/f_0
1	Acrylic	PLASTICS	1.491738	57.4	120.0	-2.14
2	IAC8	Hoya	1.713000	53.9	-40.0	-1.40
3	FD6	Hoya	1.805184	25.5	48.0	1.42
4	FCD1	Hoya	1.496997	81.6	120.0	1.56
5	NBFD15	Hoya	1.806100	33.3	-11.0	-1.69
6	CF6	Hoya	1.517419	52.2	-8.4	2.68
7	Acrylic	Plastics	1.491738	57.4	120.0	10.01

TABLE 3

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	55.0000	6.00000	ACRYLIC	61.93
2	ac	17.7228	16.70218		40.74
3	a	80.5325	5.00000	ACRYLIC	39.12
4	a	19.6134	10.74501		33.07
5		-59.7073	2.00000	S-FPL53	32.87
6		40.1547	8.50000	S-LAH66	33.27
7		-92.7858	0.50000		32.82
8		36.5520	4.50000	NBFD10	30.03
9		58.4439	17.93803		27.98
10	Aperture stop		16.16397		16.63
11		-244.0248	10.00000	S-FPL51	26.94
12		-18.4972	2.00000	NBFD15	28.84
13		-69.9376	0.50000		34.71
14		73.9485	12.00000	S-FPL51	41.58
15		-44.0735	0.50000		43.15
16		1435.0179	6.00000	FC5	44.19
17		-111.9515	0.50000		44.55
18	c	128.8048	8.00000	ACRYLIC	44.34
19	a	-66.7794	5.55641		43.95
20		∞	40.00000	604638	41.40
21		∞	2.00000	BK7	34.56
22		∞	5.01034		34.19

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-7.1726E-01
18	-6.4600E+01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	2.3720E-06	-4.1636E-09	-3.3306E-12	1.6221E-14	-1.6955E-17	5.7242E-21
2	1.1106E-05	1.7218E-08	-1.4102E-11	-1.4782E-13	1.0253E-15	-9.9160E-19
3	4.5674E-06	1.5449E-10	-3.5270E-13	-1.5663E-14	4.6591E-18	4.2830E-20
4	-8.5546E-06	-1.5848E-08	-1.3210E-10	-4.2174E-14	5.4509E-16	-2.0420E-18
19	1.2888E-06	1.3113E-08	-3.9578E-11	9.0021E-14	-1.0560E-16	5.2799E-20

TABLE 3 (continued)**First Order Data**

f/number	2.40	Overall Length	1055.89
Magnification	-0.0202	Forward Vertex Distance	180.116
Object Height	-812.80	Barrel Length	175.106
Object Distance	-875.778	Entrance Pupil Distance	31.5266
Effective Focal Length	18.3066	Exit Pupil Distance	-2421.86
Image Distance	5.01034	Stop Diameter	15.990
Stop Surface Number	10	Distance to Stop	0.00

First Order Properties of Elements

Element Number	Surface Numbers	Power	f'
1	1 2	-0.17808E-01	-56.156
2	3 4	-0.18452E-01	-54.194
3	5 6	-0.18386E-01	-54.388
4	6 7	0.26796E-01	37.320
5	8 9	0.93456E-02	107.00
6	11 12	0.25198E-01	39.686
7	12 13	-0.31497E-01	-31.749
8	14 15	0.17390E-01	57.505
9	16 17	0.46882E-02	213.30
10	18 19	0.11031E-01	90.657

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f'
3 4	5 7	0.94169E-02	106.19
6 7	11 13	-0.70497E-02	-141.85

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-3.07
2	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-2.96
3	S-FPL53	OHARA	1.438750	95.0	160.0	-2.97
4	S-LAH66	OHARA	1.772499	49.6	-38.0	2.04
5	NBFD10	HOYA	1.834001	37.3	-18.0	5.84
6	S-FPL51	OHARA	1.496999	81.5	120.0	2.17
7	NBFD15	HOYA	1.806100	33.3	-11.0	-1.73
8	S-FPL51	OHARA	1.496999	81.5	120.0	3.14
9	FC5	HOYA	1.487490	70.4	13.0	11.65
10	ACRYLIC	PLASTICS	1.491738	57.4	120.0	4.95

TABLE 4

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	152.1157	8.00000	490573	101.00
2	ac	40.3060	86.02596		78.00
3		∞	11.00000		40.50
4		-64.0652	3.30000	FCD1	36.70
5		120.4233	5.50000	FD14	38.40
6		∞	Space 1		39.20
7		203.6135	3.40000	TAF3	41.10
8		33.1426	14.00000	FD14	42.50
9		-106.0435	4.53801		43.40
10		278.2267	10.10000	FCD1	43.90
11		-42.0110	3.90000	FD4	43.90
12		-613.6439	6.70793		45.80
13		-86.0046	4.30000	FD4	47.00
14		103.4014	10.80000	FCD1	51.50
15		-103.4014	5.06806		54.00
16		352.9613	14.70000	FCD1	61.00
17		-54.3360	1.15342		62.40
18	a	-503.5699	7.00000	490573	61.70
19		-138.3938	Space 2		61.90
20		∞	92.00000	FD10	60.00
21		∞	1.00000		50.00
22		∞	59.00000	BSC7	50.00
23		∞	3.00000		43.00
24		∞	1.50000	BSC7	43.00
25		∞	Image distance		43.00

Symbol Description

- a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-6.0000E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	3.8460E-07	-1.2374E-10	3.6056E-15	4.1919E-18	1.7563E-21	-4.8084E-25
2	4.6739E-07	7.7888E-11	-1.0406E-13	-7.5454E-17	6.6142E-20	-9.7771E-26
18	-5.0533E-07	1.8921E-11	-5.8477E-14	-1.3273E-17	5.2172E-20	-2.4737E-23

Variable Spaces

Zoom Pos.	Space 1 T(6)	Space 2 T(19)	Focal Shift	Image Distance
1	70.803	11.800	0.079	0.180
2	32.487	29.862	-0.007	0.385
3	4.037	55.522	-0.036	0.366

TABLE 4 (continued)**First-Order Data**

f/number	3.00	3.00	3.00
Magnification	-0.0070	-0.0070	-0.0070
Object Height	-2750.0	-2750.0	-2750.0
Object Distance	-4421.6	-6083.2	-8407.4
Effective Focal Length	31.431	43.011	59.208
Image Distance	0.17984	0.38515	0.36635
Overall Length	4860.4	6501.9	8823.3
Forward Vertex Distance	438.78	418.73	415.92
Barrel Length	438.60	418.34	415.55
Stop Surface Number	6	6	6
Distance to Stop	35.40	0.00	2.02
Stop Diameter	27.413	28.067	39.814
Entrance Pupil Distance	67.952	60.936	61.463
Exit Pupil Distance	1855.2	8858.9	-331.25

First Order Properties of Elements

Element Number	Surface Numbers	Power	f
1	1 2	-0.87250E-02	-114.61
2	4 5	-0.11955E-01	-83.645
3	5 6	0.63262E-02	158.07
4	7 8	-0.20135E-01	-49.666
5	8 9	0.28858E-01	34.652
6	10 11	0.13474E-01	74.218
7	11 12	-0.16696E-01	-59.893
8	13 14	-0.16242E-01	-61.570
9	14 15	0.94463E-02	105.86
10	16 17	0.10428E-01	95.893
11	18 19	0.25836E-02	387.06

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	4 6	-0.55209E-02	-181.13
4 5	7 9	0.96581E-02	103.54
6 7	10 12	-0.30581E-02	-327.00
8 9	13 15	-0.60289E-02	-165.87

TABLE 4 (continued)**Glass Table**

Elem.	Glass	Catalog	n_d	V_d	Q	t/f_0
1	490573	PLASTICS	1.489971	57.3	98.0	-3.65
2	FCD1	HOYA	1.496997	81.6	120.0	-2.66
3	FD14	HOYA	1.761823	26.6	40.0	5.03
4	TAF3	HOYA	1.804200	46.5	-44.0	-1.58
5	FD14	HOYA	1.761823	26.6	40.0	1.10
6	FCD1	HOYA	1.496997	81.6	120.0	2.36
7	FD4	HOYA	1.755199	27.5	31.0	-1.91
8	FD4	HOYA	1.755199	27.5	31.0	-1.96
9	FCD1	HOYA	1.496997	81.6	120.0	3.37
10	FCD1	HOYA	1.496997	81.6	120.0	3.05
11	490573	PLASTICS	1.489971	57.3	98.0	12.31

TABLE 5

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	316.4987	9.00000	490573	106.50
2	ac	48.5107	79.22000		83.70
3		-68.2336	4.10000	FCD1	53.00
4		290.7899	7.00000	TAF3	53.00
5		-157.0756	Space 1		52.00
6		154.9494	8.14000	FD60	54.20
7		758.2655	Space 2		55.40
8		-1067.2049	8.92000	FCD1	65.80
9		-119.5453	13.48000		67.20
10		-78.2658	6.00000	FD5	68.80
11		158.5274	13.50000	FCD1	77.70
12		-158.5274	0.10000		79.90
13		139.1541	16.70000	FCD1	88.00
14		-176.7399	35.55000		88.60
15		112.2150	19.30000	FCD1	89.00
16		-157.8763	0.90000		88.00
17		-217.6579	8.00000	FEL6	85.70
18		217.6579	8.72000		80.50
19	a	-1204.7930	9.00000	490573	79.90
20		-266.7334	Space 3		79.70
21		∞	17.00000		80.00
22		∞	55.00000	BSC7	80.00
23		∞	2.50000	BSC7	70.00
24		∞	Image distance		70.00

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-1.2000E+00

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	-3.7810E-08	3.8833E-11	4.3571E-15	-1.0785E-18	-3.9211E-22	6.9576E-26
2	4.3607E-07	1.0988E-10	-3.6564E-14	2.5559E-17	1.2829E-20	-7.5081E-24
19	-7.7096E-07	-5.1172E-11	-2.0446E-14	1.5579E-17	-2.9214E-21	-7.1999E-25

Variable Spaces

Zoom Pos.	Space 1 T(5)	Space 2 T(7)	Space 3 T(20)	Focal Shift	Image Distance
1	78.612	26.342	19.043	-0.064	0.453
2	40.873	26.342	30.135	-0.088	0.432
3	7.086	26.342	44.452	-0.089	0.409

TABLE 5 (continued)**First-Order Data**

f/number	2.81	2.81	2.81
Magnification	-0.0220	-0.0220	-0.0220
Object Height	-1500.0	-1400.0	-1400.0
Object Distance	-2265.8	-2722.6	-3311.0
Effective Focal Length	51.351	61.203	73.896
Image Distance	0.45274	0.43225	0.40922
Overall Length	2712.4	3142.5	3711.4
Forward Vertex Distance	446.58	419.91	400.42
Barrel Length	446.13	419.48	400.01
Stop Surface Number	5	5	5
Distance to Stop	39.31	20.44	3.54
Stop Diameter	39.840	43.740	48.851
Entrance Pupil Distance	66.614	62.226	57.560
Exit Pupil Distance	1550.9	-1322.1	-566.17

First Order Properties of Elements

Element Number	Surface Numbers	Power	f
1	1 2	-0.84577E-02	-118.24
2	3 4	-0.90270E-02	-110.78
3	4 5	0.78305E-02	127.71
4	6 7	0.41594E-02	240.42
5	8 9	0.37032E-02	270.03
6	10 11	-0.12969E-01	-77.105
7	11 12	0.61815E-02	161.77
8	13 14	0.62715E-02	159.45
9	15 16	0.73972E-02	135.19
10	17 18	-0.49170E-02	-203.38
11	19 20	0.14348E-02	696.98

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	-0.86100E-03	-1161.4
6 7	10 12	-0.62306E-02	-160.50

TABLE 5 (continued)**Glass Table**

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	490573	PLASTICS	1.489971	57.3	98.0	-2.30
2	FCD1	HOYA	1.496997	81.6	120.0	-2.16
3	TAF3	HOYA	1.804200	46.5	-44.0	2.49
4	FD60	HOYA	1.805181	25.5	55.0	4.68
5	FCD1	HOYA	1.496997	81.6	120.0	5.26
6	FD5	HOYA	1.672701	32.2	3.2	-1.50
7	FCD1	HOYA	1.496997	81.6	120.0	3.15
8	FCD1	HOYA	1.496997	81.6	120.0	3.11
9	FCD1	HOYA	1.496997	81.6	120.0	2.63
10	FEL6	HOYA	1.531720	48.8	-18.0	-3.96
11	490573	PLASTICS	1.489971	57.3	98.0	13.57

TABLE 6

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	53.1466	4.00000	ACRYLIC	42.52
2	ac	26.9064	9.56217		36.15
3		-114.9651	4.50000	S-LAH51	35.04
4		-43.7399	2.50000	S-FPL51	34.46
5		39.0015	3.00000		29.98
6		∞	Space 1		29.98
7		200.0861	2.00000	S-TIH11	24.87
8		36.6439	5.00000	S-LAH60	24.17
9		-120.4751	0.50000		23.71
10	a	17.7399	5.00000	ACRYLIC	21.62
11	a	16.1139	9.31913		18.76
12		Aperture stop	18.20440		16.94
13	ac	-16.4549	5.00000	ACRYLIC	22.38
14	a	-19.8793	0.50000		26.42
15		99.1823	8.50000	S-LAL14	31.07
16		-29.3750	2.00000	S-TIH10	31.76
17		-55.2706	Space 2		32.95
18		-62.8452	2.50000	S-TIH10	34.23
19		93.0148	5.00000	S-LAL8	35.96
20		-1264.5589	0.50000		36.80
21	ac	35.6906	10.00000	ACRYLIC	39.22
22	a	-97.5062	7.00000		39.54
23		∞	25.00000	BSC7	37.68
24		∞	2.00000		34.28
25		∞	2.74000	SIO2	33.89
26		∞	Image distance		33.53

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface
Number****Constant**

2 -6.3815E-01
13 -1.5056E-01
21 -1.1520E+00

**Even Polynomial Aspheres
Surf.**

No.	D	E	F	G	H	I
1	-1.5185E-06	7.3691E-09	4.7636E-12	-1.2584E-14	-2.4856E-17	4.8059E-20
2	-1.2508E-06	6.3840E-09	4.7562E-11	1.4176E-14	-4.9901E-16	8.3998E-19
10	-1.5142E-05	-4.4556E-08	-3.0808E-11	-6.7076E-14	5.5962E-16	-1.1087E-17
11	-2.0551E-05	-6.2752E-08	-8.1184E-11	-4.5191E-13	-2.5842E-15	-8.2754E-18
13	3.9089E-06	3.9114E-08	5.7323E-10	-1.5401E-11	1.1304E-13	-2.6062E-16
14	3.0798E-06	4.7174E-08	-1.8457E-10	-6.3064E-13	8.2234E-15	-1.6018E-17
21	-7.1191E-07	-9.7735E-10	-3.5332E-13	-2.1057E-14	-1.2971E-17	-1.1300E-19
22	5.3521E-06	-8.8466E-09	1.2274E-11	-4.4594E-15	-1.7331E-16	1.2830E-19

TABLE 6 (continued)**Variable Spaces**

Zoom Pos.	Space 1 T(6)	Space 2 T(17)	Focal Shift	Image Distance
1	15.384	23.057	-0.079	0.821
2	3.560	35.282	-0.082	0.838

First-Order Data

f/number	2.83	3.10
Magnification	-0.0043	-0.0054
Object Height	-3872.0	-3083.0
Object Distance	-7299.7	-7297.7
Effective Focal Length	31.529	39.572
Image Distance	0.82058	0.83768
Overall Length	7473.2	7471.7
Forward Vertex Distance	173.59	174.01
Barrel Length	172.77	173.17
Stop Surface Number	12	12
Distance to Stop	0.00	0.00
Stop Diameter	16.693	16.548
Entrance Pupil Distance	33.923	30.753
Exit Pupil Distance	-854.87	-6620.9

First Order Properties of Elements

Element Number	Surface Numbers	Power	f
1	1 2	-0.85699E-02	-116.69
2	3 4	0.11441E-01	87.405
3	4 5	-0.24347E-01	-41.072
4	7 8	-0.17399E-01	-57.475
5	8 9	0.29253E-01	34.185
6	10 11	0.38110E-04	26240.
7	13 14	-0.26701E-02	-374.52
8	15 16	0.29911E-01	33.432
9	16 17	-0.11237E-01	-88.989
10	18 19	-0.19549E-01	-51.154
11	19 20	0.82166E-02	121.70
12	21 22	0.18355E-01	54.481

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	-0.13082E-01	-76.439
4 5	7 9	0.12054E-01	82.962
8 9	15 17	0.18613E-01	53.725
10 11	18 20	-0.11162E-01	-89.589

TABLE 6 (continued)**Glass Table**

Elem.	Glass	Catalog	n_d	V_d	Q	t/f_0
1	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-3.70
2	S-LAH51	OHARA	1.785896	44.2	-33.0	2.77
3	S-FPL51	OHARA	1.496999	81.5	120.0	-1.30
4	S-TIH11	OHARA	1.784723	25.7	65.0	-1.82
5	S-LAH60	OHARA	1.834000	37.2	-34.0	1.08
6	ACRYLIC	PLASTICS	1.491738	57.4	120.0	832.25
7	ACRYLIC	PLASTICS	1.491738	57.4	120.0	-11.88
8	S-LAL14	OHARA	1.696797	55.5	-34.0	1.06
9	S-TIH10	OHARA	1.728250	28.5	37.0	-2.82
10	S-TIH10	OHARA	1.728250	28.5	37.0	-1.62
11	S-LAL8	OHARA	1.712995	53.9	-33.0	3.86
12	ACRYLIC	PLASTICS	1.491738	57.4	120.0	1.73

TABLE 7

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	175.6293	8.00000	490573	114.70
2	ac	49.6670	109.50360		92.80
3		-52.2360	3.40000	FCD1	38.88
4		140.9472	6.00000	FDS90	38.10
5		3357.6690	Space 1		39.12
6		183.0864	4.00000	S-LAL9	43.77
7		44.5967	13.00000	S-TIH10	45.36
8		-92.8846	0.10000		46.01
9		140.5650	10.00000	FCD1	45.93
10		-62.0392	4.20000	FD4	45.75
11		827.4523	5.99376		46.48
12		-59.2354	4.10000	FD4	46.64
13		134.9261	11.20000	S-FPL52	51.99
14		-74.3776	14.32146		54.37
15		292.2230	13.00000	S-FPL52	67.86
16		-85.7082	0.23000		69.13
17		"	10.70000	S-FPL52	69.89
18		-91.5651	0.50000		70.14
19	ac	-372.4648	8.00000	490573	68.63
20	a	-433.2704	Space 2		67.98
21		"	35.00000	BK7	60.00
22		"	1.00000		55.00
23		"	67.50000	BK7	55.00
24		"	4.00000		44.00
25		"	3.00000	ZKN7	44.00
26		"	Image distance		44.00

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-7.4000E-01
19	3.0000E+01

Even Polynomial Aspheres

Surf. No.	D	E	F	G	H	I
1	-2.5693E-07	1.6484E-10	-5.1517E-14	1.8104E-18	2.7230E-21	-4.1156E-25
2	-2.1755E-07	-1.4824E-10	4.9982E-13	-4.8115E-16	1.9448E-19	-2.8216E-23
19	-3.9107E-07	3.4985E-11	-1.1275E-13	1.8514E-16	-1.1746E-19	1.7260E-23
20	-7.8363E-09	-5.8343E-11	2.1161E-13	-2.1799E-16	1.2824E-19	-4.2405E-23

TABLE 7 (continued)**Variable Spaces**

Zoom Pos.	Space 1 T(5)	Space 2 T(20)	Focal Shift	Image Distance
1	67.439	24.780	-0.057	0.542
2	33.926	44.123	-0.103	0.524
3	7.647	72.100	-0.062	0.497

First-Order Data

f/number	3.00	3.00	3.00
Magnification	-0.0080	-0.0080	-0.0080
Object Height	-2543.0	-2500.0	-2500.0
Object Distance	-4111.0	-5555.0	-7635.4
Effective Focal Length	33.515	45.013	61.577
Image Distance	0.54203	0.52394	0.49679
Overall Length	4540.5	5970.3	8052.4
Forward Vertex Distance	429.51	415.32	416.99
Barrel Length	428.97	414.80	416.50
Stop Surface Number	5	5	5
Distance to Stop	33.72	16.96	3.82
Stop Diameter	28.303	33.263	40.609
Entrance Pupil Distance	78.111	75.072	71.970
Exit Pupil Distance	3164.9	-584.91	-370.29

First Order Properties of Elements

Element Number	Surface Numbers	Power	f
1	1 2	-0.69276E-02	-144.35
2	3 4	-0.13117E-01	-76.238
3	4 5	0.57597E-02	173.62
4	6 7	-0.11582E-01	-86.341
5	7 8	0.23207E-01	43.090
6	9 10	0.11358E-01	88.047
7	10 11	-0.13112E-01	-76.265
8	12 13	-0.18513E-01	-54.016
9	13 14	0.93511E-02	106.94
10	15 16	0.68067E-02	146.91
11	17 18	0.49801E-02	200.80
12	19 20	-0.17663E-03	-5661.6

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	-0.72433E-02	-138.06
4 5	6 8	0.12101E-01	82.638
6 7	9 11	-0.14202E-02	-704.14
8 9	12 14	-0.80103E-02	-124.84

TABLE 7 (continued)**Glass Table**

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	490573	PLASTICS	1.489972	57.3	92.0	-4.31
2	FCD1	HOYA	1.496997	81.6	120.0	-2.27
3	FDS90	HOYA	1.846664	23.8	70.0	5.18
4	S-LAL9	OHARA	1.691002	54.8	-29.0	-2.58
5	S-TIH10	OHARA	1.728250	28.5	37.0	1.29
6	FCD1	HOYA	1.496997	81.6	120.0	2.63
7	FD4	HOYA	1.755199	27.5	31.0	-2.28
8	FD4	HOYA	1.755199	27.5	31.0	-1.61
9	S-FPL52	OHARA	1.455999	90.3	140.0	3.19
10	S-FPL52	OHARA	1.455999	90.3	140.0	4.38
11	S-FPL52	OHARA	1.455999	90.3	140.0	5.99
12	490573	PLASTICS	1.489972	57.3	92.0	-168.9

TABLE 8

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	-69.1029	3.00000	ACRYLIC	26.40
2	ac	12.0133	14.95814		19.23
3		52.8059	1.50000	LAC8	14.36
4		20.8924	4.00000	FD6	13.55
5		6822.6337	10.10479		12.42
6	Aperture stop		11.17415		5.28
7		-21.0369	2.00000	LAC8	12.88
8		-48.5214	0.00000		14.65
9		69.3003	9.00000	FCD1	15.73
10		-11.6491	1.80000	NBFD10	18.13
11		-24.2392	0.50000		21.25
12		81.0635	7.00000	FCD1	24.14
13		-22.5172	0.02752		24.99
14		-161.0142	4.00000	ACRYLIC	24.65
15	a	-38.3180	1.19361		24.62
16		∞	25.40000	SF1	24.25
17		∞	25.40000	BK7	22.15
18		∞	1.35000	BK7	19.76
19		∞	0.00022		19.63

Symbol Description

a - Polynomial asphere
c - Conic section

Conics**Surface**

Number	Constant
2	-1.6440E-01

Even Polynomial Aspheres**Surf.**

No.	D	E	F	G	H	I
1	9.2240E-05	-4.1721E-07	2.5954E-10	6.5126E-12	-2.9931E-14	4.4923E-17
2	3.0646E-05	4.8714E-07	-8.0516E-09	-3.5004E-11	5.8691E-13	-1.8014E-15
15	2.3562E-05	7.3015E-09	1.0779E-10	-5.4851E-14	-4.0961E-15	1.9036E-17

First Order Data

f/number	5.00	Overall Length	1120.06
Magnification	-0.0129	Forward Vertex Distance	122.408
Object Height	-762.00	Barrel Length	122.408
Object Distance	-997.650	Entrance Pupil Distance	14.2373
Effective Focal Length	13.0189	Exit Pupil Distance	2262.27
Image Distance	0.224818E-03	Stop Diameter	5.159
Stop Surface Number	6	Distance to Stop	0.00

TABLE 8 (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f'
1	1 2	-0.48838E-01	-20.476
2	3 4	-0.20310E-01	-49.237
3	4 5	0.38788E-01	25.781
4	7 8	-0.18698E-01	-53.483
5	9 10	0.48133E-01	20.776
6	10 11	-0.34981E-01	-28.587
7	12 13	0.27649E-01	36.167
8	14 15	0.99254E-02	100.75

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f'
2 3	3 5	0.18013E-01	55.516
5 6	9 11	0.13032E-01	76.735

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	f/f_0
1	Acrylic	Plastics	1.491738	57.4	120.0	-1.57
2	LAC8	Hoya	1.713000	53.9	-40.0	-3.78
3	FD6	Hoya	1.805184	25.5	48.0	1.98
4	LAC8	Hoya	1.713000	53.9	-40.0	-4.11
5	FCD1	Hoya	1.496997	81.6	120.0	1.60
6	NBFD10	Hoya	1.834001	37.3	-18.0	-2.20
7	FCD1	Hoya	1.496997	81.6	120.0	2.78
8	Acrylic	Plastics	1.491738	57.4	120.0	7.74

TABLE 9

Surf. No.	Type	Radius	Thickness	Glass	Clear Aperture Diameter
1	a	-135.7116	4.00000	ACRYLIC	27.90
2	ac	12.4471	17.12749		19.45
3		91.5459	1.50000	S-LAL18	12.63
4		14.5117	4.00000	S-TIH14	11.70
5		372.2407	8.68741		10.63
6	Aperture stop		11.21190		5.31
7		-61.0315	7.00000	S-FPL53	13.10
8		-11.4137	1.80000	LAF7	15.62
9		-27.4207	0.50000		18.25
10		147.8397	5.50000	S-FPL53	20.31
11		-25.0976	0.50000		21.70
12		-213.9106	5.00000	S-FPL53	22.59
13		-29.2561	0.25000		23.34
14		-162.7705	4.00000	ACRYLIC	23.36
15	a	-37.7819	1.72992		23.50
16		∞	25.40000	SF1	23.05
17		∞	25.40000	BK7	20.99
18		∞	1.35000	BK7	18.67
19		∞	-0.00262		18.55

Symbol Description

- a - Polynomial asphere
c - Conic section

Conics

Surface Number

Constant

2 -1.6440E-01

Even Polynomial Aspheres

Surf.

No.	D	E	F	G	H	I
1	9.2449E-05	-4.5052E-07	5.1305E-10	6.8379E-12	-3.3826E-14	4.6808E-17
2	6.4988E-05	5.0156E-07	-1.2742E-08	1.8984E-12	1.2845E-12	-7.6365E-15
15	1.5415E-05	-2.4240E-09	1.5005E-10	-1.2277E-12	5.0941E-15	-6.9312E-18

First Order Data

f/number	5.00	Overall Length	1129.95
Magnification	-0.0121	Forward Vertex Distance	124.954
Object Height	-762.00	Barrel Length	124.957
Object Distance	-1004.99	Entrance Pupil Distance	15.5203
Effective Focal Length	12.3908	Exit Pupil Distance	-7405.44
Image Distance	-.261753E-02	Stop Diameter	5.194
Stop Surface Number	6	Distance to Stop	0.00

TABLE 9 (continued)**First Order Properties of Elements**

Element Number	Surface Numbers	Power	f
1	1 2	-0.43695E-01	-22.886
2	3 4	-0.42116E-01	-23.744
3	4 5	0.51146E-01	19.552
4	7 8	0.32680E-01	30.599
5	8 9	-0.36726E-01	-27.229
6	10 11	0.20302E-01	49.257
7	12 13	0.13086E-01	76.420
8	14 15	0.10142E-01	98.603

First-Order Properties of Doublets

Element Numbers	Surface Numbers	Power	f
2 3	3 5	0.84789E-02	117.94
4 5	7 9	-0.62549E-02	-159.87

Glass Table

Elem.	Glass	Catalog	n_d	V_d	Q	t/f_0
1	Acrylic	PLASTICS	1.491738	57.4	120.0	-1.84
2	S-LAL18	Ohara	1.729157	54.7	-32.0	-1.92
3	S-TIH14	Ohara	1.761821	26.5	54.0	1.58
4	S-FPL53	Ohara	1.438750	95.0	160.0	2.47
5	LAF7	Hoya	1.749497	35.0	-32.0	-2.20
6	S-FPL53	Ohara	1.438750	95.0	160.0	3.97
7	S-FPL53	Ohara	1.438750	95.0	160.0	6.17
8	Acrylic	PLASTICS	1.491738	57.4	120.0	7.95

TABLE 10*

Ex.	f_0	f_1	f_2	V_{U2C}	$2h'$	d	$0.1/(p' \cdot F\#_{U2})$
1A	13.48	-71.28	27.85	118.6	20.27	0.0138	71.1
1C	13.42	-72.20	29.20	114.5	20.27	0.0138	67.5
1E	13.28	-38.97	31.63	133.8	20.27	0.0138	61.7
2A	12.03	-34.14	25.34	133.0	17.91	0.0120	70.9
2B	12.02	-24.15	24.78	117.2	17.91	0.0120	72.4
3	18.31	-191.82	37.87	128.0	32.84	0.0152	104.5
4	31.43	-53.24	84.01	188.0	38.50	0.0190	75.8
5	51.35	-104.42	115.30	167.5	66.00	0.0280	105.0
7	33.52	-51.21	85.87	188.0	40.69	0.0170	93.4
8	13.02	-56.99	25.84	114.7	19.66	0.0120	82.6
9	12.39	-34.14	25.90	144.3	18.44	0.0120	73.5

* $p' = d/f_0$ where d is the pixel width in millimeters.

$F\#_{U2} = f_2/2h'$ where $2h'$ is the maximum object diagonal.

TABLE 11*

Example	Max 1/2 FOV (deg.)	Max Distortion (%)	Lateral Color at 0.7 Field (μ)	Lateral Color at 1.0 Field (μ)	Pixel Size (μ)	BFL/ f_0
1A	37.0	0.10	5.6	6.4	13.8	2.2
1B	37.0	0.25	7.3	8.7	13.8	2.4
1C	37.0	0.25	5.6	6.8	13.8	2.4
1D	37.0	0.25	4.4	9.6	13.8	2.5
1E	37.0	0.25	7.4	8.5	13.8	3.1
1F	37.0	0.25	6.8	10.0	13.8	2.5
1G	37.0	0.25	3.7	5.2	13.8	2.5
1H	37.0	0.25	7.8	11.7	13.8	2.5
2A	36.6	0.10	5.8	8.5	12.0	2.9
2B	36.6	0.10	8.1	9.6	12.0	2.9
3	41.7	0.15	6.0	6.8	15.2	2.1
4	31.4	0.10	8.8	16.3	19.0	3.5
5	32.7	1.00	11.4	17.5	28.0	1.5
6	27.8	0.15	8.3	9.5	13.8	0.9
7	31.2	0.50	8.9	15.0	17.0	3.0
8	37.0	0.10	5.8	7.0	12.0	2.6
9	36.7	0.10	5.2	6.8	12.0	2.8

*Lateral color values were determined from the chromatic blur in the image focal plane for wavelengths in the range from 460 nanometers to 620 nanometers.

Pixel size is pixel width.

What is claimed is:

1. A projection lens for forming an image of an object which consists in order from its image end to its object end of:

(A) a first lens unit U_1 having a negative power and comprising three lens elements E_P , E_N , and $E_{N'}$, arranged in any order and having focal lengths $f_{U1/P}$, $f_{U1/N}$, and $f_{U1/N'}$, V-values $V_{U1/P}$, $V_{U1/N}$, and $V_{U1/N'}$, and Q-values $Q_{U1/P}$, $Q_{U1/N}$, and $Q_{U1/N'}$, respectively;

(B) a second lens unit having a positive power; and

(C) an optional field lens unit;

wherein E_N or $E_{N'}$ is made of glass and wherein:

$$f_{U1/P} > 0,$$

$$f_{U1/N} < 0,$$

$$f_{U1/N'} < 0,$$

$$V_{U1/N} > V_{U1/P},$$

$$V_{U1/N'} > V_{U1/P},$$

$$Q_{U1/N} > 0,$$

$$Q_{U1/N} > Q_{U1/P},$$

$$Q_{U1/N} > V_{U1/N},$$

$$Q_{U1/N'} > 0, \text{ and}$$

$$Q_{U1/N'} > Q_{U1/P}.$$

2. The projection lens of Claim 1 wherein $Q_{U1/N'} > V_{U1/N'}$.

3. The projection lens of Claim 1 wherein $Q_{U1/P} < 0$.

4. A projection lens for forming an image of an object which consists in order from its image end to its object end of:

(A) a first lens unit U_1 having a negative power and comprising two lens elements E_P and E_N , arranged in any order and having focal lengths $f_{U1/P}$ and $f_{U1/N}$, V-values $V_{U1/P}$ and $V_{U1/N}$, and Q-values $Q_{U1/P}$ and $Q_{U1/N}$, respectively;

(B) a second lens unit having a positive power; and



(C) an optional field lens unit;
wherein E_N is made of glass and wherein:



$$\begin{aligned} f_{U1/P} &> 0, \\ f_{U1/N} &< 0, \\ V_{U1/N} &> V_{U1/P}, \\ Q_{U1/N} &> 0, \text{ and} \\ Q_{U1/P} &< 0. \end{aligned}$$

5. A projection lens for forming an image of an object which consists in order from its image end to its object end of:

(A) a first lens unit U_1 having a negative power and comprising two lens elements E_P and E_N , arranged in any order and having focal lengths $f_{U1/P}$ and $f_{U1/N}$, V-values $V_{U1/P}$ and $V_{U1/N}$, and Q-values $Q_{U1/P}$ and $Q_{U1/N}$, respectively;

(B) a second lens unit having a positive power; and

(C) an optional field lens unit;

wherein:

$$\begin{aligned} f_{U1/P} &> 0, \\ f_{U1/N} &< 0, \\ V_{U1/N} &> V_{U1/P}, \\ Q_{U1/N} &> V_{U1/N}, \text{ and} \\ Q_{U1/N} &> 125. \end{aligned}$$

6. A projection lens for forming an image of an object which consists in order from its image end to its object end of:

(A) a first lens unit U_1 having a negative power;

(B) a second lens unit U_2 having a positive power and comprising two lens elements E'_P and E'_N , arranged in any order and having focal lengths $f_{U2/P}$ and $f_{U2/N}$, V-values $V_{U2/P}$ and $V_{U2/N}$, and Q-values $Q_{U2/P}$ and $Q_{U2/N}$, respectively; and

(C) an optional field lens unit;

wherein:

$$f_{U2/P} > 0,$$

$$f_{U2/N} < 0,$$

$$V_{U2/P} > V_{U2/N},$$

$$Q_{U2/P} > V_{U2/P}, \text{ and}$$

$$Q_{U2/P} > 135.$$



7. A projection lens for forming an image of an object composed of pixels, said projection lens consisting in order from its image end to its object end of:

- (A) a first lens unit U_1 having a negative power;
- (B) an aperture stop or a pseudo-aperture stop;
- (C) a second lens unit U_2 having a positive power and comprising a positive lens elements having a V-value $V_{U2/P}$; and
- (D) an optional field lens unit;

wherein:

$$V_{U2/P} > 75, \text{ and}$$

$$V_{U2/C} > 0.1/(p' \cdot F\#_{U2}),$$

where $F\#_{U2}$ is the f-number of the second lens unit as traced from the object towards the image, p' is the width of a pixel divided by f_0 , where f_0 is the focal length of the combination of the first and second lens units, and $V_{U2/C}$ is a composite V-value for the second lens unit given by:

$$V_{U2/C} = f_{U2} \{ \sum (V_{U2/i} / f_{U2/i}) \}$$

where f_{U2} is the focal length of the second lens unit, $f_{U2/i}$ and $V_{U2/i}$ are the focal length and V-value of the i^{th} lens element of the second lens unit, and the summation is over all lens elements of the second lens unit.

8. A projection lens for forming an image of an object composed of pixels, said projection lens consisting in order from its image end to its object end of:

- (A) a first lens unit having a negative power and comprising means for correcting the secondary lateral color of the projection lens, said means comprising two lens elements E_P and E_N , arranged in any order and having focal lengths $f_{U1/P}$ and $f_{U1/N}$, V-values $V_{U1/P}$ and $V_{U1/N}$, and Q-values $Q_{U1/P}$ and $Q_{U1/N}$, respectively;

- (B) a second lens unit having a positive power; and
- (C) an optional field lens unit;

wherein:

$$\begin{aligned} f_{U1/P} &> 0, \\ f_{U1/N} &< 0, \\ V_{U1/N} &> V_{U1/P}, \\ Q_{U1/N} &> 0, \text{ and} \\ Q_{U1/P} &< 0. \end{aligned}$$



9. The projection lens of Claim 1, 4, 5, 6, 7, or 8 wherein:

$$BFL/f_0 > 0.7,$$

where f_0 and BFL are the focal length and the back focal length, respectively, of the combination of the first and second lens units.

10. The projection lens of Claim 1, 4, 5, 6, or 8 wherein the projection lens has an aperture stop or a pseudo-aperture stop and the first lens unit is on the image side of said aperture stop or pseudo-aperture stop and the second lens unit is on the object side of said aperture stop or pseudo-aperture stop.

11. The projection lens of Claim 1 wherein the projection lens has an aperture stop or a pseudo-aperture stop and E_P , E_N , and E'_N are on the image side of said aperture stop or pseudo-aperture stop.

12. The projection lens of Claim 4 or 5 wherein the projection lens has an aperture stop or a pseudo-aperture stop and E_P and E_N are on the image side of said aperture stop or pseudo-aperture stop.

13. The projection lens of Claim 6 wherein the projection lens has an aperture stop or a pseudo-aperture stop and E'_P and E'_N are on the object side of said aperture stop or pseudo-aperture stop.

14. The projection lens of Claim 1, 4, 5, 6, 7, or 8 wherein the projection lens is telecentric in the direction of the object.

15. The projection lens of Claim 1, 4, 5, 6, 7, or 8 wherein the first lens unit comprises an aspherical surface.

16. The projection lens of Claim 1, 4, 5, 6, 7, or 8 wherein the second lens unit comprises an aspherical surface.

17. The projection lens of Claim 1, 4, 5, 6, 7, or 8 wherein the lens is a zoom lens.

18. The projection lens of Claim 1, 4, 5, or 8 wherein the second lens unit comprises two lens elements E'_P and E'_N , arranged in any order and having focal lengths f_{U2P} and f_{U2N} , V-values V_{U2P} and V_{U2N} , and Q-values Q_{U2P} and Q_{U2N} , respectively, where:

$$f_{U2P} > 0,$$

$$f_{U2N} < 0,$$

$$V_{U2P} > V_{U2N},$$

$$Q_{U2P} > 0,$$

$$Q_{U2P} > Q_{U2N}, \text{ and}$$

$$Q_{U2P} > V_{U2P}.$$



19. The projection lens of Claim 18 wherein:

$$Q_{U2P} > 135.$$

20. The projection lens of Claim 18 wherein:

$$Q_{U2N} < 0.$$

21. A projection lens system for forming an image of an object, said system comprising:

(a) an illumination system comprising a light source and illumination optics which forms an image of the light source, said image of the light source being the output of the illumination system;

(b) a pixelized panel which comprises the object; and

(c) the projection lens of Claim 1, 4, 5, 6, 7, or 8.

22. The projection lens system of Claim 21 wherein said projection lens has an entrance pupil whose location substantially corresponds to the location of the output of the illumination system.

23. The projection lens system of Claim 21 wherein the projection lens is a zoom lens.

24. The projection lens of Claims 1, 4, 5, or 8 wherein E_P and E_N or E_N' form a color correcting doublet.

25. A projection lens for forming an image of an object composed of pixels, said projection lens consisting in order from its image end to its object end of:

- (A) a first lens unit having a negative power;
- (B) a second lens unit having a positive power; and
- (C) an optional field lens unit;



wherein:

- (i) the projection lens has a half field of view in the direction of the image of at least 20° ;
 - (ii) the lateral color blur of the projection lens at its full field is less than a pixel for wavelengths in the range from 460 nanometers to 620 nanometers;
 - (iii) the distortion of the projection lens is less than 1.5 percent;
 - (iv) the projection lens is telecentric in the direction of the object;
- and
- (v) the projection lens is a zoom lens.

26. The projection lens of Claim 25 wherein:

$$BFL/f_0 > 0.7,$$

where f_0 and BFL are the focal length and the back focal length, respectively, of the combination of the first and second lens units.

27. The projection lens of Claim 25 wherein the projection lens has an aperture stop or a pseudo-aperture stop and the first lens unit is on the image side of said aperture stop or pseudo-aperture stop and the second lens unit is on the object side of said aperture stop or pseudo-aperture stop.

28. The projection lens of Claim 25 wherein the first lens unit comprises an aspherical surface.

29. The projection lens of Claim 25 wherein the second lens unit comprises an aspherical surface.

This Sheet Has Been Replaced



30. A projection lens system for forming an image of an object, said system comprising:

- (a) an illumination system comprising a light source and illumination optics which forms an image of the light source, said image of the light source being the output of the illumination system;
- (b) a pixelized panel which comprises the object; and
- (c) the projection lens of Claim 25.

31. The projection lens system of Claim 30 wherein said projection lens has an entrance pupil whose location substantially corresponds to the location of the output of the illumination system.



This Sheet Has Been Replaced

