

Wireless Communication Method, Network Device, and Terminal Device

The present application claims the priority of PCT patent application No. PCT/CN2018/076013 filed to China Patent Office on February 9, 2018, entitled "Wireless
5 Communication Method, Network Device and Terminal device", the priority of PCT patent application No. PCT/CN2018/078330 filed to China Patent Office on March 7, 2018, entitled "Wireless Communication Method, Network Device and Terminal device", and the priority of PCT patent application No. PCT/CN2018/079203 filed to China Patent Office on March 15, 2018, entitled "Wireless Communication Method, Network Device and Terminal device", the
10 above-identified applications are incorporated by reference herein in their entirety.

Technical Field

Embodiments of the present invention relate to the communication field, and more particularly, to a wireless communication method, a network device and a terminal device.

15

Background

In the prior art, since a Policy Section Identifier (PSI) parameter of User Equipment (UE) in a plaintext is added into an Initial registration message to be sent to a Policy Control Function (PCF), it is easy to be intercepted by other users, causing potential safety hazards.

20

For example, UE-2 acquires the PSI parameter of UE-1 through the Registration Request of UE-1 (because the Registration Request is sent in a plaintext), then UE-2 may initiate a registration request carrying the PSI parameter of UE-1, and the network device will send the UE Policy of UE-1 to UE-2, causing potential safety hazards and privacy leaks.

25

Summary

A wireless communication method, a network device and a terminal device are provided, PSI parameters can be updated timely/correctly, and then potential safety hazards can be eliminated.

In a first aspect, a wireless communication method is provided. The method includes: determining, by a first network device, whether to update policy information of a terminal device after acquiring a Policy Section Identifier (PSI) parameter of the terminal device, wherein the PSI parameter is used for identifying a part of policy information for the terminal
5 device under a subscribed user.

In an embodiment of the present invention, after acquiring the PSI parameter of the terminal device, the first network device directly determines whether to update the policy information of the terminal device, so that the PSI parameter can be updated timely/correctly, and then potential safety hazards can be eliminated.

10 In some possible implementation modes, the PSI parameter includes a subscriber identifier.

Determining whether to update the policy of the terminal device includes: receiving, by the first network device, a subscriber identifier sent by a second network device; and determining, by the first network device, whether to update the policy of the terminal device according to the
15 subscriber identifier corresponding to the PSI parameter and the subscriber identifier sent by the second network device.

In some possible implementation modes, determining, by the first network device, whether to update the policy of the terminal device according to the subscriber identifier corresponding to the PSI parameter and the subscriber identifier sent by the second network device, includes:
20 determining, by the first network device, to update the policy information of the terminal device when determining that the subscriber identifier corresponding to the PSI parameter is different from the subscriber identifier sent by the second network device.

In some possible implementation modes, determining to update the policy information of the terminal device includes: sending, by the first network device, policy information
25 corresponding to a subscriber identifier of the terminal device currently used to the terminal device.

In some possible implementation modes, determining to update the policy information of the terminal device includes: sending, by the first network device, policy information corresponding to the subscriber identifier sent by the second network device to the terminal

device.

In some possible implementation modes, the subscriber identifier includes a Subscriber Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

5 In an embodiment of the present invention, global uniqueness of the PSI parameter is uniquely identified by the subscriber identifier (e.g., SUPI and/or SUCI) in the PSI parameter, so that the network device can timely/correctly update the policy information of the terminal device. In addition, with this solution, the PSI parameter is used for identifying uniquely a part of the policy information for the terminal device under the subscribed user, and a quantity of Bits of the PSI parameter is relatively small, therefore there only needs to distinguish (dozens of)
10 different PSI parameters under one subscribed user. Finally, with this solution, the first network device can timely/correctly determine whether the terminal device needs to update the policy information by comparing the subscriber identifier carried in the PSI parameter of the terminal device with the subscriber identifier acquired from the second network device.

In some possible implementation modes, the PSI parameter includes a Public Land Mobile
15 Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely identifying a PSI parameter under the PLMN.

In some possible implementation modes, the PSI parameter includes a timestamp and/or a version identifier.

Determining whether to update a policy of the terminal device includes: acquiring, by the
20 first network device, a last update time of the policy information of the terminal device according to the timestamp and/or the version identifier in the PSI parameter, and determining whether to update the policy information of the terminal device according to an update time threshold and/or a latest version.

In an embodiment of the present invention, the PSI parameter is uniquely identified by the
25 PLMN identifier and first identifier. In this case, a quantity of bits of the first identifier will be very large (hundreds of millions), and multiple PSI parameters may be carried under one SUPI, which has a great influence on the network side. However, for users, the security is higher. In addition, in an embodiment of the present invention, a last update time of the policy information of the terminal device is acquired through the timestamp and/or version identifier

in the PSI parameter, and then whether to update the policy information of the terminal device is determined according to an update time threshold and/or a latest version, so that whether the terminal device needs to update the policy information can be timely/correctly determined.

5 In some possible implementation modes, the method further includes: updating, by the first network device, the policy information of the terminal device when determining to update a policy of the terminal device.

In some possible implementation modes, updating the policy information of the terminal device includes: updating periodically, by the first network device, the policy information of the terminal device.

10 In some possible implementation modes, updating the policy information of the terminal device includes: sending/updating, by the first network device, part of the policy information to the terminal device according to capability information of the terminal device.

15 In some possible implementation modes, the capability information includes at least one of the following: a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

20 In some possible implementation modes, before the first network device updates the policy information of the terminal device according to the capability information of the terminal device, the method further includes: acquiring, by the first network device, the capability information of the terminal device.

25 In some possible implementation modes, updating the policy information of the terminal device includes: sending, by the first network device, all policy information to the terminal device to enable the terminal device to select part of the policy information to use from the all policy information according to a capability of the terminal device.

In some possible implementation modes, the first network device is a Policy Control Function (PCF).

In some possible implementation modes, the second network device is an Access and Mobility Management Function (AMF).

In a second aspect, a wireless communication method is provided. The method includes:
determining, by a terminal device, a Policy Section Identifier (PSI) parameter which is used for
5 identifying a part of policy information for the terminal device under a subscribed user; and
sending, by the terminal device, the PSI parameter to a first network device.

In some possible implementation modes, the PSI parameter includes a subscriber identifier.

In some possible implementation modes, the method further includes: receiving, by the
10 terminal device, policy information corresponding to a subscriber identifier of the terminal
device currently used, which is sent by the first network device.

In some possible implementation modes, receiving, by the terminal device, the policy
information corresponding to the subscriber identifier of the terminal device currently used,
which is sent by the first network device, includes: receiving, by the terminal device, the policy
15 information corresponding to a subscriber identifier sent by a second network device.

In some possible implementation modes, the subscriber identifier includes a Subscriber
Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

In some possible implementation modes, the PSI parameter includes a Public Land Mobile
Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely
20 identifying a PSI parameter under the PLMN.

In some possible implementation modes, the method further includes: receiving, by the
terminal device, the policy information of the terminal device sent by the first network device.

In some possible implementation modes, receiving, by the terminal device, the policy
information of the terminal device sent by the first network device includes: receiving
25 periodically, by the terminal device, the policy information of the terminal device sent by the
first network device.

In some possible implementation modes, the policy information of the terminal device sent
by the first network device is the policy information of the terminal device determined by the

first network device according to capability information of the terminal device.

In some possible implementation modes, the capability information includes at least one of the following: a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device,
 5 Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

In some possible implementation modes, before the terminal device receives the policy
 10 information of the terminal device sent by the first network device, the method further includes: sending, by the terminal device, the capability information of the terminal device to the first network device.

In some possible implementation modes, receiving, by the terminal device, the policy information of the terminal device sent by the first network device includes: receiving, by the
 15 terminal device, all policy information of the terminal device sent by the first network device; and the method further includes: selecting, by the terminal device, part of the policy information to use from the all policy information according to a capability of the terminal device.

In some possible implementation modes, the first network device is a Policy Control
 20 Function (PCF).

In some possible implementation modes, the second network device is an Access and Mobility Management Function (AMF).

In a third aspect, a network device is provided. The network device includes a processing unit, used for determining whether to update policy information of a terminal device after
 25 acquiring a Policy Section Identifier (PSI) parameter of the terminal device, wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user.

In a fourth aspect, there is provided a network device including: a processor, used for determining whether to update policy information of a terminal device after acquiring a Policy

Section Identifier (PSI) parameter of the terminal device, wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user.

In a fifth aspect, there is provided a terminal device including: a determining unit, used for determining a Policy Section Identifier (PSI) parameter which is used for identifying a part of
5 policy information for the terminal device under a subscribed user; and a transceiving unit, used for sending the PSI parameter to a first network device.

In a sixth aspect, there is provided a terminal device including: a determiner, used for determining a Policy Section Identifier (PSI) parameter which is used for identifying a part of policy information for the terminal device under a subscribed user; and a transceiver, used for
10 sending the PSI parameter to a first network device.

In a seventh aspect, a wireless communication method is provided. The method includes: determining, by a first network device, that in a registration request message, a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null, wherein the PSI parameter is used for identifying a part of policy information for a terminal device under a subscribed user;
15 and sending, by the first network device, policy information to the terminal device.

In an eighth aspect, a wireless communication method is provided. The method includes: sending, by a terminal device, a registration request message to a network device, wherein a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null in the registration request message, wherein the PSI parameter is used for identifying a part of policy
20 information for the terminal device under a subscribed user; and receiving, by the terminal device, policy information sent by a first network device.

In a ninth aspect, there is provided a network device including: a processing unit, used for determining that in a registration request message, a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null, wherein the PSI parameter is used for identifying a part
25 of policy information for a terminal device under a subscribed user; and a transceiving unit, used for sending policy information to the terminal device.

In a tenth aspect, there is provided a terminal device including: a transceiving unit, used for sending a registration request message to a network device, wherein a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null in the registration request

message, wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user; wherein the transceiving unit is further used for receiving policy information sent by a first network device.

5 In an eleventh aspect, a computer readable medium is provided for storing a computer program. The computer program includes instructions for executing the method embodiments of the above first aspect, the second aspect, the seventh aspect and the eighth aspect.

10 In a twelfth aspect, there is provided a computer chip, including an input interface, an output interface, at least one processor, and a memory, wherein the processor is used for executing codes in the memory, and when the codes are executed, the processor may implement various processes executed by the first network device in the method embodiments of the above-mentioned first aspect, second aspect, seventh aspect, eighth aspect, and various implementation modes.

15 In a thirteenth aspect, there is provided a computer chip, including an input interface, an output interface, at least one processor, and a memory, wherein the processor is used for executing codes in the memory, and when the codes are executed, the processor may implement various processes executed by the terminal device in the method embodiments of the above-mentioned first aspect, second aspect, seventh aspect, eighth aspect, and various implementation modes.

20 In a fourteenth aspect, there is provided a communication system including the aforementioned first network device and terminal device.

Brief Description of Drawings

FIG. 1 is an example of an application scenario of the present invention.

25 FIG. 2 is a schematic block diagram of a wireless communication method according to an embodiment of the present invention.

FIG. 3 is another schematic block diagram of a wireless communication method according to an embodiment of the present invention.

FIG. 4 is a schematic diagram of a mapping relationship between policy information and

subscribers stored in a terminal device at a network side according to an embodiment of the present invention.

FIG. 5 is a schematic diagram of another mapping relationship between policy information and subscribers stored in a terminal device at a network side according to an embodiment of the present invention.

FIG. 6 is a schematic block diagram of a network device according to an embodiment of the present invention.

FIG. 7 is a schematic diagram of another network device according to an embodiment of the present invention.

FIG. 8 is a schematic block diagram of a terminal device according to an embodiment of the present invention.

FIG. 9 is a schematic block diagram of another terminal device according to an embodiment of the present invention.

Detailed Description

Technical solutions in embodiments of the present application will be clearly and completely described below with reference to the drawings in the embodiments of the present application.

It should be understood that the technical solutions of the embodiments of the present application may be applied to various communication systems, such as, a Global System of Mobile communication (GSM), a Code Division Multiple Access (CDMA) system, a Wideband Code Division Multiple Access (WCDMA) system, a General Packet Radio Service (GPRS) system, a Long Term Evolution (LTE) system, an LTE Time Division Duplex (TDD) system, a Universal Mobile Telecommunication System (UMTS), a Worldwide Interoperability for Microwave Access (WiMAX) communication system, a New Radio (NR) System or a future 5G system, etc.

In particular, the technical solutions of the embodiments of the present application can be applied to various communication systems based on non-orthogonal multiple access

technologies, such as a Sparse Code Multiple Access (SCMA) system, and a Low Density Signature (LDS) system, etc. Of course, the SCMA system and the LDS system may also be referred to as other names in the communication field. Further, the technical solutions of the embodiments of the present application can be applied to a multicarrier transmission system
5 employing non-orthogonal multiple access technology, such as an Orthogonal Frequency Division Multiplexing (OFDM) system based on the non-orthogonal multiple access technology, a Filter Bank Multi-Carrier (FBMC) system, a Generalized Frequency Division Multiplexing (GFDM) system, and a Filtered OFDM (F-OFDM) system, etc.

FIG. 1 shows a wireless communication system 100 to which an embodiment of the
10 present application is applied. The wireless communication system 100 may include an access network device 110. The access network device 110 may be a device that communicates with a terminal device. The access network device 110 may provide communication coverage for a specific geographic area and may communicate with a terminal device (e.g., UE) located within the coverage area. Optionally, the access network device 110 may be a base station (gNB) in a
15 Next Generation Radio Access Network (NG RAN) or an NR system, or a radio controller in a Cloud Radio Access Network (CRAN), or the access network device may be a relay station, an access point, an on-board device, a wearable device, or a network device in a future evolved Public Land Mobile Network (PLMN), etc. Optionally, the access network device 110 may further be a base station in an LTE system, for example, an evolved Universal Terrestrial Radio
20 Access Network (E-UTRAN) device.

The wireless communication system 100 also includes at least one terminal device 120 located within the coverage area of the access network device 110. The terminal device 120 may be mobile or fixed. Optionally, the terminal device 120 may be referred to as an access
25 terminal, a User Equipment (UE), a subscriber unit, a subscriber station, a mobile station, a remote station, a remote terminal, a mobile device, a user terminal, a terminal, a wireless communication device, a user agent, or a user apparatus. The access terminal may be a cellular phone, a cordless phone, a Session Initiation Protocol (SIP) phone, a Wireless Local Loop (WLL) station, a Personal Digital Assistant (PDA), a handheld device with a wireless communication function, a computing device, or other processing device connected to a

wireless modem, a vehicle-mounted device, a wearable device, a terminal device in a future 5G network, or a terminal device in a future evolved Public Land Mobile Network (PLMN), or the like.

In an embodiment of the present invention, the wireless communication system 100 further
5 includes a core network device 130 that communicates with the access network device. Optionally, the core network device 130 may be a 5G core network device, for example, an Access and Mobility Management Function (AMF), for another example, a Session Management Function (SMF). Optionally, the core network device 130 may also be an Evolved Packet Core (EPC) device of the LTE network, for example, a Session Management Function +
10 Core Packet Gateway (SMF+PGW-C) device.

It should be understood that SMF+PGW-C may realize the functions which can be realized by the SMF and the PGW-C at the same time.

Optionally, in an embodiment of the present application, the AMF may perform information interaction with the SMF, for example, the SMF acquires information of the radio
15 access network side from the AMF.

Alternatively, in an embodiment of the present application, the AMF may acquire a fallback identification from the radio access network, or acquire a message indicating that the bearer/flow is not successfully established for the terminal device.

FIG. 1 exemplifies one access network device, one core network device and two terminal
20 devices. Optionally, the wireless communication system 100 may include multiple access network devices, and another quantity of terminal devices may be included within the coverage area of each access network device, which is not restricted in embodiments of the present application. Optionally, the wireless communication system 100 may further include a Mobile Management Entity (MME), a Unified Data Management (UDM), an Authentication Server
25 Function (AUSF), a User Plane Function (UPF), a Signaling Gateway (SGW) or other network entities, which is not restricted in embodiments of the present application. It should be understood that the terms "system" and "network" are often used interchangeably in this document. The term "and/or" in this document is merely an association relationship describing associated objects, indicating that there may be three relationships, for example, A and/or B

may indicate three cases: A alone, A and B, and B alone. In addition, the symbol "/" in this document generally indicates that objects before and after the symbol "/" have an "or" relationship.

In addition, the terminal device shown in FIG. 1 may establish and/or bind a Protocol Data Unit (PDU) session according to a route selection descriptor table corresponding to a first rule in a UE Route Selection Policy (URSP). The route selection descriptor table includes at least one group of index combinations. Each group of index combinations in the at least one group of index combinations includes at least one index. Each group of index combinations is used for indicating a group of parameter combinations. The parameter combination includes a value of each of at least one parameter for establishing and/or binding a PDU session. The at least one index corresponds to the at least one parameter in a one-to-one way, and the each parameter includes at least one value.

Therefore, URSP is introduced in an embodiment of the present invention, and the URSP policy is a policy for selecting different Protocol Data Unit (PDU) Sessions. The URSP policy specifies a routing policy of UE for different data flow filters. For UE, there is only one URSP, and there may be multiple rules in the URSP, and the rules in the URSP may include, but not limited to, Traffic descriptors, Application identifiers, Internet Protocol (IP) descriptors, non-IP descriptors and Route Selection descriptor (RSD). Each rule may further have a different priority value. The RSD table includes, but not limited to, a value of at least one parameter for establishing and/or binding Protocol Data Unit (PDU) sessions, such as, a session and service continuity mode, Network Slice Selection Assistance Information (NSSAI), a Data Network Name (DNN), a non-seamless traffic offloading indicator, a radio access type. Each parameter may include at least one value. The parameter combination in an embodiment of the present application may refer to a combination of values of various parameters, for example, a parameter combination of a session and service continuity mode 1, NSSAI_1, a DNN_1, a non-seamless traffic offloading indicator as allowance, and a radio access type of the 3rd Generation Partnership Project (3GPP), and another parameter combination of a Session and service Continuity Mode 1, NSSAI_2, a DNN_3, a Non-Seamless traffic offloading indicator of Allowance, and a radio access type of the 3rd Generation Partnership Project (3GPP). In an

embodiment of the present application, all values of each parameter may be represented by indexes firstly. For example, the session and service continuity mode has three values, the session and service continuity mode 1 is represented by index 1, the session and service continuity mode 2 is represented by index 2, and the session and service continuity mode 3 is represented by index 3. Then an index combination may be used for indicating a parameter combination. For example, the index combination is [2; 1; 2; 1; 1], assuming that the parameters represented by indexes in the index combination from left to right are a session and service continuity mode, NSSAI, a DNN, a non-seamless traffic offloading indicator and a radio access type, respectively. Then the index combination [2; 1; 2; 1; 1] represents a parameter combination of a Session and service Continuity Mode 2, NSSAI_1, a DNN_2, a non-seamless traffic offloading indicator of allowance, and a radio access type of 3GPP. In an embodiment of the present application, at least one index combination may be added to the RSD table, and the terminal device may establish and/or bind a PDU session according to parameter values in a parameter combination indicated by the at least one index combination.

FIGs. 2 and 3 show schematic block diagrams of wireless communication methods according to embodiments of the present application. The terminal devices shown in FIGs. 2 and 3 may be the terminal device shown in FIG. 1. The method shown in FIG. 2 includes some or all of the following.

In 201, a terminal device registers a request to a (Radio) Access Network ((R)AN), including a PSI parameter.

In 202, the (Radio) Access Network ((R)AN) performs Access and Mobility Management Function (AMF) selection.

In 203, the (R)AN sends a registration request to a second AMF, including a PSI parameter.

In 204, a first AMF sends a UE context to the second AMF.

In 205, the second AMF sends a UE context response to the first AMF.

In 206, the first AMF sends an identity verification request to the terminal device.

In 207, the terminal device sends an identity verification response to the first AMF.

In 208, the first AMF performs Authentication Server Function (AUSF) selection.

In 209, an authentication/security operation is performed between the terminal device and the first AMF.

In 210, the first AMF sends a registration complete notification to the second AMF.

5 In 211, the first AMF performs an identity verification request/response operation with the terminal device and the AUSF respectively, and the AUSF performs an identity verification request/response operation with the Unified Data Management (UDM).

In 212, an identity verification request/response operation is performed between the Equipment Identity Register (EIR) and the first AMF.

10 In 213, the first AMF performs UDM selection.

In 214a, the first AMF sends a registration message to the UDM.

In 214b, the UDM sends an access message to the first AMF.

In 214c, the first AMF sends a subscription message to the UDM.

In 214d, the UDM sends a registration notification message to the second AMF.

15 In 214e, the second AMF sends a subscription to the UDM.

In 215, the first AMF performs a Policy Control Function (PCF) selection.

In 216, the first AMF and the PCF establish a policy during the registration process, including a PSI parameter.

In 217, the first AMF and the PCF perform a subscription event operation.

20 In 218, the first AMF sends an update/release PDU session to a Session Management Function (SMF).

In 219, the first AMF sends an AMF mobility request to a non-3GPP interworking function N3 (N3IWF).

In 220, the N3IWF sends an AMF mobility response for the request to the first AMF.

25 In 221, the first AMF sends a Registration Accept to the terminal device.

In 221, the terminal device sends a first Registration Complete to the first AMF.

As shown in FIG. 2, since the Policy Section Identifier (PSI) list of the User Equipment (UE) in a plaintext is added into an initial registration message to be sent to the Policy Control Function (PCF), i.e., acts 201, 203 and 216, it is easy to be intercepted by other users, causing potential safety hazards.

5 For example, UE-2 acquires the PSI parameter of UE-1 through the Registration Request of UE-1 (because the Registration Request is sent in a plaintext), then UE-2 may initiate a registration request carrying the PSI parameter of UE-1, and the network device will send the UE Policy of UE-1 to UE-2, causing potential security risk and privacy leak. For another
10 example, assuming that the content of the UE Policy is falsified or partially lost, but the UE always reports the same PSI parameter to the network side, then the network side does not send a new UE Policy, thus the content of the UE Policy is falsified or partially lost.

To solve the above technical problems, a wireless communication method is provided in an embodiment of the present invention.

15 FIG. 3 is a schematic block diagram of another wireless communication method according to an embodiment of the present invention.

Specifically, as shown in FIG. 3, the method 300 includes the following acts 310-320.

In 310, a first network device acquires a Policy Section Identifier (PSI) parameter of a terminal device.

20 In 320, the first network device determines whether to update policy information of the terminal device.

Specifically, the first network device determines whether to update policy information of a terminal device after acquiring the Policy Section Identifier (PSI) parameter of the terminal device. If determining to update the policy information of the terminal device, the first network device updates the policy information of the terminal device. It should be understood that
25 measurement information in an embodiment of the present invention may include, but not limited to, a first policy, a UE Route Selection Policy (URSP) policy, and a Wireless Local Area Network Selection Policy (WLANS). Herein, the first policy may be a policy for selecting a Service Set Identifier (SSID) for wireless local area network (WLAN) access, and the URSP policy is a policy for selecting different Protocol Data Unit (PDU) Sessions. In an

embodiment of the present invention, a Policy Section Identifier (PSI) list is introduced to flexibly divide the UE policy. For the use of PSI parameter, it may be understood that the terminal device adds the PSI parameter saved by the terminal device into a request message for Initial registration to send to the PCF, so that the PCF can acquire what the PSI parameter
5 currently stored by the terminal device is like, for the PCF to adjust the UE Policy as needed.

Below an implementation mode in which the first network device determines whether to update the policy information of the terminal device in an embodiment of the present invention will be described.

In an embodiment, the PSI parameter includes a subscriber identifier. In this case, the first
10 network device receives a subscriber identifier sent by a second network device; and the first network device determines whether to update a policy of the terminal device according to the subscriber identifier corresponding to the PSI parameter and the subscriber identifier sent by the second network device. In a specific embodiment, the first network device determines to update the policy information of the terminal device when determining that the subscriber identifier
15 corresponding to the PSI parameter is different from the subscriber identifier sent by the second network device. Specifically, when the first network device determines that the subscriber identifier corresponding to the PSI parameter is different from the subscriber identifier sent by the second network device, the first network device sends policy information corresponding to the subscriber identifier of the terminal device currently used to the terminal device. More
20 specifically, when the first network device determines that the subscriber identifier corresponding to the PSI parameter is different from the subscriber identifier sent by the second network device, the first network device sends policy information corresponding to the subscriber identifier sent by the second network device to the terminal device.

Herein, the subscriber identifier includes a Subscriber Private Identifier (SUPI) and/or a
25 Subscriber Concealed Identifier (SUCI). In other alternative embodiments, the subscriber identifier may be an International Mobile Subscriber Identification Number (IMSI) assigned to the UE by a service provider (SP). The IMSI is a sign for distinguishing mobile subscribers, is stored in a Subscriber Identification Module (SIM) card, and may be used for distinguishing valid information of mobile subscribers. The subscriber identifier may be a Temporary Mobile

Subscriber Identity (S-TMSI) or an International Mobile Equipment Identity (IMEI) or the like.

In an embodiment of the present invention, global uniqueness of the PSI parameter is uniquely identified by the subscriber identifier (e.g., SUPI and/or SUCI) in the PSI parameter, so that the network device can timely/correctly update the policy information of the terminal
5 device. In addition, with this solution, the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user, and a quantity of its Bits is relatively small, therefore there only needs to distinguish (dozens of) different PSI parameters under one subscribed user. Finally, with this solution, the first network device can timely/correctly determine whether the terminal device needs to update the policy information
10 by comparing the subscriber identifier carried in the PSI parameter of the terminal device with the subscriber identifier acquired from the second network device.

It should be understood that the first network device involved in an embodiment of the present invention may be PCF or a core network device, and the second network device may be AMF or a core network device, which is not specifically restricted in embodiments of the
15 present invention.

In an embodiment of the present invention, the PSI parameter including a subscriber identifier is taken as an example, and embodiments of the present invention are not limited thereto. For example, in other embodiments, the PSI parameter includes a Public Land Mobile Network (PLMN) identifier and a first identifier, the first identifier is used for uniquely
20 identifying a PSI parameter under a PLMN. In this case, in a realizable embodiment, the PSI parameter may further include a timestamp and/or a version identifier. Therefore, the first network device may acquire a last update time of the policy information of the terminal device according to the timestamp and/or the version identifier in the PSI parameter, and determine whether to update the policy information of the terminal device according to an update time
25 threshold and/or a latest version. For example, China Mobile's PLMN is 46000, and China Unicom's PLMN is 46001.

In an embodiment of the present invention, the PSI parameter is uniquely identified by the PLMN identifier and first identifier. In this case, a quantity of bits of the first identifier will be very large (hundreds of millions), and multiple PSI parameters may be carried under one SUPI,

which has a great influence on the network side. However, for users, the security is higher. In addition, in an embodiment of the present invention, a last update time of the policy information of the terminal device is acquired through the timestamp and/or version identifier in the PSI parameter, and then whether to update the policy information of the terminal device is determined according to a update time threshold and/or a latest version, so that whether the terminal device needs to update the policy information can be timely/correctly determined.

Furthermore, an embodiment of the present invention further provides a way to update the policy information of the terminal device. Specifically, the first network device updates the policy information of the terminal device when determining to update a policy of the terminal device. In an embodiment, the first network device may periodically update the policy information of the terminal device. In another embodiment, the first network device may aperiodically update the policy information of the terminal device. Further, when the first network device determines to update a policy of the terminal device, an embodiment of the present invention further provides an implementation mode for updating the policy information.

For example, when the first network device determines to update the policy of the terminal device, the first network device may send all policy information to the terminal device, so that the terminal device selects part of the policy information to use from the all policy information according to a capability of the terminal device. However, due to different capabilities of the terminal device, the capabilities supported by different terminals are different, and policy information needed will be different. At present, all rules subscribed by the users are sent to the terminal device without distinguishing the capabilities of the terminal device, which will cause excessive signaling load and additional terminal burden. In an embodiment of the present invention, the first network device may send/update part of policy information to the terminal device according to the capability information of the terminal device. Herein, the capability information includes at least one of the following information: a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter

indicating a PDU session characteristic is supported. For example, a parameter for mapping an upper layer request message of 3GPP for session establishment/modification may be a DNN parameter. Further, before the first network device updates the policy information of the terminal device according to the capability information of the terminal device, the first network device acquires the capability information of the terminal device.

It should be understood that the policy information (UE Policy) in an embodiment of the present application may include multiple parameters.

The policy information of an embodiment of the present application will be exemplarily explained below with reference to Table 1.

Table 1 UE route selection policy rule

Parameter name	Description	Level
Rule priority	Determine an order by which URSP rules are executed	Required
Traffic descriptor	Describe characteristics of the traffic	
Application descriptor	Include an application identifier recognizable by a terminal operating system, the application identifier uniquely refers to a certain application	Optional
IP descriptor	IP triple or IPv6 prefix, port number, protocol identifier, etc.	Optional
Non-IP descriptor	Describe characteristics of non-IP packets	Optional
DNN	DNN is provided by an application layer	Optional
Connectivity capability	The capability parameter is provided by an application layer and used for requesting to run data on a connection supporting the capability	Optional
Route selection descriptor	Route selection descriptor list, see table 2 for its specific content	Required

Table 2 Route selection descriptor

Parameter name	Description	Level
Route selection descriptor priority	Determine an order by which route selection descriptors are used	Required
Route selection parameter	Define a sum of route selection parameters	Optional
Service and continuity mode selection	Contain one value	Optional

Network slice selection	Contain one or more values	Optional
DNN selection	Contain one or more DNNs	Optional
PDU session type selection	Contain one type value	Optional
Non-seamless traffic offloading indicator	Indicate whether specific traffic needs to be offloaded to non-3GPP access	Optional
Access type selection	Only data traffic running on PDU sessions corresponding to 3GPP or non-3GPP access	Optional

As shown in table 1, UE Policy may include a UE route selection policy rule which may include a route selection descriptor. Further, as shown in FIG. 2, the route selection descriptor may include multiple parameters, for example, a route selection descriptor priority, a route selection parameter service and a continuity mode selection, etc.

In an embodiment of the present application, when the terminal device receives all policy information sent by the first network device, the terminal device may select part of the policy information to use from the all policy information according to a capability of the terminal device. Further, the terminal device may perform a first behavior or a second behavior on the policy information according to the capability of the terminal device.

The first behavior refers to that after the terminal device selects a first rule of a first priority, if the terminal device does not support a first parameter in the first rule, the terminal device does not select the first rule but selects a second rule of a second priority.

For example, if the terminal device does not support a connection capability parameter in the first rule, the first rule of the first priority is abandoned and the second rule of the second priority is selected.

For another example, if the terminal device does not support the access type selection parameter in the route selection descriptor of the first priority, the route selection descriptor of the first priority is not selected, and the route selection descriptor of the second priority is selected. Optionally, the route restriction descriptor of the first priority and the route restriction descriptor of the second priority belong to the same UE route selection policy rule.

The second behavior refers to that after the terminal device selects the first rule of the first priority, if the terminal device does not support the first parameter in the first rule, the terminal

device does not select the first parameter, and parameters other than the first parameter in the first rule remain valid.

For example, if the terminal device does not support the connection capability parameter in the first rule, the connection capability parameter in the first rule is abandoned and other parameters in the first rule remain valid.

For another example, if the terminal device does not support the access type selection parameter in the route selection descriptor of the first priority, the access type selection parameter in the route selection descriptor of the first priority is not selected, and other parameters in the route selection descriptor of the first priority remain valid.

It should be noted that since UE capability may not support all parameters, negotiation for UE capability and network behavior is needed to ensure that policy information is parameters that UE capability can support. The connection capability is taken as an example below to explain that negotiation for UE capability and network behavior is needed in combination with Table 3.

Table 3 Connectivity capability

Parameter name	Description	Level
Connectivity capability	The parameter is provided by a UE application layer and is used for requesting a connection with a specific capability, such as supporting a specific DNN of a PDU session.	Optional

As shown in Table 3, the connection capability may refer to that a communication capability (e.g., an IMS service, a voice service, etc.) requested by an application layer is mapped, through an OS layer, to DNN parameters that may be recognized and supported by a 3GPP layer (a communication layer), and UE uses the mapped DNN to establish/modify a PDU session. Therefore, negotiation of UE capability and network behavior is needed. For another example, whether the OS of the UE can directly identify a DNN provided by the application layer or allow the application layer to provide DNN information (such as opening a specific API interface), thereby binding the traffic corresponding to the belonged DNN to the PDU session corresponding to the route selection descriptor, is an optional item, therefore negotiation

of UE capability and network behavior is also needed.

In an embodiment of the present application, the negotiation of UE capability and network behavior may include the following two approaches.

1) The UE reports supported capabilities to a network element at the network side. If the
5 UE does not support a specific capability, such as a connection capability, the network side sends a UE policy that does not contain this parameter.

(2) After receiving the UE policies sent by the network side, the UE performs selection according to its own capabilities, ignores or deactivates those UE policies that contain parameters which the UE does not support. Additionally and optionally, unsupported
10 parameters and/or unsupported policies are reported to the network side. Optionally, then the network side may perform updating accordingly.

In addition, an embodiment of the present invention further provides a wireless communication method, which includes: a first network device determines that a registration request message does not carry a Policy Section Identifier (PSI) parameter. Herein, the PSI
15 parameter is used for identifying a part of policy information for a terminal device under a subscribed user; and a first network device sends policy information to the terminal device. For the terminal device, the terminal device sends a registration request message to the network device, wherein the registration request message does not carry a PSI parameter or the PSI parameter is null. The terminal device receives policy information sent by the first network
20 device. For example, when a Subscriber Identification Module (SIM) card is replaced, the terminal device initiates an initial registration request message in which a PSI parameter is not carried or the PSI parameter is set to be null, and clears the PSI parameters stored locally. For another example, the terminal device does not carry a PSI parameter or sets the PSI parameter to be null in an initial registration request message when a non-SIM card is unchanged. In this
25 case, the terminal device receives policy information corresponding to a subscriber identifier of the terminal device currently used, which is sent by the first network device. Further, the terminal device may further clear PSI parameters stored locally.

Further, the first network device determines that the registration request message may further carry first indication information for indicating that a Subscriber Identification Module

(SIM) card of the terminal device has been replaced.

Therefore, the first network device may directly update the policy information of the terminal device according to the first indication information. In an implementable mode, the first network device may generate second indication information after receiving the first indication information, wherein the second indication information is used for instructing the terminal device to delete and/or add policy information corresponding to each PSI parameter in at least one PSI parameter; and then, the first network device sends the second indication information to the terminal device. In such way, the terminal device may delete and/or add policy information according to the second indication information after receiving the second indication information sent by the first network device.

Further, the first network device sends policy information to the terminal device according to mapping relationship information which includes a corresponding relationship between subscriber identifiers and PSI parameters. For example, the first network device may generate the second indication information according to the mapping relationship information of the terminal device. In an embodiment of the present invention, before the first network device generates the second indication information according to the mapping relationship information of the terminal device, the first network device may further store the mapping relationship information of the terminal device.

In addition, an embodiment of the present invention further provides a wireless communication method, which includes: a first network device sends/updates part of policy information to a terminal device according to capability information of the terminal device. The capability information includes at least one of the following information: a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

Optionally, the first network device acquires capability information of the terminal device.

In other words, the terminal device sends the capability information of the terminal device to the first network device; and the terminal device receives the policy information of the terminal device sent by the first network device.

5 The mapping relationship in an embodiment of the present invention will be described below with reference to FIGs. 4 and 5.

In an embodiment, multiple subscriber identifiers in the mapping relationship information correspond to multiple PSI parameters, i.e., one PSI parameter in the mapping relationship information corresponds to multiple subscriber identifiers. The technical solution can effectively reduce data storage amount of the first network device. For example, as shown in
10 FIG. 4, the first network device may establish a mapping relationship between subscriber 1, subscriber 2, and subscriber 3 and all policy information. For example, subscriber 1 corresponds to PSI 1, PSI 3, and PSI 5, subscriber 2 corresponds to PSI 2 and PSI 3, and subscriber 3 corresponds to PSI 4, PSI 5, and PSI n. Herein, each PSI indicates one piece of policy information. In other alternative embodiments, each subscriber identifier in the mapping
15 relationship information corresponds to at least one PSI parameter separately, and further, one PSI parameter in the mapping relationship information corresponds to one subscriber identifier only. For example, as shown in FIG. 5, subscriber 1, subscriber 2, and subscriber 3 respectively establish corresponding relationships between PSI parameters corresponding to policy information and subscriber identifiers. For example, subscriber 1 corresponds to PSI 1, PSI 2, and PSI 3, PSI 1 is used for indicating policy information 1, PSI 2 is used for indicating policy
20 information 2, and PSI 3 is used for indicating policy information 3. It should be noted that since each subscriber identifier in the mapping relationship information corresponds to at least one PSI parameter separately, PSI and policy information between subscribers will not affect each other, and therefore, the same PSI or policy information may be used repeatedly. For
25 example, as shown in FIG. 5, PSI 4 corresponding to subscriber 2 may also be used for indicating policy information 3. In other words, the first network device may only send policy information according to the subscriber identifier.

It should be understood that the mapping relationship information shown in FIGs. 4 and 5 is only illustrative, and an embodiment of the present invention does not specifically limit a

form and quantity of the mapping relationship information. For example, subscriber 2 shown in FIG. 4 may further correspond to other multiple PSIs. For another example, the mapping relationship information may be in a form of a table or a form of a graph.

FIG. 6 is a schematic block diagram of a network device according to an embodiment of the present invention.

Specifically, as shown in FIG. 6, the network device 400 includes a processing unit 410.

The processing unit 410 is used for determining whether to update policy information of a terminal device after acquiring a Policy Section Identifier (PSI) parameter of the terminal device.

Optionally, the PSI parameter includes a subscriber identifier.

Herein, the terminal device further includes a transceiving unit 420.

The transceiving unit 420 is used for receiving a subscriber identifier sent by a second network device.

The processing unit 410 is specifically used for determining whether to update the policy of the terminal device according to the subscriber identifier corresponding to the PSI parameter and the subscriber identifier sent by the second network device.

Optionally, the processing unit 410 is further specifically used for: determining to update the policy information of the terminal device when determining that the subscriber identifier corresponding to the PSI parameter is different from the subscriber identifier sent by the second network device.

Optionally, the processing unit 410 is further specifically used for sending policy information corresponding to a subscriber identifier of the terminal device currently used to the terminal device.

Optionally, the processing unit 410 is further specifically used for sending policy information corresponding to the subscriber identifier sent by the second network device to the terminal device.

Optionally, the subscriber identifier includes a Subscriber Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

Optionally, the PSI parameter includes a Public Land Mobile Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely identifying a PSI parameter under the PLMN.

Optionally, the PSI parameter includes a timestamp and/or a version identifier.

5 Herein, the processing unit 410 is specifically used for: acquiring a last update time of the policy information of the terminal device according to the timestamp and/or the version identifier in the PSI parameter, and determining whether to update the policy information of the terminal device according to an update time threshold and/or a latest version.

10 Optionally, the processing unit 410 is further used for: updating the policy information of the terminal device when determining to update a policy of the terminal device.

Optionally, the processing unit 410 is specifically used for: updating periodically the policy information of the terminal device.

15 Optionally, the processing unit 410 is specifically used for: sending/updating part of the policy information to the terminal device according to capability information of the terminal device.

Optionally, the capability information of the terminal device includes at least one of the following:

20 a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

25 Optionally, the processing unit 410 is further used for: acquiring the capability information of the terminal device before updating the policy information of the terminal device according to the capability information of the terminal device.

Optionally, the processing unit 410 is specifically used for: sending all policy information to the terminal device so that the terminal device selects part of the policy information to use

from the all policy information according to a capability of the terminal device.

Optionally, the network device is a Policy Control Function (PCF).

Optionally, the second network device is an Access and Mobility Management Function (AMF).

5 In an embodiment of the present invention, the processing unit 410 may be implemented by a processor, and the transceiving unit 420 may be implemented by a transceiver. As shown in FIG. 7, a network device 500 may include a processor 510, a transceiver 520, and a memory 530. The memory 530 may be used for storing indication information, or may be used for storing codes, instructions, etc., executed by the processor 510. The various components in the
10 network device 500 are connected by a bus system. The bus system includes a power bus, a control bus and a status signal bus in addition to a data bus.

The network device 500 shown in FIG. 7 can implement the various processes implemented by the first network device in the method embodiment shown in FIG. 3. To avoid duplication, the details will not be repeated here.

15 FIG. 8 is a schematic block diagram of a terminal device 600 according to an embodiment of the present invention.

Specifically, as shown in FIG. 8, the terminal device 600 includes a determining unit 610 and a transceiving unit 620.

20 The determining unit 610 is used for determining a Policy Section Identifier (PSI) parameter which is used for identifying a part of policy information for the terminal device under a subscribed user.

The transceiving unit 620 is used for sending the PSI parameter to a first network device.

Optionally, the PSI parameter includes a subscriber identifier.

25 Optionally, the transceiving unit 620 is further used for: receiving policy information corresponding to a subscriber identifier of the terminal device currently used, which is sent by the first network device.

Optionally, the transceiving unit 620 is specifically used for: receiving policy information corresponding to a subscriber identifier sent by a second network device.

Optionally, the subscriber identifier includes a Subscriber Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

Optionally, the PSI parameter includes a Public Land Mobile Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely identifying a PSI parameter
5 under the PLMN.

Optionally, the transceiving unit 620 is further used for: receiving the policy information of the terminal device sent by the first network device.

Optionally, the transceiving unit 620 is further specifically used for: receiving periodically policy information of the terminal device sent by the first network device.

10 Optionally, the terminal device is the policy information of the terminal device determined by the first network device according to capability information of the terminal device.

Optionally, the capability information of the terminal device includes at least one of the following: Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device,
15 Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

Optionally, the transceiving unit 620 is further used for: before receiving the policy
20 information of the terminal device sent by the first network device, sending the capability information of the terminal device to the first network device.

Optionally, the transceiving unit 620 is specifically used for: receiving all of the policy information of the terminal device sent by the first network device; and wherein the processing unit is further used for selecting part of the policy information to use from the all policy
25 information according to a capability of the terminal device.

Optionally, the first network device is a Policy Control Function (PCF).

Optionally, the second network device is an Access and Mobility Management Function (AMF).

In an embodiment of the present invention, the processing unit 610 may be implemented by a processor, and the transceiving unit 620 may be implemented by a transceiver. As shown in FIG. 9, a terminal device 700 may include a processor 710, a transceiver 720, and a memory 730. The memory 730 may be used for storing indication information, or may be used for storing codes, instructions, etc., executed by the processor 710. The various components in the terminal device 700 are connected by a bus system. The bus system includes a power bus, a control bus and a status signal bus in addition to a data bus.

The terminal device 700 shown in FIG. 9 can implement the various processes implemented by the terminal device in the method embodiment shown in FIG. 3. To avoid duplication, the details will not be repeated here. That is, a method embodiment in embodiments of the present invention may be applied to or implemented by a processor.

In addition, an embodiment of the present invention further provides a network device, which includes a processing unit and a transceiving unit. The processing unit is used for determining that the registration request message does not carry a Policy Section Identifier (PSI) parameter, wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user. The transceiving unit is used for sending policy information to the terminal device.

Optionally, the processing unit is further used for determining that the registration request message carries first indication information, wherein the first indication information is used for indicating that a Subscriber Identification Module (SIM) card of the terminal device has been replaced.

Optionally, the processing unit is further used for generating second indication information, wherein the second indication information is used for instructing the terminal device to delete and/or add policy information corresponding to each PSI parameter in at least one PSI parameter; wherein the transceiving unit is further used for sending second indication information to the terminal device.

Optionally, the transceiving unit is specifically used for sending the policy information to the terminal device according to mapping relationship information, wherein the mapping relationship information includes a corresponding relationship between subscriber identifiers

and PSI parameters.

Optionally, each subscriber identifier in the mapping relationship information corresponds to at least one PSI parameter separately.

Optionally, one PSI parameter in the mapping relationship information corresponds to one
5 subscriber identifier only.

Optionally, multiple subscriber identifiers in the mapping relationship information correspond to multiple PSI parameters.

Optionally, one PSI parameter in the mapping relationship information corresponds to multiple subscriber identifiers.

10 Optionally, the transceiving unit is specifically used for sending policy information corresponding to a subscriber identifier sent by a second network device to the terminal device.

An embodiment of the invention further provides a terminal device, which includes a transceiving unit, used for sending a registration request message to the network device. Herein, the registration request message does not carry a Policy Section Identifier (PSI) parameter, and
15 the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user. The transceiving unit is further used for receiving policy information sent by a first network device. For example, when a Subscriber Identification Module (SIM) card is replaced, the terminal device initiates an initial registration request message in which a PSI parameter is not carried or the PSI parameter is set to be null, and clears the PSI parameters
20 stored locally. For another example, the terminal device does not carry a PSI parameter or sets the PSI parameter to be null in an initial registration request message when a non-SIM card is unchanged.

Optionally, the registration request message carries first indication information, wherein the first indication information is used for indicating that a Subscriber Identification Module
25 (SIM) card of the terminal device has been replaced.

Optionally, the transceiving unit is specifically used for: receiving second indication information sent by the first network device, wherein the second indication information is used for instructing the terminal device to delete and/or add policy information corresponding to

each PSI parameter in at least one PSI parameter; and deleting and/or adding policy information according to the second indication information.

Optionally, the transceiving unit is specifically used for receiving policy information corresponding to a subscriber identifier of the terminal device currently used, which is sent by
5 the first network device.

Optionally, the terminal device further includes a processing unit for clearing PSI parameters stored locally.

An embodiment of the present application further provides a network device, which includes: a transceiving unit, used for sending/updating part of policy information to the
10 terminal device according to capability information of the terminal device.

Optionally, the capability information includes at least one of the following: a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an
15 operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

Optionally, the transceiving unit is further used for: acquiring, by a first network device, the capability information of the terminal device.

20 An embodiment of the present application further provides a terminal device, which includes: a sending unit, used for sending capability information of the terminal device to a first network device; and a transceiving unit, used for receiving the policy information of the terminal device sent by the first network device.

Optionally, the capability information includes at least one of the following: a Permanent
25 Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into

a parameter indicating a PDU session characteristic is supported.

In an implementation process, each act of the method embodiments in the embodiments of the present invention may be completed by an integrated logic circuit of hardware in the processor or an instruction in the form of software. More specifically, the acts of the method disclosed in connection with the embodiments of the present invention may be directly embodied as accomplishment through the execution of a hardware decoding processor or accomplishment through the execution in the combination of hardware and software modules in the decoding processor. Software modules may be located in a typical storage medium in the art, such as, a random access memory (RAM), a flash memory, a read-only memory, a programmable read-only memory, an electrical erasable programmable memory, or a register. The storage medium is located in the memory, and the processor reads the information in the memory and completes the acts of the above method in combination with its hardware.

It should be understood that the processor mentioned in embodiments of the present invention may be an integrated circuit chip with a capability of signal processing. The processor can implement or execute the methods, acts or logical diagrams disclosed in the embodiments of the present invention. For example, the above processor may be a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic devices, a transistor logic device, or a discrete hardware component, or the like. Furthermore, the general purpose processor may be a microprocessor or the processor may be any conventional processor or the like.

In addition, the memory mentioned in the embodiments of the present invention may be a volatile memory or non-volatile memory, or may include both volatile and non-volatile memories. The non-transitory memory may be a read-only memory (ROM), a programmable ROM (PROM), an erasable PROM (EPROM), an electrically erasable EPROM (EEPROM), or a flash memory. The volatile memory may be a Random Access Memory (RAM) which serves as an external cache. It should be understood that, the foregoing memory is illustrative and should not be construed as limiting. For example, the memory in the embodiments of the present invention may be a Static RAM (SRAM), Dynamic RAM (DRAM), Synchronous

DRAM (SDRAM), Double Data Rate SDRAM (DDR SDRAM), Enhanced SDRAM (ESDRAM), Synch link DRAM (SLDRAM), Direct Rambus RAM (DR RAM), or the like. That is, memories in the systems and methods described in this document are intended to include, but not limited to, these and any other suitable types of memories.

5 Finally, it should be noted that the terms used in the embodiments of the present invention and the appended claims are for the purpose of describing specific embodiments only and are not intended to limit the embodiments of the present invention.

10 For example, as used in the embodiments of the present invention and the appended claims, the singular forms "a", "said", "the forgoing" and "the" include plural referents unless the context clearly dictates something else.

 For another example, the term "first identifier" may be used in an embodiment of the present invention, but these identifiers should not be limited to these terms. These terms are only used for distinguishing the identifiers from each other.

15 For another example, depending on the context, the word "when" as used herein may be interpreted as "if" or "whether" or "while" or "in response to a determination of/that" or "in response to a detection of/that". Similarly, depending on the context, the phrase "if determining" or "if detecting (a stated condition or event)" may be interpreted as "when ... is determined" or "in response to a determination" or "when (stated condition or event) is detected" or "in response to a detection of (stated condition or event)".

20 Those of ordinary skill in the art will recognize that various exemplary units and algorithm acts described in connection with the embodiments disclosed herein may be implemented in electronic hardware, or in a combination of computer software and electronic hardware. Whether these functions are implemented in hardware or software depends on a specific application and design constraint of the technical solution. One skilled in the art may use
25 different methods to implement the described functions for each particular application, but such implementation mode should not be considered to be beyond the scope of embodiments of the present invention.

 Those skilled in the art may clearly understand that for convenience and conciseness of description, specific working processes of the system, device and unit described above may

refer to the corresponding processes in the aforementioned embodiments of methods, and details are not described here again.

In several embodiments provided by the present invention, it should be understood that the disclosed systems, devices and methods may be implemented in other ways. For example, the device embodiments described above are only illustrative, for example, the division of the units is only a logical function division, and there may be other division modes in an actual implementation mode, for example, multiple units or components may be combined or integrated into another system, or some features may be ignored or not executed. On the other hand, the mutual coupling or direct coupling or communication connection between each other shown or discussed may be indirect coupling or communication connection through some interfaces, devices or units, and may be in electrical, mechanical or other forms.

The units described as separated components may or may not be physically separated, and the component shown as a unit may or may not be a physical unit, i.e., it may be located in one place or may be allocated over multiple network units. Parts or all of the units can be selected according to actual needs to achieve the purpose of the embodiments of the present invention.

In addition, various functional units in the embodiments of the present invention may be integrated in one processing unit, or various units may be presented separately in a physical way, or two or more units may be integrated into one unit.

The function units may be stored in a computer readable storage medium if realized in a form of software functional units and sold or used as a separate product. Based on this understanding, the technical solutions of the embodiments of the present invention, in essence, or the part contributing to the related art, or the part of the technical solutions, may be embodied in the form of a software product stored in a storage medium, including several instructions for causing a computer device (which may be a personal computer, a server, or a network device, etc.) to perform all or parts of the acts of the methods described in various embodiments of the present invention. The aforementioned storage medium includes a medium capable of storing program codes, such as, a U disk, a mobile hard disk, a read-only memory (ROM), a magnetic disk or an optical disk, etc.

What are described above are merely the specific implementation modes of the

embodiments of the present invention, but the protection scope of the embodiments of the present invention is not limited thereto. Any change or substitution that can be easily conceived by a person skilled in the art within the technical scope disclosed by the embodiments of the present invention shall be included within the protection scope of the embodiments of the present invention. Therefore, the scope of protection of the embodiments of the present invention should be subject to the scope of protection of the claims.

Claims:

1. A wireless communication method, comprising:

determining, by a first network device, whether to update policy information of a terminal device after acquiring a Policy Section Identifier (PSI) parameter of the terminal device,
 5 wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user.

2. The method of claim 1, wherein the PSI parameter comprises a subscriber identifier;

wherein determining whether to update the policy of the terminal device comprises:

receiving, by the first network device, a subscriber identifier sent by a second network
 10 device; and

determining, by the first network device, whether to update the policy of the terminal device according to the subscriber identifier corresponding to the PSI parameter and the subscriber identifier sent by the second network device.

3. The method of claim 2, wherein determining, by the first network device, whether to
 15 update the policy of the terminal device according to the subscriber identifier corresponding to the PSI parameter and the subscriber identifier sent by the second network device, comprises:

determining, by the first network device, to update the policy information of the terminal device in a condition of determining that the subscriber identifier corresponding to the PSI parameter is different from the subscriber identifier sent by the second network device.

20 4. The method of claim 3, wherein determining to update the policy information of the terminal device comprises:

sending, by the first network device, policy information corresponding to a subscriber identifier of the terminal device currently used to the terminal device.

25 5. The method of claim 3 or 4, wherein determining to update the policy information of the terminal device comprises:

sending, by the first network device, policy information corresponding to the subscriber identifier sent by the second network device to the terminal device.

6. The method of any one of claims 2-5, wherein the subscriber identifier comprises a Subscriber Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

7. The method of claim 1, wherein the PSI parameter comprises a Public Land Mobile Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely
5 identifying a PSI parameter under the PLMN.

8. The method of any one of claims 1-7, wherein the PSI parameter comprises a timestamp and/or a version identifier;

wherein determining whether to update the policy of the terminal device comprises:

acquiring, by the first network device, a last update time of the policy information of the
10 terminal device according to the timestamp and/or the version identifier in the PSI parameter, and determining whether to update the policy information of the terminal device according to an update time threshold and/or a latest version.

9. The method of any one of claims 1-8, wherein the method further comprises:

updating, by the first network device, the policy information of the terminal device in a
15 condition that the first network device determines to update the policy of the terminal device.

10. The method of claim 9, wherein updating the policy information of the terminal device comprises:

updating periodically, by the first network device, the policy information of the terminal device.

20 11. The method of claim 9 or 10, wherein updating the policy information of the terminal device comprises:

sending/updating, by the first network device, part of the policy information to the terminal device according to capability information of the terminal device.

25 12. The method of claim 11, wherein the capability information comprises at least one of the following:

a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an

operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

13. The method of claim 11 or 12, wherein before the first network device updates the policy information of the terminal device according to the capability information of the terminal device, the method further comprises:

acquiring, by the first network device, the capability information of the terminal device.

14. The method of claim 9 or 10, wherein updating the policy information of the terminal device comprises:

10 sending, by the first network device, all policy information to the terminal device to enable the terminal device to select part of the policy information to use from the all policy information according to a capability of the terminal device.

15. The method of any one of claims 1-14, wherein the first network device is a Policy Control Function (PCF).

15 16. The method of any one of claims 1-15, wherein the second network device is an Access and Mobility Management Function (AMF).

17. A network device, comprising:

a processing unit, used for determining whether to update policy information of a terminal device after acquiring a Policy Section Identifier (PSI) parameter of the terminal device, wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user.

18. The network device of claim 17, wherein the PSI parameter comprises a subscriber identifier; and

the terminal device further comprises:

25 a transceiving unit, used for receiving a subscriber identifier sent by a second network device;

wherein the processing unit is specifically used for determining whether to update the policy of the terminal device according to the subscriber identifier corresponding to the PSI

parameter and the subscriber identifier sent by the second network device.

19. The network device of claim 18, wherein the processing unit is further specifically used for:

5 determining to update the policy information of the terminal device in a condition of determining that the subscriber identifier corresponding to the PSI parameter is different from the subscriber identifier sent by the second network device.

20. The network device of claim 19, wherein the processing unit is further specifically used for sending policy information corresponding to a subscriber identifier of the terminal device currently used to the terminal device.

10 21. The network device of claim 19 or 20, wherein the processing unit is further specifically used for sending policy information corresponding to the subscriber identifier sent by the second network device to the terminal device.

15 22. The network device of any one of claims 18-21, wherein the subscriber identifier comprises a Subscriber Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

23. The network device of claim 17, wherein the PSI parameter comprises a Public Land Mobile Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely identifying a PSI parameter under the PLMN.

20 24. The network device of any one of claims 17-23, wherein the PSI parameter comprises a timestamp and/or a version identifier;

wherein the processing unit is specifically used for:

25 acquiring a last update time of the policy information of the terminal device according to the timestamp and/or the version identifier in the PSI parameter, and determining whether to update the policy information of the terminal device according to an update time threshold and/or a latest version.

25. The network device of any one of claims 17-24, wherein the processing unit is further used for:

updating the policy information of the terminal device in a condition of determining to

update a policy of the terminal device.

26. The network device of claim 25, wherein the processing unit is specifically used for:
updating periodically the policy information of the terminal device.

27. The network device of claim 25 or 26, wherein the processing unit is specifically used
5 for:

sending/updating part of the policy information to the terminal device according to
capability information of the terminal device.

28. The network device of claim 27, wherein the capability information comprises at least
one of the following:

10 a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device,
a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network
Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an
operating system supports receiving and/or identifying a Data Network Name (DNN) parameter
sent by an application layer, and whether mapping an upper layer request message of 3GPP into
15 a parameter indicating a PDU session characteristic is supported.

29. The network device of claim 27 or 28, wherein the processing unit is further used for:
acquiring the capability information of the terminal device before updating the policy
information of the terminal device according to the capability information of the terminal
device.

20 30. The network device of claim 25 or 26, wherein the processing unit is specifically used
for:

sending all policy information to the terminal device to enable the terminal device to select
part of the policy information to use from the all policy information according to a capability of
the terminal device.

25 31. The network device of any one of claims 17-30, wherein the network device is a Policy
Control Function (PCF).

32. The network device of any one of claims 17-30, wherein the second network device is
an Access and Mobility Management Function (AMF).

33. A wireless communication method, comprising:

determining, by a terminal device, a Policy Section Identifier (PSI) parameter which is used for identifying a part of policy information for the terminal device under a subscribed user; and

5 sending, by the terminal device, the PSI parameter to a first network device.

34. The method of claim 33, wherein the PSI parameter comprises a subscriber identifier.

35. The method of claim 33 or 34, wherein the method further comprises:

receiving, by the terminal device, policy information corresponding to a subscriber identifier of the terminal device currently used, which is sent by the first network device.

10 36. The method of claim 33 or 34, wherein receiving, by the terminal device, the policy information corresponding to the subscriber identifier of the terminal device currently used, which is sent by the first network device, comprises:

receiving, by the terminal device, the policy information corresponding to a subscriber identifier sent by a second network device.

15 37. The method of any one of claims 34-36, wherein the subscriber identifier comprises a Subscriber Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

38. The method of claim 37, wherein the PSI parameter comprises a Public Land Mobile Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely identifying a PSI parameter under the PLMN.

20 39. The method of any one of claims 33-38, wherein the method further comprises:

receiving, by the terminal device, the policy information of the terminal device sent by the first network device.

40. The method of claim 39, wherein receiving, by the terminal device, the policy information of the terminal device sent by the first network device comprises:

25 receiving periodically, by the terminal device, the policy information of the terminal device sent by the first network device.

41. The method of claim 39 or 40, wherein the policy information of the terminal device

sent by the first network device is the policy information of the terminal device determined by the first network device according to capability information of the terminal device.

42. The method of claim 41, wherein the capability information comprises at least one of the following:

5 a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into
10 a parameter indicating a PDU session characteristic is supported.

43. The method of claim 41 or 42, wherein before the terminal device receives the policy information of the terminal device sent by the first network device, the method further comprises:

15 sending, by the terminal device, the capability information of the terminal device to the first network device.

44. The method of claim 39 or 40, wherein receiving, by the terminal device, the policy information of the terminal device sent by the first network device comprises:

receiving, by the terminal device, all policy information of the terminal device sent by the first network device; and

20 the method further comprises:

selecting, by the terminal device, part of the policy information to use from the all policy information according to a capability of the terminal device.

45. The method of claim 44, wherein selecting, by the terminal device, the part of the policy information to use from the all policy information according to the capability of the
25 terminal device comprises:

performing, by the terminal device, a first behavior or a second behavior on the policy information according to the capability of the terminal device;

wherein the first behavior refers to that after the terminal device selects a first rule of a

first priority, in a condition that the terminal device does not support a first parameter in the first rule, the terminal device does not select the first rule but selects a second rule of a second priority; and

5 the second behavior refers to that after the terminal device selects the first rule of the first priority, in a condition that the terminal device does not support the first parameter in the first rule, the terminal device does not select the first parameter, and parameters other than the first parameter in the first rule remain valid.

46. The method of any one of claims 33-45, wherein the first network device is a Policy Control Function (PCF).

10 47. The method of any one of claims 33-46, wherein the second network device is an Access and Mobility Management Function (AMF).

48. A terminal device, comprising:

15 a determining unit, used for determining a Policy Section Identifier (PSI) parameter which is used for identifying a part of policy information for the terminal device under a subscribed user; and

a transceiving unit, used for sending the PSI parameter to a first network device.

49. The terminal device of claim 48, wherein the PSI parameter comprises a subscriber identifier.

20 50. The terminal device of claim 48 or 49, wherein the transceiving unit is further used for: receiving policy information corresponding to a subscriber identifier of the terminal device currently used, which is sent by the first network device.

51. The terminal device of claim 48 or 49, wherein the transceiving unit is specifically used for:

25 receiving policy information corresponding to a subscriber identifier sent by a second network device.

52. The terminal device of any one of claims 49-51, wherein the subscriber identifier comprises a Subscriber Private Identifier (SUPI) and/or a Subscriber Concealed Identifier (SUCI).

53. The terminal device of claim 48, wherein the PSI parameter comprises a Public Land Mobile Network (PLMN) identifier and a first identifier, and the first identifier is used for uniquely identifying a PSI parameter under the PLMN.

54. The terminal device of any one of claims 48-53, wherein the transceiving unit is
5 further used for:

receiving the policy information of the terminal device sent by the first network device.

55. The terminal device of claim 53, wherein the transceiving unit is specifically used for:

receiving periodically the policy information of the terminal device sent by the first network device.

10 56. The terminal device of claim 54 or 55, wherein the terminal device is the policy information of the terminal device determined by the first network device according to capability information of the terminal device.

57. The terminal device of claim 56, wherein the capability information comprises at least one of the following:

15 a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into
20 a parameter indicating a PDU session characteristic is supported.

58. The terminal device of claim 56 or 57, wherein the transceiving unit is further used for:

before receiving the policy information of the terminal device sent by the first network device, sending the capability information of the terminal device to the first network device.

59. The terminal device of claim 54 or 55, wherein the transceiving unit is specifically
25 used for:

receiving all policy information sent by the first network device; and

wherein the processing unit is further used for selecting part of the policy information to use from the all policy information according to a capability of the terminal device.

60. The terminal device of claim 59, wherein the processing unit is specifically used for:
performing a first behavior or a second behavior on the policy information according to the capability of the terminal device;

5 wherein the first behavior refers to that after the terminal device selects a first rule of a first priority, in a condition that the terminal device does not support a first parameter in the first rule, the terminal device does not select the first rule but selects a second rule of a second priority; and

10 the second behavior refers to that after the terminal device selects the first rule of the first priority, in a condition that the terminal device does not support the first parameter in the first rule, the terminal device does not select the first parameter, and parameters other than the first parameter in the first rule remain valid.

61. The terminal device of any one of claims 48-60, wherein the first network device is a Policy Control Function (PCF).

15 62. The terminal device of any one of claims 48-61, wherein the second network device is an Access and Mobility Management Function (AMF).

63. A wireless communication method, comprising:

20 determining, by a first network device, that in a registration request message, a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null, wherein the PSI parameter is used for identifying a part of policy information for a terminal device under a subscribed user; and

sending, by the first network device, policy information to the terminal device.

64. The method of claim 63, wherein the method further comprises:

25 determining, by the first network device, that the registration request message carries first indication information, wherein the first indication information is used for indicating that a Subscriber Identification Module (SIM) card of the terminal device has been replaced.

65. The method of claim 63 or 64, wherein sending, by the first network device, the policy information to the terminal device comprises:

generating, by the first network device, second indication information, wherein the second

indication information is used for instructing the terminal device to delete and/or add policy information corresponding to each PSI parameter in at least one PSI parameter; and

sending, by the first network device, the second indication information to the terminal device.

5 66. The method of any one of claims 63-65, wherein sending, by the first network device, the policy information to the terminal device comprises:

sending, by the first network device, the policy information to the terminal device according to mapping relationship information, wherein the mapping relationship information comprises a corresponding relationship between subscriber identifiers and PSI parameters.

10 67. The method of claim 66, wherein each subscriber identifier in the mapping relationship information corresponds to at least one PSI parameter separately.

68. The method of claim 67, wherein one PSI parameter in the mapping relationship information corresponds to one subscriber identifier only.

15 69. The method of claim 66, wherein a plurality of subscriber identifiers in the mapping relationship information correspond to a plurality of PSI parameters.

70. The method of claim 69, wherein one PSI parameter in the mapping relationship information corresponds to a plurality of subscriber identifiers.

71. The method of claim 63 or 64, wherein sending, by the first network device, the policy information to the terminal device comprises:

20 sending, by the first network device, policy information corresponding to a subscriber identifier sent by a second network device to the terminal device.

72. The method of any one of claims 63-71, wherein the first network device is a Policy Control Function (PCF).

25 73. The method of claim 71 or 72, wherein the second network device is an Access and Mobility Management Function (AMF).

74. A wireless communication method, comprising:

sending, by a terminal device, a registration request message to a network device, wherein

a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null in the registration request message, wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user; and

receiving, by the terminal device, policy information sent by a first network device.

5 75. The method of claim 74, wherein the registration request message carries first indication information, wherein the first indication information is used for indicating that a Subscriber Identification Module (SIM) card of the terminal device has been replaced.

76. The method of claim 74 or 75, wherein receiving, by the terminal device, the policy information sent by the first network device comprises:

10 receiving, by the terminal device, second indication information sent by the first network device, wherein the second indication information is used for instructing the terminal device to delete and/or add policy information corresponding to each PSI parameter in at least one PSI parameter; and

15 deleting and/or adding, by the terminal device, the policy information according to the second indication information.

77. The method of claim 74 or 75, wherein receiving, by the terminal device, the policy information sent by the first network device comprises:

receiving, by the terminal device, policy information corresponding to a subscriber identifier of the terminal device currently used, which is sent by the first network device.

20 78. The method of any one of claims 74-77, wherein the terminal device does not carry a PSI parameter or sets the PSI parameter to be null in an initial registration request message initiated in a condition that a Subscriber Identification Module (SIM) card is replaced.

79. The method of any one of claims 74-77, wherein the terminal device does not carry a PSI parameter or sets the PSI parameter to be null in an initial registration request message in a
25 condition that a non-SIM card is unchanged.

80. The method of any one of claims 74-79, wherein the method further comprises:

clearing, by the terminal device, PSI parameters stored locally.

81. The method of any one of claims 74-80, wherein the first network device is a Policy

Control Function (PCF).

82. A network device, comprising:

a processing unit, used for determining that in a registration request message, a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null, wherein the PSI parameter is used for identifying a part of policy information for a terminal device under a subscribed user; and

a transceiving unit, used for sending policy information to the terminal device.

83. The network device of claim 82, wherein the processing unit is further used for:

determining that the registration request message carries first indication information, wherein the first indication information is used for indicating that a Subscriber Identification Module (SIM) card of the terminal device has been replaced.

84. The network device of claim 82 or 83, wherein the processing unit is further used for:

generating second indication information, wherein the second indication information is used for instructing the terminal device to delete and/or add policy information corresponding to each PSI parameter in at least one PSI parameter; wherein the transceiving unit is further used for: sending the second indication information to the terminal device.

85. The network device of any one of claims 82-84, wherein the transceiving unit is specifically used for:

sending the policy information to the terminal device according to mapping relationship information, wherein the mapping relationship information comprises a corresponding relationship between subscriber identifiers and PSI parameters.

86. The network device of claim 85, wherein each subscriber identifier in the mapping relationship information corresponds to at least one PSI parameter separately.

87. The network device of claim 86, wherein one PSI parameter in the mapping relationship information corresponds to one subscriber identifier only.

88. The network device of claim 85, wherein a plurality of subscriber identifiers in the mapping relationship information correspond to a plurality of PSI parameters.

89. The network device of claim 88, wherein one PSI parameter in the mapping relationship information corresponds to a plurality of subscriber identifiers.

90. The network device of claim 82 or 83, wherein the transceiving unit is specifically used for:

5 sending policy information corresponding to a subscriber identifier sent by a second network device to the terminal device.

91. The network device of any one of claims 82-90, wherein the network device is a Policy Control Function (PCF).

10 92. The network device of claim 90 or 91, wherein the second network device is an Access and Mobility Management Function (AMF).

93. A terminal device, comprising:

15 a transceiving unit, used for sending a registration request message to a network device, wherein a Policy Section Identifier (PSI) parameter is not carried or the PSI parameter is null in the registration request message, wherein the PSI parameter is used for identifying a part of policy information for the terminal device under a subscribed user;

 wherein the transceiving unit is further used for receiving policy information sent by a first network device.

20 94. The terminal device of claim 93, wherein the registration request message carries first indication information, wherein the first indication information is used for indicating that a Subscriber Identification Module (SIM) card of the terminal device has been replaced.

95. The terminal device of claim 93 or 94, wherein the transceiving unit is specifically used for:

25 receiving second indication information sent by the first network device, wherein the second indication information is used for instructing the terminal device to delete and/or add policy information corresponding to each PSI parameter in at least one PSI parameter; and

 deleting and/or adding policy information according to the second indication information.

96. The terminal device of claim 93 or 94, wherein the transceiving unit is specifically used for:

receiving policy information corresponding to a subscriber identifier of the terminal device currently used, which is sent by the first network device.

97. The terminal device of any one of claims 93-96, wherein the terminal device does not carry a PSI parameter or sets the PSI parameter to be null in an initial registration request
5 message initiated in a condition that a Subscriber Identification Module (SIM) card is replaced.

98. The terminal device of any one of claims 93-96, wherein the terminal device does not carry a PSI parameter or sets the PSI parameter to be null in an initial registration request message in a condition that a non-SIM card is unchanged.

99. The terminal device of any one of claims 93-98, wherein the terminal device further
10 comprises:

a processing unit, used for clearing PSI parameters stored locally.

100. The terminal device of any one of claims 93-99, wherein the first network device is a Policy Control Function (PCF).

101. A wireless communication method, comprising:

15 sending/updating, by a first network device, part of policy information to a terminal device according to capability information of the terminal device.

102. The method of claim 101, wherein the capability information comprises at least one of the following:

20 a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

25 103. The method of claim 101 or 102, wherein the method further comprises:

acquiring, by the first network device, the capability information of the terminal device.

104. A wireless communication method, comprising:

sending, by a terminal device, capability information of the terminal device to a first network device; and

receiving, by the terminal device, policy information of the terminal device sent by the first network device.

5 105. The method of claim 104, wherein the capability information comprises at least one of the following:

10 a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

106. A network device, comprising:

15 a transceiving unit, used for sending/updating part of policy information to a terminal device according to capability information of the terminal device.

107. The network device of claim 106, wherein the capability information comprises at least one of the following:

20 a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

25 108. The network device of claim 106 or 107, wherein the transceiving unit is further used for:

acquiring, by a first network device, the capability information of the terminal device.

109. A terminal device, comprising:

a sending unit, used for sending capability information of the terminal device to a first

network device; and

a transceiving unit, used for receiving policy information of the terminal device sent by the first network device.

110. The terminal device of claim 109, wherein the capability information comprises at least one of the following:

a Permanent Equipment Identifier (PEI), a voice support capability of the terminal device, a Radio Frequency Selection Priority (RFSP) parameter of the terminal device, Single-Network Slice Selection Assistance Information (S-NSSAI) reported by the terminal device, whether an operating system supports receiving and/or identifying a Data Network Name (DNN) parameter sent by an application layer, and whether mapping an upper layer request message of 3GPP into a parameter indicating a PDU session characteristic is supported.

111. A network device, comprising:

a processor, used for calling and running a computer program from a memory, wherein the computer program comprises at least one instruction of the following: instructions for executing the method of any one of claims 1-16, instructions for executing the method of any one of claims 63-73, and instructions for executing the method of any one of claims 101-103.

112. A terminal device, comprising:

a processor, used for calling and running a computer program from a memory, wherein the computer program comprises at least one instruction of the following: instructions for executing the method of any one of claims 33 to 47, instructions for executing the method of any one of claims 74 to 81, and instructions for executing the method of any one of claims 104 to 105.

113. A chip comprising:

a processor, used for calling and running a computer program from a memory, wherein the computer program comprises at least one instruction of the following: instructions for executing the method of any one of claims 1-16, instructions for executing the method of any one of claims 63-73, and instructions for executing the method of any one of claims 101-103.

114. A chip comprising:

a processor, used for calling and running a computer program from a memory, wherein the

computer program comprises at least one instruction of the following: instructions for executing the method of any one of claims 33-47, instructions for executing the method of any one of claims 74-81, and instructions for executing the method of any one of claims 104-105.

5 115. A storage medium, wherein the storage medium is used for storing a computer program, the computer program comprises at least one instruction of the following: instructions for executing the method of any one of claims 1-16, instructions for executing the method of any one of claims 63-73, and instructions for executing the method of any one of claims 101-103.

10 116. A storage medium, wherein the storage medium is used for storing a computer program, the computer program comprises at least one instruction of the following: instructions for executing the method of any one of claims 33-46, instructions for executing the method of any one of claims 74-81, and instructions for executing the method of any one of claims 104-105.

15 117. A computer program product comprising computer program instructions, wherein the computer program instructions comprise at least one instruction of the following: instructions for executing the method of any one of claims 1-16, instructions for executing the method of any one of claims 63-73, and instructions for executing the method of any one of claims 101-103.

20 118. A computer program product comprising computer program instructions, wherein the computer program instructions comprise at least one instruction of the following: instructions for executing the method of any one of claims 33-47, instructions for executing the method of any one of claims 74-81, and instructions for executing the method of any one of claims 104-105.