

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2023/177848 A8

(43) International Publication Date
21 September 2023 (21.09.2023)

WIPO | PCT

(51) International Patent Classification:
G02B 6/42 (2006.01) *H01L 25/065* (2023.01)
G02B 6/43 (2006.01)

(21) International Application Number:
PCT/US2023/015467

(22) International Filing Date:
17 March 2023 (17.03.2023)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
63/321,453 18 March 2022 (18.03.2022) US
63/420,330 28 October 2022 (28.10.2022) US
63/448,585 27 February 2023 (27.02.2023) US


(71) Applicant: **CELESTIAL AI INC.** [US/US]; 2962 Bunker Hill Lane, Suite 200, Santa Clara, CA 95054 (US).

(72) Inventors: **WINTERBOTTOM, Philip**; C/o Celestial AI Inc., 2962 Bunker Hill Lane, Suite 200, Santa Clara, CA 95054 (US). **LAZOVSKY, David**; C/o Celestial AI Inc., 2962 Bunker Hill Lane, Suite 200, Santa Clara, CA 95054 (US). **AGGARWAL, Ankur**; C/o Celestial AI Inc., 2962 Bunker Hill Lane, Suite 200, Santa Clara, CA 95054 (US). **BOS, Martinus**; C/o Celestial AI Inc., 2962 Bunker Hill Lane, Suite 200, Santa Clara, CA 95054 (US). **SAHNI, Subal**; C/o Celestial AI Inc., 2962 Bunker Hill Lane, Suite 200, Santa Clara, CA 95054 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM,

(54) Title: OPTICAL MULTI-DIE INTERCONNECT BRIDGE (OMIB)

FIG. 4



(57) Abstract: A package includes a bridging element (an OMIB), and first and second photonic paths, forming a bidirectional photonic path. The OMIB has first and second interconnect regions to connect with one or more dies. Third and fourth unidirectional photonic paths may couple between the first interconnect region and an optical interface (OI). A photonic transceiver has a first portion in the OMIB and a second portion in one of the dies. The first and the second portions may be coupled via an electrical interconnect less than 2 mm in length. The die includes compute elements around a central region, proximate to the second portion. The OMIB may include an electro-absorption modulator fabricated with germanium, silicon, an alloy of germanium, an alloy of silicon, a III-V material based on indium phosphide (InP), or a III-V material based on gallium arsenide (GaAs). The OMIB may include a temperature compensation for the modulator.

[Continued on next page]

DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG,
KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY,
MA, MD, MG, MK, MN, MU, MW, MX, MY, MZ, NA,
NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO,
RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS,
ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, CV, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(48) Date of publication of this corrected version:

30 November 2023 (30.11.2023)

(15) Information about Correction:

see Notice of 30 November 2023 (30.11.2023)